



Date: August 6, 2021

Federal Communications Commission
Office of Engineering and Technology Laboratory Division
7435 Oakland Mills Rd.
Columbia MD 21046

Attn: Office of Engineering and Technology

HAC Attestation - FCC ID: BCG-E4031A

To whom it may concern:

Apple Inc. hereby declares that the MIF values detailed below are based on worst case operating modes for all air interfaces for which the HAC rating is provided based on the current methodology for determining MIF values.

Reference Test report Number(s): UL Verification Services Test Report 13802771.

SPEAG test files

UID	Communication System Name	MIF (dB)
10021-DAC	GSM-FDD (TDMA, GMSK)	3.63
10011-CAB	UMTS-FDD (WCDMA)	-27.23
10295-AAB	CDMA2000 (1xRTT, RC1, SO3, 1/8th Rate)	3.26
10170-CAE	LTE-FDD (SC-FDMA, 1 RB, 20 MHz,	-9.76
10182-CAE	LTE-FDD (SC-FDMA, 1 RB, 15 MHz,	-9.76
10176-CAF	LTE-FDD (SC-FDMA, 1 RB, 10 MHz,	-9.76
10173-CAF	LTE-TDD (SC-FDMA, 1 RB, 20 MHz,	-1.44
10061-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11	-2.02
10077-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM,	0.12
10069-CAC	IEEE 802.11a/n WiFi 5 GHz (OFDM, 54	-3.15
10671-AAA	IEEE 802.11ax (20MHz, MCS0, 90pc duty	-5.58
10866-AAC	5G NR (DFT-s-OFDM, 1 RB, 100 MHz,	-16.69
10903-AAA	5G NR (DFT-s-OFDM, 1 RB, 40 MHz, QPSK,	-16.68
10929-AAA	5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK,	-15.06
10930-AAA	5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK,	-15.06
10931-AAA	5G NR (DFT-s-OFDM, 1 RB, 20 MHz, QPSK,	-15.06
10934-AAA	5G NR (DFT-s-OFDM, 1 RB, 40 MHz, QPSK,	-15.07

Sincerely,

Abhishek Rala
Apple Inc.
Global Certification Manager