



# TEST REPORT

**Report Number :** 14040868-E22V2

**Applicant :** APPLE INC.  
1 APPLE PARK WAY  
CUPERTINO, CA 95104, U.S.A.

**Model :** A2632 (Parent Model)  
A2885, A2886 (Variant Models)

**Brand :** APPLE

**FCC ID :** BCG-E8139A (Parent Model)  
BCG-E8146A, BCG-E8147A (Variant Models)

**IC :** 579C-E8139A  
579C-E8146A, 579C-E8147A (Variant Models)

**EUT Description :** SMARTPHONE

**Test Standard(s) :** FCC CFR47 Part 25  
ISED RSS-170 ISSUE 3 AMENDED, RSS-GEN Issue 5

**Date Of Issue:**  
AUGUST 11, 2022

**Prepared by:**  
UL LLC  
47173 Benicia Street  
Fremont, CA 94538, U.S.A.  
TEL: (510) 319-4000  
FAX: (510) 661-0888



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	8/1/2022	Initial Review	Chris Xiong
V2	8/11/2022	Address TCB question add standard	Chris Xiong



## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS</b>	<b>5</b>
<b>2. SUMMARY OF TEST RESULTS</b>	<b>6</b>
<b>3. TEST METHODOLOGY</b>	<b>7</b>
<b>4. FACILITIES AND ACCREDITATION</b>	<b>7</b>
<b>5. DECISION RULES AND MEASUREMENT UNCERTAINTY</b>	<b>8</b>
5.1. METROLOGICAL TRACEABILITY	8
5.2. DECISION RULES	8
5.3. MEASUREMENT UNCERTAINTY	8
5.4. SAMPLE CALCULATION	8
<b>6. EQUIPMENT UNDER TEST</b>	<b>9</b>
6.1. DESCRIPTION OF EUT	9
6.2. MAXIMUM OUTPUT POWER	9
6.3. SOFTWARE AND FIRMWARE	10
6.4. MAXIMUM ANTENNA GAIN	10
6.5. WORST-CASE CONFIGURATION AND MODE	10
6.6. DESCRIPTION OF TEST SETUP	11
<b>7. TEST AND MEASUREMENT EQUIPMENT</b>	<b>14</b>
<b>8. RF OUTPUT POWER VERIFICATION</b>	<b>15</b>
<b>9. CONDUCTED TEST RESULTS</b>	<b>16</b>
9.1. OCCUPIED BANDWIDTH	16
9.2. EMISSIONS MASK WITHIN 250% OF AUTHORIZED BANDWIDTH	18
9.2.1. ANT 1	19
9.2.2. ANT 4	22
9.3. OUT OF BAND EMISSIONS	23
9.3.1. ANT 1	24
9.3.2. ANT 4	25
<b>10. RADIATED TEST RESULTS</b>	<b>26</b>
10.1. FIELD STRENGTH OF SPURIOUS RADIATION	27
10.1.1. ANT 1 (Above 1GHz)	28
10.1.2. ANT 4 (Above 1GHz)	30
10.1.3. ANT 1 (Below 1GHz)	32
10.1.4. ANT 4 (Below 1GHz)	34
10.2. ADDITIONAL UNWANTED EMISSION (1559MHz – 1610MHz)	36
10.2.1. ANT 1	38

---

10.2.2.	ANT 4 .....	42
10.3.	CARRIER-OFF STATE EMISSIONS (1559MHz – 1610MHz) .....	46
10.3.1.	ANT 1 .....	47
10.3.2.	ANT 4 .....	47
10.4.	FREQUENCY STABILITY.....	48
11.	SETUP PHOTOS.....	49

# 1. ATTESTATION OF TEST RESULTS

Applicant Name and Address	APPLE INC. 1 APPLE PARK WAY CUPERTINO, CA 95104, U.S.A.
Model	A2631 (Parent Model, Full Test) A2885, A2886 (Variant Models)
Brand	APPLE
FCC ID	BCG-E8139A (Parent Model) BCG-E8146A, BCG-E8147A (Variant Models)
IC	579C-E8139A (Parent Model) 579C-E8146A, 579C-E8147A (Variant Models)
EUT Description	SMARTPHONE
Serial Number	C7H2054008E1LYT27 (Conducted), FRQKN2FCWX (Radiated)
Sample Receipt Date	JUNE 10, 2022 , APRIL 06, 2022
Date Tested	APRIL 11, 2022 to JULY 12, 2022
Applicable Standards	FCC CFR47 PART 25 ISED RSS-170 ISSUE 3 AMENDED, RSS-GEN ISSUE 5
Test Results	COMPLIES
<p>UL LLC tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.</p> <p>The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.</p> <p>This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, any agency of the Federal Government, or any agency of the U.S. government.</p>	
Approved & Released By:	Prepared & Reviewed By:
	
Thu Chan Staff Engineer UL LLC	Chris Xiong Senior Test Engineer UL LLC

## 2. SUMMARY OF TEST RESULTS

This report contains data provided by the customer which can impact the validity of results. UL LLC is only responsible for the validity of results after the integration of the data provided by the customer.

Requirement Description	Requirement Clause Number (FCC)	Requirement Clause Number (ISED)	Result*	Remarks
RF Output Power Verification	25.204 (a)	RSS-170 §5.3.2	Complies	
Occupied Bandwidth	2.1049	RSS-170 RSS-GEN	Reporting purposes only	
Emissions Mask - within 250% of Authorized Bandwidth	25.202 (f)(1)&(2)	RSS-170 §5.4.3.1 (1)&(2)	Complies	
Out of Band Emissions	25.202 (f)(3)	RSS-170 §5.4.3.1 (3)	Complies	
Additional Unwanted Emission (1559-1610MHz)	25.216 (c)&(g) FCC 03-283	RSS-170 §5.4.3.2.1 (g)	Complies	
Carrier-Off State Emissions (155901610MHz)	25.216 (i) FCC 03-283	RSS-170 §5.4.4	Complies	
Frequency Stability	25.202 (d)	RSS-170 §5.2	Complies	

### 3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with the following:

- ANSI C63.26:2015
- ISED RSS-170 ISSUE 3 AMENDED
- ISED RSS-GEN ISSUE 5
- FCC CFR 47 Part 2 and 25
- [FCC KDB 971168 D01 v03r01](#): Power Meas License Digital Systems
- [FCC KDB 971168 D02 v02r01](#): Misc Rev Approv License Devices
- [FCC KDB 412172 D01 v01r01](#): Determining ERP and EIRP

### 4. FACILITIES AND ACCREDITATION

UL LLC is accredited by A2LA, certification #0751.05, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	Address	ISED CABID	ISED Company Number	FCC Registration
<input checked="" type="checkbox"/>	Building 1: 47173 Benicia Street, Fremont, CA 94538, USA	US0104	2324A	550739
<input checked="" type="checkbox"/>	Building 2: 47266 Benicia Street, Fremont, CA 94538, USA	US0104	22541	550739
<input checked="" type="checkbox"/>	Building 4: 47658 Kato Rd, Fremont, CA 94538, USA	US0104	2324B	550739

## 5. DECISION RULES AND MEASUREMENT UNCERTAINTY

### 5.1. METROLOGICAL TRACEABILITY

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, with a maximum time between calibrations of one year or the manufacturers' recommendation, whichever is less, and where applicable is traceable to recognized national standards.

### 5.2. DECISION RULES

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4:2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

### 5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	U <sub>Lab</sub>
Worst Case Conducted Disturbance, 9KHz to 0.15 MHz	3.78 dB
Worst Case Conducted Disturbance, 0.15 to 30 MHz	3.40 dB
Worst Case Radiated Disturbance, 9KHz to 30 MHz	2.87 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	6.01 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.73 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.51 dB
Worst Case Radiated Disturbance, 26000 to 40000 MHz	5.29 dB
Occupied Channel Bandwidth	±1.22 %
Temperature	±0.57 °C
Supply voltages	±0.57 %
Time	±3.39 %

Uncertainty figures are valid to a confidence level of 95%.

### 5.4. SAMPLE CALCULATION

#### RADIATED EMISSIONS

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB)

$$36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} = 28.9 \text{ dBuV/m}$$



## 6. EQUIPMENT UNDER TEST

### 6.1. DESCRIPTION OF EUT

The Apple iPhone is a smartphone with multimedia functions (music, application support, and video), cellular GSM, GPRS, EGPRS, UMTS, LTE, 5G, IEEE 802.11a/b/g/n/ac/ax, Bluetooth, Ultra-Wideband, GPS, NFC and MSS. All models support at least one UICC based SIM. The second SIM is either an UICC based p-SIM (physical SIM) or e-SIM (electronic SIM) in some models. The device supports a built-in inductive charging transmitter and receiver. The rechargeable battery is not user accessible.

Testing was performed on the parent model and is used to support the application for the parent and variants identified in this report based on the test plan submitted and approved via KDB inquiry by the FCC and by ISED-Canada.

Parent Model: A2632, FCC ID: BCG-E8139A, IC: 579C-E8139A

Variant Models: A2885, FCC ID: BCG-E8146A, IC: 579C-E8146A  
 A2886; FCC ID: BCG-E8147A, IC: 579C-E8147A

### 6.2. MAXIMUM OUTPUT POWER

#### EIRP/ERP TEST PROCEDURE

ANSI C63.26:2015  
 KDB 971168 D01 Section 5.6

$$\text{EIRP} = \text{PMeas} + \text{GT} - \text{LC}$$

where: EIRP = effective isotropic radiated power, respectively (expressed in the same units as PMeas, typically dBW or dBm);

PMeas = measured transmitter output power or PSD, in dBm or dBW;

GT = gain of the transmitting antenna, in dBi (EIRP);

LC = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

For devices utilizing multiple antennas, KDB 662911 provides guidance for determining the effective array transmit antenna gain term to be used in the above equation.

The transmitter has a maximum average conducted and EIRP output powers as follows:

#### FCC Part 25 & ISED RSS-170 (1610 - 1626.5MHz):

Frequency (MHz)	Conducted (Average) (dBm)	Antenna Gain (dBi)	Limit (W)	EIRP		99% BW (kHz)	Emission Designator
				(dBm)	(W)		
1610.17	27.88	-3.1	10000	24.78	0.301	200.12	200KG1D
1618.4	27.93		10000	24.83	0.304	196.42	196KG1D
1626.03	27.99		10000	24.89	0.308	198.18	198KG1D

### 6.3. SOFTWARE AND FIRMWARE

The EUT firmware installed during testing was FW Version: 0.15.02.

### 6.4. MAXIMUM ANTENNA GAIN

The antenna(s) gain as provided by the manufacturer are as follow:

Frequency Range (MHz)	ANT 1 Antenna Gain (dBi)	ANT 4 Antenna Gain (dBi)
1610-1626.5	-3.1	-2.9

### 6.5. WORST-CASE CONFIGURATION AND MODE

The EUT was investigated in three orthogonal orientations X/Y/Z on both ANT 1 and ANT 4 antennas. It was determined that X (Flatbed) orientation was the worst-case orientation with AC/DC adapter for both ANT 1 and ANT 4.

The emissions mask tests were performed based on declared authorized bandwidths of 200kHz, 230kHz and 280kHz.

Radiated spurious emissions below 1GHz were performed with the highest output power on both ANT 1 and ANT 4 as worst-case scenario.


Radiated spurious emissions below 30MHz were investigated, there were no emissions found with less than 20dB of margin below the specified emissions limits.

For simultaneous transmission of multiple channels in the 2.4GHz/5GHz WLAN, tests were conducted for various configurations having the highest power, least separation in frequencies and widest operation bandwidths. No noticeable new emission was found.


## 6.6. DESCRIPTION OF TEST SETUP

SUPPORT TEST EQUIPMENT						
Description	Manufacturer	Model	Serial Number	FCC ID/ DoC		
Laptop AC/DC adapter	Apple	61W A1555	C069083VXA1JFYFA8	DoC		
Laptop	Apple	MacBook Pro	CO2VT1RBHV29	DoC		
Laptop AC/DC adapter	Apple	87W A1719	C04719306NLGW85A9	DoC		
Laptop	Apple	MacBook Pro	C02TK02YJ10C	DoC		
AC/DC adapter	Apple	B820	C4H95160022PF4F4R	DoC		
I/O CABLES (RF CONDUCTED TEST)						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	AC	3	US 115V	Un-shielded	2.0	N/A
2	USB	1	DC	Un-shielded	1.0	N/A
3	RF In/Out	1	EUT	Un-shielded	0.6	N/A
4	RF In/Out	1	Barrel	N/A	N/A	N/A
5	RF In/Out	1	SMA	Un-shielded	1.0	N/A
I/O CABLES (RF RADIATED TEST)						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	AC	1	Lightning	Un-shielded	1.0	N/A


**CONDUCTED SETUP ANT 1**



**CONDUCTED SETUP ANT 4**



**RADIATED SETUP**



## 7. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Asset	Cal Due
Antenna, Horn 1- 18GHz	ETS-Lindgren	3117	T344	6/14/2022
RF Preamp, 1 – 18GHz	UL In-House	N/A	PRE0177819	6/12/2022
Spectrum Analyzer, PXA, 3Hz – 44GHz	Keysight Technologies Inc.	N9030A	85212	1/30/2023
Antenna, Horn 1- 18GHz	ETS-Lindgren	3117	206805	2/10/2023
RF Preamp, 1 – 18GHz	UL In-House	N/A	PRE0180997	6/22/2022
Antenna, Broadband Hybrid	Sunol Sciences Corp.	JB1	85150	10/15/2022
RF Preamp 9kHz – 1GHz	Sonoma Instrument Co.	310N	170648	2/10/2023
EMI Test Receiver	Rohde & Schwarz	ESW44	201497	2/18/2023
Chamber, Environmental	Cincinnati Sub-Zero Products Inc.	ZPHS-8-3.5-SCT/WC	T1154	12/05/2023
Spectrum Analyzer, PXA, 3Hz – 44GHz	Keysight Technologies Inc.	N9030A	85214	2/02/2023
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	10763796	8/20/2022
Directional Coupler, .5-26.5GHz	Krytar	152610	T1161	9/23/2022
Power Meter, P-Series Single Channel	Keysight Technologies Inc.	N1911A	90731	1/24/2023
Power Sensor, P - Series, 50MHz to 18GHz, Wideband	Keysight Technologies Inc.	N1921A	81319	1/24/2023
DC Power Supply	TDK-LAMBDA	GENH 60-25	PRE0074664	Not Required
Antenna, Passive Loop 30Hz – 1MHz	Electro-Metrics	EM-6871	PRE0179465	7/29/2022
Antenna, Passive Loop 100kHz – 30MHz	Electro-Metrics	EM-6872	PRE0179467	7/29/2022
UL AUTOMATION SOFTWARE				
Radiated test software	UL	UL RF	Ver 9.5 February 2, 2021	

### NOTES:

- \* Testing is completed before equipment expiration date.
- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

## 8. RF OUTPUT POWER VERIFICATION

### LIMITS

FCC: §25.204

(a) In bands shared coequally with terrestrial radio communication services, the equivalent isotropically radiated power transmitted in any direction towards the horizon by an earth station, other than an ESV, operating in frequency bands between 1 and 15 GHz, shall not exceed the following limits except as provided for in paragraph (c) of this section:

- + 40 dBW in any 4 kHz band for  $\theta \leq 0^\circ$
- + 40 + 3 $\theta$  dBW in any 4 kHz band for  $0^\circ < \theta \leq 5^\circ$

where  $\theta$  is the angle of elevation of the horizon viewed from the center of radiation of the antenna of the earth station and measured in degrees as positive above the horizontal plane and negative below it.

ISED RSS-170:

#### 5.3.2 Mobile Earth Stations (MESs)

The application for MES certification shall state the MES e.i.r.p. that is necessary for satisfactory communication. The maximum permissible e.i.r.p. will be the stated e.i.r.p. plus a 2 dB margin. If a detachable antenna is used, the certification application shall state the recommended antenna type and manufacturer, the antenna gain and the maximum transmitter output power at the antenna terminal.

### TEST PROCEDURE

The transmitter output is connected to a wideband power meter/sensor which is greater than the occupied bandwidth as worst case scenario, also the total power readings still comply with the required limit.

The cable assembly insertion loss of 13.2 dB (ANT 1) / 12.32 dB (ANT 4) (including 10.70 dB coupler and 2.5 dB cable (ANT 1) / 10 dB pad and 2.32 dB cable (ANT 4)) was entered as an offset in the power meter to allow for a gated average reading of power.

### RESULTS

<b>Test Engineer ID:</b>	26118	<b>Test Date:</b>	6/11/2022
--------------------------	-------	-------------------	-----------

Test Frequency (MHz)	Conducted Average Power (dBm)		Antenna Gain (dBi)		EIRP Average Power (dBm)	
	ANT 1	ANT 4	ANT 1	ANT 4	ANT 1	ANT 4
1610.17	27.88	25.78	-3.1	-2.9	24.78	22.88
1618.4	27.93	25.80			24.83	22.90
1626.03	<b>27.99</b>	25.80			<b>24.89</b>	22.90

## 9. CONDUCTED TEST RESULTS

### 9.1. OCCUPIED BANDWIDTH

#### RULE PART(S)

FCC: §2.1049  
ISED RSS-170 and RSS-GEN

#### LIMITS

For reporting purposes only.

#### TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at the middle channel in each band. The nominal RBW shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set  $\geq 3 \times$  RBW. The 99% bandwidths were measured and recorded.




#### RESULTS

There is no limit required; therefore, only one port of higher power, ANT1, was tested.

<b>Test Engineer ID:</b>	26618	<b>Test Date:</b>	6/11/2022
--------------------------	-------	-------------------	-----------

Test Frequency (MHz)	99% BW (kHz)
1610.17	200.12
1618.4	196.42
1626.03	198.18





## 9.2. EMISSIONS MASK WITHIN 250% OF AUTHORIZED BANDWIDTH

### LIMITS

FCC §25.202 and ISED RSS-170: 5.4.3.1

(f) Emission limitations. Except for SDARS terrestrial repeaters and as provided for in paragraph (i), the mean power of emissions shall be attenuated below the mean output power of the transmitter in accordance with the schedule set forth in paragraphs (f)(1) through (f)(4) of this section. The out-of-band emissions of SDARS terrestrial repeaters shall be attenuated in accordance with the schedule set forth in paragraph (h) of this section.

(1) In any 4 kHz band, the center frequency of which is removed from the assigned frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth: 25 dB;

(2) In any 4 kHz band, the center frequency of which is removed from the assigned frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth: 35 dB;

### TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The channel edge emissions were measured on the low, mid and high channels. The limits within 250% of the authorized bandwidth are relative to the total in-band (channel) power. The measurement bandwidth (RBW) is set to  $\geq 4$  kHz and VBW set to at least 3 times the RBW. To measure the average value of the emissions the detector is set to rms while observing the minimum required number of points as detailed in ANSI C63.26 for average rms measurements. The sweep time is set to 2ms multiplied by the number of points to obtain the average over 2ms. Multiple sweeps with max hold enabled are made to capture the maximum average value.


### RESULTS

The tests were performed based on declared authorized bandwidths of 200kHz, 230kHz and 280kHz. The ANT 4 were performed only on center channel since it was the same signal to each antenna.




<b>Test Engineer ID:</b>	26118	<b>Test Date:</b>	6/11/2022
--------------------------	-------	-------------------	-----------

### 9.2.1. ANT 1


#### 200kHz Authorized Bandwidth:




230kHz Authorized Bandwidth:




280kHz Authorized Bandwidth:



Low 1610.17MHz




Mid1618.40MHz




High 1626.03MHz

9.2.2. ANT 4


200kHz Authorized Bandwidth:



230kHz Authorized Bandwidth:



280kHz Authorized Bandwidth:



### 9.3. OUT OF BAND EMISSIONS

#### LIMITS

FCC §25.202 and ISED RSS-170: 5.4.3.1

(f) Emission limitations. Except for SDARS terrestrial repeaters and as provided for in paragraph (i), the mean power of emissions shall be attenuated below the mean output power of the transmitter in accordance with the schedule set forth in paragraphs (f)(1) through (f)(4) of this section. The out-of-band emissions of SDARS terrestrial repeaters shall be attenuated in accordance with the schedule set forth in paragraph (h) of this section.

(3) In any 4 kHz band, the center frequency of which is removed from the assigned frequency by more than 250 percent of the authorized bandwidth: An amount equal to 43 dB plus 10 times the logarithm (to the base 10) of the transmitter power in watts.

#### TEST PROCEDURE

KDB 971168 D01 v03r01/D02 v02/r01



For each out of band emissions measurement:

- Set display line at -13 dBm (the limit of  $43 + 10\log(P)$ )
- Set RWB  $\geq 4\text{kHz}$  and VBW  $\geq 3 \times \text{RBW}$  with peak detector for all measurements. The limit is an average limit so any emissions that exceed the limit using the peak detector are measured using rms detection with an averaging time of 2ms.

#### RESULTS



<b>Test Engineer ID:</b>	26118	<b>Test Date:</b>	6/11/2022
--------------------------	-------	-------------------	-----------

### 9.3.1. ANT 1





### 9.3.2. ANT 4



## 10. RADIATED TEST RESULTS

### Radiated measurement using the Field Strength Method

Using the test configuration shown in Figure 6 below, we measure the radiated emissions directly from the EUT and convert the measured field strength or received power to EIRP, as required, for comparison to the applicable limits. As stated in 5.5.1 of ANSI C63.26-2015, the field strength measurement method using a test site validated to the requirements of ANSI C63.4 is an alternative to the substitution measurement method.




Figure 6—Test site-up for radiated ERP and/or EIRP measurements

### Radiated Power Measurement Calculation According to ANSI C63.26-2015

- a)  $E \text{ (dB}\mu\text{V/m)} = \text{Measured amplitude level (dB}\mu\text{V)} + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$ .
- b)  $E \text{ (dB}\mu\text{V/m)} = \text{Measured amplitude level (dBm)} + 107 + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$ .
- c)  $E \text{ (dB}\mu\text{V/m)} = \text{EIRP (dBm)} - 20\log(D) + 104.8$ ; where D is the measurement distance (in the far field region) in m.
- d)  $\text{EIRP (dBm)} = E \text{ (dB}\mu\text{V/m)} + 20\log(D) - 104.8$ ; where D is the measurement distance (in the far field region) in m.

So, from d)

The measuring distance is usually at 3m, then  $20 \cdot \log(3) = 9.5424$

Then,  $\text{EIRP (dBm)} = E \text{ (dB}\mu\text{V/m)} + 9.5424 - 104.8 = E \text{ (dB}\mu\text{V/m)} - 95.2576$

## 10.1. FIELD STRENGTH OF SPURIOUS RADIATION

### LIMITS

FCC §25.202 and ISED RSS-170: 5.4.3.1 (3)

(f) Emission limitations. Except for SDARS terrestrial repeaters and as provided for in paragraph (i), the mean power of emissions shall be attenuated below the mean output power of the transmitter in accordance with the schedule set forth in paragraphs (f)(1) through (f)(4) of this section. The out-of-band emissions of SDARS terrestrial repeaters shall be attenuated in accordance with the schedule set forth in paragraph (h) of this section.

(3) In any 4 kHz band, the center frequency of which is removed from the assigned frequency by more than 250 percent of the authorized bandwidth: An amount equal to 43 dB plus 10 times the logarithm (to the base 10) of the transmitter power in watts;

### TEST PROCEDURE

KDB 971168 D01 v03r01/D02 v02/r01

For each out of band emissions measurement:

- Set display line at -13 dBm (the limit of  $43 + 10\log(P)$ )
- Set RWB  $\geq 4\text{kHz}$  and VBW  $\geq 3 \times \text{RBW}$  with peak detector for all measurements. The limit is an average limit so any emissions that exceed the limit using the peak detector are measured using rms detection with an averaging time of 2ms.

### RESULTS

Plots are provided for the center channel. Tabular data for all channels is presented.

### 10.1.1. ANT 1 (Above 1GHz)

<b>Project #:</b>	14040868
<b>Date:</b>	6/25/2022- 6/26/2022
<b>Test Engineer:</b>	44373
<b>Configuration:</b>	EUT + Charger
<b>Mode:</b>	TX
<b>Chamber #:</b>	Chamber I

**Low channel:**

Frequency (GHz)	Meter Reading (dBuV)	Det	Horn Antenna ACF(dB)	Amp/Cbl/Filtr (dB)	EIRP CF	Corrected Reading (dBm)	LIMIT	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
4.808905	27.26	Pk	34.6	-27.8	-95.2	-61.14	-13	-48.14	262	181	H
6.099608	26.07	Pk	36.1	-27.6	-95.2	-60.63	-13	-47.63	195	148	H
8.784283	23.53	Pk	36.5	-22.9	-95.2	-58.07	-13	-45.07	153	165	H
4.830178	26.54	Pk	34.6	-27.7	-95.2	-61.76	-13	-48.76	94	130	V
7.191155	25.4	Pk	35.9	-25.9	-95.2	-59.8	-13	-46.8	110	145	V
9.911378	25	Pk	37.4	-22.9	-95.2	-55.7	-13	-42.7	97	162	V

Pk - Peak detector

**Mid Channel:**

Frequency (GHz)	Meter Reading (dBuV)	Det	Horn Antenna ACF(dB)	Amp/Cbl/Filtr (dB)	EIRP CF	Corrected Reading (dBm)	LIMIT	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
3.236398	28.49	Pk	33.2	-29.3	-95.2	-62.81	-13	-49.81	234	147	H
4.854122	27.41	Pk	34.6	-27.9	-95.2	-61.09	-13	-48.09	324	116	H
7.978864	24.27	Pk	36.2	-24	-95.2	-58.73	-13	-45.73	111	384	H
3.604627	27.89	Pk	33.4	-30	-95.2	-63.91	-13	-50.91	339	159	V
6.542086	25.07	Pk	36	-25.5	-95.2	-59.63	-13	-46.63	87	316	V
9.30747	23.93	Pk	36.9	-23.1	-95.2	-57.47	-13	-44.47	190	118	V


Pk - Peak detector

**High Channel:**


Frequency (GHz)	Meter Reading (dBuV)	Det	Horn Antenna ACF(dB)	Amp/Cbl/Filtr (dB)	EIRP CF	Corrected Reading (dBm)	LIMIT	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
3.252021	33.77	Pk	33.2	-29.4	-95.2	-57.63	-13	-44.63	47	111	H
4.878076	31.21	Pk	34.6	-28.1	-95.2	-57.49	-13	-44.49	138	137	H
8.032604	23.02	Pk	36.3	-24.2	-95.2	-60.08	-13	-47.08	151	145	H
3.252031	34.35	Pk	33.2	-29.4	-95.2	-57.05	-13	-44.05	96	126	V
4.141725	27.72	Pk	33.8	-29.3	-95.2	-62.98	-13	-49.98	100	142	V
6.127685	26.58	Pk	36.1	-27.8	-95.2	-60.32	-13	-47.32	107	141	V

Pk - Peak detector

Mid Channel:



Horizontal Polarity



Vertical Polarity

**10.1.2. ANT 4 (Above 1GHz)**

<b>Project #:</b>	14040868
<b>Date:</b>	6/26/2022
<b>Test Engineer:</b>	44373
<b>Configuration:</b>	EUT + Charger
<b>Mode:</b>	TX
<b>Chamber #:</b>	Chamber I

**Low channel:**

Frequency (GHz)	Meter Reading (dBuV)	Det	Horn Antenna ACF(dB)	Amp/Cbl/Filtr (dB)	EIRP CF	Corrected Reading (dBm)	LIMIT	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
3.279762	28.14	Pk	33.1	-29.8	-95.2	-63.76	-13	-50.76	199	156	H
4.830487	34.79	Pk	34.6	-27.7	-95.2	-53.51	-13	-40.51	231	131	H
8.885273	22.43	Pk	36.7	-22.7	-95.2	-58.77	-13	-45.77	29	195	H
3.57527	28.4	Pk	33.5	-29.4	-95.2	-62.7	-13	-49.7	12	164	V
4.830499	34.59	Pk	34.6	-27.7	-95.2	-53.71	-13	-40.71	301	177	V
7.121591	24.87	Pk	35.9	-25.1	-95.2	-59.53	-13	-46.53	315	177	V

Pk - Peak detector

**Mid Channel:**

Frequency (GHz)	Meter Reading (dBuV)	Det	Horn Antenna ACF(dB)	Amp/Cbl/Filtr (dB)	EIRP CF	Corrected Reading (dBm)	LIMIT	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
3.864605	27.17	Pk	33.8	-29.3	-95.2	-63.53	-13	-50.53	360	142	H
6.22498	25.06	Pk	36.2	-26.3	-95.2	-60.24	-13	-47.24	18	141	H
6.225231	25.69	Pk	36.2	-26.3	-95.2	-59.61	-13	-46.61	43	154	H
9.184842	22.71	Pk	36.8	-21.9	-95.2	-57.59	-13	-44.59	87	176	H
3.471007	27.49	Pk	33	-29.3	-95.2	-64.01	-13	-51.01	106	157	V
5.476724	25.41	Pk	35.2	-27.1	-95.2	-61.69	-13	-48.69	92	153	V
7.176938	25.39	Pk	35.9	-25.8	-95.2	-59.71	-13	-46.71	117	142	V


Pk - Peak detector

**High Channel:**


Frequency (GHz)	Meter Reading (dBuV)	Det	Horn Antenna ACF(dB)	Amp/Cbl/Filtr (dB)	EIRP CF	Corrected Reading (dBm)	LIMIT	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
3.620854	28.49	Pk	33.4	-30.1	-95.2	-63.41	-13	-50.41	341	146	H
4.87813	33.96	Pk	34.6	-28.1	-95.2	-54.74	-13	-41.74	224	145	H
9.003066	23.2	Pk	36.7	-23.4	-95.2	-58.7	-13	-45.7	86	145	H
4.126222	27.84	Pk	33.7	-29.3	-95.2	-62.96	-13	-49.96	86	149	V
4.878597	26.37	Pk	34.6	-28.1	-95.2	-62.33	-13	-49.33	308	139	V
6.760306	25.48	Pk	36.1	-26.5	-95.2	-60.12	-13	-47.12	316	139	V

Pk - Peak detector

Mid Channel:




Horizontal Polarity




Vertical Polarity

### 10.1.3. ANT 1 (Below 1GHz)

<b>Project #:</b>	14040868
<b>Date:</b>	6/25/2022
<b>Test Engineer:</b>	24971
<b>Configuration:</b>	EUT + Charger
<b>Mode:</b>	TX Worst Case Channel
<b>Chamber #:</b>	Chamber I



**HORIZONTAL**



**VERTICAL**





Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	85150 AF (dB/m)	Amp Cbl (dB)	EIRP CF	Corrected Reading (dBm)	LIMIT	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	34.365	32	Pk	24.5	-31.4	-95.2	-70.1	-13	-57.1	0-360	149	H
3	66.181	41.32	Pk	14.3	-31	-95.2	-70.58	-13	-57.58	0-360	149	H
5	193.057	41.2	Pk	17.6	-30.3	-95.2	-66.7	-13	-53.7	0-360	149	H
2	34.365	43.59	Pk	24.5	-31.4	-95.2	-58.51	-13	-45.51	0-360	149	V
4	66.375	42.96	Pk	14.3	-31	-95.2	-68.94	-13	-55.94	0-360	149	V
6	191.699	41.42	Pk	17.5	-30.3	-95.2	-66.58	-13	-53.58	0-360	149	V

Pk - Peak detector

### 10.1.4. ANT 4 (Below 1GHz)

<b>Project #:</b>	14040868
<b>Date:</b>	6/25/2022
<b>Test Engineer:</b>	24971
<b>Configuration:</b>	EUT + Charger
<b>Mode:</b>	TX Worst Case Channel
<b>Chamber #:</b>	Chamber I



Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	85150 AF (dB/m)	Amp Cbl (dB)	EIRP CF	Corrected Reading (dBm)	LIMIT	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	34.85	32.74	Pk	24.2	-31.4	-95.2	-69.66	-13	-56.66	0-360	149	H
3	66.181	39.81	Pk	14.3	-31	-95.2	-72.09	-13	-59.09	0-360	149	H
5	192.96	42.01	Pk	17.6	-30.3	-95.2	-65.89	-13	-52.89	0-360	149	H
2	34.559	43.74	Pk	24.4	-31.4	-95.2	-58.46	-13	-45.46	0-360	149	V
4	66.375	42.13	Pk	14.3	-31	-95.2	-69.77	-13	-56.77	0-360	149	V
6	193.251	42.02	Pk	17.6	-30.3	-95.2	-65.88	-13	-52.88	0-360	149	V

Pk - Peak detector

## 10.2. ADDITIONAL UNWANTED EMISSION (1559MHz – 1610MHz)

### LIMITS

FCC §25.216

Limits on emissions from mobile earth stations for protection of aeronautical radionavigation-satellite service

(a) The e.i.r.p. density of emissions from mobile earth stations placed in service on or before July 21, 2002 ...

(b) The e.i.r.p. density of emissions from mobile earth stations placed in service on or before July 21, 2002 ...

(c) The e.i.r.p. density of emissions from mobile earth stations placed in service after July 21, 2002 with assigned uplink frequencies between 1610 MHz and 1660.5 MHz shall not exceed  $-70$  dBW/MHz, averaged over any 2 millisecond active transmission interval, in the band 1559-1605 MHz. The e.i.r.p. of discrete emissions of less than 700 Hz bandwidth from such stations shall not exceed  $-80$  dBW, averaged over any 2 millisecond active transmission interval, in the 1559-1605 MHz band.

FCC §25.216 and ISED RSS-170: 5.4.3.2.1

(g) Mobile earth stations manufactured more than six months after Federal Register publication of the rule changes adopted in FCC 03-283 with assigned uplink frequencies in the 1610-1626.5 MHz band shall suppress the power density of emissions in the 1605-1610 MHz band-segment to an extent determined by linear interpolation from  $-70$  dBW/MHz at 1605 MHz to  $-10$  dBW/MHz at 1610 MHz averaged over any 2 millisecond active transmission interval. The e.i.r.p. of discrete emissions of less than 700 Hz bandwidth from such stations shall not exceed a level determined by linear interpolation from  $-80$  dBW at 1605 MHz to  $-20$  dBW at 1610 MHz, averaged over any 2 millisecond active transmission interval.

### TEST PROCEDURE

KDB 971168 D01 v03r01/D02 v02/r01

Measure wideband emissions using either:

RBW = 1MHz, VB = 3MHz

RBW < 1MHz, integrate over 1MHz if necessary

Measure narrowband emissions using:

RBW = 10kHz, VB = 30kHz as worst case setting

Set detector = rms, sweep time ~ number of points x 2ms, and sweep multiple times with max hold enabled. When the detector is set to rms the number of points is set to exceed the minimum number required by ANSI C63.26 for average measurements. A peak detector may be used (e.g. to avoid slow sweep times for the narrowband emissions measurements) in lieu of average rms detection as this will provide a more conservative (higher) measured value than the rms value.

### RESULTS

Both horizontal / vertical polarizations and low/ mid/ high channels were investigated on ANT 1 and ANT 4. It was found low channel to be worst case for both antennas.

<b>Project #:</b>	14040868
<b>Date:</b>	6/6/2022, 6/7/2022, 7/7/2022
<b>Test Engineer:</b>	30606
<b>Configuration:</b>	EUT + Charger
<b>Mode:</b>	TX Low Channel 1610.17MHz
<b>Chamber #:</b>	Chamber A, H

Offset Calculation Offset:


**Chamber A**

AF 80402 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	EIRP CF	Offset (dB)
28.1	-19.4	11.8	20.3

**Chamber H**

AF 80402 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	EIRP CF	Offset (dB)
28.9	-27.5	11.8	13.2


**Plots for Determining Wide Band or Narrow Band Emissions**




Note: It was found that the marker 1 @ 1604.954MHz frequency which belonged to wideband emission.


### 10.2.1. ANT 1

Wideband Low Channel 1610.17MHz Vertical:




Plots below show passing result using integration method:








Narrowband Low Channel 1610.17MHz Vertical:



Wideband Low Channel 1610.17MHz Horizontal:




Plots below show passing result using integration method:







Narrowband Low Channel 1610.17MHz Horizontal:






### 10.2.2. ANT 4


#### Wideband Low Channel 1610.17MHz Vertical:




Plots below show passing result using integration method:





Narrowband Low Channel 1610.17MHz Vertical:




Wideband Low Channel 1610.17MHz Horizontal:



Plots below show passing result using integration method:



Narrowband Low Channel 1610.17MHz Horizontal:



### 10.3. CARRIER-OFF STATE EMISSIONS (1559MHz – 1610MHz)

#### LIMITS

FCC §25.216 and ISED RSS-170: 5.4.4

Limits on emissions from mobile earth stations for protection of aeronautical radionavigation-satellite service

(i) The e.i.r.p density of carrier-off state emissions from mobile earth stations manufactured more than six months after Federal Register publication of the rule changes adopted in FCC 03-283 with assigned uplink frequencies between 1 and 3 GHz shall not exceed -80 dBW/MHz in the 1559-1610 MHz band averaged over any two millisecond interval.

ISED RSS-170: 5.4.4 Carrier-off State Emissions

Mobile equipment with transmitting frequencies between 1 GHz and 3 GHz shall have the e.i.r.p. density of carrier-off state emissions in the band 1559-1610 MHz not exceed -80 dBW/MHz.

#### TEST PROCEDURE

KDB 971168 D01 v03r01/D02 v02/r01


Set RBW = 1MHz, VB = 3MHz, detector = rms, sweep time ~ number of points x 2ms, and sweep multiple times with max hold enabled.

#### RESULTS


No emissions were found on both horizontal and vertical polarization for ANT 1 and ANT 4.

<b>Project #:</b>	14040868
<b>Date:</b>	7/7/2022
<b>Test Engineer:</b>	30606
<b>Configuration:</b>	EUT + Charger
<b>Mode:</b>	RX – TX Off
<b>Chamber #:</b>	Chamber A

### 10.3.1. ANT 1



### 10.3.2. ANT 4



## 10.4. FREQUENCY STABILITY

### LIMITS

FCC §25.202

(d) Frequency tolerance, Earth stations. The carrier frequency of each earth station transmitter authorized in these services shall be maintained within 0.001 percent of the reference frequency.

ISED RSS-170: 5.2

For mobile earth station equipment, the carrier frequency shall not depart from the reference frequency by more than ±10 ppm.

### TEST PROCEDURE

Use spectrum with Frequency Error measurement capability.

- Temp. = -30°C to +50°C
- Voltage = (85% - 115%)  
 Low voltage, 3.23VDC, Normal, 3.8VDC and High voltage, 4.37VDC.  
 End Voltage, 2.95VDC.

#### Frequency Stability vs Temperature:

The EUT is placed inside a temperature chamber. The temperature is set to 20°C and allowed to stabilize. After sufficient soak time, the transmitting frequency error is measured. The temperature is increased by 10 degrees, allowed to stabilize and soak, and then the measurement is repeated. This is repeated until +50°C is reached.

#### Frequency Stability vs Voltage:

The peak frequency error is recorded (worst-case).

### RESULTS

Test Engineer ID:	26118	Test Date:	6/7/2022 – 6/8/2022
-------------------	-------	------------	---------------------

Frequency Reference (MHz)		1610.16956		Frequency Reading (MHz)	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ -10dB BW (MHz)	F high @ -10dB BW (MHz)			
Temperature	Voltage					
Normal (20 C)	Normal	1610.077875	1610.26125	1610.16956		
Extreme (50C)		1610.077875	1610.261875	1610.16988	312.5	0.19
Extreme (40C)		1610.078938	1610.2605	1610.16972	156.2	0.10
Extreme (30C)		1610.078813	1610.260438	1610.16963	62.5	0.04
Extreme (10C)		1610.077313	1610.260625	1610.16897	-593.8	-0.37
Extreme (0C)		1610.078438	1610.26075	1610.16959	31.2	0.02
Extreme (-10C)		1610.078688	1610.260563	1610.16963	62.5	0.04
Extreme (-20C)		1610.077688	1610.262	1610.16984	281.2	0.17
Extreme (-30C)		1610.0785	1610.260813	1610.16966	93.8	0.06
20C		15%	1610.077938	1610.261063	1610.169500	-62.5
	-15%	1610.078688	1610.261063	1610.169875	312.5	0.19
	End Point	1610.078875	1610.260688	1610.169781	218.7	0.14



## 11. SETUP PHOTOS

Please refer to 140408681-EP1V1 for setup photos

**END OF REPORT**