



SAR Test Report

FOR:

Manufacturer: Apple Inc.
Model Name: A1397
iPad
FCC ID: BCGA1397
IC ID: 579C-A1397

Test Report #: SAR_APPLE_070_FCC

Date of Report: 2011-02-28
Date of Issue: 2011-02-28



FCC Listed #:
A2LA Accredited

IC Recognized #
3462B-1

CETECOM Inc.

411 Dixon Landing Road ♦ Milpitas, CA 95035 ♦ U.S.A.

Phone: + 1 (408) 586 6200 ♦ Fax: + 1 (408) 586 6299 ♦ E-mail: info@cetecomusa.com ♦ <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2113686

Board of Directors: Dr. Harald Ansoerge, Hans Peter May.



TABLE OF CONTENTS

1. Assessment 4

2. Administrative Data 5

2.1. Identification of the Testing Laboratory Issuing the EMC Test Report5

2.2. Identification of the Client5

2.3. Identification of the Manufacturer5

3. Equipment under Test (EUT) 6

3.1. Specification of the Equipment under Test6

3.2. Identification of the Equipment Under Test (EUT).....6

4. Subject of Investigation 7

4.1. The IEEE Standard C95.1 and the FCC Exposure Criteria.....7

4.2. Distinction Between Exposed Population, Duration of Exposure and Frequencies7

4.3. Distinction between Maximum Permissible Exposure and SAR Limits.....8

4.4. SAR Limit.....8

5. The FCC Measurement Procedure 9

5.1. General Requirements.....9

5.2. Body-worn and Other Configurations.....9

5.3. Procedure for assessing the peak spatial-average SAR.....10

5.4. Determination of the largest peak spatial-average SAR12

6. The Measurement System 13

6.1. Robot system specification13

6.2. Isotropic E-Field Probe for Dosimetric Measurements14

6.3. Data Acquisition Electronics.....14

6.4. Phantoms14

6.5. Interpolation and Extrapolation schemes.....14

7. Uncertainty Assessment 15



7.1. Measurement Uncertainty Budget15

8. Test results summary 16

8.1. Conducted Average Output Power16

8.2. SAR Testing Considerations & FCC KDB Inquiries16

8.2.1 iPad Back Surface SAR Testing Distance16

8.2.2 iPad Top Edge Secondary Portrait SAR Testing Distance16

8.2.3 iPad WIFI Exclusions for SAR Testing16

8.2.4 Additional SAR Testing for the Back Surface and Top Edge.....16

8.2.5 Method of SAR Measurement With and Without Back-off Enabled.....17

8.3. Test Positions and Configurations.....18

8.4. SAR results18

8.5. Dipole verification.....19

9. References 20



1. Assessment

The following device was tested against the limits for general population uncontrolled exposure specified in FCC 2.1093. The device was tested according to measurement standards and procedures specified in FCC OET Bulletin 65, Supplement C (Edition 01-01) and IEEE P1528/D1.2, April 21, 2003 and no deviations were ascertained during the course of the tests performed.

Company	Description	Model #
Apple Inc.	iPad	A1397

Responsible for Testing Laboratory:

2011-02-28	Compliance	Thomas Tam (Test Lab Manager)	
Date	Section	Name	Signature

Responsible for the Report:

2011-02-28	Compliance	Satya Radhakrishna (EMC Project Engineer)	
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section 3. CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

2. Administrative Data

2.1. Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Address:	411 Dixon Landing Road Milpitas, CA 95035 U.S.A.
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
Test Lab Director:	Heiko Strehlow
Responsible Project Leader:	Satya Radhakrishna

2.2. Identification of the Client

Applicant's Name:	Apple Inc.
Street Address:	1 Infinite Loop, MS 26A
City/Zip Code	Cupertino, CA 95014
Country	United States of America
Contact Person:	Bob Steinfeld
Phone No.	408-974-2618
e-mail:	Steinfel@apple.com

2.3. Identification of the Manufacturer

Manufacturer's Name:	Apple Inc.
Manufacturers Address:	1 Infinite Loop, MS 26A
City/Zip Code	Cupertino, CA 95014
Country	United States of America

3. Equipment under Test (EUT)

3.1. Specification of the Equipment under Test

Product Type:	Tablet Device
Marketing Name:	iPad
Model No:	A1397
Supported Radios:	CDMA2000, WiFi, Bluetooth
Hardware Revision :	DVT
Software Revision :	0.9.10
FCC-ID:	BCGA1397
IC-ID :	579C-A1397
Frequency Range (MHz):	824 – 849, 1850 – 1910, 2412 – 2462, 5150 – 5250, 5250 – 5350, 5500 – 5700, 5725 - 5850
Type(s) of Modulation:	QPSK, OQPSK, HPSK, OFDM, CCK, GFSK, $\pi/4$ DPSK, 8PSK
Modes of Operation:	1xRTT, EV-DO
Antenna Type:	Apple PT 631-1781

3.2. Identification of the Equipment Under Test (EUT)

EUT #	Serial Number	HW Version	SW Version
EUT A	DLXDV00MDK61	DVT	0.9.10

4. Subject of Investigation

Device The Apple iPad, Model A1397 is a tablet device with iPod functions (music, application support, and video), 802.11a/b/g/n radio, Bluetooth radio functions, and cellular using the CDMA data radio functions.

The objective of the measurements done by Cetecom Inc. was the dosimetric assessment of one device. The tests were performed in configurations for devices operated next to a person's body. The examinations were carried out with the dosimetric assessment system DASY52 described in Section 6.

This is a supplement report to report number, 10U13600-1, issued by Compliance Certification Services, 2-4-2011. This report adds SAR measurements performed with the proximity sensor disabled.

4.1. The IEEE Standard C95.1 and the FCC Exposure Criteria

In the USA the recent FCC exposure criteria [FCC 2001] are based upon the IEEE Standard C95.1 [IEEE 1999]. The IEEE standard C95.1 sets limits for human exposure to radio frequency electromagnetic fields in the frequency range 3 kHz to 300 GHz.

4.2. Distinction Between Exposed Population, Duration of Exposure and Frequencies

The American Standard [IEEE 1999] distinguishes between controlled and uncontrolled environment. Controlled environments are locations where there is exposure that may be incurred by persons who are aware of the potential for exposure as a concomitant of employment or by other cognizant persons. Uncontrolled environments are locations where there is the exposure of individuals who have no knowledge or control of their exposure. The exposures may occur in living quarters or workplaces. For exposure in controlled environments higher field strengths are admissible. In addition the duration of exposure is considered. Due to the influence of frequency on important parameters, as the penetration depth of the electromagnetic fields into the human body and the absorption capability of different tissues, the limits in general vary with frequency.

4.3. Distinction between Maximum Permissible Exposure and SAR Limits

The biological relevant parameter describing the effects of electromagnetic fields in the frequency range of interest is the specific absorption rate SAR (dimension: power/mass). It is a measure of the power absorbed per unit mass. The SAR may be spatially averaged over the total mass of an exposed body or its parts. The SAR is calculated from the r.m.s. electric field strength E inside the human body, the conductivity σ and the mass density ρ of the biological tissue:

$$SAR = \sigma \frac{E^2}{\rho} = c \frac{\partial T}{\partial t} \Big|_{t \rightarrow 0^+}$$

The specific absorption rate describes the initial rate of temperature rise $\partial T / \partial t$ as a function of the specific heat capacity c of the tissue. A limitation of the specific absorption rate prevents an excessive heating of the human body by electromagnetic energy.

As it is sometimes difficult to determine the SAR directly by measurement (e.g. whole body averaged SAR), the standard specifies more readily measurable maximum permissible exposures in terms of external electric E and magnetic field strength H and power density S , derived from the SAR limits. The limits for E , H and S have been fixed so that even under worst case conditions, the limits for the specific absorption rate SAR are not exceeded.

For the relevant frequency range the maximum permissible exposure may be exceeded if the exposure can be shown by appropriate techniques to produce SAR values below the corresponding limits.

4.4. SAR Limit

In this report the comparison between the American exposure limits and the measured data is made using the spatial peak SAR; the power level of the device under test guarantees that the whole body averaged SAR is not exceeded.

Having in mind a worst case consideration, the SAR limit is valid for uncontrolled environment and mobile respectively portable transmitters. According to Table 1 the SAR values have to be averaged over a mass of 1 g (SAR_{1g}) with the shape of a cube.

Standard	Status	SAR limit (W/kg)
IEEE C95.1	In force	1.6

Table 1: Relevant spatial peak SAR limit averaged over a mass of 1 g

5. The FCC Measurement Procedure

The Federal Communications Commission (FCC) has published a report and order on the 1st of August 1996 [FCC 1996], which requires routine dosimetric assessment of mobile telecommunications devices, either by laboratory measurement techniques or by computational modeling, prior to equipment authorization or use. In 2001 the Commission's Office of Engineering and Technology has released Edition 01-01 of Supplement C to OET Bulletin 65. This revised edition, which replaces Edition 97-01, provides additional guidance and information for evaluating compliance of mobile and portable devices with FCC limits for human exposure to radiofrequency emissions [FCC 2001]. The following KDB Publications have also been used:

- 447498 – Mobile and portable device RF Exposure Procedures
- 616217 – SAR Evaluation Considerations for Laptops with Antennas on Display Screens
- 941225 – SAR Measurement Procedures for 3G Devices
- Power reduction by sensing-October 2010 TCB council workshop

5.1. General Requirements

The test shall be performed in a laboratory with an environment which avoids influence on SAR measurements by ambient EM sources and any reflection from the environment itself. The ambient temperature shall be in the range of 20°C to 26°C and 30-70% humidity.

5.2. Body-worn and Other Configurations

Phantom Requirements

For body-worn and other configurations a flat phantom shall be used which is comprised of material with electrical properties similar to the corresponding tissues.

Test Position

The body-worn configurations shall be tested with the supplied accessories (belt-clips, holsters, etc.) attached to the device in normal use configuration. Devices with a headset output shall be tested with a connected headset.

Test to be Performed

For purpose of determining test requirements, accessories may be divided into two categories: those that do not contain metallic components and those that do. For multiple accessories that do not contain metallic components, the device may be tested only with that accessory which provides the closest spacing to the body. For multiple accessories that contain metallic components, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component, only the accessory that provides the closest spacing to the body must be tested. If the manufacturer provides none body-worn accessories a separation distance of 1.5 cm between the back of the device and the flat phantom is recommended. Other separation distances may be used, but they shall not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance

greater than that tested for the device provided however that the accessory contains no metallic components.

For devices with retractable antenna the SAR test shall be performed with the antenna fully extended and fully retracted. Other factors that may affect the exposure shall also be tested. For example, optional antennas or optional battery packs which may significantly change the volume, lengths, flip open/closed, etc. of the device, or any other accessories which might have the potential to considerably increase the peak spatial-average SAR value.

5.3. Procedure for assessing the peak spatial-average SAR

Step 1: Power reference measurement:

Prior to the SAR test, a local SAR measurement should be taken at a user-selected spatial reference point to monitor power variations during testing. For example, this power reference point can be spaced 10 mm or less in the normal direction from the liquid-shell interface and within ± 10 mm transverse to the normal line at the ear reference point.

Step 2: Area scan

The measurement procedures for evaluating SAR associated with wireless handsets typically start with a coarse measurement grid in order to determine the approximate location of the local peak SAR values. This is referred to as the "area scan" procedure. The SAR distribution is scanned along the inside surface of typically half of the head of the phantom but at least larger than the areas projected (normal to the phantom's surface) by the handset and antenna. An example grid is given in Figure 4. The distance between the measured points and phantom surface should be less than 8 mm, and should remain constant (variation less than ± 1 mm) during the entire scan in order to determine the locations of the local peak SAR with sufficient precision. The distance between the measurement points should enable the detection of the location of local maximum with an accuracy of better than half the linear dimension of the tissue cube after interpolation. The resolution can also be tested using the functions in Annex E (see E.5.2). The approximate locations of the peak SARs should be determined from area scan. Since a given amplitude local peak with steep gradients may produce lower spatial-average SAR than slightly lower amplitude peaks with less steep gradients, it is necessary to evaluate the other peaks as well. However, since the spatial gradients of local SAR peaks are a function of wavelength inside the tissue simulating liquid and incident magnetic field strength, it is not necessary to evaluate peaks that are less than -2 dB of the local maximum. Two-dimensional spline algorithms [Press, et al, 1996], [Brishoual, 2001] are typically used to determine the peaks and gradients within the scanned area. If the peak is closer than one-half of the linear dimension of the 1 g or 10 g tissue cube to the scan border, the measurement area should be enlarged if possible, e.g., by tilting the probe or the phantom (see Figure 5).




Figure 4 – Example of an area scan including the position of the handset. The scanned area (white dots) should be larger than the area projected by the handset and antenna.

Step 3: Zoom scan

In order to assess the peak spatial SAR values averaged over a 1 g and 10 g cube, fine resolution volume scans, called "zoom scans", are performed at the peak SAR locations determined during the "area scan." The zoom scan volume should have at least 1.5 times the linear dimension of either a 1 g or a 10 g tissue cube for whichever peak spatial-average SAR is being evaluated. The peak local SAR locations that were determined in the area scan (interpolated value) should be on the centerline of the zoom scans. The centerline is the line that is normal to the surface and in the center of the volume scan. If this is not possible, the zoom scan can be shifted but not by more than half the dimension of the 1 g or a 10 g tissue cube.

The maximum spatial-average SAR is determined by a numerical analysis of the SAR values obtained in the volume of the zoom scan, whereby interpolation (between measured points) and extrapolation (between surface and closest measured points) routines should be applied. A 3-D-spline algorithm [Press, et al, 1996], [Kreyszig, 1983], [Brishoual, 2001] can be used for interpolation and a trapezoidal algorithm for the integration (averaging). Scan resolutions of larger than 2 mm can be used provided the uncertainty is evaluated according to E (see E.5).

In some areas of the phantom, such as the jaw and upper head region, the angle of the probe with respect to the line normal to the surface might become large, e.g., at angles larger than $\pm 30^\circ$ (see Figure 5), which may increase the boundary effect to an unacceptable level. In these cases, a change in the orientation of the probe and/or the phantom is recommended during the zoom scan so that the angle between the probe housing tube and the line normal to the surface is significantly reduced ($<30^\circ$).

Step 4: Power reference measurement

The local SAR should be measured at exactly the same location as in Step 1. The absolute value of the measurement drift (the difference between the SAR measured in Step 4 and Step 1) should be recorded in the uncertainty budget. It is recommended that the drift be kept within $\pm 5\%$. If this is not possible, even with repeat testing, additional information may be used to demonstrate the power stability during the test. Power reference measurements can be taken after each zoom scan, if more than one zoom scan is needed. However, the drift should always be referred to the initial state with fully charged battery.

5.4. Determination of the largest peak spatial-average SAR

In order to determine the largest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes should be tested for each frequency band according to steps 1 to 3 below.

Step 1: The tests of 6.4 should be conducted at the channel that is closest to the center of the transmit frequency band (f_c) for:

- a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom,
- b) all configurations for each device position in (a), e.g. antenna extended and retracted, and
- c) all operational modes for each device position in (a) and configuration in (b) in each frequency band, e.g. analog and digital.

If more than three frequencies need to be tested, (i.e., $N_c > 3$), then all frequencies, configurations and modes must be tested for all of the above positions.

Step 2: For the condition providing highest spatial peak SAR determined in Step 1 conduct all tests of 6.4 at all other test frequencies, e.g. lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the spatial peak SAR value determined in Step 1 is within 3dB of the applicable SAR limit, it is recommended that all other test frequencies should be tested as well¹.

Step 3: Examine all data to determine the largest value of the peak spatial-average SAR found in Steps 1 to 2.

6. The Measurement System

6.1. Robot system specification

The SAR measurement system being used is the SPEAG DASY52 system, which consists of a Stäubli TX90XL 6-axis robot arm and CS8c controller, SPEAG SAR Probe, Data Acquisition Electronics, and SAM Twin Phantom. The robot is used to articulate the probe to programmed positions inside the phantom to obtain the SAR readings from the EUT.

The system is controlled remotely from a PC, which contains the software to control the robot and data acquisition equipment. The software also displays the data obtained from test scans.




Figure 5: Schematic diagram of the SAR measurement system

In operation, the system first does an area (2D) scan at a fixed depth within the liquid from the inside wall of the phantom. When the maximum SAR point has been found, the system will then carry out a 3D scan centered at that point to determine volume averaged SAR level.

6.2. Isotropic E-Field Probe for Dosimetric Measurements

The probes are constructed using three orthogonal dipole sensors arranged on an interlocking, triangular prism core. The probes have built-in shielding against static charges and are contained within a PEEK cylindrical enclosure material at the tip. Probe calibration is described in the probe's calibration certificate (see appendix C).

6.3. Data Acquisition Electronics

The DAE contains a signal amplifier, multiplexer, 16bit A/D converter and control logic. It uses an optical link for communication with the DASY5 system. The DAE has a dynamic range of -100 to 300 mV. It also contains a two step probe touch detector for mechanical surface detection and emergency robot stop.

6.4. Phantoms

The Twin SAM V4.0 Phantom is designed to specifications defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region.

6.5. Interpolation and Extrapolation schemes

The interpolation, extrapolation and maximum search routines are all based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation. The routines construct a once-continuously differentiable function that interpolates the measurement values.

7. Uncertainty Assessment

Measurement uncertainty values were evaluated for SAR measurements performed by Cetecom Inc. The uncertainty values for components specified in *FCC Supplement C (01-01) to OET Bulletin 65 (97-01)* were evaluated according to the procedures of *IEEE 1528-200X December 29, 2002, NIST 1297 1994 edition and ISO Guide to the Expression of Uncertainty in Measurements (GUM)*.

7.1. Measurement Uncertainty Budget

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e = f(d,k)</i>	<i>f</i>	<i>g = c x f / e</i>	<i>k</i>
Uncertainty Component	Sec.	Tol. (± %)	Prob. Dist.	Div.	<i>c_i</i> (1-g)	1-g <i>u_i</i> (±%)	<i>v_i</i>
Measurement System							
Probe Calibration	E2.1	5.5	N	1	1	5.5	∞
Axial Isotropy	E2.2	4.7	R	√3	0.7	1.9	∞
Hemispherical Isotropy	E2.2	9.6	R	√3	0.7	3.9	∞
Boundary Effect	E2.3	1.0	R	√3	1	0.6	∞
Linearity	E2.4	4.7	R	√3	1	2.7	∞
System Detection Limits	E2.5	1.0	R	√3	1	0.6	∞
Readout Electronics	E2.6	0.3	N	1	1	0.3	∞
Response Time	E2.7	0.8	R	√3	1	0.5	∞
Integration Time	E2.8	2.6	R	√3	1	1.5	∞
RF Ambient Noise	E6.1	3.0	R	√3	1	1.7	∞
RF Ambient Reflections	E6.1	3.0	R	√3	1	1.7	∞
Probe Positioner Mechanical Tolerance	E6.2	0.4	R	√3	1	0.2	∞
Probe Positioning with respect to Phantom Shell	E6.3	2.9	R	√3	1	1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E5.2	1.0	R	√3	1	0.6	∞
Test sample Related							
Test Sample Positioning	E4.2	2.9	N	1	1	2.9	145
Device Holder Uncertainty	E4.1	3.6	N	1	1	3.6	5
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	√3	1	2.9	∞
Phantom and Tissue Parameters							
Phantom Uncertainty (shape and thickness tolerances)	E3.1	4.0	R	√3	1	2.3	∞
Liquid Conductivity Target - tolerance	E3.2	5.0	R	√3	0.7	1.8	∞
Liquid Conductivity - measurement uncertainty	E3.3	3.7	N	1	0.7	2.6	∞
Liquid Permittivity Target tolerance	E3.2	5.0	R	√3	0.6	1.7	∞
Liquid Permittivity - measurement uncertainty	E3.3	2.5	N	1	0.6	1.5	∞
Combined Standard Uncertainty			RSS			± 11.6%	
Expanded Uncertainty (95% CONFIDENCE INTERVAL)			<i>k</i> = 2.00705			± 23.2%	

8. Test results summary

8.1. Conducted Average Output Power

Conducted Average Output Power (dBm)						
Frequency	Service Option 55		Service Option 32		EV-DO	
	RC1	RC3	SCH ₀ disabled	SCH ₀ enabled	Rev. 0	Rev. A
824.7	24.5	24.6	24.5	24.5	24.2	24.2
836.52	24.5	24.5	24.5	24.6	24.2	24.1
848.31	24.6	24.6	24.7	24.6	24.3	24.3
1851.25	23.5	23.6	23.6	23.5	23.1	23.1
1880	23.6	23.5	23.5	23.7	23.1	23
1908.75	23.5	23.9	23.7	23.7	23.2	23.2

8.2. SAR Testing Considerations & FCC KDB Inquiries

8.2.1 iPad Back Surface SAR Testing Distance

For the iPad Back Surface general composite testing (with back-off disabled), a distance of 10mm from the body phantom was chosen for the transmitting modes of the device. These test conditions were based on the form factor, size, operational configurations, exposure conditions, and display orientations.

8.2.2 iPad Top Edge Secondary Portrait SAR Testing Distance

For the iPad Top Edge Secondary Portrait a composite and conservative test (with back-off disabled), separation distance of 9.5mm from the body phantom was determined to be applicable for the top edge based on the form factor, size, operational configurations, exposure conditions, and display orientations.

8.2.3 iPad WIFI Exclusions for SAR Testing

The iPad does not have proximity sensors or back-off capabilities on WiFi.

8.2.4 Additional SAR Testing for the Back Surface and Top Edge

Based on discussions with the FCC it was determined that additional SAR testing is required. The additional testing required testing at a conservative distance from the iPad with the power back-off disabled via special development software. Details about the proximity sensor operation, and special development software are included in a separate document titled “Operational Description”.

Proximity Sensor Status Table – Back Surface In Conservative Proximity Sensor Operation

Distance to Back Surface of iPad (mm)	8.0	9.0	10.0	11.0	12.0	13.0	14.0	15.0
Proximity Sensor Status	ON	ON	ON	OFF	OFF	OFF	OFF	OFF

Proximity Sensor Status Table –Top Edge Secondary Portrait In Conservative Proximity Sensor Operation

Distance to Top Edge of iPad (mm)	8.5	9.5	10.5	11.5	12.5	13.5	14.5	15.5
Proximity Sensor Status	ON	ON	OFF	OFF	OFF	OFF	OFF	OFF

8.2.5 Method of SAR Measurement With and Without Back-off Enabled

Based on the above proximity sensor activation vs. distance results, the iPad was tested at zero spacing, back-off enabled and additionally at a conservative test distance of 9.5 mm on the top edge and 10 mm on back surface with back-off disabled (maximum power).

To test SAR with back-off enabled at zero spacing, the iPad was placed in maximum power transmit mode (with back-off enabled) with a base station simulator. The device was then positioned under the tissue equivalent liquid-filled flat phantom at zero distance.

To test SAR with back-off disabled at 9.5 mm, the iPad utilized special development software. The ability to disable the back-off is not available in the production release of software. The device was placed in maximum power transmit mode with a base station simulator. The iPad was then positioned under the tissue equivalent liquid-filled flat phantom at a distance of 9.5mm when in the “Top Edge – Secondary Portrait” orientation and at 10mm when in “Tablet Mode-Back surface” and tested with the back-off disabled.



8.3. Test Positions and Configurations

The area scan is over the transmitting antenna.

See Appendix B for test setup photos.

If the SAR value on the middle channel was more than 3dB below the limit, high and low channels were not evaluated.

In accordance with KDB 941225, SAR measurements were made using Subtype 0/1 Physical Layer configurations for Rev. 0. SAR for Subtype 2 Physical Layer configurations for Rev. A was not measured using Rev. A since the maximum average output is less than that measured in Subtype 0/1. SAR was also measured using 1xRTT in RC3 configured with service option 32. SAR with SCH₀ enabled was not performed since the maximum average output is less than ¼ dB higher than that measured with FCH only.

Back surface position was tested with an air gap of 10mm. Top Edge position was tested with an air gap of 9.5mm. All measurements performed with the proximity sensor disabled. Sensor was disabled by an option provided by special development software loaded on device.

8.4. SAR results

Position	Band	Operation Mode	Channel	Frequency (MHz)	SAR 1g (W/kg)	Area Scan (Appendix A)	Positioning Photo (Appendix B)
Back surface (10mm)	Cell	1xRTT	384	836.52	0.564	Plot 1	Photo 1
		EV-DO Release 0	384	836.52	0.522	Plot 2	Photo 1
	PCS	1xRTT	600	1880	0.577	Plot 3	Photo 1
		EV-DO Release 0	600	1880	0.639	Plot 4	Photo 1
Top Edge (9.5mm)	Cell	1xRTT	384	836.52	0.383	Plot 5	Photo 2
		EV-DO Release 0	384	836.52	0.353	Plot 6	Photo 2
	PCS	1xRTT	25	1851.25	1.04	Plot 7	Photo 2
			60	1880	1.19	Plot 8	Photo 2
			1175	1908.75	1.4	Plot 9	Photo 2
	EV-DO Release 0	EV-DO Release 0	25	1851.25	1.04	Plot 10	Photo 2
			60	1880	1.18	Plot 11	Photo 2
			1175	1908.75	1.42	Plot 12	Photo 2

8.5. Dipole verification

Prior to formal testing at each frequency a system verification was performed in accordance with IEEE 1528 and the 1 Watt reference SAR value is taken from the Speag dipole calibration report. All of the testing described in this report was performed within 24 hours of the system verification. The following results were obtained:

Date	Frequency (MHz)	CW input at dipole feed (Watts)	1g SAR (W/kg)	1 Watt reference SAR value (W/kg)	Difference reference SAR value to normalized SAR	Area scan (See Appendix A)
2-26-2011	835	1	10.4	10.2	2%	Plot 13
2-26-2011	1900	1	44.7	40.8	9.6%	Plot 14
2-28-2011	1900	1	44.2	40.8	8.3%	Plot 15

9. References

1. [FCC 2001] Federal Communications Commission: Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, Supplement C (Edition 01-01) to OET Bulletin 65 (Edition 97-01), FCC, 2001.
2. [IEEE 1999] IEEE Std C95.1-1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, Inst. of Electrical and Electronics Engineers, Inc., 1999.
3. [IEEE 200x] IEEE Std 1528-200x: DRAFT Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques. Draft 6.2, Inst. of Electrical and Electronics Engineers, Inc., 2000.
4. [NIST 1994] NIST: Guidelines for Evaluating and Expressing the Uncertainty of NIST Measurement Results, Technical Note 1297 (TN1297), United States Department of Commerce Technology Administration, National Institute of Standards and Technology, 1994.