




# TEST REPORT


**Test Report No. : UL-RPT-RP10407443JD10E V3.0**

**Manufacturer** : Apple Inc.  
**Model No.** : A1600  
**FCC ID** : BCGA1600  
**Technology** : LTE – Band 5  
**Test Standard(s)** : FCC Part 22 Subpart H

1. This test report shall not be reproduced in full or partial, without the written approval of UL VS LTD.
2. The results in this report apply only to the sample(s) tested.
3. The sample tested is in compliance with the above standard(s).
4. The test results in this report are traceable to the national or international standards.
5. Version 3.0 supersedes all previous versions.

**Date of Issue:** 15 September 2014

**Checked by:**   
Sarah Williams  
Engineer, Radio Laboratory

**Issued by :**   
pp  
John Newell  
Quality Manager,  
UL VS LTD



This laboratory is accredited by UKAS.  
The tests reported herein have been  
performed in accordance with its' terms  
of accreditation.

---

## UL VS LTD

Pavilion A, Ashwood Park, Ashwood Way, Basingstoke, Hampshire, RG23 8BG, UK  
Telephone: +44 (0)1256 312000  
Facsimile: +44 (0)1256 312001

This page has been left intentionally blank.

**Table of Contents**

<b>1. Customer Information.....</b>	<b>4</b>
<b>2. Summary of Testing .....</b>	<b>5</b>
2.1. General Information	5
2.2. Summary of Test Results	5
2.3. Methods and Procedures	5
2.4. Deviations from the Test Specification	5
<b>3. Equipment Under Test (EUT) .....</b>	<b>6</b>
3.1. Identification of Equipment Under Test (EUT)	6
3.2. Description of EUT	6
3.3. Modifications Incorporated in the EUT	6
3.4. Additional Information Related to Testing	7
3.5. Support Equipment	8
<b>4. Operation and Monitoring of the EUT during Testing .....</b>	<b>9</b>
4.1. Operating Modes	9
4.2. Configuration and Peripherals	9
4.3. Resource Block Allocation	10
<b>5. Measurements, Examinations and Derived Results.....</b>	<b>11</b>
5.1. General Comments	11
5.2. Test Results	12
5.2.1. Transmitter Output Power (ERP)	12
5.2.2. Transmitter Occupied Bandwidth	20
5.2.3. Transmitter Out of Band Radiated Emissions	45
5.2.4. Transmitter Radiated Emissions at Band Edges	48
5.2.5. Transmitter Frequency Stability (Temperature Variation)	65
5.2.6. Transmitter Frequency Stability (Voltage Variation)	67
<b>6. Measurement Uncertainty .....</b>	<b>68</b>
<b>7. Report Revision History .....</b>	<b>69</b>

**1. Customer Information**








<b>Company Name:</b>	Apple Inc.
<b>Address:</b>	1 Infinite Loop Cupertino, CA 95014 U.S.A.

## 2. Summary of Testing

### 2.1. General Information

<b>Specification Reference:</b>	47CFR22
<b>Specification Title:</b>	Code of Federal Regulations Volume 47 (Telecommunications): Part 22 Subpart H (Public Mobile Services)
<b>Site Registration:</b>	209735
<b>Location of Testing:</b>	UL VS LTD, Unit 3 Horizon, Wade Road, Kingsland Business Park, Basingstoke, Hampshire, RG24 8AH, United Kingdom
<b>Test Dates:</b>	09 July 2014 to 14 September 2014

### 2.2. Summary of Test Results

FCC Reference (47CFR)	Measurement	Result
Part 22.913(a)(2)	Transmitter Output Power (ERP)	
Part 2.1049	Transmitter Occupied Bandwidth	
Part 2.1053 / 22.917	Transmitter Out of Band Radiated Emissions	
Part 2.1053 / 22.917	Transmitter Band Edge Radiated Emissions	
Part 2.1055 / 22.355	Transmitter Frequency Stability (Temperature and Voltage Variation)	
<b>Key to Results</b>		
 = Complied  = Did not comply		

### 2.3. Methods and Procedures

<b>Reference:</b>	ANSI/TIA-603-C-2004
<b>Title:</b>	Land Mobile Communications Equipment, Measurements and performance Standards
<b>Reference:</b>	FCC KDB 971168 D01 v02r01, 7 June 2013
<b>Title:</b>	Measurement Guidance for Certification of Licensed Digital Transmitters

### 2.4. Deviations from the Test Specification

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above.

### **3. Equipment Under Test (EUT)**

#### **3.1. Identification of Equipment Under Test (EUT)**

<b>Brand Name:</b>	Apple
<b>Model Name or Number:</b>	A1600
<b>Test Sample IMEI:</b>	352025060238798 ( <i>Radiated Sample</i> )
<b>Hardware Version Number:</b>	REV1.0
<b>Software Version Number:</b>	iOS 12A314 BB: 3.08.08
<b>FCC ID:</b>	BCGA1600

<b>Brand Name:</b>	Apple
<b>Model Name or Number:</b>	A1600
<b>Test Sample IMEI:</b>	352025060274538 ( <i>Conducted Sample</i> )
<b>Hardware Version Number:</b>	REV1.0
<b>Software Version Number:</b>	iOS 12A314 BB: 3.08.08
<b>FCC ID:</b>	BCGA1600

#### **3.2. Description of EUT**

The Equipment Under Test was a tablet with GSM/GPRS/EGPRS/UMTS/LTE and CDMA technologies. It also supports IEEE 802.11a/b/g/n (MIMO 2x2) and *Bluetooth®*. The rechargeable battery is not user accessible.

#### **3.3. Modifications Incorporated in the EUT**

No modifications were applied to the EUT during testing.

**3.4. Additional Information Related to Testing**

<b>Tested Technology:</b>	LTE Band 5		
<b>Type of Equipment</b>	Transceiver		
<b>Channel Bandwidth(s):</b>	1.4, 3, 5 & 10 MHz		
<b>Modulation Type:</b>	QPSK & 16QAM		
<b>Duty Cycle:</b>	100%		
<b>Antenna Gain:</b>	-5.10 dBd		
<b>Power Supply Requirement:</b>	Nominal	3.8 V	
	Minimum	3.4 V	
	Maximum	4.2 V	
<b>Transmit Frequency Range:</b>	824 MHz to 849 MHz		
<b>Channels Tested:</b>	<b>Channel Bandwidth (MHz)</b>	<b>N<sub>ul</sub></b>	<b>Frequency of Uplink (MHz)</b>
<b>Bottom Channel</b>	1.4	20407	824.7
	3	20415	825.5
	5	20425	826.5
	10	20450	829.0
<b>Middle Channel</b>	All	20525	836.5
<b>Top Channel</b>	1.4	20643	848.3
	3	20635	847.5
	5	20625	846.5
	10	20600	844.0

### **3.5. Support Equipment**

The following support equipment was used to exercise the EUT during testing:

<b>Brand Name:</b>	Dell
<b>Description:</b>	Laptop computer
<b>Model Name or Number:</b>	Inspiron
<b>Serial Number:</b>	Asset RFI00788

<b>Brand Name:</b>	Not stated
<b>Description:</b>	USB Diagnostic cable
<b>Model Name or Number:</b>	Not stated
<b>Serial Number:</b>	Not stated

<b>Brand Name:</b>	Apple
<b>Description:</b>	Test Laptop
<b>Model Name or Number:</b>	MacBook Pro
<b>Serial Number:</b>	C2QLQ03XF9F2

<b>Brand Name:</b>	Apple
<b>Description:</b>	USB Cable
<b>Model Name or Number:</b>	A1480
<b>Serial Number:</b>	Not stated

<b>Brand Name:</b>	Apple
<b>Description:</b>	USB Charger
<b>Model Name or Number:</b>	A1399
<b>Serial Number:</b>	Not stated

<b>Brand Name:</b>	Apple
<b>Description:</b>	PHF
<b>Model Name or Number:</b>	Apple Ear Plugs
<b>Serial Number:</b>	Not stated



## **4. Operation and Monitoring of the EUT during Testing**

### **4.1. Operating Modes**

The EUT was tested in the following operating mode(s):

- Transmit Mode - The EUT was set to transmit with maximum output power using the required channel bandwidth. QPSK and 16QAM modulations were both tested, with Resource Block allocation as detailed in section 4.3.

### **4.2. Configuration and Peripherals**

The EUT was tested in the following configuration(s):

- The EUT was connected to a Rohde and Schwarz CMW500 LTE system simulator, operating in a transceiver mode.
- Transmitter radiated spurious emissions tests were performed with the EUT set to transmit with a 5 MHz channel bandwidth with QPSK modulation applied and 1 resource block with 0 offset. This was found to be the worst case modulation scheme with regards to emissions after preliminary investigations and, as this mode emits the highest transmit output power level, it was deemed to be the worst case.
- Transmitter radiated spurious emissions tests were performed with the AC Charger and PHF connected to the EUT as this was found to be the worst case during pre-scans. All the accessories were individually connected and measurements made during the pre-scans to determine the worst case combination.
- Conducted measurements at temperature and voltage extremes were performed using a conducted sample supplied by the customer. Short 4-wire DC flying leads were connected internally to the device in place of the battery, and exited through a hole in the casing. These leads were then extended to a DC power supply for testing purposes.
- For conducted cellular measurements, the RF conducted port was created by removing a micro connector from the pcb antenna and extending it with a short flexible microstrip supplied by the customer. This microstrip exited the device through a hole in the casing and was terminated in a proprietary micro-coax to SMA adaptor.
- The conducted sample with IMEI 352025060274538 was used for frequency stability, occupied bandwidth and power measurements.
- The radiated sample with IMEI 352025060238798 was used for all radiated measurements.

### **4.3. Resource Block Allocation**

Channel Bandwidth (MHz)	Maximum No. of Resource Blocks	Resource Block / Offset Number							
		Sub Test 1		Sub Test 2		Sub Test 3		Sub Test 4	
		RB	Offset	RB	Offset	RB	Offset	RB	Offset
1.4	6	1	0	1	5	3	2	6	0
3	15	1	0	1	14	8	4	15	0
5	25	1	0	1	24	12	6	25	0
10	50	1	0	1	49	25	12	50	0

Transmitter Output Power was carried out using sub tests 1, 2, 3 and 4, with both QPSK and 16QAM modulation schemes.

Transmitter Occupied Bandwidth was carried out using sub tests 3 and 4, for both QPSK and 16QAM modulation schemes.

Transmitter radiated spurious emissions tests were performed with the EUT was set to transmit with a 5 MHz channel bandwidth with QPSK modulation applied and 1 resource block with 0 offset. This was found to be the worst case modulation scheme with regards to emissions after preliminary investigations and, as this mode emits the highest transmit output power level, it was deemed to be the worst case.

Transmitter Radiated Band Edge Emissions was tested with sub test 4 on all supported channel bandwidths, using QPSK and 16QAM modulations with the maximum resource blocks settings.

Transmitter Frequency Stability test was carried out with sub test 4, with a channel bandwidth of 1.4 MHz only.

## **5. Measurements, Examinations and Derived Results**

### **5.1. General Comments**

Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate coverage factor to provide a statistical confidence level of approximately 95%. Please refer to *Section 6. Measurement Uncertainty* for details.

In accordance with UKAS requirements all the measurement equipment is on a calibration schedule. All equipment was within the calibration period on the date of testing.

## **5.2. Test Results**

### **5.2.1. Transmitter Output Power (ERP)**

#### **Test Summary:**

<b>Test Engineer:</b>	Keith Tucker	<b>Test Date:</b>	29 July 2014
<b>Test Sample IMEI:</b>	352025060274538		

<b>FCC Reference:</b>	Part 22.913(a)(2)
<b>Test Method Used:</b>	As detailed in FCC KDB 971168 Section 5.2.3

#### **Environmental Conditions:**

<b>Temperature (°C):</b>	25
<b>Relative Humidity (%):</b>	39

#### **Note(s):**

1. The customer stated that the EUT has a maximum antenna gain of -2.95 dBi. As the limit is ERP, the gain in dBi has been converted to dBd. The dBd gain figure has been calculated as:  
$$-2.95 \text{ dBi} - 2.15 \text{ dB} = -5.10 \text{ dBd}$$
2. Measurements were performed with the EUT transmitting with QPSK and 16QAM modulation schemes, with resource blocks settings as detailed in section 4.3 of this report.

**Transmitter Output Power (ERP) (continued)****Results: 1.4 MHz Channel Bandwidth / Bottom Channel / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
824.7	6	0	22.1	-5.1	17.0	38.5	21.5	Complied
824.7	3	2	22.6	-5.1	17.5	38.5	21.0	Complied
824.7	1	0	22.6	-5.1	17.5	38.5	21.0	Complied
824.7	1	5	22.7	-5.1	17.6	38.5	20.9	Complied

**Results: 1.4 MHz Channel Bandwidth / Bottom Channel / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
824.7	6	0	21.1	-5.1	16.0	38.5	22.5	Complied
824.7	3	2	22.2	-5.1	17.1	38.5	21.4	Complied
824.7	1	0	21.9	-5.1	16.8	38.5	21.7	Complied
824.7	1	5	21.9	-5.1	16.8	38.5	21.7	Complied

**Results: 1.4 MHz Channel Bandwidth / Middle Channel / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
836.5	6	0	22.2	-5.1	17.1	38.5	21.4	Complied
836.5	3	2	23.1	-5.1	18.0	38.5	20.5	Complied
836.5	1	0	23.1	-5.1	18.0	38.5	20.5	Complied
836.5	1	5	23.2	-5.1	18.1	38.5	20.4	Complied

**Results: 1.4 MHz Channel Bandwidth / Middle Channel / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
836.5	6	0	21.1	-5.1	16.0	38.5	22.5	Complied
836.5	3	2	22.1	-5.1	17.0	38.5	21.5	Complied
836.5	1	0	22.1	-5.1	17.0	38.5	21.5	Complied
836.5	1	5	22.1	-5.1	17.0	38.5	21.5	Complied

**Transmitter Output Power (ERP) (continued)****Results: 1.4 MHz Channel Bandwidth / Top Channel / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
848.3	6	0	21.7	-5.1	16.6	38.5	21.9	Complied
848.3	3	2	22.6	-5.1	17.5	38.5	21.0	Complied
848.3	1	0	22.6	-5.1	17.5	38.5	21.0	Complied
848.3	1	5	22.6	-5.1	17.5	38.5	21.0	Complied

**Results: 1.4 MHz Channel Bandwidth / Top Channel / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
848.3	6	0	20.6	-5.1	15.5	38.5	23.0	Complied
848.3	3	2	21.7	-5.1	16.6	38.5	21.9	Complied
848.3	1	0	21.5	-5.1	16.4	38.5	22.1	Complied
848.3	1	5	21.5	-5.1	16.4	38.5	22.1	Complied

**Results: 3 MHz Channel Bandwidth / Bottom Channel / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
825.5	15	0	22.0	-5.1	16.9	38.5	21.6	Complied
825.5	8	4	22.0	-5.1	16.9	38.5	21.6	Complied
825.5	1	0	22.6	-5.1	17.5	38.5	21.0	Complied
825.5	1	14	22.7	-5.1	17.6	38.5	20.9	Complied

**Results: 3 MHz Channel Bandwidth / Bottom Channel / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
825.5	15	0	21.1	-5.1	16.0	38.5	22.5	Complied
825.5	8	4	21.1	-5.1	16.0	38.5	22.5	Complied
825.5	1	0	21.9	-5.1	16.8	38.5	21.7	Complied
825.5	1	14	21.9	-5.1	16.8	38.5	21.7	Complied

**Transmitter Output Power (ERP) (continued)****Results: 3 MHz Channel Bandwidth / Middle Channel / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
836.5	15	0	22.2	-5.1	17.1	38.5	21.4	Complied
836.5	8	4	22.2	-5.1	17.1	38.5	21.4	Complied
836.5	1	0	23.2	-5.1	18.1	38.5	20.4	Complied
836.5	1	14	23.2	-5.1	18.1	38.5	20.4	Complied

**Results: 3 MHz Channel Bandwidth / Middle Channel / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
836.5	15	0	21.3	-5.1	16.2	38.5	22.3	Complied
836.5	8	4	21.2	-5.1	16.1	38.5	22.4	Complied
836.5	1	0	22.1	-5.1	17.0	38.5	21.5	Complied
836.5	1	14	22.1	-5.1	17.0	38.5	21.5	Complied

**Results: 3 MHz Channel Bandwidth / Top Channel / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
847.5	15	0	22.1	-5.1	17.0	38.5	21.5	Complied
847.5	8	4	22.1	-5.1	17.0	38.5	21.5	Complied
847.5	1	0	22.6	-5.1	17.5	38.5	21.0	Complied
847.5	1	14	22.6	-5.1	17.5	38.5	21.0	Complied

**Results: 3 MHz Channel Bandwidth / Top Channel / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
847.5	15	0	21.1	-5.1	16.0	38.5	22.5	Complied
847.5	8	4	21.0	-5.1	15.9	38.5	22.6	Complied
847.5	1	0	21.8	-5.1	16.7	38.5	21.8	Complied
847.5	1	14	21.8	-5.1	16.7	38.5	21.8	Complied

**Transmitter Output Power (ERP) (continued)****Results: 5 MHz Channel Bandwidth / Bottom Channel / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
826.5	25	0	22.0	-5.1	16.9	38.5	21.6	Complied
826.5	12	6	22.0	-5.1	16.9	38.5	21.6	Complied
826.5	1	0	22.6	-5.1	17.5	38.5	21.0	Complied
826.5	1	24	22.8	-5.1	17.7	38.5	20.8	Complied

**Results: 5 MHz Channel Bandwidth / Bottom Channel / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
826.5	25	0	21.0	-5.1	15.9	38.5	22.6	Complied
826.5	12	6	21.0	-5.1	15.9	38.5	22.6	Complied
826.5	1	0	21.9	-5.1	16.8	38.5	21.7	Complied
826.5	1	24	22.1	-5.1	17.0	38.5	21.5	Complied

**Results: 5 MHz Channel Bandwidth / Middle Channel / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
836.5	25	0	22.2	-5.1	17.1	38.5	21.4	Complied
836.5	12	6	22.2	-5.1	17.1	38.5	21.4	Complied
836.5	1	0	23.2	-5.1	18.1	38.5	20.4	Complied
836.5	1	24	23.2	-5.1	18.1	38.5	20.4	Complied

**Results: 5 MHz Channel Bandwidth / Middle Channel / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
836.5	25	0	21.2	-5.1	16.1	38.5	22.4	Complied
836.5	12	6	21.2	-5.1	16.1	38.5	22.4	Complied
836.5	1	0	22.1	-5.1	17.0	38.5	21.5	Complied
836.5	1	24	22.0	-5.1	16.9	38.5	21.6	Complied



**Transmitter Output Power (ERP) (continued)****Results: 5 MHz Channel Bandwidth / Top Channel / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
846.5	25	0	22.0	-5.1	16.9	38.5	21.6	Complied
846.5	12	6	22.1	-5.1	17.0	38.5	21.5	Complied
846.5	1	0	22.7	-5.1	17.6	38.5	20.9	Complied
846.5	1	24	22.6	-5.1	17.5	38.5	21.0	Complied

**Results: 5 MHz Channel Bandwidth / Top Channel / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
846.5	25	0	21.1	-5.1	16.0	38.5	22.5	Complied
846.5	12	6	21.0	-5.1	15.9	38.5	22.6	Complied
846.5	1	0	22.0	-5.1	16.9	38.5	21.6	Complied
846.5	1	24	21.9	-5.1	16.8	38.5	21.7	Complied

**Results: 10 MHz Channel Bandwidth / Bottom Channel / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
829.0	50	0	22.1	-5.1	17.0	38.5	21.5	Complied
829.0	25	12	22.2	-5.1	17.1	38.5	21.4	Complied
829.0	1	0	22.7	-5.1	17.6	38.5	20.9	Complied
829.0	1	49	22.8	-5.1	17.7	38.5	20.8	Complied

**Results: 10 MHz Channel Bandwidth / Bottom Channel / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
829.0	50	0	21.2	-5.1	16.1	38.5	22.4	Complied
829.0	25	12	21.1	-5.1	16.0	38.5	22.5	Complied
829.0	1	0	22.0	-5.1	16.9	38.5	21.6	Complied
829.0	1	49	22.0	-5.1	16.9	38.5	21.6	Complied

**Transmitter Output Power (ERP) (continued)****Results: 10 MHz Channel Bandwidth / Middle Channel / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
836.5	50	0	22.2	-5.1	17.1	38.5	21.4	Complied
836.5	25	12	22.2	-5.1	17.1	38.5	21.4	Complied
836.5	1	0	23.2	-5.1	18.1	38.5	20.4	Complied
836.5	1	49	23.1	-5.1	18.0	38.5	20.5	Complied

**Results: 10 MHz Channel Bandwidth / Middle Channel / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
836.5	50	0	21.1	-5.1	16.0	38.5	22.5	Complied
836.5	25	12	21.2	-5.1	16.1	38.5	22.4	Complied
836.5	1	0	22.1	-5.1	17.0	38.5	21.5	Complied
836.5	1	49	22.0	-5.1	16.9	38.5	21.6	Complied

**Results: 10 MHz Channel Bandwidth / Top Channel / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
844.0	50	0	22.0	-5.1	16.9	38.5	21.6	Complied
844.0	25	12	22.1	-5.1	17.0	38.5	21.5	Complied
844.0	1	0	22.7	-5.1	17.6	38.5	20.9	Complied
844.0	1	49	22.5	-5.1	17.4	38.5	21.1	Complied

**Results: 10 MHz Channel Bandwidth / Top Channel / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Conducted RF Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP Limit (dBm)	Margin (dB)	Result
844.0	50	0	21.0	-5.1	15.9	38.5	22.6	Complied
844.0	25	12	21.0	-5.1	15.9	38.5	22.6	Complied
844.0	1	0	21.9	-5.1	16.8	38.5	21.7	Complied
844.0	1	49	21.8	-5.1	16.7	38.5	21.8	Complied

**Transmitter Output Power (ERP) (continued)****Test Equipment Used:**

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1658	Thermohygrometer	JM Handelspunkt	30.5015.13	None stated	14 Mar 2015	12
M1871	Power Meter	Agilent	N1911A	MY45100338	28 May 2015	12
M1872	Wideband Power Sensor	Agilent	N1921A	MY45241950	08 Oct 2014	12
S0537	DC Power Supply	TTi	EL302D	249928	Calibrated before use	-
M1251	Digital Multimeter	Fluke	175	89170179	19 May 2015	12
A2535	Directional Coupler	AtlanTec RF	CDC-003060-20	14041701719	Calibrated before use	-
A2508	Attenuator	AtlanTec RF	AN18-10	821846#3	Calibrated before use	-
A539	Power Splitter	Rohde & Schwarz	RVZ	22441	Calibrated before use	-

**5.2.2. Transmitter Occupied Bandwidth****Test Summary:**

<b>Test Engineer:</b>	Keith Tucker	<b>Test Dates:</b>	18 July 2014 & 15 August 2014
<b>Test Sample IMEI:</b>	352025060274538		

<b>FCC Reference:</b>	Part 2.1049
<b>Test Method Used:</b>	As detailed in KDB 971168 Section 4.2

**Environmental Conditions:**

<b>Temperature (°C):</b>	23
<b>Relative Humidity (%):</b>	38 to 42


**Note(s):**

1. Occupied bandwidth (99% bandwidth) was measured using a test receiver occupied bandwidth function.
2. Measurements were performed with the EUT transmitting with QPSK and 16QAM modulation schemes, with resource blocks settings as detailed in section 4.3 of this report.
3. The test receiver was connected to the RF port on the EUT using suitable attenuation and RF cable.


**Transmitter Occupied Bandwidth (continued)**

**Results: 1.4 MHz Channel Bandwidth / Bottom Channel / QPSK**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
824.7	6	0	20	100	1.086
824.7	3	2	20	100	0.584



**QPSK / 6 Resource Blocks (0 Offset)**




**QPSK / 3 Resource Blocks (2 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 1.4 MHz Channel Bandwidth / Bottom Channel / 16QAM**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
824.7	6	0	20	100	1.094
824.7	3	2	20	100	0.579



**16QAM / 6 Resource Blocks (0 Offset)**




**16QAM / 3 Resource Blocks (2 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 1.4 MHz Channel Bandwidth / Middle Channel / QPSK**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
836.5	6	0	20	100	1.098
836.5	3	2	20	100	0.575



**QPSK / 6 Resource Blocks (0 Offset)**




**QPSK / 3 Resource Blocks (2 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 1.4 MHz Channel Bandwidth / Middle Channel / 16QAM**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
836.5	6	0	20	100	1.082
836.5	3	2	20	100	0.575



**16QAM / 6 Resource Blocks (0 Offset)**




**16QAM / 3 Resource Blocks (2 Offset)**




**Transmitter Occupied Bandwidth (continued)**

**Results: 1.4 MHz Channel Bandwidth / Top Channel / QPSK**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
848.3	6	0	20	100	1.086
848.3	3	2	20	100	0.584



**QPSK / 6 Resource Blocks (0 Offset)**



**QPSK / 3 Resource Blocks (2 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 1.4 MHz Channel Bandwidth / Top Channel / 16QAM**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
848.3	6	0	20	100	1.094
848.3	3	2	20	100	0.579



**16QAM / 6 Resource Blocks (0 Offset)**




**16QAM / 3 Resource Blocks (2 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 3 MHz Channel Bandwidth / Bottom Channel / QPSK**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
825.5	15	0	30	100	2.683
825.5	8	4	30	100	1.467



**QPSK / 15 Resource Blocks (0 Offset)**




**QPSK / 8 Resource Blocks (4 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 3 MHz Channel Bandwidth / Bottom Channel / 16QAM**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
825.5	15	0	30	100	2.692
825.5	8	4	30	100	1.467



**16QAM / 15 Resource Blocks (0 Offset)**




**16QAM / 8 Resource Blocks (4 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 3 MHz Channel Bandwidth / Middle Channel / QPSK**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
836.5	15	0	30	100	2.692
836.5	8	4	30	100	1.467



**QPSK / 15 Resource Blocks (0 Offset)**




**QPSK / 8 Resource Blocks (4 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 3 MHz Channel Bandwidth / Middle Channel / 16QAM**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
836.5	15	0	30	100	2.683
836.5	8	4	30	100	1.485



**16QAM / 15 Resource Blocks (0 Offset)**




**16QAM / 8 Resource Blocks (4 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 3 MHz Channel Bandwidth / Top Channel / QPSK**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
847.5	15	0	30	100	2.683
847.5	8	4	30	100	1.476



**QPSK / 15 Resource Blocks (0 Offset)**




**QPSK / 8 Resource Blocks (4 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 3 MHz Channel Bandwidth / Top Channel / 16QAM**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
847.5	15	0	30	100	2.700
847.5	8	4	30	100	1.493



**16QAM / 15 Resource Blocks (0 Offset)**




**16QAM / 8 Resource Blocks (4 Offset)**




**Transmitter Occupied Bandwidth (continued)**

**Results: 5 MHz Channel Bandwidth / Bottom Channel / QPSK**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
826.5	25	0	50	200	4.486
826.5	12	6	50	200	2.229



**QPSK / 25 Resource Blocks (0 Offset)**




**QPSK / 12 Resource Blocks (6 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 5 MHz Channel Bandwidth / Bottom Channel / 16QAM**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
826.5	25	0	50	200	4.486
826.5	12	6	50	200	2.200



**16QAM / 25 Resource Blocks (0 Offset)**




**16QAM / 12 Resource Blocks (6 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 5 MHz Channel Bandwidth / Middle Channel / QPSK**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
836.5	25	0	50	200	4.486
836.5	12	6	50	200	2.200



**QPSK / 25 Resource Blocks (0 Offset)**




**QPSK / 12 Resource Blocks (6 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 5 MHz Channel Bandwidth / Middle Channel / 16QAM**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
836.5	25	0	50	200	4.486
836.5	12	6	50	200	2.200



**16QAM / 25 Resource Blocks (0 Offset)**




**16QAM / 12 Resource Blocks (6 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 5 MHz Channel Bandwidth / Top Channel / QPSK**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
846.5	25	0	50	200	4.472
846.5	12	6	50	200	2.200



**QPSK / 25 Resource Blocks (0 Offset)**




**QPSK / 12 Resource Blocks (6 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 5 MHz Channel Bandwidth / Top Channel / 16QAM**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
846.5	25	0	50	200	4.486
846.5	12	6	50	200	2.214



**16QAM / 25 Resource Blocks (0 Offset)**




**16QAM / 12 Resource Blocks (6 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 10 MHz Channel Bandwidth / Bottom Channel / QPSK**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
829.0	50	0	100	300	8.973
829.0	25	12	100	300	4.573



**QPSK / 50 Resource Blocks (0 Offset)**




**QPSK / 25 Resource Blocks (12 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 10 MHz Channel Bandwidth / Bottom Channel / 16QAM**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
829.0	50	0	100	300	8.944
829.0	25	12	100	300	4.573



**16QAM / 50 Resource Blocks (0 Offset)**




**16QAM / 25 Resource Blocks (12 Offset)**




**Transmitter Occupied Bandwidth (continued)**

**Results: 10 MHz Channel Bandwidth / Middle Channel / QPSK**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
836.5	50	0	100	300	8.944
836.5	25	12	100	300	4.573



**QPSK / 50 Resource Blocks (0 Offset)**




**QPSK / 25 Resource Blocks (12 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 10 MHz Channel Bandwidth / Middle Channel / 16QAM**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
836.5	50	0	100	300	8.944
836.5	25	12	100	300	4.689



**16QAM / 50 Resource Blocks (0 Offset)**




**16QAM / 25 Resource Blocks (12 Offset)**


**Transmitter Occupied Bandwidth (continued)**

**Results: 10 MHz Channel Bandwidth / Top Channel / QPSK**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
844.0	50	0	100	300	8.944
844.0	25	12	100	300	4.573





**QPSK / 50 Resource Blocks (0 Offset)**



**QPSK / 25 Resource Blocks (12 Offset)**

**Transmitter Occupied Bandwidth (continued)****Results: 10 MHz Channel Bandwidth / Top Channel / 16QAM**

Frequency (MHz)	Resource Blocks	Resource Block Offset	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Occupied Bandwidth (MHz)
844.0	50	0	100	300	8.944
844.0	25	12	100	300	4.573

**16QAM / 50 Resource Blocks (0 Offset)****16QAM / 25 Resource Blocks (12 Offset)****Test Equipment Used:**

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1658	Thermohygrometer	JM Handelspunkt	30.5015.13	None stated	14 Mar 2015	12
L1127	Signal Analyser	Rohde & Schwarz	FSV13	100863	24 Apr 2015	12
S0537	DC Power Supply	TTi	EL302D	249928	Calibrated before use	-
M1251	Digital Multimeter	Fluke	175	89170179	19 May 2015	12
A2535	Directional Coupler	AtlanTec RF	CDC-003060-20	14041701719	Calibrated before use	-
A2508	Attenuator	AtlanTec RF	AN18-10	821846#3	Calibrated before use	-
A539	Power Splitter	Rohde & Schwarz	RVZ	22441	Calibrated before use	-

**5.2.3. Transmitter Out of Band Radiated Emissions****Test Summary:**

<b>Test Engineers:</b>	David Doyle & Nick Steele	<b>Test Dates:</b>	07 August 2014 & 09 August 2014
<b>Test Sample IMEI:</b>	352025060238798		

<b>FCC Reference:</b>	Parts 2.1053 & 22.917
<b>Test Method Used:</b>	As detailed in KDB 971168 Section 6.1 referencing FCC Part 2.1053
<b>Frequency Range:</b>	30 MHz to 9 GHz
<b>Configuration:</b>	5 MHz, QPSK, 1RB, 0 Offset

**Environmental Conditions:**

<b>Temperature (°C):</b>	22 to 25
<b>Relative Humidity (%):</b>	31 to 40





**Note(s):**


1. The EUT was set to transmit with a 5 MHz channel bandwidth with QPSK modulation applied and 1 resource block with 0 offset, as this was found to be the worst case modulation scheme with regards to emissions after preliminary investigations and, as this mode emits the highest transmit output power level, it was deemed to be the worst case.
2. The emission seen on the 30 MHz to 1 GHz plot at approximately 846.5 MHz is the EUT carrier.
3. No spurious emissions were detected above the measurement system noise floor therefore the highest peak noise floor reading of the measuring receiver was recorded in the table below.
4. Measurements below 1 GHz were performed in a semi-anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.
5. Pre-scans above 1 GHz were performed in a fully anechoic chamber (Asset Number K0002) at a distance of 3 metres. The EUT was placed at a height of 1.5 metres above the test chamber floor in the centre of the chamber turntable. All measurement antennas were placed at a fixed height of 1.5 metres above the test chamber floor, in line with the EUT. Final measurements above 1 GHz were performed in a semi-anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.

**Results: Top Channel**

<b>Frequency (MHz)</b>	<b>Peak Level (dBm)</b>	<b>Limit (dBm)</b>	<b>Margin (dB)</b>	<b>Result</b>
3981.964	-36.3	-13.0	23.3	Complied

### Transmitter Out of Band Radiated Emissions (continued)



**Transmitter Out of Band Radiated Emissions (continued)****Test Equipment Used:**

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1622	Thermohygrometer	JM Handelspunkt	30.5015.06	None stated	31 Dec 2014	12
K0001	5m RSE Chamber	Rainford EMC	N/A	N/A	26 Nov 2014	12
M1273	Test Receiver	Rohde & Schwarz	ESIB 26	100275	15 Feb 2015	12
G0543	Amplifier	Sonoma	310N	230801	19 Aug 2014	3
A490	Antenna	Chase	CBL6111A	1590	29 Apr 2015	12
A1834	Attenuator	Hewlett Packard	8491B	10444	15 Nov 2014	12
A1393	Attenuator	Huber & Suhner	6820.17.B	757456	02 May 2015	12
M1656	Thermohygrometer	JM Handelspunkt	30.5015.13	Not stated	14 Mar 2015	12
K0002	3m RSE Chamber	Rainford EMC	N/A	N/A	14 Nov 2014	12
M1124	Test Receiver	Rohde & Schwarz	ESIB 26	100046K	01 Oct 2014	12
A1534	Pre-Amplifier	Hewlett Packard	8449B	3008A00405	18 May 2015	12
A1818	Antenna	EMCO	3115	00075692	14 Nov 2014	12
A253	Antenna	Flann Microwave	12240-20	128	14 Nov 2014	12
A254	Antenna	Flann Microwave	14240-20	139	14 Nov 2014	12
A255	Antenna	Flann Microwave	16240-20	519	14 Nov 2014	12
A1396	Attenuator	Huber & Suhner	6810.17.B	757987	02 May 2015	12
A1974	High Pass Filter	AtlanTecRF	AFH-01000	090000283	12 Apr 2015	12
A1975	High Pass Filter	AtlanTecRF	AFH-03000	090424010	12 Apr 2015	12

**5.2.4. Transmitter Radiated Emissions at Band Edges****Test Summary:**

<b>Test Engineers:</b>	Andrew Edwards & Nick Steele	<b>Test Dates:</b>	16 July 2014 & 14 September 2014
<b>Test Sample IMEI:</b>	352025060238798		

<b>FCC Reference:</b>	Parts 2.1053 & 22.917
<b>Test Method Used:</b>	As detailed in KDB 971168 Section 6.1 referencing FCC Part 22.917

**Environmental Conditions:**

<b>Temperature (°C):</b>	24 to 25
<b>Relative Humidity (%):</b>	42 to 46

**Note(s):**


1. Measurements were performed with the EUT transmitting QPSK and 16QAM modulation schemes, with the maximum resource blocks settings.
2. Measurements were performed in a fully anechoic chamber (Asset Number K0002) at a distance of 3 metres. The EUT was placed at a height of 1.5 metres above the test chamber floor in the centre of the chamber turntable. The measurement antenna was placed at a fixed height of 1.5 metres above the test chamber floor in line with the EUT.
3. 1.4 MHz Channel bandwidth: In the first 1.0 MHz immediately outside and adjacent to the operating band, the test receiver resolution bandwidth was set to 20 kHz (>1% of 1.45 MHz, the widest 26 dB emission bandwidth) and video bandwidth 100 kHz (as close to > three times the resolution bandwidth as the test receiver allowed).
4. 3 MHz Channel bandwidth: In the first 1.0 MHz immediately outside and adjacent to the operating band, the test receiver resolution bandwidth was set to 30 kHz (1% of 3 MHz, the widest 26 dB emission bandwidth) and video bandwidth 100 kHz (as close to > three times the resolution bandwidth as the test receiver allowed).
5. 5 MHz Channel bandwidth: In the first 1.0 MHz immediately outside and adjacent to the operating band, the test receiver resolution bandwidth was set to 50 kHz (1% of 5 MHz, the widest 26 dB emission bandwidth) and video bandwidth 200 kHz (as close to > three times the resolution bandwidth as the test receiver allowed).
6. 10 MHz Channel bandwidth: In the first 1.0 MHz immediately outside and adjacent to the operating band, the test receiver resolution bandwidth was set to 100 kHz (>1% of 9.9 MHz, the widest 26 dB emission bandwidth) and video bandwidth 300 kHz (three times the resolution bandwidth).




**Transmitter Radiated Emissions at Band Edges (continued)**

**Results: 1.4 MHz Channel Bandwidth / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	6	0	-31.5	-13.0	18.5	Complied
849	6	0	-32.3	-13.0	19.3	Complied
849.011	6	0	-31.5	-13.0	18.5	Complied



**QPSK / Lower Band Edge**




**QPSK / Upper Band Edge**


**Transmitter Radiated Emissions at Band Edges (continued)**

**Results: 1.4 MHz Channel Bandwidth / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	1	0	-25.2	-13.0	12.2	Complied
849	1	5	-25.9	-13.0	12.9	Complied



**QPSK / Lower Band Edge**




**QPSK / Upper Band Edge**


**Transmitter Radiated Emissions at Band Edges (continued)**

**Results: 1.4 MHz Channel Bandwidth / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Result
823.998	6	0	-33.5	-13.0	20.5	Complied
824	6	0	-34.0	-13.0	21.0	Complied
849	6	0	-32.6	-13.0	19.6	Complied



**16QAM / Lower Band Edge**




**16QAM / Upper Band Edge**


**Transmitter Radiated Emissions at Band Edges (continued)**

**Results: 1.4 MHz Channel Bandwidth / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	1	0	-25.7	-13.0	12.7	Complied
849	1	5	-28.7	-13.0	15.7	Complied



**16QAM / Lower Band Edge**




**16QAM / Upper Band Edge**


**Transmitter Radiated Emissions at Band Edges (continued)**

**Results: 3 MHz Channel Bandwidth / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Result
823.979	15	0	-31.2	-13.0	18.2	Complied
824	15	0	-35.1	-13.0	22.1	Complied
849	15	0	-32.5	-13.0	19.5	Complied
849.006	15	0	-31.5	-13.0	18.5	Complied



**QPSK / Lower Band Edge**




**QPSK / Upper Band Edge**


**Transmitter Radiated Emissions at Band Edges (continued)**

**Results: 3 MHz Channel Bandwidth / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	1	0	-24.1	-13.0	11.1	Complied
849	1	14	-24.1	-13.0	11.1	Complied



**QPSK / Lower Band Edge**




**QPSK / Upper Band Edge**


**Transmitter Radiated Emissions at Band Edges (continued)**

**Results: 3 MHz Channel Bandwidth / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Result
823.992	15	0	-32.7	-13.0	19.7	Complied
824	15	0	-34.9	-13.0	21.9	Complied
849	15	0	-33.2	-13.0	20.2	Complied
849.008	15	0	-32.7	-13.0	19.7	Complied



**16QAM / Lower Band Edge**



**16QAM / Upper Band Edge**


**Transmitter Radiated Emissions at Band Edges (continued)**

**Results: 3 MHz Channel Bandwidth / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	1	0	-24.7	-13.0	11.7	Complied
849	1	14	-26.5	-13.0	13.5	Complied



**16QAM / Lower Band Edge**




**16QAM / Upper Band Edge**




**Transmitter Radiated Emissions at Band Edges (continued)**

**Results: 5 MHz Channel Bandwidth / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Result
823.997	25	0	-34.8	-13.0	21.8	Complied
824	25	0	-36.0	-13.0	23.0	Complied
849	25	0	-33.7	-13.0	20.7	Complied



**QPSK / Lower Band Edge**




**QPSK / Upper Band Edge**


**Transmitter Radiated Emissions at Band Edges (continued)**

**Results: 5 MHz Channel Bandwidth / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	1	0	-28.3	-13.0	15.3	Complied
849	1	24	-28.3	-13.0	15.3	Complied



**QPSK / Lower Band Edge**




**QPSK / Upper Band Edge**


**Transmitter Radiated Emissions at Band Edges (continued)**

**Results: 5 MHz Channel Bandwidth / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Result
823.989	25	0	-36.1	-13.0	23.1	Complied
824	25	0	-37.8	-13.0	24.8	Complied
849	25	0	-36.5	-13.0	23.5	Complied
849.011	25	0	-33.9	-13.0	20.9	Complied



**16QAM / Lower Band Edge**




**16QAM / Upper Band Edge**


**Transmitter Radiated Emissions at Band Edges (continued)**

**Results: 5 MHz Channel Bandwidth / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	1	0	-28.6	-13.0	15.6	Complied
849	1	24	-30.8	-13.0	17.8	Complied



**16QAM / Lower Band Edge**




**16QAM / Upper Band Edge**


**Transmitter Radiated Emissions at Band Edges (continued)**

**Results: 10 MHz Channel Bandwidth / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Result
823.926	50	0	-32.6	-13.0	19.6	Complied
824	50	0	-33.9	-13.0	20.9	Complied
849	50	0	-35.7	-13.0	22.7	Complied
849.030	50	0	-35.2	-13.0	22.2	Complied



**QPSK / Lower Band Edge**




**QPSK / Upper Band Edge**


**Transmitter Radiated Emissions at Band Edges (continued)**

**Results: 10 MHz Channel Bandwidth / QPSK**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	1	0	-31.2	-13.0	18.2	Complied
849	1	49	-31.9	-13.0	18.9	Complied



**QPSK / Lower Band Edge**




**QPSK / Upper Band Edge**


**Transmitter Radiated Emissions at Band Edges (continued)**

**Results: 10 MHz Channel Bandwidth / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Result
823.821	50	0	-32.9	-13.0	19.9	Complied
824	50	0	-34.5	-13.0	21.5	Complied
849	50	0	-35.7	-13.0	22.7	Complied
849.024	50	0	-35.3	-13.0	22.3	Complied



**16QAM / Lower Band Edge**




**16QAM / Upper Band Edge**


**Transmitter Radiated Emissions at Band Edges (continued)**

**Results: 10 MHz Channel Bandwidth / 16QAM**

Frequency (MHz)	Resource Block(s)	Resource Block Offset	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	1	0	-32.2	-13.0	19.2	Complied
849	1	49	-32.4	-13.0	19.4	Complied



16QAM / Lower Band Edge



16QAM / Upper Band Edge

**Test Equipment Used:**

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1656	Thermohygrometer	JM Handelspunkt	30.5015.13	Not stated	14 Mar 2015	12
K0002	3m RSE Chamber	Rainford	N/A	N/A	14 Nov 2014	12
M1874	Test Receiver	Rohde & Schwarz	ESU26	100553	13 May 2015	12
A288	Antenna	Chase	CBL6111A	1589	20 Aug 2014	12
A1393	Attenuator	Huber & Suhner	6820.17.B	757456	02 May 2015	12



**5.2.5. Transmitter Frequency Stability (Temperature Variation)****Test Summary:**

<b>Test Engineer:</b>	Keith Tucker	<b>Test Dates:</b>	09 July 2014 & 10 July 2014
<b>Test Sample IMEI:</b>	352025060274538		

<b>FCC Reference:</b>	Parts 2.1055 & 22.355
<b>Test Method Used:</b>	As detailed in KDB 971168 Section 9.0 referencing ANSI TIA-603-C-2004 Section 2.2.2 and FCC Part 2.1055

**Environmental Conditions:**

<b>Ambient Temperature (°C):</b>	22 to 23
<b>Ambient Relative Humidity (%):</b>	38 to 49

**Note(s):**

1. Flying leads were connected internally to the EUT in place of the battery. These leads were extended and connected to a bench power supply, set at the EUT nominal voltage.
2. Frequency error was measured using a calibrated Rohde & Schwarz CMW 500 Universal Radio Communications Tester in accordance with current Rohde & Schwarz application notes. The EUT was connected by suitable RF cables to the CMW 500. A bi-directional communications link was established between the EUT and CMW 500. The frequency meter value was recorded.
3. Temperature was monitored throughout the test with a calibrated digital thermometer.

**Results: Middle Channel (836.5 MHz)**

Temperature (°C)	Measured Frequency (MHz)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)	Margin (ppm)	Result
-30	836.500009	9	0.0108	2.5	2.4892	Complied
-20	836.500008	8	0.0096	2.5	2.4904	Complied
-10	836.499993	7	0.0084	2.5	2.4916	Complied
0	836.500007	7	0.0084	2.5	2.4916	Complied
10	836.500008	8	0.0096	2.5	2.4904	Complied
20	836.500008	8	0.0096	2.5	2.4904	Complied
30	836.500007	7	0.0084	2.5	2.4916	Complied
40	836.499991	9	0.0108	2.5	2.4892	Complied
50	836.500007	7	0.0084	2.5	2.4916	Complied

**Transmitter Frequency Stability (Temperature Variation) (continued)****Test Equipment Used:**

<b>Asset No.</b>	<b>Instrument</b>	<b>Manufacturer</b>	<b>Type No.</b>	<b>Serial No.</b>	<b>Date Calibration Due</b>	<b>Cal. Interval (Months)</b>
M1658	Thermohygrometer	JM Handelpunkt	30.5015.13	None stated	14 Mar 2015	12
M1870	Wideband Radio Comms Tester	Rohde & Schwarz	CMW500	145919	05 May 2015	12
G088	Dual DC power supply	Thurlby Thandar	CPX200	100700	Calibrated before use	-
M1251	Multimeter	Fluke	175	89170179	19 May 2015	12
M1643	Thermometer	Fluke	52II	18890136	07 Apr 2015	12
E013	Environmental Chamber	Sanyo	MTH-4200PR	none	Calibrated before use	-

**5.2.6. Transmitter Frequency Stability (Voltage Variation)****Test Summary:**

<b>Test Engineer:</b>	Keith Tucker	<b>Test Dates:</b>	09 July 2014 & 10 July 2014
<b>Test Sample IMEI:</b>	352025060274538		

<b>FCC Reference:</b>	Part 2.1055 & 22.355
<b>Test Method Used:</b>	As detailed in KDB 971168 Section 9.0 referencing ANSI TIA-603-C-2004 Section 2.2.2 and FCC Part 2.1055

**Environmental Conditions:**

<b>Temperature (°C):</b>	22 to 23
<b>Relative Humidity (%):</b>	38 to 49

**Note(s):**

1. Flying leads were connected internally to the EUT in place of the battery. These leads were extended and connected to a bench power supply.
2. Frequency error was measured using a calibrated Rohde & Schwarz CMW 500 Universal Radio Communications Tester in accordance with current Rohde & Schwarz application notes. The EUT was connected by suitable RF cables to the CMW 500. A bi-directional communications link was established between the EUT and CMW 500. The frequency meter value was recorded.
3. Voltage was monitored throughout the test with a calibrated digital voltmeter.

**Results: Middle Channel (836.5 MHz)**

Supply Voltage (V)	Measured Frequency (MHz)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)	Margin (ppm)	Result
3.4	836.500007	7	0.0084	2.5	2.4916	Complied
4.2	836.500008	8	0.0096	2.5	2.4904	Complied

**Test Equipment Used:**

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1658	Thermohygrometer	JM Handelpunkt	30.5015.13	None stated	14 Mar 2015	12
M1870	Wideband Radio Comms Tester	Rohde & Schwarz	CMW500	145919	05 May 2015	12
G088	Dual DC power supply	Thurlby Thandar	CPX200	100700	Calibrated before use	-
M1251	Multimeter	Fluke	175	89170179	19 May 2015	12

## **6. Measurement Uncertainty**

No measurement or test can ever be perfect and the imperfections give rise to error of measurement in the results. Consequently the result of a measurement is only an approximation to the value of the measurand (the specific quantity subject to measurement) and is only complete when accompanied by a statement of the uncertainty of the approximation.

The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

The uncertainty of the result may need to be taken into account when interpreting the measurement results.

The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor such that a confidence level of approximately 95% is maintained. For the purposes of this document "approximately" is interpreted as meaning "effectively" or "for most practical purposes".

<b>Measurement Type</b>	<b>Range</b>	<b>Confidence Level (%)</b>	<b>Calculated Uncertainty</b>
Conducted Output Power	824 to 849 MHz	95%	±0.76 dB
Frequency Stability	824 to 849 MHz	95%	±23 Hz
Occupied Bandwidth	824 to 849 MHz	95%	±3.92 %
Radiated Spurious Emissions	30 MHz to 1 GHz	95%	±5.65 dB
Radiated Spurious Emissions	1 GHz to 9 GHz	95%	±2.94 dB

The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty the published guidance of the appropriate accreditation body is followed.

## **7. Report Revision History**

Version Number	Revision Details		
	Page No(s)	Clause	Details
1.0	-	-	Initial Version
2.0	35	-	Updated plot
3.0	-	-	Admin updates Additional Radiated Band Edge measurements

--- END OF REPORT ---