



**Add value.
Inspire trust.**

Report On

Specific Absorption Rate Testing of the Apple Inc, A2179.

Covering FCC 47CFR 2.1093, RSS 102 Issue 5
and related documents.

FCC ID: BCGA2179
IC: 579C-A2179

COMMERCIAL-IN-CONFIDENCE

Document 75945251 Report 18 Issue 3

February 2020



TÜV SÜD, Octagon House, Concorde Way, Segensworth North,
Fareham, Hampshire, United Kingdom, PO15 5RL
Tel: +44 (0) 1489 558100. Website: www.tuv-sud.co.uk

COMMERCIAL-IN-CONFIDENCE

REPORT ON

Specific Absorption Rate Testing of the
Apple Inc, A2179

Document 75945251 Report 18 Issue 2

February 2020

PREPARED FOR

Apple Inc
One Apple Park Way
Cupertino
California 95014
USA

PREPARED BY

Handwritten signature of Stephen Dodd in black ink.

Stephen Dodd
Engineer (SAR and RF)

APPROVED BY

Handwritten signature of Jon Kenny in black ink.

Jon Kenny
Authorised Signatory

DATED

25 February 2020



CONTENTS

Section	Page No
1	REPORT SUMMARY 3
1.1	Report Modification History 4
1.2	Introduction 4
1.3	Brief Summary of Results 5
1.4	Test Results Summary 6
1.5	Power Tables (Tune up values)..... 16
1.6	Power Measurements..... 19
2	TEST DETAILS 24
2.1	DASY5 Measurement System 25
2.2	Bluetooth 2450 MHz Body SAR Test Results 29
2.3	WLAN 2450 MHz Body SAR Test Results 30
2.4	WLAN U-NII 2A Body SAR Test Results 33
2.5	WLAN U-NII 2C Body SAR Test Results..... 37
2.6	WLAN U-NII 3 Body SAR Test Results 43
3	TEST EQUIPMENT USED 46
3.1	Test Equipment Used 47
3.2	Test Software..... 48
3.3	Dielectric Properties of Simulant Liquids 49
3.4	Test Conditions..... 50
3.5	Measurement Uncertainty 51
4	ACCREDITATION, DISCLAIMERS AND COPYRIGHT..... 53
4.1	Accreditation, Disclaimers and Copyright..... 54
ANNEX A	Probe Calibration Reports A.2
ANNEX B	Dipole Calibration Reports..... B.2
ANNEX C	Photographs C.2



SECTION 1

REPORT SUMMARY

Specific Absorption Rate Testing of the
A2179



1.1 REPORT MODIFICATION HISTORY

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
01	First Issue	31 January 2020
02	Amended FCC ID	10 February 2020
03	Section 1.4.3 – Simultaneous transmission explanation corrected. and Rear Of Display SAR measurements included. EUT and Test Positional Photographs moved to Annex C.	25 February 2020

1.2 INTRODUCTION

The information contained in this report is intended to show verification of the Specific Absorption Rate Testing of the A2179 to the requirements of KDB 447498 D01 v06 General RF Exposure Guidance.

Objective	To perform Specific Absorption Rate Testing to determine the Equipment Under Test's (EUT's) compliance with the requirements specified of KDB 447498 D01 v06 General RF Exposure Guidance, for the series of tests carried out.
Applicant	Apple Inc
Manufacturer	Apple Inc
Manufacturing Description	Laptop Computer
Model Number	A2179
Serial Numbers	C02ZD00KM8M5 (Radiated Sample) C02ZC00AM8N2 (Conducted Sample)
Number of Samples Tested	2
Hardware Version	Rev 1.0
Software Version	19C4
Battery Cell Manufacturer	Not Supplied
Battery Model Number	Not Supplied
Test Specification/Issue/Date	KDB 447498 D01 v06 General RF Exposure Guidance
Order Number	0540175478
Date of Receipt of EUT	04-October-2019
Start of Test	22-November-2019
Finish of Test	02-December-2019
Related Documents	FCC 47CFR 2.1093: 2015 KDB 865664 – D01 v01r04 KDB 865664 – D02 v01r02 KDB 648474 – D04 v01r03 KDB 447498 – D01 v06 IEEE 1528-2013 KDB 248227 – D01 v02r02
Name of Engineers	Mohamud Mohamud Stephen Dodd



1.3 BRIEF SUMMARY OF RESULTS

The measurements shown in this report were made in accordance with the procedures specified KDB 447498 D01 v06 General RF Exposure Guidance.

The maximum 1g volume averaged stand-alone SAR found during this Assessment:

Max 1g SAR (W/kg) Body	0.95 (Measured)	1.09 (Scaled)
The maximum 1g volume averaged SAR level measured for all the tests performed did not exceed the limits for General Population/Uncontrolled Exposure Partial Body of 1.6 W/kg.		

The maximum 1g volume averaged stand-alone Reported SAR found during this Assessment for each supported mode:

RAT	Band	Test Configuration	Max Reported SAR (W/kg)	Highest Simultaneous Transmission SAR (W/kg)
Bluetooth	2450 MHz	Body - Ant WF1	0.20	1.01
WLAN	U-NII-2C	Body - Ant WF1	0.81	
The maximum 1g volume averaged SAR level measured for all the tests performed (including simultaneous transmission analysis results) did not exceed the limits for General Population/Uncontrolled Exposure Partial Body of 1.6 W/kg.				



1.4 TEST RESULTS SUMMARY

1.4.1 System Performance / Validation Check Results

Prior to formal testing being performed a System Check was performed in accordance with KDB 865664 and the results were compared against published data in Standard IEEE 1528-2013. The following results were obtained: -

System performance / Validation results

Date	Frequency (MHz)	Fluid Type	Measured Max 1g SAR (W/kg) *	Max 1g SAR (W/kg) Target	Percentage Drift on Reference
22-11-2019	2450	MBBL	49.08	51.2	-4.31
22-11-2019	5300	MBBL	71.83	74.2	-3.30
23-11-2019	5600	MBBL	77.42	76.1	1.70
25-11-2019	5300	MBBL	70.03	74.2	-5.95
26-11-2019	5600	MBBL	74.22	76.1	-2.53
02-12-2019	2450	MBBL	50.48	51.2	-1.43

*Normalised to a forward power of 1W



1.4.2 Results Summary Tables

Bluetooth - 2450 MHz - BDR - DH5 - Antenna WF1 :
Specific Absorption Rate (Maximum SAR) 1g Results

Test Position	Channel Number	Frequency (MHz)	Measured Average Power (dBm)	Tune Up (dBm)	Measured 1g SAR (W/kg)	Scaled 1g SAR (W/kg)	Scan Figure Number
0mm - Bottom	78	2480	16.10	16.50	0.18	0.20	3
0mm - Rear of Display	78	2480	16.10	16.50	0.03	0.03	4
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is: ≤ 0.8W/kg when the transmission band is ≤ 100MHz ≤ 0.6W/kg when the transmission band is between 100MHz and 200MHz ≤ 0.4W/kg when the transmission band is ≥ 200MHz							

WLAN - 2450 MHz - 802.11b - 20 MHz - 1 Mbps - SISO Antenna WF1 :
Specific Absorption Rate (Maximum SAR) 1g Results

Test Position	Channel Number	Frequency (MHz)	Measured Average Power (dBm)	Tune Up (dBm)	Measured 1g SAR (W/kg)	Scaled 1g SAR (W/kg)	Scan Figure Number
0mm Bottom	10	2457	19.60	20.00	0.64	0.70	5
0mm Rear of Display	10	2457	19.60	20.00	0.12	0.13	6
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) KDB 248227 D01 v02 - Testing was not required for OFDM as per Section 5.2.2 KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is: ≤ 0.8W/kg when the transmission band is ≤ 100MHz ≤ 0.6W/kg when the transmission band is between 100MHz and 200MHz ≤ 0.4W/kg when the transmission band is ≥ 200MHz							

WLAN - 2450 MHz - 802.11b - 20 MHz - 1 Mbps - SISO Antenna WF2:
Specific Absorption Rate (Maximum SAR) 1g Results

Test Position	Channel Number	Frequency (MHz)	Measured Average Power (dBm)	Tune Up (dBm)	Measured 1g SAR (W/kg)	Scaled 1g SAR (W/kg)	Scan Figure Number
0mm - Bottom	6	2437	19.60	20.00	0.68	0.75	7
0mm - Rear of Display	6	2437	19.60	20.00	0.11	0.12	8
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) KDB 248227 D01 v02 - Testing was not required for OFDM as per Section 5.2.2 KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is: ≤ 0.8W/kg when the transmission band is ≤ 100MHz ≤ 0.6W/kg when the transmission band is between 100MHz and 200MHz ≤ 0.4W/kg when the transmission band is ≥ 200MHz							



WLAN - 2450 MHz - 802.11b - 20 MHz - 1 Mbps – 2x2 MIMO - Antenna WF1 and WF2:
Specific Absorption Rate (Maximum SAR) 1g Results

Test Position	Ant	Channel Number	Frequency (MHz)	Measured Average Power (dBm)	Tune Up (dBm)	Measured 1g SAR (W/kg)	Scaled 1g SAR (W/kg)	Scan Figure Number
0mm Bottom	WF1	6	2437	19.50	20.00	0.60	0.68	9
0mm Bottom	WF2	6	2437	19.40	20.00	0.69	0.80	
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) KDB 248227 D01 v02 - Testing was not required for OFDM as per Section 5.2.2 KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is: ≤ 0.8W/kg when the transmission band is ≤ 100MHz ≤ 0.6W/kg when the transmission band is between 100MHz and 200MHz ≤ 0.4W/kg when the transmission band is ≥ 200MHz Worst case position which was found in 2.4Ghz SISO testing was used.								

WLAN - U-NII-2A - 802.11n - 40 MHz - MCS0 - SISO Antenna WF1
Specific Absorption Rate(Maximum SAR) 1g Results

Test Position	Channel Number	Frequency (MHz)	Measured Average Power (dBm)	Tune Up (dBm)	Measured 1g SAR (W/kg)	Scaled 1g SAR (W/kg)	Scan Figure Number
0mm Bottom	62	5310	15.00	15.50	0.58	0.66	10
0mm Rear of Display	62	5310	15.00	15.50	0.11	0.13	11
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is: ≤ 0.8W/kg when the transmission band is ≤ 100MHz ≤ 0.6W/kg when the transmission band is between 100MHz and 200MHz ≤ 0.4W/kg when the transmission band is ≥ 200MHz							

WLAN - U-NII-2A - 802.11n - 40 MHz - MCS0 - SISO Antenna WF2
Specific Absorption Rate(Maximum SAR) 1g Results

Test Position	Channel Number	Frequency (MHz)	Measured Average Power (dBm)	Tune Up (dBm)	Measured 1g SAR (W/kg)	Scaled 1g SAR (W/kg)	Scan Figure Number
0mm Bottom	54	5270	14.90	15.50	0.86	0.99	12
0mm Rear of Display	54	5270	14.90	15.50	0.19	0.21	13
0mm Bottom	62	5310	14.90	15.50	0.95	1.09	14
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is: ≤ 0.8W/kg when the transmission band is ≤ 100MHz ≤ 0.6W/kg when the transmission band is between 100MHz and 200MHz ≤ 0.4W/kg when the transmission band is ≥ 200MHz							



WLAN - U-NII-2A - 802.11n - 20 MHz - MCS0 - 2x2 MIMO - Antenna WF1 and WF2:
Specific Absorption Rate (Maximum SAR) 1g Results

Test Position	Ant	Channel Number	Frequency (MHz)	Measured Average Power (dBm)	Tune Up (dBm)	Measured 1g SAR (W/kg)	Scaled 1g SAR (W/kg)	Scan Figure Number
0mm Bottom	WF1	54	5270	15.00	15.50	0.61	0.68	15
0mm Bottom	WF2	54	5270	14.90	15.50	0.78	0.90	
0mm Bottom	WF1	62	5310	14.10	14.75	0.39	0.45	16
0mm Bottom	WF2	62	5310	14.20	14.75	0.60	0.68	
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is: $\leq 0.8W/kg$ when the transmission band is $\leq 100MHz$ $\leq 0.6W/kg$ when the transmission band is between 100MHz and 200MHz $\leq 0.4W/kg$ when the transmission band is $\geq 200MHz$ Worst case position which was found in SISO testing was used.								

WLAN - U-NII-2C - 802.11ac - 80 MHz - MCS0 - SISO Antenna WF1
Specific Absorption Rate(Maximum SAR) 1g Results

Test Position	Channel Number	Frequency (MHz)	Measured Average Power (dBm)	Tune Up (dBm)	Measured 1g SAR (W/kg)	Scaled 1g SAR (W/kg)	Scan Figure Number
0mm Bottom	138	5690	14.00	14.50	0.73	0.81	17
0mm Rear of Display	138	5690	14.00	14.50	0.21	0.24	18
0mm Bottom	106	5530	14.00	14.50	0.61	0.69	19
0mm Bottom	122	5610	13.90	14.50	0.65	0.75	20
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is: $\leq 0.8W/kg$ when the transmission band is $\leq 100MHz$ $\leq 0.6W/kg$ when the transmission band is between 100MHz and 200MHz $\leq 0.4W/kg$ when the transmission band is $\geq 200MHz$							



WLAN - U-NII-2C - 802.11ac - 80 MHz - MCS0 - SISO Antenna WF2
 Specific Absorption Rate(Maximum SAR) 1g Results

Test Position	Channel Number	Frequency (MHz)	Measured Average Power (dBm)	Tune Up (dBm)	Measured 1g SAR (W/kg)	Scaled 1g SAR (W/kg)	Scan Figure Number
0mm Bottom	122	5610	14.00	14.50	0.75	0.84	21
0mm Rear of Display	122	5610	14.00	14.50	0.17	0.19	22
0mm Bottom	138	5610	14.00	14.50	0.84	0.94	23
0mm Bottom	106	5530	13.90	14.50	0.80	0.92	24
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is: ≤ 0.8W/kg when the transmission band is ≤ 100MHz ≤ 0.6W/kg when the transmission band is between 100MHz and 200MHz ≤ 0.4W/kg when the transmission band is ≥ 200MHz							

WLAN - U-NII-2C - 802.11ac - 80 MHz - MCS0 - 2x2 MIMO - Antenna WF1 and WF2:
 Specific Absorption Rate (Maximum SAR) 1g Results

Test Position	Antenna	Channel Number	Frequency (MHz)	Measured Average Power (dBm)	Tune Up (dBm)	Measured 1g SAR (W/kg)	Scaled 1g SAR (W/kg)	Scan Figure Number
0mm Bottom	Antenna WF1	122	5610	14.10	14.50	0.77	0.84	25
0mm Bottom	Antenna WF2	122	5610	14.10	14.50	0.78	0.85	
0mm Bottom	Antenna WF1	138	5690	14.10	14.50	0.69	0.75	26
0mm Bottom	Antenna WF2	138	5690	14.10	14.50	0.68	0.74	
0mm Bottom	Antenna WF1	106	5530	13.90	14.50	0.46	0.52	27
0mm Bottom	Antenna WF2	106	5530	13.90	14.50	0.57	0.65	
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is: ≤ 0.8W/kg when the transmission band is ≤ 100MHz ≤ 0.6W/kg when the transmission band is between 100MHz and 200MHz ≤ 0.4W/kg when the transmission band is ≥ 200MHz Worst case position which was found in SISO testing was used.								



WLAN - U-NII-3 - 802.11ac - 80 MHz - MCS0 - SISO Antenna WF1
 Specific Absorption Rate(Maximum SAR) 1g Results

Test Position	Channel Number	Frequency (MHz)	Measured Average Power (dBm)	Tune Up (dBm)	Measured 1g SAR (W/kg)	Scaled 1g SAR (W/kg)	Scan Figure Number
0mm Bottom	155	5775.00	12.90	13.50	0.54	0.61	28
0mm Rear of Display	155	5775.00	12.90	13.50	0.15	0.17	29
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is: ≤ 0.8W/kg when the transmission band is ≤ 100MHz ≤ 0.6W/kg when the transmission band is between 100MHz and 200MHz ≤ 0.4W/kg when the transmission band is ≥ 200MHz							

WLAN - U-NII-3 - 802.11ac - 80 MHz - MCS0 - SISO Antenna WF2
 Specific Absorption Rate(Maximum SAR) 1g Results

Test Position	Channel Number	Frequency (MHz)	Measured Average Power (dBm)	Tune Up (dBm)	Measured 1g SAR (W/kg)	Scaled 1g SAR (W/kg)	Scan Figure Number
0mm Bottom	155	5775.00	13.10	13.50	0.55	0.60	30
0mm Rear of Display	155	5775.00	13.10	13.50	0.13	0.14	31
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is: ≤ 0.8W/kg when the transmission band is ≤ 100MHz ≤ 0.6W/kg when the transmission band is between 100MHz and 200MHz ≤ 0.4W/kg when the transmission band is ≥ 200MHz							

WLAN - U-NII-3 - 802.11ac - 80 MHz - MCS0 - 2x2 MIMO - Antenna WF1 and WF2:
 Specific Absorption Rate (Maximum SAR) 1g Results

Test Position	Ant	Channel Number	Frequency (MHz)	Measured Average Power (dBm)	Tune Up (dBm)	Measured 1g SAR (W/kg)	Scaled 1g SAR (W/kg)	Scan Figure Number
0mm Bottom	Antenna WF1	155	5775	13.10	13.50	0.45	0.49	32
0mm Bottom	Antenna WF2	155	5775	13.00	13.50	0.41	0.46	
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is: ≤ 0.8W/kg when the transmission band is ≤ 100MHz ≤ 0.6W/kg when the transmission band is between 100MHz and 200MHz ≤ 0.4W/kg when the transmission band is ≥ 200MHz Worst case position which was found in U-NII-1 SISO testing was used.								



1.4.3 Simultaneous Transmission

Position	WLAN-SISO Antenna WF1 1 g SAR (W/kg)	WLAN-SISO Antenna WF2 1 g SAR (W/kg)	Bluetooth Antenna WF1 1 g SAR (W/kg)	Sum of 1 g SAR (W/Kg)	Peak Location Separation Ratio required?	Peak Location Separation Ratio
Bottom	0.81	-	0.20	1.01	No	N/A
Bottom	-	1.09	0.20	1.39	No	N/A
Rear Of Display	0.24	-	0.03	0.27	No	N/A
Rear Of Display	-	0.21	0.03	0.24	No	N/A

KDB 447498 D01 - Section 4.3.2: Simultaneous test exclusion is applicable as the sum of 1-g SAR of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit.

1.4.4 Measurement Variability (KDB 865664 D01)

Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR value of the initial repeated measurement is < 1.45 W/kg with $\leq 20\%$ variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. A second repeated measurement is required only if the measured result for the initial repeated measurement is within 10% of the SAR limit and vary by more than 20%, which are often related to device and measurement setup difficulties. The following procedures are applied to determine if repeated measurements are required. The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds. The repeated measurement results must be clearly identified in the SAR report. All measured SAR, including the repeated results, must be considered to determine compliance.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2 to 4 do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

Repeated measurements were required for the U-NII-2A and U-NII-2C frequency bands, All results for 2.4GHz and U-NII- Bands were all lower than 0.8W/kg



U-NII-2A : SISO WF2

Test Position	Ant	Channel Number	Frequency (MHz)	Scaled 1g SAR (W/kg)	Test	Ratio
0mm Bottom	Antenna WF2	62	5310	1.09	Initial	1.03
0mm Bottom	Antenna WF2	62	5310	1.06	Repeated	

U-NII-2C : SISO WF2

Test Position	Ant	Channel Number	Frequency (MHz)	Scaled 1g SAR (W/kg)	Test	Ratio
0mm Bottom	Antenna WF1	138	5690	0.94	Initial	1.07
0mm Bottom	Antenna WF1	138	5690	0.88	Repeated	

1.4.5 Standalone SAR Test Exclusion Considerations. (KDB 447498 D01)

The 1g SAR Test exclusion thresholds for 100 MHz to 6 GHz *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \sqrt{f (\text{GHz})} \leq 3.0, \text{ where}$$

- f (GHz) is the RF channel transmit frequency in GHz.
- Power and distance are rounded to the nearest mW and mm before calculation.
- The result is rounded to one decimal place for comparison.
- When the maximum test separation distance is < 5 mm, a distance of 5 mm is applied.

RAT & Band	Frequency (MHz)	Power (dBm)	Power (mW)	Test Position	Distance (mm)	Threshold	Test Exclusion
Bluetooth - 2450 MHz	2480	16.50	44.67	Body	5	14.1	No
WLAN – 2450MHz	2457	20.00	100.00	Body	5	31.3	No
WLAN – U-NII-1	5240	15.25	33.50	Body	5	15.3	No
WLAN – U-NII-2A	5320	15.50	35.48	Body	5	16.4	No
WLAN – U-NII-2C	5720	14.50	28.18	Body	5	13.5	No
WLAN – U-NII-3	5795	13.50	22.39	Body	5	10.8	No



1.4.6 Technical Description

The equipment under test (EUT) was an Apple Inc, A2179 Laptop Computer. A full technical description can be found in the manufacturer’s documentation.

1.4.7 Test Configuration and Modes of Operation

The testing was performed with an integral battery supplied by Apple Inc. The batteries were fully charged before each measurement and there were no external connections.

Supported technologies are Bluetooth (BDR/EDR/LE), 2.4 GHz WLAN 802.11b/g/n and 5 GHz WLAN 802.11a/n/ac. 2x2 MIMO is supported for WLAN, Bluetooth is transmitted on Antenna WF1 only.

WLAN and Bluetooth testing were achieved using the devices internal software, scripts and settings supplied by the customer. For each scan, the device was configured into a continuous transmission test mode at maximum power. Testing was performed in each position at the frequency that gave the highest output power for each band. Some SAR levels were found to be > 0.80 W/kg (KDB 447498 D01) therefore additional testing was required at the relevant frequencies / channels of the bands.

Conducted power measurements were performed on a modified device (accessible conducted ports) and the measured SAR results were power scaled to the maximum declared tune-up level.

For each antenna, the bottom surface and the rear of the EUT display were assessed for SAR. MIMO testing was carried out on the bottom surface of the EUT only. (Worst case position of SISO results)




Figure 1 Antenna Location Diagram



2450 MHz 802.11g/n OFDM configurations met the test exclusion requirements of KDB 248227 D01 section 5.2.2 as the highest reported SAR for DSSS was adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR was ≤ 1.2 W/kg.

For the 5GHz frequency bands the transmission mode used for testing was determined by the 802.11 configuration with the highest declared output power in each frequency band. Where multiple 802.11 configurations have the same specified output power, testing was performed using the mode with the largest channel bandwidth with the lowest order modulation and lowest data rate.

The U-NII-1 Band was not tested as this met the test exclusion requirements of KDB 248227 D01 section 5.3.1.

For SAR assessment, the relevant surfaces of the device were placed against an Elliptical phantom with a 0mm separation distance.

The Elliptical Flat Phantom dimensions are 600mm major axis and 400mm minor axis with a shell thickness of 2mm. The phantom was filled to a minimum depth of 150mm with the appropriate body simulant liquid. The dielectric properties were measured and found to be in accordance with the requirements specified in KDB 865665.

Included in this report are descriptions of the test method; the equipment used and an analysis of the test uncertainties applicable and diagrams indicating the locations of maximum SAR for each test position along with photographs indicating the positioning of the EUT against the elliptical phantom as appropriate.

1.4.8 Deviations from Standard

Initially, area scans were completed covering the whole of the bottom surface of the EUT to determine that there were no other RF radiators (unintentional) other than the antennas. The actual SAR measurements were completed using smaller area scans covering the antenna locations only.



1.5 POWER TABLES (TUNE UP VALUES)

Note: Power levels highlighted in blue apply to ISED only and values highlighted in green apply to FCC only. All other values are universal.

All levels in dBm

Bluetooth – FCC and ISED

Band	Configuration	Channel	BDR	EDR	LE/LE2M	HDR4/HDR8
2.4GHz	iPA	All	12.00	10.00	6.00	4.50
	ePa		16.50	16.50	N/A	10.00

WLAN – FCC and ISED

Band	Channel	Center Frequency (MHz)	802.11b (SISO)	802.11g (SISO)	802.11n HT20 (SISO)	802.11n HT20 (2 Tx, DSSS)	802.11n HT20 (2 Tx, non-TXBF)	802.11n HT20 (2 Tx, TXBF)
2.4GHz	1	2412	20.00	15.00	15.00	19.00	14.00	12.00
2.4GHz	2	2417	20.00	18.50	18.50	20.00	17.50	15.50
2.4GHz	3	2422	20.00	19.25	19.25	20.00	18.50	16.50
2.4GHz	4	2427	20.00	20.00	20.00	20.00	19.50	17.50
2.4GHz	5	2432	20.00	20.00	20.00	20.00	20.00	18.00
2.4GHz	6	2437	20.00	20.00	20.00	20.00	20.00	19.00
2.4GHz	7	2442	20.00	20.00	20.00	20.00	19.75	17.75
2.4GHz	8	2447	20.00	20.00	20.00	20.00	18.50	16.50
2.4GHz	9	2452	20.00	18.25	18.25	20.00	17.50	15.50
2.4GHz	10	2457	20.00	17.50	17.50	19.00	16.00	14.00
2.4GHz	11	2462	19.00	13.50	13.50	18.00	12.00	10.00
2.4GHz	12	2467	16.00	11.50	11.50	14.00	9.50	7.50
2.4GHz	13	2472	13.00	2.00	2.00	12.50	-0.50	-2.50



Band	Channel	Center Frequency (MHz)	802.11a (SISO)		802.11n HT20 (SISO)		802.11n HT20 (2 Tx CDD, non-TXBF)		802.11n HT20 (2 Tx SDM, non-TXBF)		802.11n HT20 (2 Tx, TXBF)	
			15.25	15.00	15.25	15.00	15.25	9.50	15.25	12.50	13.50	9.50
U-NII-1	36	5180	15.25	15.00	15.25	15.00	15.25	9.50	15.25	12.50	13.50	9.50
U-NII-1	40	5200	15.25	15.00	15.25	15.00	15.25	9.50	15.25	12.50	15.25	9.50
U-NII-1	44	5220	15.25	15.00	15.25	15.00	15.25	9.50	15.25	12.50	15.25	9.50
U-NII-1	48	5240	15.25	15.00	15.25	15.00	15.25	9.50	15.25	12.50	15.25	9.50
U-NII-2A	52	5260	15.50		15.50		15.50		15.50		15.50	
U-NII-2A	56	5280	15.50		15.50		15.50		15.50		15.50	
U-NII-2A	60	5300	15.50		15.50		15.50		15.50		15.50	
U-NII-2A	64	5320	15.50		15.50		15.50		15.50		13.50	
U-NII-2C	100	5500	14.50		14.50		14.50		14.50		13.50	
U-NII-2C	104	5520	14.50		14.50		14.50		14.50		14.50	
U-NII-2C	108	5540	14.50		14.50		14.50		14.50		14.50	
U-NII-2C	112	5560	14.50		14.50		14.50		14.50		14.50	
U-NII-2C	116	5580	14.50		14.50		14.50		14.50		14.50	
U-NII-2C	120	5600	14.50		14.50		14.50		14.50		14.50	
U-NII-2C	124	5620	14.50		14.50		14.50		14.50		14.50	
U-NII-2C	128	5640	14.50		14.50		14.50		14.50		14.50	
U-NII-2C	132	5660	14.50		14.50		14.50		14.50		14.50	
U-NII-2C	136	5680	14.50		14.50		14.50		14.50		14.50	
U-NII-2C	140	5700	14.50		14.50		14.50		14.50		14.50	
U-NII-2C	144	5720	14.50		14.50		14.50		14.50		14.50	
U-NII-3	149	5745	13.50		13.50		13.50		13.50		13.50	
U-NII-3	153	5765	13.50		13.50		13.50		13.50		13.50	
U-NII-3	157	5785	13.50		13.50		13.50		13.50		13.50	
U-NII-3	161	5805	13.50		13.50		13.50		13.50		13.50	
U-NII-3	165	5825	13.50		13.50		13.50		13.50		13.50	



Band	Channel	Center Frequency (MHz)	802.11n HT40 (1 Tx)	802.11n HT40 (2 Tx CDD, non-TXBF)		802.11n HT40 (2 Tx SDM, non-TXBF)	802.11n HT40 (2 Tx, TXBF)	
U-NII-1	38	5190	15.25	14.50	12.50	14.50	12.50	
U-NII-1	46	5230	15.25	15.25	12.50	15.25	15.25	12.50
U-NII-2A	54	5270	15.50	15.50		15.50	15.50	
U-NII-2A	62	5310	15.50	14.75		14.75	12.75	
U-NII-2C	102	5510	14.50	14.50		14.50	13.00	
U-NII-2C	110	5550	14.50	14.50		14.50	14.50	
U-NII-2C	118	5590	14.50	14.50		14.50	14.50	
U-NII-2C	126	5630	14.50	14.50		14.50	14.50	
U-NII-2C	134	5670	14.50	14.50		14.50	14.50	
U-NII-2C	142	5710	14.50	14.50		14.50	14.50	
U-NII-3	151	5755	13.50	13.50		13.50	13.50	
U-NII-3	159	5795	13.50	13.50		13.50	13.50	

Band	Channel	Center Frequency (MHz)	802.11ac VHT80 (1 Tx)	802.11ac VHT80 (2 Tx CDD, non-TXBF)	802.11ac VHT80 (2 Tx SDM, non-TXBF)	802.11ac VHT80 (2 Tx, TXBF)
U-NII-1	42	5210	15.00	14.00	14.00	12.00
U-NII-2A	58	5290	15.25	14.25	14.50	12.25
U-NII-2C	106	5530	14.50	14.50	14.50	12.75
U-NII-2C	122	5610	14.50	14.50	14.50	14.50
U-NII-2C	138	5690	14.50	14.50	14.50	14.50
U-NII-3	155	5775	13.50	13.50	13.50	13.50



1.6 POWER MEASUREMENTS

1.6.1 Method

Conducted power measurements were performed with a power meter.

Bluetooth- BDR – Antenna WF1

Technology	Channel	Modulation	Duty Cycle (%)	Packet Type	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
BDR	0	GFSK	77.0	DH5	2402	16.0	16.5
BDR	39	GFSK	77.0	DH5	2441	15.8	16.5
BDR	78	GFSK	77.0	DH5	2480	16.1	16.5

Technology	Channel	Modulation	Duty Cycle (%)	Packet Type	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
EDR	0	PSK	77.0	3-DH5	2402	16.0	16.5
EDR	39	PSK	77.0	3-DH5	2441	15.6	16.5
EDR	78	PSK	77.0	3-DH5	2480	15.6	16.5

WLAN 2450 MHz SISO Antenna WF1

Technology	Channel	Modulation	Duty Cycle (%)	Rate (Mbps)	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
802.11b	1	BPSK	100	1	2412	19.5	20.0
802.11b	6	BPSK	100	1	2437	19.5	20.0
802.11b	10	BPSK	100	1	2457	19.6	20.0
802.11b	11	BPSK	100	1	2462	18.4	19.0

- Top Channel , has lower declared power,hence measurement performed on adjacent channel.
- Power measurements were not performed for OFDM modes OFDM configurations met the test exclusion requirements of KDB 248227 D01 section 5.2.2



WLAN 2450 MHz SISO Antenna WF2

Technology	Channel	Modulation	Duty Cycle (%)	Rate (Mbps)	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
802.11b	1	BPSK	100	1	2412	19.5	20.0
802.11b	6	BPSK	100	1	2437	19.6	20.0
802.11b	10	BPSK	100	1	2457	19.5	20.0
802.11b	11	BPSK	100	1	2462	18.4	19.0

- Top Channel , has lower declared power,hence measurement performed on adjacent channel.
- Power measurements were not performed for OFDM modes as OFDM configurations met the test exclusion requirements of KDB 248227 D01 section 5.2.2

WLAN 2450 MHz 2x2 MIMO - Antenna WF1 and Antenna WF2

Core0

Technology	Channel	Modulation	Duty Cycle (%)	Rate (Mbps)	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
802.11b	1	BPSK	100	1	2412	18.4	19.0
802.11b	2	BPSK	100	1	2417	19.4	20.0
802.11b	6	BPSK	100	1	2437	19.5	20.0
802.11b	9	BPSK	100	1	2452	19.4	20.0
802.11b	10	BPSK	100	1	2457	18.6	19.0
802.11b	11	BPSK	100	1	2462	17.5	18.0

Core1

Technology	Channel	Modulation	Duty Cycle (%)	Rate (Mbps)	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
802.11b	1	BPSK	100	1	2412	18.5	19.0
802.11b	2	BPSK	100	1	2417	19.5	20.0
802.11b	6	BPSK	100	1	2437	19.4	20.0
802.11b	9	BPSK	100	1	2452	19.5	20.0
802.11b	10	BPSK	100	1	2457	18.5	19.0
802.11b	11	BPSK	100	1	2462	17.5	18.0



WLAN U-NII 2A SISO Antenna WF1

Technology	Channel	Modulation	Duty Cycle (%)	Rate (Mbps)	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
802.11n HT40	54	BPSK	100	13.5	5270	15.0	15.5
802.11n HT40	62	BPSK	100	13.5	5310	15.0	15.5

WLAN U-NII 2A SISO Antenna WF2

Technology	Channel	Modulation	Duty Cycle (%)	Rate (Mbps)	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
802.11n HT40	54	BPSK	100	13.5	5270	14.9	15.5
802.11n HT40	62	BPSK	100	13.5	5310	14.9	15.5

WLAN U-NII 2A 2x2 MIMO - Antenna WF1 and Antenna WF2

Antenna WF1

Technology	Channel	Modulation	Duty Cycle (%)	Rate (Mbps)	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
802.11n HT40	54	BPSK	100	13.5	5270	15.0	15.5
802.11n HT40	62	BPSK	100	13.5	5310	14.1	14.75

Antenna WF2

Technology	Channel	Modulation	Duty Cycle (%)	Rate (Mbps)	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
802.11n HT40	54	BPSK	100	13.5	5270	14.9	15.5
802.11n HT40	62	BPSK	100	13.5	5310	14.2	14.75



WLAN U-NII 2C SISO Antenna WF1

Technology	Channel	Modulation	Duty Cycle (%)	Rate (Mbps)	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
802.11ac VHT80	106	BPSK	100	29.3	5530	14.0	14.5
802.11ac VHT80	122	BPSK	100	29.3	5610	13.9	14.5
802.11ac VHT80	138	BPSK	100	29.3	5690	14.0	14.5

WLAN U-NII 2C SISO Antenna WF2

Technology	Channel	Modulation	Duty Cycle (%)	Rate (Mbps)	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
802.11ac VHT80	106	BPSK	100	29.3	5530	13.9	14.5
802.11ac VHT80	122	BPSK	100	29.3	5610	14.0	14.5
802.11ac VHT80	138	BPSK	100	29.3	5690	14.0	14.5

WLAN U-NII 2C 2x2 MIMO - Antenna WF1 and Antenna WF2

Antenna WF1

Technology	Channel	Modulation	Duty Cycle (%)	Rate (Mbps)	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
802.11ac VHT80	106	BPSK	100	29.3	5530	13.9	14.5
802.11ac VHT80	122	BPSK	100	29.3	5610	14.1	14.5
802.11ac VHT80	138	BPSK	100	29.3	5690	14.1	14.5

Antenna WF2

Technology	Channel	Modulation	Duty Cycle (%)	Rate (Mbps)	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
802.11ac VHT80	106	BPSK	100	29.3	5530	13.9	14.5
802.11ac VHT80	122	BPSK	100	29.3	5610	14.1	14.5



WLAN U-NII 3 SISO Antenna WF1

Technology	Channel	Modulation	Duty Cycle (%)	Rate (Mbps)	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
802.11ac VHT80	155	BPSK	100	29.3	5775	12.9	13.5

WLAN U-NII 3 SISO Antenna WF2

Technology	Channel	Modulation	Duty Cycle (%)	Rate (Mbps)	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
802.11ac VHT80	155	BPSK	100	29.3	5775	13.1	13.5

WLAN U-NII 3 2x2 MIMO - Antenna WF1 and Antenna WF2

Antenna WF1

Technology	Channel	Modulation	Duty Cycle (%)	Rate (Mbps)	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
802.11ac VHT80	155	BPSK	100	29.3	5775	13.1	13.5

Antenna WF2

Technology	Channel	Modulation	Duty Cycle (%)	Rate (Mbps)	Frequency (MHz)	Measured Power (dBm)	Tune Up (dBm)
802.11ac VHT80	155	BPSK	100	29.3	5775	13.0	13.5



SECTION 2

TEST DETAILS

Specific Absorption Rate Testing of the
A2179



2.1 DASY5 MEASUREMENT SYSTEM

2.1.1 System Description

The DASY5 system for performing compliance tests consists of the following items:




Figure 2 System Description Diagram

A standard high precision 6-axis robot (Stäubli TX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).

An isotropic field probe optimized and calibrated for the targeted measurement.

A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.

The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.

The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.

A computer running the DASY5 software.

Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.

The phantom, the device holder and other accessories according to the targeted measurement.



2.1.2 Probe Specification

The probes used by the DASY system are isotropic E-field probes, constructed with a symmetric design and a triangular core. The probes have built-in shielding against static charges and are contained within a PEEK enclosure material. These probes are specially designed and calibrated for use in liquids with high permittivities. The frequency range of the probes are from 6 MHz to 6 GHz.

2.1.3 Data Acquisition Electronics

The data acquisition electronics (DAE4 or DAE3) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of both the DAE4 as well as of the DAE3 box is 200M Ω ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

2.1.4 SAR Evaluation Description

The DASY5 software includes all numerical procedures necessary to evaluate the spatial peak SAR values.

Based on the IEEE 1528 standard, a new algorithm has been implemented. The spatial-peak SAR can be computed over any required mass.

The base for the evaluation is a "cube" measurement in a volume of 30mm³ (7x7x7 points). The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the centre of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan. If the 10g cube or both cubes are not entirely inside the measured volumes, the system issues a warning regarding the evaluated spatial peak values within the Post processing engine (SEMCAD X). This means that if the measured volume is shifted, higher values might be possible. To get the correct values you can use a finer measurement grid for the area scan. In complicated field distributions, a large grid spacing for the area scan might miss some details and give an incorrectly interpolated peak location.

The entire evaluation of the spatial peak values is performed within the Post-processing engine (SEMCAD X). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

1. extraction of the measured data (grid and values) from the Zoom Scan
2. calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
3. generation of a high-resolution mesh within the measured volume
4. interpolation of all measured values from the measurement grid to the high-resolution grid
5. extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
6. calculation of the averaged SAR within masses of 1g and 10g



2.1.5 Interpolation, Extrapolation and Detection of Maxima

The probe is calibrated at the centre of the dipole sensors which is located 1 to 2.7mm away from the probe tip. During measurements, the probe stops shortly above the phantom surface, depending on the probe and the surface detecting system. Both distances are included as parameters in the probe configuration file. The software always knows exactly how far away the measured point is from the surface. As the probe cannot directly measure at the surface, the values between the deepest measured point and the surface must be extrapolated.

In DASYS, the choice of the coordinate system defining the location of the measurement points has no influence on the uncertainty of the interpolation, Maxima Search and extrapolation routines. The interpolation, extrapolation and maximum search routines are all based on the modified Quadratic Shepard's method. Thereby, the interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation. The DASYS routines construct a once-continuously differentiable function that interpolates the measurement values as follows:

For each measurement point a trivariate (3-D) / bivariate (2-D) quadratic is computed. It interpolates the measurement values at the data point and forms a least-square fit to neighbouring measurement values. The spatial location of the quadratic with respect to the measurement values is attenuated by an inverse distance weighting. This is performed since the calculated quadratic will fit measurement values at nearby points more accurately than at points located further away.

After the quadratics are calculated for all measurement points, the interpolating function is calculated as a weighted average of the quadratics.

There are two control parameters that govern the behaviour of the interpolation method. One specifies the number of measurement points to be used in computing the least-square fits for the local quadratics. These measurement points are the ones nearest the input point for which the quadratic is being computed. The second parameter specifies the number of measurement points that will be used in calculating the weights for the quadratics to produce the final function. The input data points used there are the ones nearest the point at which the interpolation is desired. Appropriate defaults are chosen for each of the control parameters.

The trivariate quadratics that have been previously computed for the 3-D interpolation and whose input data are at the closest distance from the phantom surface, are used in order to extrapolate the fields to the surface of the phantom.

In order to determine all the field maxima in 2-D (Area Scan) and 3-D (Zoom Scan), the measurement grid is refined by a default factor of 10 and the interpolation function is used to evaluate all field values between corresponding measurement points. Subsequently, a linear search is applied to find all the candidate maxima. In a last step, non-physical maxima are removed and only those maxima which are within 2 dB of the global maximum value are retained.

In the Area Scan, the gradient of the interpolation function is evaluated to find all the extrema of the SAR distribution. The uncertainty on the locations of the extrema is less than 1/20 of the grid size. Only local maxima within 2 dB of the global maximum are searched and passed for the Zoom Scan measurement.

In the Zoom Scan, the interpolation function is used to extrapolate the Peak SAR from the lowest measurement points to the inner phantom surface (the extrapolation distance). The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1g and 10g cubes, the extrapolation distance should not be larger than 5mm.



2.1.6 Averaging and Determination of Spatial Peak SAR

The interpolated data is used to average the SAR over the 1g and 10g cubes by spatially discretising the entire measured volume. The resolution of this spatial grid used to calculate the averaged SAR is 1mm or about 42875 interpolated points. The resulting volumes are defined as cubical volumes containing the appropriate tissue parameters that are centered at the location. The location is defined as the centre of the incremental volume (voxel).

The spatial-peak SAR must be evaluated in cubical volumes containing a mass that is within 5% of the required mass. The cubical volume centered at each location, as defined above, should be expanded in all directions until the desired value for the mass is reached, with no surface boundaries of the averaging volume extending beyond the outermost surface of the considered region. In addition, the cubical volume should not consist of more than 10% of air. If these conditions are not satisfied, then the centre of the averaging volume is moved to the next location. Otherwise, the exact size of the final sampling cube is found using an inverse polynomial approximation algorithm, leading to results with improved accuracy. If one boundary of the averaging volume reaches the boundary of the measured volume during its expansion, it will not be evaluated at all. Reference is kept of all locations used and those not used for averaging the SAR. All average SAR values are finally assigned to the centered location in each valid averaging volume.

All locations included in an averaging volume are marked to indicate that they have been used at least once. If a location has been marked as used but has never been assigned to the centre of a cube, the highest averaged SAR value of all other cubical volumes which have used this location for averaging is assigned to this location. Only those locations that are not part of any valid averaging volume should be marked as unused. For the case of an unused location, a new averaging volume must be constructed which will have the unused location centered at one surface of the cube. The remaining five surfaces are expanded evenly in all directions until the required mass is enclosed, regardless of the amount of included air. Of the six possible cubes with one surface centered on the unused location, the smallest cube is used, which still contains the required mass.

If the final cube containing the highest averaged SAR touches the surface of the measured volume, an appropriate warning is issued within the Post-processing engine.



2.2 BLUETOOTH 2450 MHz BODY SAR TEST RESULTS

SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.0 °C
DATE:	02/12/2019	RELATIVE HUMIDITY:	25.9 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	2.042 S/m
DUT CONFIGURATION:	Bluetooth - BDR - DH5 - Antenna WF1	RELATIVE PERMITTIVITY:	51.654
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	20.5 °C
RAT:	Bluetooth	SCAN TYPE:	Full
FREQUENCY:	2480 MHz	DRIFT:	-0.16 dB
MODULATION:	GFSK	PEAK SAR:	0.44 W/kg
DUTY CYCLE:	77 %	SAR (1g):	0.20 W/kg




Figure 3: SAR Body Testing Results for the A2179 at 2480 MHz.

SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.0 °C
DATE:	02/12/2019	RELATIVE HUMIDITY:	25.9 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	2.042 S/m
DUT CONFIGURATION:	Bluetooth - BDR - DH5 - Antenna WF1	RELATIVE PERMITTIVITY:	51.654
DUT POSITION:	0mm - Rear Of Display	LIQUID TEMPERATURE:	20.5 °C
RAT:	Bluetooth	SCAN TYPE:	Full
FREQUENCY:	2480 MHz	DRIFT:	-0.09 dB
MODULATION:	GFSK	PEAK SAR:	0.06 W/kg
DUTY CYCLE:	77 %	SAR (1g):	0.03 W/kg




Figure 4: SAR Body Testing Results for the A2179 at 2480 MHz.



2.3 WLAN 2450 MHz BODY SAR TEST RESULTS




Figure 5: SAR Body Testing Results for the A2179 at 2457 MHz.




Figure 6: SAR Body Testing Results for the A2179 at 2457 MHz.



SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.5 °C
DATE:	25/11/2019	RELATIVE HUMIDITY:	37.7 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	2.023 S/m
DUT CONFIGURATION:	802.11b 20 MHz 1Mbps - SISO Antenna WF1	RELATIVE PERMITTIVITY:	52.97
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	20.9 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	2437 MHz	DRIFT:	0.04 dB
MODULATION:	BPSK	PEAK SAR:	1.58 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.75 W/kg




Figure 7: SAR Body Testing Results for the A2179 at 2437 MHz.

SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.5 °C
DATE:	22/11/2019	RELATIVE HUMIDITY:	37.7 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	2.049 S/m
DUT CONFIGURATION:	802.11b 20 MHz 1Mbps - SISO Antenna WF1	RELATIVE PERMITTIVITY:	52.552
DUT POSITION:	0mm - Rear Of Display	LIQUID TEMPERATURE:	20.9 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	2437 MHz	DRIFT:	-0.05 dB
MODULATION:	BPSK	PEAK SAR:	0.24 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.12 W/kg




Figure 8: SAR Body Testing Results for the A2179 at 2437 MHz.



SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.5 °C
DATE:	22/11/2019	RELATIVE HUMIDITY:	37.7 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	2.049 S/m
DUT CONFIGURATION:	802.11b 20 MHz 1Mbps - MIMO Antenna WF1 & 1	RELATIVE PERMITTIVITY:	52.552
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	20.9 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	2437 MHz	DRIFT:	-0.17 dB
MODULATION:	BPSK	PEAK SAR:	1.60 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.80 W/kg




Figure 9: SAR Body Testing Results for the A2179 at 2437 MHz.



2.4 WLAN U-NII 2A BODY SAR TEST RESULTS




Figure 10: SAR Body Testing Results for the A2179 at 5310 MHz.




Figure 11: SAR Body Testing Results for the A2179 at 5310 MHz.



SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	23.6 °C
DATE:	23/11/2019	RELATIVE HUMIDITY:	33.1 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	5.507 S/m
DUT CONFIGURATION:	802.11n 40 MHz 13.5 Mbps - SISO Antenna WF2	RELATIVE PERMITTIVITY:	47.249
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	21.4 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5270 MHz	DRIFT:	0.05 dB
MODULATION:	MCS0	PEAK SAR:	2.99 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.99 W/kg




Figure 12: SAR Body Testing Results for the A2179 at 5270 MHz.

SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	23.6 °C
DATE:	23/11/2019	RELATIVE HUMIDITY:	33.1 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	5.507 S/m
DUT CONFIGURATION:	802.11n 40 MHz 13.5 Mbps - SISO Antenna WF2	RELATIVE PERMITTIVITY:	47.249
DUT POSITION:	0mm - Rear Of Display	LIQUID TEMPERATURE:	21.4 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5270 MHz	DRIFT:	0.14 dB
MODULATION:	MCS0	PEAK SAR:	0.63 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.21 W/kg




Figure 13: SAR Body Testing Results for the A2179 at 5270 MHz.



SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	23.6 °C
DATE:	23/11/2019	RELATIVE HUMIDITY:	33.1 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	5.562 S/m
DUT CONFIGURATION:	802.11n 40 MHz 13.5 Mbps - SISO Antenna WF2	RELATIVE PERMITTIVITY:	47.166
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	21.4 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5310 MHz	DRIFT:	-0.02 dB
MODULATION:	MCS0	PEAK SAR:	3.27 W/kg
DUTY CYCLE:	100 %	SAR (1g):	1.09 W/kg




Figure 14: SAR Body Testing Results for the A2179 at 5310 MHz.

SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	23.6 °C
DATE:	23/11/2019	RELATIVE HUMIDITY:	33.1 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	5.507 S/m
DUT CONFIGURATION:	802.11n 40 MHz 13.5 Mbps - MIMO Antenna WF1 & 1	RELATIVE PERMITTIVITY:	47.249
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	21.4 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5270 MHz	DRIFT:	-0.07 dB
MODULATION:	MCS0	PEAK SAR:	2.03 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.90 W/kg




Figure 15: SAR Body Testing Results for the A2179 at 5270 MHz.



SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	23.6 °C
DATE:	23/11/2019	RELATIVE HUMIDITY:	33.1 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	5.562 S/m
DUT CONFIGURATION:	802.11n 40 MHz 13.5 Mbps - MIMO Antenna WF1 & 1	RELATIVE PERMITTIVITY:	47.166
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	21.4 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5310 MHz	DRIFT:	-0.06 dB
MODULATION:	MCS0	PEAK SAR:	1.30 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.68 W/kg




Figure 16: SAR Body Testing Results for the A2179 at 5310 MHz.



2.5 WLAN U-NII 2C BODY SAR TEST RESULTS

SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.3 °C
DATE:	23/11/2019	RELATIVE HUMIDITY:	41.2 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	6.051 S/m
DUT CONFIGURATION:	802.11ac 80 MHz 29.3 Mbps - SISO Antenna WF1	RELATIVE PERMITTIVITY:	46.967
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	23.7 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5690 MHz	DRIFT:	0.03 dB
MODULATION:	MCS0	PEAK SAR:	2.69 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.81 W/kg




Figure 17: SAR Body Testing Results for the A2179 at 5690 MHz.

SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.3 °C
DATE:	23/11/2019	RELATIVE HUMIDITY:	45.2 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	6.051 S/m
DUT CONFIGURATION:	802.11ac 80 MHz 29.3 Mbps - SISO Antenna WF1	RELATIVE PERMITTIVITY:	46.967
DUT POSITION:	0mm - Rear Of Display	LIQUID TEMPERATURE:	23.7 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5690 MHz	DRIFT:	-0.04 dB
MODULATION:	MCS0	PEAK SAR:	0.81 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.24 W/kg




Figure 18: SAR Body Testing Results for the A2179 at 5690 MHz.



SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.3 °C
DATE:	23/11/2019	RELATIVE HUMIDITY:	45.2 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	5.821 S/m
DUT CONFIGURATION:	802.11ac 80 MHz 29.3 Mbps - SISO Antenna WF1	RELATIVE PERMITTIVITY:	47.26
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	23.7 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5530 MHz	DRIFT:	-0.14 dB
MODULATION:	MCS0	PEAK SAR:	2.21 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.69 W/kg




Figure 19: SAR Body Testing Results for the A2179 at 5530 MHz.

SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.3 °C
DATE:	23/11/2019	RELATIVE HUMIDITY:	45.2 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	5.935 S/m
DUT CONFIGURATION:	802.11ac 80 MHz 29.3 Mbps - SISO Antenna WF1	RELATIVE PERMITTIVITY:	47.112
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	23.7 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5610 MHz	DRIFT:	-0.14 dB
MODULATION:	MCS0	PEAK SAR:	2.43 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.75 W/kg




Figure 20: SAR Body Testing Results for the A2179 at 5610 MHz.



SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.3 °C
DATE:	23/11/2019	RELATIVE HUMIDITY:	45.2 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	5.935 S/m
DUT CONFIGURATION:	802.11ac 80 MHz 29.3 Mbps - SISO Antenna WF2	RELATIVE PERMITTIVITY:	47.112
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	23.7 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5610 MHz	DRIFT:	0.16 dB
MODULATION:	MCS0	PEAK SAR:	2.84 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.84 W/kg




Figure 21: SAR Body Testing Results for the A2179 at 5610 MHz.

SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.3 °C
DATE:	23/11/2019	RELATIVE HUMIDITY:	45.2 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	5.935 S/m
DUT CONFIGURATION:	802.11ac 80 MHz 29.3 Mbps - SISO Antenna WF2	RELATIVE PERMITTIVITY:	47.112
DUT POSITION:	0mm - Rear Of Display	LIQUID TEMPERATURE:	23.7 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5610 MHz	DRIFT:	0.01 dB
MODULATION:	MCS0	PEAK SAR:	0.63 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.19 W/kg




Figure 22: SAR Body Testing Results for the A2179 at 5610 MHz.



SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.3 °C
DATE:	23/11/2019	RELATIVE HUMIDITY:	45.2 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	6.051 S/m
DUT CONFIGURATION:	802.11ac 80 MHz 29.3 Mbps - SISO Antenna WF2	RELATIVE PERMITTIVITY:	46.967
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	23.7 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5690 MHz	DRIFT:	-0.07 dB
MODULATION:	MCS0	PEAK SAR:	3.24 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.94 W/kg




Figure 23: SAR Body Testing Results for the A2179 at 5690 MHz.

SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.2 °C
DATE:	25/11/2019	RELATIVE HUMIDITY:	42.8 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	5.821 S/m
DUT CONFIGURATION:	802.11ac 80 MHz 29.3 Mbps - SISO Antenna WF2	RELATIVE PERMITTIVITY:	47.26
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	22.28 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5530 MHz	DRIFT:	-0.02 dB
MODULATION:	MCS0	PEAK SAR:	2.96 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.92 W/kg




Figure 24: SAR Body Testing Results for the A2179 at 5530 MHz.



SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.3 °C
DATE:	23/11/2019	RELATIVE HUMIDITY:	45.2 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	5.935 S/m
DUT CONFIGURATION:	802.11ac 80 MHz 29.3 Mbps - MIMO Antenna WF1 & 1	RELATIVE PERMITTIVITY:	47.112
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	23.7 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5610 MHz	DRIFT:	-0.11 dB
MODULATION:	MCS0	PEAK SAR:	2.79 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.85 W/kg




Figure 25: SAR Body Testing Results for the A2179 at 5610 MHz.

SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.3 °C
DATE:	24/11/2019	RELATIVE HUMIDITY:	45.2 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	6.051 S/m
DUT CONFIGURATION:	802.11ac 80 MHz 29.3 Mbps - MIMO Antenna WF1 & 1	RELATIVE PERMITTIVITY:	46.967
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	23.7 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5690 MHz	DRIFT:	-0.07 dB
MODULATION:	MCS0	PEAK SAR:	2.63 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.75 W/kg




Figure 26: SAR Body Testing Results for the A2179 at 5690 MHz.



SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.3 °C
DATE:	24/11/2019	RELATIVE HUMIDITY:	45.2 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	5.821 S/m
DUT CONFIGURATION:	802.11ac 80 MHz 29.3 Mbps - MIMO Antenna WF1 & 1	RELATIVE PERMITTIVITY:	47.26
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	23.7 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5530 MHz	DRIFT:	-0.01 dB
MODULATION:	MCS0	PEAK SAR:	1.66 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.65 W/kg




Figure 27: SAR Body Testing Results for the A2179 at 5530 MHz.



2.6 WLAN U-NII 3 BODY SAR TEST RESULTS




Figure 28: SAR Body Testing Results for the A2179 at 5775 MHz.




Figure 29: SAR Body Testing Results for the A2179 at 5775 MHz.



SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.5 °C
DATE:	24/11/2019	RELATIVE HUMIDITY:	40.6 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	6.176 S/m
DUT CONFIGURATION:	802.11ac 80 MHz 29.3 Mbps - SISO Antenna WF2	RELATIVE PERMITTIVITY:	46.812
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	22.3 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5775 MHz	DRIFT:	-0.07 dB
MODULATION:	MCS0	PEAK SAR:	2.21 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.60 W/kg




Figure 30: SAR Body Testing Results for the A2179 at 5775 MHz.

SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.5 °C
DATE:	24/11/2019	RELATIVE HUMIDITY:	40.6 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	6.176 S/m
DUT CONFIGURATION:	802.11ac 80 MHz 29.3 Mbps - SISO Antenna WF2	RELATIVE PERMITTIVITY:	46.812
DUT POSITION:	0mm - Rear Of Display	LIQUID TEMPERATURE:	22.3 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5775 MHz	DRIFT:	0.05 dB
MODULATION:	MCS0	PEAK SAR:	0.53 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.14 W/kg




Figure 31: SAR Body Testing Results for the A2179 at 5775 MHz.



SOFTWARE VERSION:	52.10.2(1495)	AMBIENT TEMPERATURE:	22.5 °C
DATE:	24/11/2019	RELATIVE HUMIDITY:	40.6 %
PHANTOM:	QD OVA 004 Ax	CONDUCTIVITY:	6.176 S/m
DUT CONFIGURATION:	802.11ac 80 MHz 29.3 Mbps - MIMO Antenna WF1 & 1	RELATIVE PERMITTIVITY:	46.812
DUT POSITION:	0mm - Bottom	LIQUID TEMPERATURE:	22.3 °C
RAT:	WLAN	SCAN TYPE:	Full
FREQUENCY:	5775 MHz	DRIFT:	-0.08 dB
MODULATION:	MCS0	PEAK SAR:	1.78 W/kg
DUTY CYCLE:	100 %	SAR (1g):	0.49 W/kg




Figure 32: SAR Body Testing Results for the A2179 at 5775 MHz.



SECTION 3

TEST EQUIPMENT USED



3.1 TEST EQUIPMENT USED

The following test equipment was used at TÜV SÜD:

Instrument Description	Manufacturer	Model Type	TE Number	Cal Period (months)	Calibration Due Date
Thermometer	Digitron	T208	64	12	12-Jun-2020
Hygrometer	Rotronic	I-1000	3068	12	27-Jun-2020
Power Meter	Rohde & Schwarz	NRP	3491	12	11-Oct-2020
Wideband Power Sensor, 50MHz - 18GHz	Rohde & Schwarz	NRP-Z81	3492	12	11-Oct-2020
Attenuator (30dB, 25W)	Weinschel	46-30-34	2776	12	23-Jul-2020
Data Acquisition Electronics	Speag	DAE 4 - SD 000 D04 BN	5327	12	07-Jun-2020
Validation Dipole (5GHz)	Speag	D5GzV2	5328	12	07-Jun-2020
Validation Dipole (2450MHz)	Speag	D2450V2	5329	12	07-Jun-2020
Dosimetric SAR Probe	Speag	EX3DV4	5330	12	07-Jun-2020
Body Phantom	Speag	Oval Flat Phantom ELI v8.0	5333	-	TU
Device Holder	Speag	MD4HHTV5	5335	-	TU
Measurement server	Speag	DASY 6 Measurement Server	5337	-	TU
Robot	Staubli	TX90 XLRobot	5340	-	TU
RF power source	Speag	POWERSOURCE1-SE UMS 160 BA	5371	12	12-Sept-2020
MBBL Fluid	Speag	Batch 3	N/A	Weekly	09-Dec-2019

TU - Traceability Unscheduled



3.2 TEST SOFTWARE

The following software was used to control the TÜV SÜD DASYS Systems.

Instrument	Version Number
DASY system	52.10.2(1495)



3.3 DIELECTRIC PROPERTIES OF SIMULANT LIQUIDS

The fluid properties of the simulant fluids used during routine SAR evaluation meet the dielectric properties required KDB 865665.

The dielectric properties of the tissue simulant liquids used for the SAR testing at TÜV SÜD are as follows:

Fluid Type and Frequency	Relative Permittivity Target (ϵ_r)	Relative Permittivity Measured (ϵ_r)	Conductivity Target (S/m)	Conductivity Measured (S/m)	Date	Fluid Temperature °C
MBBL @ 2450 MHz	52.70	52.53	1.95	2.06	22-11-2019	21.7
MBBL @ 5200 MHz	49.01	47.40	5.30	5.41	22-11-2019	21.7
MBBL @ 5300 MHz	48.88	47.19	5.41	5.55	22-11-2019	21.7
MBBL @ 5500 MHz	48.61	46.78	5.65	5.83	22-11-2019	21.7
MBBL @ 5600 MHz	48.47	46.59	5.77	5.98	22-11-2019	21.7
MBBL @ 5800 MHz	48.20	46.22	6.00	6.27	22-11-2019	21.7
MBBL @ 2450 MHz	52.70	52.62	1.95	2.03	23-11-2019	21.7
MBBL @ 5200 MHz	49.01	47.52	5.30	5.38	23-11-20-9	21.7
MBBL @ 5300 MHz	48.88	47.31	5.41	5.52	23-11-2019	21.7
MBBL @ 5500 MHz	48.61	46.90	5.65	5.80	23-11-2019	21.7
MBBL @ 5600 MHz	48.47	46.72	5.77	5.94	23-11-2019	21.7
MBBL @ 5800 MHz	48.20	46.71	6.00	5.95	23-11-2019	21.7
MBBL @ 2450 MHz	52.70	53.13	1.95	2.03	27-11-2019	21.5
MBBL @ 5200 MHz	49.01	47.93	5.30	5.36	27-11-2019	21.5
MBBL @ 5300 MHz	48.88	47.72	5.41	5.50	27-11-2019	21.5
MBBL @ 5500 MHz	48.61	47.32	5.65	5.78	27-11-2019	21.5
MBBL @ 5600 MHz	48.47	47.12	5.77	5.93	27-11-2019	21.5
MBBL @ 5800 MHz	48.20	46.73	6.00	6.21	27-11-2019	21.5



3.4 TEST CONDITIONS

3.4.1 Test Laboratory Conditions

Ambient temperature: Within +15°C to +35°C.
 The actual temperature during the testing ranged from 22.0°C to 24.3°C.
 The actual humidity during the testing ranged from 25.9% to 43.1% RH.

3.4.2 Test Fluid Temperature Range

Frequency	Fluid Type	Min Temperature °C	Max Temperature °C
2402 - 2480 MHz	MBBL	20.5	20.9
5180 - 5320 MHz	MBBL	21.4	21.4
5500 - 5720 MHz	MBBL	21.3	22.3
5745 - 5825 MHz	MBBL	22.3	22.3

3.4.3 SAR Drift

The SAR Drift was within acceptable limits during scans. The maximum SAR Drift was recorded as 0.19 dB



3.5 MEASUREMENT UNCERTAINTY

Full SAR Measurements, 300 MHz to 3 GHz

Source of Uncertainty	Uncertainty \pm %	Probability distribution	Div	c_i (1g)	Standard Uncertainty \pm % (1g)	V_i (V_{eff})
Measurement System						
Probe calibration	6.0	N	1.00	1.00	6.0	Infinity
Axial Isotropy	4.7	R	1.73	0.70	1.9	Infinity
Hemispherical Isotropy	9.6	R	1.73	0.70	3.9	Infinity
Boundary effect	1.0	R	1.73	1.00	0.6	Infinity
Linearity	4.7	R	1.73	1.00	2.7	Infinity
System Detection limits	1.0	R	1.73	1.00	0.6	Infinity
Modulation response	2.4	R	1.73	1.00	1.4	Infinity
Readout electronics	0.3	N	1.00	1.00	0.3	Infinity
Response time	0.8	R	1.73	1.00	0.5	Infinity
Integration time	2.6	R	1.73	1.00	1.5	Infinity
RF ambient noise	3.0	R	1.73	1.00	1.7	Infinity
RF ambient reflections	3.0	R	1.73	1.00	1.7	Infinity
Probe positioner	0.4	R	1.73	1.00	0.2	Infinity
Probe positioning	2.9	R	1.73	1.00	1.7	Infinity
Max SAR Evaluation	2.0	R	1.73	1.00	1.2	Infinity
Test sample related						
Device Positioning	2.9	N	1.00	1.00	2.9	145
Device Holder	3.6	N	1.00	1.00	3.6	5
Input Power and SAR Drift	5.0	R	1.73	1.00	2.9	Infinity
Phantom and Setup						
Phantom uncertainty	6.1	R	1.73	1.00	3.5	Infinity
SAR Correction	1.9	R	1.73	1.00	1.1	Infinity
Liquid conductivity Meas.	2.5	R	1.73	0.78	1.1	Infinity
Liquid Permittivity Meas.	2.5	R	1.73	0.23	0.3	Infinity
Temp. Unc. Conductivity	3.4	R	1.73	0.78	1.5	Infinity
Temp. Unc. Permittivity	0.4	R	1.73	0.23	0.1	Infinity
Combined Standard Uncertainty		RSS			11.1	361
Expanded Standard Uncertainty		K=2			22.2	



Full SAR Measurements, 3 GHz to 6 GHz

Source of Uncertainty	Uncertainty ± %	Probability distribution	Div	c _i (1g)	Standard Uncertainty ± % (1g)	v _i (V _{eff})
Measurement System						
Probe calibration	6.0	N	1.00	0.00	0.0	
Axial Isotropy	4.7	R	1.73	0.70	1.9	Infinity
Hemispherical Isotropy	9.6	R	1.73	0.70	3.9	Infinity
Boundary effect	1.0	R	1.73	1.00	0.6	Infinity
Linearity	4.7	R	1.73	1.00	2.7	Infinity
System Detection limits	1.0	R	1.73	1.00	0.6	Infinity
Modulation response	2.4	R	1.73	1.00	1.4	Infinity
Readout electronics	0.3	N	1.00	0.00	0.0	
Response time	0.8	R	1.73	0.00	0.0	
Integration time	2.6	R	1.73	1.00	1.5	Infinity
RF ambient noise	3.0	R	1.73	1.00	1.7	Infinity
RF ambient reflections	3.0	R	1.73	0.00	0.0	
Probe positioner	0.4	R	1.73	1.00	0.2	Infinity
Probe positioning	2.9	R	1.73	1.00	1.7	Infinity
Spatial x-y-Resolution	10.0	R	1.73	1.00	5.8	Infinity
Fast SAR z-Approximation	7.0	R	1.73	1.00	4.0	Infinity
Test sample related						
Device Positioning	2.9	N	1.00	1.00	2.9	145
Device Holder	3.6	N	1.00	1.00	3.6	5
Input Power and SAR Drift	5.0	R	1.73	1.00	2.9	Infinity
Phantom and Setup						
Phantom uncertainty	6.1	R	1.73	1.00	3.5	Infinity
SAR Correction	1.9	R	1.73	0.00	0.0	
Liquid conductivity Meas.	2.5	R	1.73	0.00	0.0	
Liquid Permittivity Meas.	2.5	R	1.73	0.00	0.0	
Temp. Unc. Conductivity	3.4	R	1.73	0.00	0.0	
Temp. Unc. Permittivity	0.4	R	1.73	0.00	0.0	
Combined Standard Uncertainty		RSS			12.2	
Expanded Standard Uncertainty		K=2			24.5	



SECTION 4

ACCREDITATION, DISCLAIMERS AND COPYRIGHT



4.1 ACCREDITATION, DISCLAIMERS AND COPYRIGHT



This report relates only to the actual item/items tested.

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation.

Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited).

This report must not be reproduced, except in its entirety, without the written permission of TÜV SÜD

© 2020 TÜV SÜD



ANNEX A

PROBE CALIBRATION REPORT



**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **TüV Süd UK**

Certificate No: **EX3-7536_Jun19**

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:7536**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-14.v5, QA CAL-23.v5, QA CAL-25.v7
Calibration procedure for dosimetric E-field probes**

Calibration date: **June 7, 2019**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	03-Apr-19 (No. 217-02892/02893)	Apr-20
Power sensor NRP-Z91	SN: 103244	03-Apr-19 (No. 217-02892)	Apr-20
Power sensor NRP-Z91	SN: 103245	03-Apr-19 (No. 217-02893)	Apr-20
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-19 (No. 217-02894)	Apr-20
DAE4	SN: 660	19-Dec-18 (No. DAE4-660_Dec18)	Dec-19
Reference Probe ES3DV2	SN: 3013	31-Dec-18 (No. ES3-3013_Dec18)	Dec-19
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-18)	In house check: Jun-20
Network Analyzer E8358A	SN: US41080477	31-Mar-14 (in house check Oct-18)	In house check: Oct-19

	Name	Function	Signature
Calibrated by:	Jeton Kastrati	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: June 12, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., ϑ = 0 is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- *NORM_{x,y,z}*: Assessed for E-field polarization ϑ = 0 (f ≤ 900 MHz in TEM-cell; f > 1800 MHz: R22 waveguide). *NORM_{x,y,z}* are only intermediate values, i.e., the uncertainties of *NORM_{x,y,z}* does not affect the E²-field uncertainty inside TSL (see below *ConvF*).
- *NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- *DCP_{x,y,z}*: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- *PAR*: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- *A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}*: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- *ConvF and Boundary Effect Parameters*: Assessed in flat phantom using E-field (or Temperature Transfer Standard for f ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to *NORM_{x,y,z} * ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- *Spherical isotropy (3D deviation from isotropy)*: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- *Sensor Offset*: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- *Connector Angle*: The angle is assessed using the information gained by determining the *NORM_x* (no uncertainty required).



EX3DV4 – SN:7536

June 7, 2019

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7536

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu V/(V/m)^2$) ^A	0.55	0.61	0.65	± 10.1 %
DCP (mV) ^B	95.4	98.2	102.0	

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB $\sqrt{\mu V}$	C	D dB	VR mV	Max dev.	Max Unc ^E (k=2)
0	CW	X	0.00	0.00	1.00	0.00	172.6	±3.5 %	± 4.7 %
		Y	0.00	0.00	1.00		188.0		
		Z	0.00	0.00	1.00		193.1		
10352-AAA	Pulse Waveform (200Hz, 10%)	X	15.00	89.69	20.89	10.00	60.0	± 3.9 %	± 9.6 %
		Y	15.00	88.32	19.87		60.0		
		Z	15.00	89.29	20.40		60.0		
10353-AAA	Pulse Waveform (200Hz, 20%)	X	15.00	92.02	21.04	6.99	80.0	± 2.2 %	± 9.6 %
		Y	15.00	90.27	19.63		80.0		
		Z	15.00	91.91	20.79		80.0		
10354-AAA	Pulse Waveform (200Hz, 40%)	X	15.00	97.33	22.29	3.98	95.0	± 1.1 %	± 9.6 %
		Y	15.00	94.70	20.25		95.0		
		Z	15.00	96.95	21.96		95.0		
10355-AAA	Pulse Waveform (200Hz, 60%)	X	15.00	105.37	24.66	2.22	120.0	± 1.1 %	± 9.6 %
		Y	15.00	94.51	18.63		120.0		
		Z	15.00	103.12	23.50		120.0		
10387-AAA	QPSK Waveform, 1 MHz	X	1.00	65.46	12.05	0.00	150.0	± 2.5 %	± 9.6 %
		Y	0.59	60.00	7.77		150.0		
		Z	0.79	62.56	10.15		150.0		
10388-AAA	QPSK Waveform, 10 MHz	X	2.56	70.23	16.97	0.00	150.0	± 1.2 %	± 9.6 %
		Y	2.01	66.26	14.66		150.0		
		Z	2.31	68.43	15.94		150.0		
10396-AAA	64-QAM Waveform, 100 kHz	X	3.26	71.76	19.45	3.01	150.0	± 1.3 %	± 9.6 %
		Y	2.54	67.60	17.57		150.0		
		Z	3.42	72.97	19.95		150.0		
10399-AAA	64-QAM Waveform, 40 MHz	X	3.70	68.00	16.39	0.00	150.0	± 2.0 %	± 9.6 %
		Y	3.37	66.26	15.26		150.0		
		Z	3.57	67.31	15.90		150.0		
10414-AAA	WLAN CCDF, 64-QAM, 40MHz	X	5.06	66.10	15.93	0.00	150.0	± 4.0 %	± 9.6 %
		Y	4.77	65.17	15.29		150.0		
		Z	4.94	65.75	15.63		150.0		

Note: For details on UID parameters see Appendix

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E²-field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



EX3DV4– SN:7536

June 7, 2019

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7536

Sensor Model Parameters

	C1 fF	C2 fF	α V ⁻¹	T1 ms.V ⁻²	T2 ms.V ⁻¹	T3 ms	T4 V ⁻²	T5 V ⁻¹	T6
X	53.2	403.81	36.76	16.78	0.22	5.10	0.79	0.43	1.01
Y	45.6	350.95	37.32	11.58	0.16	5.10	0.00	0.45	1.01
Z	49.8	374.34	35.95	16.56	0.05	5.10	1.65	0.25	1.01

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	74.1
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm



DASY/EASY - Parameters of Probe: EX3DV4 - SN:7536

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
2450	39.2	1.80	7.98	7.98	7.98	0.34	0.86	± 12.0 %
5200	36.0	4.66	5.56	5.56	5.56	0.40	1.80	± 13.1 %
5300	35.9	4.76	5.41	5.41	5.41	0.40	1.80	± 13.1 %
5500	35.6	4.96	4.95	4.95	4.95	0.40	1.80	± 13.1 %
5600	35.5	5.07	4.80	4.80	4.80	0.40	1.80	± 13.1 %
5800	35.3	5.27	4.90	4.90	4.90	0.40	1.80	± 13.1 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4-9 MHz, and ConvF assessed at 13 MHz is 9-19 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.



DASY/EASY - Parameters of Probe: EX3DV4 - SN:7536

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
2450	52.7	1.95	7.89	7.89	7.89	0.36	0.87	± 12.0 %
5200	49.0	5.30	5.02	5.02	5.02	0.50	1.90	± 13.1 %
5300	48.9	5.42	4.83	4.83	4.83	0.50	1.90	± 13.1 %
5500	48.6	5.65	4.64	4.64	4.64	0.50	1.90	± 13.1 %
5600	48.5	5.77	4.47	4.47	4.47	0.50	1.90	± 13.1 %
5800	48.2	6.00	4.40	4.40	4.40	0.50	1.90	± 13.1 %


^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4-9 MHz, and ConvF assessed at 13 MHz is 9-19 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.



Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)



Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz,TEM



f=1800 MHz,R22



Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ (k=2)



Dynamic Range f(SAR_{head}) (TEM cell , f_{eval}= 1900 MHz)




Uncertainty of Linearity Assessment: ± 0.6% (k=2)




EX3DV4- SN:7536

June 7, 2019

Conversion Factor Assessment



Deviation from Isotropy in Liquid Error (ϕ, ϑ), f = 900 MHz





EX3DV4- SN:7536

June 7, 2019

Appendix: Modulation Calibration Parameters

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E (k=2)
0		CW	CW	0.00	± 4.7 %
10010	CAA	SAR Validation (Square, 100ms, 10ms)	Test	10.00	± 9.6 %
10011	CAB	UMTS-FDD (WCDMA)	WCDMA	2.91	± 9.6 %
10012	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	WLAN	1.87	± 9.6 %
10013	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	WLAN	9.46	± 9.6 %
10021	DAC	GSM-FDD (TDMA, GMSK)	GSM	9.39	± 9.6 %
10023	DAC	GPRS-FDD (TDMA, GMSK, TN 0)	GSM	9.57	± 9.6 %
10024	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	GSM	6.56	± 9.6 %
10025	DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	GSM	12.62	± 9.6 %
10026	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	GSM	9.55	± 9.6 %
10027	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	GSM	4.80	± 9.6 %
10028	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	GSM	3.55	± 9.6 %
10029	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	GSM	7.78	± 9.6 %
10030	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH1)	Bluetooth	5.30	± 9.6 %
10031	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	Bluetooth	1.87	± 9.6 %
10032	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	Bluetooth	1.16	± 9.6 %
10033	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	Bluetooth	7.74	± 9.6 %
10034	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH3)	Bluetooth	4.53	± 9.6 %
10035	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)	Bluetooth	3.83	± 9.6 %
10036	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	Bluetooth	8.01	± 9.6 %
10037	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	Bluetooth	4.77	± 9.6 %
10038	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	Bluetooth	4.10	± 9.6 %
10039	CAB	CDMA2000 (1xRTT, RC1)	CDMA2000	4.57	± 9.6 %
10042	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Halfrate)	AMPS	7.78	± 9.6 %
10044	CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	AMPS	0.00	± 9.6 %
10048	CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	DECT	13.80	± 9.6 %
10049	CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	DECT	10.79	± 9.6 %
10056	CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	TD-SCDMA	11.01	± 9.6 %
10058	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	GSM	6.52	± 9.6 %
10059	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	WLAN	2.12	± 9.6 %
10060	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	WLAN	2.83	± 9.6 %
10061	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	WLAN	3.60	± 9.6 %
10062	CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)	WLAN	8.68	± 9.6 %
10063	CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)	WLAN	8.63	± 9.6 %
10064	CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)	WLAN	9.09	± 9.6 %
10065	CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)	WLAN	9.00	± 9.6 %
10066	CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	WLAN	9.38	± 9.6 %
10067	CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)	WLAN	10.12	± 9.6 %
10068	CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)	WLAN	10.24	± 9.6 %
10069	CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	WLAN	10.56	± 9.6 %
10071	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	WLAN	9.83	± 9.6 %
10072	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	WLAN	9.62	± 9.6 %
10073	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)	WLAN	9.94	± 9.6 %
10074	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)	WLAN	10.30	± 9.6 %
10075	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)	WLAN	10.77	± 9.6 %
10076	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)	WLAN	10.94	± 9.6 %
10077	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	WLAN	11.00	± 9.6 %
10081	CAB	CDMA2000 (1xRTT, RC3)	CDMA2000	3.97	± 9.6 %
10082	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Fullrate)	AMPS	4.77	± 9.6 %
10090	DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)	GSM	6.56	± 9.6 %
10097	CAB	UMTS-FDD (HSDPA)	WCDMA	3.98	± 9.6 %
10098	CAB	UMTS-FDD (HSUPA, Subtest 2)	WCDMA	3.98	± 9.6 %
10099	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-4)	GSM	9.55	± 9.6 %
10100	CAE	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	LTE-FDD	5.67	± 9.6 %
10101	CAE	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	LTE-FDD	6.42	± 9.6 %
10102	CAE	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	LTE-FDD	6.60	± 9.6 %
10103	CAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	LTE-TDD	9.29	± 9.6 %
10104	CAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	LTE-TDD	9.97	± 9.6 %
10105	CAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	LTE-TDD	10.01	± 9.6 %
10108	CAG	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-FDD	5.80	± 9.6 %



EX3DV4-- SN:7536

June 7, 2019

10109	CAG	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	LTE-FDD	6.43	± 9.6 %
10110	CAG	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	LTE-FDD	5.75	± 9.6 %
10111	CAG	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	LTE-FDD	6.44	± 9.6 %
10112	CAG	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	LTE-FDD	6.59	± 9.6 %
10113	CAG	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	LTE-FDD	6.62	± 9.6 %
10114	CAC	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	WLAN	8.10	± 9.6 %
10115	CAC	IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)	WLAN	8.46	± 9.6 %
10116	CAC	IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM)	WLAN	8.15	± 9.6 %
10117	CAC	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	WLAN	8.07	± 9.6 %
10118	CAC	IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)	WLAN	8.59	± 9.6 %
10119	CAC	IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)	WLAN	8.13	± 9.6 %
10140	CAE	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-FDD	6.49	± 9.6 %
10141	CAE	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	LTE-FDD	6.53	± 9.6 %
10142	CAE	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-FDD	5.73	± 9.6 %
10143	CAE	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-FDD	6.35	± 9.6 %
10144	CAE	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-FDD	6.65	± 9.6 %
10145	CAF	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-FDD	5.76	± 9.6 %
10146	CAF	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.41	± 9.6 %
10147	CAF	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.72	± 9.6 %
10149	CAE	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	LTE-FDD	6.42	± 9.6 %
10150	CAE	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	LTE-FDD	6.60	± 9.6 %
10151	CAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	LTE-TDD	9.28	± 9.6 %
10152	CAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	LTE-TDD	9.92	± 9.6 %
10153	CAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	LTE-TDD	10.05	± 9.6 %
10154	CAG	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	LTE-FDD	5.75	± 9.6 %
10155	CAG	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	LTE-FDD	6.43	± 9.6 %
10156	CAG	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	LTE-FDD	5.79	± 9.6 %
10157	CAG	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	LTE-FDD	6.49	± 9.6 %
10158	CAG	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-FDD	6.62	± 9.6 %
10159	CAG	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	LTE-FDD	6.56	± 9.6 %
10160	CAE	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	LTE-FDD	5.82	± 9.6 %
10161	CAE	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	LTE-FDD	6.43	± 9.6 %
10162	CAE	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	LTE-FDD	6.58	± 9.6 %
10166	CAF	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	LTE-FDD	5.46	± 9.6 %
10167	CAF	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.21	± 9.6 %
10168	CAF	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.79	± 9.6 %
10169	CAE	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-FDD	5.73	± 9.6 %
10170	CAE	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	LTE-FDD	6.52	± 9.6 %
10171	AAE	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	LTE-FDD	6.49	± 9.6 %
10172	CAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-TDD	9.21	± 9.6 %
10173	CAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	LTE-TDD	9.48	± 9.6 %
10174	CAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	LTE-TDD	10.25	± 9.6 %
10175	CAG	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	LTE-FDD	5.72	± 9.6 %
10176	CAG	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	LTE-FDD	6.52	± 9.6 %
10177	CAI	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	LTE-FDD	5.73	± 9.6 %
10178	CAG	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	LTE-FDD	6.52	± 9.6 %
10179	CAG	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	LTE-FDD	6.50	± 9.6 %
10180	CAG	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	LTE-FDD	6.50	± 9.6 %
10181	CAE	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	LTE-FDD	5.72	± 9.6 %
10182	CAE	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	LTE-FDD	6.52	± 9.6 %
10183	AAD	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	LTE-FDD	6.50	± 9.6 %
10184	CAE	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	LTE-FDD	5.73	± 9.6 %
10185	CAE	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	LTE-FDD	6.51	± 9.6 %
10186	AAE	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	LTE-FDD	6.50	± 9.6 %
10187	CAF	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-FDD	5.73	± 9.6 %
10188	CAF	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.52	± 9.6 %
10189	AAF	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.50	± 9.6 %
10193	CAC	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	WLAN	8.09	± 9.6 %
10194	CAC	IEEE 802.11n (HT Greenfield, 39 Mbps, 16-QAM)	WLAN	8.12	± 9.6 %
10195	CAC	IEEE 802.11n (HT Greenfield, 65 Mbps, 64-QAM)	WLAN	8.21	± 9.6 %
10196	CAC	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	WLAN	8.10	± 9.6 %
10197	CAC	IEEE 802.11n (HT Mixed, 39 Mbps, 16-QAM)	WLAN	8.13	± 9.6 %
10198	CAC	IEEE 802.11n (HT Mixed, 65 Mbps, 64-QAM)	WLAN	8.27	± 9.6 %
10219	CAC	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	WLAN	8.03	± 9.6 %



EX3DV4- SN:7536

June 7, 2019

10220	CAC	IEEE 802.11n (HT Mixed, 43.3 Mbps, 16-QAM)	WLAN	8.13	± 9.6 %
10221	CAC	IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)	WLAN	8.27	± 9.6 %
10222	CAC	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	WLAN	8.06	± 9.6 %
10223	CAC	IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)	WLAN	8.48	± 9.6 %
10224	CAC	IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)	WLAN	8.08	± 9.6 %
10225	CAB	UMTS-FDD (HSPA+)	WCDMA	5.97	± 9.6 %
10226	CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.49	± 9.6 %
10227	CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.26	± 9.6 %
10228	CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-TDD	9.22	± 9.6 %
10229	CAC	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	LTE-TDD	9.48	± 9.6 %
10230	CAC	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	LTE-TDD	10.25	± 9.6 %
10231	CAC	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	LTE-TDD	9.19	± 9.6 %
10232	CAF	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	LTE-TDD	9.48	± 9.6 %
10233	CAF	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	LTE-TDD	10.25	± 9.6 %
10234	CAF	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	LTE-TDD	9.21	± 9.6 %
10235	CAF	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	LTE-TDD	9.48	± 9.6 %
10236	CAF	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	LTE-TDD	10.25	± 9.6 %
10237	CAF	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	LTE-TDD	9.21	± 9.6 %
10238	CAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	LTE-TDD	9.48	± 9.6 %
10239	CAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	LTE-TDD	10.25	± 9.6 %
10240	CAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	LTE-TDD	9.21	± 9.6 %
10241	CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.82	± 9.6 %
10242	CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	LTE-TDD	9.86	± 9.6 %
10243	CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	LTE-TDD	9.46	± 9.6 %
10244	CAC	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-TDD	10.06	± 9.6 %
10245	CAC	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-TDD	10.06	± 9.6 %
10246	CAC	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-TDD	9.30	± 9.6 %
10247	CAF	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	LTE-TDD	9.91	± 9.6 %
10248	CAF	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	LTE-TDD	10.09	± 9.6 %
10249	CAF	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	LTE-TDD	9.29	± 9.6 %
10250	CAF	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	LTE-TDD	9.81	± 9.6 %
10251	CAF	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-TDD	10.17	± 9.6 %
10252	CAF	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	LTE-TDD	9.24	± 9.6 %
10253	CAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	LTE-TDD	9.90	± 9.6 %
10254	CAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	LTE-TDD	10.14	± 9.6 %
10255	CAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	LTE-TDD	9.20	± 9.6 %
10256	CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.96	± 9.6 %
10257	CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.08	± 9.6 %
10258	CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-TDD	9.34	± 9.6 %
10259	CAC	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-TDD	9.98	± 9.6 %
10260	CAC	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-TDD	9.97	± 9.6 %
10261	CAC	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-TDD	9.24	± 9.6 %
10262	CAF	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	LTE-TDD	9.83	± 9.6 %
10263	CAF	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	LTE-TDD	10.16	± 9.6 %
10264	CAF	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	LTE-TDD	9.23	± 9.6 %
10265	CAF	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	LTE-TDD	9.92	± 9.6 %
10266	CAF	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	LTE-TDD	10.07	± 9.6 %
10267	CAF	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-TDD	9.30	± 9.6 %
10268	CAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-TDD	10.06	± 9.6 %
10269	CAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	LTE-TDD	10.13	± 9.6 %
10270	CAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	LTE-TDD	9.58	± 9.6 %
10274	CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	WCDMA	4.87	± 9.6 %
10275	CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	WCDMA	3.96	± 9.6 %
10277	CAA	PHS (QPSK)	PHS	11.81	± 9.6 %
10278	CAA	PHS (QPSK, BW 884MHz, Rolloff 0.5)	PHS	11.81	± 9.6 %
10279	CAA	PHS (QPSK, BW 884MHz, Rolloff 0.38)	PHS	12.18	± 9.6 %
10290	AAB	CDMA2000, RC1, SO55, Full Rate	CDMA2000	3.91	± 9.6 %
10291	AAB	CDMA2000, RC3, SO55, Full Rate	CDMA2000	3.46	± 9.6 %
10292	AAB	CDMA2000, RC3, SO32, Full Rate	CDMA2000	3.39	± 9.6 %
10293	AAB	CDMA2000, RC3, SO3, Full Rate	CDMA2000	3.50	± 9.6 %
10295	AAB	CDMA2000, RC1, SO3, 1/8th Rate 25 fr.	CDMA2000	12.49	± 9.6 %
10297	AAD	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	LTE-FDD	5.81	± 9.6 %
10298	AAD	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-FDD	5.72	± 9.6 %
10299	AAD	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-FDD	6.39	± 9.6 %



EX3DV4- SN:7536

June 7, 2019

10300	AAD	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-FDD	6.60	± 9.6 %
10301	AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC)	WiMAX	12.03	± 9.6 %
10302	AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC, 3 CTRL symbols)	WiMAX	12.57	± 9.6 %
10303	AAA	IEEE 802.16e WiMAX (31:15, 5ms, 10MHz, 64QAM, PUSC)	WiMAX	12.52	± 9.6 %
10304	AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, 64QAM, PUSC)	WiMAX	11.86	± 9.6 %
10305	AAA	IEEE 802.16e WiMAX (31:15, 10ms, 10MHz, 64QAM, PUSC, 15 symbols)	WiMAX	15.24	± 9.6 %
10306	AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 64QAM, PUSC, 18 symbols)	WiMAX	14.67	± 9.6 %
10307	AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, PUSC, 18 symbols)	WiMAX	14.49	± 9.6 %
10308	AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, PUSC)	WiMAX	14.46	± 9.6 %
10309	AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, AMC 2x3, 18 symbols)	WiMAX	14.58	± 9.6 %
10310	AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, AMC 2x3, 18 symbols)	WiMAX	14.57	± 9.6 %
10311	AAD	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	LTE-FDD	6.06	± 9.6 %
10313	AAA	iDEN 1:3	iDEN	10.51	± 9.6 %
10314	AAA	iDEN 1:6	iDEN	13.48	± 9.6 %
10315	AAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	WLAN	1.71	± 9.6 %
10316	AAB	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)	WLAN	8.36	± 9.6 %
10317	AAC	IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)	WLAN	8.36	± 9.6 %
10352	AAA	Pulse Waveform (200Hz, 10%)	Generic	10.00	± 9.6 %
10353	AAA	Pulse Waveform (200Hz, 20%)	Generic	6.99	± 9.6 %
10354	AAA	Pulse Waveform (200Hz, 40%)	Generic	3.98	± 9.6 %
10355	AAA	Pulse Waveform (200Hz, 60%)	Generic	2.22	± 9.6 %
10356	AAA	Pulse Waveform (200Hz, 80%)	Generic	0.97	± 9.6 %
10387	AAA	QPSK Waveform, 1 MHz	Generic	5.10	± 9.6 %
10388	AAA	QPSK Waveform, 10 MHz	Generic	5.22	± 9.6 %
10396	AAA	64-QAM Waveform, 100 kHz	Generic	6.27	± 9.6 %
10399	AAA	64-QAM Waveform, 40 MHz	Generic	6.27	± 9.6 %
10400	AAD	IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle)	WLAN	8.37	± 9.6 %
10401	AAD	IEEE 802.11ac WiFi (40MHz, 64-QAM, 99pc duty cycle)	WLAN	8.60	± 9.6 %
10402	AAD	IEEE 802.11ac WiFi (80MHz, 64-QAM, 99pc duty cycle)	WLAN	8.53	± 9.6 %
10403	AAB	CDMA2000 (1xEV-DO, Rev. 0)	CDMA2000	3.76	± 9.6 %
10404	AAB	CDMA2000 (1xEV-DO, Rev. A)	CDMA2000	3.77	± 9.6 %
10406	AAB	CDMA2000, RC3, SO32, SCH0, Full Rate	CDMA2000	5.22	± 9.6 %
10410	AAF	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9, Subframe Conf=4)	LTE-TDD	7.82	± 9.6 %
10414	AAA	WLAN CCDF, 64-QAM, 40MHz	Generic	8.54	± 9.6 %
10415	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	WLAN	1.54	± 9.6 %
10416	AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	WLAN	8.23	± 9.6 %
10417	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)	WLAN	8.23	± 9.6 %
10418	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preamble)	WLAN	8.14	± 9.6 %
10419	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preamble)	WLAN	8.19	± 9.6 %
10422	AAB	IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)	WLAN	8.32	± 9.6 %
10423	AAB	IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)	WLAN	8.47	± 9.6 %
10424	AAB	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	WLAN	8.40	± 9.6 %
10425	AAB	IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)	WLAN	8.41	± 9.6 %
10426	AAB	IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)	WLAN	8.45	± 9.6 %
10427	AAB	IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)	WLAN	8.41	± 9.6 %
10430	AAD	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)	LTE-FDD	8.28	± 9.6 %
10431	AAD	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)	LTE-FDD	8.38	± 9.6 %
10432	AAC	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)	LTE-FDD	8.34	± 9.6 %
10433	AAC	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)	LTE-FDD	8.34	± 9.6 %
10434	AAA	W-CDMA (BS Test Model 1, 64 DPCH)	WCDMA	8.60	± 9.6 %
10435	AAF	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	± 9.6 %
10447	AAD	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.56	± 9.6 %
10448	AAD	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.53	± 9.6 %
10449	AAC	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.51	± 9.6 %
10450	AAC	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.48	± 9.6 %

Certificate No: EX3-7536_Jun19

Page 14 of 20



EX3DV4- SN:7536

June 7, 2019

10451	AAA	W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)	WCDMA	7.59	± 9.6 %
10456	AAB	IEEE 802.11ac WiFi (160MHz, 64-QAM, 99pc duty cycle)	WLAN	8.63	± 9.6 %
10457	AAA	UMTS-FDD (DC-HSDPA)	WCDMA	6.62	± 9.6 %
10458	AAA	CDMA2000 (1xEV-DO, Rev. B, 2 carriers)	CDMA2000	6.55	± 9.6 %
10459	AAA	CDMA2000 (1xEV-DO, Rev. B, 3 carriers)	CDMA2000	8.25	± 9.6 %
10460	AAA	UMTS-FDD (WCDMA, AMR)	WCDMA	2.39	± 9.6 %
10461	AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	± 9.6 %
10462	AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.30	± 9.6 %
10463	AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.56	± 9.6 %
10464	AAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	± 9.6 %
10465	AAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	± 9.6 %
10466	AAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	± 9.6 %
10467	AAE	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	± 9.6 %
10468	AAE	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	± 9.6 %
10469	AAE	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.56	± 9.6 %
10470	AAE	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	± 9.6 %
10471	AAE	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	± 9.6 %
10472	AAE	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	± 9.6 %
10473	AAE	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	± 9.6 %
10474	AAE	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	± 9.6 %
10475	AAE	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	± 9.6 %
10477	AAF	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	± 9.6 %
10478	AAF	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	± 9.6 %
10479	AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	± 9.6 %
10480	AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.18	± 9.6 %
10481	AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.45	± 9.6 %
10482	AAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.71	± 9.6 %
10483	AAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.39	± 9.6 %
10484	AAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.47	± 9.6 %
10485	AAE	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.59	± 9.6 %
10486	AAE	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.38	± 9.6 %
10487	AAE	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.60	± 9.6 %
10488	AAE	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.70	± 9.6 %
10489	AAE	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.31	± 9.6 %
10490	AAE	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	± 9.6 %
10491	AAE	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	± 9.6 %



EX3DV4- SN:7536

June 7, 2019

10492	AAE	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.41	± 9.6 %
10493	AAE	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.55	± 9.6 %
10494	AAF	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	± 9.6 %
10495	AAF	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.37	± 9.6 %
10496	AAF	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	± 9.6 %
10497	AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.67	± 9.6 %
10498	AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.40	± 9.6 %
10499	AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.68	± 9.6 %
10500	AAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.67	± 9.6 %
10501	AAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.44	± 9.6 %
10502	AAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.52	± 9.6 %
10503	AAE	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.72	± 9.6 %
10504	AAE	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.31	± 9.6 %
10505	AAE	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	± 9.6 %
10506	AAE	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	± 9.6 %
10507	AAE	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.36	± 9.6 %
10508	AAE	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.55	± 9.6 %
10509	AAE	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.99	± 9.6 %
10510	AAE	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.49	± 9.6 %
10511	AAE	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.51	± 9.6 %
10512	AAF	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	± 9.6 %
10513	AAF	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.42	± 9.6 %
10514	AAF	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.45	± 9.6 %
10515	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	WLAN	1.58	± 9.6 %
10516	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	WLAN	1.57	± 9.6 %
10517	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	WLAN	1.58	± 9.6 %
10518	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	WLAN	8.23	± 9.6 %
10519	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	WLAN	8.39	± 9.6 %
10520	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	WLAN	8.12	± 9.6 %
10521	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	WLAN	7.97	± 9.6 %
10522	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	WLAN	8.45	± 9.6 %
10523	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	WLAN	8.08	± 9.6 %
10524	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	WLAN	8.27	± 9.6 %
10525	AAB	IEEE 802.11ac WiFi (20MHz, MCS0, 99pc duty cycle)	WLAN	8.36	± 9.6 %
10526	AAB	IEEE 802.11ac WiFi (20MHz, MCS1, 99pc duty cycle)	WLAN	8.42	± 9.6 %
10527	AAB	IEEE 802.11ac WiFi (20MHz, MCS2, 99pc duty cycle)	WLAN	8.21	± 9.6 %
10528	AAB	IEEE 802.11ac WiFi (20MHz, MCS3, 99pc duty cycle)	WLAN	8.36	± 9.6 %
10529	AAB	IEEE 802.11ac WiFi (20MHz, MCS4, 99pc duty cycle)	WLAN	8.36	± 9.6 %
10531	AAB	IEEE 802.11ac WiFi (20MHz, MCS6, 99pc duty cycle)	WLAN	8.43	± 9.6 %
10532	AAB	IEEE 802.11ac WiFi (20MHz, MCS7, 99pc duty cycle)	WLAN	8.29	± 9.6 %
10533	AAB	IEEE 802.11ac WiFi (20MHz, MCS8, 99pc duty cycle)	WLAN	8.38	± 9.6 %
10534	AAB	IEEE 802.11ac WiFi (40MHz, MCS0, 99pc duty cycle)	WLAN	8.45	± 9.6 %



EX3DV4-- SN:7536

June 7, 2019

10535	AAB	IEEE 802.11ac WiFi (40MHz, MCS1, 99pc duty cycle)	WLAN	8.45	± 9.6 %
10536	AAB	IEEE 802.11ac WiFi (40MHz, MCS2, 99pc duty cycle)	WLAN	8.32	± 9.6 %
10537	AAB	IEEE 802.11ac WiFi (40MHz, MCS3, 99pc duty cycle)	WLAN	8.44	± 9.6 %
10538	AAB	IEEE 802.11ac WiFi (40MHz, MCS4, 99pc duty cycle)	WLAN	8.54	± 9.6 %
10540	AAB	IEEE 802.11ac WiFi (40MHz, MCS6, 99pc duty cycle)	WLAN	8.39	± 9.6 %
10541	AAB	IEEE 802.11ac WiFi (40MHz, MCS7, 99pc duty cycle)	WLAN	8.46	± 9.6 %
10542	AAB	IEEE 802.11ac WiFi (40MHz, MCS8, 99pc duty cycle)	WLAN	8.65	± 9.6 %
10543	AAB	IEEE 802.11ac WiFi (40MHz, MCS9, 99pc duty cycle)	WLAN	8.65	± 9.6 %
10544	AAB	IEEE 802.11ac WiFi (80MHz, MCS0, 99pc duty cycle)	WLAN	8.47	± 9.6 %
10545	AAB	IEEE 802.11ac WiFi (80MHz, MCS1, 99pc duty cycle)	WLAN	8.55	± 9.6 %
10546	AAB	IEEE 802.11ac WiFi (80MHz, MCS2, 99pc duty cycle)	WLAN	8.35	± 9.6 %
10547	AAB	IEEE 802.11ac WiFi (80MHz, MCS3, 99pc duty cycle)	WLAN	8.49	± 9.6 %
10548	AAB	IEEE 802.11ac WiFi (80MHz, MCS4, 99pc duty cycle)	WLAN	8.37	± 9.6 %
10550	AAB	IEEE 802.11ac WiFi (80MHz, MCS6, 99pc duty cycle)	WLAN	8.38	± 9.6 %
10551	AAB	IEEE 802.11ac WiFi (80MHz, MCS7, 99pc duty cycle)	WLAN	8.50	± 9.6 %
10552	AAB	IEEE 802.11ac WiFi (80MHz, MCS8, 99pc duty cycle)	WLAN	8.42	± 9.6 %
10553	AAB	IEEE 802.11ac WiFi (80MHz, MCS9, 99pc duty cycle)	WLAN	8.45	± 9.6 %
10554	AAC	IEEE 802.11ac WiFi (160MHz, MCS0, 99pc duty cycle)	WLAN	8.48	± 9.6 %
10555	AAC	IEEE 802.11ac WiFi (160MHz, MCS1, 99pc duty cycle)	WLAN	8.47	± 9.6 %
10556	AAC	IEEE 802.11ac WiFi (160MHz, MCS2, 99pc duty cycle)	WLAN	8.50	± 9.6 %
10557	AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 99pc duty cycle)	WLAN	8.52	± 9.6 %
10558	AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 99pc duty cycle)	WLAN	8.61	± 9.6 %
10560	AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 99pc duty cycle)	WLAN	8.73	± 9.6 %
10561	AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 99pc duty cycle)	WLAN	8.56	± 9.6 %
10562	AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 99pc duty cycle)	WLAN	8.69	± 9.6 %
10563	AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 99pc duty cycle)	WLAN	8.77	± 9.6 %
10564	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	WLAN	8.25	± 9.6 %
10565	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	WLAN	8.45	± 9.6 %
10566	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	WLAN	8.13	± 9.6 %
10567	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	WLAN	8.00	± 9.6 %
10568	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	WLAN	8.37	± 9.6 %
10569	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	WLAN	8.10	± 9.6 %
10570	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle)	WLAN	8.30	± 9.6 %
10571	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	WLAN	1.99	± 9.6 %
10572	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	WLAN	1.99	± 9.6 %
10573	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	WLAN	1.98	± 9.6 %
10574	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)	WLAN	1.98	± 9.6 %
10575	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	WLAN	8.59	± 9.6 %
10576	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)	WLAN	8.60	± 9.6 %
10577	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	WLAN	8.70	± 9.6 %
10578	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	WLAN	8.49	± 9.6 %
10579	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	WLAN	8.36	± 9.6 %
10580	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	WLAN	8.76	± 9.6 %
10581	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	WLAN	8.35	± 9.6 %
10582	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	WLAN	8.67	± 9.6 %
10583	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	WLAN	8.59	± 9.6 %
10584	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	WLAN	8.60	± 9.6 %
10585	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	WLAN	8.70	± 9.6 %
10586	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	WLAN	8.49	± 9.6 %
10587	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	WLAN	8.36	± 9.6 %