



SAR EVALUATION REPORT

Applicant Name:
Apple Inc.
One Apple Park Way
Cupertino, CA 95014 USA

Date of Testing:
05/22/19 - 07/03/19
Test Site/Location:
PCTEST Lab, Morgan Hill, CA, USA
Document Serial No.:
1C1901280003-01-R3.BCG

FCC ID: BCGA2200
APPLICANT: APPLE, INC.

DUT Type: Tablet Device
Application Type: Certification
FCC Rule Part(s): CFR §2.1093
Model: A2200

Equipment Class	Band & Mode	Tx Frequency	SAR 1g Body (W/kg)
PCB	GPRS/EDGE 850	824.20 - 848.80 MHz	1.16
PCB	GPRS/EDGE 1900	1850.20 - 1909.80 MHz	1.01
PCB	UMTS 850	826.40 - 846.60 MHz	1.07
PCB	UMTS 1750	1712.4 - 1752.6 MHz	1.04
PCB	UMTS 1900	1852.4 - 1907.6 MHz	1.17
PCB	LTE Band 71	665.5 - 695.5 MHz	1.02
PCB	LTE Band 12	699.7 - 713.3 MHz	0.93
PCB	LTE Band 17	706.5 - 713.5 MHz	N/A
PCB	LTE Band 13	779.5 - 784.5 MHz	1.12
PCB	LTE Band 14	790.5 - 795.5 MHz	0.96
PCB	LTE Band 26 (Cell)	814.7 - 848.3 MHz	1.19
PCB	LTE Band 5 (Cell)	824.7 - 848.3 MHz	1.14
PCB	LTE Band 66 (AWS)	1710.7 - 1779.3 MHz	1.15
PCB	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	N/A
PCB	LTE Band 25 (PCS)	1850.7 - 1914.3 MHz	1.06
PCB	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	N/A
PCB	LTE Band 30	2307.5 - 2312.5 MHz	1.02
PCB	LTE Band 7	2502.5 - 2567.5 MHz	1.18
PCB	LTE Band 41	2498.5 - 2697.5 MHz	1.19
DTX	2.4 GHz WLAN	2412 - 2472 MHz	0.95
NI	U-NII-1	5180 - 5240 MHz	N/A
NI	U-NII-2A	5260 - 5320 MHz	0.98
NI	U-NII-2C	5500 - 5720 MHz	1.11
NI	U-NII-3	5745 - 5825 MHz	0.94
DSS/DTX	Bluetooth	2402 - 2480 MHz	1.07
Simultaneous SAR per KDB 690783 D01v01r03:			1.38

Note: This revised Test Report (S/N: 1C1901280003-01-R3.BCG) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.9 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



The SAR Tick is an initiative of the Mobile & Wireless Forum (MWF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MWF. Further details can be obtained by emailing: sartick@mwfai.info.

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 1 of 116

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	15
3	INTRODUCTION	16
4	DOSIMETRIC ASSESSMENT	17
5	TEST CONFIGURATION POSITIONS	18
6	RF EXPOSURE LIMITS	19
7	FCC MEASUREMENT PROCEDURES.....	20
8	RF CONDUCTED POWERS.....	25
9	SYSTEM VERIFICATION.....	85
10	SAR DATA SUMMARY	87
11	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	105
12	SAR MEASUREMENT VARIABILITY	109
13	ADDITIONAL TESTING PER FCC GUIDANCE	110
14	EQUIPMENT LIST.....	112
15	MEASUREMENT UNCERTAINTIES.....	113
16	CONCLUSION.....	114
17	REFERENCES	115
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		
APPENDIX G: POWER REDUCTION VERIFICATION		
APPENDIX H: DOWNLINK LTE CA RF CONDUCTED POWERS		

FCC ID: BCGA2200	 SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device
		Page 2 of 116

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GPRS/EDGE 850	Data	824.20 - 848.80 MHz
GPRS/EDGE 1900	Data	1850.20 - 1909.80 MHz
UMTS 850	Data	826.40 - 846.60 MHz
UMTS 1750	Data	1712.4 - 1752.6 MHz
UMTS 1900	Data	1852.4 - 1907.6 MHz
LTE Band 71	Data	665.5 - 695.5 MHz
LTE Band 12	Data	699.7 - 715.3 MHz
LTE Band 17	Data	706.5 - 713.5 MHz
LTE Band 13	Data	779.5 - 784.5 MHz
LTE Band 14	Data	790.5 - 795.5 MHz
LTE Band 26 (Cell)	Data	814.7 - 848.3 MHz
LTE Band 5 (Cell)	Data	824.7 - 848.3 MHz
LTE Band 66 (AWS)	Data	1710.7 - 1779.3 MHz
LTE Band 4 (AWS)	Data	1710.7 - 1754.3 MHz
LTE Band 25 (PCS)	Data	1850.7 - 1914.3 MHz
LTE Band 2 (PCS)	Data	1850.7 - 1909.3 MHz
LTE Band 30	Data	2307.5 - 2312.5 MHz
LTE Band 7	Data	2502.5 - 2567.5 MHz
LTE Band 41	Data	2498.5 - 2687.5 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2472 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5720 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz

1.2 Power Reduction for SAR

This device uses the manufacturer's proprietary motion detect mode to determine proximity to the user's body and set the licensed power level accordingly for SAR compliance. When being used in the hand or the body, the output power for licensed transmitters will always be reduced. Per FCC KDB Guidance, SAR testing was performed only using reduced output powers following the test positions in KDB Publication 616217.

This device additionally utilizes a power reduction mechanism for Bluetooth operations. When Bluetooth is operating simultaneously with 5 GHz WLAN, the output power is permanently reduced. SAR evaluations were additionally performed at the maximum allowed output power for these scenarios to evaluate simultaneous transmission compliance.

Detailed descriptions of the power reduction mechanisms are included in the operational description. The power reduction mechanisms were confirmed during the SAR Evaluation. Section 8.5 and Appendix G contains a summary of the verification results.

FCC ID: BCGA2200	 SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device
		Page 3 of 116

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 2G/3G/4G Output Power for Portable Use Conditions

A. Antenna C

Mode / Band		Burst Average GMSK (dBm)		Burst Average 8-PSK (dBm)	
		1 TX Slots	2 TX Slots	1 TX Slots	2 TX Slots
GPRS/EDGE 850	Maximum	27.75	24.75	24.75	23.75
	Nominal	27.00	24.00	24.00	23.00
GPRS/EDGE 1900	Maximum	21.95	18.95	21.95	18.95
	Nominal	21.20	18.20	21.20	18.20

Mode / Band		Modulated Average (dBm)			
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA	3GPP DC-HSDPA
UMTS Band 5 (850 MHz)	Maximum	17.70	17.70	17.70	17.70
	Nominal	17.20	17.20	17.20	17.20
UMTS Band 4 (1750 MHz)	Maximum	13.30	13.30	13.30	13.30
	Nominal	12.80	12.80	12.80	12.80
UMTS Band 2 (1900 MHz)	Maximum	13.10	13.10	13.10	13.10
	Nominal	12.60	12.60	12.60	12.60

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 4 of 116

Mode / Band		Modulated Average (dBm)
LTE Band 71	Maximum	18.10
	Nominal	17.60
LTE Band 12	Maximum	17.50
	Nominal	17.00
LTE Band 17	Maximum	17.50
	Nominal	17.00
LTE Band 13	Maximum	18.10
	Nominal	17.60
LTE Band 14	Maximum	18.10
	Nominal	17.60
LTE Band 26 (Cell)	Maximum	19.00
	Nominal	18.50
LTE Band 5 (Cell)	Maximum	17.70
	Nominal	17.20
LTE Band 66 (AWS)	Maximum	13.30
	Nominal	12.80
LTE Band 4 (AWS)	Maximum	13.30
	Nominal	12.80
LTE Band 25 (PCS)	Maximum	13.10
	Nominal	12.60
LTE Band 2 (PCS)	Maximum	13.10
	Nominal	12.60
LTE Band 30	Maximum	13.20
	Nominal	12.70
LTE Band 7 ULCA	Maximum	12.40
	Nominal	11.40
LTE Band 7	Maximum	12.40
	Nominal	11.90
LTE Band 41 (PC3) ULCA	Maximum	15.40
	Nominal	14.40
LTE Band 41 (PC3)	Maximum	15.40
	Nominal	14.90
LTE Band 41 (PC2)	Maximum	15.40
	Nominal	14.90

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 5 of 116

B. Antenna D

Mode / Band		Burst Average GMSK (dBm)		Burst Average 8-PSK (dBm)	
		1 TX Slots	2 TX Slots	1 TX Slots	2 TX Slots
GPRS/EDGE 850	Maximum	28.25	25.50	22.75	21.75
	Nominal	27.50	24.75	22.00	21.00
GPRS/EDGE 1900	Maximum	21.25	18.25	21.25	18.25
	Nominal	20.50	17.50	20.50	17.50

Mode / Band		Modulated Average (dBm)			
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA	3GPP DC-HSDPA
UMTS Band 5 (850 MHz)	Maximum	19.20	19.20	19.20	19.20
	Nominal	18.70	18.70	18.70	18.70
UMTS Band 4 (1750 MHz)	Maximum	13.20	13.20	13.20	13.20
	Nominal	12.70	12.70	12.70	12.70
UMTS Band 2 (1900 MHz)	Maximum	12.00	12.00	12.00	12.00
	Nominal	11.50	11.50	11.50	11.50

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 6 of 116

Mode / Band		Modulated Average (dBm)
LTE Band 71	Maximum	17.20
	Nominal	16.70
LTE Band 12	Maximum	17.20
	Nominal	16.70
LTE Band 17	Maximum	17.20
	Nominal	16.70
LTE Band 13	Maximum	18.30
	Nominal	17.80
LTE Band 14	Maximum	18.30
	Nominal	17.80
LTE Band 26 (Cell)	Maximum	18.20
	Nominal	17.70
LTE Band 5 (Cell)	Maximum	19.20
	Nominal	18.70
LTE Band 66 (AWS)	Maximum	13.20
	Nominal	12.70
LTE Band 4 (AWS)	Maximum	13.20
	Nominal	12.70
LTE Band 25 (PCS)	Maximum	12.00
	Nominal	11.50
LTE Band 2 (PCS)	Maximum	12.00
	Nominal	11.50
LTE Band 30	Maximum	12.80
	Nominal	12.30
LTE Band 7 ULCA	Maximum	12.40
	Nominal	11.40
LTE Band 7	Maximum	12.40
	Nominal	11.90
LTE Band 41 (PC3) ULCA	Maximum	15.40
	Nominal	14.40
LTE Band 41 (PC3)	Maximum	15.40
	Nominal	14.90
LTE Band 41 (PC2)	Maximum	15.40
	Nominal	14.90

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 7 of 116

1.3.2 Unlicensed Maximum Output Power

Mode / Band		Modulated Average - Single Tx Chain (dBm) - Antenna A				
Channel		1	2 - 10	11	12	13
IEEE 802.11b (2.4 GHz)	Maximum	16.00				14.50
	Nominal	14.50				13.00
IEEE 802.11g (2.4 GHz)	Maximum	15.00	16.00	14.00	12.00	2.00
	Nominal	13.50	14.50	12.50	10.50	0.50
IEEE 802.11n (2.4 GHz)	Maximum	15.00	16.00	14.00	12.00	2.00
	Nominal	13.50	14.50	12.50	10.50	0.50

Mode / Band		Modulated Average - Single Tx Chain (dBm) - Antenna B				
Channel		1	2 - 10	11	12	13
IEEE 802.11b (2.4 GHz)	Maximum	16.00				14.50
	Nominal	14.50				13.00
IEEE 802.11g (2.4 GHz)	Maximum	15.00	16.00	14.00	12.00	2.00
	Nominal	13.50	14.50	12.50	10.50	0.50
IEEE 802.11n (2.4 GHz)	Maximum	15.00	16.00	14.00	12.00	2.00
	Nominal	13.50	14.50	12.50	10.50	0.50

Mode / Band			Modulated Average - MIMO (dBm)				
			20 MHz Bandwidth				
Channel			1	2 - 10	11	12	13
IEEE 802.11g/n (2.4 GHz)	Antenna A	Maximum	13.50	16.00	13.00	10.50	0.50
		Nominal	12.00	14.50	11.50	9.00	-1.00
	Antenna B	Maximum	13.50	16.00	13.00	10.50	0.50
		Nominal	12.00	14.50	11.50	9.00	-1.00

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 8 of 116

Mode / Band		Modulated Average - Single Tx Chain (dBm) - Antenna A									
Bluetooth BDR/LE		Maximum									
		Nominal									
Bluetooth EDR		Maximum									
		Nominal									

Mode / Band		Modulated Average - Single Tx Chain (dBm) - Antenna A																			
		20 MHz Bandwidth										40 MHz Bandwidth									
Channel		36	40-48	52-60	64	100	104-136	140	144	149-165		38	46	54	62	102	110-126	134	142	151-159	
IEEE 802.11a (5 GHz)	Maximum	16.00	16.50	17.00	16.00	15.00	17.50	15.00	17.50	16.25											
	Nominal	14.50	15.00	15.50	14.50	13.50	16.00	13.50	16.00	14.75											
IEEE 802.11n (5 GHz)	Maximum	16.00	16.50	17.00	16.00	15.00	17.50	15.00	17.50	16.25		14.00	16.50	17.00	14.50	14.00	17.50	15.50	17.50	16.25	
	Nominal	14.50	15.00	15.50	14.50	13.50	16.00	13.50	16.00	14.75		12.50	15.00	15.50	13.00	12.50	16.00	14.00	16.00	14.75	
IEEE 802.11ac (5 GHz)	Maximum	16.00	16.50	17.00	16.00	15.00	17.50	15.00	17.50	16.25		14.00	16.50	17.00	14.50	14.00	17.50	15.50	17.50	16.25	13.00
	Nominal	14.50	15.00	15.50	14.50	13.50	16.00	13.50	16.00	14.75		12.50	15.00	15.50	13.00	12.50	16.00	14.00	16.00	14.75	11.50

Mode / Band		Modulated Average - Single Tx Chain (dBm) - Antenna B																			
		20 MHz Bandwidth										40 MHz Bandwidth									
Channel		36	40-48	52-60	64	100	104-136	140	144	149-165		38	46	54	62	102	110-126	134	142	151-159	
IEEE 802.11a (5 GHz)	Maximum	16.00	16.25	16.75	16.00	15.00	17.25	15.00	17.25	16.50											
	Nominal	14.50	14.75	15.25	14.50	13.50	15.75	13.50	15.75	15.00											
IEEE 802.11n (5 GHz)	Maximum	16.00	16.25	16.75	16.00	15.00	17.25	15.00	17.25	16.50		14.00	16.25	16.75	14.50	14.00	17.25	15.50	17.25	16.50	
	Nominal	14.50	14.75	15.25	14.50	13.50	15.75	13.50	15.75	15.00		12.50	14.75	15.25	13.00	12.50	15.75	14.00	15.75	15.00	
IEEE 802.11ac (5 GHz)	Maximum	16.00	16.25	16.75	16.00	15.00	17.25	15.00	17.25	16.50		14.00	16.25	16.75	14.50	14.00	17.25	15.50	17.25	16.50	13.00
	Nominal	14.50	14.75	15.25	14.50	13.50	15.75	13.50	15.75	15.00		12.50	14.75	15.25	13.00	12.50	15.75	14.00	15.75	15.00	11.50

Mode / Band		Modulated Average - MIMO (dBm) 2Tx CDD																			
		20 MHz Bandwidth										40 MHz Bandwidth									
Channel		36	40-48	52-60	64-100	104-136	140	144	149-165			38	46	54	62	102	110-126	134	142	151-159	
IEEE 802.11a (5 GHz)	Antenna A	Maximum	15.00	16.50	16.50	14.50	15.50	13.50	15.50	16.25											
		Nominal	13.50	15.00	15.00	13.00	14.00	12.00	14.00	14.75											
	Antenna B	Maximum	15.00	16.25	16.50	14.50	15.50	13.50	15.50	16.50											
		Nominal	13.50	14.75	15.00	13.00	14.00	12.00	14.00	15.00											
IEEE 802.11n (5 GHz)	Antenna A	Maximum	15.00	16.50	16.50	14.50	15.50	13.50	15.50	16.25		12.50	16.50	17.00	13.50	13.00	17.50	14.00	17.50	16.25	
		Nominal	13.50	15.00	15.00	13.00	14.00	12.00	14.00	14.75		11.00	15.00	15.50	12.00	11.50	16.00	12.50	16.00	14.75	
	Antenna B	Maximum	15.00	16.25	16.50	14.50	15.50	13.50	15.50	16.50		12.50	16.25	16.75	13.50	13.00	17.25	14.00	17.25	16.50	
		Nominal	13.50	14.75	15.00	13.00	14.00	12.00	14.00	15.00		11.00	14.75	15.25	12.00	11.50	15.75	12.50	15.75	15.00	
IEEE 802.11ac (5 GHz)	Antenna A	Maximum	15.00	16.50	16.50	14.50	15.50	13.50	15.50	16.25		12.50	16.50	17.00	13.50	13.00	17.50	14.00	17.50	16.25	11.50
		Nominal	13.50	15.00	15.00	13.00	14.00	12.00	14.00	14.75		11.00	15.00	15.50	12.00	11.50	16.00	12.50	16.00	14.75	10.00
	Antenna B	Maximum	15.00	16.25	16.50	14.50	15.50	13.50	15.50	16.50		12.50	16.25	16.75	13.50	13.00	17.25	14.00	17.25	16.50	11.50
		Nominal	13.50	14.75	15.00	13.00	14.00	12.00	14.00	15.00		11.00	14.75	15.25	12.00	11.50	15.75	12.50	15.75	15.00	10.00

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

Mode / Band		Modulated Average - MIMO (dBm) 2Tx SDM																			
		20 MHz Bandwidth										40 MHz Bandwidth									
Channel		36	40-48	52-60	64-100	104-136	140	144	149-165			38	46	54	62	102	110-126	134	142	151-159	
IEEE 802.11n (5 GHz)	Antenna A	Maximum	15.00	16.50	17.00	14.50	17.50	13.50	17.50	16.25		12.50	16.50	17.00	13.50	13.00	17.50	14.00	17.50	16.25	
		Nominal	13.50	15.00	15.50	13.00	16.00	12.00	16.00	14.75		11.00	15.00	15.50	12.00	11.50	16.00	12.50	16.00	14.75	
	Antenna B	Maximum	15.00	16.25	16.75	14.50	17.25	13.50	17.25	16.50		12.50	16.25	16.75	13.50	13.00	17.25	14.00	17.25	16.50	
		Nominal	13.50	14.75	15.25	13.00	15.75	12.00	15.75	15.00		11.00	14.75	15.25	12.00	11.50	15.75	12.50	15.75	15.00	
IEEE 802.11ac (5 GHz)	Antenna A	Maximum	15.00	16.50	17.00	14.50	17.50	13.50	17.50	16.25		12.50	16.50	17.00	13.50	13.00	17.50	14.00	17.50	16.25	11.50
		Nominal	13.50	15.00	15.50	13.00	16.00	12.00	16.00	14.75		11.00	15.00	15.50	12.00	11.50	16.00	12.50	16.00	14.75	10.00
	Antenna B	Maximum	15.00	16.25	16.75	14.50	17.25	13.50	17.25	16.50		12.50	16.25	16.75	13.50	13.00	17.25	14.00	17.25	16.50	11.50
		Nominal	13.50	14.75	15.25	13.00	15.75	12.00	15.75	15.00		11.00	14.75	15.25	12.00	11.50	15.75	12.50	15.75	15.00	10.00

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2200		 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device		Page 9 of 116

1.3.3 Unlicensed Reduced Output Power

Mode / Band		Modulated Average - Single Tx Chain (dBm) - Antenna A
Bluetooth BDR/EDR/LE	Maximum	10.00
	Nominal	8.50

Note: Bluetooth operations on Antenna A are reduced in output power when it is operating simultaneously with 5 GHz WLAN. Detailed description of the power reduction mechanism is included in the operational description.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 10 of 116

1.4 DUT Antenna Locations

The overall dimensions of this device is > 200 mm. A diagram showing the location of the device antennas can be found in Appendix F. Exact antenna dimensions and separation distances are shown in the Technical Descriptions in the FCC filings.

**Table 1-1
Device Edges/Sides for SAR Testing**

Device Sides/Edges for SAR Testing						
Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850 Antenna C	Yes	No	Yes	No	Yes	No
GPRS 1900 Antenna C	Yes	No	Yes	No	Yes	No
UMTS 850 Antenna C	Yes	No	Yes	No	Yes	No
UMTS 1750 Antenna C	Yes	No	Yes	No	Yes	No
UMTS 1900 Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 71 Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 12 Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 13 Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 14 Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 26 (Cell) Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 5 (Cell) Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 66 (AWS) Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 25 (PCS) Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 30 Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 7 Antenna C	Yes	No	Yes	Yes	Yes	No
LTE Band 41 Antenna C	Yes	No	Yes	Yes	Yes	No
GPRS 850 Antenna D	Yes	No	Yes	Yes	No	Yes
GPRS 1900 Antenna D	Yes	No	Yes	No	No	Yes
UMTS 850 Antenna D	Yes	No	Yes	No	No	Yes
UMTS 1750 Antenna D	Yes	No	Yes	No	No	Yes
UMTS 1900 Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 71 Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 12 Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 13 Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 14 Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 26 (Cell) Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 5 (Cell) Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 66 (AWS) Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 25 (PCS) Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 30 Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 7 Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 41 Antenna D	Yes	No	Yes	No	No	Yes
2.4 GHz WLAN Antenna A	Yes	No	No	Yes	No	Yes
2.4 GHz WLAN Antenna B	Yes	No	No	Yes	Yes	No
5 GHz WLAN Antenna A	Yes	No	No	Yes	No	Yes
5 GHz WLAN Antenna B	Yes	No	No	Yes	Yes	No
Bluetooth Antenna A	Yes	No	No	Yes	No	Yes

Note: Per FCC KDB Publication 616217 D04v01r01, particular edges were not required to be evaluated for SAR based on the SAR exclusion threshold in KDB 447498 D01V06. Additional edges may have been evaluated for simultaneous transmission analysis.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 11 of 116

1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be operating simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds.

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Body
1	Cellular Band + 2.4 GHz WI-FI	Yes
2	Cellular Band + 5 GHz WI-FI	Yes
3	Cellular Band + 2.4 GHz Bluetooth	Yes
4	Cellular Band+ 2.4 GHz WI-FI MIMO	Yes
5	Cellular Band + 5 GHz WI-FI MIMO	Yes
6	Cellular Band + 2.4 GHz Bluetooth + 5 GHz WI-FI	Yes
7	Cellular Band + 2.4 GHz Bluetooth + 5 GHz WI-FI MIMO	Yes
8	2.4 GHz Bluetooth + 5 GHz WI-FI	Yes
9	2.4 GHz Bluetooth + 5 GHz WI-FI MIMO	Yes

1. There are no limitations in the above listed simultaneous transmission scenarios between cellular antennas and BT/WI-FI antennas.
2. 2.4 GHz WLAN and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously on any antenna (Antenna A, Antenna B).
3. All licensed modes share the same antenna path and cannot transmit simultaneously.
4. This device supports 2x2 MIMO Tx for WLAN. 802.11a/g/n/ac supports CDD/STBC and 802.11n/ac additionally supports SDM. Each WLAN antenna can transmit independently or together when operating with MIMO.
5. This device support VoWiFi.

1.6 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since U-NII-2A band have a higher or same specified maximum output power than U-NII-1 for both Antenna A and Antenna B, U-NII-2A was evaluated for both Antenna A and Antenna B SAR. Additional testing for U-NII-1 Antenna A and Antenna B was not required since all reported SAR for U-NII-2A was less than 1.2 W/kg per FCC KDB Publication 248227 D01v02r02.

Configurations according to FCC KDB Publication 941225 D06v02r01. Since Wireless Router operations are not allowed by the chipset firmware using U-NII-1, U-NII-2A & U-NII-2C WIFI, only 2.4 GHz and U-NII-3 WIFI

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 12 of 116

The WLAN/Bluetooth chipset in this device is produced by two different suppliers. The electrically identical modules are manufactured with the identical mechanical structure to meet the same specifications and functions. Two device variants are referenced as Variant 1 and Variant 2 in this report.

WLAN/Bluetooth SAR worst case configuration was evaluated for Variant 1 and Variant 2. The Variant with the highest reported SAR value was evaluated for the remaining WLAN/Bluetooth configurations.

This device supports channel 1-13 for 2.4 GHz WLAN. However, because channel 12/13 targets are not higher than that of channels 1-11, channels 1, 6 and 11 were considered for SAR testing per FCC KDB 248227 D01V02r02.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx Antenna output
- d) 256 QAM is supported
- e) TDWR and Band gap channels are supported

(B) Licensed Transmitter(s)

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

This device supports LTE Carrier Aggregation (CA) in the downlink. All uplink communications are identical to Release 8 specifications. ULCA is only supported in Power Class 3. Per FCC KDB Publication 941225 D05A v01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive. The downlink carrier aggregation exclusion analysis can be found in Appendix H. This device supports LTE Carrier Aggregation (CA) for LTE Band 7 and LTE Band 41 with two component carriers in the uplink. SAR Measurements and conducted powers were evaluated per 2017 Fall TCB Workshop Notes.

This device supports LTE capabilities with overlapping transmission frequency ranges. When the supported frequency range of an LTE Band falls completely within an LTE band with a larger transmission frequency range, both LTE bands have the same target power (or the band with the larger transmission frequency range has a higher target power), and both LTE bands share the same transmission path and signal characteristics, SAR was only assessed for the band with the larger transmission frequency range.

This device supports 64QAM on the uplink and 256QAM on the downlink for LTE Operations. Conducted powers for 64QAM uplink configurations were measured per Section 5.1 of FCC KDB Publication 941225 D05v02r05. SAR was not required for 64QAM since the highest maximum output power for 64 QAM is $\leq \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg, per Section 5.2.4 of FCC KDB Publication 941225 D05v02r05.

This device supports both Power Class 2 (PC2) and Power Class 3 (PC3) for LTE Band 41. Per May 2017 TCB Workshop Notes, SAR tests were performed with Power Class 3 (given the specific UL/DL limitations for Power Class 2). Additionally, SAR testing for the power class condition was evaluated for the highest

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 13 of 116

configuration in Power Class 3 for each test configuration to confirm the results were scalable linearly (See Section 14.2).

1.7 Guidance Applied

- FCC KDB Publication 941225 D01v03r01, D05v02r04, D05Av01r02 (2G/3G/4G)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 616217 D04v01r02 (Tablet)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)
- May 2017 TCB Workshop Notes (LTE Band 41 Power Class 2/3)
- April 2018 TCB Workshop Notes (LTE Carrier Aggregation)

1.8 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 11.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 14 of 116

LTE Information				
FCC ID	BCGA2200			
Form Factor	Tablet Device			
Frequency Range of each LTE transmission band	LTE Band 71 (665.5 - 695.5 MHz) LTE Band 12 (699.7 - 715.3 MHz) LTE Band 17 (706.5 - 713.5 MHz) LTE Band 13 (779.5 - 784.5 MHz) LTE Band 14 (790.5 - 795.5 MHz) LTE Band 26 (Cell) (814.7 - 848.3 MHz) LTE Band 5 (Cell) (824.7 - 848.3 MHz) LTE Band 66 (AWS) (1710.7 - 1779.3 MHz) LTE Band 4 (AWS) (1710.7 - 1754.3 MHz) LTE Band 25 (PCS) (1850.7 - 1914.3 MHz) LTE Band 2 (PCS) (1850.7 - 1909.3 MHz) LTE Band 30 (2307.5 - 2312.5 MHz) LTE Band 7 (2502.5 - 2567.5 MHz) LTE Band 41 (2498.5 - 2687.5 MHz)			
Channel Bandwidths	LTE Band 71: 5 MHz, 10 MHz, 15 MHz, 20 MHz LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz LTE Band 17: 5 MHz, 10 MHz LTE Band 13: 5 MHz, 10 MHz LTE Band 14: 5 MHz, 10 MHz LTE Band 26 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz LTE Band 66 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz LTE Band 25 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz LTE Band 30: 5 MHz, 10 MHz LTE Band 7: 5 MHz, 10 MHz, 15 MHz, 20 MHz LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz			
Channel Numbers and Frequencies (MHz)	Low	Low-Mid	Mid	Mid-High
LTE Band 71: 5 MHz	665.5 (133147)	680.5 (133297)	695.5 (133447)	
LTE Band 71: 10 MHz	668 (133172)	680.5 (133297)	693 (133422)	
LTE Band 71: 15 MHz	670.5 (133197)	680.5 (133297)	690.5 (133397)	
LTE Band 71: 20 MHz	673 (133222)	680.5 (133297)	688 (133372)	
LTE Band 12: 1.4 MHz	699.7 (23017)	707.5 (23095)	715.3 (23173)	
LTE Band 12: 3 MHz	700.5 (23025)	707.5 (23095)	714.5 (23165)	
LTE Band 12: 5 MHz	701.5 (23035)	707.5 (23095)	713.5 (23155)	
LTE Band 12: 10 MHz	704 (23060)	707.5 (23095)	711 (23130)	
LTE Band 17: 5 MHz	706.5 (23755)	710 (23790)	713.5 (23825)	
LTE Band 17: 10 MHz	709 (23780)	710 (23790)	711 (23800)	
LTE Band 13: 5 MHz	779.5 (23205)	782 (23230)	784.5 (23255)	
LTE Band 13: 10 MHz	N/A	782 (23230)	N/A	
LTE Band 14: 5 MHz	790.5 (23305)	793 (23330)	795.5 (23355)	
LTE Band 14: 10 MHz	N/A	793 (23330)	N/A	
LTE Band 26 (Cell): 1.4 MHz	814.7 (26697)	831.5 (26865)	848.3 (27033)	
LTE Band 26 (Cell): 3 MHz	815.5 (26705)	831.5 (26865)	847.5 (27025)	
LTE Band 26 (Cell): 5 MHz	816.5 (26715)	831.5 (26865)	846.5 (27015)	
LTE Band 26 (Cell): 10 MHz	819 (26740)	831.5 (26865)	844 (26990)	
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)	836.5 (20525)	848.3 (20643)	
LTE Band 5 (Cell): 3 MHz	825.5 (20415)	836.5 (20525)	847.5 (20635)	
LTE Band 5 (Cell): 5 MHz	826.5 (20425)	836.5 (20525)	846.5 (20625)	
LTE Band 5 (Cell): 10 MHz	829 (20450)	836.5 (20525)	844 (20600)	
LTE Band 66 (AWS): 1.4 MHz	1710.7 (131979)	1745 (132322)	1779.3 (132665)	
LTE Band 66 (AWS): 3 MHz	1711.5 (131987)	1745 (132322)	1778.5 (132657)	
LTE Band 66 (AWS): 5 MHz	1712.5 (131997)	1745 (132322)	1777.5 (132647)	
LTE Band 66 (AWS): 10 MHz	1715 (132022)	1745 (132322)	1775 (132622)	
LTE Band 66 (AWS): 15 MHz	1717.5 (132047)	1745 (132322)	1772.5 (132597)	
LTE Band 66 (AWS): 20 MHz	1720 (132072)	1745 (132322)	1770 (132572)	
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19967)	1732.5 (20175)	1754.3 (20393)	
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)	1732.5 (20175)	1753.5 (20385)	
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)	1732.5 (20175)	1752.5 (20375)	
LTE Band 4 (AWS): 10 MHz	1715 (20000)	1732.5 (20175)	1750 (20350)	
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)	1732.5 (20175)	1747.5 (20325)	
LTE Band 4 (AWS): 20 MHz	1720 (20050)	1732.5 (20175)	1745 (20300)	
LTE Band 25 (PCS): 1.4 MHz	1850.7 (26047)	1882.5 (26365)	1914.3 (26683)	
LTE Band 25 (PCS): 3 MHz	1851.5 (26055)	1882.5 (26365)	1913.5 (26675)	
LTE Band 25 (PCS): 5 MHz	1852.5 (26065)	1882.5 (26365)	1912.5 (26665)	
LTE Band 25 (PCS): 10 MHz	1855 (26090)	1882.5 (26365)	1910 (26640)	
LTE Band 25 (PCS): 15 MHz	1857.5 (26115)	1882.5 (26365)	1907.5 (26615)	
LTE Band 25 (PCS): 20 MHz	1860 (26140)	1882.5 (26365)	1905 (26590)	
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)	1880 (18900)	1909.3 (19193)	
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)	1880 (18900)	1908.5 (19185)	
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)	1880 (18900)	1907.5 (19175)	
LTE Band 2 (PCS): 10 MHz	1855 (18650)	1880 (18900)	1905 (19150)	
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)	1880 (18900)	1902.5 (19125)	
LTE Band 2 (PCS): 20 MHz	1860 (18700)	1880 (18900)	1900 (19100)	
LTE Band 30: 5 MHz	2307.5 (27685)	2310 (27710)	2312.5 (27735)	
LTE Band 30: 10 MHz	N/A	2310 (27710)	N/A	
LTE Band 7: 5 MHz	2502.5 (20775)	2535 (21100)	2567.5 (21425)	
LTE Band 7: 10 MHz	2505 (20800)	2535 (21100)	2565 (21400)	
LTE Band 7: 15 MHz	2507.5 (20825)	2535 (21100)	2562.5 (21375)	
LTE Band 41: 5 MHz	2510 (20850)	2535 (21100)	2560 (21350)	
LTE Band 41: 10 MHz	2506 (39750)	2549.5 (40185)	2636.5 (41055)	2680 (41490)
LTE Band 41: 15 MHz	2506 (39750)	2549.5 (40185)	2636.5 (41055)	2680 (41490)
LTE Band 41: 20 MHz	2506 (39750)	2549.5 (40185)	2636.5 (41055)	2680 (41490)
UE Category	DL UE Cat 16 (QPSK, 16QAM, 64QAM, 256QAM), UL UE Cat 13 (QPSK, 16QAM, 64QAM)			
Modulations Supported in UL	QPSK, 16QAM, 64QAM			
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.57 (manufacturer attestation to be provided)	YES			
A-MPR (Additional MPR) disabled for SAR Testing?	YES			
LTE Carrier Aggregation Possible Combinations	The technical description includes all the possible carrier aggregation combinations			
LTE Additional Information	This device does not support full CA features on 3GPP Release 13. It supports carrier aggregation features as shown in Section 8 and Appendix H. All other uplink communications are identical to the Release 8 specifications. Uplink communications are done on the PCC unless otherwise specified. The following LTE Release 13 features are not supported: Relay, HetNet, Enhanced MIMO, eICIC, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.			

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 15 of 116

3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 16 of 116

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1 point
Sample SAR Area
Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 17 of 116

5 TEST CONFIGURATION POSITIONS

5.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

5.2 SAR Testing for Tablet per KDB Publication 616217 D04v01r02

Per FCC KDB Publication 616217 D04v01r02, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. The SAR Exclusion Threshold in KDB 447498 D01v06 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 18 of 116

6 RF EXPOSURE LIMITS

6.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

6.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 19 of 116

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

7.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

7.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

7.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

7.4 SAR Measurement Conditions for UMTS

7.4.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 20 of 116

7.4.2 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

7.4.3 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

7.4.4 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

7.4.5 SAR Measurement Conditions for DC-HSDPA

SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

7.5 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

7.5.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 21 of 116

7.5.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

7.5.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

7.5.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

7.5.5 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05v02r04. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

7.5.6 Downlink Only Carrier Aggregation

Conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. Additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band. Per FCC KDB Publication 941225 D05Av01r02, no SAR

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 22 of 116

measurements are required for downlink only carrier aggregation configurations when the average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive.

7.6 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

7.6.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

7.6.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg.

7.6.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

7.6.4 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 23 of 116

- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

7.6.5 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

7.6.6 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.7.6).

7.6.7 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required.

7.6.8 MIMO SAR considerations

Per KDB Publication 248227 D01v02r02, the simultaneous SAR provisions in KDB Publication 447498 D01v06 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is < 1.6 W/kg, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 24 of 116

8.1 GSM Conducted Powers

Table 8-1
Conducted Power Antenna C

Maximum Burst-Averaged Output Power					
Band	Channel	GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
		GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	26.86	23.70	24.69	23.68
	190	26.80	23.62	24.67	23.62
	251	26.77	23.65	24.70	23.55
GSM 1900	512	21.64	18.68	21.61	18.60
	661	21.48	18.55	21.51	18.52
	810	21.67	18.69	21.67	18.68
Calculated Maximum Frame-Averaged Output Power					
Band	Channel	GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
		GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	17.83	17.68	15.66	17.66
	190	17.77	17.60	15.64	17.60
	251	17.74	17.63	15.67	17.53
GSM 1900	512	12.61	12.66	12.58	12.58
	661	12.45	12.53	12.48	12.50
	810	12.64	12.67	12.64	12.66
GSM 850	Frame	17.97	17.98	14.97	16.98
GSM 1900	Avg. Targets:	12.17	12.18	12.17	12.18

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 25 of 116

Table 8-2
Conducted Power Antenna D

Maximum Burst-Averaged Output Power					
		GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
Band	Channel	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	28.14	25.50	22.74	21.73
	190	28.10	25.45	22.72	21.71
	251	28.06	25.42	22.69	21.69
GSM 1900	512	20.91	17.87	20.87	17.84
	661	20.95	17.95	20.96	17.95
	810	20.98	17.97	20.96	17.95
Calculated Maximum Frame-Averaged Output Power					
		GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
Band	Channel	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	19.11	19.48	13.71	15.71
	190	19.07	19.43	13.69	15.69
	251	19.03	19.40	13.66	15.67
GSM 1900	512	11.88	11.85	11.84	11.82
	661	11.92	11.93	11.93	11.93
	810	11.95	11.95	11.93	11.93
GSM 850	Frame Avg.Targets:	18.47	18.73	12.97	14.98
GSM 1900		11.47	11.48	11.47	11.48

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 26 of 116

Note:

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
3. EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: C
GPRS Multislot class: 10 (Max 2 Tx uplink slots)
EDGE Multislot class: 10 (Max 2 Tx uplink slots)
DTM Multislot Class: N/A



Figure 8-1
Power Measurement Setup

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 27 of 116

8.2 UMTS Conducted Powers

Table 8-3
Conducted Power Antenna C

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	17.65	17.60	17.58	13.25	13.28	13.20	12.90	12.99	13.08	-
6	HSDPA	Subtest 1	17.61	17.51	17.48	13.25	13.25	13.18	13.01	13.01	13.03	0
6		Subtest 2	17.62	17.53	17.49	13.20	13.26	13.16	12.93	12.95	12.99	0
6		Subtest 3	17.64	17.56	17.47	13.19	13.24	13.17	12.94	12.94	12.97	0.5
6		Subtest 4	17.64	17.57	17.47	13.20	13.25	13.19	12.90	12.98	12.97	0.5
6	HSUPA	Subtest 1	17.51	17.48	17.39	13.19	13.27	13.15	13.02	13.05	13.01	0
6		Subtest 2	17.58	17.51	17.41	13.16	13.24	13.16	12.93	12.96	12.89	2
6		Subtest 3	17.57	17.51	17.39	13.21	13.25	13.16	12.98	12.95	12.91	1
6		Subtest 4	17.56	17.51	17.37	13.20	13.25	13.15	13.01	13.03	13.01	2
6		Subtest 5	17.53	17.46	17.39	13.26	13.27	13.18	13.04	13.02	13.02	0
8	DC-HSDPA	Subtest 1	17.55	17.52	17.50	13.25	13.27	13.14	13.06	13.04	13.05	0
8		Subtest 2	17.55	17.41	17.53	13.15	13.21	13.11	13.02	13.02	13.01	0
8		Subtest 3	17.64	17.54	17.48	13.17	13.21	13.13	13.00	13.02	13.03	0.5
8		Subtest 4	17.62	17.55	17.48	13.20	13.24	13.15	13.00	13.03	13.03	0.5

Table 8-4
Conducted Power Antenna D

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	19.12	19.04	19.14	13.14	13.10	13.07	12.00	11.92	11.90	-
6	HSDPA	Subtest 1	19.17	19.13	19.12	13.15	13.19	13.14	12.00	11.72	11.66	0
6		Subtest 2	19.17	19.14	19.10	13.10	13.17	13.11	11.95	11.70	11.61	0
6		Subtest 3	19.18	19.14	19.04	13.10	13.15	13.10	11.95	11.71	11.59	0.5
6		Subtest 4	19.20	19.16	19.11	13.12	13.16	13.10	11.97	11.71	11.60	0.5
6	HSUPA	Subtest 1	19.14	19.16	19.10	13.05	13.07	13.00	12.00	11.75	11.77	0
6		Subtest 2	19.17	19.20	19.15	13.17	13.16	13.07	11.88	11.66	11.64	2
6		Subtest 3	19.16	19.15	19.11	13.12	13.10	13.02	11.95	11.71	11.71	1
6		Subtest 4	19.16	19.19	19.12	13.19	13.16	13.06	11.89	11.66	11.65	2
6		Subtest 5	19.16	19.14	19.12	13.20	13.20	13.10	11.98	11.73	11.75	0
8	DC-HSDPA	Subtest 1	19.03	19.12	19.11	13.14	13.11	13.02	11.93	11.66	11.68	0
8		Subtest 2	19.16	19.14	19.05	13.06	13.02	12.88	11.91	11.57	11.65	0
8		Subtest 3	19.17	19.17	19.04	13.07	13.02	12.97	11.87	11.62	11.63	0.5
8		Subtest 4	19.17	19.19	19.11	13.06	13.10	13.03	11.87	11.66	11.65	0.5

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 28 of 116

DC-HSDPA considerations

- 3GPP Specification 34.121-1 Release 8 Ver 8.10.0 was used for DC-HSDPA guidance
- H-Set 12 (QPSK) was confirmed to be used during DC-HSDPA measurements
- The DUT supports UE category 24 for HSDPA



Figure 8-2
Power Measurement Setup

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 29 of 116

8.3 LTE Conducted Powers

8.3.1 LTE Band 71

Table 8-5
LTE Band 71 Conducted Powers – 20 MHz Bandwidth – Antenna C

LTE Band 71 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	18.04	0	0
	1	50	17.99		0
	1	99	18.05		0
	50	0	17.82	0-1	0
	50	25	17.83		0
	50	50	17.93		0
	100	0	17.91		0
16QAM	1	0	18.07	0-1	0
	1	50	17.93		0
	1	99	18.06		0
	50	0	17.92	0-2	0
	50	25	17.84		0
	50	50	17.92		0
	100	0	17.91		0
64QAM	1	0	18.08	0-2	0
	1	50	17.99		0
	1	99	17.97		0
	50	0	17.65	0-3	0
	50	25	17.68		0
	50	50	17.75		0
	100	0	17.73		0

Note: LTE Band 71 at 20 MHz does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-6
LTE Band 71 Conducted Powers - 15 MHz Bandwidth – Antenna C

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	18.02	0	0
	1	36	18.07		0
	1	74	17.98		0
	36	0	17.96	0-1	0
	36	18	17.94		0
	36	37	17.89		0
	75	0	17.91		0
16QAM	1	0	18.01	0-1	0
	1	36	18.02		0
	1	74	17.97		0
	36	0	17.76	0-2	0
	36	18	17.75		0
	36	37	17.69		0
	75	0	17.80		0
64QAM	1	0	18.03	0-2	0
	1	36	18.04		0
	1	74	18.02		0
	36	0	17.81	0-3	0
	36	18	17.83		0
	36	37	17.79		0
	75	0	17.86		0

Note: LTE Band 71 at 15 MHz does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 30 of 116

Table 8-7
LTE Band 71 Conducted Powers - 10 MHz Bandwidth – Antenna C

LTE Band 71 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.10	18.03	17.83	0	0
	1	25	17.88	17.92	17.80		0
	1	49	17.86	17.81	17.89		0
	25	0	17.90	17.98	17.77	0-1	0
	25	12	17.88	17.92	17.78		0
	25	25	17.92	17.93	17.85		0
16QAM	50	0	17.87	17.96	17.80	0	0
	1	0	18.06	18.01	17.90	0-1	0
	1	25	17.85	17.92	17.93		0
	1	49	17.89	17.83	17.95		0
	25	0	17.65	17.57	17.51	0-2	0
	25	12	17.64	17.54	17.50		0
25	25	17.70	17.54	17.49	0		
64QAM	50	0	17.59	17.50	17.47	0	0
	1	0	18.01	17.97	17.74	0-2	0
	1	25	17.81	17.92	17.66		0
	1	49	17.73	17.86	17.74		0
	25	0	17.63	17.60	17.51	0-3	0
	25	12	17.59	17.53	17.51		0
25	25	17.65	17.56	17.54	0		
	50	0	17.62	17.54	17.49		0

Table 8-8
LTE Band 71 Conducted Powers - 5 MHz Bandwidth – Antenna C

LTE Band 71 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.08	17.84	17.72	0	0
	1	12	17.87	17.84	17.73		0
	1	24	17.84	17.87	17.71		0
	12	0	17.87	17.76	17.76	0-1	0
	12	6	17.78	17.75	17.76		0
	12	13	17.76	17.79	17.79		0
16QAM	25	0	17.79	17.78	17.70	0-1	0
	1	0	18.07	17.87	17.75		0
	1	12	17.93	17.95	17.77		0
	1	24	17.88	17.94	17.80	0-2	0
	12	0	17.59	17.49	17.49		0
	12	6	17.48	17.51	17.50		0
64QAM	12	13	17.48	17.52	17.51	0-2	0
	25	0	17.49	17.46	17.47		0
	1	0	18.06	17.79	17.78		0-2
	1	12	17.87	17.73	17.83	0	
	1	24	17.86	17.71	17.70	0	
	12	0	17.65	17.56	17.51	0-3	0
12	6	17.58	17.59	17.55	0		
12	13	17.61	17.61	17.58	0		
25	0	17.58	17.58	17.54	0		

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device		Page 31 of 116

Table 8-9
LTE Band 71 Conducted Powers - 20 MHz Bandwidth – Antenna D

LTE Band 71 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz) Conducted Power [dBm]		
QPSK	1	0	16.89	0	0
	1	50	16.86		0
	1	99	16.88		0
	50	0	16.84	0-1	0
	50	25	16.79		0
	50	50	16.70		0
	100	0	16.83		0
16QAM	1	0	16.90	0-1	0
	1	50	16.80		0
	1	99	16.78		0
	50	0	16.37	0-2	0
	50	25	16.42		0
	50	50	16.31		0
	100	0	16.46		0
64QAM	1	0	16.89	0-2	0
	1	50	16.85		0
	1	99	16.79		0
	50	0	16.60	0-3	0
	50	25	16.67		0
	50	50	16.55		0
	100	0	16.70		0

Note: LTE Band 71 at 20 MHz does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-10
LTE Band 71 Conducted Powers - 15 MHz Bandwidth – Antenna D

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz) Conducted Power [dBm]		
QPSK	1	0	16.82	0	0
	1	36	16.93		0
	1	74	16.72		0
	36	0	17.02	0-1	0
	36	18	16.97		0
	36	37	16.85		0
	75	0	17.01		0
16QAM	1	0	16.96	0-1	0
	1	36	16.99		0
	1	74	16.84		0
	36	0	17.01	0-2	0
	36	18	16.92		0
	36	37	16.82		0
	75	0	16.93		0
64QAM	1	0	16.99	0-2	0
	1	36	16.98		0
	1	74	16.94		0
	36	0	16.90	0-3	0
	36	18	16.89		0
	36	37	16.73		0
	75	0	16.92		0

Note: LTE Band 71 at 15 MHz does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 32 of 116

Table 8-11
LTE Band 71 Conducted Powers - 10 MHz Bandwidth – Antenna D

LTE Band 71 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	16.95	16.83	16.72	0	0
	1	25	16.82	16.72	16.67		0
	1	49	16.73	16.63	16.64		0
	25	0	16.81	16.75	16.74	0-1	0
	25	12	16.80	16.77	16.72		0
	25	25	16.80	16.70	16.70		0
	50	0	16.84	16.81	16.72		0
16QAM	1	0	16.95	16.90	16.75	0-1	0
	1	25	16.94	16.87	16.74		0
	1	49	16.70	16.78	16.86		0
	25	0	16.79	16.75	16.65	0-2	0
	25	12	16.82	16.76	16.69		0
	25	25	16.78	16.68	16.62		0
	50	0	16.82	16.76	16.68		0
64QAM	1	0	16.95	16.91	16.94	0-2	0
	1	25	16.93	16.90	16.81		0
	1	49	16.78	16.67	16.87		0
	25	0	16.67	16.66	16.60	0-3	0
	25	12	16.64	16.69	16.59		0
	25	25	16.67	16.62	16.55		0
	50	0	16.73	16.75	16.60		0

Table 8-12
LTE Band 71 Conducted Powers - 5 MHz Bandwidth – Antenna D

LTE Band 71 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	16.95	16.77	16.53	0	0
	1	12	16.87	16.78	16.52		0
	1	24	16.93	16.71	16.55		0
	12	0	16.83	16.77	16.60	0-1	0
	12	6	16.76	16.74	16.62		0
	12	13	16.78	16.73	16.65		0
16QAM	25	0	16.76	16.76	16.62		0
	1	0	16.95	16.93	16.63	0-1	0
	1	12	16.89	16.82	16.60		0
	1	24	16.94	16.70	16.66		0
	12	0	16.85	16.78	16.56	0-2	0
	12	6	16.75	16.78	16.52		0
12	13	16.79	16.75	16.55	0		
64QAM	25	0	16.77	16.74	16.60		0
	1	0	16.95	16.86	16.79	0-2	0
	1	12	16.94	16.94	16.74		0
	1	24	16.95	16.73	16.69		0
	12	0	16.79	16.77	16.55	0-3	0
	12	6	16.64	16.77	16.52		0
12	13	16.67	16.74	16.54	0		
	25	0	16.70	16.74	16.54		0

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 33 of 116

8.3.2 LTE Band 12

Table 8-13
LTE Band 12 Conducted Powers - 10 MHz Bandwidth – Antenna C

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	17.38	0	0
	1	25	17.23		0
	1	49	17.43		0
	25	0	17.28	0-1	0
	25	12	17.24		0
	25	25	17.40		0
	50	0	17.25		0
16QAM	1	0	17.33	0-1	0
	1	25	17.23		0
	1	49	17.45		0
	25	0	16.87	0-2	0
	25	12	16.84		0
	25	25	17.00		0
	50	0	16.81		0
64QAM	1	0	17.38	0-2	0
	1	25	17.20		0
	1	49	17.46		0
	25	0	16.86	0-3	0
	25	12	16.81		0
	25	25	16.99		0
	50	0	16.86		0

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-14
LTE Band 12 Conducted Powers - 5 MHz Bandwidth – Antenna C

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.43	17.32	17.46	0	0
	1	12	17.50	17.30	17.39		0
	1	24	17.45	17.37	17.39		0
	12	0	17.34	17.29	17.40	0-1	0
	12	6	17.43	17.30	17.34		0
	12	13	17.38	17.31	17.29		0
	25	0	17.43	17.27	17.35		0
16QAM	1	0	17.27	17.43	17.48	0-1	0
	1	12	17.38	17.28	17.39		0
	1	24	17.41	17.32	17.34		0
	12	0	17.04	16.95	17.06	0-2	0
	12	6	17.11	16.94	17.02		0
	12	13	17.07	17.02	16.94		0
	25	0	17.05	17.03	17.02		0
64QAM	1	0	17.26	17.22	17.42	0-2	0
	1	12	17.41	17.17	17.15		0
	1	24	17.36	17.25	17.08		0
	12	0	17.02	16.94	17.02	0-3	0
	12	6	17.13	16.91	16.96		0
	12	13	17.09	16.92	16.90		0
	25	0	17.13	16.90	16.92		0

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 34 of 116

Table 8-15
LTE Band 12 Conducted Powers - 3 MHz Bandwidth – Antenna C

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.31	17.34	17.32	0	0
	1	7	17.36	17.40	17.32		0
	1	14	17.37	17.36	17.27		0
	8	0	17.32	17.34	17.32	0-1	0
	8	4	17.34	17.35	17.29		0
	8	7	17.41	17.32	17.32		0
16QAM	15	0	17.38	17.33	17.30		0
	1	0	17.36	17.31	17.44	0-1	0
	1	7	17.48	17.47	17.41		0
	1	14	17.44	17.32	17.41		0
	8	0	17.11	17.15	17.12	0-2	0
	8	4	17.15	17.12	17.09		0
8	7	17.21	17.16	17.13	0		
64QAM	15	0	17.11	17.13	17.04		0
	1	0	17.34	17.37	17.50	0-2	0
	1	7	17.40	17.40	17.44		0
	1	14	17.47	17.36	17.43		0
	8	0	17.24	17.27	17.26	0-3	0
	8	4	17.27	17.25	17.24		0
8	7	17.36	17.34	17.28	0		
	15	0	17.27	17.21	17.19		0

Table 8-16
LTE Band 12 Conducted Powers - 1.4 MHz Bandwidth – Antenna C

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.30	17.44	17.24	0	0
	1	2	17.29	17.40	17.21		0
	1	5	17.33	17.43	17.24		0
	3	0	17.22	17.32	17.14		0
	3	2	17.21	17.31	17.14		0
	3	3	17.22	17.31	17.17	0	
	6	0	17.21	17.29	17.15	0-1	0
16QAM	1	0	17.23	17.41	17.21	0-1	0
	1	2	17.24	17.37	17.15		0
	1	5	17.30	17.34	17.27		0
	3	0	17.07	17.21	17.01		0
	3	2	17.09	17.15	16.99		0
	3	3	17.06	17.19	17.04	0	
	6	0	17.01	17.10	16.93	0-2	0
64QAM	1	0	17.34	17.46	17.17	0-2	0
	1	2	17.29	17.39	17.15		0
	1	5	17.35	17.42	17.20		0
	3	0	17.01	17.12	16.93		0
	3	2	17.07	17.03	16.92		0
	3	3	17.04	17.04	16.96	0	
	6	0	16.99	17.01	16.94	0-3	0

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 35 of 116

Table 8-17
LTE Band 12 Conducted Powers - 10 MHz Bandwidth - Antenna D

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel 23095 (707.5 MHz)	MPR Allowed per 3GPP [dB]	MPR [dB]
			Conducted Power [dBm]		
QPSK	1	0	17.08	0	0
	1	25	16.97		0
	1	49	17.17		0
	25	0	17.01	0-1	0
	25	12	16.97		0
	25	25	17.08		0
	50	0	17.01		0
16QAM	1	0	17.09	0-1	0
	1	25	17.04		0
	1	49	17.15		0
	25	0	16.66	0-2	0
	25	12	16.65		0
	25	25	16.76		0
	50	0	16.67		0
64QAM	1	0	17.07	0-2	0
	1	25	16.98		0
	1	49	17.06		0
	25	0	16.80	0-3	0
	25	12	16.71		0
	25	25	16.74		0
	50	0	16.71		0

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-18
LTE Band 12 Conducted Powers - 5 MHz Bandwidth - Antenna D

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.12	17.08	17.03	0	0
	1	12	17.19	17.04	17.05		0
	1	24	17.18	16.94	17.10		0
	12	0	17.05	17.16	17.05	0-1	0
	12	6	17.12	17.14	17.02		0
	12	13	17.13	17.11	16.98		0
	25	0	17.13	17.14	17.03		0
16QAM	1	0	17.03	17.14	17.14	0-1	0
	1	12	17.10	17.09	17.09		0
	1	24	17.11	17.02	17.11		0
	12	0	16.93	17.03	16.93	0-2	0
	12	6	16.95	17.01	16.87		0
	12	13	16.99	16.98	16.84		0
	25	0	16.98	16.98	16.84		0
64QAM	1	0	17.04	17.18	17.09	0-2	0
	1	12	17.14	17.14	17.08		0
	1	24	17.12	17.06	17.01		0
	12	0	16.88	16.94	16.85	0-3	0
	12	6	16.96	16.91	16.80		0
	12	13	16.98	16.87	16.74		0
	25	0	16.96	16.91	16.79		0

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 36 of 116

Table 8-19
LTE Band 12 Conducted Powers - 3 MHz Bandwidth - Antenna D

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	16.92	17.05	16.96	0	0
	1	7	17.00	17.12	16.98		0
	1	14	17.04	17.03	16.95		0
	8	0	17.05	17.12	17.01	0-1	0
	8	4	17.06	17.11	16.98		0
	8	7	17.14	17.09	17.04		0
	15	0	17.07	17.13	17.01		0
16QAM	1	0	17.06	17.16	17.06	0-1	0
	1	7	17.14	17.15	17.08		0
	1	14	17.15	17.10	17.02		0
	8	0	16.93	17.06	16.89	0-2	0
	8	4	16.95	17.03	16.86		0
	8	7	17.02	17.04	16.88		0
	15	0	16.94	16.98	16.86		0
64QAM	1	0	17.01	17.12	17.07	0-2	0
	1	7	17.05	17.18	17.02		0
	1	14	17.16	17.03	16.98		0
	8	0	16.95	17.01	16.92	0-3	0
	8	4	16.94	17.03	16.88		0
	8	7	17.03	16.98	16.93		0
	15	0	16.92	16.98	16.86		0

Table 8-20
LTE Band 12 Conducted Powers - 1.4 MHz Bandwidth - Antenna D

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.11	17.19	17.13	0	0
	1	2	17.07	17.16	17.16		0
	1	5	17.12	17.19	17.16		0
	3	0	17.12	17.19	17.10		0
	3	2	17.13	17.19	17.09		0
	3	3	17.14	17.18	17.09		0
	6	0	17.11	17.18	17.08	0-1	0
16QAM	1	0	17.01	17.15	16.99	0-1	0
	1	2	16.99	17.10	17.01		0
	1	5	17.06	17.16	17.05		0
	3	0	16.91	16.98	16.88		0
	3	2	16.92	16.95	16.87		0
	3	3	16.89	16.96	16.85		0
	6	0	16.84	16.95	16.86	0-2	0
64QAM	1	0	17.06	17.18	17.03	0-2	0
	1	2	17.02	17.17	17.13		0
	1	5	17.06	17.19	17.09		0
	3	0	16.98	17.14	17.15		0
	3	2	16.96	17.10	17.07		0
	3	3	16.99	17.09	17.10		0
	6	0	16.95	17.12	16.88	0-3	0

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 37 of 116

8.3.3 LTE Band 13

Table 8-21
LTE Band 13 Conducted Powers - 10 MHz Bandwidth - Antenna C

LTE Band 13 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	18.07	0	0
	1	25	17.70		0
	1	49	17.65		0
	25	0	17.72	0-1	0
	25	12	17.73		0
	25	25	17.75		0
	50	0	17.72		0
16QAM	1	0	18.09	0-1	0
	1	25	17.76		0
	1	49	17.79		0
	25	0	17.70	0-2	0
	25	12	17.54		0
	25	25	17.52		0
	50	0	17.53		0
64QAM	1	0	18.09	0-2	0
	1	25	17.68		0
	1	49	17.67		0
	25	0	17.30	0-3	0
	25	12	17.29		0
	25	25	17.28		0
	50	0	17.33		0

Table 8-22
LTE Band 13 Conducted Powers - 5 MHz Bandwidth - Antenna C

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	18.06	0	0
	1	12	17.92		0
	1	24	17.97		0
	12	0	18.08	0-1	0
	12	6	17.99		0
	12	13	18.01		0
	25	0	18.00		0
16QAM	1	0	18.06	0-1	0
	1	12	17.93		0
	1	24	17.92		0
	12	0	17.58	0-2	0
	12	6	17.49		0
	12	13	17.53		0
	25	0	17.46		0
64QAM	1	0	18.05	0-2	0
	1	12	17.87		0
	1	24	17.92		0
	12	0	17.69	0-3	0
	12	6	17.66		0
	12	13	17.64		0
	25	0	17.59		0

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 38 of 116

Table 8-23
LTE Band 13 Conducted Powers - 10 MHz Bandwidth - Antenna D

LTE Band 13 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	17.89	0	0
	1	25	17.70		0
	1	49	17.62		0
	25	0	17.67	0-1	0
	25	12	17.59		0
	25	25	17.48		0
	50	0	17.62		0
16QAM	1	0	17.98	0-1	0
	1	25	17.57		0
	1	49	17.41		0
	25	0	17.38	0-2	0
	25	12	17.31		0
	25	25	17.37		0
	50	0	17.42		0
64QAM	1	0	17.99	0-2	0
	1	25	17.49		0
	1	49	17.52		0
	25	0	17.49	0-3	0
	25	12	17.37		0
	25	25	17.34		0
	50	0	17.38		0

Table 8-24
LTE Band 13 Conducted Powers - 5 MHz Bandwidth - Antenna D

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	17.95	0	0
	1	12	17.78		0
	1	24	17.81		0
	12	0	18.00	0-1	0
	12	6	17.99		0
	12	13	18.00		0
	25	0	17.91		0
16QAM	1	0	17.97	0-1	0
	1	12	17.85		0
	1	24	17.86		0
	12	0	17.72	0-2	0
	12	6	17.71		0
	12	13	17.73		0
	25	0	17.66		0
64QAM	1	0	17.96	0-2	0
	1	12	17.79		0
	1	24	17.81		0
	12	0	17.69	0-3	0
	12	6	17.68		0
	12	13	17.69		0
	25	0	17.54		0

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 39 of 116

8.3.4 LTE Band 14

Table 8-25
LTE Band 14 Conducted Powers - 10 MHz Bandwidth – Antenna C

LTE Band 14 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz) Conducted Power [dBm]		
QPSK	1	0	17.86	0	0
	1	25	17.82		0
	1	49	18.04		0
	25	0	17.83	0-1	0
	25	12	17.81		0
	25	25	17.97		0
	50	0	17.83		0
16QAM	1	0	17.97	0-1	0
	1	25	17.95		0
	1	49	18.09		0
	25	0	17.58	0-2	0
	25	12	17.57		0
	25	25	17.74		0
	50	0	17.60		0
64QAM	1	0	17.85	0-2	0
	1	25	17.78		0
	1	49	18.03		0
	25	0	17.59	0-3	0
	25	12	17.56		0
	25	25	17.70		0
	50	0	17.60		0

Table 8-26
LTE Band 14 Conducted Powers - 5 MHz Bandwidth – Antenna C

LTE Band 14 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz) Conducted Power [dBm]		
QPSK	1	0	18.01	0	0
	1	12	17.94		0
	1	24	17.86		0
	12	0	18.02	0-1	0
	12	6	18.00		0
	12	13	17.99		0
	25	0	17.98		0
16QAM	1	0	18.04	0-1	0
	1	12	17.96		0
	1	24	17.92		0
	12	0	17.61	0-2	0
	12	6	17.61		0
	12	13	17.56		0
	25	0	17.58		0
64QAM	1	0	18.04	0-2	0
	1	12	17.90		0
	1	24	17.84		0
	12	0	17.63	0-3	0
	12	6	17.67		0
	12	13	17.65		0
	25	0	17.63		0

Note: LTE Band 14 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 40 of 116

Table 8-27
LTE Band 14 Conducted Powers - 10 MHz Bandwidth - Antenna D

LTE Band 14 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz) Conducted Power [dBm]		
QPSK	1	0	17.97	0	0
	1	25	17.89		0
	1	49	17.98		0
	25	0	17.94	0-1	0
	25	12	17.86		0
	25	25	17.92		0
	50	0	17.86		0
16QAM	1	0	17.92	0-1	0
	1	25	17.81		0
	1	49	17.94		0
	25	0	17.57	0-2	0
	25	12	17.48		0
	25	25	17.55		0
	50	0	17.45		0
64QAM	1	0	17.94	0-2	0
	1	25	17.90		0
	1	49	17.96		0
	25	0	17.59	0-3	0
	25	12	17.50		0
	25	25	17.56		0
	50	0	17.54		0

Table 8-28
LTE Band 14 Conducted Powers - 5 MHz Bandwidth - Antenna D

LTE Band 14 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz) Conducted Power [dBm]		
QPSK	1	0	17.98	0	0
	1	12	17.88		0
	1	24	17.93		0
	12	0	17.91	0-1	0
	12	6	17.92		0
	12	13	17.90		0
	25	0	17.91		0
16QAM	1	0	17.86	0-1	0
	1	12	17.90		0
	1	24	17.91		0
	12	0	17.59	0-2	0
	12	6	17.61		0
	12	13	17.60		0
	25	0	17.56		0
64QAM	1	0	17.98	0-2	0
	1	12	17.95		0
	1	24	17.87		0
	12	0	17.65	0-3	0
	12	6	17.60		0
	12	13	17.59		0
	25	0	17.61		0

Note: LTE Band 14 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 41 of 116

8.3.5 LTE Band 26

Table 8-29
LTE Band 26 (Cell) Conducted Powers - 10 MHz Bandwidth - Antenna C

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.93	18.88	18.65	0	0
	1	25	18.83	18.99	18.72		0
	1	49	18.78	18.88	18.75		0
	25	0	18.86	18.90	18.72	0-1	0
	25	12	18.83	18.92	18.76		0
	25	25	18.81	18.91	18.78		0
16QAM	50	0	18.85	18.91	18.76	0-1	0
	1	0	18.91	18.84	18.78		0
	1	25	18.81	18.95	18.81		0
	1	49	18.73	18.93	18.87	0-2	0
	25	0	18.53	18.57	18.35		0
	25	12	18.49	18.58	18.40		0
64QAM	25	25	18.47	18.61	18.42	0-2	0
	50	0	18.49	18.59	18.41		0
	1	0	18.95	18.88	18.88	0-2	0
	1	25	18.84	19.00	18.92		0
	1	49	18.72	18.95	18.90	0-3	0
	25	0	18.51	18.61	18.34		0
25	12	18.48	18.63	18.37	0		
64QAM	25	25	18.46	18.66	18.41	0-3	0
	50	0	18.49	18.60	18.39		0

Table 8-30
LTE Band 26 (Cell) Conducted Powers - 5 MHz Bandwidth - Antenna C

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.97	18.70	18.75	0	0
	1	12	18.91	18.66	18.86		0
	1	24	18.92	18.68	18.94		0
	12	0	18.95	18.79	18.86	0-1	0
	12	6	18.92	18.78	18.88		0
	12	13	18.93	18.79	18.93		0
16QAM	25	0	18.94	18.80	18.93	0-1	0
	1	0	19.00	18.74	18.77		0
	1	12	18.89	18.72	18.85		0
	1	24	18.93	18.75	18.93	0-2	0
	12	0	18.36	18.13	18.20		0
	12	6	18.31	18.14	18.24		0
64QAM	12	13	18.35	18.14	18.33	0-2	0
	25	0	18.31	18.15	18.28		0
	1	0	19.00	18.80	18.83	0-2	0
	1	12	18.98	18.79	18.91		0
	1	24	18.97	18.85	18.94	0-3	0
	12	0	18.39	18.31	18.38		0
12	6	18.37	18.27	18.42	0		
12	13	18.39	18.30	18.44	0		
	25	0	18.39	18.28	18.39		0

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 42 of 116

Table 8-31
LTE Band 26 (Cell) Conducted Powers - 3 MHz Bandwidth - Antenna C

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.94	18.68	18.81	0	0
	1	7	18.91	18.72	18.92		0
	1	14	18.85	18.67	18.86		0
	8	0	18.97	18.79	18.90	0-1	0
	8	4	18.98	18.78	18.96		0
	8	7	18.95	18.79	18.96		0
	15	0	18.97	18.79	18.98		0
16QAM	1	0	18.96	18.66	18.85	0-1	0
	1	7	18.95	18.64	18.92		0
	1	14	18.85	18.58	18.90		0
	8	0	18.62	18.42	18.52	0-2	0
	8	4	18.65	18.43	18.60		0
	8	7	18.59	18.45	18.62		0
	15	0	18.53	18.40	18.49		0
64QAM	1	0	18.95	18.65	18.96	0-2	0
	1	7	18.93	18.63	19.00		0
	1	14	18.94	18.62	18.95		0
	8	0	18.79	18.57	18.63	0-3	0
	8	4	18.77	18.59	18.67		0
	8	7	18.69	18.56	18.63		0
	15	0	18.69	18.50	18.61		0

Table 8-32
LTE Band 26 (Cell) Conducted Powers - 1.4 MHz Bandwidth - Antenna C

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.90	18.60	19.00	0	0
	1	2	18.89	18.56	18.98		0
	1	5	18.87	18.57	18.98		0
	3	0	18.93	18.65	18.86		0
	3	2	18.88	18.64	18.84		0
	3	3	18.86	18.66	18.84		0
	6	0	18.85	18.65	18.83	0-1	0
16QAM	1	0	18.91	18.84	18.96	0-1	0
	1	2	18.87	18.85	18.88		0
	1	5	18.85	18.81	18.87		0
	3	0	18.81	18.66	18.75		0
	3	2	18.75	18.67	18.76		0
	3	3	18.79	18.62	18.74		0
	6	0	18.70	18.58	18.69	0-2	0
64QAM	1	0	18.95	18.62	19.00	0-2	0
	1	2	18.92	18.60	18.99		0
	1	5	18.94	18.71	18.96		0
	3	0	18.99	18.60	18.80		0
	3	2	18.90	18.59	18.76		0
	3	3	18.93	18.65	18.79		0
	6	0	18.66	18.56	18.68	0-3	0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 43 of 116

Table 8-33
LTE Band 26 (Cell) Conducted Powers - 10 MHz Bandwidth – Antenna D

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.14	17.94	18.07	0	0
	1	25	18.03	17.87	18.08		0
	1	49	18.00	18.00	18.10		0
	25	0	17.93	17.84	18.01	0-1	0
	25	12	17.92	17.83	17.96		0
	25	25	17.94	17.90	17.99		0
	50	0	17.93	17.83	17.98		0
16QAM	1	0	18.19	18.06	18.10	0-1	0
	1	25	18.16	17.96	18.13		0
	1	49	18.14	18.05	18.16		0
	25	0	17.62	17.56	17.78	0-2	0
	25	12	17.63	17.54	17.68		0
	25	25	17.66	17.62	17.69		0
	50	0	17.63	17.54	17.69		0
64QAM	1	0	17.97	17.89	18.07	0-2	0
	1	25	17.90	17.81	18.02		0
	1	49	17.80	17.91	18.08		0
	25	0	17.52	17.52	17.68	0-3	0
	25	12	17.56	17.46	17.63		0
	25	25	17.57	17.51	17.64		0
	50	0	17.53	17.49	17.65		0

Table 8-34
LTE Band 26 (Cell) Conducted Powers - 5 MHz Bandwidth – Antenna D

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.15	17.92	18.01	0	0
	1	12	18.00	17.85	18.02		0
	1	24	18.06	17.90	18.08		0
	12	0	17.92	17.83	17.96	0-1	0
	12	6	17.91	17.80	17.97		0
	12	13	17.96	17.86	18.02		0
	25	0	17.94	17.81	17.96		0
16QAM	1	0	18.06	17.98	17.99	0-1	0
	1	12	17.97	17.84	18.00		0
	1	24	18.01	18.01	18.02		0
	12	0	17.64	17.58	17.60	0-2	0
	12	6	17.61	17.53	17.62		0
	12	13	17.63	17.61	17.68		0
	25	0	17.62	17.52	17.62		0
64QAM	1	0	18.16	17.99	18.04	0-2	0
	1	12	18.00	17.85	18.05		0
	1	24	18.02	17.92	18.07		0
	12	0	17.60	17.51	17.54	0-3	0
	12	6	17.56	17.52	17.61		0
	12	13	17.60	17.61	17.64		0
	25	0	17.52	17.49	17.55		0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 44 of 116

Table 8-35
LTE Band 26 (Cell) Conducted Powers - 3 MHz Bandwidth – Antenna D

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.09	17.88	17.98	0	0
	1	7	18.13	17.94	18.10		0
	1	14	18.03	17.88	18.01		0
	8	0	18.20	18.04	18.07	0-1	0
	8	4	18.18	18.03	18.12		0
	8	7	18.13	18.04	18.12		0
	15	0	18.16	18.03	18.13		0
16QAM	1	0	18.17	17.95	17.99	0-1	0
	1	7	18.19	18.02	18.07		0
	1	14	18.05	17.92	17.97		0
	8	0	17.98	17.73	17.81	0-2	0
	8	4	17.91	17.71	17.83		0
	8	7	17.88	17.72	17.84		0
	15	0	17.84	17.70	17.80		0
64QAM	1	0	18.11	17.87	18.12	0-2	0
	1	7	18.15	17.90	18.18		0
	1	14	18.02	17.82	18.12		0
	8	0	17.97	17.78	17.81	0-3	0
	8	4	17.93	17.78	17.82		0
	8	7	17.88	17.79	17.85		0
	15	0	17.86	17.70	17.79		0

Table 8-36
LTE Band 26 (Cell) Conducted Powers - 1.4 MHz Bandwidth – Antenna D

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.19	17.75	17.91	0	0
	1	2	18.20	17.76	17.90		0
	1	5	18.20	17.81	17.90		0
	3	0	18.09	17.91	17.95		0
	3	2	18.09	17.92	17.94		0
	3	3	18.10	17.92	17.94		0
	6	0	18.09	17.87	17.94	0-1	0
16QAM	1	0	18.18	18.04	18.18	0-1	0
	1	2	18.19	17.97	18.17		0
	1	5	18.16	18.02	18.17		0
	3	0	18.04	17.86	17.98		0
	3	2	18.02	17.88	17.94		0
	3	3	18.07	17.85	17.95		0
	6	0	17.95	17.84	17.96	0-2	0
64QAM	1	0	18.18	18.08	18.20	0-2	0
	1	2	18.19	18.16	18.20		0
	1	5	18.17	18.15	18.19		0
	3	0	18.11	18.06	18.03		0
	3	2	18.13	18.09	18.02		0
	3	3	18.14	18.07	18.01		0
	6	0	18.06	17.84	17.92	0-3	0

FCC ID: BCGA2200	 SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device
Page 45 of 116		

8.3.6 LTE Band 5

Table 8-37
LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth - Antenna C

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz) Conducted Power [dBm]		
QPSK	1	0	17.67	0	0
	1	25	17.44		0
	1	49	17.37		0
	25	0	17.60	0-1	0
	25	12	17.49		0
	25	25	17.41		0
	50	0	17.50		0
16QAM	1	0	17.56	0-1	0
	1	25	17.39		0
	1	49	17.26		0
	25	0	17.17	0-2	0
	25	12	17.08		0
	25	25	17.00		0
	50	0	17.07		0
64QAM	1	0	17.63	0-2	0
	1	25	17.46		0
	1	49	17.32		0
	25	0	17.20	0-3	0
	25	12	17.11		0
	25	25	17.00		0
	50	0	17.11		0

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-38
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth - Antenna C

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.70	17.62	17.58	0	0
	1	12	17.56	17.61	17.65		0
	1	24	17.55	17.65	17.70		0
	12	0	17.59	17.61	17.59	0-1	0
	12	6	17.56	17.61	17.63		0
	12	13	17.55	17.63	17.68		0
	25	0	17.59	17.60	17.65		0
16QAM	1	0	17.68	17.63	17.52	0-1	0
	1	12	17.54	17.64	17.59		0
	1	24	17.62	17.61	17.66		0
	12	0	17.19	17.18	17.13	0-2	0
	12	6	17.16	17.15	17.17		0
	12	13	17.16	17.16	17.18		0
	25	0	17.13	17.11	17.09		0
64QAM	1	0	17.59	17.47	17.53	0-2	0
	1	12	17.42	17.48	17.61		0
	1	24	17.44	17.52	17.62		0
	12	0	17.13	17.06	17.10	0-3	0
	12	6	17.11	17.08	17.12		0
	12	13	17.06	17.09	17.13		0
	25	0	17.05	17.07	17.13		0

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 46 of 116

Table 8-39
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth - Antenna C

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.63	17.50	17.53	0	0
	1	7	17.61	17.54	17.61		0
	1	14	17.55	17.48	17.52		0
	8	0	17.62	17.52	17.61	0-1	0
	8	4	17.56	17.52	17.65		0
	8	7	17.56	17.52	17.64		0
	15	0	17.56	17.54	17.63		0
16QAM	1	0	17.70	17.52	17.68	0-1	0
	1	7	17.68	17.54	17.69		0
	1	14	17.66	17.60	17.68		0
	8	0	17.15	17.11	17.14	0-2	0
	8	4	17.06	17.08	17.16		0
	8	7	17.04	17.11	17.15		0
	15	0	17.02	17.03	17.08		0
64QAM	1	0	17.51	17.46	17.66	0-2	0
	1	7	17.51	17.51	17.69		0
	1	14	17.42	17.44	17.67		0
	8	0	17.18	17.05	17.15	0-3	0
	8	4	17.13	17.02	17.21		0
	8	7	17.10	17.04	17.25		0
	15	0	17.09	17.02	17.15		0

Table 8-40
LTE Band 5 (Cell) Conducted Powers - 1.4 MHz Bandwidth - Antenna C

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.68	17.63	17.62	0	0
	1	2	17.65	17.60	17.59		0
	1	5	17.62	17.62	17.61		0
	3	0	17.64	17.50	17.66		0
	3	2	17.63	17.48	17.65		0
	3	3	17.62	17.49	17.67		0
	6	0	17.63	17.53	17.68	0-1	0
16QAM	1	0	17.68	17.52	17.67	0-1	0
	1	2	17.64	17.48	17.64		0
	1	5	17.64	17.52	17.63		0
	3	0	17.14	17.17	17.19		0
	3	2	17.18	17.03	17.18		0
	3	3	17.10	17.05	17.17		0
	6	0	17.09	17.01	17.06	0-2	0
64QAM	1	0	17.68	17.46	17.70	0-2	0
	1	2	17.64	17.47	17.69		0
	1	5	17.55	17.51	17.62		0
	3	0	17.21	17.24	17.26		0
	3	2	17.14	17.22	17.23		0
	3	3	17.17	17.24	17.21		0
	6	0	17.19	17.24	17.23	0-3	0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 47 of 116

Table 8-41
LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth - Antenna D

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	19.14	0	0
	1	25	19.04		0
	1	49	18.96		0
	25	0	19.03	0-1	0
	25	12	19.01		0
	25	25	18.89		0
	50	0	19.00		0
16QAM	1	0	19.17	0-1	0
	1	25	19.06		0
	1	49	18.95		0
	25	0	18.73	0-2	0
	25	12	18.73		0
	25	25	18.63		0
	50	0	18.71		0
64QAM	1	0	19.19	0-2	0
	1	25	19.10		0
	1	49	19.17		0
	25	0	18.87	0-3	0
	25	12	18.86		0
	25	25	18.86		0
	50	0	18.84		0

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-42
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth - Antenna D

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.06	19.04	19.03	0	0
	1	12	18.96	18.95	19.08		0
	1	24	19.02	19.01	19.08		0
	12	0	19.06	19.06	19.09	0-1	0
	12	6	19.05	19.04	19.13		0
	12	13	19.06	19.10	19.17		0
16QAM	25	0	19.05	19.05	19.13		0
	1	0	19.13	19.14	19.10	0-1	0
	1	12	19.03	18.99	19.18		0
	1	24	19.10	19.01	19.19		0
	12	0	18.76	18.79	18.80	0-2	0
	12	6	18.79	18.73	18.80		0
12	13	18.75	18.80	18.87	0		
64QAM	25	0	18.74	18.75	18.78		0
	1	0	19.18	19.20	19.17	0-2	0
	1	12	18.99	19.00	19.10		0
	1	24	19.02	18.99	19.15		0
	12	0	18.85	18.83	18.85	0-3	0
	12	6	18.82	18.85	18.86		0
12	13	18.81	18.84	18.92	0		
	25	0	18.79	18.79	18.85		0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 48 of 116

Table 8-43
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth - Antenna D

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.02	19.02	19.09	0	0
	1	7	19.00	19.01	19.17		0
	1	14	18.95	19.02	19.06		0
	8	0	19.14	19.09	19.16	0-1	0
	8	4	19.05	19.07	19.19		0
	8	7	19.05	19.15	19.19		0
	15	0	19.06	19.08	19.20		0
16QAM	1	0	19.13	19.12	19.20	0-1	0
	1	7	19.12	19.10	19.19		0
	1	14	19.09	19.07	19.15		0
	8	0	18.85	18.80	18.88	0-2	0
	8	4	18.78	18.79	18.95		0
	8	7	18.77	18.84	18.90		0
	15	0	18.78	18.79	18.90		0
64QAM	1	0	19.10	19.05	19.06	0-2	0
	1	7	19.00	18.99	19.18		0
	1	14	19.01	18.96	19.11		0
	8	0	18.87	18.86	18.89	0-3	0
	8	4	18.84	18.91	18.98		0
	8	7	18.87	18.90	18.93		0
	15	0	18.85	18.82	18.91		0

Table 8-44
LTE Band 5 (Cell) Conducted Powers - 1.4 MHz Bandwidth - Antenna D

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.87	18.80	19.19	0	0
	1	2	18.85	18.71	19.15		0
	1	5	18.80	18.75	19.14		0
	3	0	18.92	18.83	19.01		0
	3	2	18.92	18.83	19.00		0
	3	3	18.91	18.84	19.00		0
	6	0	18.90	18.81	18.96	0-1	0
16QAM	1	0	19.05	19.13	19.20	0-1	0
	1	2	19.02	19.16	19.18		0
	1	5	19.12	19.15	19.10		0
	3	0	19.01	19.01	18.95		0
	3	2	18.99	18.95	18.93		0
	3	3	19.00	18.92	19.10		0
	6	0	18.88	18.85	18.99	0-2	0
64QAM	1	0	18.95	19.18	19.19	0-2	0
	1	2	18.99	19.18	19.11		0
	1	5	19.06	19.09	19.15		0
	3	0	19.02	19.13	19.11		0
	3	2	19.00	19.09	19.16		0
	3	3	18.96	19.08	19.08		0
	6	0	18.95	18.88	18.86	0-3	0

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 49 of 116

8.3.7 LTE Band 66

Table 8-45
LTE Band 66 (AWS) Conducted Powers - 20 MHz Bandwidth - Antenna C

LTE Band 66 (AWS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.26	13.06	12.94	0	0
	1	50	13.30	12.98	12.83		0
	1	99	13.25	12.82	13.06		0
	50	0	13.22	12.95	12.90	0-1	0
	50	25	13.21	12.93	12.87		0
	50	50	13.18	12.88	12.90		0
	100	0	13.21	12.99	12.94		0
16QAM	1	0	13.20	13.07	12.85	0-1	0
	1	50	13.22	13.04	12.74		0
	1	99	13.20	12.88	12.99		0
	50	0	12.92	12.61	12.54	0-2	0
	50	25	12.90	12.62	12.51		0
	50	50	12.84	12.55	12.58		0
	100	0	12.94	12.76	12.60		0
64QAM	1	0	13.14	13.13	12.73	0-2	0
	1	50	13.20	13.12	12.61		0
	1	99	13.16	13.04	12.91		0
	50	0	12.90	12.59	12.49	0-3	0
	50	25	12.87	12.62	12.48		0
	50	50	12.82	12.55	12.59		0
	100	0	12.94	12.67	12.57		0

Table 8-46
LTE Band 66 (AWS) Conducted Powers - 15 MHz Bandwidth - Antenna C

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.16	13.01	13.15	0	0
	1	36	13.01	12.89	13.07		0
	1	74	12.94	12.78	13.02		0
	36	0	13.08	13.08	12.96	0-1	0
	36	18	13.10	12.97	12.88		0
	36	37	13.04	12.94	12.84		0
	75	0	13.11	12.97	12.85		0
16QAM	1	0	13.15	13.05	12.92	0-1	0
	1	36	12.99	12.89	12.74		0
	1	74	12.92	12.73	12.73		0
	36	0	12.66	12.68	12.59	0-2	0
	36	18	12.69	12.63	12.52		0
	36	37	12.67	12.55	12.46		0
	75	0	12.66	12.62	12.48		0
64QAM	1	0	13.11	13.03	12.87	0-2	0
	1	36	12.92	12.85	12.85		0
	1	74	12.89	12.72	12.77		0
	36	0	12.71	12.69	12.58	0-3	0
	36	18	12.75	12.61	12.56		0
	36	37	12.74	12.56	12.44		0
	75	0	12.70	12.59	12.50		0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 50 of 116

Table 8-47
LTE Band 66 (AWS) Conducted Powers - 10 MHz Bandwidth - Antenna C

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.19	13.10	12.98	0	0
	1	25	13.07	12.87	12.84		0
	1	49	13.05	12.90	12.82		0
	25	0	13.08	12.98	12.87	0-1	0
	25	12	13.01	12.90	12.88		0
	25	25	13.04	12.87	12.87		0
50	0	13.11	12.91	12.88	0		
16QAM	1	0	13.16	13.08	12.97	0-1	0
	1	25	12.89	12.89	12.73		0
	1	49	13.04	12.71	12.74		0
	25	0	12.71	12.66	12.48	0-2	0
	25	12	12.64	12.55	12.48		0
	25	25	12.66	12.53	12.51		0
50	0	12.72	12.58	12.46	0		
64QAM	1	0	13.14	13.03	13.01	0-2	0
	1	25	13.03	12.82	12.78		0
	1	49	12.89	12.81	12.88		0
	25	0	12.66	12.68	12.53	0-3	0
	25	12	12.61	12.61	12.49		0
	25	25	12.63	12.58	12.50		0
50	0	12.71	12.61	12.48	0		

Table 8-48
LTE Band 66 (AWS) Conducted Powers - 5 MHz Bandwidth - Antenna C

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.19	12.80	12.81	0	0
	1	12	13.07	12.64	12.77		0
	1	24	12.98	12.65	12.70		0
	12	0	13.00	12.68	12.69	0-1	0
	12	6	12.97	12.64	12.64		0
	12	13	12.89	12.63	12.68		0
	25	0	12.93	12.66	12.64		0
16QAM	1	0	13.16	13.11	12.88	0-1	0
	1	12	13.07	12.99	12.73		0
	1	24	12.97	12.87	12.83		0
	12	0	12.93	12.55	12.62	0-2	0
	12	6	12.86	12.52	12.53		0
	12	13	12.80	12.54	12.57		0
	25	0	12.76	12.55	12.51		0
64QAM	1	0	13.17	13.05	13.01	0-2	0
	1	12	12.99	12.82	12.87		0
	1	24	12.93	12.85	12.86		0
	12	0	12.80	12.61	12.56	0-3	0
	12	6	12.65	12.59	12.51		0
	12	13	12.62	12.53	12.57		0
	25	0	12.66	12.54	12.52		0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 51 of 116

Table 8-49
LTE Band 66 (AWS) Conducted Powers - 3 MHz Bandwidth - Antenna C

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.03	12.73	12.81	0	0
	1	7	13.09	12.72	12.88		0
	1	14	13.02	12.67	12.78		0
	8	0	13.15	12.81	12.80	0-1	0
	8	4	13.15	12.79	12.84		0
	8	7	13.14	12.78	12.82		0
	15	0	13.15	12.77	12.83		0
16QAM	1	0	13.28	12.91	12.87	0-1	0
	1	7	13.15	12.84	12.78		0
	1	14	13.07	12.76	12.76		0
	8	0	12.99	12.61	12.62	0-2	0
	8	4	12.95	12.61	12.63		0
	8	7	12.89	12.57	12.65		0
	15	0	12.94	12.55	12.61		0
64QAM	1	0	13.16	12.85	12.88	0-2	0
	1	7	13.23	12.83	12.85		0
	1	14	13.15	12.75	12.78		0
	8	0	12.99	12.68	12.65	0-3	0
	8	4	12.99	12.66	12.68		0
	8	7	12.96	12.61	12.67		0
	15	0	12.88	12.55	12.62		0

Table 8-50
LTE Band 66 (AWS) Conducted Powers - 1.4 MHz Bandwidth - Antenna C

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.25	12.89	13.10	0	0
	1	2	13.26	12.84	13.06		0
	1	5	13.28	12.87	13.04		0
	3	0	13.30	12.91	12.92		0
	3	2	13.29	12.90	12.91		0
	3	3	13.30	12.89	12.89		0
	6	0	13.28	12.91	12.90	0-1	0
16QAM	1	0	13.28	12.87	12.83	0-1	0
	1	2	13.29	12.79	12.82		0
	1	5	13.27	12.84	12.89		0
	3	0	13.05	12.63	12.71		0
	3	2	13.07	12.59	12.67		0
	3	3	13.11	12.61	12.59		0
	6	0	12.97	12.66	12.59	0-2	0
64QAM	1	0	13.27	12.77	12.84	0-2	0
	1	2	13.26	12.79	12.82		0
	1	5	13.23	12.89	12.82		0
	3	0	13.05	12.71	12.76		0
	3	2	13.04	12.75	12.78		0
	3	3	13.11	12.71	12.80		0
	6	0	13.00	12.78	12.63	0-3	0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 52 of 116

Table 8-51
LTE Band 66 (AWS) Conducted Powers - 20 MHz Bandwidth - Antenna D

LTE Band 66 (AWS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.14	13.07	13.12	0	0
	1	50	12.96	12.96	13.08		0
	1	99	12.97	13.01	12.96		0
	50	0	13.05	12.91	12.98	0-1	0
	50	25	12.99	12.86	12.91		0
	50	50	12.94	12.93	12.88		0
	100	0	13.04	12.91	12.95		0
16QAM	1	0	13.19	13.17	13.08	0-1	0
	1	50	13.06	13.05	13.03		0
	1	99	13.12	13.00	12.82		0
	50	0	12.57	12.58	12.50	0-2	0
	50	25	12.56	12.53	12.43		0
	50	50	12.48	12.52	12.43		0
	100	0	12.55	12.53	12.45		0
64QAM	1	0	13.12	13.06	13.01	0-2	0
	1	50	12.95	12.91	13.02		0
	1	99	13.00	12.87	12.82		0
	50	0	12.76	12.74	12.71	0-3	0
	50	25	12.73	12.70	12.70		0
	50	50	12.77	12.63	12.60		0
	100	0	12.79	12.73	12.74		0

Table 8-52
LTE Band 66 (AWS) Conducted Powers - 15 MHz Bandwidth - Antenna D

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.86	12.91	13.14	0	0
	1	36	12.79	12.89	13.00		0
	1	74	12.77	12.70	12.83		0
	36	0	12.84	12.98	12.98	0-1	0
	36	18	12.83	12.97	12.84		0
	36	37	12.81	12.88	12.71		0
	75	0	12.82	12.95	12.83		0
16QAM	1	0	13.05	13.10	13.03	0-1	0
	1	36	12.96	13.04	12.94		0
	1	74	12.89	12.89	12.70		0
	36	0	12.66	12.81	12.79	0-2	0
	36	18	12.66	12.79	12.69		0
	36	37	12.63	12.70	12.58		0
	75	0	12.66	12.73	12.67		0
64QAM	1	0	13.05	13.09	13.11	0-2	0
	1	36	12.92	13.08	13.05		0
	1	74	12.87	12.93	12.84		0
	36	0	12.67	12.87	12.78	0-3	0
	36	18	12.67	12.85	12.70		0
	36	37	12.65	12.77	12.55		0
	75	0	12.66	12.80	12.65		0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 53 of 116

Table 8-53
LTE Band 66 (AWS) Conducted Powers - 10 MHz Bandwidth - Antenna D

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.99	12.88	12.96	0	0
	1	25	12.79	12.79	12.79		0
	1	49	12.82	12.79	12.70		0
	25	0	12.85	12.90	12.92	0-1	0
	25	12	12.79	12.87	12.84		0
	25	25	12.80	12.87	12.77		0
16QAM	50	0	12.86	12.88	12.86	0	
	1	0	13.05	13.08	13.01	0-1	0
	1	25	12.84	12.89	12.88		0
	1	49	12.84	12.87	12.74		0
	25	0	12.66	12.72	12.65	0-2	0
	25	12	12.62	12.71	12.58		0
25	25	12.58	12.67	12.51	0		
64QAM	50	0	12.61	12.66	12.59	0	
	1	0	13.08	13.03	13.06	0-2	0
	1	25	12.91	12.88	12.87		0
	1	49	12.89	12.86	12.80		0
	25	0	12.71	12.71	12.68	0-3	0
	25	12	12.66	12.57	12.59		0
	25	25	12.59	12.62	12.55		0
	50	0	12.66	12.68	12.60		0

Table 8-54
LTE Band 66 (AWS) Conducted Powers - 5 MHz Bandwidth - Antenna D

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.09	13.00	13.02	0	0
	1	12	12.96	12.92	12.91		0
	1	24	12.94	12.94	12.91		0
	12	0	13.09	13.02	12.87	0-1	0
	12	6	12.98	12.99	12.81		0
	12	13	12.98	12.99	12.82		0
25	0	12.98	13.00	12.84	0		
16QAM	1	0	13.04	13.05	12.91	0-1	0
	1	12	12.94	12.89	12.74		0
	1	24	12.99	12.92	12.79		0
	12	0	12.90	12.84	12.64	0-2	0
	12	6	12.83	12.79	12.59		0
	12	13	12.83	12.81	12.62		0
25	0	12.76	12.75	12.59	0		
64QAM	1	0	13.07	13.07	12.88	0-2	0
	1	12	13.05	13.01	12.77		0
	1	24	13.02	12.99	12.85		0
	12	0	12.74	12.65	12.54	0-3	0
	12	6	12.68	12.61	12.48		0
	12	13	12.70	12.61	12.51		0
	25	0	12.68	12.62	12.47		0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 54 of 116

Table 8-55
LTE Band 66 (AWS) Conducted Powers - 3 MHz Bandwidth - Antenna D

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.99	12.97	12.68	0	0
	1	7	13.03	12.93	12.74		0
	1	14	12.86	12.88	12.65		0
	8	0	13.12	13.01	12.80	0-1	0
	8	4	13.11	13.00	12.80		0
	8	7	13.02	12.99	12.79		0
	15	0	13.11	12.99	12.81		0
16QAM	1	0	13.02	12.96	12.65	0-1	0
	1	7	13.08	12.92	12.64		0
	1	14	12.92	12.86	12.66		0
	8	0	12.88	12.77	12.53	0-2	0
	8	4	12.86	12.74	12.54		0
	8	7	12.79	12.75	12.54		0
	15	0	12.84	12.68	12.53		0
64QAM	1	0	12.95	12.87	12.54	0-2	0
	1	7	12.87	12.79	12.57		0
	1	14	12.86	12.84	12.61		0
	8	0	12.85	12.69	12.48	0-3	0
	8	4	12.82	12.68	12.50		0
	8	7	12.79	12.72	12.47		0
	15	0	12.74	12.64	12.47		0

Table 8-56
LTE Band 66 (AWS) Conducted Powers - 1.4 MHz Bandwidth - Antenna D

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.91	13.02	12.59	0	0
	1	2	12.93	12.97	12.55		0
	1	5	12.94	13.02	12.57		0
	3	0	12.87	12.76	12.66		0
	3	2	12.86	12.74	12.67		0
	3	3	12.86	12.76	12.66		0
	6	0	12.86	12.78	12.66	0-1	0
16QAM	1	0	13.03	12.87	12.75	0-1	0
	1	2	12.97	12.74	12.68		0
	1	5	12.98	12.90	12.59		0
	3	0	12.81	12.70	12.54		0
	3	2	12.82	12.68	12.53		0
	3	3	12.79	12.73	12.55		0
	6	0	12.78	12.65	12.45	0-2	0
64QAM	1	0	12.94	12.79	12.64	0-2	0
	1	2	12.92	12.69	12.69		0
	1	5	12.96	12.82	12.66		0
	3	0	12.89	12.66	12.56		0
	3	2	12.93	12.72	12.55		0
	3	3	12.89	12.67	12.52		0
	6	0	12.88	12.65	12.53	0-3	0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 55 of 116

8.3.8 LTE Band 25

Table 8-57
LTE Band 25 (PCS) Conducted Powers - 20 MHz Bandwidth - Antenna C

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.08	13.03	12.98	0	0
	1	50	12.99	12.96	12.94		0
	1	99	12.96	13.04	12.95		0
	50	0	12.89	12.87	13.03	0-1	0
	50	25	12.88	12.88	13.00		0
	50	50	12.85	12.92	13.00		0
	100	0	12.99	12.98	13.02		0
16QAM	1	0	12.80	12.90	13.05	0-1	0
	1	50	12.78	12.81	13.03		0
	1	99	12.79	12.80	13.09		0
	50	0	12.60	12.55	12.66	0-2	0
	50	25	12.59	12.51	12.62		0
	50	50	12.57	12.58	12.75		0
	100	0	12.68	12.60	12.71		0
64QAM	1	0	13.09	13.10	13.08	0-2	0
	1	50	13.01	12.95	13.05		0
	1	99	13.05	13.02	13.03		0
	50	0	12.71	12.61	12.77	0-3	0
	50	25	12.69	12.60	12.75		0
	50	50	12.70	12.65	12.72		0
	100	0	12.79	12.71	12.82		0

Table 8-58
LTE Band 25 (PCS) Conducted Powers - 15 MHz Bandwidth - Antenna C

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.05	12.77	12.93	0	0
	1	36	13.09	12.78	12.78		0
	1	74	12.90	12.79	12.80		0
	36	0	13.08	12.75	12.85	0-1	0
	36	18	12.97	12.80	12.84		0
	36	37	12.89	12.84	12.85		0
	75	0	12.97	12.79	12.91		0
16QAM	1	0	12.78	12.58	12.74	0-1	0
	1	36	12.68	12.58	12.59		0
	1	74	12.62	12.55	12.61		0
	36	0	12.47	12.28	12.31	0-2	0
	36	18	12.36	12.28	12.29		0
	36	37	12.28	12.26	12.25		0
	75	0	12.35	12.31	12.42		0
64QAM	1	0	12.99	12.87	12.91	0-2	0
	1	36	12.91	12.74	12.78		0
	1	74	12.88	12.87	12.75		0
	36	0	12.77	12.49	12.61	0-3	0
	36	18	12.66	12.49	12.61		0
	36	37	12.56	12.50	12.55		0
	75	0	12.62	12.54	12.66		0

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 56 of 116

Table 8-59
LTE Band 25 (PCS) Conducted Powers - 10 MHz Bandwidth - Antenna C

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.06	12.75	12.80	0	0
	1	25	13.02	12.71	12.63		0
	1	49	12.83	12.83	12.74		0
	25	0	13.06	12.82	12.79	0-1	0
	25	12	13.01	12.76	12.73		0
	25	25	12.91	12.75	12.75		0
	50	0	13.01	12.80	12.78		0
16QAM	1	0	12.99	12.72	12.84	0-1	0
	1	25	12.87	12.59	12.78		0
	1	49	12.72	12.68	12.83		0
	25	0	12.61	12.40	12.41	0-2	0
	25	12	12.54	12.34	12.33		0
	25	25	12.46	12.31	12.38		0
	50	0	12.53	12.35	12.38		0
64QAM	1	0	13.03	12.81	12.95	0-2	0
	1	25	12.97	12.69	12.78		0
	1	49	12.78	12.72	12.89		0
	25	0	12.78	12.58	12.54	0-3	0
	25	12	12.73	12.50	12.47		0
	25	25	12.62	12.49	12.50		0
	50	0	12.72	12.48	12.50		0

Table 8-60
LTE Band 25 (PCS) Conducted Powers - 5 MHz Bandwidth - Antenna C

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.97	12.57	12.58	0	0
	1	12	13.02	12.50	12.59		0
	1	24	13.00	12.51	12.68		0
	12	0	12.81	12.41	12.53	0-1	0
	12	6	12.85	12.37	12.58		0
	12	13	12.86	12.36	12.64		0
	25	0	12.82	12.41	12.60		0
16QAM	1	0	12.95	12.80	12.73	0-1	0
	1	12	13.00	12.72	12.70		0
	1	24	12.96	12.52	12.75		0
	12	0	12.70	12.35	12.39	0-2	0
	12	6	12.72	12.31	12.37		0
	12	13	12.73	12.28	12.44		0
	25	0	12.64	12.30	12.37		0
64QAM	1	0	13.00	12.60	12.81	0-2	0
	1	12	12.96	12.56	12.79		0
	1	24	13.07	12.60	12.58		0
	12	0	12.68	12.31	12.40	0-3	0
	12	6	12.71	12.26	12.41		0
	12	13	12.75	12.27	12.49		0
	25	0	12.61	12.25	12.43		0

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 57 of 116

Table 8-61
LTE Band 25 (PCS) Conducted Powers - 3 MHz Bandwidth - Antenna C

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.00	12.84	12.76	0	0
	1	7	13.06	12.85	12.85		0
	1	14	13.02	12.85	12.80		0
	8	0	13.04	12.74	12.79	0-1	0
	8	4	13.08	12.74	12.82		0
	8	7	13.10	12.73	12.80		0
	15	0	13.07	12.72	12.86		0
16QAM	1	0	13.04	12.86	12.92	0-1	0
	1	7	13.06	12.91	12.91		0
	1	14	13.02	12.84	12.84		0
	8	0	12.97	12.63	12.74	0-2	0
	8	4	13.01	12.61	12.69		0
	8	7	13.00	12.62	12.74		0
	15	0	12.94	12.55	12.71		0
64QAM	1	0	13.05	12.83	12.85	0-2	0
	1	7	13.02	12.78	12.92		0
	1	14	13.06	12.76	12.88		0
	8	0	12.92	12.60	12.65	0-3	0
	8	4	12.97	12.55	12.63		0
	8	7	12.93	12.57	12.71		0
	15	0	12.91	12.54	12.64		0

Table 8-62
LTE Band 25 (PCS) Conducted Powers - 1.4 MHz Bandwidth - Antenna C

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.00	12.60	12.93	0	0
	1	2	12.97	12.56	12.88		0
	1	5	13.04	12.57	12.89		0
	3	0	12.87	12.59	12.76		0
	3	2	12.86	12.58	12.75		0
	3	3	12.88	12.60	12.76		0
	6	0	12.89	12.56	12.77	0-1	0
16QAM	1	0	13.06	12.61	12.77	0-1	0
	1	2	13.04	12.62	12.68		0
	1	5	13.09	12.55	12.70		0
	3	0	12.80	12.43	12.70		0
	3	2	12.89	12.46	12.67		0
	3	3	12.92	12.48	12.64		0
	6	0	12.81	12.46	12.58	0-2	0
64QAM	1	0	12.87	12.44	12.65	0-2	0
	1	2	12.89	12.44	12.77		0
	1	5	12.89	12.43	12.75		0
	3	0	12.86	12.46	12.58		0
	3	2	12.80	12.44	12.56		0
	3	3	12.83	12.40	12.58		0
	6	0	12.70	12.30	12.49	0-3	0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 58 of 116

Table 8-63
LTE Band 25 (PCS) Conducted Powers - 20 MHz Bandwidth - Antenna D

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.88	11.92	11.97	0	0
	1	50	11.77	11.81	11.95		0
	1	99	11.85	11.87	11.90		0
	50	0	11.75	11.74	11.93	0-1	0
	50	25	11.83	11.81	11.95		0
	50	50	11.93	11.91	11.94		0
	100	0	11.90	11.93	11.94		0
16QAM	1	0	11.94	11.92	11.76	0-1	0
	1	50	11.87	11.83	11.78		0
	1	99	11.92	11.73	11.71		0
	50	0	11.50	11.24	11.34	0-2	0
	50	25	11.45	11.20	11.34		0
	50	50	11.40	11.33	11.33		0
	100	0	11.49	11.36	11.40		0
64QAM	1	0	11.96	11.65	11.76	0-2	0
	1	50	11.67	11.61	11.78		0
	1	99	11.83	11.78	11.82		0
	50	0	11.65	11.35	11.39	0-3	0
	50	25	11.47	11.32	11.35		0
	50	50	11.54	11.35	11.30		0
	100	0	11.53	11.42	11.37		0

Table 8-64
LTE Band 25 (PCS) Conducted Powers - 15 MHz Bandwidth - Antenna D

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.00	11.75	11.69	0	0
	1	36	11.79	11.73	11.66		0
	1	74	11.69	11.82	11.69		0
	36	0	12.00	11.69	11.72	0-1	0
	36	18	11.89	11.63	11.72		0
	36	37	11.79	11.73	11.71		0
	75	0	11.95	11.79	11.75		0
16QAM	1	0	11.98	11.64	11.71	0-1	0
	1	36	11.91	11.57	11.68		0
	1	74	11.86	11.70	11.73		0
	36	0	11.72	11.39	11.40	0-2	0
	36	18	11.61	11.37	11.43		0
	36	37	11.52	11.45	11.43		0
	75	0	11.60	11.48	11.47		0
64QAM	1	0	11.99	11.68	11.76	0-2	0
	1	36	11.90	11.71	11.75		0
	1	74	11.75	11.81	11.72		0
	36	0	11.75	11.39	11.47	0-3	0
	36	18	11.62	11.37	11.51		0
	36	37	11.55	11.45	11.48		0
	75	0	11.60	11.46	11.47		0

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 59 of 116

Table 8-65
LTE Band 25 (PCS) Conducted Powers - 10 MHz Bandwidth - Antenna D

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.00	11.51	11.55	0	0
	1	25	11.82	11.45	11.43		0
	1	49	11.68	11.54	11.60		0
	25	0	11.95	11.59	11.54	0-1	0
	25	12	11.92	11.51	11.55		0
	25	25	11.80	11.55	11.59		0
	50	0	11.90	11.60	11.57		0
16QAM	1	0	11.98	11.56	11.61	0-1	0
	1	25	11.96	11.49	11.56		0
	1	49	11.78	11.57	11.63		0
	25	0	11.69	11.30	11.33	0-2	0
	25	12	11.66	11.21	11.29		0
	25	25	11.52	11.25	11.33		0
	50	0	11.64	11.35	11.30		0
64QAM	1	0	11.98	11.60	11.63	0-2	0
	1	25	11.92	11.51	11.52		0
	1	49	11.79	11.55	11.67		0
	25	0	11.67	11.38	11.31	0-3	0
	25	12	11.60	11.29	11.27		0
	25	25	11.51	11.32	11.37		0
	50	0	11.62	11.33	11.32		0

Table 8-66
LTE Band 25 (PCS) Conducted Powers - 5 MHz Bandwidth - Antenna D

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.00	11.40	11.40	0	0
	1	12	11.91	11.41	11.49		0
	1	24	11.88	11.43	11.57		0
	12	0	11.99	11.48	11.58	0-1	0
	12	6	11.94	11.44	11.65		0
	12	13	11.92	11.51	11.68		0
	25	0	11.91	11.55	11.64		0
16QAM	1	0	11.99	11.62	11.47	0-1	0
	1	12	11.91	11.60	11.51		0
	1	24	11.80	11.56	11.59		0
	12	0	11.84	11.33	11.32	0-2	0
	12	6	11.76	11.29	11.33		0
	12	13	11.70	11.31	11.41		0
	25	0	11.69	11.37	11.30		0
64QAM	1	0	12.00	11.56	11.68	0-2	0
	1	12	11.98	11.52	11.70		0
	1	24	11.90	11.54	11.74		0
	12	0	11.71	11.26	11.26	0-3	0
	12	6	11.61	11.20	11.32		0
	12	13	11.60	11.31	11.31		0
	25	0	11.61	11.28	11.26		0

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 60 of 116

Table 8-67
LTE Band 25 (PCS) Conducted Powers - 3 MHz Bandwidth - Antenna D

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.96	11.39	11.47	0	0
	1	7	11.97	11.46	11.59		0
	1	14	11.84	11.40	11.56		0
	8	0	12.00	11.54	11.61	0-1	0
	8	4	12.00	11.55	11.68		0
	8	7	11.95	11.54	11.68		0
	15	0	12.00	11.57	11.69		0
16QAM	1	0	11.99	11.47	11.60	0-1	0
	1	7	11.98	11.50	11.67		0
	1	14	11.96	11.52	11.68		0
	8	0	11.86	11.36	11.37	0-2	0
	8	4	11.85	11.39	11.46		0
	8	7	11.81	11.42	11.48		0
	15	0	11.84	11.34	11.44		0
64QAM	1	0	11.98	11.53	11.48	0-2	0
	1	7	11.99	11.63	11.63		0
	1	14	11.91	11.53	11.58		0
	8	0	11.88	11.32	11.39	0-3	0
	8	4	11.86	11.36	11.47		0
	8	7	11.83	11.37	11.47		0
	15	0	11.81	11.32	11.39		0

Table 8-68
LTE Band 25 (PCS) Conducted Powers - 1.4 MHz Bandwidth - Antenna D

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.87	11.46	11.49	0	0
	1	2	11.87		11.47		0
	1	5	11.80	11.48	11.49		0
	3	0	11.99	11.38	11.55		0
	3	2	11.95	11.44	11.54		0
	3	3	11.94	11.45	11.55		0
	6	0	11.91	11.43	11.54	0-1	0
16QAM	1	0	11.98	11.46	11.44	0-1	0
	1	2	11.99	11.45	11.45		0
	1	5	11.95	11.49	11.46		0
	3	0	11.85	11.30	11.35		0
	3	2	11.79	11.34	11.33		0
	3	3	11.81	11.35	11.32		0
	6	0	11.74	11.35	11.31	0-2	0
64QAM	1	0	11.99	11.39	11.48	0-2	0
	1	2	11.96	11.39	11.43		0
	1	5	11.89	11.36	11.47		0
	3	0	11.88	11.30	11.39		0
	3	2	11.85	11.29	11.40		0
	3	3	11.87	11.31	11.40		0
	6	0	11.70	11.29	11.40	0-3	0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 61 of 116

8.3.9 LTE Band 30

Table 8-69
LTE Band 30 Conducted Powers - 10 MHz Bandwidth - Antenna C

Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz) Conducted Power [dBm]		
QPSK	1	0	13.18	0	0
	1	25	13.09		0
	1	49	13.01		0
	25	0	13.17	0-1	0
	25	12	13.16		0
	25	25	13.06		0
16QAM	50	0	13.02	0-1	0
	1	0	13.18		0
	1	25	13.06		0
	1	49	13.07	0-2	0
	25	0	12.79		0
	25	12	12.76		0
64QAM	25	25	12.63	0-2	0
	50	0	12.71		0
	1	0	13.17	0-3	0
	1	25	13.08		0
	1	49	13.00		0
	25	0	12.82	0-3	0
	25	12	12.81		0
	25	25	12.65		0
	50	0	12.74		0

Table 8-70
LTE Band 30 Conducted Powers - 5 MHz Bandwidth - Antenna C

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz) Conducted Power [dBm]		
QPSK	1	0	13.10	0	0
	1	12	13.04		0
	1	24	13.04		0
	12	0	13.17	0-1	0
	12	6	13.16		0
	12	13	13.15		0
16QAM	25	0	13.15	0-1	0
	1	0	13.16		0
	1	12	13.15	0-2	0
	1	24	13.14		0
	12	0	12.97		0
	12	6	12.95	0-2	0
64QAM	12	13	12.88		0
	25	0	12.92		0
	1	0	13.16	0-2	0
	1	12	13.14		0
	1	24	13.12	0-3	0
	12	0	12.86		0
	12	6	12.81		0
	12	13	12.81		0
	25	0	12.85		0

Note: LTE Band 30 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 62 of 116

Table 8-71
LTE Band 30 Conducted Powers - 10 MHz Bandwidth - Antenna D

LTE Band 30 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	12.59	0	0
	1	25	12.42		0
	1	49	12.47		0
	25	0	12.45	0-1	0
	25	12	12.41		0
	25	25	12.43		0
	50	0	12.44		0
16QAM	1	0	12.53	0-1	0
	1	25	12.33		0
	1	49	12.46		0
	25	0	12.05	0-2	0
	25	12	12.03		0
	25	25	12.00		0
	50	0	12.01		0
64QAM	1	0	12.55	0-2	0
	1	25	12.36		0
	1	49	12.48		0
	25	0	12.08	0-3	0
	25	12	12.04		0
	25	25	12.01		0
	50	0	12.03		0

Table 8-72
LTE Band 30 Conducted Powers - 5 MHz Bandwidth - Antenna D

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	12.39	0	0
	1	12	12.41		0
	1	24	12.40		0
	12	0	12.37	0-1	0
	12	6	12.37		0
	12	13	12.39		0
	25	0	12.42		0
16QAM	1	0	12.48	0-1	0
	1	12	12.57		0
	1	24	12.51		0
	12	0	12.12	0-2	0
	12	6	12.13		0
	12	13	12.15		0
	25	0	12.20		0
64QAM	1	0	12.43	0-2	0
	1	12	12.48		0
	1	24	12.42		0
	12	0	12.19	0-3	0
	12	6	12.17		0
	12	13	12.18		0
	25	0	12.21		0

Note: LTE Band 30 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 63 of 116

8.3.10 LTE Band 7

Table 8-73
LTE Band 7 Conducted Powers - 20 MHz Bandwidth - Antenna C

LTE Band 7 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20850 (2510.0 MHz)	21100 (2535.0 MHz)	21350 (2560.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.32	12.08	12.26	0	0
	1	50	12.34	12.06	12.30		0
	1	99	12.40	12.09	12.37		0
	50	0	12.14	12.18	12.23	0-1	0
	50	25	12.24	12.14	12.29		0
	50	50	12.32	12.16	12.28		0
	100	0	12.31	12.21	12.31		0
16QAM	1	0	12.23	12.14	12.29	0-1	0
	1	50	12.35	12.08	12.40		0
	1	99	12.40	12.13	12.39		0
	50	0	12.20	11.98	11.96	0-2	0
	50	25	12.25	11.96	12.01		0
	50	50	12.34	11.97	12.00		0
	100	0	12.34	11.95	12.03		0
64QAM	1	0	12.36	12.04	12.17	0-2	0
	1	50	12.33	12.14	12.22		0
	1	99	12.40	12.13	12.25		0
	50	0	11.83	11.87	11.85	0-3	0
	50	25	11.86	11.86	11.86		0
	50	50	11.94	11.83	11.87		0
	100	0	11.93	11.86	11.94		0

Table 8-74
LTE Band 7 Conducted Powers - 15 MHz Bandwidth - Antenna C

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.88	12.26	11.90	0	0
	1	36	12.07	12.37	12.00		0
	1	74	12.00	12.11	11.84		0
	36	0	12.08	12.24	12.04	0-1	0
	36	18	12.17	12.26	12.07		0
	36	37	12.20	12.11	11.96		0
	75	0	12.20	12.20	12.03		0
16QAM	1	0	12.00	12.35	12.06	0-1	0
	1	36	12.29	12.39	12.19		0
	1	74	12.25	12.10	12.09		0
	36	0	11.92	12.12	11.85	0-2	0
	36	18	12.01	12.12	11.86		0
	36	37	12.04	11.93	11.86		0
	75	0	12.02	12.01	11.81		0
64QAM	1	0	12.10	12.38	12.08	0-2	0
	1	36	12.22	12.39	12.18		0
	1	74	12.36	12.02	12.06		0
	36	0	12.03	12.22	12.01	0-3	0
	36	18	12.11	12.18	11.94		0
	36	37	12.13	12.11	11.92		0
	75	0	12.09	12.10	11.92		0

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 64 of 116

Table 8-75
LTE Band 7 Conducted Powers - 10 MHz Bandwidth - Antenna C

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.12	12.37	12.13	0	0
	1	25	12.13	12.28	12.03		0
	1	49	12.28	12.22	12.06		0
	25	0	12.25	12.39	12.23	0-1	0
	25	12	12.22	12.40	12.13		0
	25	25	12.32	12.39	12.16		0
	50	0	12.25	12.37	12.12		0
16QAM	1	0	12.12	12.36	12.13	0-1	0
	1	25	12.06	12.32	12.11		0
	1	49	12.34	12.18	12.20		0
	25	0	11.94	12.05	11.86	0-2	0
	25	12	11.95	12.06	11.85		0
	25	25	12.01	12.01	11.90		0
	50	0	11.95	11.99	11.87		0
64QAM	1	0	12.19	12.33	12.18	0-2	0
	1	25	12.22	12.28	12.15		0
	1	49	12.29	12.26	12.24		0
	25	0	11.98	12.13	11.94	0-3	0
	25	12	11.97	12.16	11.85		0
	25	25	12.05	12.12	11.89		0
	50	0	11.97	12.10	11.92		0

Table 8-76
LTE Band 7 Conducted Powers - 5 MHz Bandwidth - Antenna C

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.12	12.25	12.30	0	0
	1	12	12.13		12.22		0
	1	24	12.16	12.22	12.19		0
	12	0	12.13	12.36	12.19	0-1	0
	12	6	12.20	12.39	12.16		0
	12	13	12.18	12.33	12.14		0
	25	0	12.22	12.32	12.20		0
16QAM	1	0	12.02	12.39	12.38	0-1	0
	1	12	12.16	12.30	12.26		0
	1	24	12.21	12.35	12.37		0
	12	0	11.88	12.19	12.01	0-2	0
	12	6	11.90	12.15	12.05		0
	12	13	11.92	12.09	11.98		0
	25	0	11.91	12.07	12.03		0
64QAM	1	0	12.05	12.37	12.06	0-2	0
	1	12	12.15	12.35	12.11		0
	1	24	12.19	12.20	12.06		0
	12	0	11.90	12.05	11.92	0-3	0
	12	6	11.91	12.01	11.90		0
	12	13	11.90		11.89		0
	25	0	11.92	11.93	11.89		0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 65 of 116

Table 8-77
LTE Band 7 Reduced Conducted Powers - 20 MHz Bandwidth - Antenna D

LTE Band 7 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20850 (2510.0 MHz)	21100 (2535.0 MHz)	21350 (2560.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.00	12.14	11.96	0	0
	1	50	12.01	12.05	11.94		0
	1	99	11.99	12.04	11.84		0
	50	0	12.01	11.99	11.93	0-1	0
	50	25	12.10	12.00	11.96		0
	50	50	12.03	11.98	11.94		0
	100	0	12.05	11.99	11.92		0
16QAM	1	0	11.96	12.16	11.91	0-1	0
	1	50	12.03	12.05	11.99		0
	1	99	11.97	11.96	11.84		0
	50	0	11.62	11.64	11.49	0-2	0
	50	25	11.57	11.59	11.57		0
	50	50	11.60	11.56	11.51		0
	100	0	11.62	11.61	11.63		0
64QAM	1	0	11.77	11.96	11.70	0-2	0
	1	50	12.02	11.95	11.87		0
	1	99	11.98	11.97	11.77		0
	50	0	11.64	11.70	11.69	0-3	0
	50	25	11.77	11.71	11.70		0
	50	50	11.74	11.65	11.71		0
	100	0	11.80	11.69	11.73		0

Table 8-78
LTE Band 7 Conducted Powers - 15 MHz Bandwidth - Antenna D

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.94	12.09	12.11	0	0
	1	36	12.11	12.20	12.20		0
	1	74	12.02	11.45	12.15		0
	36	0	12.05	12.11	12.19	0-1	0
	36	18	12.20	12.18	12.18		0
	36	37	12.20	12.04	12.17		0
	75	0	12.20	12.08	12.18		0
16QAM	1	0	12.05	12.06	11.80	0-1	0
	1	36	12.16	12.18	11.91		0
	1	74	12.19	12.05	11.84		0
	36	0	11.86	11.94	11.79	0-2	0
	36	18	12.04	12.03	11.78		0
	36	37	12.07	11.90	11.81		0
	75	0	12.05	11.93	11.75		0
64QAM	1	0	11.93	12.17	11.99	0-2	0
	1	36	12.09	12.19	12.15		0
	1	74	12.07	12.13	12.12		0
	36	0	11.86	11.88	11.96	0-3	0
	36	18	12.01	11.97	11.97		0
	36	37	11.99	11.87	11.96		0
	75	0	11.98	11.84	11.94		0

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 66 of 116

Table 8-79
LTE Band 7 Conducted Powers - 10 MHz Bandwidth - Antenna D

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.91	11.98	12.08	0	0
	1	25	11.94	11.92	12.06		0
	1	49	12.09	11.93	12.04		0
	25	0	12.13	12.10	12.20	0-1	0
	25	12	11.99	12.13	12.20		0
	25	25	12.11	12.09	12.16		0
	50	0	12.07	12.05	12.19		0
16QAM	1	0	12.10	12.10	12.19	0-1	0
	1	25	12.12	12.16	12.14		0
	1	49	12.19	12.14	12.19		0
	25	0	11.83	11.97	12.03	0-2	0
	25	12	11.88	11.98	11.98		0
	25	25	11.98	11.95	11.94		0
	50	0	11.91	11.94	12.00		0
64QAM	1	0	11.92	12.00	12.20	0-2	0
	1	25	11.98	12.02	12.18		0
	1	49	12.11	11.94	12.15		0
	25	0	11.76	11.87	11.93	0-3	0
	25	12	11.81	11.90	11.89		0
	25	25	11.87	11.89	11.88		0
	50	0	11.82	11.83	11.94		0

Table 8-80
LTE Band 7 Conducted Powers - 5 MHz Bandwidth - Antenna D

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.96	12.11	12.15	0	0
	1	12	11.97	12.09	12.09		0
	1	24	12.06	12.15	11.98		0
	12	0	12.00	12.09	12.16	0-1	0
	12	6	12.04	12.15	12.18		0
	12	13	12.02	12.11	12.10		0
	25	0	12.05	12.10	12.19		0
16QAM	1	0	12.14	12.11	12.16	0-1	0
	1	12	12.13	12.06	12.12		0
	1	24	12.16	12.09	12.14		0
	12	0	11.81	11.91	12.02	0-2	0
	12	6	11.82	11.91	12.02		0
	12	13	11.82	11.87	11.96		0
	25	0	11.87	11.89	12.00		0
64QAM	1	0	12.16	12.12	12.20	0-2	0
	1	12	12.17	12.03	12.17		0
	1	24	12.18	12.12	12.19		0
	12	0	11.82	11.95	12.01	0-3	0
	12	6	11.84	11.97	12.03		0
	12	13	11.86	11.91	12.01		0
	25	0	11.87	11.87	12.00		0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 67 of 116

8.3.11 LTE Band 41 PC3

Table 8-81
LTE Band 41 PC3 Conducted Powers - 20 MHz Bandwidth - Antenna C

LTE Band 41 20 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	15.28	15.36	14.97	15.22	15.26	0	0	
	1	50	15.09	15.20	14.91	15.13	15.01		0-1	0
	1	99	15.22	15.13	15.14	15.16	15.07			0
	50	0	15.20	15.27	14.91	15.18	14.79	0		
	50	25	15.08	15.18	14.90	15.08	14.81	0		0
	50	50	15.14	15.11	15.15	15.09	15.03		0	
	100	0	15.13	15.21	14.93	15.12	14.75		0	
16QAM	1	0	15.20	15.25	14.95	15.03	14.69	0-1	0	
	1	50	15.06	15.13	14.93	15.03	14.66		0-2	0
	1	99	15.17	15.17	15.00	15.00	14.76			0
	50	0	15.09	15.09	14.79	14.91	14.57	0		0
	50	25	14.97	15.06	14.77	14.88	14.57			0
	50	50	15.00	15.01	14.76	14.89	14.59		0	
	100	0	15.04	15.08	14.81	14.91	14.62	0		
64QAM	1	0	15.21	15.27	14.91	15.04	14.72	0-2	0	
	1	50	15.01	15.12	14.84	14.98	14.63		0-3	0
	1	99	15.19	15.05	14.97	14.96	14.73			0
	50	0	15.10	15.10	14.78	14.92	14.58	0		0
	50	25	14.97	15.07	14.76	14.88	14.57			0
	50	50	15.00	15.02	14.77	14.90	14.61		0	
	100	0	15.03	15.10	14.80	14.91	14.62	0		

Table 8-82
LTE Band 41 PC3 Conducted Powers - 15 MHz Bandwidth - Antenna C

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.35	15.31	15.14	15.18	15.12	0	0
	1	36	15.39	15.36	15.23	15.24	15.13		0
	1	74	15.30	15.22	15.18	15.09	15.02		0
	36	0	15.34	15.31	15.21	15.18	15.07	0-1	0
	36	18	15.40	15.31	15.26	15.22	15.07		0
	36	37	15.33	15.28	15.24	15.18	15.02		0
	75	0	15.34	15.29	15.26	15.22	15.06		0
16QAM	1	0	15.30	15.05	15.02	15.10	14.90	0-1	0
	1	36	15.36	15.11	15.11	15.13	14.88		0
	1	74	15.35	14.99	15.10	15.05	14.79		0
	36	0	15.19	15.16	15.12	15.01	14.89	0-2	0
	36	18	15.27	15.13	15.16	15.07	14.89		0
	36	37	15.18	15.11	15.11	15.00	14.86		0
	75	0	15.19	15.11	15.14	15.08	14.89		0
64QAM	1	0	15.12	15.20	15.23	15.09	15.01	0-2	0
	1	36	15.19	15.28	15.36	15.17	15.09		0
	1	74	15.13	15.08	15.22	14.92	14.84		0
	36	0	15.26	15.20	15.11	15.06	14.97	0-3	0
	36	18	15.31	15.21	15.15	15.17	14.97		0
	36	37	15.27	15.18	15.10	15.11	14.90		0
	75	0	15.26	15.22	15.16	15.14	14.94		0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 68 of 116

Table 8-83
LTE Band 41 PC3 Conducted Powers - 10 MHz Bandwidth - Antenna C

LTE Band 41 10 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	15.38	15.34	15.30	15.18	15.16	0	0	
	1	25	15.35	15.31	15.31	15.17	15.07		0-1	0
	1	49	15.36	15.24	15.33	15.14	15.09			0
	25	0	15.33	15.28	15.19	15.14	15.04	0		
	25	12	15.34	15.22	15.17	15.15	15.02	0		
	25	25	15.29	15.23	15.21	15.13	15.01	0		
	50	0	15.30	15.24	15.20	15.17	15.04	0		
16QAM	1	0	15.20	15.30	15.01	15.00	15.09	0-1	0	
	1	25	15.11	15.20	15.13	15.05	15.01		0-2	0
	1	49	15.19	15.19	15.19	14.99	15.00			0
	25	0	15.20	15.16	15.13	15.04	14.95	0		
	25	12	15.25	15.11	15.14	15.06	14.92	0		
	25	25	15.22	15.14	15.13	15.05	14.90	0		
	50	0	15.19	15.10	15.12	15.11	14.95	0		
64QAM	1	0	15.37	15.25	15.22	15.35	15.10	0-2	0	
	1	25	15.35	15.30	15.20	15.30	15.03		0-3	0
	1	49	15.33	15.18	15.28	15.32	15.00			0
	25	0	15.26	15.32	15.23	15.15	15.03	0		
	25	12	15.25	15.23	15.21	15.16	14.99	0		
	25	25	15.23	15.24	15.24	15.17	14.98	0		
	50	0	15.19	15.22	15.19	15.14	15.02	0		

Table 8-84
LTE Band 41 PC3 Conducted Powers - 5 MHz Bandwidth - Antenna C

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.37	15.35	15.19	15.19	15.06	0	0
	1	12	15.30	15.27	15.15	15.20	15.00		0
	1	24	15.33	15.30	15.19	15.21	15.04		0
	12	0	15.23	15.16	15.16	15.06	14.92	0-1	0
	12	6	15.24	15.18	15.13	15.11	14.94		0
	12	13	15.22	15.19	15.16	15.10	14.91		0
	25	0	15.24	15.20	15.15	15.12	14.92		0
16QAM	1	0	15.35	15.23	15.21	15.20	14.99	0-1	0
	1	12	15.36	15.17	15.18	15.22	14.92		0
	1	24	15.36	15.25	15.22	15.19	15.00		0
	12	0	15.22	15.11	15.13	15.05	14.91	0-2	0
	12	6	15.23	15.13	15.10	15.08	14.85		0
	12	13	15.19	15.18	15.09	15.09	14.88		0
	25	0	15.20	15.17	15.17	15.08	14.90		0
64QAM	1	0	15.25	15.23	15.32	15.01	15.03	0-2	0
	1	12	15.16	15.30	15.25	14.98	14.99		0
	1	24	15.12	15.24	15.34	14.96	14.93		0
	12	0	15.20	15.09	15.15	14.93	14.86	0-3	0
	12	6	15.16	15.10	15.18	15.01	14.82		0
	12	13	15.11	15.14	15.14	15.00	14.81		0
	25	0	15.12	15.12	15.13	15.03	14.80		0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 69 of 116

Table 8-85
LTE Band 41 PC3 Conducted Powers - 20 MHz Bandwidth - Antenna D

LTE Band 41 20 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.32	15.35	15.27	15.26	15.10	0	0
	1	50	15.29	15.33	15.18	15.15	14.99		0
	1	99	15.25	15.40	15.07	15.07	14.88		0
	50	0	15.32	15.29	15.17	14.97	14.97	0-1	0
	50	25	15.25	15.28	15.15	14.99	14.93		0
	50	50	15.22	15.27	15.10	14.98	14.86		0
	100	0	15.23	15.26	15.11	14.96	14.85		0
16QAM	1	0	15.33	15.32	15.24	14.98	15.16	0-1	0
	1	50	15.18	15.29	15.22	14.94	15.17		0
	1	99	15.19	15.24	15.06	14.96	15.00		0
	50	0	15.20	15.18	15.14	14.93	14.90	0-2	0
	50	25	15.15	15.18	15.13	14.96	14.83		0
	50	50	15.16	15.22	15.06	14.95	14.85		0
	100	0	15.19	15.18	15.11	14.95	14.88		0
64QAM	1	0	15.26	15.32	15.26	14.86	15.13	0-2	0
	1	50	15.12	15.31	15.11	14.82	15.00		0
	1	99	15.18	15.37	14.90	14.93	14.89		0
	50	0	15.09	15.06	15.02	14.73	14.86	0-3	0
	50	25	15.03	15.04	14.98	14.79	14.80		0
	50	50	15.03	15.04	14.88	14.80	14.72		0
	100	0	15.04	15.03	15.01	14.76	14.84		0

Table 8-86
LTE Band 41 PC3 Conducted Powers - 15 MHz Bandwidth - Antenna D

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.39	15.32	15.23	15.06	15.14	0	0
	1	36	15.40	15.39	15.30	15.16	15.11		0
	1	74	15.25	15.32	15.12	15.07	14.84		0
	36	0	15.30	15.37	15.25	15.00	15.04	0-1	0
	36	18	15.32	15.35	15.26	15.07	15.02		0
	36	37	15.24	15.35	15.16	15.03	14.91		0
	75	0	15.26	15.34	15.24	15.07	15.01		0
16QAM	1	0	15.39	15.37	15.25	15.06	15.03	0-1	0
	1	36	15.37	15.40	15.33	15.07	15.04		0
	1	74	15.28	15.39	15.11	15.02	14.77		0
	36	0	15.26	15.24	15.08	14.86	14.92	0-2	0
	36	18	15.23	15.24	15.09	14.91	14.89		0
	36	37	15.14	15.24	15.00	14.87	14.77		0
	75	0	15.16	15.25	15.06	14.91	14.87		0
64QAM	1	0	15.39	15.32	15.17	14.92	15.18	0-2	0
	1	36	15.39	15.37	15.25	15.02	15.17		0
	1	74	15.19	15.31	15.07	14.95	14.91		0
	36	0	15.32	15.29	15.14	14.90	14.94	0-3	0
	36	18	15.32	15.31	15.16	15.00	14.91		0
	36	37	15.20	15.29	15.08	14.95	14.79		0
	75	0	15.22	15.29	15.12	14.97	14.92		0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 70 of 116

Table 8-87
LTE Band 41 PC3 Conducted Powers - 10 MHz Bandwidth - Antenna D

LTE Band 41 10 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	15.40	15.35	15.31	15.04	15.03	0	0	
	1	25	15.30	15.31	15.26	15.09	14.94		0-1	0
	1	49	15.28	15.31	15.21	15.13	14.83			0
	25	0	15.27	15.32	15.13	14.89	14.96	0		
	25	12	15.28	15.28	15.12	14.96	14.91	0		
	25	25	15.21	15.31	15.07	14.96	14.86		0	
	50	0	15.22	15.30	15.12	14.98	14.93		0	
16QAM	1	0	15.39	15.38	15.29	15.04	15.06	0-1	0	
	1	25	15.35	15.39	15.20	15.03	15.01		0-2	0
	1	49	15.32	15.37	15.21	15.08	14.87			0
	25	0	15.18	15.28	15.07	14.85	14.89	0		
	25	12	15.21	15.20	15.09	14.85	14.82	0		
	25	25	15.16	15.24	15.03	14.84	14.77		0	
	50	0	15.14	15.23	15.06	14.88	14.87		0	
64QAM	1	0	15.38	15.39	15.36	15.18	15.07	0-2	0	
	1	25	15.37	15.37	15.32	15.23	15.02		0-3	0
	1	49	15.28	15.38	15.27	15.20	14.95			0
	25	0	15.34	15.40	15.25	15.00	15.04	0		
	25	12	15.36	15.31	15.24	15.03	14.96	0		
	25	25	15.31	15.34	15.19	15.03	14.91		0	
	50	0	15.29	15.32	15.22	15.05	14.96		0	

Table 8-88
LTE Band 41 PC3 Conducted Powers - 5 MHz Bandwidth - Antenna D

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.27	15.40	15.30	14.98	15.09	0	0
	1	12	15.19	15.38	15.27	15.06	15.03		0
	1	24	15.23	15.40	15.22	15.08	15.00		0
	12	0	15.26	15.28	15.16	14.86	14.92	0-1	0
	12	6	15.25	15.28	15.13	14.94	14.90		0
	12	13	15.18	15.29	15.12	14.94	14.87		0
	25	0	15.19	15.31	15.14	14.96	14.89		0
16QAM	1	0	15.31	15.38	15.30	15.07	15.07	0-1	0
	1	12	15.24	15.36	15.23	15.04	15.03		0
	1	24	15.29	15.38	15.18	15.02	15.02		0
	12	0	15.18	15.27	15.12	14.87	14.86	0-2	0
	12	6	15.17	15.28	15.11	14.89	14.86		0
	12	13	15.17	15.28	15.07	14.88	14.83		0
	25	0	15.16	15.25	15.08	14.85	14.83		0
64QAM	1	0	15.29	15.39	15.27	14.91	15.00	0-2	0
	1	12	15.24	15.35	15.21	14.96	14.96		0
	1	24	15.25	15.37	15.19	15.01	14.90		0
	12	0	15.11	15.20	15.11	14.76	14.87	0-3	0
	12	6	15.15	15.22	15.11	14.86	14.82		0
	12	13	15.10	15.25	15.07	14.85	14.80		0
	25	0	15.08	15.18	15.06	14.85	14.77		0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 71 of 116

8.3.12 LTE Band 41 PC2

Table 8-89
LTE Band 41 PC2 Conducted Powers - 20 MHz Bandwidth - Antenna C

LTE Band 41 20 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	15.34	15.36	14.96	15.11	14.72	0	0	
	1	50	15.15	15.21	14.89	15.08	14.61		0-1	0
	1	99	15.30	15.13	15.02	15.10	14.63			0
	50	0	15.21	15.28	14.92	15.09	14.66	0		
	50	25	15.10	15.21	14.91	15.07	14.65	0		
	50	50	15.15	15.15	14.96	15.08	14.66	0		
	100	0	15.13	15.24	14.95	15.10	14.71	0		
16QAM	1	0	15.22	15.35	14.99	15.09	14.89	0-1	0	
	1	50	15.07	15.22	14.91	15.10	14.76		0-2	0
	1	99	15.19	15.16	14.97	15.10	14.78			0
	50	0	14.87	14.87	14.54	14.68	14.41	0		
	50	25	14.75	14.80	14.52	14.66	14.40	0		
	50	50	14.78	14.77	14.51	14.65	14.44	0		
	100	0	14.81	14.81	14.53	14.66	14.46	0		
64QAM	1	0	15.24	15.37	15.04	15.14	14.82	0-2	0	
	1	50	15.10	15.24	14.94	15.12	14.72		0-3	0
	1	99	15.20	15.16	14.99	15.07	14.76			0
	50	0	14.84	14.87	14.54	14.67	14.42	0		
	50	25	14.73	14.80	14.50	14.64	14.40	0		
	50	50	14.76	14.77	14.51	14.65	14.41	0		
	100	0	14.80	14.83	14.55	14.68	14.44	0		

Table 8-90
LTE Band 41 PC2 Conducted Powers - 15 MHz Bandwidth - Antenna C

LTE Band 41 15 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	15.32	15.26	15.19	15.16	15.05	0	0	
	1	36	15.40	15.29	15.27	15.26	15.06		0-1	0
	1	74	15.32	15.15	15.23	15.11	14.96			0
	36	0	15.26	15.22	15.12	15.10	14.97	0		
	36	18	15.32	15.20	15.17	15.17	14.97	0		
	36	37	15.28	15.18	15.16	15.10	14.92	0		
	75	0	15.30	15.20	15.18	15.17	14.97	0		
16QAM	1	0	15.35	15.21	15.27	15.28	15.05	0-1	0	
	1	36	15.37	15.28	15.40	15.37	15.03		0-2	0
	1	74	15.34	15.15	15.31	15.15	14.97			0
	36	0	14.90	14.79	14.75	14.71	14.58	0		
	36	18	14.96	14.82	14.77	14.80	14.57	0		
	36	37	14.87	14.82	14.75	14.72	14.52	0		
	75	0	14.89	14.81	14.78	14.78	14.56	0		
64QAM	1	0	15.30	15.26	15.25	15.28	15.01	0-2	0	
	1	36	15.38	15.24	15.31	15.35	15.07		0-3	0
	1	74	15.28	15.14	15.26	15.24	14.97			0
	36	0	14.78	14.76	14.70	14.60	14.50	0		
	36	18	14.83	14.73	14.74	14.70	14.50	0		
	36	37	14.77	14.73	14.72	14.61	14.50	0		
	75	0	14.76	14.72	14.71	14.68	14.47	0		

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device		Page 72 of 116

Table 8-91
LTE Band 41 PC2 Conducted Powers - 10 MHz Bandwidth - Antenna C

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.26	15.25	15.17	15.19	15.08	0	0
	1	25	15.23	15.18	15.17	15.22	15.00		0
	1	49	15.28	15.16	15.20	15.19	15.01		0
	25	0	15.27	15.24	15.14	15.06	14.92	0-1	0
	25	12	15.27	15.17	15.13	15.11	14.90		0
	25	25	15.25	15.19	15.15	15.09	14.87		0
	50	0	15.26	15.19	15.15	15.12	14.92		0
16QAM	1	0	15.40	15.36	15.28	15.28	15.24	0-1	0
	1	25	15.34	15.30	15.25	15.29	15.15		0
	1	49	15.37	15.25	15.30	15.26	15.13		0
	25	0	14.87	14.82	14.74	14.68	14.57	0-2	0
	25	12	14.90	14.77	14.72	14.76	14.54		0
	25	25	14.83	14.79	14.75	14.70	14.55		0
	50	0	14.84	14.77	14.73	14.73	14.59		0
64QAM	1	0	15.34	15.29	15.35	15.27	15.27	0-2	0
	1	25	15.28	15.31	15.28	15.33	15.19		0
	1	49	15.36	15.32	15.32	15.30	15.23		0
	25	0	14.91	14.85	14.74	14.72	14.55	0-3	0
	25	12	14.92	14.80	14.70	14.76	14.52		0
	25	25	14.85	14.81	14.73	14.73	14.51		0
	50	0	14.82	14.81	14.71	14.75	14.51		0

Table 8-92
LTE Band 41 PC2 Conducted Powers - 5 MHz Bandwidth - Antenna C

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.38	15.36	15.28	15.22	15.05	0	0
	1	12	15.31	15.28	15.32	15.19	15.00		0
	1	24	15.33	15.31	15.34	15.16	15.02		0
	12	0	15.33	15.25	15.22	15.13	14.98	0-1	0
	12	6	15.33	15.24	15.23	15.15	14.96		0
	12	13	15.28	15.27	15.23	15.13	14.96		0
	25	0	15.28	15.25	15.23	15.20	14.97		0
16QAM	1	0	15.38	15.39	15.35	15.22	15.10	0-1	0
	1	12	15.33	15.33	15.38	15.30	14.99		0
	1	24	15.35	15.34	15.36	15.25	15.05		0
	12	0	14.88	14.83	14.82	14.66	14.51	0-2	0
	12	6	14.90	14.82	14.79	14.71	14.50		0
	12	13	14.85	14.84	14.80	14.69	14.47		0
	25	0	14.78	14.80	14.81	14.72	14.50		0
64QAM	1	0	15.36	15.39	15.36	15.30	15.11	0-2	0
	1	12	15.32	15.37	15.31	15.29	15.10		0
	1	24	15.35	15.34	15.34	15.21	15.08		0
	12	0	14.82	14.77	14.74	14.68	14.49	0-3	0
	12	6	14.84	14.77	14.73	14.74	14.47		0
	12	13	14.77	14.79	14.71	14.68	14.46		0
	25	0	14.77	14.71	14.70	14.65	14.47		0

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 73 of 116

Table 8-93
LTE Band 41 PC2 Conducted Powers - 20 MHz Bandwidth - Antenna D

LTE Band 41 20 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	15.38	15.31	15.18	15.03	15.05	0	0	
	1	50	15.25	15.27	15.12	15.00	14.96		0-1	0
	1	99	15.26	15.39	14.95	15.00	14.84			0
	50	0	15.21	15.22	15.14	14.88	14.90	0		
	50	25	15.14	15.20	15.10	14.89	14.86	0		0
	50	50	15.15	15.20	15.05	14.89	14.79		0	
	100	0	15.17	15.21	15.09	14.87	14.84		0	
16QAM	1	0	15.36	15.33	15.22	14.95	14.99	0-1	0	
	1	50	15.16	15.24	15.17	15.04	14.98		0-2	0
	1	99	15.17	15.38	15.26	15.00	14.84			0
	50	0	14.92	14.89	14.80	14.61	14.55	0		0
	50	25	14.78	14.86	14.76	14.63	14.55			0
	50	50	14.79	14.89	14.69	14.60	14.47		0	
	100	0	14.81	14.89	14.74	14.62	14.45	0		
64QAM	1	0	15.08	15.37	15.21	15.05	15.07	0-2	0	
	1	50	14.92	15.22	15.17	15.04	15.03		0-3	0
	1	99	14.95	15.29	14.93	15.11	14.84			0
	50	0	14.97	14.90	14.88	14.57	14.67	0		
	50	25	14.85	14.92	14.82	14.63	14.62	0		0
	50	50	14.83	14.87	14.75	14.66	14.55		0	
	100	0	14.87	14.91	14.84	14.62	14.62		0	

Table 8-94
LTE Band 41 PC2 Conducted Powers - 15 MHz Bandwidth - Antenna D

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.37	15.27	15.23	14.96	15.06	0	0
	1	36	15.31	15.26	15.21	14.99	15.03		0
	1	74	15.19	15.28	15.06	14.97	14.89		0
	36	0	15.24	15.24	15.24	14.96	15.03	0-1	0
	36	18	15.30	15.21	15.19	14.92	14.95		0
	36	37	15.23	15.22	15.04	14.91	14.90		0
	75	0	15.25	15.20	15.09	14.92	14.91		0
16QAM	1	0	15.35	15.19	15.32	14.92	14.99	0-1	0
	1	36	15.27	15.28	15.29	14.97	14.86		0
	1	74	15.09	15.22	15.14	15.02	14.78		0
	36	0	14.85	14.88	14.77	14.56	14.57	0-2	0
	36	18	14.83	14.84	14.74	14.54	14.56		0
	36	37	14.76	14.85	14.68	14.53	14.51		0
	75	0	14.78	14.81	14.72	14.52	14.57		0
64QAM	1	0	15.37	15.35	15.31	15.00	15.05	0-2	0
	1	36	15.29	15.31	15.26	14.96	15.08		0
	1	74	15.17	15.40	15.11	14.91	14.91		0
	36	0	14.97	14.98	14.96	14.65	14.77	0-3	0
	36	18	14.96	14.95	14.87	14.65	14.75		0
	36	37	14.86	14.96	14.78	14.64	14.68		0
	75	0	14.88	14.95	14.86	14.62	14.73		0

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 74 of 116

Table 8-95
LTE Band 41 PC2 Conducted Powers - 10 MHz Bandwidth - Antenna D

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.38	15.30	15.27	14.94	15.08	0	0
	1	25	15.24	15.23	15.20	15.00	15.03		0
	1	49	15.22	15.25	15.11	15.01	14.96		0
	25	0	15.27	15.28	15.13	14.85	14.96	0-1	0
	25	12	15.28	15.21	15.11	14.91	14.94		0
	25	25	15.24	15.24	15.05	14.90	14.90		0
	50	0	15.25	15.22	15.11	14.89	14.89		0
16QAM	1	0	15.33	15.36	15.29	14.92	15.03	0-1	0
	1	25	15.15	15.40	15.22	14.91	14.91		0
	1	49	15.08	15.34	15.14	14.96	14.99		0
	25	0	14.87	14.90	14.84	14.57	14.62	0-2	0
	25	12	14.88	14.87	14.85	14.63	14.61		0
	25	25	14.84	14.92	14.82	14.64	14.58		0
	50	0	14.81	14.89	14.81	14.64	14.60		0
64QAM	1	0	15.33	15.23	15.09	15.01	14.97	0-2	0
	1	25	15.21	15.22	14.97	14.96	14.89		0
	1	49	15.20	15.25	14.89	14.91	14.85		0
	25	0	14.74	15.01	14.70	14.48	14.55	0-3	0
	25	12	14.73	14.89	14.66	14.46	14.52		0
	25	25	14.69	14.92	14.60	14.50	14.50		0
	50	0	14.84	14.90	14.65	14.47	14.53		0

Table 8-96
LTE Band 41 PC2 Conducted Powers - 5 MHz Bandwidth - Antenna D

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.28	15.31	15.20	14.89	15.03	0	0
	1	12	15.20	15.23	15.16	14.95	15.01		0
	1	24	15.22	15.28	15.10	14.96	15.00		0
	12	0	15.18	15.20	15.15	14.82	14.97	0-1	0
	12	6	15.21	15.20	15.13	14.89	14.93		0
	12	13	15.13	15.22	15.10	14.89	14.94		0
	25	0	15.14	15.21	15.12	14.88	14.95		0
16QAM	1	0	15.09	15.34	15.24	14.94	14.89	0-1	0
	1	12	14.95	15.25	15.21	14.86	14.79		0
	1	24	15.06	15.31	15.15	14.96	14.82		0
	12	0	14.56	14.68	14.66	14.45	14.49	0-2	0
	12	6	14.57	14.69	14.63	14.43	14.43		0
	12	13	14.56	14.70	14.61	14.42	14.42		0
	25	0	14.53	14.66	14.57	14.40	14.40		0
64QAM	1	0	15.29	15.30	15.03	14.94	14.98	0-2	0
	1	12	15.13	15.28	15.08	14.87	14.93		0
	1	24	15.19	15.26	15.05	14.90	14.90		0
	12	0	14.82	14.76	14.76	14.46	14.55	0-3	0
	12	6	14.82	14.84	14.74	14.48	14.52		0
	12	13	14.80	14.85	14.68	14.49	14.52		0
	25	0	14.66	14.75	14.68	14.55	14.51		0

FCC ID: BCGA2200	 SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device		Page 75 of 116

8.3.13 LTE Uplink Carrier Aggregation Conducted Powers

Table 8-97
LTE Uplink Carrier Aggregation Conducted Powers – Antenna C

	PCC									SCC									Power	
Combination	PCC Band	PCC Bandwidth [MHz]	PCC UL Channel	PCC UL Frequency [MHz]	PCC DL Channel	PCC DL Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	SCC Band	SCC Bandwidth [MHz]	SCC UL Channel	SCC UL Frequency [MHz]	SCC DL Channel	SCC DL Frequency [MHz]	Modulation	SCC UL# RB	SCC UL RB Offset	LTE Tx-Power with UL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_7C (1)	LTE B7	20	21100	2535.0	2525	2655.0	QPSK	1	99	LTE B7	20	21298	2554.8	3298	2674.8	QPSK	1	0	12.10	12.09

	PCC									SCC						Power	
Combination	PCC Band	PCC Bandwidth [MHz]	PCC (UL/DL) Channel	PCC (UL/DL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	SCC Band	SCC Bandwidth [MHz]	SCC (UL/DL) Channel	SCC (UL/DL) Frequency [MHz]	Modulation	SCC UL# RB	SCC UL RB Offset	LTE Tx-Power with UL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)	
CA_41C	LTE B41	20	40620	2593.0	QPSK	1	99	LTE B41	20	40818	2612.8	QPSK	1	0	15.39	15.14	

Table 8-98
LTE Uplink Carrier Aggregation Conducted Powers – Antenna D

	PCC									SCC									Power	
Combination	PCC Band	PCC Bandwidth [MHz]	PCC UL Channel	PCC UL Frequency [MHz]	PCC DL Channel	PCC DL Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	SCC Band	SCC Bandwidth [MHz]	SCC UL Channel	SCC UL Frequency [MHz]	SCC DL Channel	SCC DL Frequency [MHz]	Modulation	SCC UL# RB	SCC UL RB Offset	LTE Tx.Power with UL CA Enabled (dBm)	LTE Single Carrier Power (dBm)
CA_7C(1)	LTE B7	20	21350	2560.0	3350	2680.0	QPSK	1	0	LTE B7	20	21152	2540.2	3152	2660.2	QPSK	1	99	11.73	11.96

	PCC									SCC									Power	
Combination	PCC Band	PCC Bandwidth [MHz]	PCC (UL/DL) Channel	PCC (UL/DL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	SCC Band	SCC Bandwidth [MHz]	SCC (UL/DL) Channel	SCC (UL/DL) Frequency [MHz]	Modulation	SCC UL# RB	SCC UL RB Offset	LTE Tx.Power with UL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)				
CA_41C	LTE B41	20	41055	2636.5	QPSK	1	0	LTE B41	20	40857	2616.7	QPSK	1	99	15.00	15.26				

Notes:

1. This device supports uplink carrier aggregation for LTE CA_41C and LTE CA_7C(1) with a maximum of two 20 MHz component carriers. For intraband contiguous carrier aggregation scenarios, 3GPP 36.101 Table 6.2.2A-1 specifies that the aggregate maximum allowed output power is equivalent to the single carrier scenario. 3GPP 36.101 6.2.3A allows for several dB of MPR to be applied when non-contiguous RB allocation is implemented. The conducted powers and MPR settings in this device are permanently implemented per the above 3GPP requirements.
2. Per FCC Guidance, the output power with uplink CA active was measured for the configuration with the highest reported SAR with single carrier for each exposure condition. The power was measured with wideband signal integration over both component carriers.
3. Uplink carrier aggregation is only possible when the device is operating with Power Class 3 for LTE Band 41.



Figure 8-3
Power Measurement Setup

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 76 of 116

8.4 WLAN Conducted Powers

8.4.1 Variant 1

Table 8-99
2.4 GHz WLAN Maximum Average RF Power – Antenna A

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	15.46	14.90	14.90
2417	2	N/A	15.50	15.50
2437	6	15.50	15.41	15.41
2457	10	N/A	15.43	15.43
2462	11	15.42	13.45	13.45

Table 8-100
2.4 GHz WLAN Maximum Average RF Power – Antenna B

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	15.42	15.00	15.00
2417	2	N/A	15.49	15.49
2437	6	15.49	15.50	15.50
2457	10	N/A	15.48	15.48
2462	11	15.40	13.50	13.50

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 77 of 116

Table 8-101
5 GHz WLAN Maximum Average RF Power – Antenna A

5GHz (40MHz) Conducted Power [dBm]				5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode		Freq [MHz]	Channel	IEEE Transmission Mode
		802.11n	802.11ac			802.11ac
5190	38	13.94	13.99	5530	106	13.93
5230	46	16.50	16.42	5610	122	16.86
5270	54	16.82	16.91	5690	138	16.89
5310	62	14.41	14.47	5775	155	16.25

Table 8-102
5 GHz WLAN Maximum Average RF Power – Antenna B

5GHz (40MHz) Conducted Power [dBm]				5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode		Freq [MHz]	Channel	IEEE Transmission Mode
		802.11n	802.11ac			802.11ac
5190	38	13.98	14.00	5530	106	13.91
5230	46	16.24	16.09	5610	122	16.99
5270	54	16.71	16.75	5690	138	16.80
5310	62	14.49	14.28	5775	155	16.50

8.4.2 Variant 2

Table 8-103
2.4 GHz WLAN Maximum Average RF Power – Antenna A

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	15.32	15.00	15.00
2417	2	N/A	15.49	15.49
2437	6	15.35	15.46	15.46
2457	10	N/A	15.48	15.48
2462	11	15.34	13.47	13.47

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 78 of 116

Table 8-104
2.4 GHz WLAN Maximum Average RF Power – Antenna B

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	15.34	15.00	15.00
2417	2	N/A	15.49	15.49
2437	6	15.35	15.47	15.47
2457	10	N/A	15.50	15.50
2462	11	15.30	13.50	13.50

Table 8-105
5 GHz WLAN Maximum Average RF Power – Antenna A

5GHz (40MHz) Conducted Power [dBm]				5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode		Freq [MHz]	Channel	IEEE Transmission Mode
		802.11n	802.11ac			802.11ac
5190	38	13.98	13.93	5530	106	13.85
5230	46	16.47	16.42	5610	122	16.92
5270	54	17.00	16.85	5690	138	17.00
5310	62	14.32	14.42	5775	155	16.25

Table 8-106
5 GHz WLAN Maximum Average RF Power – Antenna B

5GHz (40MHz) Conducted Power [dBm]				5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode		Freq [MHz]	Channel	IEEE Transmission Mode
		802.11n	802.11ac			802.11ac
5190	38	13.95	13.91	5530	106	14.00
5230	46	16.25	16.14	5610	122	16.87
5270	54	16.59	16.74	5690	138	16.85
5310	62	14.50	14.41	5775	155	16.37

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device		Page 79 of 116

8.4.3 Notes for WLAN

- Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:
- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The WLAN chipset in this device is produced by two different suppliers. The electrically identical modules are manufactured with the identical mechanical structure to meet the same specifications and functions.
- WLAN SAR worst case configuration was evaluated for Variant 1 and Variant 2. The Variant with the highest reported SAR value was evaluated for the remaining WLAN configurations.
- The bolded data rate and channel above were tested for SAR.
- Full power measurements were performed for Variant 1 and Variant 2 per FCC KDB Procedures 248227.




Figure 8-4
Power Measurement Setup

8.5 Bluetooth Conducted Powers

Table 8-107
Maximum Bluetooth Average RF Power – Antenna A – Variant 1

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2402	GFSK	1.0	0	15.69	37.068
2441	GFSK	1.0	39	15.10	32.359
2480	GFSK	1.0	78	16.04	40.179

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 80 of 116

Table 8-108
Maximum Bluetooth Average RF Power – Antenna A - Variant 2

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2402	GFSK	1.0	0	16.57	45.394
2441	GFSK	1.0	39	16.49	44.566
2480	GFSK	1.0	78	15.83	38.282

Table 8-109
Reduced Bluetooth Average RF Power – Antenna A - Variant 1

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2402	GFSK	1.0	0	9.57	9.057
2441	GFSK	1.0	39	9.75	9.441
2480	GFSK	1.0	78	9.55	9.016

Table 8-110
Reduced Bluetooth Average RF Power – Antenna A - Variant 2

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2402	GFSK	1.0	0	9.17	8.260
2441	GFSK	1.0	39	9.75	9.441
2480	GFSK	1.0	78	9.29	8.492

Note: The bolded data rates and channel above were tested for SAR.

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 81 of 116




Figure 8-5
Bluetooth Transmission Plot & Duty Cycle Calculation – Antenna A Variant 1

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{2.896\text{ms}}{3.744\text{ms}} * 100\% = 77.4\%$$




Figure 8-6
Bluetooth Transmission Plot & Duty Cycle Calculation – Antenna A Variant 2

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{2.904\text{ms}}{3.752\text{ms}} * 100\% = 77.4\%$$

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 82 of 116




Figure 8-7
Reduced Bluetooth Transmission Plot & Duty Cycle Calculation – Antenna A Variant 2

$$Duty\ Cycle = \frac{Pulse\ Width}{Period} * 100\% = \frac{2.904ms}{3.752ms} * 100\% = 77.4\%$$

8.5.1 Bluetooth Power Reduction Verification Summary

Antenna	Mode/Band	Condition (s)	Maximum Target Power [dBm]	Reduced Target Power [dBm]	Maximum Measured Power	Reduced Measured Power	Verdict
			(Tolerance [dB])	(Tolerance [dB])	[dBm]	[dBm]	
A	2.4 GHz Bluetooth	5 GHz WLAN ON Antenna A	15.50 (+1.5/-2.0)	8.50 (+1.5/-2.0)	15.29	7.68	Pass
	2.4 GHz Bluetooth	5 GHz WLAN ON Antenna B	15.50 (+1.5/-2.0)	8.50 (+1.5/-2.0)	15.29	7.7	Pass
	2.4 GHz Bluetooth	5 GHz WLAN ON Antenna A & Antenna B	15.50 (+1.5/-2.0)	8.50 (+1.5/-2.0)	15.29	8.09	Pass

Conducted powers were measured for each Mode/Band and applied condition. All conducted power measurements were verified to be within tolerance.

FCC ID: BCGA2200	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 83 of 116

8.5.2 Notes for Bluetooth

- The Bluetooth chipset in this device is produced by two different suppliers. The electrically identical modules are manufactured with the identical mechanical structure to meet the same specifications and functions. Two device variants are referenced as Variant 1 and Variant 2 in this report.
- Bluetooth SAR worst case configuration was evaluated for Variant 1 and Variant 2. The Variant with the highest reported SAR value was evaluated for the remaining Bluetooth configurations.
- Full power measurements were performed for Variant 1 and Variant 2 per FCC KDB Procedures 248227.




Figure 8-8
Power Measurement Setup

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 84 of 116

9 SYSTEM VERIFICATION

9.1 Tissue Verification

Table 9-1
Measured Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
5/28/2019	750B	22.5	680	0.915	55.520	0.928	55.504	-4.49%	-0.51%
			685	0.920	55.505	0.959	55.745	-4.07%	-0.43%
			700	0.922	55.500	0.959	55.726	-3.86%	-0.41%
			710	0.925	55.498	0.960	55.687	-3.65%	-0.36%
			720	0.929	55.474	0.961	55.648	-3.33%	-0.31%
			725	0.931	55.465	0.961	55.629	-3.12%	-0.29%
			740	0.936	55.432	0.963	55.570	-2.80%	-0.25%
			755	0.942	55.398	0.964	55.512	-2.28%	-0.21%
			770	0.947	55.364	0.965	55.453	-1.87%	-0.16%
			785	0.953	55.332	0.966	55.395	-1.35%	-0.11%
			800	0.958	55.295	0.967	55.336	-0.93%	-0.07%
			680	0.933	54.419	0.958	55.804	-2.61%	-2.48%
6/27/2019	750B	20.9	685	0.939	54.383	0.959	55.745	-2.09%	-2.44%
			700	0.941	54.374	0.959	55.726	-1.88%	-2.43%
			710	0.944	54.355	0.960	55.687	-1.67%	-2.39%
			720	0.948	54.334	0.961	55.648	-1.35%	-2.36%
			725	0.950	54.321	0.961	55.629	-1.14%	-2.35%
			740	0.955	54.288	0.963	55.570	-0.83%	-2.31%
			755	0.961	54.250	0.964	55.512	-0.31%	-2.27%
			770	0.966	54.215	0.965	55.453	0.10%	-2.23%
			785	0.972	54.187	0.966	55.395	0.62%	-2.18%
			800	0.978	54.165	0.967	55.336	1.14%	-2.12%
			835	1.003	53.678	0.970	55.200	3.40%	-2.76%
			850	1.010	53.662	0.988	55.154	2.23%	-2.71%
5/28/2019	835B	19.7	800	0.923	53.247	0.967	55.336	-4.55%	-3.78%
			820	0.930	53.187	0.969	55.258	-4.02%	-3.75%
			835	0.936	53.155	0.970	55.200	-3.51%	-3.70%
			850	0.942	53.129	0.988	55.154	-4.66%	-3.67%
5/28/2019	1750B	22.2	1710	1.434	52.742	1.463	53.537	-1.98%	-1.48%
			1750	1.463	52.692	1.488	53.432	-1.68%	-1.38%
			1790	1.491	52.627	1.514	53.326	-1.52%	-1.31%
5/28/2019	1900B	22.2	1850	1.531	52.530	1.520	53.300	0.72%	-1.44%
			1880	1.552	52.482	1.520	53.300	2.11%	-1.53%
6/30/2019	2300B	24.6	1910	1.572	52.448	1.520	53.300	3.42%	-1.60%
			2300	1.881	51.031	1.809	52.900	3.98%	-3.53%
			2310	1.885	50.989	1.816	52.887	3.80%	-3.59%
			2320	1.896	50.987	1.826	52.873	2.83%	-3.57%
5/22/2019	2450B	23.0	2400	1.969	50.734	1.902	52.767	3.52%	-3.85%
			2450	2.027	50.586	1.950	52.700	3.95%	-4.01%
			2500	2.082	50.441	2.021	52.636	3.02%	-4.17%
			2400	1.980	50.792	1.902	52.767	4.10%	-3.74%
6/5/2019	2450B	22.2	2450	2.024	50.720	1.950	52.700	3.79%	-3.76%
			2500	2.067	50.641	2.021	52.636	2.28%	-3.79%
			2600	2.166	50.955	2.163	52.509	0.14%	-2.96%
5/28/2019	2600B	20.1	2650	2.215	50.861	2.234	52.445	-0.85%	-3.02%
			2700	2.262	50.791	2.305	52.382	-1.87%	-3.04%
			2500	2.064	50.523	2.021	52.636	2.13%	-4.01%
			2550	2.110	50.436	2.092	52.573	0.86%	-4.06%
7/3/2019	2600B	20.9	2600	2.161	50.329	2.163	52.509	-0.09%	-4.15%
			2650	2.209	50.250	2.234	52.445	-1.12%	-4.19%
			2700	2.257	50.135	2.305	52.382	-2.08%	-4.29%
			5180	5.376	48.044	5.276	48.041	1.90%	-2.03%
05/28/2019	5200B-5800B	22.6	5200	5.404	48.020	5.299	48.014	1.98%	-2.03%
			5220	5.424	47.974	5.323	48.987	1.90%	-2.07%
			5240	5.450	47.920	5.346	48.960	1.95%	-2.12%
			5260	5.481	47.894	5.369	48.933	2.09%	-2.12%
			5280	5.502	47.860	5.393	48.906	2.02%	-2.14%
			5300	5.526	47.834	5.416	48.879	2.03%	-2.14%
			5320	5.554	47.788	5.439	48.851	2.11%	-2.18%
			5500	5.801	47.487	5.650	48.607	2.67%	-2.30%
			5520	5.826	47.464	5.673	48.580	2.70%	-2.30%
			5540	5.851	47.442	5.696	48.553	2.72%	-2.29%
			5560	5.881	47.397	5.720	48.526	2.81%	-2.33%
			5580	5.914	47.358	5.743	48.499	2.98%	-2.35%
			5600	5.939	47.332	5.766	48.471	3.00%	-2.35%
			5620	5.967	47.313	5.790	48.444	3.06%	-2.33%
			5640	5.990	47.264	5.813	48.417	3.04%	-2.38%
			5660	6.024	47.221	5.837	48.390	3.20%	-2.42%
			5680	6.053	47.190	5.860	48.363	3.29%	-2.43%
			5700	6.076	47.162	5.883	48.336	3.28%	-2.39%
			5745	6.126	47.109	5.936	48.275	3.20%	-2.42%
			5765	6.161	47.046	5.959	48.248	3.35%	-2.45%
			5785	6.194	47.022	5.982	48.220	3.54%	-2.48%
			5800	6.211	47.020	6.000	48.200	3.52%	-2.45%
			5805	6.214	47.018	6.006	48.193	3.46%	-2.44%
			5825	6.235	46.970	6.029	48.166	3.42%	-2.48%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.


FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 85 of 116

9.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

**Table 9-2
System Verification Results**

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
AM7	750	BODY	05/28/2019	22.2	20.8	0.200	1097	3837	1.840	8.560	9.200	7.48%
AM7	750	BODY	06/27/2019	22.6	21.1	0.200	1034	3837	1.790	8.570	8.950	4.43%
AM2	835	BODY	05/28/2019	21.3	20.1	0.200	4d040	7416	2.040	9.560	10.200	6.69%
AM6	835	BODY	05/28/2019	23.1	21.0	0.200	4d040	7427	1.800	9.560	9.000	-5.86%
AM3	1750	BODY	05/28/2019	20.9	20.2	0.100	1104	7420	3.910	36.600	39.100	6.83%
AM3	1900	BODY	05/28/2019	20.9	20.2	0.100	5d181	7420	3.760	39.500	37.600	-4.81%
AM5	2300	BODY	06/30/2019	18.3	22.6	0.100	1038	3318	4.930	46.700	49.300	5.57%
AM2	2450	BODY	05/22/2019	22.3	21.8	0.100	750	7416	5.440	51.200	54.400	6.25%
AM5	2450	BODY	06/05/2019	19.9	20.8	0.100	921	3318	5.300	50.800	53.000	4.33%
AM5	2600	BODY	05/28/2019	21.4	20.0	0.100	1069	3318	5.810	55.300	58.100	5.06%
AM7	2600	BODY	07/03/2019	20.9	21.9	0.100	1069	3837	5.330	55.300	53.300	-3.62%
AM8	5250	BODY	05/28/2019	21.0	22.0	0.050	1163	7491	3.610	77.700	72.200	-7.08%
AM8	5600	BODY	05/28/2019	20.9	22.0	0.050	1163	7491	4.000	80.100	80.000	-0.12%
AM8	5750	BODY	05/28/2019	21.2	22.0	0.050	1163	7491	3.670	77.800	73.400	-5.66%



**Figure 10-1
System Verification Setup Diagram**



**Figure 10-2
System Verification Setup Photo**

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 86 of 116

10 SAR DATA SUMMARY

10.1 Standalone Body SAR Data

Table 10-1
GSM 850 Body SAR – Antenna C

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot
MHz	Ch.												(W/kg)		(W/kg)	(W/kg)		
824.20	128	GSM 850	GPRS	24.75	23.70	-0.02	0 mm	Antenna C	F9FYLO1XMLWN	2	1:4.15	back	0.833	1.274	1.061	0.415	0.529	
836.60	190	GSM 850	GPRS	24.75	23.62	-0.11	0 mm	Antenna C	F9FYLO1XMLWN	2	1:4.15	back	0.772	1.297	1.001	0.386	0.501	
848.80	251	GSM 850	GPRS	24.75	23.65	-0.16	0 mm	Antenna C	F9FYLO1XMLWN	2	1:4.15	back	0.719	1.288	0.926	0.359	0.462	
824.20	128	GSM 850	GPRS	24.75	23.70	0.00	0 mm	Antenna C	F9FYLO1XMLWN	2	1:4.15	top	0.598	1.274	0.762	0.342	0.436	
836.60	190	GSM 850	GPRS	24.75	23.62	0.08	0 mm	Antenna C	F9FYLO1XMLWN	2	1:4.15	top	0.715	1.297	0.927	0.396	0.514	
848.80	251	GSM 850	GPRS	24.75	23.65	0.00	0 mm	Antenna C	F9FYLO1XMLWN	2	1:4.15	top	0.592	1.288	0.762	0.340	0.438	
836.60	190	GSM 850	GPRS	24.75	23.62	-0.15	0 mm	Antenna C	F9FYLO1XMLWN	2	1:4.15	bottom	0.020	1.297	0.026	0.009	0.012	
836.60	190	GSM 850	GPRS	24.75	23.62	0.01	0 mm	Antenna C	F9FYLO1XMLWN	2	1:4.15	right	0.134	1.297	0.174	0.063	0.082	
836.60	190	GSM 850	GPRS	24.75	23.62	-0.04	0 mm	Antenna C	F9FYLO1XMLWN	2	1:4.15	left	0.015	1.297	0.019	0.006	0.008	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak							Body 1.6 W/kg (mW/g) averaged over 1 gram											
Uncontrolled Exposure/General Population																		

Table 10-2
GSM 850 Body SAR – Antenna D

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	(W/kg)	(W/kg)	
824.20	128	GSM 850	GPRS	25.50	25.50	-0.04	0 mm	Antenna D	F9FYLO0EMLWN	2	1:4.15	back	1.120	1.000	1.120	0.560	0.560	
836.60	190	GSM 850	GPRS	25.50	25.45	-0.09	0 mm	Antenna D	F9FYLO0EMLWN	2	1:4.15	back	1.130	1.012	1.144	0.562	0.569	
848.80	251	GSM 850	GPRS	25.50	25.42	-0.02	0 mm	Antenna D	F9FYLO0EMLWN	2	1:4.15	back	1.140	1.019	1.162	0.569	0.580	A1
824.20	128	GSM 850	GPRS	25.50	25.50	-0.09	0 mm	Antenna D	F9FYLO0EMLWN	2	1:4.15	top	1.100	1.000	1.100	0.618	0.618	
836.60	190	GSM 850	GPRS	25.50	25.45	-0.11	0 mm	Antenna D	F9FYLO0EMLWN	2	1:4.15	top	1.030	1.012	1.042	0.551	0.558	
848.80	251	GSM 850	GPRS	25.50	25.42	-0.02	0 mm	Antenna D	F9FYLO0EMLWN	2	1:4.15	top	1.130	1.019	1.151	0.626	0.638	
836.60	190	GSM 850	GPRS	25.50	25.45	-0.04	0 mm	Antenna D	F9FYLO0EMLWN	2	1:4.15	bottom	0.023	1.012	0.023	0.011	0.011	
836.60	190	GSM 850	GPRS	25.50	25.45	0.00	0 mm	Antenna D	F9FYLO0EMLWN	2	1:4.15	right	0.019	1.012	0.019	0.009	0.009	
836.60	190	GSM 850	GPRS	25.50	25.45	0.09	0 mm	Antenna D	F9FYLO0EMLWN	2	1:4.15	left	0.168	1.012	0.170	0.079	0.080	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak												Body 1.6 W/kg (mW/g) averaged over 1 gram						
Uncontrolled Exposure/General Population																		

Table 10-3
GSM 1900 Body SAR – Antenna C

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	(W/kg)		
1850.20	512	GSM 1900	GPRS	18.95	18.68	-0.02	0 mm	Antenna C	F9FYLO0EMLWN	2	1:4.15	back	0.837	1.064	0.891	0.379	0.403	
1880.00	661	GSM 1900	GPRS	18.95	18.55	0.02	0 mm	Antenna C	F9FYLO0EMLWN	2	1:4.15	back	0.887	1.096	0.972	0.404	0.443	
1909.80	810	GSM 1900	GPRS	18.95	18.69	-0.03	0 mm	Antenna C	F9FYLO0EMLWN	2	1:4.15	back	0.883	1.062	0.938	0.403	0.428	
1880.00	661	GSM 1900	GPRS	18.95	18.55	0.00	0 mm	Antenna C	F9FYLO0EMLWN	2	1:4.15	top	0.590	1.096	0.647	0.276	0.302	
1880.00	661	GSM 1900	GPRS	18.95	18.55	0.00	0 mm	Antenna C	F9FYLO0EMLWN	2	1:4.15	bottom	0.000	1.096	0.000	0.000	0.000	
1880.00	661	GSM 1900	GPRS	18.95	18.55	-0.02	0 mm	Antenna C	F9FYLO0EMLWN	2	1:4.15	right	0.080	1.096	0.088	0.038	0.042	
1880.00	661	GSM 1900	GPRS	18.95	18.55	0.07	0 mm	Antenna C	F9FYLO0EMLWN	2	1:4.15	left	0.026	1.096	0.028	0.012	0.013	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 87 of 116

Table 10-4
GSM 1900 Body SAR – Antenna D

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	(W/kg)		
1850.20	512	GSM 1900	GPRS	18.25	17.87	-0.05	0 mm	Antenna D	F9FYL00EMLWN	2	1:4.15	back	0.875	1.091	0.955	0.369	0.403	
1880.00	661	GSM 1900	GPRS	18.25	17.95	-0.02	0 mm	Antenna D	F9FYL00EMLWN	2	1:4.15	back	0.885	1.072	0.949	0.375	0.402	
1909.80	810	GSM 1900	GPRS	18.25	17.97	0.05	0 mm	Antenna D	F9FYL00EMLWN	2	1:4.15	back	0.946	1.067	1.009	0.397	0.424	A2
1880.00	661	GSM 1900	GPRS	18.25	17.95	-0.01	0 mm	Antenna D	F9FYL00EMLWN	2	1:4.15	top	0.610	1.072	0.654	0.278	0.298	
1880.00	661	GSM 1900	GPRS	18.25	17.95	0.00	0 mm	Antenna D	F9FYL00EMLWN	2	1:4.15	bottom	0.000	1.072	0.000	0.000	0.000	
1880.00	661	GSM 1900	GPRS	18.25	17.95	-0.02	0 mm	Antenna D	F9FYL00EMLWN	2	1:4.15	right	0.011	1.072	0.012	0.005	0.005	
1880.00	661	GSM 1900	GPRS	18.25	17.95	0.04	0 mm	Antenna D	F9FYL00EMLWN	2	1:4.15	left	0.058	1.072	0.062	0.026	0.028	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 10-5
UMTS 850 Body SAR – Antenna C

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	(W/kg)	(W/kg)	
826.40	4132	UMTS 850	RMC	17.70	17.65	0.08	0 mm	Antenna C	F9FYL00EMLWN	1:1	back	1.030	1.012	1.042	0.520	0.526	
836.60	4183	UMTS 850	RMC	17.70	17.60	0.10	0 mm	Antenna C	F9FYL00EMLWN	1:1	back	0.994	1.023	1.017	0.500	0.512	
846.60	4233	UMTS 850	RMC	17.70	17.58	0.07	0 mm	Antenna C	F9FYL00EMLWN	1:1	back	0.960	1.028	0.987	0.486	0.500	
836.60	4183	UMTS 850	RMC	17.70	17.60	-0.05	0 mm	Antenna C	F9FYL00EMLWN	1:1	top	0.720	1.023	0.737	0.411	0.420	
836.60	4183	UMTS 850	RMC	17.70	17.60	0.02	0 mm	Antenna C	F9FYL00EMLWN	1:1	bottom	0.017	1.023	0.017	0.009	0.009	
836.60	4183	UMTS 850	RMC	17.70	17.60	-0.09	0 mm	Antenna C	F9FYL00EMLWN	1:1	right	0.101	1.023	0.103	0.051	0.052	
836.60	4183	UMTS 850	RMC	17.70	17.60	-0.13	0 mm	Antenna C	F9FYL00EMLWN	1:1	left	0.015	1.023	0.015	0.008	0.008	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram										

Table 10-6
UMTS 850 Body SAR – Antenna D

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	(W/kg)	(W/kg)	
826.40	4132	UMTS 850	RMC	19.20	19.12	-0.14	0 mm	Antenna D	F9FYL00EMLWN	1:1	back	1.000	1.019	1.019	0.503	0.513	
836.60	4183	UMTS 850	RMC	19.20	19.04	-0.20	0 mm	Antenna D	F9FYL00EMLWN	1:1	back	1.000	1.038	1.038	0.498	0.517	
846.60	4233	UMTS 850	RMC	19.20	19.14	-0.03	0 mm	Antenna D	F9FYL00EMLWN	1:1	back	1.050	1.014	1.065	0.528	0.535	A3
826.40	4132	UMTS 850	RMC	19.20	19.12	0.02	0 mm	Antenna D	F9FYL00EMLWN	1:1	top	0.930	1.019	0.948	0.505	0.515	
836.60	4183	UMTS 850	RMC	19.20	19.04	0.02	0 mm	Antenna D	F9FYL00EMLWN	1:1	top	0.951	1.038	0.987	0.509	0.528	
846.60	4233	UMTS 850	RMC	19.20	19.14	0.08	0 mm	Antenna D	F9FYL00EMLWN	1:1	top	0.895	1.014	0.908	0.482	0.489	
836.60	4183	UMTS 850	RMC	19.20	19.04	0.16	0 mm	Antenna D	F9FYL00EMLWN	1:1	bottom	0.035	1.038	0.036	0.016	0.017	
836.60	4183	UMTS 850	RMC	19.20	19.04	0.11	0 mm	Antenna D	F9FYL00EMLWN	1:1	right	0.029	1.038	0.030	0.013	0.013	
836.60	4183	UMTS 850	RMC	19.20	19.04	0.07	0 mm	Antenna D	F9FYL00EMLWN	1:1	left	0.236	1.038	0.245	0.111	0.115	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 88 of 116

Table 10-7
UMTS 1750 Body SAR – Antenna C

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	(W/kg)	(W/kg)	
1712.40	1312	UMTS 1750	RMC	13.30	13.25	-0.01	0 mm	Antenna C	F9FYL00EMLWN	1:1	back	1.020	1.012	1.032	0.484	0.490	
1732.40	1412	UMTS 1750	RMC	13.30	13.28	-0.03	0 mm	Antenna C	F9FYL00EMLWN	1:1	back	1.030	1.005	1.035	0.491	0.493	A4
1752.60	1513	UMTS 1750	RMC	13.30	13.20	0.01	0 mm	Antenna C	F9FYL00EMLWN	1:1	back	1.020	1.023	1.043	0.487	0.498	
1732.40	1412	UMTS 1750	RMC	13.30	13.28	-0.01	0 mm	Antenna C	F9FYL00EMLWN	1:1	top	0.609	1.005	0.612	0.297	0.298	
1732.40	1412	UMTS 1750	RMC	13.30	13.28	0.14	0 mm	Antenna C	F9FYL00EMLWN	1:1	bottom	0.002	1.005	0.002	0.001	0.001	
1732.40	1412	UMTS 1750	RMC	13.30	13.28	0.07	0 mm	Antenna C	F9FYL00EMLWN	1:1	right	0.080	1.005	0.080	0.037	0.037	
1732.40	1412	UMTS 1750	RMC	13.30	13.28	0.16	0 mm	Antenna C	F9FYL00EMLWN	1:1	left	0.017	1.005	0.017	0.008	0.008	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram									

Table 10-8
UMTS 1750 Body SAR – Antenna D

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	(W/kg)	(W/kg)	
1712.40	1312	UMTS 1750	RMC	13.20	13.14	0.01	0 mm	Antenna D	F9FYL00EMLWN	1:1	back	0.878	1.014	0.890	0.385	0.390	
1732.40	1412	UMTS 1750	RMC	13.20	13.10	-0.04	0 mm	Antenna D	F9FYL00EMLWN	1:1	back	0.729	1.023	0.746	0.322	0.329	
1752.60	1513	UMTS 1750	RMC	13.20	13.07	-0.01	0 mm	Antenna D	F9FYL00EMLWN	1:1	back	0.989	1.030	1.019	0.433	0.446	
1732.40	1412	UMTS 1750	RMC	13.20	13.10	0.01	0 mm	Antenna D	F9FYL00EMLWN	1:1	top	0.477	1.023	0.488	0.222	0.227	
1732.40	1412	UMTS 1750	RMC	13.20	13.10	0.07	0 mm	Antenna D	F9FYL00EMLWN	1:1	bottom	0.000	1.023	0.000	0.000	0.000	
1732.40	1412	UMTS 1750	RMC	13.20	13.10	0.05	0 mm	Antenna D	F9FYL00EMLWN	1:1	right	0.008	1.023	0.008	0.004	0.004	
1732.40	1412	UMTS 1750	RMC	13.20	13.10	0.01	0 mm	Antenna D	F9FYL00EMLWN	1:1	left	0.049	1.023	0.050	0.023	0.024	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram									

Table 10-9
UMTS 1900 Body SAR – Antenna C

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	(W/kg)		
1852.40	9262	UMTS 1900	RMC	13.10	12.90	-0.02	0 mm	Antenna C	F9FYL01XMLWN	1:1	back	1.100	1.047	1.152	0.497	0.520	
1880.00	9400	UMTS 1900	RMC	13.10	12.99	-0.02	0 mm	Antenna C	F9FYL01XMLWN	1:1	back	1.140	1.026	1.170	0.516	0.529	A5
1907.60	9538	UMTS 1900	RMC	13.10	13.08	-0.01	0 mm	Antenna C	F9FYL01XMLWN	1:1	back	1.120	1.005	1.126	0.509	0.512	
1880.00	9400	UMTS 1900	RMC	13.10	12.99	-0.03	0 mm	Antenna C	F9FYL01XMLWN	1:1	top	0.762	1.026	0.782	0.356	0.365	
1880.00	9400	UMTS 1900	RMC	13.10	12.99	0.00	0 mm	Antenna C	F9FYL01XMLWN	1:1	bottom	0.000	1.026	0.000	0.000	0.000	
1880.00	9400	UMTS 1900	RMC	13.10	12.99	0.01	0 mm	Antenna C	F9FYL01XMLWN	1:1	right	0.101	1.026	0.104	0.047	0.048	
1880.00	9400	UMTS 1900	RMC	13.10	12.99	-0.02	0 mm	Antenna C	F9FYL01XMLWN	1:1	left	0.035	1.026	0.036	0.017	0.017	
1880.00	9400	UMTS 1900	RMC	13.10	12.99	-0.02	0 mm	Antenna C	F9FYL01XMLWN	1:1	back	1.130	1.026	1.159	0.518	0.531	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram									

Note: Blue entry represents variability measurement.

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 89 of 116

Table 10-10
UMTS 1900 Body SAR – Antenna D

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	(W/kg)	(W/kg)	
1852.40	9262	UMTS 1900	RMC	12.00	12.00	0.03	0 mm	Antenna D	F9FYLO1XMLWN	1:1	back	1.090	1.000	1.090	0.474	0.474	
1880.00	9400	UMTS 1900	RMC	12.00	11.92	0.01	0 mm	Antenna D	F9FYLO1XMLWN	1:1	back	1.110	1.019	1.131	0.481	0.490	
1907.60	9538	UMTS 1900	RMC	12.00	11.90	-0.01	0 mm	Antenna D	F9FYLO1XMLWN	1:1	back	1.140	1.023	1.166	0.497	0.508	
1880.00	9400	UMTS 1900	RMC	12.00	11.92	-0.04	0 mm	Antenna D	F9FYLO1XMLWN	1:1	top	0.650	1.019	0.662	0.296	0.302	
1880.00	9400	UMTS 1900	RMC	12.00	11.92	0.00	0 mm	Antenna D	F9FYLO1XMLWN	1:1	bottom	0.000	1.019	0.000	0.000	0.000	
1880.00	9400	UMTS 1900	RMC	12.00	11.92	0.05	0 mm	Antenna D	F9FYLO1XMLWN	1:1	right	0.009	1.019	0.009	0.004	0.004	
1880.00	9400	UMTS 1900	RMC	12.00	11.92	0.08	0 mm	Antenna D	F9FYLO1XMLWN	1:1	left	0.052	1.019	0.053	0.023	0.023	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram									

Table 10-11
LTE Band 71 Body SAR – Antenna C

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
680.50	133297	Mid	LTE Band 71	20	18.10	18.05	-0.02	0	Antenna C	F9FYLO0UMLWN	QPSK	1	99	0 mm	back	1:1	0.910	1.012	0.921	0.449	0.454	A6
680.50	133297	Mid	LTE Band 71	20	18.10	17.93	-0.04	0	Antenna C	F9FYLO0UMLWN	QPSK	50	50	0 mm	back	1:1	0.984	1.040	1.023	0.482	0.501	
680.50	133297	Mid	LTE Band 71	20	18.10	17.91	-0.04	0	Antenna C	F9FYLO0UMLWN	QPSK	100	0	0 mm	back	1:1	0.959	1.045	1.002	0.471	0.492	
680.50	133297	Mid	LTE Band 71	20	18.10	18.05	-0.03	0	Antenna C	F9FYLO0UMLWN	QPSK	1	99	0 mm	top	1:1	0.502	1.012	0.508	0.252	0.255	
680.50	133297	Mid	LTE Band 71	20	18.10	17.93	-0.05	0	Antenna C	F9FYLO0UMLWN	QPSK	50	50	0 mm	top	1:1	0.529	1.040	0.550	0.272	0.283	
680.50	133297	Mid	LTE Band 71	20	18.10	18.05	0.06	0	Antenna C	F9FYLO0UMLWN	QPSK	1	99	0 mm	bottom	1:1	0.023	1.012	0.023	0.013	0.013	
680.50	133297	Mid	LTE Band 71	20	18.10	17.93	-0.06	0	Antenna C	F9FYLO0UMLWN	QPSK	50	50	0 mm	bottom	1:1	0.026	1.040	0.027	0.016	0.017	
680.50	133297	Mid	LTE Band 71	20	18.10	18.05	0.05	0	Antenna C	F9FYLO0UMLWN	QPSK	1	99	0 mm	right	1:1	0.113	1.012	0.114	0.055	0.056	
680.50	133297	Mid	LTE Band 71	20	18.10	17.93	0.07	0	Antenna C	F9FYLO0UMLWN	QPSK	50	50	0 mm	right	1:1	0.113	1.040	0.118	0.055	0.057	
680.50	133297	Mid	LTE Band 71	20	18.10	18.05	0.04	0	Antenna C	F9FYLO0UMLWN	QPSK	1	99	0 mm	left	1:1	0.021	1.012	0.021	0.009	0.009	
680.50	133297	Mid	LTE Band 71	20	18.10	17.93	-0.02	0	Antenna C	F9FYLO0UMLWN	QPSK	50	50	0 mm	left	1:1	0.027	1.040	0.028	0.012	0.012	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram														

Table 10-12
LTE Band 71 Body SAR – Antenna D

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
680.50	133297	Mid	LTE Band 71	20	17.20	16.89	0.11	0	Antenna D	F9FYLO08MLWP	QPSK	1	0	0 mm	back	1:1	0.896	1.074	0.962	0.448	0.481	
680.50	133297	Mid	LTE Band 71	20	17.20	16.84	0.00	0	Antenna D	F9FYLO08MLWP	QPSK	50	0	0 mm	back	1:1	0.869	1.086	0.944	0.434	0.471	
680.50	133297	Mid	LTE Band 71	20	17.20	16.83	0.00	0	Antenna D	F9FYLO08MLWP	QPSK	100	0	0 mm	back	1:1	0.854	1.089	0.930	0.428	0.466	
680.50	133297	Mid	LTE Band 71	20	17.20	16.89	0.00	0	Antenna D	F9FYLO08MLWP	QPSK	1	0	0 mm	top	1:1	0.430	1.074	0.462	0.217	0.233	
680.50	133297	Mid	LTE Band 71	20	17.20	16.84	-0.17	0	Antenna D	F9FYLO08MLWP	QPSK	50	0	0 mm	top	1:1	0.416	1.086	0.452	0.212	0.230	
680.50	133297	Mid	LTE Band 71	20	17.20	16.89	0.19	0	Antenna D	F9FYLO08MLWP	QPSK	1	0	0 mm	bottom	1:1	0.014	1.074	0.015	0.009	0.010	
680.50	133297	Mid	LTE Band 71	20	17.20	16.84	0.05	0	Antenna D	F9FYLO08MLWP	QPSK	50	0	0 mm	bottom	1:1	0.014	1.086	0.015	0.009	0.010	
680.50	133297	Mid	LTE Band 71	20	17.20	16.89	0.19	0	Antenna D	F9FYLO08MLWP	QPSK	1	0	0 mm	right	1:1	0.011	1.074	0.012	0.005	0.005	
680.50	133297	Mid	LTE Band 71	20	17.20	16.84	0.03	0	Antenna D	F9FYLO08MLWP	QPSK	50	0	0 mm	right	1:1	0.014	1.086	0.015	0.006	0.007	
680.50	133297	Mid	LTE Band 71	20	17.20	16.89	0.06	0	Antenna D	F9FYLO08MLWP	QPSK	1	0	0 mm	left	1:1	0.096	1.074	0.103	0.048	0.052	
680.50	133297	Mid	LTE Band 71	20	17.20	16.84	0.04	0	Antenna D	F9FYLO08MLWP	QPSK	50	0	0 mm	left	1:1	0.100	1.086	0.109	0.050	0.054	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram														

FCC ID: BCGA2200		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 90 of 116	

Table 10-13
LTE Band 12 Body SAR – Antenna C

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)		Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Pilot #
MHz	Ch.															(W/kg)	(W/kg)		(W/kg)	(W/kg)		
707.50	23095	Mid	LTE Band 12	10	17.50	17.43	0.14	0	Antenna C	F9FYL00UMLWN	QPSK	1	49	0 mm	back	1:1	0.893	1.016	0.907	0.444	0.451	A7
707.50	23095	Mid	LTE Band 12	10	17.50	17.40	-0.06	0	Antenna C	F9FYL00UMLWN	QPSK	25	25	0 mm	back	1:1	0.910	1.023	0.931	0.441	0.451	
707.50	23095	Mid	LTE Band 12	10	17.50	17.25	-0.03	0	Antenna C	F9FYL00UMLWN	QPSK	50	0	0 mm	back	1:1	0.866	1.059	0.917	0.430	0.455	
707.50	23095	Mid	LTE Band 12	10	17.50	17.43	-0.04	0	Antenna C	F9FYL00UMLWN	QPSK	1	49	0 mm	top	1:1	0.496	1.016	0.504	0.227	0.231	
707.50	23095	Mid	LTE Band 12	10	17.50	17.40	-0.03	0	Antenna C	F9FYL00UMLWN	QPSK	25	25	0 mm	top	1:1	0.511	1.023	0.523	0.280	0.286	
707.50	23095	Mid	LTE Band 12	10	17.50	17.43	0.15	0	Antenna C	F9FYL00UMLWN	QPSK	1	49	0 mm	bottom	1:1	0.019	1.016	0.019	0.009	0.009	
707.50	23095	Mid	LTE Band 12	10	17.50	17.40	-0.03	0	Antenna C	F9FYL00UMLWN	QPSK	25	25	0 mm	bottom	1:1	0.018	1.023	0.018	0.009	0.009	
707.50	23095	Mid	LTE Band 12	10	17.50	17.43	0.07	0	Antenna C	F9FYL00UMLWN	QPSK	1	49	0 mm	right	1:1	0.084	1.016	0.085	0.042	0.043	
707.50	23095	Mid	LTE Band 12	10	17.50	17.40	-0.03	0	Antenna C	F9FYL00UMLWN	QPSK	25	25	0 mm	right	1:1	0.078	1.023	0.080	0.038	0.039	
707.50	23095	Mid	LTE Band 12	10	17.50	17.43	-0.11	0	Antenna C	F9FYL00UMLWN	QPSK	1	49	0 mm	left	1:1	0.015	1.016	0.015	0.007	0.007	
707.50	23095	Mid	LTE Band 12	10	17.50	17.40	-0.02	0	Antenna C	F9FYL00UMLWN	QPSK	25	25	0 mm	left	1:1	0.015	1.023	0.015	0.008	0.008	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

Table 10-14
LTE Band 12 Body SAR – Antenna D

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)		Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Pilot #
MHz	Ch.															(W/kg)	(W/kg)		(W/kg)	(W/kg)		
707.50	23095	Mid	LTE Band 12	10	17.20	17.17	0.02	0	Antenna D	F9FYL00UMLWN	QPSK	1	49	0 mm	back	1:1	0.853	1.007	0.859	0.408	0.411	
707.50	23095	Mid	LTE Band 12	10	17.20	17.08	0.01	0	Antenna D	F9FYL00UMLWN	QPSK	25	25	0 mm	back	1:1	0.876	1.028	0.901	0.409	0.420	
707.50	23095	Mid	LTE Band 12	10	17.20	17.01	-0.01	0	Antenna D	F9FYL00UMLWN	QPSK	50	0	0 mm	back	1:1	0.839	1.045	0.877	0.405	0.423	
707.50	23095	Mid	LTE Band 12	10	17.20	17.17	0.02	0	Antenna D	F9FYL00UMLWN	QPSK	1	49	0 mm	top	1:1	0.454	1.007	0.457	0.250	0.252	
707.50	23095	Mid	LTE Band 12	10	17.20	17.08	0.09	0	Antenna D	F9FYL00UMLWN	QPSK	25	25	0 mm	top	1:1	0.461	1.028	0.474	0.252	0.259	
707.50	23095	Mid	LTE Band 12	10	17.20	17.17	-0.03	0	Antenna D	F9FYL00UMLWN	QPSK	1	49	0 mm	bottom	1:1	0.018	1.007	0.018	0.011	0.011	
707.50	23095	Mid	LTE Band 12	10	17.20	17.08	-0.04	0	Antenna D	F9FYL00UMLWN	QPSK	25	25	0 mm	bottom	1:1	0.019	1.028	0.020	0.011	0.011	
707.50	23095	Mid	LTE Band 12	10	17.20	17.17	0.05	0	Antenna D	F9FYL00UMLWN	QPSK	1	49	0 mm	right	1:1	0.020	1.007	0.020	0.010	0.010	
707.50	23095	Mid	LTE Band 12	10	17.20	17.08	0.20	0	Antenna D	F9FYL00UMLWN	QPSK	25	25	0 mm	right	1:1	0.017	1.028	0.017	0.008	0.008	
707.50	23095	Mid	LTE Band 12	10	17.20	17.17	-0.09	0	Antenna D	F9FYL00UMLWN	QPSK	1	49	0 mm	left	1:1	0.075	1.007	0.076	0.040	0.040	
707.50	23095	Mid	LTE Band 12	10	17.20	17.08	-0.05	0	Antenna D	F9FYL00UMLWN	QPSK	25	25	0 mm	left	1:1	0.071	1.028	0.073	0.038	0.039	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

Table 10-15
LTE Band 13 Body SAR – Antenna C

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)		Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Pilot #
MHz	Ch.															(W/kg)	(W/kg)		(W/kg)	(W/kg)		
782.00	23230	Mid	LTE Band 13	10	18.10	18.07	0.01	0	Antenna C	F9FYL00EMLWN	QPSK	1	0	0 mm	back	1:1	1.110	1.007	1.118	0.534	0.538	A8
782.00	23230	Mid	LTE Band 13	10	18.10	17.75	0.02	0	Antenna C	F9FYL00EMLWN	QPSK	25	25	0 mm	back	1:1	0.998	1.084	1.082	0.486	0.527	
782.00	23230	Mid	LTE Band 13	10	18.10	17.72	0.03	0	Antenna C	F9FYL00EMLWN	QPSK	50	0	0 mm	back	1:1	1.000	1.091	1.091	0.489	0.533	
782.00	23230	Mid	LTE Band 13	10	18.10	18.07	-0.03	0	Antenna C	F9FYL00EMLWN	QPSK	1	0	0 mm	top	1:1	0.675	1.007	0.680	0.357	0.359	
782.00	23230	Mid	LTE Band 13	10	18.10	17.75	-0.04	0	Antenna C	F9FYL00EMLWN	QPSK	25	25	0 mm	top	1:1	0.669	1.084	0.725	0.353	0.383	
782.00	23230	Mid	LTE Band 13	10	18.10	18.07	0.01	0	Antenna C	F9FYL00EMLWN	QPSK	1	0	0 mm	bottom	1:1	0.023	1.007	0.023	0.011	0.011	
782.00	23230	Mid	LTE Band 13	10	18.10	17.75	0.04	0	Antenna C	F9FYL00EMLWN	QPSK	25	25	0 mm	bottom	1:1	0.019	1.084	0.021	0.010	0.011	
782.00	23230	Mid	LTE Band 13	10	18.10	18.07	-0.01	0	Antenna C	F9FYL00EMLWN	QPSK	1	0	0 mm	right	1:1	0.113	1.007	0.114	0.055	0.055	
782.00	23230	Mid	LTE Band 13	10	18.10	17.75	0.02	0	Antenna C	F9FYL00EMLWN	QPSK	25	25	0 mm	right	1:1	0.091	1.084	0.099	0.045	0.049	
782.00	23230	Mid	LTE Band 13	10	18.10	18.07	0.11	0	Antenna C	F9FYL00EMLWN	QPSK	1	0	0 mm	left	1:1	0.021	1.007	0.021	0.009	0.009	
782.00	23230	Mid	LTE Band 13	10	18.10	17.75	-0.06	0	Antenna C	F9FYL00EMLWN	QPSK	25	25	0 mm	left	1:1	0.008	1.084	0.009	0.004	0.004	
782.00	23230	Mid	LTE Band 13	10	18.1	18.07	0.01	0	Antenna C	F9FYL00EMLWN	QPSK	1	0	0 mm	back	1:1	1.090	1.007	1.096	0.530	0.534	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

Note: Blue entry represents variability measurement.

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 91 of 116

Table 10-16
LTE Band 13 Body SAR – Antenna D

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
782.00	23230	Mid	LTE Band 13	10	18.30	17.89	0.01	0	Antenna D	F9FYL00EMLWN	QPSK	1	0	0 mm	back	1:1	0.914	1.099	1.004	0.488	0.536	
782.00	23230	Mid	LTE Band 13	10	18.30	17.67	0.00	0	Antenna D	F9FYL00EMLWN	QPSK	25	0	0 mm	back	1:1	0.821	1.156	0.949	0.439	0.507	
782.00	23230	Mid	LTE Band 13	10	18.30	17.62	0.01	0	Antenna D	F9FYL00EMLWN	QPSK	50	0	0 mm	back	1:1	0.818	1.169	0.956	0.432	0.505	
782.00	23230	Mid	LTE Band 13	10	18.30	17.89	-0.06	0	Antenna D	F9FYL00EMLWN	QPSK	1	0	0 mm	top	1:1	0.723	1.099	0.795	0.393	0.432	
782.00	23230	Mid	LTE Band 13	10	18.30	17.67	-0.07	0	Antenna D	F9FYL00EMLWN	QPSK	25	0	0 mm	top	1:1	0.689	1.156	0.796	0.373	0.431	
782.00	23230	Mid	LTE Band 13	10	18.30	17.89	-0.04	0	Antenna D	F9FYL00EMLWN	QPSK	1	0	0 mm	bottom	1:1	0.027	1.099	0.030	0.013	0.014	
782.00	23230	Mid	LTE Band 13	10	18.30	17.67	-0.02	0	Antenna D	F9FYL00EMLWN	QPSK	25	0	0 mm	bottom	1:1	0.030	1.156	0.035	0.015	0.017	
782.00	23230	Mid	LTE Band 13	10	18.30	17.89	-0.12	0	Antenna D	F9FYL00EMLWN	QPSK	1	0	0 mm	right	1:1	0.036	1.099	0.040	0.019	0.021	
782.00	23230	Mid	LTE Band 13	10	18.30	17.67	0.06	0	Antenna D	F9FYL00EMLWN	QPSK	25	0	0 mm	right	1:1	0.032	1.156	0.037	0.016	0.018	
782.00	23230	Mid	LTE Band 13	10	18.30	17.89	-0.09	0	Antenna D	F9FYL00EMLWN	QPSK	1	0	0 mm	left	1:1	0.167	1.099	0.184	0.080	0.088	
782.00	23230	Mid	LTE Band 13	10	18.30	17.67	-0.15	0	Antenna D	F9FYL00EMLWN	QPSK	25	0	0 mm	left	1:1	0.163	1.156	0.188	0.078	0.090	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

Table 10-17
LTE Band 14 Body SAR – Antenna C

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)	(W/kg)		
793.00	23330	Mid	LTE Band 14	10	18.10	18.04	0.13	0	Antenna C	F9FYL00UMLWN	QPSK	1	49	0 mm	back	1:1	0.883	1.014	0.895	0.426	0.432	A9
793.00	23330	Mid	LTE Band 14	10	18.10	17.97	0.04	0	Antenna C	F9FYL00UMLWN	QPSK	25	25	0 mm	back	1:1	0.877	1.030	0.903	0.424	0.437	
793.00	23330	Mid	LTE Band 14	10	18.10	17.83	0.02	0	Antenna C	F9FYL00UMLWN	QPSK	50	0	0 mm	back	1:1	0.877	1.064	0.933	0.424	0.451	
793.00	23330	Mid	LTE Band 14	10	18.10	18.04	-0.03	0	Antenna C	F9FYL00UMLWN	QPSK	1	49	0 mm	top	1:1	0.415	1.014	0.421	0.186	0.189	
793.00	23330	Mid	LTE Band 14	10	18.10	17.97	0.04	0	Antenna C	F9FYL00UMLWN	QPSK	25	25	0 mm	top	1:1	0.358	1.030	0.369	0.183	0.188	
793.00	23330	Mid	LTE Band 14	10	18.10	18.04	0.09	0	Antenna C	F9FYL00UMLWN	QPSK	1	49	0 mm	bottom	1:1	0.006	1.014	0.006	0.002	0.002	
793.00	23330	Mid	LTE Band 14	10	18.10	17.97	0.01	0	Antenna C	F9FYL00UMLWN	QPSK	25	25	0 mm	bottom	1:1	0.000	1.030	0.000	0.000	0.000	
793.00	23330	Mid	LTE Band 14	10	18.10	18.04	0.03	0	Antenna C	F9FYL00UMLWN	QPSK	1	49	0 mm	right	1:1	0.053	1.014	0.054	0.029	0.029	
793.00	23330	Mid	LTE Band 14	10	18.10	17.97	-0.02	0	Antenna C	F9FYL00UMLWN	QPSK	25	25	0 mm	right	1:1	0.069	1.030	0.071	0.029	0.030	
793.00	23330	Mid	LTE Band 14	10	18.10	18.04	0.05	0	Antenna C	F9FYL00UMLWN	QPSK	1	49	0 mm	left	1:1	0.108	1.014	0.110	0.041	0.042	
793.00	23330	Mid	LTE Band 14	10	18.10	17.97	-0.02	0	Antenna C	F9FYL00UMLWN	QPSK	25	25	0 mm	left	1:1	0.078	1.030	0.080	0.034	0.035	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

Table 10-18
LTE Band 14 Body SAR – Antenna D

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
793.00	23330	Mid	LTE Band 14	10	18.30	17.98	-0.01	0	Antenna D	F9FYL00EMLWN	QPSK	1	49	0 mm	back	1:1	0.873	1.076	0.939	0.412	0.443	
793.00	23330	Mid	LTE Band 14	10	18.30	17.94	-0.01	0	Antenna D	F9FYL00EMLWN	QPSK	25	0	0 mm	back	1:1	0.883	1.086	0.959	0.421	0.457	
793.00	23330	Mid	LTE Band 14	10	18.30	17.86	-0.02	0	Antenna D	F9FYL00EMLWN	QPSK	50	0	0 mm	back	1:1	0.753	1.107	0.834	0.401	0.444	
793.00	23330	Mid	LTE Band 14	10	18.30	17.98	-0.02	0	Antenna D	F9FYL00EMLWN	QPSK	1	49	0 mm	top	1:1	0.714	1.076	0.768	0.391	0.421	
793.00	23330	Mid	LTE Band 14	10	18.30	17.94	0.02	0	Antenna D	F9FYL00EMLWN	QPSK	25	0	0 mm	top	1:1	0.709	1.086	0.770	0.392	0.426	
793.00	23330	Mid	LTE Band 14	10	18.30	17.98	-0.02	0	Antenna D	F9FYL00EMLWN	QPSK	1	49	0 mm	bottom	1:1	0.023	1.076	0.025	0.013	0.014	
793.00	23330	Mid	LTE Band 14	10	18.30	17.94	-0.02	0	Antenna D	F9FYL00EMLWN	QPSK	25	0	0 mm	bottom	1:1	0.028	1.086	0.030	0.016	0.017	
793.00	23330	Mid	LTE Band 14	10	18.30	17.98	-0.17	0	Antenna D	F9FYL00EMLWN	QPSK	1	49	0 mm	right	1:1	0.043	1.076	0.046	0.023	0.025	
793.00	23330	Mid	LTE Band 14	10	18.30	17.94	0.01	0	Antenna D	F9FYL00EMLWN	QPSK	25	0	0 mm	right	1:1	0.038	1.086	0.041	0.020	0.022	
793.00	23330	Mid	LTE Band 14	10	18.30	17.98	-0.05	0	Antenna D	F9FYL00EMLWN	QPSK	1	49	0 mm	left	1:1	0.148	1.076	0.159	0.081	0.087	
793.00	23330	Mid	LTE Band 14	10	18.30	17.94	-0.11	0	Antenna D	F9FYL00EMLWN	QPSK	25	0	0 mm	left	1:1	0.151	1.086	0.164	0.083	0.090	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 92 of 116

Table 10-19
LTE Band 26 (Cell) Body SAR- Antenna C

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
819.00	26740	Low	LTE Band 26 (Cell)	10	19.00	18.93	0.01	0	Antenna C	F9FYL00UMLWN	QPSK	1	0	0 mm	back	1:1	1.160	1.016	1.179	0.609	0.619	A10
831.50	26865	Mid	LTE Band 26 (Cell)	10	19.00	18.99	0.02	0	Antenna C	F9FYL00UMLWN	QPSK	1	25	0 mm	back	1:1	1.060	1.002	1.062	0.555		
844.00	26990	High	LTE Band 26 (Cell)	10	19.00	18.75	-0.01	0	Antenna C	F9FYL00UMLWN	QPSK	1	49	0 mm	back	1:1	0.993	1.059	1.052	0.520	0.556	
819.00	26740	Low	LTE Band 26 (Cell)	10	19.00	18.86	-0.01	0	Antenna C	F9FYL00UMLWN	QPSK	25	0	0 mm	back	1:1	1.110	1.033	1.147	0.576	0.595	
831.50	26865	Mid	LTE Band 26 (Cell)	10	19.00	18.92	0.01	0	Antenna C	F9FYL00UMLWN	QPSK	25	12	0 mm	back	1:1	1.070	1.019	1.090	0.553	0.564	
844.00	26990	High	LTE Band 26 (Cell)	10	19.00	18.78	0.01	0	Antenna C	F9FYL00UMLWN	QPSK	25	25	0 mm	back	1:1	1.020	1.052	1.073	0.531	0.559	
831.50	26865	Mid	LTE Band 26 (Cell)	10	19.00	18.91	-0.01	0	Antenna C	F9FYL00UMLWN	QPSK	50	0	0 mm	back	1:1	1.070	1.021	1.092	0.552	0.564	
819.00	26740	Low	LTE Band 26 (Cell)	10	19.00	18.93	-0.09	0	Antenna C	F9FYL00UMLWN	QPSK	1	0	0 mm	top	1:1	0.878	1.016	0.892	0.498	0.506	
831.50	26865	Mid	LTE Band 26 (Cell)	10	19.00	18.99	0.06	0	Antenna C	F9FYL00UMLWN	QPSK	1	25	0 mm	top	1:1	0.885	1.002	0.887	0.506	0.507	
844.00	26990	High	LTE Band 26 (Cell)	10	19.00	18.75	-0.03	0	Antenna C	F9FYL00UMLWN	QPSK	1	49	0 mm	top	1:1	0.889	1.059	0.941	0.507	0.537	
819.00	26740	Low	LTE Band 26 (Cell)	10	19.00	18.86	0.05	0	Antenna C	F9FYL00UMLWN	QPSK	25	0	0 mm	top	1:1	0.831	1.033	0.858	0.472	0.488	
831.50	26865	Mid	LTE Band 26 (Cell)	10	19.00	18.92	-0.01	0	Antenna C	F9FYL00UMLWN	QPSK	25	12	0 mm	top	1:1	0.904	1.019	0.921	0.512	0.522	
844.00	26990	High	LTE Band 26 (Cell)	10	19.00	18.78	-0.07	0	Antenna C	F9FYL00UMLWN	QPSK	25	25	0 mm	top	1:1	0.852	1.052	0.896	0.482	0.507	
831.50	26865	Mid	LTE Band 26 (Cell)	10	19.00	18.91	-0.02	0	Antenna C	F9FYL00UMLWN	QPSK	50	0	0 mm	top	1:1	0.817	1.021	0.834	0.462	0.472	
831.50	26865	Mid	LTE Band 26 (Cell)	10	19.00	18.99	-0.04	0	Antenna C	F9FYL00UMLWN	QPSK	1	25	0 mm	bottom	1:1	0.020	1.002	0.020	0.012	0.012	
831.50	26865	Mid	LTE Band 26 (Cell)	10	19.00	18.92	0.08	0	Antenna C	F9FYL00UMLWN	QPSK	25	12	0 mm	bottom	1:1	0.022	1.019	0.022	0.012	0.012	
831.50	26865	Mid	LTE Band 26 (Cell)	10	19.00	18.99	-0.03	0	Antenna C	F9FYL00UMLWN	QPSK	1	25	0 mm	right	1:1	0.129	1.002	0.129	0.070	0.070	
831.50	26865	Mid	LTE Band 26 (Cell)	10	19.00	18.92	-0.02	0	Antenna C	F9FYL00UMLWN	QPSK	25	12	0 mm	right	1:1	0.127	1.019	0.129	0.069	0.070	
831.50	26865	Mid	LTE Band 26 (Cell)	10	19.00	18.99	0.02	0	Antenna C	F9FYL00UMLWN	QPSK	1	25	0 mm	left	1:1	0.020	1.002	0.020	0.010	0.010	
831.50	26865	Mid	LTE Band 26 (Cell)	10	19.00	18.92	0.04	0	Antenna C	F9FYL00UMLWN	QPSK	25	12	0 mm	left	1:1	0.020	1.019	0.020	0.011	0.011	
819.00	26740	Low	LTE Band 26 (Cell)	10	19.00	18.93	0.02	0	Antenna C	F9FYL00UMLWN	QPSK	1	0	0 mm	back	1:1	1.110	1.016	1.128	0.561	0.570	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

Note: Blue entry represents variability measurement.

Table 10-20
LTE Band 26 (Cell) Body SAR- Antenna D

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	18.14	-0.02	0	Antenna D	F9FYL00EMLWN	QPSK	1	0	0 mm	back	1:1	0.917	1.014	0.930	0.469	0.476	
831.50	26865	Mid	LTE Band 26 (Cell)	10	18.20	18.00	-0.02	0	Antenna D	F9FYL00EMLWN	QPSK	1	49	0 mm	back	1:1	0.789	1.047	0.826	0.405	0.424	
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	18.10	-0.01	0	Antenna D	F9FYL00EMLWN	QPSK	1	49	0 mm	back	1:1	0.736	1.023	0.753	0.378	0.387	
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	18.01	0.10	0	Antenna D	F9FYL00EMLWN	QPSK	25	0	0 mm	back	1:1	0.736	1.045	0.769	0.377	0.394	
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	17.98	-0.01	0	Antenna D	F9FYL00EMLWN	QPSK	50	0	0 mm	back	1:1	0.823	1.052	0.866	0.420	0.442	
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	18.14	-0.11	0	Antenna D	F9FYL00EMLWN	QPSK	1	0	0 mm	top	1:1	0.806	1.014	0.817	0.432	0.438	
831.50	26865	Mid	LTE Band 26 (Cell)	10	18.20	18.00	0.04	0	Antenna D	F9FYL00EMLWN	QPSK	1	49	0 mm	top	1:1	0.742	1.047	0.777	0.399	0.418	
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	18.10	0.01	0	Antenna D	F9FYL00EMLWN	QPSK	1	49	0 mm	top	1:1	0.672	1.023	0.687	0.364	0.372	
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	18.01	-0.07	0	Antenna D	F9FYL00EMLWN	QPSK	25	0	0 mm	top	1:1	0.706	1.045	0.738	0.378	0.395	
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	17.98	-0.07	0	Antenna D	F9FYL00EMLWN	QPSK	50	0	0 mm	top	1:1	0.690	1.052	0.726	0.372	0.391	
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	18.14	0.03	0	Antenna D	F9FYL00EMLWN	QPSK	1	0	0 mm	bottom	1:1	0.023	1.014	0.023	0.011	0.011	
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	18.01	-0.11	0	Antenna D	F9FYL00EMLWN	QPSK	25	0	0 mm	bottom	1:1	0.022	1.045	0.023	0.012	0.013	
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	18.14	0.06	0	Antenna D	F9FYL00EMLWN	QPSK	1	0	0 mm	right	1:1	0.017	1.014	0.017	0.008	0.008	
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	18.01	0.03	0	Antenna D	F9FYL00EMLWN	QPSK	25	0	0 mm	right	1:1	0.010	1.045	0.010	0.004	0.004	
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	18.14	-0.03	0	Antenna D	F9FYL00EMLWN	QPSK	1	0	0 mm	left	1:1	0.133	1.014	0.135	0.057	0.020	
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	18.01	-0.01	0	Antenna D	F9FYL00EMLWN	QPSK	25	0	0 mm	left	1:1	0.186	1.045	0.194	0.091	0.095	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 93 of 116

Table 10-21
LTE Band 5 (Cell) Body SAR- Antenna C

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.67	-0.05	0	Antenna C	F9FY00UMLWN	QPSK	1	0	0 mm	back	1:1	1.020	1.007	1.027	0.507	0.511	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.60	-0.03	0	Antenna C	F9FY00UMLWN	QPSK	25	0	0 mm	back	1:1	0.988	1.023	1.011	0.487	0.498	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.50	-0.03	0	Antenna C	F9FY00UMLWN	QPSK	50	0	0 mm	back	1:1	0.966	1.047	1.011	0.479	0.502	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.67	-0.14	0	Antenna C	F9FY00UMLWN	QPSK	1	0	0 mm	top	1:1	0.666	1.007	0.671	0.383	0.386	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.60	-0.14	0	Antenna C	F9FY00UMLWN	QPSK	25	0	0 mm	top	1:1	0.656	1.023	0.671	0.377	0.386	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.67	-0.10	0	Antenna C	F9FY00UMLWN	QPSK	1	0	0 mm	bottom	1:1	0.017	1.007	0.017	0.009	0.009	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.60	-0.01	0	Antenna C	F9FY00UMLWN	QPSK	25	0	0 mm	bottom	1:1	0.018	1.023	0.018	0.010	0.010	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.67	0.02	0	Antenna C	F9FY00UMLWN	QPSK	1	0	0 mm	right	1:1	0.085	1.007	0.086	0.042	0.042	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.60	-0.01	0	Antenna C	F9FY00UMLWN	QPSK	25	0	0 mm	right	1:1	0.089	1.023	0.091	0.045	0.046	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.67	0.13	0	Antenna C	F9FY00UMLWN	QPSK	1	0	0 mm	left	1:1	0.008	1.007	0.008	0.003	0.003	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.60	-0.02	0	Antenna C	F9FY00UMLWN	QPSK	25	0	0 mm	left	1:1	0.010	1.023	0.010	0.005	0.005	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak									Body 1.6 W/kg (mW/g) averaged over 1 gram													
Uncontrolled Exposure/General Population																						

Table 10-22
LTE Band 5 (Cell) Body SAR- Antenna D

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.14	-0.03	0	Antenna D	F9FY01XMLWN	QPSK	1	0	0 mm	back	1:1	1.100	1.014	1.115	0.543	0.551	A11
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.03	0.01	0	Antenna D	F9FY01XMLWN	QPSK	25	0	0 mm	back	1:1	1.100	1.040	1.144	0.540	0.562	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.00	-0.06	0	Antenna D	F9FY01XMLWN	QPSK	50	0	0 mm	back	1:1	1.090	1.047	1.141	0.538	0.563	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.14	0.05	0	Antenna D	F9FY01XMLWN	QPSK	1	0	0 mm	top	1:1	0.741	1.014	0.751	0.406	0.412	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.03	-0.04	0	Antenna D	F9FY01XMLWN	QPSK	25	0	0 mm	top	1:1	0.718	1.040	0.747	0.393	0.409	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.14	0.18	0	Antenna D	F9FY01XMLWN	QPSK	1	0	0 mm	bottom	1:1	0.024	1.014	0.024	0.012	0.012	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.03	0.03	0	Antenna D	F9FY01XMLWN	QPSK	25	0	0 mm	bottom	1:1	0.023	1.040	0.024	0.011	0.011	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.14	0.03	0	Antenna D	F9FY01XMLWN	QPSK	1	0	0 mm	right	1:1	0.017	1.014	0.017	0.009	0.009	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.03	-0.12	0	Antenna D	F9FY01XMLWN	QPSK	25	0	0 mm	right	1:1	0.015	1.040	0.016	0.008	0.008	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.14	-0.10	0	Antenna D	F9FY01XMLWN	QPSK	1	0	0 mm	left	1:1	0.158	1.014	0.160	0.080	0.081	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.03	-0.17	0	Antenna D	F9FY01XMLWN	QPSK	25	0	0 mm	left	1:1	0.152	1.040	0.158	0.078	0.081	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak									Body 1.6 W/kg (mW/g)													
Uncontrolled Exposure/General Population									averaged over 1 gram													

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 94 of 116

Table 10-23
LTE Band 66 (AWS) Body SAR- Antenna C

MEASUREMENT RESULTS																						
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Pilot #
MHz	Ch.	Low															(W/kg)		(W/kg)	(W/kg)		
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.30	-0.05	0	Antenna C	F9FYL00EMLWN	QPSK	1	50	0 mm	back	1:1	0.849	1.000	0.849	0.400	0.400	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	13.30	13.06	-0.01	0	Antenna C	F9FYL00EMLWN	QPSK	1	0	0 mm	back	1:1	0.923	1.057	0.976	0.437	0.462	
1770.00	132572	High	LTE Band 66 (AWS)	20	13.30	13.06	0.07	0	Antenna C	F9FYL00EMLWN	QPSK	1	99	0 mm	back	1:1	0.870	1.057	0.920	0.411	0.434	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.22	0.03	0	Antenna C	F9FYL00EMLWN	QPSK	50	0	0 mm	back	1:1	0.860	1.019	0.876	0.401	0.409	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	13.30	12.95	0.04	0	Antenna C	F9FYL00EMLWN	QPSK	50	0	0 mm	back	1:1	0.859	1.084	0.931	0.404	0.438	
1770.00	132572	High	LTE Band 66 (AWS)	20	13.30	12.90	0.05	0	Antenna C	F9FYL00EMLWN	QPSK	50	0	0 mm	back	1:1	0.859	1.096	0.941	0.403	0.442	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.21	0.01	0	Antenna C	F9FYL00EMLWN	QPSK	100	0	0 mm	back	1:1	0.885	1.021	0.904	0.412	0.421	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.30	-0.02	0	Antenna C	F9FYL00EMLWN	QPSK	1	50	0 mm	top	1:1	0.454	1.000	0.454	0.223	0.223	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.22	-0.01	0	Antenna C	F9FYL00EMLWN	QPSK	50	0	0 mm	top	1:1	0.449	1.019	0.458	0.218	0.222	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.30	0.01	0	Antenna C	F9FYL00EMLWN	QPSK	1	50	0 mm	bottom	1:1	0.001	1.000	0.001	0.000	0.000	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.22	0.01	0	Antenna C	F9FYL00EMLWN	QPSK	50	0	0 mm	bottom	1:1	0.000	1.019	0.000	0.000	0.000	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.30	0.06	0	Antenna C	F9FYL00EMLWN	QPSK	1	50	0 mm	right	1:1	0.056	1.000	0.056	0.026	0.026	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.22	-0.11	0	Antenna C	F9FYL00EMLWN	QPSK	50	0	0 mm	right	1:1	0.053	1.019	0.054	0.025	0.025	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.30	0.15	0	Antenna C	F9FYL00EMLWN	QPSK	1	50	0 mm	left	1:1	0.018	1.000	0.018	0.009	0.009	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.22	0.08	0	Antenna C	F9FYL00EMLWN	QPSK	50	0	0 mm	left	1:1	0.018	1.019	0.018	0.009	0.009	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

Table 10-24
LTE Band 66 (AWS) Body SAR- Antenna D

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Pilot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.14	0.06	0	Antenna D	F9FYLO1XMLWN	QPSK	1	0	0 mm	back	1:1	0.947	1.014	0.960	0.411	0.417	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	13.20	13.07	-0.01	0	Antenna D	F9FYLO1XMLWN	QPSK	1	0	0 mm	back	1:1	1.010	1.030	1.040	0.439	0.452	
1770.00	132572	High	LTE Band 66 (AWS)	20	13.20	13.12	0.01	0	Antenna D	F9FYLO1XMLWN	QPSK	1	0	0 mm	back	1:1	1.090	1.019	1.111	0.467	0.476	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.05	-0.01	0	Antenna D	F9FYLO1XMLWN	QPSK	50	0	0 mm	back	1:1	0.945	1.035	0.978	0.408	0.422	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	13.20	12.93	0.02	0	Antenna D	F9FYLO1XMLWN	QPSK	50	50	0 mm	back	1:1	1.020	1.064	1.085	0.436	0.464	
1770.00	132572	High	LTE Band 66 (AWS)	20	13.20	12.98	-0.02	0	Antenna D	F9FYLO1XMLWN	QPSK	50	0	0 mm	back	1:1	1.090	1.052	1.147	0.465	0.489	A12
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.04	0.01	0	Antenna D	F9FYLO1XMLWN	QPSK	100	0	0 mm	back	1:1	0.976	1.038	1.013	0.422	0.438	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.14	-0.01	0	Antenna D	F9FYLO1XMLWN	QPSK	1	0	0 mm	top	1:1	0.590	1.014	0.598	0.277	0.281	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.05	0.01	0	Antenna D	F9FYLO1XMLWN	QPSK	50	0	0 mm	top	1:1	0.582	1.035	0.602	0.271	0.280	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.14	0.04	0	Antenna D	F9FYLO1XMLWN	QPSK	1	0	0 mm	bottom	1:1	0.002	1.014	0.002	0.001	0.001	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.05	0.15	0	Antenna D	F9FYLO1XMLWN	QPSK	50	0	0 mm	bottom	1:1	0.003	1.035	0.003	0.001	0.001	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.14	0.06	0	Antenna D	F9FYLO1XMLWN	QPSK	1	0	0 mm	right	1:1	0.008	1.014	0.008	0.004	0.004	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.05	0.13	0	Antenna D	F9FYLO1XMLWN	QPSK	50	0	0 mm	right	1:1	0.009	1.035	0.009	0.004	0.004	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.14	0.12	0	Antenna D	F9FYLO1XMLWN	QPSK	1	0	0 mm	left	1:1	0.074	1.014	0.075	0.035	0.035	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.05	-0.03	0	Antenna D	F9FYLO1XMLWN	QPSK	50	0	0 mm	left	1:1	0.071	1.035	0.073	0.033	0.034	
1770.00	132572	High	LTE Band 66 (AWS)	20	13.20	12.98	-0.01	0	Antenna D	F9FYLO1XMLWN	QPSK	50	0	0 mm	back	1:1	1.080	1.052	1.136	0.471	0.495	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

Note: Blue entry represents variability measurement.

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 95 of 116

Table 10-25
LTE Band 25 (PCS) Body SAR – Antenna C

MEASUREMENT RESULTS																						
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.	(W/kg)															(W/kg)		(W/kg)			
1860.00	26140	Low	LTE Band 25 (PCS)	20	13.10	13.08	0.02	0	Antenna C	F9FYL01XMLWN	QPSK	1	0	0 mm	back	1:1	0.976	1.005	0.981	0.450	0.452	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	13.10	13.04	0.01	0	Antenna C	F9FYL01XMLWN	QPSK	1	99	0 mm	back	1:1	0.981	1.014	0.995	0.452	0.458	
1905.00	26590	High	LTE Band 25 (PCS)	20	13.10	12.98	0.01	0	Antenna C	F9FYL01XMLWN	QPSK	1	0	0 mm	back	1:1	0.986	1.028	1.014	0.456	0.469	
1860.00	26140	Low	LTE Band 25 (PCS)	20	13.10	12.89	0.01	0	Antenna C	F9FYL01XMLWN	QPSK	50	0	0 mm	back	1:1	0.960	1.050	1.008	0.440	0.462	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	13.10	12.92	0.01	0	Antenna C	F9FYL01XMLWN	QPSK	50	50	0 mm	back	1:1	0.951	1.042	0.991	0.438	0.456	
1905.00	26590	High	LTE Band 25 (PCS)	20	13.10	13.03	0.01	0	Antenna C	F9FYL01XMLWN	QPSK	50	0	0 mm	back	1:1	0.960	1.016	0.975	0.441	0.448	
1905.00	26590	High	LTE Band 25 (PCS)	20	13.10	13.02	0.01	0	Antenna C	F9FYL01XMLWN	QPSK	100	0	0 mm	back	1:1	0.970	1.019	0.988	0.446	0.454	
1860.00	26140	Low	LTE Band 25 (PCS)	20	13.10	13.08	0.06	0	Antenna C	F9FYL01XMLWN	QPSK	1	0	0 mm	top	1:1	0.671	1.005	0.674	0.316	0.318	
1905.00	26590	High	LTE Band 25 (PCS)	20	13.10	13.03	-0.04	0	Antenna C	F9FYL01XMLWN	QPSK	50	0	0 mm	top	1:1	0.692	1.016	0.703	0.322	0.327	
1860.00	26140	Low	LTE Band 25 (PCS)	20	13.10	13.08	0.00	0	Antenna C	F9FYL01XMLWN	QPSK	1	0	0 mm	bottom	1:1	0.000	1.005	0.000	0.000	0.000	
1905.00	26590	High	LTE Band 25 (PCS)	20	13.10	13.03	0.00	0	Antenna C	F9FYL01XMLWN	QPSK	50	0	0 mm	bottom	1:1	0.000	1.016	0.000	0.000	0.000	
1860.00	26140	Low	LTE Band 25 (PCS)	20	13.10	13.08	0.01	0	Antenna C	F9FYL01XMLWN	QPSK	1	0	0 mm	right	1:1	0.089	1.005	0.089	0.041	0.041	
1905.00	26590	High	LTE Band 25 (PCS)	20	13.10	13.03	0.06	0	Antenna C	F9FYL01XMLWN	QPSK	50	0	0 mm	right	1:1	0.084	1.016	0.085	0.038	0.039	
1860.00	26140	Low	LTE Band 25 (PCS)	20	13.10	13.08	0.14	0	Antenna C	F9FYL01XMLWN	QPSK	1	0	0 mm	left	1:1	0.029	1.005	0.029	0.014	0.014	
1905.00	26590	High	LTE Band 25 (PCS)	20	13.10	13.03	0.00	0	Antenna C	F9FYL01XMLWN	QPSK	50	0	0 mm	left	1:1	0.023	1.016	0.023	0.011	0.011	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

Table 10-26
LTE Band 25 (PCS) Body SAR – Antenna D

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
1860.00	26140	Low	LTE Band 25 (PCS)	20	12.00	11.88	0.01	0	Antenna D	F9FYL01XMLWN	QPSK	1	0	0 mm	back	1:1	1.000	1.028	1.028	0.438	0.450	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	12.00	11.92	0.00	0	Antenna D	F9FYL01XMLWN	QPSK	1	0	0 mm	back	1:1	1.010	1.019	1.029	0.439	0.447	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.97	-0.01	0	Antenna D	F9FYL01XMLWN	QPSK	1	0	0 mm	back	1:1	1.050	1.007	1.057	0.458	0.461	A13
1860.00	26140	Low	LTE Band 25 (PCS)	20	12.00	11.93	-0.01	0	Antenna D	F9FYL01XMLWN	QPSK	50	50	0 mm	back	1:1	0.966	1.016	0.981	0.421	0.428	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	12.00	11.91	-0.02	0	Antenna D	F9FYL01XMLWN	QPSK	50	50	0 mm	back	1:1	0.979	1.021	1.000	0.426	0.435	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.95	-0.05	0	Antenna D	F9FYL01XMLWN	QPSK	50	25	0 mm	back	1:1	1.010	1.012	1.022	0.441	0.446	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.94	-0.03	0	Antenna D	F9FYL01XMLWN	QPSK	100	0	0 mm	back	1:1	1.030	1.014	1.044	0.447	0.453	
1860.00	26140	Low	LTE Band 25 (PCS)	20	12.00	11.88	-0.02	0	Antenna D	F9FYL01XMLWN	QPSK	1	0	0 mm	top	1:1	0.716	1.028	0.736	0.326	0.335	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	12.00	11.92	0.03	0	Antenna D	F9FYL01XMLWN	QPSK	1	0	0 mm	top	1:1	0.752	1.019	0.766	0.343	0.350	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.97	-0.01	0	Antenna D	F9FYL01XMLWN	QPSK	1	0	0 mm	top	1:1	0.877	1.007	0.883	0.401	0.404	
1860.00	26140	Low	LTE Band 25 (PCS)	20	12.00	11.93	-0.05	0	Antenna D	F9FYL01XMLWN	QPSK	50	50	0 mm	top	1:1	0.700	1.016	0.711	0.318	0.323	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	12.00	11.91	0.02	0	Antenna D	F9FYL01XMLWN	QPSK	50	50	0 mm	top	1:1	0.735	1.021	0.750	0.333	0.340	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.95	-0.01	0	Antenna D	F9FYL01XMLWN	QPSK	50	25	0 mm	top	1:1	0.844	1.012	0.854	0.384	0.389	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.94	-0.02	0	Antenna D	F9FYL01XMLWN	QPSK	100	0	0 mm	top	1:1	0.860	1.014	0.872	0.392	0.397	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.97	0.00	0	Antenna D	F9FYL01XMLWN	QPSK	1	0	0 mm	bottom	1:1	0.000	1.007	0.000	0.000	0.000	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.95	0.00	0	Antenna D	F9FYL01XMLWN	QPSK	50	25	0 mm	bottom	1:1	0.000	1.012	0.000	0.000	0.000	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.97	0.06	0	Antenna D	F9FYL01XMLWN	QPSK	1	0	0 mm	right	1:1	0.013	1.007	0.013	0.006	0.006	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.95	0.04	0	Antenna D	F9FYL01XMLWN	QPSK	50	25	0 mm	right	1:1	0.014	1.012	0.014	0.006	0.006	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.97	0.05	0	Antenna D	F9FYL01XMLWN	QPSK	1	0	0 mm	left	1:1	0.067	1.007	0.067	0.030	0.030	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.95	0.01	0	Antenna D	F9FYL01XMLWN	QPSK	50	25	0 mm	left	1:1	0.061	1.012	0.062	0.027	0.027	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 96 of 116

Table 10-27
LTE Band 30 Body SAR – Antenna C

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
2310.00	27710	Mid	LTE Band 30	10	13.20	13.18	0.04	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	back	1:1	0.901	1.005	0.906	0.385	0.387	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.17	0.04	0	Antenna C	F9FYLO0UMLWN	QPSK	25	0	0 mm	back	1:1	0.911	1.007	0.917	0.389	0.392	
2310.00	27710	Mid	LTE Band 30	10	13.2	13.02	0.03	0	Antenna C	F9FYLO0UMLWN	QPSK	50	0	0 mm	back	1:1	0.928	1.042	0.967	0.396	0.413	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.18	0.00	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	top	1:1	1.000	1.005	1.005	0.452	0.454	A14
2310.00	27710	Mid	LTE Band 30	10	13.20	13.17	-0.03	0	Antenna C	F9FYLO0UMLWN	QPSK	25	0	0 mm	top	1:1	0.967	1.007	0.974	0.436	0.439	
2310.00	27710	Mid	LTE Band 30	10	13.2	13.02	-0.06	0	Antenna C	F9FYLO0UMLWN	QPSK	50	0	0 mm	top	1:1	0.963	1.042	1.003	0.434	0.452	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.18	0.00	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	bottom	1:1	0.000	1.005	0.000	0.000	0.000	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.17	0.00	0	Antenna C	F9FYLO0UMLWN	QPSK	25	0	0 mm	bottom	1:1	0.000	1.007	0.000	0.000	0.000	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.18	0.05	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	right	1:1	0.128	1.005	0.129	0.055	0.055	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.17	0.03	0	Antenna C	F9FYLO0UMLWN	QPSK	25	0	0 mm	right	1:1	0.130	1.007	0.131	0.055	0.055	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.18	-0.01	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	left	1:1	0.022	1.005	0.022	0.010	0.010	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.17	0.02	0	Antenna C	F9FYLO0UMLWN	QPSK	25	0	0 mm	left	1:1	0.025	1.007	0.025	0.011	0.011	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.18	0.00	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	top	1:1	0.984	1.005	0.989	0.445	0.447	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak								Body 1.6 W/kg (mW/g) averaged over 1 gram														
Uncontrolled Exposure/General Population																						

Note: Blue entry represents variability measurement.

Table 10-28
LTE Band 30 Body SAR – Antenna D

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
2310.00	27710	Mid	LTE Band 30	10	12.80	12.59	0.06	0	Antenna D	F9FYL002MLX9	QPSK	1	0	0 mm	back	1:1	0.916	1.050	0.962	0.419	0.440	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.45	0.03	0	Antenna D	F9FYL002MLX9	QPSK	25	0	0 mm	back	1:1	0.920	1.084	0.997	0.420	0.455	
2310.00	27710	Mid	LTE Band 30	10	12.8	12.44	0.01	0	Antenna D	F9FYL002MLX9	QPSK	50	0	0 mm	back	1:1	0.943	1.086	1.024	0.431	0.468	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.59	-0.03	0	Antenna D	F9FYL002MLX9	QPSK	1	0	0 mm	top	1:1	0.689	1.050	0.723	0.310	0.326	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.45	0.04	0	Antenna D	F9FYL002MLX9	QPSK	25	0	0 mm	top	1:1	0.692	1.084	0.750	0.311	0.337	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.59	0.00	0	Antenna D	F9FYL002MLX9	QPSK	1	0	0 mm	bottom	1:1	0.000	1.050	0.000	0.000	0.000	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.45	0.00	0	Antenna D	F9FYL002MLX9	QPSK	25	0	0 mm	bottom	1:1	0.000	1.084	0.000	0.000	0.000	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.59	0.19	0	Antenna D	F9FYL002MLX9	QPSK	1	0	0 mm	right	1:1	0.039	1.050	0.041	0.017	0.018	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.45	0.03	0	Antenna D	F9FYL002MLX9	QPSK	25	0	0 mm	right	1:1	0.037	1.084	0.040	0.017	0.018	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.59	-0.03	0	Antenna D	F9FYL002MLX9	QPSK	1	0	0 mm	left	1:1	0.124	1.050	0.130	0.054	0.057	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.45	0.03	0	Antenna D	F9FYL002MLX9	QPSK	25	0	0 mm	left	1:1	0.121	1.084	0.131	0.052	0.056	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak								Body 1.6 W/kg (mW/g) averaged over 1 gram														
Uncontrolled Exposure/General Population																						

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 97 of 116

Table 10-29
LTE Band 7 Body SAR – Antenna C

MEASUREMENT RESULTS																								
1 CC Uplink	Component Carrier	FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	SAR (10g) (W/kg)	Reported SAR (10g) (W/kg)	Plot #	
		MHz	Ch.																					
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.4	12.40	-0.12	0	Antenna C	F9FYLD00UMLWN	QPSK	1	99	0 mm	back	1:1	1.020	1.000	1.020	0.432	0.432	
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.4	12.09	-0.12	0	Antenna C	F9FYLD00UMLWN	QPSK	1	99	0 mm	back	1:1	0.964	1.074	1.035	0.409	0.439	
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.4	12.37	-0.04	0	Antenna C	F9FYLD00UMLWN	QPSK	1	99	0 mm	back	1:1	0.924	1.007	0.930	0.392	0.395	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.4	12.32	-0.14	0	Antenna C	F9FYLD00UMLWN	QPSK	50	50	0 mm	back	1:1	1.000	1.019	1.019	0.425	0.433	
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.4	12.18	-0.11	0	Antenna C	F9FYLD00UMLWN	QPSK	50	0	0 mm	back	1:1	0.978	1.052	1.029	0.419	0.441	
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.4	12.29	-0.05	0	Antenna C	F9FYLD00UMLWN	QPSK	50	25	0 mm	back	1:1	0.955	1.026	0.980	0.406	0.417	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.4	12.31	-0.06	0	Antenna C	F9FYLD00UMLWN	QPSK	100	0	0 mm	back	1:1	1.000	1.021	1.021	0.429	0.438	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.4	12.40	-0.07	0	Antenna C	F9FYLD00UMLWN	QPSK	1	99	0 mm	top	1:1	1.140	1.000	1.140	0.482	0.482	
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.4	12.09	-0.10	0	Antenna C	F9FYLD00UMLWN	QPSK	1	99	0 mm	top	1:1	1.100	1.074	1.181	0.467	0.502	
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.4	12.37	-0.14	0	Antenna C	F9FYLD00UMLWN	QPSK	1	99	0 mm	top	1:1	1.170	1.007	1.178	0.487	0.490	A15
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.4	12.32	-0.10	0	Antenna C	F9FYLD00UMLWN	QPSK	50	50	0 mm	top	1:1	1.090	1.019	1.111	0.462	0.471	
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	12.18	-0.11	0	Antenna C	F9FYLD00UMLWN	QPSK	50	0	0 mm	top	1:1	1.120	1.052	1.178	0.470	0.494	
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.4	12.29	-0.13	0	Antenna C	F9FYLD00UMLWN	QPSK	50	25	0 mm	top	1:1	1.140	1.026	1.170	0.478	0.490	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.31	-0.02	0	Antenna C	F9FYLD00UMLWN	QPSK	100	0	0 mm	top	1:1	1.090	1.021	1.113	0.462	0.472	
2 CC Uplink	PCC	2535.00	21100	Mid	LTE Band 7	20	12.4	12.10	-0.03	0	Antenna C	F9FYLD00UMLWN	QPSK	1	99	0 mm	top	1:1	1.100	1.072	1.179	0.451	0.483	
2 CC Uplink	SCC	2554.80	21298	Mid	LTE Band 7	20							1	0										
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.4	12.40	0.00	0	Antenna C	F9FYLD00UMLWN	QPSK	1	99	0 mm	bottom	1:1	0.000	1.000	0.000	0.000	0.000	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.4	12.32	0.00	0	Antenna C	F9FYLD00UMLWN	QPSK	50	50	0 mm	bottom	1:1	0.000	1.019	0.000	0.000	0.000	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.4	12.40	0.04	0	Antenna C	F9FYLD00UMLWN	QPSK	1	99	0 mm	right	1:1	0.141	1.000	0.141	0.062	0.062	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.4	12.32	0.04	0	Antenna C	F9FYLD00UMLWN	QPSK	50	50	0 mm	right	1:1	0.136	1.019	0.139	0.061	0.062	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.4	12.40	-0.02	0	Antenna C	F9FYLD00UMLWN	QPSK	1	99	0 mm	left	1:1	0.023	1.000	0.023	0.009	0.009	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.4	12.32	-0.02	0	Antenna C	F9FYLD00UMLWN	QPSK	50	50	0 mm	left	1:1	0.022	1.019	0.022	0.009	0.009	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.4	12.40	-0.07	0	Antenna C	F9FYLD00UMLWN	QPSK	1	99	0 mm	top	1:1	1.120	1.000	1.120	0.478	0.478	
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.4	12.37	-0.14	0	Antenna C	F9FYLD00UMLWN	QPSK	1	99	0 mm	top	1:1	1.150	1.007	1.158	0.478	0.481	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Body														
Spatial Peak										1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population										averaged over 1 gram														

Note: Blue entry represents variability measurement.

Table 10-30
LTE Band 7 Body SAR – Antenna D

MEASUREMENT RESULTS																								
1 CC Uplink	Component Carrier	FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	SAR (10g) (W/kg)	Reported SAR (10g) (W/kg)	Plot #	
		MHz	Ch.																					
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.01	-0.12	0	Antenna D	F9FYLD00UMLWN	QPSK	1	50	0 mm	back	1:1	0.814	1.094	0.891	0.365	0.399	
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	12.14	0.02	0	Antenna D	F9FYLD00UMLWN	QPSK	1	0	0 mm	back	1:1	0.853	1.062	0.906	0.377	0.400	
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.4	11.96	-0.03	0	Antenna D	F9FYLD00UMLWN	QPSK	1	0	0 mm	back	1:1	0.734	1.107	0.813	0.327	0.362	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.10	-0.06	0	Antenna D	F9FYLD00UMLWN	QPSK	50	25	0 mm	back	1:1	0.809	1.072	0.867	0.360	0.386	
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.4	12.00	-0.08	0	Antenna D	F9FYLD00UMLWN	QPSK	50	25	0 mm	back	1:1	0.737	1.096	0.808	0.329	0.361	
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.4	11.96	-0.05	0	Antenna D	F9FYLD00UMLWN	QPSK	50	25	0 mm	back	1:1	0.708	1.107	0.784	0.315	0.349	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.05	-0.01	0	Antenna D	F9FYLD00UMLWN	QPSK	100	0	0 mm	back	1:1	0.826	1.084	0.895	0.369	0.400	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.01	-0.01	0	Antenna D	F9FYLD00UMLWN	QPSK	1	50	0 mm	top	1:1	0.999	1.094	1.093	0.414	0.453	
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	12.14	-0.04	0	Antenna D	F9FYLD00UMLWN	QPSK	1	0	0 mm	top	1:1	1.030	1.062	1.094	0.429	0.456	
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.40	11.96	-0.04	0	Antenna D	F9FYLD00UMLWN	QPSK	1	0	0 mm	top	1:1	1.040	1.107	1.151	0.427	0.473	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.10	0.01	0	Antenna D	F9FYLD00UMLWN	QPSK	50	25	0 mm	top	1:1	0.992	1.072	1.063	0.413	0.443	
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.4	12.00	-0.06	0	Antenna D	F9FYLD00UMLWN	QPSK	50	25	0 mm	top	1:1	1.020	1.096	1.118	0.420	0.460	
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.4	11.96	-0.06	0	Antenna D	F9FYLD00UMLWN	QPSK	50	25	0 mm	top	1:1	1.030	1.107	1.140	0.424	0.469	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.05	-0.01	0	Antenna D	F9FYLD00UMLWN	QPSK	100	0	0 mm	top	1:1	1.010	1.084	1.095	0.423	0.459	
2 CC Uplink	PCC	2560.00	21350	High	LTE Band 7	20	12.40	11.73	0.07	0	Antenna D	F9FYLD00UMLWN	QPSK	1	0	0 mm	top	1:1	0.976	1.167	1.139	0.419	0.489	
2 CC Uplink	SCC	2540.20	21152	High	LTE Band 7	20								1	99									
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	12.14	0.00	0	Antenna D	F9FYLD00UMLWN	QPSK	1	0	0 mm	bottom	1:1	0.000	1.062	0.000	0.000	0.000	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.10	0.00	0	Antenna D	F9FYLD00UMLWN	QPSK	50	25	0 mm	bottom	1:1	0.000	1.072	0.000	0.000	0.000	
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	12.14	-0.09	0	Antenna D	F9FYLD00UMLWN	QPSK	1	0	0 mm	right	1:1	0.013	1.062	0.014	0.006	0.006	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.10	0.08	0	Antenna D	F9FYLD00UMLWN	QPSK	50	25	0 mm	right	1:1	0.012	1.072	0.013	0.005	0.005	
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	12.14	-0.09	0	Antenna D	F9FYLD00UMLWN	QPSK	1	0	0 mm	left	1:1	0.146	1.062	0.155	0.059	0.063	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.10	-0.07	0	Antenna D	F9FYLD00UMLWN	QPSK	50	25	0 mm	left	1:1	0.145	1.072	0.155	0.060	0.064	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Body														
Spatial Peak										1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population										averaged over 1 gram														

Table 10-31
LTE Band 41 Body SAR – Antenna C

MEASUREMENT RESULTS																								
1 CC Uplink / 2 CC Uplink, Power Class	Component Carrier	FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
		MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.28	-0.04	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	back	1:1.58	0.846	1.028	0.870	0.321	0.330	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.36	0.06	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	back	1:1.58	1.010	1.009	1.019	0.416	0.420	
1 CC Uplink - Power Class 3	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	15.14	0.02	0	Antenna C	F9FYLO0UMLWN	QPSK	1	99	0 mm	back	1:1.58	0.900	1.062	0.956	0.366	0.389	
1 CC Uplink - Power Class 3	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	15.22	0.01	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	back	1:1.58	0.931	1.042	0.970	0.373	0.389	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	15.26	-0.11	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	back	1:1.58	0.568	1.033	0.587	0.229	0.237	
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.20	-0.05	0	Antenna C	F9FYLO0UMLWN	QPSK	50	0	0 mm	back	1:1.58	0.839	1.047	0.878	0.381	0.399	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.27	0.01	0	Antenna C	F9FYLO0UMLWN	QPSK	50	0	0 mm	back	1:1.58	0.989	1.030	1.019	0.406	0.418	
1 CC Uplink - Power Class 3	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	15.15	0.12	0	Antenna C	F9FYLO0UMLWN	QPSK	50	50	0 mm	back	1:1.58	0.762	1.059	0.807	0.322	0.341	
1 CC Uplink - Power Class 3	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	15.18	0.03	0	Antenna C	F9FYLO0UMLWN	QPSK	50	0	0 mm	back	1:1.58	0.899	1.052	0.946	0.359	0.378	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	15.03	0.06	0	Antenna C	F9FYLO0UMLWN	QPSK	50	50	0 mm	back	1:1.58	0.568	1.089	0.619	0.220	0.240	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.21	-0.04	0	Antenna C	F9FYLO0UMLWN	QPSK	100	0	0 mm	back	1:1.58	0.977	1.045	1.021	0.400	0.418	
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.28	-0.01	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	top	1:1.58	1.010	1.028	1.038	0.437	0.449	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.36	-0.02	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	top	1:1.58	1.120	1.009	1.130	0.475	0.479	
1 CC Uplink - Power Class 3	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	15.14	0.02	0	Antenna C	F9FYLO0UMLWN	QPSK	1	99	0 mm	top	1:1.58	1.120	1.062	1.189	0.478	0.508	
1 CC Uplink - Power Class 3	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	15.22	-0.04	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	top	1:1.58	1.140	1.042	1.188	0.478	0.498	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	15.26	0.05	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	top	1:1.58	1.150	1.033	1.188	0.476	0.492	A16
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.20	-0.03	0	Antenna C	F9FYLO0UMLWN	QPSK	50	0	0 mm	top	1:1.58	1.010	1.047	1.057	0.432	0.452	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.27	-0.04	0	Antenna C	F9FYLO0UMLWN	QPSK	50	0	0 mm	top	1:1.58	1.080	1.030	1.112	0.458	0.472	
1 CC Uplink - Power Class 3	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	15.15	0.01	0	Antenna C	F9FYLO0UMLWN	QPSK	50	50	0 mm	top	1:1.58	1.120	1.059	1.186	0.474	0.502	
1 CC Uplink - Power Class 3	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	15.18	0.01	0	Antenna C	F9FYLO0UMLWN	QPSK	50	0	0 mm	top	1:1.58	1.130	1.052	1.189	0.469	0.493	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	15.03	-0.01	0	Antenna C	F9FYLO0UMLWN	QPSK	50	50	0 mm	top	1:1.58	1.090	1.089	1.187	0.445	0.485	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.21	0.12	0	Antenna C	F9FYLO0UMLWN	QPSK	100	0	0 mm	top	1:1.58	1.110	1.045	1.160	0.469	0.490	
1 CC Uplink - Power Class 2	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	15.02	-0.06	0	Antenna C	F9FYLO0UMLWN	QPSK	1	99	0 mm	top	12:31	0.752	1.091	0.820	0.316	0.345	
2 CC Uplink - Power Class 3	PCC	2593.00	40620	Mid	LTE Band 41	20	15.40	15.39	-0.15	0	Antenna C	F9FYLO0UMLWN	QPSK	1	99	0 mm	top	1:1.58	1.140	1.002	1.142	0.476	0.477	
2 CC Uplink - Power Class 3	SCC	2612.80	40818	Mid	LTE Band 41	20								1	0	0 mm	top	1:1.58						
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.36	0.00	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	bottom	1:1.58	0.000	1.009	0.000	0.000	0.000	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.27	0.00	0	Antenna C	F9FYLO0UMLWN	QPSK	50	0	0 mm	bottom	1:1.58	0.000	1.030	0.000	0.000	0.000	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.36	0.01	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	right	1:1.58	0.159	1.009	0.160	0.064	0.065	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.27	0.06	0	Antenna C	F9FYLO0UMLWN	QPSK	50	0	0 mm	right	1:1.58	0.154	1.030	0.159	0.062	0.064	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.36	0.07	0	Antenna C	F9FYLO0UMLWN	QPSK	1	0	0 mm	left	1:1.58	0.034	1.009	0.034	0.014	0.014	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.27	0.09	0	Antenna C	F9FYLO0UMLWN	QPSK	50	0	0 mm	left	1:1.58	0.035	1.030	0.036	0.014	0.014	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Body														
Spatial Peak										1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population										averaged over 1 gram														

FCC ID: BCGA2200		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 99 of 116	

Table 10-32
LTE Band 41 Body SAR – Antenna D

MEASUREMENT RESULTS																								
1 CC Uplink / 2 CC Uplink, Power Class	Component Carrier	FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Pilot #
		MHz		Ch.															(W/kg)		(W/kg)	(W/kg)	(W/kg)	
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.32	-0.06	0	Antenna D	F9FY00UMLWN	QPSK	1	0	0 mm	back	1:1.58	0.992	1.019	1.011	0.427	0.435	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.40	0.03	0	Antenna D	F9FY00UMLWN	QPSK	1	99	0 mm	back	1:1.58	0.834	1.000	0.834	0.353	0.353	
1 CC Uplink - Power Class 3	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	15.27	0.01	0	Antenna D	F9FY00UMLWN	QPSK	1	0	0 mm	back	1:1.58	0.784	1.030	0.808	0.326	0.336	
1 CC Uplink - Power Class 3	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	15.26	0.00	0	Antenna D	F9FY00UMLWN	QPSK	1	0	0 mm	back	1:1.58	0.699	1.033	0.722	0.288	0.298	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	15.10	-0.01	0	Antenna D	F9FY00UMLWN	QPSK	1	0	0 mm	back	1:1.58	0.498	1.072	0.534	0.212	0.227	
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.32	0.00	0	Antenna D	F9FY00UMLWN	QPSK	50	0	0 mm	back	1:1.58	0.968	1.019	0.986	0.416	0.424	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.29	0.00	0	Antenna D	F9FY00UMLWN	QPSK	50	0	0 mm	back	1:1.58	0.842	1.026	0.864	0.354	0.363	
1 CC Uplink - Power Class 3	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	15.17	-0.02	0	Antenna D	F9FY00UMLWN	QPSK	50	0	0 mm	back	1:1.58	0.747	1.054	0.787	0.307	0.324	
1 CC Uplink - Power Class 3	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	14.99	0.01	0	Antenna D	F9FY00UMLWN	QPSK	50	25	0 mm	back	1:1.58	0.666	1.099	0.732	0.273	0.300	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	14.97	0.00	0	Antenna D	F9FY00UMLWN	QPSK	50	0	0 mm	back	1:1.58	0.523	1.104	0.577	0.208	0.230	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.26	-0.01	0	Antenna D	F9FY00UMLWN	QPSK	100	0	0 mm	back	1:1.58	0.831	1.033	0.858	0.351	0.363	
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.32	-0.16	0	Antenna D	F9FY00UMLWN	QPSK	1	0	0 mm	top	1:1.58	0.825	1.019	0.841	0.362	0.369	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.40	0.07	0	Antenna D	F9FY00UMLWN	QPSK	1	99	0 mm	top	1:1.58	1.130	1.000	1.130	0.464	0.464	
1 CC Uplink - Power Class 3	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	15.27	-0.18	0	Antenna D	F9FY00UMLWN	QPSK	1	0	0 mm	top	1:1.58	1.130	1.030	1.164	0.452	0.466	
1 CC Uplink - Power Class 3	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	15.26	0.05	0	Antenna D	F9FY00UMLWN	QPSK	1	0	0 mm	top	1:1.58	1.150	1.033	1.188	0.460	0.475	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	15.10	0.06	0	Antenna D	F9FY00UMLWN	QPSK	1	0	0 mm	top	1:1.58	1.090	1.072	1.168	0.441	0.473	
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.32	-0.02	0	Antenna D	F9FY00UMLWN	QPSK	50	0	0 mm	top	1:1.58	0.884	1.019	0.901	0.361	0.368	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.29	-0.03	0	Antenna D	F9FY00UMLWN	QPSK	50	0	0 mm	top	1:1.58	0.967	1.026	0.992	0.419	0.430	
1 CC Uplink - Power Class 3	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	15.17	0.01	0	Antenna D	F9FY00UMLWN	QPSK	50	0	0 mm	top	1:1.58	1.090	1.054	1.149	0.437	0.461	
1 CC Uplink - Power Class 3	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	14.99	-0.04	0	Antenna D	F9FY00UMLWN	QPSK	50	25	0 mm	top	1:1.58	1.070	1.099	1.176	0.428	0.470	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	14.97	0.10	0	Antenna D	F9FY00UMLWN	QPSK	50	0	0 mm	top	1:1.58	0.991	1.104	1.094	0.396	0.437	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.26	-0.02	0	Antenna D	F9FY00UMLWN	QPSK	100	0	0 mm	top	1:1.58	1.020	1.033	1.054	0.419	0.433	
1 CC Uplink - Power Class 2	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	15.03	0.04	0	Antenna D	F9FY00UMLWN	QPSK	1	0	0 mm	top	12:31	0.771	1.089	0.840	0.313	0.341	
2 CC Uplink - Power Class 3	PCC	2636.50	41055	Mid-High	LTE Band 41	20	15.40	15.00	0.06	0	Antenna D	F9FY00UMLWN	QPSK	1	0	0 mm	top	1:1.58	1.050	1.096	1.151	0.427	0.468	
2 CC Uplink - Power Class 3	SCC	2616.70	40857	Mid-High	LTE Band 41	20								1	99									
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.40	0.01	0	Antenna D	F9FY00UMLWN	QPSK	1	99	0 mm	bottom	1:1.58	0.000	1.000	0.000	0.000	0.000	
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.32	0.02	0	Antenna D	F9FY00UMLWN	QPSK	50	0	0 mm	bottom	1:1.58	0.001	1.019	0.001	0.000	0.000	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.40	0.01	0	Antenna D	F9FY00UMLWN	QPSK	1	99	0 mm	right	1:1.58	0.023	1.000	0.023	0.009	0.009	
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.32	0.07	0	Antenna D	F9FY00UMLWN	QPSK	50	0	0 mm	right	1:1.58	0.023	1.019	0.023	0.009	0.009	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.40	0.04	0	Antenna D	F9FY00UMLWN	QPSK	1	99	0 mm	left	1:1.58	0.142	1.000	0.142	0.054	0.054	
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.32	0.05	0	Antenna D	F9FY00UMLWN	QPSK	50	0	0 mm	left	1:1.58	0.167	1.019	0.170	0.069	0.070	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Body														
Spatial Peak										1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population										averaged over 1 gram														

Table 10-33
2.4GHz WLAN Body SAR- Antenna A

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Pilot #
MHz	Ch.														(W/kg)			(W/kg)		(W/kg)	
2437	6	802.11b	DSSS	22	16.00	15.50	0.11	0 mm	Antenna A	V1	F9FYL00TMLWN	1	back	100.0	0.043	1.122	1.000	0.048	0.017	0.019	
2437	6	802.11b	DSSS	22	16.00	15.50	-0.01	0 mm	Antenna A	V1	F9FYL00TMLWN	1	top	100.0	0.004	1.122	1.000	0.004	0.001	0.001	
2412	1	802.11b	DSSS	22	16.00	15.46	-0.14	0 mm	Antenna A	V1	F9FYL00TMLWN	1	bottom	100.0	0.814	1.132	1.000	0.921	0.260	0.294	
2437	6	802.11b	DSSS	22	16.00	15.50	0.01	0 mm	Antenna A	V1	F9FYL00TMLWN	1	bottom	100.0	0.842	1.122	1.000	0.945	0.275	0.309	A17
2437	6	802.11b	DSSS	22	16.00	15.35	-0.14	0 mm	Antenna A	V2	F9FYL001MLWQ	1	bottom	100.0	0.701	1.161	1.000	0.814	0.228	0.265	
2462	11	802.11b	DSSS	22	16.00	15.42	-0.16	0 mm	Antenna A	V1	F9FYL00TMLWN	1	bottom	100.0	0.776	1.143	1.000	0.887	0.247	0.282	
2437	6	802.11b	DSSS	22	16.00	15.50	0.00	0 mm	Antenna A	V1	F9FYL00TMLWN	1	right	100.0	0.000	1.122	1.000	0.000	0.000	0.000	
2437	6	802.11b	DSSS	22	16.00	15.50	0.06	0 mm	Antenna A	V1	F9FYL00TMLWN	1	left	100.0	0.112	1.122	1.000	0.126	0.047	0.053	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Body												
Spatial Peak									1.6 W/kg (mW/g)												
Uncontrolled Exposure/General Population									averaged over 1 gram												

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 100 of 116

Table 10-34
2.4GHz WLAN Body SAR- Antenna B

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.														(W/kg)			(W/kg)	(W/kg)			
2437	6	802.11b	DSSS	22	16.00	15.49	0.01	0 mm	Antenna B	V1	F9FY00TMLWN	1	back	100.0	0.072	1.125	1.000	0.081	0.025	0.028		
2437	6	802.11b	DSSS	22	16.00	15.49	0.04	0 mm	Antenna B	V1	F9FY00TMLWN	1	top	100.0	0.005	1.125	1.000	0.006	0.001	0.001		
2412	1	802.11b	DSSS	22	16.00	15.42	0.14	0 mm	Antenna B	V1	F9FY00TMLWN	1	bottom	100.0	0.798	1.143	1.000	0.912	0.259	0.296		
2412	1	802.11b	DSSS	22	16.00	15.34	0.10	0 mm	Antenna B	V2	F9FY00TMLWQ	1	bottom	100.0	0.680	1.164	1.000	0.792	0.222	0.258		
2437	6	802.11b	DSSS	22	16.00	15.49	0.12	0 mm	Antenna B	V1	F9FY00TMLWN	1	bottom	100.0	0.775	1.125	1.000	0.872	0.247	0.278		
2462	11	802.11b	DSSS	22	16.00	15.40	0.00	0 mm	Antenna B	V1	F9FY00TMLWN	1	bottom	100.0	0.668	1.148	1.000	0.767	0.214	0.246		
2437	6	802.11b	DSSS	22	16.00	15.49	-0.07	0 mm	Antenna B	V1	F9FY00TMLWN	1	right	100.0	0.144	1.125	1.000	0.162	0.060	0.068		
2437	6	802.11b	DSSS	22	16.00	15.49	0.06	0 mm	Antenna B	V1	F9FY00TMLWN	1	left	100.0	0.001	1.125	1.000	0.001	0.000	0.000		
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

Table 10-35
5GHz WLAN Body SAR- Antenna A

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)		Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.														(W/kg)	(W/kg)			(W/kg)	(W/kg)		
5270	54	802.11n	OFDM	40	17.00	17.00	0.02	0 mm	Antenna A	V2	F9FYL001MLWQ	13.5	back	97.4	0.051	1.000	1.027	0.052	0.019	0.020		
5270	54	802.11n	OFDM	40	17.00	17.00	0.02	0 mm	Antenna A	V2	F9FYL001MLWQ	13.5	top	97.4	0.022	1.000	1.027	0.023	0.004	0.004		
5270	54	802.11n	OFDM	40	17.00	16.82	0.01	0 mm	Antenna A	V1	F9FYL00WMLWN	13.5	bottom	97.4	0.758	1.042	1.027	0.811	0.245	0.262		
5270	54	802.11n	OFDM	40	17.00	17.00	-0.09	0 mm	Antenna A	V2	F9FYL001MLWQ	13.5	bottom	97.4	0.860	1.000	1.027	0.883	0.281	0.289		
5310	62	802.11n	OFDM	40	14.50	14.32	0.03	0 mm	Antenna A	V2	F9FYL001MLWQ	13.5	bottom	97.4	0.445	1.042	1.027	0.476	0.146	0.156		
5270	54	802.11n	OFDM	40	17.00	17.00	0.00	0 mm	Antenna A	V2	F9FYL001MLWQ	13.5	right	97.4	0.000	1.000	1.027	0.000	0.000	0.000		
5270	54	802.11n	OFDM	40	17.00	17.00	0.07	0 mm	Antenna A	V2	F9FYL001MLWQ	13.5	left	97.4	0.090	1.000	1.027	0.092	0.034	0.035		
5690	138	802.11ac	OFDM	80	17.50	17.00	0.00	0 mm	Antenna A	V2	F9FYL001MLWQ	29.3	back	95.0	0.091	1.122	1.053	0.108	0.029	0.034		
5690	138	802.11ac	OFDM	80	17.50	17.00	0.01	0 mm	Antenna A	V2	F9FYL001MLWQ	29.3	top	95.0	0.010	1.122	1.053	0.012	0.002	0.002		
5530	106	802.11ac	OFDM	80	14.00	13.85	-0.02	0 mm	Antenna A	V2	F9FYL001MLWQ	29.3	bottom	95.0	0.432	1.035	1.053	0.471	0.145	0.158		
5610	122	802.11ac	OFDM	80	17.00	16.92	0.01	0 mm	Antenna A	V2	F9FYL001MLWQ	29.3	bottom	95.0	0.639	1.019	1.053	0.686	0.218	0.234		
5690	138	802.11ac	OFDM	80	17.50	16.89	-0.13	0 mm	Antenna A	V1	F9FYL00TMLWN	29.3	bottom	95.0	0.678	1.151	1.053	0.822	0.232	0.281		
5690	138	802.11ac	OFDM	80	17.50	17.00	-0.04	0 mm	Antenna A	V2	F9FYL001MLWQ	29.3	bottom	95.0	0.806	1.122	1.053	0.952	0.274	0.324		
5690	138	802.11ac	OFDM	80	17.50	17.00	0.00	0 mm	Antenna A	V2	F9FYL001MLWQ	29.3	right	95.0	0.000	1.122	1.053	0.000	0.000	0.000		
5690	138	802.11ac	OFDM	80	17.50	17.00	-0.03	0 mm	Antenna A	V2	F9FYL001MLWQ	29.3	left	95.0	0.116	1.122	1.053	0.137	0.039	0.046		
5775	155	802.11ac	OFDM	80	16.25	16.25	0.11	0 mm	Antenna A	V2	F9FYL001MLWQ	29.3	back	95.0	0.072	1.000	1.053	0.076	0.025	0.026		
5775	155	802.11ac	OFDM	80	16.25	16.25	0.04	0 mm	Antenna A	V2	F9FYL001MLWQ	29.3	top	95.0	0.020	1.000	1.053	0.021	0.006	0.006		
5775	155	802.11ac	OFDM	80	16.25	16.25	0.04	0 mm	Antenna A	V1	F9FYL00WMLWN	29.3	bottom	95.0	0.686	1.000	1.053	0.722	0.230	0.242		
5775	155	802.11ac	OFDM	80	16.25	16.25	0.01	0 mm	Antenna A	V2	F9FYL001MLWQ	29.3	bottom	95.0	0.797	1.000	1.053	0.839	0.266	0.280		
5775	155	802.11ac	OFDM	80	16.25	16.25	0.00	0 mm	Antenna A	V2	F9FYL001MLWQ	29.3	right	95.0	0.000	1.000	1.053	0.000	0.000	0.000		
5775	155	802.11ac	OFDM	80	16.25	16.25	-0.02	0 mm	Antenna A	V2	F9FYL001MLWQ	29.3	left	95.0	0.089	1.000	1.053	0.094	0.031	0.033		
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 101 of 116

Table 10-36
5GHz WLAN Body SAR – Antenna B

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)		Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.														(W/kg)	(W/kg)			(W/kg)	(W/kg)		
5270	54	802.11n	OFDM	40	16.75	16.59	0.06	0 mm	Antenna B	V2	F9FYL001MLWQ	13.5	back	97.7	0.068	1.038	1.024	0.072	0.025	0.027		
5270	54	802.11n	OFDM	40	16.75	16.59	0.01	0 mm	Antenna B	V2	F9FYL001MLWQ	13.5	top	97.7	0.023	1.038	1.024	0.024	0.007	0.007		
5270	54	802.11n	OFDM	40	16.75	16.71	0.12	0 mm	Antenna B	V1	F9FYL00WMLWN	13.5	bottom	97.7	0.820	1.009	1.024	0.847	0.261	0.270		
5270	54	802.11n	OFDM	40	16.75	16.59	0.01	0 mm	Antenna B	V2	F9FYL001MLWQ	13.5	bottom	97.7	0.926	1.038	1.024	0.984	0.308	0.327		
5310	62	802.11n	OFDM	40	14.50	14.50	0.04	0 mm	Antenna B	V2	F9FYL001MLWQ	13.5	bottom	97.7	0.492	1.000	1.024	0.504	0.162	0.166		
5270	54	802.11n	OFDM	40	16.75	16.59	-0.06	0 mm	Antenna B	V2	F9FYL001MLWQ	13.5	right	97.7	0.108	1.038	1.024	0.115	0.041	0.044		
5270	54	802.11n	OFDM	40	16.75	16.59	0.00	0 mm	Antenna B	V2	F9FYL001MLWQ	13.5	left	97.7	0.000	1.038	1.024	0.000	0.000	0.000		
5690	138	802.11ac	OFDM	80	17.25	16.85	0.02	0 mm	Antenna B	V2	F9FYL001MLWQ	29.3	back	95.0	0.069	1.096	1.053	0.080	0.026	0.030		
5690	138	802.11ac	OFDM	80	17.25	16.85	0.01	0 mm	Antenna B	V2	F9FYL001MLWQ	29.3	top	95.0	0.023	1.096	1.053	0.027	0.007	0.008		
5530	106	802.11ac	OFDM	80	14.00	14.00	0.12	0 mm	Antenna B	V2	F9FYL001MLWQ	29.3	bottom	95.0	0.370	1.000	1.053	0.390	0.124	0.131		
5610	122	802.11ac	OFDM	80	17.00	16.87	0.04	0 mm	Antenna B	V2	F9FYL001MLWQ	29.3	bottom	95.0	0.872	1.030	1.053	0.946	0.297	0.322		
5690	138	802.11ac	OFDM	80	17.25	16.80	0.10	0 mm	Antenna B	V1	F9FYL00TMLWN	29.3	bottom	95.0	0.885	1.109	1.053	1.033	0.312	0.364		
5690	138	802.11ac	OFDM	80	17.25	16.85	0.00	0 mm	Antenna B	V2	F9FYL001MLWQ	29.3	bottom	95.0	0.958	1.096	1.053	1.106	0.324	0.374	A18	
5690	138	802.11ac	OFDM	80	17.25	16.85	0.02	0 mm	Antenna B	V2	F9FYL001MLWQ	29.3	right	95.0	0.091	1.096	1.053	0.105	0.033	0.038		
5690	138	802.11ac	OFDM	80	17.25	16.85	0.00	0 mm	Antenna B	V2	F9FYL001MLWQ	29.3	left	95.0	0.000	1.096	1.053	0.000	0.000	0.000		
5775	155	802.11ac	OFDM	80	16.50	16.37	0.05	0 mm	Antenna B	V2	F9FYL001MLWQ	29.3	back	95.0	0.078	1.030	1.053	0.085	0.027	0.029		
5775	155	802.11ac	OFDM	80	16.50	16.37	0.17	0 mm	Antenna B	V2	F9FYL001MLWQ	29.3	top	95.0	0.013	1.030	1.053	0.014	0.003	0.003		
5775	155	802.11ac	OFDM	80	16.50	16.50	0.05	0 mm	Antenna B	V1	F9FYL00WMLWN	29.3	bottom	95.0	0.799	1.000	1.053	0.841	0.283	0.298		
5775	155	802.11ac	OFDM	80	16.50	16.37	0.03	0 mm	Antenna B	V2	F9FYL001MLWQ	29.3	bottom	95.0	0.866	1.030	1.053	0.939	0.294	0.319		
5775	155	802.11ac	OFDM	80	16.50	16.37	0.14	0 mm	Antenna B	V2	F9FYL001MLWQ	29.3	right	95.0	0.073	1.030	1.053	0.079	0.025	0.027		
5775	155	802.11ac	OFDM	80	16.50	16.37	0.00	0 mm	Antenna B	V2	F9FYL001MLWQ	29.3	left	95.0	0.001	1.030	1.053	0.001	0.000	0.000		
5270	54	802.11n	OFDM	40	16.75	16.59	0.02	0 mm	Antenna B	V2	F9FYL001MLWQ	13.5	bottom	97.7	0.924	1.038	1.024	0.982	0.307	0.326		
5610	122	802.11ac	OFDM	80	17.00	16.87	0.16	0 mm	Antenna B	V2	F9FYL001MLWQ	29.3	bottom	95.0	0.873	1.030	1.053	0.947	0.303	0.329		
5690	138	802.11ac	OFDM	80	17.25	16.85	0.00	0 mm	Antenna B	V2	F9FYL001MLWQ	29.3	bottom	95.0	0.941	1.096	1.053	1.086	0.324	0.374		
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

Note: Blue entry represents variability measurement.

Table 10-37
Bluetooth Body SAR – Antenna A

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.													(W/kg)			(W/kg)	(W/kg)		
2402	0	Bluetooth	FHSS	17.00	16.57	0.09	0 mm	Antenna A	V2	F9FYL000MLWQ	1	back	77.4	0.066	1.104	1.001	0.073	0.028	0.031	
2402	0	Bluetooth	FHSS	17.00	16.57	0.00	0 mm	Antenna A	V2	F9FYL000MLWQ	1	top	77.4	0.002	1.104	1.001	0.002	0.000	0.000	
2402	0	Bluetooth	FHSS	17.00	15.69	-0.02	0 mm	Antenna A	V1	F9FYL00WMLWN	1	bottom	77.4	0.696	1.352	1.001	0.942	0.224	0.303	
2402	0	Bluetooth	FHSS	17.00	16.57	-0.07	0 mm	Antenna A	V2	F9FYL000MLWQ	1	bottom	77.4	0.967	1.104	1.001	1.069	0.316	0.349	A19
2441	39	Bluetooth	FHSS	17.00	16.49	-0.02	0 mm	Antenna A	V2	F9FYL000MLWQ	1	bottom	77.4	0.883	1.125	1.001	0.994	0.288	0.324	
2480	78	Bluetooth	FHSS	17.00	15.83	0.12	0 mm	Antenna A	V2	F9FYL000MLWQ	1	bottom	77.4	0.723	1.309	1.001	0.947	0.234	0.307	
2402	0	Bluetooth	FHSS	17.00	16.57	0.00	0 mm	Antenna A	V2	F9FYL000MLWQ	1	right	77.4	0.000	1.104	1.001	0.000	0.000	0.000	
2402	0	Bluetooth	FHSS	17.00	16.57	0.12	0 mm	Antenna A	V2	F9FYL000MLWQ	1	left	77.4	0.143	1.104	1.001	0.158	0.060	0.066	
2441	39	Bluetooth	FHSS	10.00	9.75	0.05	0 mm	Antenna A	V2	F9FYL000MLWQ	1	back	77.4	0.010	1.059	1.001	0.011	0.004	0.004	
2441	39	Bluetooth	FHSS	10.00	9.75	0.05	0 mm	Antenna A	V2	F9FYL000MLWQ	1	top	77.4	0.001	1.059	1.001	0.001	0.000	0.000	
2441	39	Bluetooth	FHSS	10.00	9.75	-0.10	0 mm	Antenna A	V2	F9FYL000MLWQ	1	bottom	77.4	0.167	1.059	1.001	0.177	0.055	0.058	
2441	39	Bluetooth	FHSS	10.00	9.75	0.00	0 mm	Antenna A	V2	F9FYL000MLWQ	1	right	77.4	0.000	1.059	1.001	0.000	0.000	0.000	
2441	39	Bluetooth	FHSS	10.00	9.75	0.15	0 mm	Antenna A	V2	F9FYL000MLWQ	1	left	77.4	0.023	1.059	1.001	0.024	0.010	0.011	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body													
Spatial Peak							1.6 W/kg (mW/g)													
Uncontrolled Exposure/General Population							averaged over 1 gram													

Note: The reported SAR was scaled to the 77.5% transmission duty factor to determine compliance since the duty factor of the device is permanently limited to 77.5% per the manufacturer.

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 102 of 116

10.2 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in FCC KDB Publication 616217 D04v01r02 and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 12 for variability analysis.
7. FCC KDB Publication 616217 D04v01r02 Section 4.3, SAR tests are required for the back surface and edges of the tablet with the tablet touching the phantom. The SAR Exclusion Threshold in FCC KDB 447498 D01v06 was applied to determine SAR test exclusion for adjacent edge configurations.

GSM Test Notes:

1. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 7.5.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 and MCC=001 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 103 of 116

4. Per FCC KDB Publication 447498 D01v06, when the reported LTE Band 41 SAR measured at the highest output power channel in a given a test configuration was > 0.6 W/kg for 1g evaluations, testing at the other channels was required for such test configurations.
5. TDD LTE was tested per the guidance provided in FCC KDB Publication 941225 D05v02r04. Testing was performed using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using extended cyclic prefix only and special subframe configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.
6. Per KDB Publication 941225 D05Av01r02, SAR for downlink only LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.
7. This device supports Power Class 2 and Power Class 3 operations for LTE Band 41. The highest available duty cycle for Power Class 2 operations is 43.3 % using UL-DL configuration 1. Per FCC Guidance, all SAR tests were performed using Power Class 3. SAR with power class 2 at the available duty factor was additionally performed for the power class 3 configuration with the highest SAR configuration for each exposure conditions. Please see Section 14 for linearity results.
8. For LTE Band 7 and 41, per FCC guidance, SAR was first measured with only a single carrier active in the uplink (carrier aggregation not active). For each exposure condition, the uplink CA scenario with two component carriers was additionally tested for the configuration with the highest SAR when carrier aggregation was not active. The SCC was configured with the closest available contiguous channel. The two component carriers were configured so the resource blocks are physically allocated side by side to achieve the maximum output power. ULCA is only supported in Power Class 3.

WLAN Notes:

1. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.7.5 for more information.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg for 1g evaluations. See Section 8.7.6 for more information.
3. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg for 1g evaluations or all test channels were measured.
4. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

Bluetooth Notes

1. Bluetooth SAR was measured with the device connected to a call box with hopping disabled with DH5 operation and Tx Tests test mode type. Per October 2016 TCB Workshop Notes, the reported SAR was scaled to the 100% transmission duty factor to determine compliance. See Section 8.5 for the time domain plot and calculation for the duty factor of the device.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 104 of 116

11 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

11.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

11.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR.

Note: ** The SAR distributions for at least one of the antennas are spatially separated from the other antennas per FCC KDB Publication 248227 Section 6.1 procedures. Therefore, the simultaneous transmission were treated independently for this configuration. See Section 11.4 for more information about the Spatial Separation Analysis.

For each position, the highest SAR value across all modes for the applicable cellular band antenna was considered for summation to determine simultaneous SAR test exclusion.

11.3 Body SAR Simultaneous Transmission Analysis

Table 11-1
Cellular Antenna C Simultaneous Transmission Scenario with 2.4 GHz WLAN

Simult Tx	Configuration	Cellular Antenna C SAR (W/kg)	2.4 GHz WLAN Antenna A SAR (W/kg)	2.4 GHz WLAN Antenna B SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body SAR	Back	1.179	0.048	0.081	1.227	1.260	1.308
	Top	1.189	0.004	0.006	1.193	1.195	1.199
	Bottom	0.027	0.945	0.912	0.972	0.939	0.972**
	Right	0.174	0.000	0.162	0.174	0.336	0.336
	Left	0.110	0.126	0.001	0.236	0.111	0.237

Table 11-2
Cellular Antenna D Simultaneous Transmission Scenario with 2.4 GHz WLAN

Simult Tx	Configuration	Cellular Antenna D SAR (W/kg)	2.4 GHz WLAN Antenna A SAR (W/kg)	2.4 GHz WLAN Antenna B SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body SAR	Back	1.166	0.048	0.081	1.214	1.247	1.295
	Top	1.188	0.004	0.006	1.192	1.194	1.198
	Bottom	0.036	0.945	0.912	0.981	0.948	0.981**
	Right	0.046	0.000	0.162	0.046	0.208	0.208
	Left	0.245	0.126	0.001	0.371	0.246	0.372

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 105 of 116

Table 11-3
Cellular Antenna C Simultaneous Transmission Scenario with 5 GHz WLAN

Simult Tx	Configuration	Cellular Antenna C SAR (W/kg)	5 GHz WLAN Antenna A SAR (W/kg)	5 GHz WLAN Antenna B SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body SAR	Back	1.179	0.108	0.085	1.287	1.264	1.372
	Top	1.189	0.023	0.027	1.212	1.216	1.239
	Bottom	0.027	0.952	1.106	0.979	1.133	1.133**
	Right	0.174	0.000	0.115	0.174	0.289	0.289
	Left	0.110	0.137	0.001	0.247	0.111	0.248

Table 11-4
Cellular Antenna D Simultaneous Transmission Scenario with 5 GHz WLAN

Simult Tx	Configuration	Cellular Antenna D SAR (W/kg)	5 GHz WLAN Antenna A SAR (W/kg)	5 GHz WLAN Antenna B SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body SAR	Back	1.166	0.108	0.085	1.274	1.251	1.359
	Top	1.188	0.023	0.027	1.211	1.215	1.238
	Bottom	0.036	0.952	1.106	0.988	1.142	1.142**
	Right	0.046	0.000	0.115	0.046	0.161	0.161
	Left	0.245	0.137	0.001	0.382	0.246	0.383

Table 11-5
Cellular Antenna C Simultaneous Transmission Scenario with Bluetooth

Simult Tx	Configuration	Cellular Antenna C SAR (W/kg)	Bluetooth Antenna A at 17.00 dBm SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body SAR	Back	1.179	0.073	1.252
	Top	1.189	0.002	1.191
	Bottom	0.027	1.069	1.096
	Right	0.174	0.000	0.174
	Left	0.110	0.158	0.268

Table 11-6
Cellular Antenna D Simultaneous Transmission Scenario with Bluetooth

Simult Tx	Configuration	Cellular Antenna D SAR (W/kg)	Bluetooth Antenna A at 17.00 dBm SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body SAR	Back	1.166	0.073	1.239
	Top	1.188	0.002	1.190
	Bottom	0.036	1.069	1.105
	Right	0.046	0.000	0.046
	Left	0.245	0.158	0.403

FCC ID: BCGA2200	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device		Page 106 of 116

Table 11-7

Cellular Antenna C Simultaneous Transmission Scenario with Bluetooth and 5 GHz WLAN

Simult Tx	Configuration	Cellular Antenna C SAR (W/kg)	Bluetooth Antenna A Reduced at 10.00 dBm SAR (W/kg)	5 GHz WLAN Antenna A SAR (W/kg)	5 GHz WLAN Antenna B SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	4	1+2+3	1+2+4	1+2+3+4
Body SAR	Back	1.179	0.011	0.108	0.085	1.298	1.275	1.383
	Top	1.189	0.001	0.023	0.027	1.213	1.217	1.240
	Bottom	0.027	0.177	0.952	1.106	1.156	1.310	1.156**
	Right	0.174	0.000	0.000	0.115	0.174	0.289	0.289
	Left	0.110	0.024	0.137	0.001	0.271	0.135	0.272

Table 11-8

Cellular Antenna D Simultaneous Transmission Scenario with Bluetooth and 5 GHz WLAN

Simult Tx	Configuration	Cellular Antenna D SAR (W/kg)	Bluetooth Antenna A Reduced at 10.00 dBm SAR (W/kg)	5 GHz WLAN Antenna A SAR (W/kg)	5 GHz WLAN Antenna B SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	4	1+2+3	1+2+4	1+2+3+4
Body SAR	Back	1.166	0.011	0.108	0.085	1.285	1.262	1.370
	Top	1.188	0.001	0.023	0.027	1.212	1.216	1.239
	Bottom	0.036	0.177	0.952	1.106	1.165	1.319	1.165**
	Right	0.046	0.000	0.000	0.115	0.046	0.161	0.161
	Left	0.245	0.024	0.137	0.001	0.406	0.270	0.407

Table 11-9

Simultaneous Transmission Scenario with Bluetooth and 5 GHz WLAN

Simult Tx	Configuration	Bluetooth Antenna A Reduced at 10.00 dBm SAR (W/kg)	5 GHz WLAN Antenna A SAR (W/kg)	5 GHz WLAN Antenna B SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body SAR	Back	0.011	0.108	0.085	0.119	0.096	0.204
	Top	0.001	0.023	0.027	0.024	0.028	0.051
	Bottom	0.177	0.952	1.106	1.129	1.283	1.129**
	Right	0.000	0.000	0.115	0.000	0.115	0.115
	Left	0.024	0.137	0.001	0.161	0.025	0.162

11.4 Spatial Separation Analysis


Per FCC KDB Publication 248227, antennas may be considered spatially separated when the aggregate SAR from multiple antennas at any location in the combined SAR distribution is either ≤ 1.2 W/kg where at least 90% of the SAR is attributed to a single SAR distribution or ≤ 0.4 W/kg where no more than one SAR distribution is contributing > 0.1 W/kg.

Spatial separation was determined by inspection of the area scan SAR distributions to confirm that at all locations, SAR was < 1.2 W/kg, where at least 90% of the SAR is attributed to a single SAR distribution. See below for illustrations of the spatial separated antennas considered.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 107 of 116

11.4.1 Bottom Edge Spatial Separation Analysis

Figure 11-1
Bottom Edge Spatial Separation for Antenna B and Antenna A



11.5 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 108 of 116

12 SAR MEASUREMENT VARIABILITY

12.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg
- 5) When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

Table 12-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS															
Band	FREQUENCY		Mode	Service	Antenna Configuration	Data Rate (Mbps)	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.							(W/kg)	(W/kg)		(W/kg)			
750	782.00	23230	LTE Band 13, 10 MHz Bandwidth	QPSK, 1 RB, 0 RB Offset	Antenna C	N/A	back	0 mm	1.110	1.090	1.02	N/A	N/A	N/A	N/A
850	819.00	26740	LTE Band 26 (Cell), 10 MHz Bandwidth	QPSK, 1 RB, 0 RB Offset	Antenna C	N/A	back	0 mm	1.160	1.110	1.05	N/A	N/A	N/A	N/A
1750	1770.00	132572	LTE Band 66 (AWS), 20 MHz Bandwidth	QPSK, 50 RB, 0 RB Offset	Antenna D	N/A	back	0 mm	1.090	1.080	1.01	N/A	N/A	N/A	N/A
1900	1880.00	9400	UMTS 1900	RMC	Antenna C	N/A	back	0 mm	1.140	1.130	1.01	N/A	N/A	N/A	N/A
2300	2310.00	27710	LTE Band 30, 10 MHz Bandwidth	QPSK, 1 RB, 0 RB Offset	Antenna C	N/A	top	0 mm	1.000	0.984	1.02	N/A	N/A	N/A	N/A
2450	2510.00	20850	LTE Band 7, 20 MHz Bandwidth	QPSK, 1 RB, 99 RB Offset	Antenna C	N/A	top	0 mm	1.140	1.120	1.02	N/A	N/A	N/A	N/A
2600	2560.00	21350	LTE Band 7, 20 MHz Bandwidth	QPSK, 1 RB, 99 RB Offset	Antenna C	N/A	top	0 mm	1.170	1.150	1.02	N/A	N/A	N/A	N/A
5250	5270.00	54	802.11n, 40 MHz Bandwidth	OFDM	Antenna B	13.5	bottom	0 mm	0.926	0.924	1.00	N/A	N/A	N/A	N/A
5600	5610.00	122	802.11ac, 80 MHz Bandwidth	OFDM	Antenna B	29.3	bottom	0 mm	0.872	0.873	1.00	N/A	N/A	N/A	N/A
5750	5690.00	138	802.11ac, 80 MHz Bandwidth	OFDM	Antenna B	29.3	bottom	0 mm	0.958	0.941	1.02	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Body 1.6 W/kg (mW/g) averaged over 1 gram						
Spatial Peak Uncontrolled Exposure/General Population															

12.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for 1g and < 3.75 W/kg for 10g for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 109 of 116

13 ADDITIONAL TESTING PER FCC GUIDANCE


13.1 LTE Band 41 Power Class 2 and Power Class 3 Linearity

This device supports Power Class 2 and Power Class 3 operations for LTE Band 41. The highest available duty cycle for Power Class 2 operations is 43.3 % using UL-DL configuration 1. Per May 2017 TCB Workshop Notes based on the device behavior, all SAR tests were performed using Power Class 3. SAR with Power Class 2 at the highest power and available duty factor was additionally performed for the Power Class 3 configuration with the highest SAR for each exposure condition. The linearity between the Power Class 2 and Power Class 3 SAR results and the respective frame averaged powers was calculated to determine that the results were linear. Per May 2017 TCB Workshop, no additional SAR measurements were required since the linearity between power classes was < 10% and all reported SAR values were < 1.4 W/kg for 1g and < 3.5 W/kg for 10g.

LTE Band 41 SAR testing with power class 2 at the highest power and available duty factor was additionally performed for the power class 3 configuration with the highest SAR for each exposure condition.

Table 13-1
LTE Band 41 Body Linearity Data – Antenna C

	LTE Band 41 PC3	LTE Band 41 PC2
Maximum Allowed Output Power (dBm)	15.4	15.4
Measured Output Power (dBm)	15.14	15.02
Measured SAR (W/kg)	1.12	0.752
Measured Power (mW)	32.66	31.77
Duty Cycle	63.3%	43.3%
Frame Averaged Output Power (mW)	20.67	13.76
% deviation from expected linearity		0.91%




FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 110 of 116

Table 13-2
LTE Band 41 Body Linearity Data – Antenna D

	LTE Band 41 PC3	LTE Band 41 PC2
Maximum Allowed Output Power (dBm)	15.4	15.4
Measured Output Power (dBm)	15.26	15.03
Measured SAR (W/kg)	1.15	0.771
Measured Power (mW)	33.57	31.84
Duty Cycle	63.3%	43.3%
Frame Averaged Output Power (mW)	21.25	13.79
% deviation from expected linearity		3.34%

LTE B41 SAR for PC2 and PC3 Operations



FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 111 of 116

14 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	85033E	3.5mm Standard Calibration Kit	8/13/2018	Annual	8/13/2019	MY53402352
Agilent	8753ES	S-Parameter Network Analyzer	10/2/2018	Annual	10/2/2019	US39170118
Agilent	E4438C	ESG Vector Signal Generator	6/22/2018	Annual	6/22/2019	MY53401181
Agilent	E4438C	ESG Vector Signal Generator	6/26/2018	Annual	6/26/2019	MY42081752
Agilent	N5182A	MXG Vector Signal Generator	11/28/2018	Annual	11/28/2019	MY47420603
Agilent	E4440A	PSA Series Spectrum Analyzer	11/14/2018	Annual	11/14/2019	MY46186272
Agilent	E5515C	Wireless Communications Test Set	2/28/2018	Biennial	2/28/2020	GB41450275
Agilent	N5182A	MXG Vector Signal Generator	6/15/2018	Annual	6/15/2019	MY47420837
Amplifier Research	150A100C	Amplifier	CBT	N/A	CBT	350132
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	343972
Anritsu	MA24106A	USB Power Sensor	7/17/2018	Annual	7/17/2019	1827527
Anritsu	MA24106A	USB Power Sensor	5/6/2019	Annual	5/6/2020	1231538
Anritsu	MA24106A	USB Power Sensor	6/5/2018	Annual	6/5/2019	1248508
Anritsu	ML2495A	Power Meter	11/20/2018	Annual	11/20/2019	1039008
Anritsu	MT8820C	Radio Communication Analyzer	6/27/2018	Annual	6/27/2019	6201240328
Control Company	4040	Temperature / Humidity Monitor	2/28/2018	Biennial	2/28/2020	150761911
Control Company	4352	Ultra Long Stem Thermometer	2/28/2018	Biennial	2/28/2020	170330160
Control Company	4352	Ultra Long Stem Thermometer	2/28/2018	Biennial	2/28/2020	170330158
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
Mini Circuits	NLP-2950+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini Circuits	NLP-1000+	Low Pass Filter	CBT	N/A	CBT	N/A
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mitutoyo	CD-6"CSX	Digital Caliper	4/18/2018	Biennial	4/18/2020	13264165
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Narda	BW-S3W2	Attenuator (3dB)	CBT	N/A	CBT	120
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
MCL	BW-N3W5+	3dB Attenuator	CBT	N/A	CBT	1707
MCL	BW-N10W5+	10dB Attenuator	CBT	N/A	CBT	1705
Mini Circuits	ZHDC-16-63-S+	50-6000MHz Bidirectional Coupler	CBT	N/A	CBT	N/A
Mini Circuits	ZNDC-20-2G-S+	800-2000MHz Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE5011-1	Torque Wrench	7/19/2017	Biennial	7/19/2019	N/A
Rohde & Schwarz	CMW500	Radio Communication Tester	4/15/2019	Annual	4/15/2020	167284
Rohde & Schwarz	CMW500	Radio Communication Tester	4/17/2019	Annual	4/17/2020	167285
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	7/6/2018	Annual	7/6/2019	151849
SPEAG	DAK-12	Dielectric Assessment Kit (10MHz - 3GHz)	11/13/2018	Annual	11/13/2019	1121
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/7/2019	Annual	5/7/2020	1070
SPEAG	DAKS-3.5	Portable DAK	9/11/2018	Annual	9/11/2019	1045
SPEAG	D750V3	750 MHz SAR Dipole	9/8/2017	Biennial	9/8/2019	1097
SPEAG	D750V3	750 MHz SAR Dipole	5/18/2018	Biennial	5/18/2020	1034
SPEAG	D835V2	835 MHz SAR Dipole	6/13/2017	Biennial	6/13/2019	4d040
SPEAG	D1750V2	1750 MHz SAR Dipole	9/7/2017	Biennial	9/7/2019	1104
SPEAG	D1900V2	1900 MHz SAR Dipole	9/7/2017	Biennial	9/7/2019	5d181
SPEAG	D2300V2	2300 MHz SAR Dipole	3/7/2018	Biennial	3/7/2020	1038
SPEAG	D2450V2	2450 MHz SAR Dipole	6/7/2017	Biennial	6/7/2019	750
SPEAG	D2450V2	2450 MHz SAR Dipole	11/12/2018	Annual	11/12/2019	921
SPEAG	D2600V2	2600 MHz SAR Dipole	9/11/2017	Biennial	9/11/2019	1069
SPEAG	D5GHzV2	5 GHz SAR Dipole	9/13/2018	Annual	9/13/2019	1163
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/15/2019	Annual	1/15/2020	793
SPEAG	DAE4	Dasy Data Acquisition Electronics	7/10/2018	Annual	7/10/2019	1402
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/13/2019	Annual	2/13/2020	1403
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/12/2018	Annual	11/12/2019	1449
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/14/2018	Annual	8/14/2019	1408
SPEAG	DAE4	Dasy Data Acquisition Electronics	10/18/2018	Annual	10/18/2019	1364
SPEAG	EX3DV4	SAR Probe	1/28/2019	Annual	1/28/2020	3837
SPEAG	EX3DV4	SAR Probe	7/20/2018	Annual	7/20/2019	7416
SPEAG	EX3DV4	SAR Probe	2/19/2019	Annual	2/19/2020	7427
SPEAG	EX3DV4	SAR Probe	9/18/2018	Annual	9/18/2019	7420
SPEAG	ES3DV3	SAR Probe	11/19/2018	Annual	11/19/2019	3318
SPEAG	EX3DV4	SAR Probe	7/20/2018	Annual	7/20/2019	7491

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements. Each equipment item was used solely within its respective calibration period.

FCC ID: BCGA2200		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 112 of 116

15 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)						RSS	11.5	11.3
Expanded Uncertainty (95% CONFIDENCE LEVEL)						k=2	23.0	22.6

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 113 of 116

16 CONCLUSION

16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: BCGA2200	 SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device
		Page 114 of 116

17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 115 of 116

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: BCGA2200	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1901280003-01-R3.BCG	Test Dates: 05/22/19 - 07/03/19	DUT Type: Tablet Device	Page 116 of 116

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL00EMLWN

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 848.8 MHz; Duty Cycle: 1:4.15

Medium: 835 MHz Body Medium parameters used (interpolated)

$f = 848.8 \text{ MHz}$; $\sigma = 1.009 \text{ S/m}$; $\epsilon_r = 53.663$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-28-2019; Ambient Temp: 21.3°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7416; ConvF(9.4, 9.4, 9.4) @ 848.8 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1402; Calibrated: 7/10/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CA; Serial: 1275

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 850 Antenna D, Body SAR, Back side, High.ch, 2 Tx Slots


Area Scan (10x16x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 33.78 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 3.12 W/kg

SAR(1 g) = 1.14 W/kg; SAR(10 g) = 0.569 W/kg



0 dB = 2.27 W/kg = 3.56 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL00EMLWN

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 1909.8 MHz; Duty Cycle: 1:4.15

Medium: 1900 MHz Body Medium parameters used:

$f = 1910 \text{ MHz}$; $\sigma = 1.572 \text{ S/m}$; $\epsilon_r = 52.448$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-28-2019; Ambient Temp: 20.9°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN7420; ConvF(7.7, 7.7, 7.7) @ 1909.8 MHz; Calibrated: 9/18/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1449; Calibrated: 11/12/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CC; Serial: 1596

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 1900 Antenna D, Body SAR, Back side, High.ch, 2 Tx Slots


Area Scan (15x19x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 26.30 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 2.05 W/kg

SAR(1 g) = 0.946 W/kg; SAR(10 g) = 0.397 W/kg



0 dB = 1.66 W/kg = 2.20 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL00EMLWN

Communication System: UID 0, UMTS; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium: 835 MHz Body Medium parameters used (interpolated):

$f = 846.6 \text{ MHz}$; $\sigma = 1.008 \text{ S/m}$; $\epsilon_r = 53.666$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-28-2019; Ambient Temp: 21.3°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7416; ConvF(9.4, 9.4, 9.4) @ 846.6 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1402; Calibrated: 7/10/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CA; Serial: 1275

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 850 Antenna D, Body SAR, Back side, High.ch


Area Scan (10x16x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x7x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.31 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 2.62 W/kg

SAR(1 g) = 1.05 W/kg; SAR(10 g) = 0.528 W/kg



0 dB = 1.59 W/kg = 2.01 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL00EMLWN

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 MHz Body Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$; $\sigma = 1.45 \text{ S/m}$; $\epsilon_r = 52.714$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-28-2019; Ambient Temp: 20.9°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN7420; ConvF(8.03, 8.03, 8.03) @ 1732.4 MHz; Calibrated: 9/18/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1449; Calibrated: 11/12/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CC; Serial: 1596

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1750 Antenna C, Body SAR, Back side, Mid.ch


Area Scan (11x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 28.36 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 2.11 W/kg

SAR(1 g) = 1.03 W/kg; SAR(10 g) = 0.491 W/kg



0 dB = 1.75 W/kg = 2.43 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL01XMLWN

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 MHz Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.552 \text{ S/m}$; $\epsilon_r = 52.482$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-28-2019; Ambient Temp: 20.9°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN7420; ConvF(7.7, 7.7, 7.7) @ 1880 MHz; Calibrated: 9/18/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1449; Calibrated: 11/12/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CC; Serial: 1596

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1900 Antenna C, Body SAR, Back side, Mid.ch


Area Scan (11x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 29.14 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 2.40 W/kg

SAR(1 g) = 1.14 W/kg; SAR(10 g) = 0.516 W/kg



0 dB = 2.00 W/kg = 3.01 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL00UMLWN

Communication System: UID 0, LTE Band 71; Frequency: 680.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 680.5 \text{ MHz}$; $\sigma = 0.933 \text{ S/m}$; $\epsilon_r = 54.418$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-27-2019; Ambient Temp: 22.6°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN3837; ConvF(9.2, 9.2, 9.2) @ 680.5 MHz; Calibrated: 1/28/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn793; Calibrated: 1/15/2019

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Mode: LTE Band 71 Antenna C, Body SAR, Back side, Mid.ch,
20 MHz Bandwidth, QPSK, 50 RB, 50 RB Offset**


Area Scan (10x16x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 29.47 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 2.57 W/kg

SAR(1 g) = 0.984 W/kg; SAR(10 g) = 0.482 W/kg



0 dB = 1.81 W/kg = 2.58 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL00UMLWN

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 MHz Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.924 \text{ S/m}$; $\epsilon_r = 55.491$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-28-2019; Ambient Temp: 22.2°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN3837; ConvF(9.2, 9.2, 9.2) @ 707.5 MHz; Calibrated: 1/28/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn793; Calibrated: 1/15/2019

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1403

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 12 Antenna C, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 25 RB, 25 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 31.06 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 2.46 W/kg

SAR(1 g) = 0.910 W/kg; SAR(10 g) = 0.441 W/kg



0 dB = 1.73 W/kg = 2.38 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL00EMLWN

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.971 \text{ S/m}$; $\epsilon_r = 54.193$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-27-2019; Ambient Temp: 22.6°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN3837; ConvF(9.2, 9.2, 9.2) @ 782 MHz; Calibrated: 1/28/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn793; Calibrated: 1/15/2019

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Mode: LTE Band 13 Antenna C, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (15x19x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 34.02 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 2.86 W/kg

SAR(1 g) = 1.11 W/kg; SAR(10 g) = 0.534 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL00UMLWN

Communication System: UID 0, LTE Band 14; Frequency: 793 MHz; Duty Cycle: 1:1

Medium: 750 MHz Medium parameters used (interpolated):

$f = 793 \text{ MHz}$; $\sigma = 0.956 \text{ S/m}$; $\epsilon_r = 55.312$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-28-2019; Ambient Temp: 22.2°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN3837; ConvF(9.2, 9.2, 9.2) @ 793 MHz; Calibrated: 1/28/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn793; Calibrated: 1/15/2019

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1403

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 14 Antenna C, Body SAR, Back side Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset**


Area Scan (10x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.795 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 2.21 W/kg

SAR(1 g) = 0.883 W/kg; SAR(10 g) = 0.426 W/kg



0 dB = 1.42 W/kg = 1.52 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL00UMLWN

Communication System: UID 0, _LTE Band 26; Frequency: 819 MHz; Duty Cycle: 1:1

Medium: 835 MHz Body Medium parameters used (interpolated):

$f = 819 \text{ MHz}$; $\sigma = 0.93 \text{ S/m}$; $\epsilon_r = 53.19$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-28-2019; Ambient Temp: 23.1°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7427, ConvF(10.18, 10.18, 10.18) @ 819 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1403; Calibrated: 2/13/2019

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 26 (Cell.) Antenna C, Body SAR, Back side, Low.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (15x19x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 36.65 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 2.56 W/kg

SAR(1 g) = 1.16 W/kg; SAR(10 g) = 0.609 W/kg



0 dB = 1.88 W/kg = 2.74 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL01XMLWN

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 MHz Body Medium parameters used (interpolated):

$f = 836.5$ MHz; $\sigma = 1.004$ S/m; $\epsilon_r = 53.676$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-28-2019; Ambient Temp: 21.3°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7416; ConvF(9.4, 9.4, 9.4) @ 836.5 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1402; Calibrated: 7/10/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CA; Serial: 1275

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 5 (Cell.) Antenna D, Body SAR, Back side,
Mid.ch, 10 MHz Bandwidth, QPSK, 25 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 34.22 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 2.89 W/kg

SAR(1 g) = 1.1 W/kg; SAR(10 g) = 0.540 W/kg



0 dB = 2.17 W/kg = 3.36 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL01XMLWN

Communication System: UID 0, _LTE Band 66 (AWS); Frequency: 1770 MHz; Duty Cycle: 1:1

Medium: 1750 MHz Body Medium parameters used (interpolated):

$f = 1770 \text{ MHz}$; $\sigma = 1.477 \text{ S/m}$; $\epsilon_r = 52.66$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-28-2019; Ambient Temp: 20.9°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN7420ConvF(8.03, 8.03, 8.03) @ 1770 MHz; Calibrated: 9/18/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1449; Calibrated: 11/12/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CC; Serial: 1596

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 66 (AWS) Antenna D, Body SAR, Back side, High.ch,
20 MHz Bandwidth, QPSK, 50 RB, 0 RB Offset**


Area Scan (14x21x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.73 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 2.35 W/kg

SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.465 W/kg



0 dB = 1.99 W/kg = 2.99 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL01XMLWN

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 MHz Body Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.569 \text{ S/m}$; $\epsilon_r = 52.454$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-28-2019; Ambient Temp: 20.9°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN7420; ConvF(7.7, 7.7, 7.7) @ 1905 MHz; Calibrated: 9/18/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1449; Calibrated: 11/12/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CC; Serial: 1596

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 25 (PCS) Antenna D, Body SAR, Back side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (12x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 28.37 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 2.20 W/kg

SAR(1 g) = 1.05 W/kg; SAR(10 g) = 0.458 W/kg



0 dB = 1.82 W/kg = 2.60 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL00UMLWN

Communication System: UID 0, LTE Band 30; Frequency: 2310 MHz; Duty Cycle: 1:1

Medium: 2300 Body Medium parameters used:

$f = 2310 \text{ MHz}$; $\sigma = 1.885 \text{ S/m}$; $\epsilon_r = 50.989$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-30-2019; Ambient Temp: 18.3°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3318; ConvF(4.65, 4.65, 4.65) @ 2310 MHz; Calibrated: 11/19/2018

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 8/14/2018

Phantom: Twin-SAM V8.0; Type: QD 000 P41 Ax; Serial: 1936

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Mode: LTE Band 30 Antenna C, Body SAR, Top Edge, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (11x16x1): Measurement grid: dx=5mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.43 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 2.06 W/kg

SAR(1 g) = 1 W/kg; SAR(10 g) = 0.452 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL00UMLWN

Communication System: UID 0, LTE Band 7; Frequency: 2560 MHz; Duty Cycle: 1:1

Medium: 2600 Body Medium parameters used (interpolated):

$f = 2560 \text{ MHz}$; $\sigma = 2.12 \text{ S/m}$; $\epsilon_r = 50.415$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-03-2019; Ambient Temp: 20.9°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN3837; ConvF(7.17, 7.17, 7.17) @ 2560 MHz; Calibrated: 1/28/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn793; Calibrated: 1/15/2019

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1403

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Mode: LTE Band 7 Antenna C, Body SAR, Top Edge, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (10x17x1): Measurement grid: dx=5mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.64 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 2.83 W/kg

SAR(1 g) = 1.17 W/kg; SAR(10 g) = 0.487 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL01XMLWN

Communication System: UID 0, LTE Band 41 (Class 3); Frequency: 2680 MHz; Duty Cycle: 1:1.58

Medium: 2600 MHz Body Medium parameters used (interpolated):

$f = 2680 \text{ MHz}$; $\sigma = 2.243 \text{ S/m}$; $\epsilon_r = 50.819$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-28-2019; Ambient Temp: 21.4°C; Tissue Temp: 20.0°C

Probe: ES3DV3 - SN3318; ConvF(4.32, 4.32, 4.32) @ 2680 MHz; Calibrated: 11/19/2018

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 8/14/2018

Phantom: Twin-SAM V8.0; Type: QD 000 P41 Ax; Serial: 1936

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 41 Antenna C, Body SAR, Top Edge, High. ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x19x1): Measurement grid: dx=5mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.19 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 2.74 W/kg

SAR(1 g) = 1.15 W/kg; SAR(10 g) = 0.476 W/kg



0 dB = 1.57 W/kg = 1.96 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL00TMLWN

Communication System: UID 0, _IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 MHz Body Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 2.013 \text{ S/m}$; $\epsilon_r = 50.739$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-05-2019; Ambient Temp: 19.9°C; Tissue Temp: 20.8°C

Probe: ES3DV3 - SN3318; ConvF(4.49, 4.49, 4.49) @ 2437 MHz; Calibrated: 11/19/2018

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 8/14/2018

Phantom: Twin-SAM V8.0; Type: QD 000 P41 Ax; Serial: 1936

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7470)

**Mode: IEEE 802.11b Antenna A Variant 1, 22 MHz Bandwidth,
Body SAR, Ch 6, 1 Mbps, bottom Edge**


Area Scan (11x18x1): Measurement grid: dx=5mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.34 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 2.68 W/kg

SAR(1 g) = 0.842 W/kg; SAR(10 g) = 0.275 W/kg



0 dB = 1.31 W/kg = 1.17 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL001MLWQ

Communication System: UID 0, _IEEE 802.11ac; Frequency: 5690 MHz; Duty Cycle: 1:1

Medium: 5GHz Body Medium parameters used (interpolated):

$f = 5690 \text{ MHz}$; $\sigma = 6.065 \text{ S/m}$; $\epsilon_r = 47.186$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-28-2019; Ambient Temp: 20.9°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7491; ConvF(4.37, 4.37, 4.37) @ 5690 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 10/18/2018

Phantom: Twin-SAM V8.0_Left; Type: QD 000 P41 AA; Serial: 1935

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: IEEE 802.11ac, Antenna B Variant 2, U-NII-2C, 80 MHz Bandwidth
Body SAR, Ch 138, 29.3 Mbps, Bottom Edge**


Area Scan (11x20x1): Measurement grid: $dx=5\text{mm}$, $dy=10\text{mm}$

Zoom Scan (9x9x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 11.60 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 4.39 W/kg

SAR(1 g) = 0.958 W/kg; SAR(10 g) = 0.324 W/kg



0 dB = 2.49 W/kg = 3.96 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA2200; Type: Tablet Device; Serial: F9FYL000MLWQ

Communication System: UID 0, Bluetooth; Frequency: 2402 MHz; Duty Cycle: 1:1.29

Medium: 2450 MHz Body Medium parameters used (interpolated):

$f = 2402 \text{ MHz}$; $\sigma = 1.971 \text{ S/m}$; $\epsilon_r = 50.728$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-22-2019; Ambient Temp: 22.3°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN7416; ConvF(7.31, 7.31, 7.31) @ 2402 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1402; Calibrated: 7/10/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CA; Serial: 1275

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: Bluetooth Antenna A Variant 2, Body SAR, Ch 0, 1 Mbps, Bottom Edge


Area Scan (11x17x1): Measurement grid: $dx=5\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.26 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 3.11 W/kg

SAR(1 g) = 0.967 W/kg; SAR(10 g) = 0.316 W/kg



0 dB = 1.91 W/kg = 2.81 dBW/kg

APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1097

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 MHz Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.94 \text{ S/m}$; $\epsilon_r = 55.409$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 05-28-2019; Ambient Temp: 22.2°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN3837; ConvF(9.2, 9.2, 9.2) @ 750 MHz; Calibrated: 1/28/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn793; Calibrated: 1/15/2019

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1403

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.90 W/kg

SAR(1 g) = 1.84 W/kg; SAR(10 g) = 1.19 W/kg

Deviation(1 g) = 7.48%



0 dB = 2.44 W/kg = 3.87 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1034

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.959 \text{ S/m}$; $\epsilon_r = 54.263$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-27-2019; Ambient Temp: 22.6°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN3837; ConvF(9.2, 9.2, 9.2) @ 750 MHz; Calibrated: 1/28/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn793; Calibrated: 1/15/2019

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7470)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.77 W/kg

SAR(1 g) = 1.79 W/kg; SAR(10 g) = 1.17 W/kg

Deviation(1 g) = 4.43%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d040

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 MHz Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 1.003 \text{ S/m}$; $\epsilon_r = 53.678$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 05-28-2019; Ambient Temp: 21.3°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7416; ConvF(9.4, 9.4, 9.4) @ 835 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1402; Calibrated: 7/10/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CA; Serial: 1275

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 3.14 W/kg

SAR(1 g) = 2.04 W/kg; SAR(10 g) = 1.33 W/kg

Deviation(1 g) = 6.69%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d040

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 MHz Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.936 \text{ S/m}$; $\epsilon_r = 53.155$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 05-28-2019; Ambient Temp: 23.1°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7427; ConvF(10.18, 10.18, 10.18) @ 835 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1403; Calibrated: 2/13/2019

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.68 W/kg

SAR(1 g) = 1.8 W/kg; SAR(10 g) = 1.19 W/kg

Deviation(1 g) = -5.86%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1104

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 MHz Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.463 \text{ S/m}$; $\epsilon_r = 52.692$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-28-2019; Ambient Temp: 20.9°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN7420; ConvF(8.03, 8.03, 8.03) @ 1750 MHz; Calibrated: 9/18/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1449; Calibrated: 11/12/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CC; Serial: 1596

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.11 W/kg

SAR(1 g) = 3.91 W/kg; SAR(10 g) = 2.07 W/kg

Deviation(1 g) = 6.83%



0 dB = 5.99 W/kg = 7.77 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d181

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 MHz Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.565 \text{ S/m}$; $\epsilon_r = 52.459$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-28-2019; Ambient Temp: 20.9°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN7420; ConvF(7.7, 7.7, 7.7) @ 1900 MHz; Calibrated: 9/18/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1449; Calibrated: 11/12/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CC; Serial: 1596

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.84 W/kg

SAR(1 g) = 3.76 W/kg; SAR(10 g) = 1.95 W/kg

Deviation(1 g) = -4.81%



0 dB = 5.79 W/kg = 7.63 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2300 MHz; Type: D2300V3; Serial: 1038

Communication System: UID 0, CW; Frequency: 2300 MHz; Duty Cycle: 1:1

Medium: 2300 Body Medium parameters used:

$f = 2300 \text{ MHz}$; $\sigma = 1.881 \text{ S/m}$; $\epsilon_r = 51.031$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-30-2019; Ambient Temp: 18.3°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3318; ConvF(4.65, 4.65, 4.65) @ 2300 MHz; Calibrated: 11/19/2018

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 8/14/2018

Phantom: Twin-SAM V8.0; Type: QD 000 P41 Ax; Serial: 1936

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7470)

2300 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 9.73 W/kg

SAR(1 g) = 4.93 W/kg; SAR(10 g) = 2.34 W/kg

Deviation(1 g) = 5.57%



0 dB = 6.46 W/kg = 8.10 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 750

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 MHz Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.027 \text{ S/m}$; $\epsilon_r = 50.586$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-22-2019; Ambient Temp: 22.3°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN7416; ConvF(7.31, 7.31, 7.31) @ 2450 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1402; Calibrated: 7/10/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CA; Serial: 1275

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 11.7 W/kg

SAR(1 g) = 5.44 W/kg; SAR(10 g) = 2.46 W/kg

Deviation(1 g) = 6.25%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 921

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 MHz Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.024 \text{ S/m}$; $\epsilon_r = 50.72$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-05-2019; Ambient Temp: 19.9°C; Tissue Temp: 20.8°C

Probe: ES3DV3 - SN3318; ConvF(4.49, 4.49, 4.49) @ 2450 MHz; Calibrated: 11/19/2018

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 8/14/2018

Phantom: Twin-SAM V8.0; Type: QD 000 P41 Ax; Serial: 1936

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 11.4 W/kg

SAR(1 g) = 5.3 W/kg; SAR(10 g) = 2.42 W/kg

Deviation(1 g) = 4.33%



0 dB = 6.97 W/kg = 8.43 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1069

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2600 MHz Body Medium parameters used:

$f = 2600 \text{ MHz}$; $\sigma = 2.166 \text{ S/m}$; $\epsilon_r = 50.955$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-28-2019; Ambient Temp: 21.4°C; Tissue Temp: 20.0°C

Probe: ES3DV3 - SN3318; ConvF(4.32, 4.32, 4.32) @ 2600 MHz; Calibrated: 11/19/2018

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 8/14/2018

Phantom: Twin-SAM V8.0; Type: QD 000 P41 Ax; Serial: 1936

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 13.0 W/kg

SAR(1 g) = 5.81 W/kg; SAR(10 g) = 2.56 W/kg

Deviation(1 g) = 5.06%



0 dB = 7.67 W/kg = 8.85 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1069

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2600 Body Medium parameters used:

$f = 2600 \text{ MHz}$; $\sigma = 2.161 \text{ S/m}$; $\epsilon_r = 50.329$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-03-2019; Ambient Temp: 20.9°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN3837; ConvF(7.17, 7.17, 7.17) @ 2600 MHz; Calibrated: 1/28/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn793; Calibrated: 1/15/2019

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1403

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7470)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 12.3 W/kg

SAR(1 g) = 5.33 W/kg; SAR(10 g) = 2.3 W/kg

Deviation(1 g) = -3.62%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1163

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5GHz Body Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 5.466 \text{ S/m}$; $\epsilon_r = 47.907$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-28-2019; Ambient Temp: 20.9°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7491; ConvF(4.82, 4.82, 4.82) @ 5250 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 10/18/2018

Phantom: Twin-SAM V8.0_Left; Type: QD 000 P41 AA; Serial: 1935

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.1 W/kg

SAR(1 g) = 3.61 W/kg; SAR(10 g) = 0.993 W/kg

Deviation(1 g) = -7.08%



0 dB = 8.79 W/kg = 9.44 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1163

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.939 \text{ S/m}$; $\epsilon_r = 47.332$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-28-2019; Ambient Temp: 20.9°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7491; ConvF(4.19, 4.19, 4.19) @ 5600 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 10/18/2018

Phantom: Twin-SAM V8.0_Left; Type: QD 000 P41 AA; Serial: 1935

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.1 W/kg

SAR(1 g) = 4 W/kg; SAR(10 g) = 1.1 W/kg

Deviation(1 g) = -0.12%



0 dB = 9.84 W/kg = 9.93 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1163

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5GHz Body Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 6.135 \text{ S/m}$; $\epsilon_r = 47.093$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-28-2019; Ambient Temp: 20.9°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7491; ConvF(4.37, 4.37, 4.37) @ 5750 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 10/18/2018

Phantom: Twin-SAM V8.0_Left; Type: QD 000 P41 AA; Serial: 1935

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.6 W/kg

SAR(1 g) = 3.67 W/kg; SAR(10 g) = 1.01 W/kg

Deviation(1 g) = -5.66%



0 dB = 9.23 W/kg = 9.65 dBW/kg

APPENDIX C: PROBE CALIBRATION



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client: **PG Test**

Certificate No: **D750V3-1097_Sep17**

CALIBRATION CERTIFICATE

Object: **D750V3 - SN:1097**

Calibration procedure(s): **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

SC ✓
 10/03/2017

Calibration date: **September 08, 2017**

SC ✓
 9/8/2018

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18
Reference Probe EX3DV4	SN: 7349	31-May-17 (No. EX3-7349_May17)	May-18
DAE4	SN: 601	28-Mar-17 (No. DAE4-601_Mar17)	Mar-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-16)	In house check: Oct-17

Calibrated by: **Claudio Leubler** Name: **Claudio Leubler** Function: **Laboratory Technician**

Signature:

Approved by: **Katja Pokojic** Name: **Katja Pokojic** Technical Manager:

Signature:

Issued: September 8, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	750 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.9	0.89 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	41.2 $\pm$ 6 %	0.90 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.08 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	8.22 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.36 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.39 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.5	0.96 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	55.5 $\pm$ 6 %	0.96 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.14 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	8.56 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.42 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	5.68 W/kg $\pm$ 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	54.4 Ω - 0.6 j Ω
Return Loss	- 27.5 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	50.0 Ω - 3.6 j Ω
Return Loss	- 28.8 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.034 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	July 05, 2013

DASY5 Validation Report for Head TSL

Date: 08.09.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1097

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.9 \text{ S/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.49, 10.49, 10.49); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 4.9 (front); Type: QD 00L P49 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Head Tissue/Pin=250 mW, $d=15\text{mm}$ /Zoom Scan (7x7x7)/Cube 0:


Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 58.59 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.19 W/kg

SAR(1 g) = 2.08 W/kg; SAR(10 g) = 1.36 W/kg

Maximum value of SAR (measured) = 2.80 W/kg



0 dB = 2.80 W/kg = 4.47 dBW/kg

Impedance Measurement Plot for Head TSL

8 Sep 2017 13:09:24
 CH1 S11 1 U FS 1: 54.383 Ω -552.73 m Ω 383.92 pF 750.000 000 MHz

*

De1

CA

Avg
16

H1d

CH2 S11 LOG 5 dB/REF -20 dB 1:-27.463 dB 750.000 000 MHz

CA

Avg
16

H1d

START 550.000 000 MHz

STOP 950.000 000 MHz

DASY5 Validation Report for Body TSL

Date: 08.09.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1097

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used: $f = 750$ MHz; $\sigma = 0.96$ S/m; $\epsilon_r = 55.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.35, 10.35, 10.35); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 4.9 (Back); Type: QD 00R P49 AA; Serial: 1005
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 56.96 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 3.16 W/kg

SAR(1 g) = 2.14 W/kg; SAR(10 g) = 1.42 W/kg

Maximum value of SAR (measured) = 2.81 W/kg



0 dB = 2.81 W/kg = 4.49 dBW/kg

Impedance Measurement Plot for Body TSL

8 Sep 2017 13:08:43
 CH1 S11 1 U FS 1: 49.951 Ω -3.6172 Ω 58.666 pF 750.000 000 MHz

*
 De1
 CA

Avg
 15

H1d

CH2 S11 LOG 5 dB/REF -20 dB 1: -28.833 dB 750.000 000 MHz

CA

Avg
 16

H1d

START 550.000 000 MHz

STOP 950.000 000 MHz

Certification of Calibration

Object: D750V3 – SN: 1097

Calibration procedure(s): Procedure for Calibration Extension for SAR Dipoles.



Extended Calibration date: September 08, 2018

Description: SAR Validation Dipole at 750 MHz.

Calibration Equipment used:

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8753ES	S-Parameter Network Analyzer	9/14/2017	Annual	9/14/2018	US39170118
Agilent	N5182A	MXG Vector Signal Generator	3/19/2018	Annual	3/19/2019	US46240505
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	343972
Anritsu	ML2496A	Power Meter	10/9/2017	Annual	10/9/2018	1138001
Anritsu	MA2411B	Pulse Power Sensor	11/15/2017	Annual	11/15/2018	1339007
Anritsu	MA2411B	Pulse Power Sensor	11/22/2017	Annual	11/22/2018	1339008
Control Company	4040	Temperature / Humidity Monitor	2/28/2018	Biennial	2/28/2020	150761911
Control Company	4352	Ultra Long Stem Thermometer	2/14/2017	Biennial	2/14/2019	170112507
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
Keysight Technologies	85033E	Standard Mechanical Calibration Kit (DC to 9GHz, 3.5mm)	6/4/2018	Annual	6/4/2019	MY53401181
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE5011-1	Torque Wrench	7/19/2017	Biennial	7/19/2019	N/A
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/15/2018	Annual	5/15/2019	1070
SPEAG	ES3DV3	SAR Probe	9/18/2017	Annual	9/18/2018	3287
SPEAG	DAE4	Data Acquisition Electronics	1/26/2018	Annual	1/26/2019	1533
SPEAG	EX3DV4	SAR Probe	7/20/2018	Annual	7/20/2019	7416
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/18/2018	Annual	1/18/2019	793

Measurement Uncertainty = $\pm 23\%$ (k=2)

	Name	Function	Signature
Calibrated By:	Sangmin Cha	Team Lead Engineer	
Approved By:	Kaitlin O'Keefe	Senior Technical Manager	

DIPOLE CALIBRATION EXTENSION



Per KDB 865664 D01, calibration intervals of up to three years may be considered for reference dipoles when it is demonstrated that the SAR target, impedance and return loss of a dipole have remained stable according to the following requirements:

1. The measured SAR does not deviate more than 10% from the target on the calibration certificate.
2. The return-loss does not deviate more than 20% from the previous measurement and meets the required 20dB minimum return-loss requirement.
3. The measurement of real or imaginary parts of impedance does not deviate more than 5Ω from the previous measurement.



The following dipole was checked to pass the above 3 requirements to have 2-year calibration period from the calibration date:

Calibration Date	Extension Date	Certificate Electrical Delay (ns)	Certificate SAR Target Head (1g) W/kg @ 23.0 dBm	Measured Head SAR (1g) W/kg @ 23.0 dBm	Deviation 1g (%)	Certificate SAR Target Body (10g) W/kg @ 23.0 dBm	Measured Body SAR (10g) W/kg @ 23.0 dBm	Deviation 10g (%)	Certificate Impedance Head (Ohm) Real	Measured Impedance Head (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Head (Ohm) Imaginary	Measured Impedance Head (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Head (dB)	Measured Return Loss Head (dB)	Deviation (%)	PASS/FAIL
9/8/2017	9/8/2018	1.034	1.644	1.7	3.41%	1.078	1.12	3.90%	54.4	54.1	0.3	-0.6	-0.6	0	-27.5	-25.5	7.30%	PASS
Calibration Date	Extension Date	Certificate Electrical Delay (ns)	Certificate SAR Target Body (1g) W/kg @ 23.0 dBm	Measured Body SAR (1g) W/kg @ 23.0 dBm	Deviation 1g (%)	Certificate SAR Target Body (10g) W/kg @ 23.0 dBm	Measured Body SAR (10g) W/kg @ 23.0 dBm	Deviation 10g (%)	Certificate Impedance Body (Ohm) Real	Measured Impedance Body (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Body (Ohm) Imaginary	Measured Impedance Body (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Body (dB)	Measured Return Loss Body (dB)	Deviation (%)	PASS/FAIL
9/8/2017	9/8/2018	1.034	1.712	1.78	3.97%	1.136	1.17	2.99%	50	49.6	0.4	-3.6	-3.1	0.5	-28.8	-30.3	-5.20%	PASS

Impedance & Return-Loss Measurement Plot for Head TSL



Impedance & Return-Loss Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D750V3-1034_May18**

CALIBRATION CERTIFICATE

Object **D750V3 - SN:1034**

Calibration procedure(s) **QA CAL-05.v10**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **May 18, 2018**

SC ✓
 5/31/2018
 BN ✓
 05/01/2019

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-18 (No. 217-02682)	Apr-19
Type-N mismatch combination	SN: 5047.2 / 06327	04-Apr-18 (No. 217-02683)	Apr-19
Reference Probe EX3DV4	SN: 7349	30-Dec-17 (No. EX3-7349_Dec17)	Dec-18
DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

Calibrated by:	Name Manu Seitz	Function Laboratory Technician	Signature
Approved by:	Katja Pokovic	Technical Manager	

Issued: May 22, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.1
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	750 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.9	0.89 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	41.0 $\pm$ 6 %	0.89 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.09 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	8.32 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.36 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.42 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.5	0.96 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	54.7 $\pm$ 6 %	0.96 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.15 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	8.57 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.42 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	5.67 W/kg $\pm$ 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	55.3 Ω + 0.0 j Ω
Return Loss	- 26.0 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	50.0 Ω - 3.2 j Ω
Return Loss	- 29.8 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.034 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	July 06, 2011

DASY5 Validation Report for Head TSL

Date: 17.05.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1034

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used: $f = 750$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 41$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.22, 10.22, 10.22) @ 750 MHz; Calibrated: 30.12.2017
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 4.9 (front); Type: QD 00L P49 AA; Serial: 1001
- DASY52 52.10.1(1476); SEMCAD X 14.6.11(7439)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:



Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 59.66 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 3.18 W/kg


SAR(1 g) = 2.09 W/kg; SAR(10 g) = 1.36 W/kg

Maximum value of SAR (measured) = 2.82 W/kg



0 dB = 2.82 W/kg = 4.50 dBW/kg

Impedance Measurement Plot for Head TSL



DASY5 Validation Report for Body TSL

Date: 18.05.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1034

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used: $f = 750$ MHz; $\sigma = 0.96$ S/m; $\epsilon_r = 54.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.19, 10.19, 10.19) @ 750 MHz; Calibrated: 30.12.2017
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 4.9 (Back); Type: QD 00R P49 AA; Serial: 1005
- DASY52 52.10.1(1476); SEMCAD X 14.6.11(7439)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.60 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.16 W/kg

SAR(1 g) = 2.15 W/kg; SAR(10 g) = 1.42 W/kg

Maximum value of SAR (measured) = 2.83 W/kg




0 dB = 2.83 W/kg = 4.52 dBW/kg

Impedance Measurement Plot for Body TSL

18 May 2018 09:54:01
CH1 S11 1 U FS 1: 49.951 $\angle$ -3.2324 $\angle$ 65.649 pF 750.000 000 MHz

*
De1
Cor




Avg
16
H1d

CH2 S11 LOG 5 dB/ REF -20 dB 1: -29.809 dB 750.000 000 MHz

Cor

Avg
16

H1d



Certification of Calibration

Object D750V3 – SN: 1034

Calibration procedure(s) Procedure for Calibration Extension for SAR Dipoles.

Extended Calibration date: May 16, 2019

Description: SAR Validation Dipole at 750 MHz.

Calibration Equipment used:

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8753ES	S-Parameter Network Analyzer	10/2/2018	Annual	10/2/2019	US39170118
Agilent	N5182A	MXG Vector Signal Generator	6/15/2018	Annual	6/15/2019	MY47420837
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	343972
Anritsu	ML2495A	Power Meter	10/21/2018	Annual	10/21/2019	941001
Anritsu	MA2411B	Pulse Power Sensor	10/30/2018	Annual	10/30/2019	1207470
Anritsu	MA2411B	Pulse Power Sensor	11/20/2018	Annual	11/20/2019	1339007
Control Company	4040	Temperature / Humidity Monitor	2/28/2018	Biennial	2/28/2020	150761911
Control Company	4352	Ultra Long Stem Thermometer	2/28/2018	Biennial	2/28/2020	170330160
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
Keysight Technologies	85033E	Standard Mechanical Calibration Kit (DC to 9GHz, 3.5mm)	6/4/2018	Annual	6/4/2019	MY53401181
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE5011-1	Torque Wrench	7/19/2017	Biennial	7/19/2019	N/A
SPEAG	DAKS-3.5	Portable DAK	9/11/2018	Annual	9/11/2019	1045
SPEAG	EX3DV4	SAR Probe	7/20/2018	Annual	7/20/2019	7416
SPEAG	DAE4	Dasy Data Acquisition Electronics	7/10/2018	Annual	7/10/2019	1402

Measurement Uncertainty = $\pm 23\%$ (k=2)

	Name	Function	Signature
Calibrated By:	Parker Jones	Team Lead Engineer	<i>Parker Jones</i>
Approved By:	Kaitlin O'Keefe	Senior Technical Manager	<i>KOK</i>

DIPOLE CALIBRATION EXTENSION



Per KDB 865664 D01, calibration intervals of up to three years may be considered for reference dipoles when it is demonstrated that the SAR target, impedance and return loss of a dipole have remained stable according to the following requirements:

1. The measured SAR does not deviate more than 10% from the target on the calibration certificate.
2. The return-loss does not deviate more than 20% from the previous measurement and meets the required 20dB minimum return-loss requirement.
3. The measurement of real or imaginary parts of impedance does not deviate more than 5Ω from the previous measurement.


The following dipole was checked to pass the above 3 requirements to have 2-year calibration period from the calibration date:

Calibration Date	Extension Date	Certificate Electrical Delay (ns)	Certificate SAR Target Head (1g) W/kg @ 23.0 dBm	Measured Head SAR (1g) W/kg @ 23.0 dBm	Deviation 1g (%)	Certificate SAR Target Body (10g) W/kg @ 23.0 dBm	Measured Body SAR (10g) W/kg @ 23.0 dBm	Deviation 10g (%)	Certificate Impedance Head (Ohm) Real	Measured Impedance Head (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Head (Ohm) Imaginary	Measured Impedance Head (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Head (dB)	Measured Return Loss Head (dB)	Deviation (%)	PASS/FAIL
5/18/2018	5/16/2019	1.034	1.664	1.65	-0.84%	1.064	1.08	-0.37%	55.3	54.4	0.9	0	-2.2	2.2	-26	-26.5	-1.90%	PASS
Calibration Date	Extension Date	Certificate Electrical Delay (ns)	Certificate SAR Target Body (1g) W/kg @ 23.0 dBm	Measured Body SAR (1g) W/kg @ 23.0 dBm	Deviation 1g (%)	Certificate SAR Target Body (10g) W/kg @ 23.0 dBm	Measured Body SAR (10g) W/kg @ 23.0 dBm	Deviation 10g (%)	Certificate Impedance Body (Ohm) Real	Measured Impedance Body (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Body (Ohm) Imaginary	Measured Impedance Body (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Body (dB)	Measured Return Loss Body (dB)	Deviation (%)	PASS/FAIL
5/18/2018	5/16/2019	1.034	1.714	1.81	5.60%	1.134	1.19	4.94%	50	51.7	1.7	-3.2	-1	2.2	-29.8	-31	-3.90%	PASS

Impedance & Return-Loss Measurement Plot for Head TSL



Impedance & Return-Loss Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D835V2-4d040_Jun17**

CALIBRATION CERTIFICATE

Object **D835V2 - SN:4d040**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **June 13, 2017**

BNV
8/31/2017
SC
6/1/2018

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18
Reference Probe EX3DV4	SN: 7349	31-May-17 (No. EX3-7349_May17)	May-18
DAE4	SN: 601	28-Mar-17 (No. DAE4-601_Mar17)	Mar-18

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-16)	In house check: Oct-17

Calibrated by: **Johannes Kurikka** Name: **Johannes Kurikka** Function: **Laboratory Technician**

Approved by: **Katja Pokovic** Name: **Katja Pokovic** Technical Manager

Signature

Johannes Kurikka

Katja Pokovic

Issued: June 15, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- e) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	41.0 $\pm$ 6 %	0.93 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.43 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	9.46 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.56 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	6.11 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	54.7 $\pm$ 6 %	1.00 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.45 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	9.56 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.60 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	6.28 W/kg $\pm$ 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	49.8 Ω - 4.4 j Ω
Return Loss	- 27.0 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	46.4 Ω - 6.5 j Ω
Return Loss	- 22.3 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.391 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	September 20, 2005

DASY5 Validation Report for Head TSL

Date: 13.06.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:4d040

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.93 \text{ S/m}$; $\epsilon_r = 41$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.07, 10.07, 10.07); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 4.9 (front); Type: QD 00L P49 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:



Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 62.24 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 3.79 W/kg

SAR(1 g) = 2.43 W/kg; SAR(10 g) = 1.56 W/kg

Maximum value of SAR (measured) = 3.32 W/kg




0 dB = 3.32 W/kg = 5.21 dBW/kg

Impedance Measurement Plot for Head TSL

13 Jun 2017 12:56:55
CH1 S11 1 U FS 1: 49.830 Ω -4.4453 Ω 42.878 pF 835.000 000 MHz

*
 De1
 CA



Av9
 16


H1d

CH2 S11 LOG 5 dB/REF -20 dB 1:-27.030 dB 835.000 000 MHz

CA

Av9
 16

H1d



DASY5 Validation Report for Body TSL

Date: 12.06.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:4d040

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used: $f = 835$ MHz; $\sigma = 1$ S/m; $\epsilon_r = 54.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.2, 10.2, 10.2); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 4.9 (Back); Type: QD 00R P49 AA; Serial: 1005
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 59.95 V/m; Power Drift = -0.01 dB


Peak SAR (extrapolated) = 3.72 W/kg

SAR(1 g) = 2.45 W/kg; SAR(10 g) = 1.6 W/kg

Maximum value of SAR (measured) = 3.26 W/kg



Impedance Measurement Plot for Body TSL



Certification of Calibration

Object D835V2 – SN: 4d040

Calibration procedure(s) Procedure for Calibration Extension for SAR Dipoles.



Extended Calibration date: June 01, 2018

Description: SAR Validation Dipole at 835 MHz.

Calibration Equipment used:

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8753ES	S-Parameter Network Analyzer	9/14/2017	Annual	9/14/2018	US39170118
Agilent	N5182A	MXG Vector Signal Generator	3/19/2018	Annual	3/19/2019	US46240505
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	343972
Anritsu	ML2496A	Power Meter	10/9/2017	Annual	10/9/2018	1138001
Anritsu	MA2411B	Pulse Power Sensor	11/15/2017	Annual	11/15/2018	1339007
Anritsu	MA2411B	Pulse Power Sensor	11/22/2017	Annual	11/22/2018	1339008
Control Company	4040	Temperature / Humidity Monitor	2/28/2018	Biennial	2/28/2020	150761911
Control Company	4352	Ultra Long Stem Thermometer	2/14/2017	Biennial	2/14/2019	170112507
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
Keysight Technologies	85033E	Standard Mechanical Calibration Kit (DC to 9GHz, 3.5mm)	6/1/2017	Annual	6/1/2018	MY53401181
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE5011-1	Torque Wrench	7/19/2017	Biennial	7/19/2019	N/A
SPEAG	DAKS-3.5	Portable DAK	9/5/2017	Annual	9/5/2018	1045
SPEAG	ES3DV3	SAR Probe	3/13/2018	Annual	3/13/2019	3131
SPEAG	EX3DV4	SAR Probe	1/26/2018	Annual	1/26/2019	7490
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/7/2018	Annual	3/7/2019	604
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/26/2018	Annual	1/26/2019	1532

Measurement Uncertainty = $\pm 23\%$ (k=2)

	Name	Function	Signature
Calibrated By:	Sangmin Cha	Biomedical Engineer II	
Approved By:	Kaitlin O'Keefe	Senior Technical Manager	

DIPOLE CALIBRATION EXTENSION

Per KDB 865664 D01, calibration intervals of up to three years may be considered for reference dipoles when it is demonstrated that the SAR target, impedance and return loss of a dipole have remained stable according to the following requirements:



1. The measured SAR does not deviate more than 10% from the target on the calibration certificate.
2. The return-loss does not deviate more than 20% from the previous measurement and meets the required 20dB minimum return-loss requirement.
3. The measurement of real or imaginary parts of impedance does not deviate more than 5Ω from the previous measurement.

The following dipole was checked to pass the above 3 requirements to have 2-year calibration period from the calibration date:



Calibration Date	Extension Date	Certificate Electrical Delay (ns)	Certificate SAR Target Head (1g) W/kg @ 23.0 dBm	Measured Head SAR (1g) W/kg @ 23.0 dBm	Deviation 1g (%)	Certificate SAR Target Head (10g) W/kg @ 23.0 dBm	Measured Head SAR (10g) W/kg @ 23.0 dBm	Deviation 10g (%)	Certificate Impedance Head (Ohm) Real	Measured Impedance Head (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Head (Ohm) Imaginary	Measured Impedance Head (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Head (dB)	Measured Return Loss Head (dB)	Deviation (%)	PASS/FAIL
6/13/2017	6/1/2018	1.391	1.892	1.99	5.18%	1.222	1.3	6.38%	49.8	49.1	0.7	-4.4	-3.3	1.1	-27	-29.1	-7.80%	PASS

Calibration Date	Extension Date	Certificate Electrical Delay (ns)	Certificate SAR Target Body (1g) W/kg @ 23.0 dBm	Measured Body SAR (1g) W/kg @ 23.0 dBm	Deviation 1g (%)	Certificate SAR Target Body (10g) W/kg @ 23.0 dBm	Measured Body SAR (10g) W/kg @ 23.0 dBm	Deviation 10g (%)	Certificate Impedance Body (Ohm) Real	Measured Impedance Body (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Body (Ohm) Imaginary	Measured Impedance Body (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Body (dB)	Measured Return Loss Body (dB)	Deviation (%)	PASS/FAIL
6/13/2017	6/1/2018	1.391	1.912	1.9	-0.63%	1.256	1.26	0.32%	46.4	45	1.4	-6.5	-5.8	0.7	-22.3	-22.5	-0.90%	PASS

Impedance & Return-Loss Measurement Plot for Head TSL



Impedance & Return-Loss Measurement Plot for Body TSL



Calibration Laboratory of
Schmid & Partner
Engineering AG
 Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D1750V2-1104_Sep17**

CALIBRATION CERTIFICATE

Object **D1750V2 - SN:1104**

Calibration procedure(s) **QA CAL-05.v9**
 Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **September 07, 2017**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02528)	Apr-18
Reference Probe EX3DV4	SN: 7349	31-May-17 (No. EX3-7349_May17)	May-18
DAE4	SN: 601	28-Mar-17 (No. DAE4-601_Mar17)	Mar-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-16)	In house check: Oct-17

Calibrated by: **Michael Weber** Name: **Michael Weber** Function: **Laboratory Technician**

Approved by: **Katja Pokovic** Technical Manager

Signature

[Signature]

[Signature]

Issued: September 7, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1750 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.1	1.37 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	39.1 $\pm$ 6 %	1.36 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	9.11 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	36.4 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	4.81 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	19.2 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.4	1.49 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	53.8 $\pm$ 6 %	1.46 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	9.03 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	36.6 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	4.85 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	19.6 W/kg $\pm$ 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	50.8 Ω - 0.2 j Ω
Return Loss	- 41.5 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	46.5 Ω - 0.7 j Ω
Return Loss	- 28.7 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.217 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	May 16, 2013

DASY5 Validation Report for Head TSL

Date: 07.09.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN:1104

Communication System: UID 0 - CW; Frequency: 1750 MHz

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.36$ S/m; $\epsilon_r = 39.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.73, 8.73, 8.73); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:



Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 104.9 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 17.0 W/kg

SAR(1 g) = 9.11 W/kg; SAR(10 g) = 4.81 W/kg

Maximum value of SAR (measured) = 13.9 W/kg




0 dB = 13.9 W/kg = 11.43 dBW/kg

Impedance Measurement Plot for Head TSL

7 Sep 2017 12:19:31
 CH1 S11 1 U FS 1: 50.834 Ω -150.39 m Ω 604.73 pF 1 750.000 000 MHz

*
 Del
 CA



Avg
 16


H1d

CH2 S11 LOG 5 dB/REF -20 dB 1:-41.481 dB 1 750.000 000 MHz

CA

Avg
 16

H1d



DASY5 Validation Report for Body TSL

Date: 07.09.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN:1104

Communication System: UID 0 - CW; Frequency: 1750 MHz

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.46$ S/m; $\epsilon_r = 53.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.46, 8.46, 8.46); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 99.30 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 15.6 W/kg

SAR(1 g) = 9.03 W/kg; SAR(10 g) = 4.85 W/kg

Maximum value of SAR (measured) = 12.9 W/kg




0 dB = 12.9 W/kg = 11.11 dBW/kg

Impedance Measurement Plot for Body TSL


7 Sep 2017 12:18:38
CH1 S11 1 U FS 1: 46.527 Ω -689.45 m Ω 131.91 pF 1 750.000 000 MHz

*
Del
CA
Avg
16
H1d



CH2 S11 LOG 5 dB/REF -20 dB 1: -28.710 dB 1 750.000 000 MHz

CA
Avg
16
H1d



Certification of Calibration

Object D1750V2 – SN: 1104

Calibration procedure(s) Procedure for Calibration Extension for SAR Dipoles.



Extended Calibration date: September 07, 2018

Description: SAR Validation Dipole at 1750 MHz.

Calibration Equipment used:

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8753ES	S-Parameter Network Analyzer	9/14/2017	Annual	9/14/2018	US39170118
Agilent	N5182A	MXG Vector Signal Generator	3/19/2018	Annual	3/19/2019	US46240505
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	343972
Anritsu	ML2496A	Power Meter	10/9/2017	Annual	10/9/2018	1138001
Anritsu	MA2411B	Pulse Power Sensor	11/15/2017	Annual	11/15/2018	1339007
Anritsu	MA2411B	Pulse Power Sensor	11/22/2017	Annual	11/22/2018	1339008
Control Company	4040	Temperature / Humidity Monitor	2/28/2018	Biennial	2/28/2020	150761911
Control Company	4352	Ultra Long Stem Thermometer	2/14/2017	Biennial	2/14/2019	170112507
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
Keysight Technologies	85033E	Standard Mechanical Calibration Kit (DC to 9GHz, 3.5mm)	6/4/2018	Annual	6/4/2019	MY53401181
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE5011-1	Torque Wrench	7/19/2017	Biennial	7/19/2019	N/A
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/15/2018	Annual	5/15/2019	1070
SPEAG	ES3DV3	SAR Probe	9/18/2017	Annual	9/18/2018	3287
SPEAG	DAE4	Data Acquisition Electronics	1/26/2018	Annual	1/26/2019	1533

Measurement Uncertainty = $\pm 23\%$ (k=2)

	Name	Function	Signature
Calibrated By:	Sangmin Cha	Team Lead Engineer	
Approved By:	Kaitlin O'Keefe	Senior Technical Manager	

DIPOLE CALIBRATION EXTENSION



Per KDB 865664 D01, calibration intervals of up to three years may be considered for reference dipoles when it is demonstrated that the SAR target, impedance and return loss of a dipole have remained stable according to the following requirements:

1. The measured SAR does not deviate more than 10% from the target on the calibration certificate.
2. The return-loss does not deviate more than 20% from the previous measurement and meets the required 20dB minimum return-loss requirement.
3. The measurement of real or imaginary parts of impedance does not deviate more than 5Ω from the previous measurement.



The following dipole was checked to pass the above 3 requirements to have 2-year calibration period from the calibration date:

Calibration Date	Extension Date	Certificate Electrical Delay (ns)	Certificate SAR Target Head (1g) W/kg @ 20.0 dBm	Measured Head SAR (1g) W/kg @ 20.0 dBm	Deviation 1g (%)	Certificate SAR Target Body (10g) W/kg @ 20.0 dBm	Measured Body SAR (10g) W/kg @ 20.0 dBm	Deviation 10g (%)	Certificate Impedance Head (Ohm) Real	Measured Impedance Head (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Head (Ohm) Imaginary	Measured Impedance Head (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Head (dB)	Measured Return Loss Head (dB)	Deviation (%)	PASS/FAIL
9/7/2017	9/7/2018	1.217	3.64	3.62	-0.55%	1.92	1.94	1.04%	50.8	49.8	1	-0.2	-0.3	0.1	-41.5	-35.9	13.50%	PASS
Calibration Date	Extension Date	Certificate Electrical Delay (ns)	Certificate SAR Target Body (1g) W/kg @ 20.0 dBm	Measured Body SAR (1g) W/kg @ 20.0 dBm	Deviation 1g (%)	Certificate SAR Target Body (10g) W/kg @ 20.0 dBm	Measured Body SAR (10g) W/kg @ 20.0 dBm	Deviation 10g (%)	Certificate Impedance Body (Ohm) Real	Measured Impedance Body (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Body (Ohm) Imaginary	Measured Impedance Body (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Body (dB)	Measured Return Loss Body (dB)	Deviation (%)	PASS/FAIL
9/7/2017	9/7/2018	1.217	3.66	3.84	4.92%	1.96	2.07	5.61%	46.527	45.4	1.1	-0.69	-1.6	0.9	-28.7	-25.8	10.10%	PASS

Impedance & Return-Loss Measurement Plot for Head TSL



Impedance & Return-Loss Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D1900V2-5d181_Sep17**

CALIBRATION CERTIFICATE

Object **D1900V2 - SN:5d181**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **September 07, 2017**

SC ✓
10/03/2017
SC ✓
9/7/2018

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18
Reference Probe EX3DV4	SN: 7349	31-May-17 (No. EX3-7349_May17)	May-18
DAE4	SN: 601	28-Mar-17 (No. DAE4-601_Mar17)	Mar-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-18)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-16)	In house check: Oct-17

Calibrated by: **Jeton Kastrati** Name
Laboratory Technician Function

Approved by: **Katja Pokovic** Name
Technical Manager Function

Signature

Issued: September 7, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- e) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1900 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	39.0 $\pm$ 6 %	1.38 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	9.85 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	39.5 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	5.15 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	20.6 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.3	1.52 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	54.3 $\pm$ 6 %	1.47 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	9.65 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	39.5 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.14 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	20.9 W/kg $\pm$ 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	$53.7 \Omega + 4.6 j\Omega$
Return Loss	- 24.9 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	$49.2 \Omega + 5.6 j\Omega$
Return Loss	- 24.8 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.200 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	August 23, 2013

DASY5 Validation Report for Head TSL

Date: 07.09.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:5d181

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.38$ S/m; $\epsilon_r = 39$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.43, 8.43, 8.43); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 106.8 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 18.5 W/kg

SAR(1 g) = 9.85 W/kg; SAR(10 g) = 5.15 W/kg

Maximum value of SAR (measured) = 14.8 W/kg



0 dB = 14.8 W/kg = 11.70 dBW/kg

Impedance Measurement Plot for Head TSL

7 Sep 2017 09:10:32
 CH1 S11 1 U FS 3: 53.668 Ω 4.5957 Ω 384.96 μH 1 900.000 000 MHz


*

De1

CA

Avg
16

H1d




CH2 S11 LOG 5 dB/REF -20 dB 3:-24.931 dB 1 900.000 000 MHz

CA

Avg
16

H1d



DASY5 Validation Report for Body TSL

Date: 07.09.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:5d181

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.47$ S/m; $\epsilon_r = 54.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.2, 8.2, 8.2); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:



Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 101.4 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 17.0 W/kg

SAR(1 g) = 9.65 W/kg; SAR(10 g) = 5.14 W/kg

Maximum value of SAR (measured) = 13.8 W/kg




0 dB = 13.8 W/kg = 11.40 dBW/kg

Impedance Measurement Plot for Body TSL

7 Sep 2017 09:09:41
CH1 S11 1 U FS 3: 49.201 Ω 5.6484 Ω 473.15 pF 1 900.000 000 MHz

*
De1
CA




Avg
16
H1d

CH2 S11 LOG 5 dB/REF -20 dB 3: -24.816 dB 1 900.000 000 MHz

CA

Avg
16
H1d



START 1 700.000 000 MHz

STOP 2 100.000 000 MHz

Certification of Calibration

Object D1900V2 – SN: 5d181

Calibration procedure(s) Procedure for Calibration Extension for SAR Dipoles.



Extended Calibration date: September 07, 2018

Description: SAR Validation Dipole at 1900 MHz.

Calibration Equipment used:

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8753ES	S-Parameter Network Analyzer	9/14/2017	Annual	9/14/2018	US39170118
Agilent	N5182A	MXG Vector Signal Generator	3/19/2018	Annual	3/19/2019	US46240505
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	343972
Anritsu	ML2496A	Power Meter	10/9/2017	Annual	10/9/2018	1138001
Anritsu	MA2411B	Pulse Power Sensor	11/15/2017	Annual	11/15/2018	1339007
Anritsu	MA2411B	Pulse Power Sensor	11/22/2017	Annual	11/22/2018	1339008
Control Company	4040	Temperature / Humidity Monitor	2/28/2018	Biennial	2/28/2020	150761911
Control Company	4352	Ultra Long Stem Thermometer	2/14/2017	Biennial	2/14/2019	170112507
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
Keysight Technologies	85033E	Standard Mechanical Calibration Kit (DC to 9GHz, 3.5mm)	6/4/2018	Annual	6/4/2019	MY53401181
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE5011-1	Torque Wrench	7/19/2017	Biennial	7/19/2019	N/A
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/15/2018	Annual	5/15/2019	1070
SPEAG	ES3DV3	SAR Probe	9/18/2017	Annual	9/18/2018	3287
SPEAG	DAE4	Data Acquisition Electronics	1/26/2018	Annual	1/26/2019	1533
SPEAG	ES3DV3	SAR Probe	3/13/2018	Annual	3/13/2019	3131
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/7/2018	Annual	3/7/2019	604

Measurement Uncertainty = $\pm 23\%$ (k=2)

	Name	Function	Signature
Calibrated By:	Sangmin Cha	Team Lead Engineer	
Approved By:	Kaitlin O'Keefe	Senior Technical Manager	

DIPOLE CALIBRATION EXTENSION



Per KDB 865664 D01, calibration intervals of up to three years may be considered for reference dipoles when it is demonstrated that the SAR target, impedance and return loss of a dipole have remained stable according to the following requirements:

1. The measured SAR does not deviate more than 10% from the target on the calibration certificate.
2. The return-loss does not deviate more than 20% from the previous measurement and meets the required 20dB minimum return-loss requirement.
3. The measurement of real or imaginary parts of impedance does not deviate more than 5Ω from the previous measurement.

The following dipole was checked to pass the above 3 requirements to have 2-year calibration period from the calibration date:

Calibration Date	Extension Date	Certificate Electrical Delay (ns)	Certificate SAR Target Head (1g) W/kg @ 20.0 dBm	Measured Head SAR (1g) W/kg @ 20.0 dBm	Deviation 1g (%)	Certificate SAR Target Head (10g) W/kg @ 20.0 dBm	Measured Head SAR (10g) W/kg @ 20.0 dBm	Deviation 10g (%)	Certificate Impedance Head (Ohm) Real	Measured Impedance Head (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Head (Ohm) Imaginary	Measured Impedance Head (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Head (dB)	Measured Return Loss Head (dB)	Deviation (%)	PASS/FAIL
9/7/2017	9/7/2018	1.2	3.95	3.99	1.01%	2.06	2.07	0.49%	53.7	49.6	4.1	4.6	2.6	2	-24.9	-28.9	-16.10%	PASS
Calibration Date	Extension Date	Certificate Electrical Delay (ns)	Certificate SAR Target Body (1g) W/kg @ 20.0 dBm	Measured Body SAR (1g) W/kg @ 20.0 dBm	Deviation 1g (%)	Certificate SAR Target Body (10g) W/kg @ 20.0 dBm	Measured Body SAR (10g) W/kg @ 20.0 dBm	Deviation 10g (%)	Certificate Impedance Body (Ohm) Real	Measured Impedance Body (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Body (Ohm) Imaginary	Measured Impedance Body (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Body (dB)	Measured Return Loss Body (dB)	Deviation (%)	PASS/FAIL
9/7/2017	9/7/2018	1.2	3.95	4.13	4.56%	2.09	2.14	2.39%	49.2	45.8	3.4	5.6	2.1	3.5	-24.8	-24.7	0.40%	PASS

Impedance & Return-Loss Measurement Plot for Head TSL



Impedance & Return-Loss Measurement Plot for Body TSL

