

# FCC and ISEDC Test Report

Apple Inc.  
Model: A2304

In accordance with FCC 47 CFR Part 15C and  
ISEDC RSS-GEN

Prepared for: Apple Inc.  
One Apple Park Way  
Cupertino  
California 95014  
USA



Add value.  
Inspire trust.

FCC ID: BCGA2304

IC: 579C-A2304

## COMMERCIAL-IN-CONFIDENCE

Document 75945250-14 Issue 01

### SIGNATURE

*A3/Lawson*

| NAME        | JOB TITLE       | RESPONSIBLE FOR      | ISSUE DATE       |
|-------------|-----------------|----------------------|------------------|
| Andy Lawson | Senior Engineer | Authorised Signatory | 28 November 2019 |

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD document control rules.

### ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate limited compliance with FCC 47 CFR Part 15C and ISEDC RSS-GEN. The sample tested was found to comply with the requirements defined in the applied rules.

| RESPONSIBLE FOR | NAME          | DATE             | SIGNATURE |
|-----------------|---------------|------------------|-----------|
| Testing         | Matthew Smart | 28 November 2019 | <i>ms</i> |

FCC Accreditation  
90987 Octagon House, Fareham Test Laboratory

Industry Canada Accreditation  
12669A Octagon House, Fareham Test Laboratory

### EXECUTIVE SUMMARY

A sample of this product was tested and found to be compliant with FCC 47 CFR Part 15C: 2018 and ISEDC RSS-GEN: Issue 5 A1 (2019-03) for the tests detailed in section 1.3.



### DISCLAIMER AND COPYRIGHT

This non-binding report has been prepared by TÜV SÜD with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD. No part of this document may be reproduced without the prior written approval of TÜV SÜD. © 2019 TÜV SÜD. This report relates only to the actual item/items tested.

### ACCREDITATION

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation. Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited).

TÜV SÜD  
is a trading name of TÜV SÜD Ltd  
Registered in Scotland at East Kilbride,  
Glasgow G75 0QF, United Kingdom  
Registered number: SC215164

TÜV SÜD Ltd is a  
TÜV SÜD Group Company

Phone: +44 (0) 1489 558100  
Fax: +44 (0) 1489 558101  
[www.tuv-sud.co.uk](http://www.tuv-sud.co.uk)

TÜV SÜD  
Octagon House  
Concorde Way  
Fareham  
Hampshire PO15 5RL  
United Kingdom



Contents

1      **Report Summary .....2**

1.1    Report Modification Record.....2

1.2    Introduction.....2

1.3    Brief Summary of Results .....3

1.4    Product Information .....4

1.5    Deviations from the Standard.....4

1.6    EUT Modification Record .....4

1.7    Test Location .....4

2      **Test Details .....5**

2.1    AC Power Line Conducted Emissions .....5

3      **Measurement Uncertainty ..... 14**



# 1 Report Summary

## 1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

| Issue | Description of Change | Date of Issue    |
|-------|-----------------------|------------------|
| 1     | First Issue           | 28 November 2019 |

**Table 1**

## 1.2 Introduction

|                               |                                                                 |
|-------------------------------|-----------------------------------------------------------------|
| Applicant                     | Apple Inc.                                                      |
| Manufacturer                  | Apple Inc.                                                      |
| Model Number(s)               | A2304                                                           |
| Serial Number(s)              | C02Z1003N5VN                                                    |
| Hardware Version(s)           | REV 1.0                                                         |
| Software Version(s)           | 19A556                                                          |
| Number of Samples Tested      | 1                                                               |
| Test Specification/Issue/Date | FCC 47 CFR Part 15C: 2018<br>ISED RSS-GEN: Issue 5 A1 (2019-03) |
| Order Number                  | 0540176069                                                      |
| Date                          | 25-February-2019                                                |
| Date of Receipt of EUT        | 21-October-2019                                                 |
| Start of Test                 | 31-October-2019                                                 |
| Finish of Test                | 31-October-2019                                                 |
| Name of Engineer(s)           | Matthew Smart                                                   |
| Related Document(s)           | ANSI C63.10 (2013)                                              |



### 1.3 Brief Summary of Results

A brief summary of the tests carried out in accordance with FCC 47 CFR Part 15C, ISED RSS-GEN is shown below.

| Section                                   | Specification Clause |         | Test Description                  | Result | Comments/Base Standard |
|-------------------------------------------|----------------------|---------|-----------------------------------|--------|------------------------|
|                                           | Part 15C             | RSS-GEN |                                   |        |                        |
| Configuration and Mode: 2.4 GHz Bluetooth |                      |         |                                   |        |                        |
| 2.1                                       | 15.207               | 8.8     | AC Power Line Conducted Emissions | Pass   | ANSI C63.10 (2013)     |
| Configuration and Mode: 2.4 GHz WLAN      |                      |         |                                   |        |                        |
| 2.1                                       | 15.207               | 8.8     | AC Power Line Conducted Emissions | Pass   | ANSI C63.10 (2013)     |
| Configuration and Mode: 5.0 GHz WLAN      |                      |         |                                   |        |                        |
| 2.1                                       | 15.207               | 8.8     | AC Power Line Conducted Emissions | Pass   | ANSI C63.10 (2013)     |

**Table 2**



## 1.4 Product Information

### 1.4.1 Technical Description

The Equipment Under Test (EUT) was a rack mounted computer, with Bluetooth, Bluetooth Low Energy and 802.11 a/b/g/n/ac capabilities in the 2.4 GHz and 5.0 GHz bands.

### 1.5 Deviations from the Standard

No deviations from the applicable test standard were made during testing.

### 1.6 EUT Modification Record

The table below details modifications made to the EUT during the test programme.

The modifications incorporated during each test are recorded on the appropriate test pages.

| Modification State                        | Description of Modification still fitted to EUT | Modification Fitted By | Date Modification Fitted |
|-------------------------------------------|-------------------------------------------------|------------------------|--------------------------|
| Model: A2304: Serial Number: C02Z1003N5VN |                                                 |                        |                          |
| 0                                         | As supplied by the customer                     | Not Applicable         | Not Applicable           |

**Table 3**

### 1.7 Test Location

TÜV SÜD conducted the following tests at our Fareham Test Laboratory.

| Test Name                                 | Name of Engineer(s) | Accreditation |
|-------------------------------------------|---------------------|---------------|
| Configuration and Mode: 2.4 GHz Bluetooth |                     |               |
| AC Power Line Conducted Emissions         | Matthew Smart       | UKAS          |
| Configuration and Mode: 2.4 GHz WLAN      |                     |               |
| AC Power Line Conducted Emissions         | Matthew Smart       | UKAS          |
| Configuration and Mode: 5.0 GHz WLAN      |                     |               |
| AC Power Line Conducted Emissions         | Matthew Smart       | UKAS          |

**Table 4**

Office Address:

Octagon House  
Concorde Way  
Segensworth North  
Fareham  
Hampshire  
PO15 5RL  
United Kingdom



## 2 Test Details

### 2.1 AC Power Line Conducted Emissions

#### 2.1.1 Specification Reference

FCC 47 CFR Part 15C, Clause 15.207  
ISED RSS-GEN, Clause 18.8

#### 2.1.2 Equipment Under Test and Modification State

A2304, S/N: C02Z1003N5VN - Modification State 0

#### 2.1.3 Date of Test

31-October-2019

#### 2.1.4 Test Method

The test was performed in accordance with ANSI C63.10, clause 6.2.

#### 2.1.5 Environmental Conditions


|                     |         |
|---------------------|---------|
| Ambient Temperature | 21.5 °C |
| Relative Humidity   | 45.0 %  |

#### 2.1.6 Example Calculation

Quasi-Peak level (dB $\mu$ V) = Receiver level (dB $\mu$ V) + Correction Factor (dB)  
Margin (dB) = Quasi-Peak level (dB $\mu$ V) – Limit (dB $\mu$ V)

CISPR Average level (dB $\mu$ V) = Receiver level (dB $\mu$ V) + Correction Factor (dB)  
Margin (dB) = CISPR Average level (dB $\mu$ V) - Limit (dB $\mu$ V)

### 2.1.7 Example Test Setup Diagram



### Figure 1 - Conducted Disturbance Example Test Setup

## 2.1.8 Test Results

### 2.4 GHz Bluetooth


Applied supply Voltage: 120 V AC

Applied supply frequency: 60 Hz

| Frequency (MHz) | QP Level (dBμV) | QP Limit (dBμV) | QP Margin (dB) | CISPR Average Level (dBμV) | CISPR Average Limit (dBμV) | CISPR Average Margin (dB) |
|-----------------|-----------------|-----------------|----------------|----------------------------|----------------------------|---------------------------|
| *               |                 |                 |                |                            |                            |                           |

**Table 5 - Live Line Emissions Results**

\* No emissions were detected with 10 dB of the limit.




**Figure 2 - Live Line - 150 kHz to 30 MHz**

| Frequency (MHz) | QP Level (dBμV) | QP Limit (dBμV) | QP Margin (dB) | CISPR Average Level (dBμV) | CISPR Average Limit (dBμV) | CISPR Average Margin (dB) |
|-----------------|-----------------|-----------------|----------------|----------------------------|----------------------------|---------------------------|
| 10.998          | 33.4            | 60.0            | -26.6          | 25.4                       | 50.0                       | -24.6                     |
| 11.243          | 34.6            | 60.0            | -25.4          | 26.5                       | 50.0                       | -23.5                     |

**Table 6 - Neutral Line Emissions Results**

No other emissions were detected with 10 dB of the limit.



**Figure 3 - Neutral Line - 150 kHz to 30 MHz**

## 2.4 GHz WLAN


Applied supply Voltage: 120 V AC

Applied supply frequency: 60 Hz

| Frequency (MHz) | QP Level (dBμV) | QP Limit (dBμV) | QP Margin (dB) | CISPR Average Level (dBμV) | CISPR Average Limit (dBμV) | CISPR Average Margin (dB) |
|-----------------|-----------------|-----------------|----------------|----------------------------|----------------------------|---------------------------|
| 10.971          | 33.4            | 60.0            | -26.6          | 25.8                       | 50.0                       | -24.2                     |

**Table 7 - Live Line Emissions Results**

No other emissions were detected with 10 dB of the limit.




**Figure 4 - Live Line - 150 kHz to 30 MHz**



| Frequency (MHz) | QP Level (dBμV) | QP Limit (dBμV) | QP Margin (dB) | CISPR Average Level (dBμV) | CISPR Average Limit (dBμV) | CISPR Average Margin (dB) |
|-----------------|-----------------|-----------------|----------------|----------------------------|----------------------------|---------------------------|
| 0.654           | 33.3            | 56.0            | -22.7          | 24.1                       | 46.0                       | -21.9                     |
| 11.269          | 35.2            | 60.0            | -24.8          | 28.4                       | 50.0                       | -21.6                     |

**Table 8 - Neutral Line Emissions Results**

No other emissions were detected with 10 dB of the limit.



**Figure 5 - Neutral Line - 150 kHz to 30 MHz**

## 5.0 GHz WLAN


Applied supply Voltage: 120 V AC

Applied supply frequency: 60 Hz

| Frequency (MHz) | QP Level (dBμV) | QP Limit (dBμV) | QP Margin (dB) | CISPR Average Level (dBμV) | CISPR Average Limit (dBμV) | CISPR Average Margin (dB) |
|-----------------|-----------------|-----------------|----------------|----------------------------|----------------------------|---------------------------|
| 11.142          | 34.5            | 60.0            | -25.5          | 26.3                       | 50.0                       | -23.7                     |

**Table 9 - Live Line Emissions Results**

No other emissions were detected with 10 dB of the limit.




**Figure 6 - Live Line - 150 kHz to 30 MHz**

| Frequency (MHz) | QP Level (dB $\mu$ V) | QP Limit (dB $\mu$ V) | QP Margin (dB) | CISPR Average Level (dB $\mu$ V) | CISPR Average Limit (dB $\mu$ V) | CISPR Average Margin (dB) |
|-----------------|-----------------------|-----------------------|----------------|----------------------------------|----------------------------------|---------------------------|
| 11.032          | 33.9                  | 60.0                  | -26.1          | 26.4                             | 50.0                             | -23.6                     |

**Table 10 - Neutral Line Emissions Results**

No other emissions were detected with 10 dB of the limit.



**Figure 7 - Neutral Line - 150 kHz to 30 MHz**

FCC 47 CFR Part 15, Limit Clause 15.207 and ISEDC RSS-GEN, Limit Clause 8.8

| Frequency of Emission (MHz) | Conducted Limit (dB $\mu$ V) |               |
|-----------------------------|------------------------------|---------------|
|                             | Quasi-Peak                   | CISPR Average |
| 0.15 to 0.5                 | 66 to 56*                    | 56 to 46*     |
| 0.5 to 5                    | 56                           | 46            |
| 5 to 30                     | 60                           | 50            |

**Table 11**

\*Decreases with the logarithm of the frequency.



### 2.1.9 Test Location and Test Equipment Used

This test was carried out in EMC Chamber 5.

| Instrument                              | Manufacturer    | Type No  | TE No | Calibration Period (months) | Calibration Due |
|-----------------------------------------|-----------------|----------|-------|-----------------------------|-----------------|
| Screened Room (5)                       | Rainford        | Rainford | 1545  | 36                          | 23-Jan-2021     |
| Compliance 5 Emissions                  | Teseq           | V5.26.51 | 3275  | -                           | Software        |
| EMI Test Receiver                       | Rohde & Schwarz | ESU40    | 3506  | 12                          | 17-Dec-2019     |
| Transient Limiter                       | Hewlett Packard | 11947A   | 2377  | 12                          | 26-Feb-2020     |
| 3 Phase Artificial Mains Network (LISN) | Rohde & Schwarz | ESH2-Z5  | 16    | 12                          | 28-Feb-2020     |
| LISN                                    | Rohde & Schwarz | ESH3-Z5  | 1390  | 12                          | 20-Nov-2019     |

**Table 12**



### 3 Measurement Uncertainty

For a 95% confidence level, the measurement uncertainties for defined systems are:

| Test Name                         | Measurement Uncertainty               |
|-----------------------------------|---------------------------------------|
| AC Power Line Conducted Emissions | 150 kHz to 30 MHz, LISN, $\pm 3.7$ dB |

**Table 13**

#### Measurement Uncertainty Decision Rule

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115:2007, clause 4.4.3 and 4.5.1.