



Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 2422MHz
Channel: 3



Plot 7-196. Radiated Restricted Lower Band Edge Measurement ANT WF7b (Peak & Average – RU242)


Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 2427MHz
Channel: 4



Plot 7-197. Radiated Restricted Lower Band Edge Measurement ANT WF7b (Peak & Average – RU242)


FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 147 of 173

Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 2432MHz
Channel: 5



Plot 7-198. Radiated Restricted Lower Band Edge Measurement ANT WF7b (Peak & Average – RU242)


Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 2442MHz
Channel: 7



Plot 7-199. Radiated Restricted Upper Band Edge Measurement ANT WF7b (Peak & Average – RU242)


FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 148 of 173

Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 2447MHz
Channel: 8



Plot 7-200. Radiated Restricted Upper Band Edge Measurement ANT WF7b (Peak & Average – RU242)


Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 2452MHz
Channel: 9



Plot 7-201. Radiated Restricted Upper Band Edge Measurement ANT WF7b (Peak & Average – RU242)


FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 149 of 173

Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 2457MHz
Channel: 10



Plot 7-202. Radiated Restricted Upper Band Edge Measurement ANT WF7b (Peak & Average – RU242)


Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 2462MHz
Channel: 11



Plot 7-203. Radiated Restricted Upper Band Edge Measurement ANT WF7b (Peak & Average – RU242)

FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 150 of 173

Worst Case Mode:	802.11ax OFDMA
Worst Case Transfer Rate:	MCS9
RU Index:	61
Distance of Measurements:	3 Meters
Operating Frequency:	2467MHz
Channel:	12



Plot 7-204. Radiated Restricted Upper Band Edge Measurement ANT WF7b (Peak & Average – RU242)


FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 151 of 173

7.7.6 CDD Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]


The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode:	802.11ax OFDMA
Worst Case Transfer Rate:	MCS9
RU Index:	0
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	1



Plot 7-205. Radiated Restricted Lower Band Edge Measurement CDD (Peak & Average – RU26)


Worst Case Mode:	802.11ax OFDMA
Worst Case Transfer Rate:	MCS9
RU Index:	0
Distance of Measurements:	3 Meters
Operating Frequency:	2417MHz
Channel:	2



Plot 7-206. Radiated Restricted Lower Band Edge Measurement CDD (Peak & Average – RU26)


FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 152 of 173

Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 0
Distance of Measurements: 3 Meters
Operating Frequency: 2422MHz
Channel: 3



Plot 7-207. Radiated Restricted Lower Band Edge Measurement CDD (Peak & Average – RU26)


Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 0
Distance of Measurements: 3 Meters
Operating Frequency: 2427MHz
Channel: 4



Plot 7-208. Radiated Restricted Lower Band Edge Measurement CDD (Peak & Average – RU26)


FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 153 of 173

Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 0
Distance of Measurements: 3 Meters
Operating Frequency: 2432MHz
Channel: 5



Plot 7-209. Radiated Restricted Lower Band Edge Measurement CDD (Peak & Average – RU26)


Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 8
Distance of Measurements: 3 Meters
Operating Frequency: 2452MHz
Channel: 9



Plot 7-210. Radiated Restricted Upper Band Edge Measurement CDD (Peak & Average – RU26)


FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 154 of 173

Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 8
Distance of Measurements: 3 Meters
Operating Frequency: 2457MHz
Channel: 10



Plot 7-211. Radiated Restricted Upper Band Edge Measurement CDD (Peak & Average – RU26)


Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 8
Distance of Measurements: 3 Meters
Operating Frequency: 2462MHz
Channel: 11



Plot 7-212. Radiated Restricted Upper Band Edge Measurement CDD (Peak & Average – RU26)

FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 155 of 173


Worst Case Mode:	802.11ax OFDMA
Worst Case Transfer Rate:	MCS9
RU Index:	8
Distance of Measurements:	3 Meters
Operating Frequency:	2467MHz
Channel:	12



Plot 7-213. Radiated Restricted Upper Band Edge Measurement CDD (Peak & Average – RU26)


FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 156 of 173

Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 1



Plot 7-214. Radiated Restricted Lower Band Edge Measurement CDD (Peak & Average – RU242)


Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 2417MHz
Channel: 2



Plot 7-215. Radiated Restricted Lower Band Edge Measurement CDD (Peak & Average – RU242)


FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 157 of 173

Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 2422MHz
Channel: 3



Plot 7-216. Radiated Restricted Lower Band Edge Measurement CDD (Peak & Average – RU242)


Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 2427MHz
Channel: 4



Plot 7-217. Radiated Restricted Lower Band Edge Measurement CDD (Peak & Average – RU242)


FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 158 of 173

Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 2432MHz
Channel: 5



Plot 7-218. Radiated Restricted Lower Band Edge Measurement CDD (Peak & Average – RU242)


Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 2452MHz
Channel: 9



Plot 7-219. Radiated Restricted Upper Band Edge Measurement CDD (Peak & Average – RU242)


FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 159 of 173

Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 2457MHz
Channel: 10



Plot 7-220. Radiated Restricted Upper Band Edge Measurement CDD (Peak & Average – RU242)


Worst Case Mode: 802.11ax OFDMA
Worst Case Transfer Rate: MCS9
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 2462MHz
Channel: 11



Plot 7-221. Radiated Restricted Upper Band Edge Measurement CDD (Peak & Average – RU242)

FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 160 of 173

Worst Case Mode:	802.11ax OFDMA
Worst Case Transfer Rate:	MCS9
RU Index:	61
Distance of Measurements:	3 Meters
Operating Frequency:	2467MHz
Channel:	12



Plot 7-222. Radiated Restricted Upper Band Edge Measurement CDD (Peak & Average – RU242)

FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 161 of 173

7.8 Radiated Spurious Emissions – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-50 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-50. Radiated Limits

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold

FCC ID: BCGA2316		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 162 of 173

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-7. Radiated Test Setup < 30Mhz




Figure 7-8. Radiated Test Setup < 1GHz

FCC ID: BCGA2316	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 163 of 173

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen(8.10) are below the limit shown in Table 7-50.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes. For below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector for emissions within 6dB of the limit.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger
8. No spurious emissions were detected within 20dB of the limit below 30MHz.
9. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
10. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.
11. All antenna configurations and data rates were investigated and only the worst case are reported.
12. For radiated measurements, emissions were investigated for the fully-loaded RU configuration and for all the partially-loaded RU configurations. Among all of the available partially-loaded RU configurations, only the configuration with the worst case emissions is reported.

Sample Calculations


Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB/m]}$
- $\text{AFCL}_{[dB/m]} = \text{Antenna Factor}_{[dB/m]} + \text{Cable Loss}_{[dB]} - \text{Preamplifier Gain}_{[dB]}$
- $\text{Margin}_{[dB]} = \text{Field Strength Level}_{[dB\mu V/m]} - \text{Limit}_{[dB\mu V/m]}$


FCC ID: BCGA2316		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 164 of 173

CDD Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



Plot 7-223. Radiated Spurious Emissions below 1GHz CDD Ch.6 (RU26), with AC/DC Adapter



Plot 7-224. Radiated Spurious Emissions below 1GHz CDD Ch.6 (RU242), with AC/DC Adapter

FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 165 of 173

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
31.41	Max Peak	V	100	191	-66.26	-18.18	22.56	40.00	-17.44
71.56	Max Peak	H	250	213	-58.42	-26.47	22.11	40.00	-17.89
156.63	Max Peak	V	100	104	-66.19	-21.63	19.18	43.52	-24.34
200.38	Max Peak	H	100	150	-64.71	-22.30	19.99	43.52	-23.53
338.51	Max Peak	H	100	193	-71.31	-17.58	18.11	46.02	-27.91
538.18	Max Peak	V	250	10	-77.64	-10.28	19.08	46.02	-26.94

Table 7-51. Radiated Spurious Emissions below 1GHz CDD Ch.6 (RU26), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
31.16	Max Peak	V	100	282	-64.05	-18.05	24.90	40.00	-15.10
69.53	Max Peak	H	250	193	-58.28	-26.50	22.22	40.00	-17.78
163.08	Max Peak	H	100	150	-67.58	-22.96	16.46	43.52	-27.06
206.10	Max Peak	H	100	168	-63.61	-21.88	21.51	43.52	-22.01
218.67	Max Peak	H	100	150	-66.19	-21.79	19.02	46.02	-27.00
339.28	Max Peak	H	100	205	-72.76	-17.52	16.72	46.02	-29.30

Table 7-52. Radiated Spurious Emissions below 1GHz CDD Ch.6 (RU242), with AC/DC Adapter

FCC ID: BCGA2316		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 166 of 173

7.9 AC Line-Conducted Emissions Measurement

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-53. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Section 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA2316		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 167 of 173

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-9. Test Instrument & Measurement Setup

Test Notes

- All modes of operation were investigated and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
- Both configurations below were investigated, and the worst case has been reported.
 - EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - EUT powered by host PC via USB-C cable with wire charger
- The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.207 and RSS-Gen(8.8).
- $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
- $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
- $\text{Margin (dB)} = \text{QP/AV Level (dB}\mu\text{V)} - \text{QP/AV Limit (dB}\mu\text{V)}$
- Traces shown in plot are made using quasi peak and average detectors.
- Deviations to the Specifications: None.
- All RU's were investigated and only worst case partially-loaded and fully-loaded RU's are reported.


FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 168 of 173



Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.168	FINAL	53.1	—	65.06	-12.00	L1	GND
0.173	FINAL	—	38.50	54.84	-16.34	L1	GND
0.254	FINAL	—	32.94	51.64	-18.70	L1	GND
0.258	FINAL	47.8	—	61.50	-13.68	L1	GND
0.337	FINAL	—	25.95	49.28	-23.34	L1	GND
0.344	FINAL	42.4	—	59.12	-16.69	L1	GND
0.508	FINAL	37.0	—	56.00	-19.02	L1	GND
0.517	FINAL	—	19.65	46.00	-26.35	L1	GND
0.593	FINAL	35.2	—	56.00	-20.81	L1	GND
0.596	FINAL	—	17.23	46.00	-28.77	L1	GND
4.439	FINAL	33.1	—	56.00	-22.92	L1	GND
4.448	FINAL	—	18.62	46.00	-27.38	L1	GND

Table 7-54. AC Line Conducted Data with 802.11ax (RU26) Ch.6 (L1, with AC/DC Adapter)

FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 169 of 173




Plot 7-226. AC Line Conducted Emissions with 802.11ax (RU26) Ch.6 (N, with AC/DC Adapter)

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.168	FINAL	48.6	—	65.06	-16.43	N	GND
0.170	FINAL	—	35.51	54.95	-19.44	N	GND
0.254	FINAL	—	29.56	51.64	-22.08	N	GND
0.256	FINAL	43.8	—	61.57	-17.74	N	GND
0.339	FINAL	—	23.63	49.23	-25.60	N	GND
0.339	FINAL	39.0	—	59.23	-20.23	N	GND
0.425	FINAL	—	20.82	47.36	-26.54	N	GND
0.429	FINAL	36.7	—	57.27	-20.57	N	GND
0.506	FINAL	—	19.48	46.00	-26.52	N	GND
0.515	FINAL	36.6	—	56.00	-19.42	N	GND
4.441	FINAL	34.5	—	56.00	-21.49	N	GND
4.526	FINAL	—	20.22	46.00	-25.78	N	GND

Table 7-55. AC Line Conducted Data with 802.11ax (RU26) Ch.6 (N, with AC/DC Adapter)

FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 170 of 173




Plot 7-227. AC Line Conducted Emissions with 802.11ax (RU242) Ch.6 (L1, with AC/DC Adapter)

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.168	FINAL	48.5	—	65.06	-16.52	L1	GND
0.170	FINAL	—	35.05	54.95	-19.89	L1	GND
0.202	FINAL	51.3	—	63.54	-12.29	L1	GND
0.204	FINAL	—	37.92	53.45	-15.53	L1	GND
0.301	FINAL	43.6	—	60.22	-16.63	L1	GND
0.308	FINAL	—	27.78	50.04	-22.25	L1	GND
0.503	FINAL	36.3	—	56.00	-19.75	L1	GND
0.506	FINAL	—	18.93	46.00	-27.07	L1	GND
0.605	FINAL	—	17.22	46.00	-28.78	L1	GND
0.609	FINAL	34.8	—	56.00	-21.24	L1	GND
0.733	FINAL	34.6	—	56.00	-21.42	L1	GND
0.733	FINAL	—	18.85	46.00	-27.15	L1	GND

Table 7-56. AC Line Conducted Data with 802.11ax (RU242) Ch.6 (L1, with AC/DC Adapter)

FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 171 of 173



Plot 7-228. AC Line Conducted Emissions with 802.11ax (RU242) Ch.6 (N, with AC/DC Adapter)

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.168	FINAL	46.3	—	65.06	-18.80	N	GND
0.168	FINAL	—	33.75	55.06	-21.31	N	GND
0.202	FINAL	49.7	—	63.54	-13.86	N	GND
0.204	FINAL	—	37.41	53.45	-16.04	N	GND
0.301	FINAL	41.9	—	60.22	-18.35	N	GND
0.303	FINAL	—	26.69	50.16	-23.47	N	GND
0.506	FINAL	—	20.64	46.00	-25.36	N	GND
0.508	FINAL	35.7	—	56.00	-20.28	N	GND
0.713	FINAL	—	20.25	46.00	-25.75	N	GND
0.713	FINAL	36.0	—	56.00	-19.96	N	GND
0.800	FINAL	35.8	—	56.00	-20.21	N	GND
0.800	FINAL	—	22.25	46.00	-23.75	N	GND

Table 7-57. AC Line Conducted Data with 802.11ax (RU242) Ch.6 (N, with AC/DC Adapter)

FCC ID: BCGA2316	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 172 of 173

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Tablet Device FCC ID: BCGA2316** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCGA2316		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270028-03.BCG	Test Dates: 6/15/2020 - 08/14/2020	EUT Type: Tablet Device	Page 173 of 173