

MEASUREMENT REPORT

FCC Part 90

Applicant Name:

Apple Inc.
One Apple Park Way
Cupertino, CA 95014
United States

Date of Testing:

05/01/2020 - 07/29/2020

Test Site/Location:

PCTEST Morgan Hill, CA, USA

Test Report Serial No.:

1C2004270034-04.BCG

FCC ID:

BCGA2429

APPLICANT:

Apple Inc.

Application Type:

Certification

Model:

A2429, A2430

EUT Type:

Tablet Device

FCC Classification:

PCS Licensed Transmitter (PCB)

FCC Rule Part:

§2.1049, §90(S), §90(R)

Test Procedure(s):

ANSI C63.26-2015, TIA-603-E-2016, KDB 971168 D01 v03r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President

FCC ID: BCGA2429	 MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device
Page 1 of 57		

TABLE OF CONTENTS


1.0	INTRODUCTION.....	4
1.1	Scope.....	4
1.2	PCTEST Test Location	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description	5
2.2	Device Capabilities	5
2.3	Antenna Description.....	5
2.4	Test Support Equipment.....	6
2.5	Test Configuration	6
2.6	Software and Firmware	6
2.7	EMI Suppression Device(s)/Modifications	6
3.0	DESCRIPTION OF TESTS.....	7
3.1	Evaluation Procedure.....	7
3.2	Radiated Spurious Emissions.....	7
4.0	MEASUREMENT UNCERTAINTY.....	8
5.0	TEST EQUIPMENT CALIBRATION DATA	9
6.0	SAMPLE CALCULATIONS.....	10
7.0	TEST RESULTS	11
7.1	Summary.....	11
7.2	Occupied Bandwidth	13
7.3	Spurious and Harmonic Emissions at Antenna Terminal.....	23
7.4	Band Edge Emissions at Antenna Terminal	29
7.5	Conducted Power Output Data.....	39
7.6	Radiated Power (ERP).....	41
7.7	Radiated Spurious Emissions.....	44
7.7.1	Antenna C (Port A) Radiated Spurious Emissions Measurements.....	46
7.7.2	Antenna D (Port B) Radiated Spurious Emissions Measurements.....	50
7.8	Frequency Stability / Temperature Variation.....	52
8.0	CONCLUSION	57

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 2 of 57



MEASUREMENT REPORT

FCC Part 90



Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	Measurement	Max. Power [W]	Max. Power [dBm]	Emission Designator
LTE Band 26	10 MHz	QPSK	819.0	Conducted	0.355	25.50	9M03G7W
		16QAM	819.0	Conducted	0.308	24.89	9M01D7W
		64QAM	819.0	Conducted	0.237	23.74	9M02D7W
	5 MHz	QPSK	816.5 - 821.5	Conducted	0.355	25.50	4M51G7W
		16QAM	816.5 - 821.5	Conducted	0.318	25.02	4M51D7W
		64QAM	816.5 - 821.5	Conducted	0.236	23.73	4M51D7W
	3 MHz	QPSK	815.5 - 822.5	Conducted	0.352	25.47	2M71G7W
		16QAM	815.5 - 822.5	Conducted	0.309	24.90	2M70D7W
		64QAM	815.5 - 822.5	Conducted	0.240	23.80	2M71D7W
	1.4 MHz	QPSK	814.7 - 823.3	Conducted	0.355	25.50	1M09G7W
		16QAM	814.7 - 823.3	Conducted	0.312	24.94	1M09D7W
		64QAM	814.7 - 823.3	Conducted	0.248	23.95	1M09D7W
LTE Band 14	10 MHz	QPSK	793.0	ERP	0.193	22.85	9M07G7W
		16QAM	793.0	ERP	0.163	22.12	9M05D7W
		64QAM	793.0	ERP	0.129	21.11	9M07D7W
	5 MHz	QPSK	790.5 - 795.5	ERP	0.193	22.85	4M57G7W
		16QAM	790.5 - 795.5	ERP	0.167	22.23	4M54D7W
		64QAM	790.5 - 795.5	ERP	0.136	21.34	4M54D7W

EUT Overview

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 3 of 57

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST located in Morgan Hill, CA 95037, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (22831) test laboratory with the site description on file with ISED.

FCC ID: BCGA2429	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 4 of 57

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Tablet Device FCC ID: BCGA2429**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Parts 90(S) & 90(R).

Test Device Serial No.: F9FCN00DQ7LC, F9FCN01QQ7LC, F9FCN007Q7L9, F9FCN00FQ7L9

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE)

This device supports simultaneous multi radio transmission feature, which allows Bluetooth (1x, EDR, LE) and WiFi UNII 5GHz (802.11a/n/ac) to transmit simultaneously at the same antenna. All possible simultaneous configurations have been investigated and worst case mode has been found and reported in Bluetooth and UNII test reports.

2.3 Antenna Description

Following antennas were used for testing.

Antenna and Port	
Port A	Port B
Antenna C	Antenna D

Table 2-1. Antennas vs Ports

Frequency [MHz]	Antennas	
	Antenna C	Antenna D
650-800	-0.5	-0.7
820-960	-0.8	-0.6

Table 2-2. Highest Antenna Gain

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 5 of 57

2.4 Test Support Equipment

1	Apple MacBook	Model:	A1398	S/N:	C2QKP008F6F3
	w/AC/DC Adapter	Model:	A1435	S/N:	N/A
2	Apple USB Cable	Model:	Kanzi	S/N:	32530F
3	USB-C to Lightning Cable	Model:	N/A	S/N:	N/A
	w/ AC Adapter	Model:	A2305	S/N:	N/A
4	Apple Pencil	Model:	A1603	S/N:	G64TG0FEGWTJ
5	DC Power Supply	Model:	KPS3010D	S/N:	N/A

Table 2-3. Test Support Equipment List

2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.26-2015, TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz were tested with the highest transmitting power and the worst case channel.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

2.6 Software and Firmware

The test was conducted with firmware version 18A325 installed on the EUT.

2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 6 of 57

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI C63.26-2015/TIA-603-E-2016) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

3.2 Radiated Spurious Emissions

§2.1053, §90.635, §90(S)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Per the guidelines of KDB 412172 D01 v01r01, radiated power levels are measured using the following formula:

$$ERP \text{ or } EIRP = P_T + G_T - L_C$$

Where P_T is the transmitter output power, expressed in dBm, G_T is the gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP), and L_C signal attenuation in the connecting cable between the transmitter and antenna in dB.

Per the guidance of ANSI C63.26-2015 and TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10 \log_{10}(\text{Power [Watts]})$ specified in 90(S).

For fundamental radiated power measurements, the guidance of KDB 971168 D01 v03r01 is used to record the EUT power level that is subsequently matched via the aforementioned substitution method given in ANSI C63.26-2015 and TIA-603-E-2016.

Per KDB 414788 D01 v01r01, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was used while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 7 of 57

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.30
Radiated Disturbance (<1GHz)	4.15
Radiated Disturbance (>1GHz)	4.59
Radiated Disturbance (>18GHz)	4.96

FCC ID: BCGA2429	 MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device
		Page 8 of 57

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent Technologies	N9030A	3Hz-44GHz PXA Signal Analyzer	3/4/2020	Annual	3/4/2021	MY49430244
ESPEC	SU-241	Tabletop Temperature Chamber	9/3/2019	Annual	9/3/2020	92009574
ETS-Lindgren	3142E-PA	Pre-Amplifier (30MHz - 6GHz)	9/19/2019	Annual	9/19/2020	213236
ETS-Lindgren	3142E	BiConiLog Antenna (30MHz - 6GHz)	1/6/2020	Annual	1/6/2021	224569
ETS-Lindgren	3117	Double Ridged Guide Antenna (1-18 GHz)	4/21/2020	Annual	4/21/2021	205956
Rohde & Schwarz	FSV40	Signal Analyzer (10Hz-40GHz)	3/2/2020	Annual	3/2/2021	101619
Rohde & Schwarz	ESW26	EMI Test Receiver	6/1/2020	Annual	6/1/2021	101299
Rohde & Schwarz	ESW44	EMI Test Receiver	9/13/2019	Annual	9/13/2020	101570
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	11/16/2019	Annual	11/16/2020	164715
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	4/16/2020	Annual	4/16/2021	166869
Rohde & Schwarz	TC-TA18	Cross Polarized Vivaldi Antenna (400MHz-18GHz)	11/14/2019	Annual	11/14/2020	101057
Rohde & Schwarz	HFH2-Z2	Loop Antenna	3/12/2020	Annual	3/12/2021	100546

Table 5-1. Test Equipment List

Notes:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: BCGA2429	 MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device
		Page 9 of 57

6.0 SAMPLE CALCULATIONS

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7W

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination of Any

16QAM Modulation

Emission Designator = 8M45D7W

LTE BW = 8.45 MHz

D = Amplitude/Angle Modulated

7 = Quantized/Digital Info

W = Combination of Any

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80).

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 10 of 57

7.0 TEST RESULTS

7.1 Summary

Company Name: Apple Inc.
FCC ID: BCGA2429
FCC Classification: PCS Licensed Transmitter (PCB)
Mode(s): LTE
Band: Band 26 / Band 14

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 90(S).691(a) 90(R).543(a)	Conducted Band Edge / Spurious Emissions	On all frequencies between 769-775 MHz and 799-805 MHz, attenuation by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations. On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, attenuation by at least $43 + 10 \log(P)$ dB.(Band 14) > $43 + 10 \log_{10}(P[\text{Watts}])$ for all out-of-band emissions except > $50 + 10 \log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge (Band 26)		PASS	Sections 7.3, 7.4
2.1046 90.635	Conducted Power	< 100 Watts		PASS	Section 7.5
90.542(a)(7)	Effective Radiated Power (Band 14)	< 3 Watts max. ERP		PASS	Section 7.6
2.1053 90(S).691(a) 90(R).543(e)	Radiated Spurious Emissions	> $43 + 10 \log_{10}(P[\text{Watts}])$ for all out-of-band emissions except > $50 + 10 \log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge	RADIATED	PASS	Section 7.7
2.1055 90.213	Frequency Stability	< 2.5 ppm	CONDUCTED	PASS	Section 7.8

Table 7-1. Summary of Test Results

FCC ID: BCGA2429	 MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	Page 11 of 57
EUT Type: Tablet Device		

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 were taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 4.2.
- 5) All ports were investigated and for some test cases only the worst case data was reported.

FCC ID: BCGA2429	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 12 of 57

7.2 Occupied Bandwidth

S2.1049

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup

Test Notes


All ports were investigated and only the worst case data was reported

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 13 of 57

LTE Band 26




Plot 7-1. Occupied Bandwidth Plot (LTE Band 26 - 10MHz QPSK - Full RB Configuration)




Plot 7-2. Occupied Bandwidth Plot (LTE Band 26 - 10MHz 16-QAM - Full RB Configuration)

FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 14 of 57




Plot 7-3. Occupied Bandwidth Plot (LTE Band 26 - 10MHz 64-QAM - Full RB Configuration)




Plot 7-4. Occupied Bandwidth Plot (LTE Band 26 - 5MHz QPSK - Full RB Configuration)

FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 15 of 57




Plot 7-5. Occupied Bandwidth Plot (LTE Band 26 - 5MHz 16-QAM - Full RB Configuration)




Plot 7-6. Occupied Bandwidth Plot (LTE Band 26 - 5MHz 64-QAM - Full RB Configuration)

FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 16 of 57




Plot 7-7. Occupied Bandwidth Plot (LTE Band 26 - 3MHz QPSK - Full RB Configuration)




Plot 7-8. Occupied Bandwidth Plot (LTE Band 26 - 3MHz 16-QAM - Full RB Configuration)

FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 17 of 57




Plot 7-9. Occupied Bandwidth Plot (LTE Band 26 - 3MHz 64-QAM - Full RB Configuration)




Plot 7-10. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz QPSK - Full RB Configuration)

FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 18 of 57




Plot 7-11. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz 16-QAM - Full RB Configuration)



Plot 7-12. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz 64-QAM - Full RB Configuration)

FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 19 of 57

LTE Band 14




Plot 7-13. Occupied Bandwidth Plot (Band 14 - 10MHz QPSK - Full RB Configuration)




Plot 7-14. Occupied Bandwidth Plot (Band 14 - 10MHz 16-QAM - Full RB Configuration)

FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 20 of 57




Plot 7-15. Occupied Bandwidth Plot (Band 14 - 10MHz 64-QAM - Full RB Configuration)




Plot 7-16. Occupied Bandwidth Plot (Band 14 - 5MHz QPSK - Full RB Configuration)

FCC ID: BCGA2429		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 21 of 57



Plot 7-17. Occupied Bandwidth Plot (Band 14 - 5MHz 16-QAM - Full RB Configuration)



Plot 7-18. Occupied Bandwidth Plot (Band 14 - 5MHz 64-QAM - Full RB Configuration)

FCC ID: BCGA2429		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 22 of 57

7.3 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051 §90(S).691(a) §90(R).543(e)

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + 10 \log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz (separated into at least two plots per channel)
2. RBW $\geq$ 100kHz
3. VBW $\geq$ 3 x RBW
4. Detector = RMS
5. Trace mode = trace average
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup

Test Notes


1. Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 90. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
2. All ports were tested and only the worst case data were reported.

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 23 of 57

LTE Band 26




Plot 7-19. Conducted Spurious Plot (LTE Band 26 - 5MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-20. Conducted Spurious Plot (LTE Band 26 - 5MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 24 of 57




Plot 7-21. Conducted Spurious Plot (LTE Band 26 - 5MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-22. Conducted Spurious Plot (LTE Band 26 - 5MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 25 of 57




Plot 7-23. Conducted Spurious Plot (LTE Band 26 - 5MHz QPSK - RB Size 1, RB Offset 0 - High Channel)




Plot 7-24. Conducted Spurious Plot (LTE Band 26 - 5MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 26 of 57

LTE Band 14




Plot 7-25. Conducted Spurious Plot (Band 14 - 10MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)



Plot 7-26. Conducted Spurious Plot (Band 14 - 10MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: BCGA2429	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 27 of 57



Plot 7-27. Conducted Spurious Plot (Band 14 - 10MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 28 of 57

7.4 Band Edge Emissions at Antenna Terminal

§2.1051 §90(S).691(a) §90(R).543(e)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

For LTE B26 operation under Part 90.691, the minimum permissible attenuation level of any spurious emission removed from the EA licensee's frequency block by greater than 37.5 kHz is $43 + 10\log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts. The minimum permissible attenuation level of any spurious emission removed from the EA licensee's frequency block by up to and including 37.5 kHz is $50 + 10\log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Span was set large enough so as to capture all out of band emissions near the band edge
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Detector = RMS
5. Trace mode = trace average
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. Test Instrument & Measurement Setup


FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 29 of 57

Test Notes


1. For channel edge emission, the signal analyzer's "ACP" measurement capability is used.
2. Per Part 90, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center.
3. For LTE Band 14 operation under Part 90.543, the power of any emission must be reduced below the mean output power (P) by at least $43 + 10\log(P)$ dB measured in a 100 kHz bandwidth for frequencies less than 1 GHz, and in a 1 MHz bandwidth for frequencies greater than 1 GHz.
4. Additionally, for LTE Band 14 operation, on all frequencies between 769-775 MHz and 799-805 MHz, the power of any emission shall be attenuated by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations.
5. All ports were tested and only the worst case data were reported.

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 30 of 57

LTE Band 26




Plot 7-28. Channel Edge Plot (LTE Band 26 - 10MHz QPSK - Mid Channel)




Plot 7-29. Channel Edge Plot (LTE Band 26 - 5MHz QPSK - Low Channel)

FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 31 of 57




Plot 7-30. Channel Edge Plot (LTE Band 26 - 5MHz QPSK - High Channel)




Plot 7-31. Channel Edge Plot (LTE Band 26 - 3MHz QPSK - Low Channel)

FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 32 of 57




Plot 7-32. Channel Edge Plot (LTE Band 26 - 3MHz QPSK - High Channel)



Plot 7-33. Channel Edge Plot (LTE Band 26 - 1.4MHz QPSK - Low Channel)


FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 33 of 57



Plot 7-34. Channel Edge Plot (LTE Band 26 - 1.4MHz QPSK - High Channel)

FCC ID: BCGA2429		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 34 of 57

LTE Band 14




Plot 7-35. Lower Band Edge Plot (Band 14 - 10MHz QPSK - Full RB Configuration)



Plot 7-36. Lower Extended Band Edge Plot (Band 14 - 10MHz QPSK - Full RB Configuration)

FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 35 of 57




Plot 7-37. Upper Band Edge Plot (Band 14 - 10MHz QPSK - Full RB Configuration)




Plot 7-38. Upper Extended Band Edge Plot (Band 14 - 10MHz QPSK - Full RB Configuration)

FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 36 of 57



Plot 7-39. Lower Band Edge Plot (Band 14 - 5MHz QPSK - Full RB Configuration)



Plot 7-40. Lower Extended Band Edge Plot (Band 14 - 5MHz QPSK - Full RB Configuration)

FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 37 of 57



Plot 7-41. Upper Band Edge Plot (Band 14 - 5MHz QPSK - Full RB Configuration)



Plot 7-42. Upper Extended Band Edge Plot (Band 14 - 5MHz QPSK - Full RB Configuration)

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 38 of 57

7.5 Conducted Power Output Data

~~\$2.1046~~ ~~\$90.635~~

Test Overview

Conducted power measurements are performed to measure the average output power of the EUT. The averaging is to be performed only over duration of active transmissions at maximum output power level. The average measurements do not include averaging over periods when the transmitter is quiescent or when operating at reduced power level.

Test Procedures Used

KDB 971168 D01 v03r01

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-4. Conducted Power Measurement Setup

Test Notes

1. The EUT was tested in all possible test configurations. The worst case emissions are reported with the EUT modulations and channel bandwidth configurations shown in the tables below.
2. This unit was tested with its standard battery.
3. Refer to Table 2-1 Section 2.3 of this test report for correlation between Antennas and Ports

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 39 of 57

Port A

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]	Conducted Power [Watts]	Conducted Power Limit [dBm]	Margin [dB]
10 MHz	QPSK	26740	819.0	1 / 0	25.50	0.355	50.00	-24.50
	16-QAM	26740	819.0	1 / 0	24.89	0.308	50.00	-25.11
	64-QAM	26740	819.0	1 / 0	23.74	0.237	50.00	-26.26
5 MHz	QPSK	26715	816.5	1 / 0	25.50	0.355	50.00	-24.50
		26765	821.5	1 / 0	25.43	0.349	50.00	-24.57
	16-QAM	26715	816.5	1 / 0	25.02	0.318	50.00	-24.98
	64-QAM	26715	816.5	1 / 0	23.71	0.235	50.00	-26.29
3 MHz	QPSK	26705	815.5	1 / 7	25.47	0.352	50.00	-24.53
		26775	822.5	1 / 7	25.37	0.344	50.00	-24.63
	16-QAM	26705	815.5	1 / 0	24.90	0.309	50.00	-25.10
	64-QAM	26705	815.5	1 / 7	23.80	0.240	50.00	-26.20
1.4 MHz	QPSK	26697	814.7	1 / 0	25.50	0.355	50.00	-24.50
		26783	823.3	1 / 5	25.49	0.354	50.00	-24.51
	16-QAM	26697	814.7	1 / 5	24.94	0.312	50.00	-25.06
	64-QAM	26697	814.7	1 / 5	23.95	0.248	50.00	-26.05

Table 7-2. LTE Band 26 Conducted Power Output Data

Port B

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]	Conducted Power [Watts]	Conducted Power Limit [dBm]	Margin [dB]
10 MHz	QPSK	26740	819.0	1 / 0	24.45	0.279	50.00	-25.55
	16-QAM	26740	819.0	1 / 25	23.89	0.245	50.00	-26.11
	64-QAM	26740	819.0	1 / 49	22.76	0.189	50.00	-27.24
5 MHz	QPSK	26715	816.5	1 / 0	24.42	0.277	50.00	-25.58
		26765	821.5	1 / 0	24.50	0.282	50.00	-25.50
	16-QAM	26765	821.5	1 / 24	23.81	0.240	50.00	-26.19
	64-QAM	26765	821.5	1 / 24	22.78	0.190	50.00	-27.22
3 MHz	QPSK	26705	815.5	1 / 0	24.48	0.281	50.00	-25.52
		26775	822.5	1 / 7	24.49	0.281	50.00	-25.51
	16-QAM	26775	822.5	1 / 7	23.71	0.235	50.00	-26.29
	64-QAM	26775	822.5	1 / 7	22.67	0.185	50.00	-27.33
1.4 MHz	QPSK	26697	814.7	1 / 5	24.44	0.278	50.00	-25.56
		26783	823.3	1 / 0	24.50	0.282	50.00	-25.50
	16-QAM	26783	823.3	1 / 3	23.81	0.240	50.00	-26.19
	64-QAM	26783	823.3	1 / 3	22.66	0.185	50.00	-27.34

Table 7-3. LTE Band 26 Conducted Power Output Data

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 40 of 57

7.6 Radiated Power (ERP) §90.542(a)(7)

Test Overview

Effective Radiated Power (ERP) measurements are calculated by adding highest antenna gain to maximum measured conducted output power. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.2.1
ANSI C63.26-2015
TIA-603-E-2016 – Section 2.2.17

Test Settings

The relevant equation for determining the ERP or EIRP from the conducted RF output power measured is:

$$\text{ERP/EIRP} = \text{PMeas} - \text{LC} + \text{GT}$$

Where:

ERP/EIRP = effective or equivalent radiated power, respectively (expressed in the same units as PMeas, typically dBW or dBm)

PMeas = measured transmitter output power or PSD, in dBW or dBm

LC = signal attenuation in the connecting cable between the transmitter and antenna in dB

GT = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-5. ERP/EIRP Measurement Setup

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 41 of 57

Test Notes

- 1) The worst case emissions are reported with the modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.
- 3) The Level (dBm) readings in the table were taken with a correction table loaded into the base station simulator. The correction table was used to account for the signal attenuation in the connecting cable between the transmitter and antenna.
- 4) The Ant. Gains (GT) are listed in dBi.
- 5) Refer to Table 2-1 Section 2.3 of this test report for correlation between Antennas and Ports

FCC ID: BCGA2429	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 42 of 57

Antenna C - ERP

Bandwidth	Modulation	Channel	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
10 MHz	QPSK	23330	793.0	-0.50	1 / 49	25.50	22.85	0.19	38.45	-15.60
	16-QAM	23330	793.0	-0.50	1 / 49	24.77	22.12	0.16	38.45	-16.33
	64-QAM	23330	793.0	-0.50	1 / 49	23.76	21.11	0.13	38.45	-17.34
5 MHz	QPSK	23305	790.5	-0.50	1 / 24	25.36	22.71	0.19	38.45	-15.74
		23330	793.0	-0.50	1 / 24	25.50	22.85	0.19	38.45	-15.60
		23355	795.5	-0.50	1 / 24	25.42	22.77	0.19	38.45	-15.68
	16-QAM	23330	793.0	-0.50	1 / 24	24.88	22.23	0.17	38.45	-16.22
	64-QAM	23330	793.0	-0.50	1 / 24	23.82	21.17	0.13	38.45	-17.28

Table 7-4. ERP Data (Band 14)

Antenna D - ERP

Bandwidth	Modulation	Channel	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
10 MHz	QPSK	23330	793.0	-0.70	1 / 25	24.50	21.65	0.15	38.45	-16.80
	16-QAM	23330	793.0	-0.70	1 / 49	23.90	21.05	0.13	38.45	-17.40
	64-QAM	23330	793.0	-0.70	1 / 49	22.91	20.06	0.10	38.45	-18.39
5 MHz	QPSK	23305	790.5	-0.70	1 / 24	24.44	21.59	0.14	38.45	-16.86
		23330	793.0	-0.70	1 / 24	24.50	21.65	0.15	38.45	-16.80
		23355	795.5	-0.70	1 / 0	24.47	21.62	0.15	38.45	-16.83
	16-QAM	23330	793.0	-0.70	1 / 12	23.87	21.02	0.13	38.45	-17.43
	64-QAM	23330	793.0	-0.70	1 / 24	22.88	20.03	0.10	38.45	-18.42

Table 7-5. ERP Data (Band 14)

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 43 of 57

7.7 Radiated Spurious Emissions

§2.1053 §90(S).691(a) §90(R).543(e)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI C63.26-2015 and TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.8
 ANSI C63.26-2015
 TIA-603-E-2016 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 44 of 57

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Test Instrument & Measurement Setup < 1GHz




Figure 7-7. Test Instrument & Measurement Setup >1 GHz


Test Notes

1. For LTE mode, the device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1 RB.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
4. The "-" shown in the following RSE tables are used to denote a noise floor measurement.


FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 45 of 57

7.7.1 Antenna C (Port A) Radiated Spurious Emissions Measurements

LTE Band 26



Plot 7-43. Radiated Spurious Emissions Below 1GHz (Band 26)



Plot 7-44. Radiated Spurious Emissions Above 1GHz (Band 26)

FCC ID: BCGA2429		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 46 of 57

Bandwidth (MHz):	5
Frequency (MHz):	816.5
Modulation Signal:	QPSK

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1633.0	H	-	-	-76.20	-4.70	26.10	-69.15	-13.00	-56.15
2449.5	H	-	-	-76.67	0.07	30.40	-64.86	-13.00	-51.86
3266.0	H	-	-	-77.22	1.59	31.37	-63.88	-13.00	-50.88

Table 7-6. Radiated Spurious Data (LTE Band 26 – Low Channel)


Bandwidth (MHz):	5
Frequency (MHz):	821.5
Modulation Signal:	QPSK

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1643.0	H	-	-	-76.13	-4.64	26.23	-69.03	-13.00	-56.03
2464.5	H	-	-	-76.77	0.20	30.43	-64.82	-13.00	-51.82
3286.0	H	-	-	-77.57	1.66	31.09	-64.17	-13.00	-51.17


Table 7-7. Radiated Spurious Data (LTE Band 26 – High Channel)

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 47 of 57

LTE Band 14



Plot 7-45. Radiated Spurious Emissions Below 1GHz (Band 14)



Plot 7-46. Radiated Spurious Emissions Above 1GHz (Band 14)

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 48 of 57

Bandwidth (MHz):	5
Frequency (MHz):	790.5
Modulation Signal:	QPSK

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1581.0	H	-	-	-75.32	-0.85	30.83	-64.43	-40.00	-24.43
2371.5	H	-	-	-76.28	1.30	32.02	-63.24	-13.00	-50.24
3162.0	H	-	-	-76.54	2.53	32.99	-62.27	-13.00	-49.27
3952.5	H	-	-	-76.19	3.96	34.77	-60.49	-13.00	-47.49

Table 7-8. Radiated Spurious Data (LTE Band 14 – Low Channel)

Bandwidth (MHz):	5
Frequency (MHz):	793.0
Modulation Signal:	QPSK

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1586.0	H	-	-	-75.37	-0.85	30.78	-64.48	-40.00	-24.48
2379.0	H	-	-	-76.26	1.36	32.10	-63.16	-13.00	-50.16
3172.0	H	-	-	-77.25	2.47	32.22	-63.04	-13.00	-50.04

Table 7-9. Radiated Spurious Data (LTE Band 14 – Mid Channel)

Bandwidth (MHz):	5
Frequency (MHz):	795.5
Modulation Signal:	QPSK

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1591.0	H	-	-	-76.50	-0.64	29.86	-65.40	-40.00	-25.40
2386.5	H	-	-	-77.15	1.14	30.99	-64.27	-13.00	-51.27
3182.0	H	-	-	-78.01	2.39	31.38	-63.88	-13.00	-50.88

Table 7-10. Radiated Spurious Data (LTE Band 14 – High Channel)

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 49 of 57

7.7.2 Antenna D (Port B) Radiated Spurious Emissions Measurements

LTE Band 26

Bandwidth (MHz):	5
Frequency (MHz):	816.5
Modulation Signal:	QPSK

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1633.0	V	-	-	-76.06	-4.70	26.24	-69.01	-13.00	-56.01
2449.5	V	-	-	-76.37	0.07	30.70	-64.56	-13.00	-51.56
3266.0	V	-	-	-77.03	1.59	31.56	-63.69	-13.00	-50.69

Table 7-11. Radiated Spurious Data (LTE Band 26 – Low Channel)

Bandwidth (MHz):	5
Frequency (MHz):	821.5
Modulation Signal:	QPSK

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1643.0	V	-	-	-76.18	-4.64	26.18	-69.08	-13.00	-56.08
2464.5	V	-	-	-76.57	0.20	30.63	-64.62	-13.00	-51.62
3286.0	V	-	-	-77.58	1.66	31.08	-64.18	-13.00	-51.18

Table 7-12. Radiated Spurious Data (LTE Band 26 – High Channel)

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 50 of 57

LTE Band 14

Bandwidth (MHz):	5
Frequency (MHz):	790.5
Modulation Signal:	QPSK

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1581.0	V	-	-	-76.03	-4.62	26.35	-68.91	-40.00	-28.91
2371.5	V	-	-	-76.15	-1.08	29.77	-65.49	-13.00	-52.49
3162.0	V	-	-	-77.26	1.37	31.11	-64.14	-13.00	-51.14
3952.5	V	-	-	-77.66	2.46	31.80	-63.45	-13.00	-50.45

Table 7-13. Radiated Spurious Data (LTE Band 14 – Low Channel)

Bandwidth (MHz):	5
Frequency (MHz):	793.0
Modulation Signal:	QPSK

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1586.0	V	-	-	-75.89	-1.06	30.05	-65.21	-40.00	-25.21
2379.0	V	-	-	-76.27	1.21	31.94	-63.32	-13.00	-50.32
3172.0	V	-	-	-77.30	2.53	32.23	-63.02	-13.00	-50.02
3965.0	V	-	-	-77.69	4.16	33.47	-61.78	-13.00	-48.78

Table 7-14. Radiated Spurious Data (LTE Band 14 – Mid Channel)

Bandwidth (MHz):	5
Frequency (MHz):	795.5
Modulation Signal:	QPSK

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1591.0	V	-	-	-76.04	-0.90	30.06	-65.20	-40.00	-25.20
2386.5	V	-	-	-75.92	1.05	32.13	-63.12	-13.00	-50.12
3182.0	V	-	-	-77.21	2.33	32.12	-63.14	-13.00	-50.14
3977.5	V	-	-	-77.08	4.23	34.15	-61.11	-13.00	-48.11

Table 7-15. Radiated Spurious Data (LTE Band 14 – High Channel)

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 51 of 57

7.8 Frequency Stability / Temperature Variation §2.1055 §90.213

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Test Procedure Used

ANSI C63.26 2015
TIA-603-E-2016

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup



Figure 7-8. Test Instrument & Measurement Setup

Test Notes

All ports were tested and only the worst case data were reported.

FCC ID: BCGA2429	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 52 of 57

Frequency Stability / Temperature Variation

§2.1055, §90.213

Operating Frequency (Hz):	819,000,000
Ref. Voltage (VDC):	3.80
Deviation Limit:	± 0.00025% or 2.5 ppm

Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	- 30	819,000,007	7	0.0000009
		- 20	819,000,013	13	0.0000016
		- 10	819,000,011	11	0.0000013
		0	819,000,008	8	0.0000010
		+ 10	819,000,006	6	0.0000007
		+ 20 (Ref)	819,000,017	17	0.0000021
		+ 30	819,000,007	7	0.0000009
		+ 40	819,000,003	3	0.0000004
		+ 50	819,000,012	12	0.0000015
Battery Endpoint	3.40	+ 20	819,000,004	4	0.0000005

Table 7-16. Frequency Stability Data (LTE Band 26 – 10MHz QPSK – Full RB Configuration)

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 53 of 57

Frequency Stability / Temperature Variation

§2.1055, §90.213




Figure 7-9. Frequency Stability Chart (LTE Band 26 – 10MHz QPSK – Full RB Configuration)

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 54 of 57

Frequency Stability / Temperature Variation

§2.1055, §90.213

Operating Frequency (Hz):	793,000,000
Ref. Voltage (VDC):	3.80

Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	- 30	793,000,006	6	0.0000008
		- 20	793,000,012	12	0.0000015
		- 10	793,000,005	5	0.0000006
		0	793,000,006	6	0.0000008
		+ 10	793,000,007	7	0.0000009
		+ 20 (Ref)	793,000,007	7	0.0000009
		+ 30	793,000,007	7	0.0000009
		+ 40	793,000,010	10	0.0000013
		+ 50	793,000,005	5	0.0000006
Battery Endpoint	3.40	+ 20	793,000,003	3	0.0000004

Table 7-17. Frequency Stability Data (LTE Band 14 – 10MHz QPSK – Full RB Configuration)

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 55 of 57

Frequency Stability / Temperature Variation

§2.1055, §90.213




Figure 7-10. Frequency Stability Chart (LTE Band 14 – 10MHz QPSK – Full RB Configuration)

FCC ID: BCGA2429	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 56 of 57

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Apple Tablet Device** **FCC ID: BCGA2429** complies with all the requirements of Part 90 of the FCC rules.

FCC ID: BCGA2429	 Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270034-04.BCG	Test Dates: 05/01/2020 - 07/29/2020	EUT Type: Tablet Device	Page 57 of 57