



SAR EVALUATION REPORT

Applicant Name:
Apple Inc.
One Apple Park Way
Cupertino, CA 95014 USA

Date of Testing:
06/07/2020-07/20/2020
Test Site/Location:
PCTEST Lab, Morgan Hill, CA, USA
Document Serial No.:
1C2004270034-01.BCG


FCC ID: BCGA2429
APPLICANT: APPLE, INC.

DUT Type: Tablet Device
Application Type: Certification
FCC Rule Part(s): CFR §2.1093
Model: A2429, A2430

Equipment Class	Band & Mode	Tx Frequency	SAR
			1g Body (W/kg)
PCB	GPRS/EDGE 850	824.20 - 848.80 MHz	1.08
PCB	GPRS/EDGE 1900	1850.20 - 1909.80 MHz	1.00
PCB	UMTS 850	826.40 - 846.60 MHz	1.08
PCB	UMTS 1750	1712.4 - 1752.6 MHz	1.00
PCB	UMTS 1900	1852.4 - 1907.6 MHz	1.05
PCB	LTE Band 12	699.7 - 715.3 MHz	0.93
PCB	LTE Band 17	706.5 - 713.5 MHz	N/A
PCB	LTE Band 13	779.5 - 784.5 MHz	0.87
PCB	LTE Band 14	790.5 - 795.5 MHz	0.80
PCB	LTE Band 26 (Cell)	814.7 - 848.3 MHz	1.10
PCB	LTE Band 5 (Cell)	824.7 - 848.3 MHz	1.00
PCB	LTE Band 66 (AWS)	1710.7 - 1779.3 MHz	0.95
PCB	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	N/A
PCB	LTE Band 25 (PCS)	1850.7 - 1914.3 MHz	1.01
PCB	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	N/A
PCB	LTE Band 30	2307.5 - 2312.5 MHz	0.78
PCB	LTE Band 7	2502.5 - 2567.5 MHz	0.92
PCB	LTE Band 41	2498.5 - 2687.5 MHz	1.12
DTS	2.4 GHz WLAN	2412 - 2472 MHz	0.87
NII	U-NII-1	5180 - 5240 MHz	N/A
NII	U-NII-2A	5260 - 5320 MHz	0.88
NII	U-NII-2C	5500 - 5720 MHz	1.07
NII	U-NII-3	5745 - 5825 MHz	0.94
DSS/DTS	Bluetooth	2402 - 2480 MHz	0.90
Simultaneous SAR per KDB 690783 D01v01r03:			1.33

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.7 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



The SAR Tick is an initiative of the Mobile & Wireless Forum (MWF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MWF. Further details can be obtained by emailing: sartick@mwfai.info.

FCC ID: BCGA2429		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 1 of 114

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	20
3	INTRODUCTION	21
4	DOSIMETRIC ASSESSMENT	22
5	TEST CONFIGURATION POSITIONS	23
6	RF EXPOSURE LIMITS	24
7	FCC MEASUREMENT PROCEDURES.....	25
8	RF CONDUCTED POWERS.....	30
9	SYSTEM VERIFICATION.....	83
10	SAR DATA SUMMARY	85
11	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	103
12	SAR MEASUREMENT VARIABILITY	107
13	ADDITIONAL TESTING PER FCC GUIDANCE	108
14	EQUIPMENT LIST.....	110
15	MEASUREMENT UNCERTAINTIES.....	111
16	CONCLUSION.....	112
17	REFERENCES	113
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: SAR TISSUE SPECIFICATIONS		
APPENDIX D: SAR SYSTEM VALIDATION		
APPENDIX E: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		
APPENDIX F: DOWNLINK LTE CA RF CONDUCTED POWERS		
APPENDIX G: POWER REDUCTION VERIFICATION		
APPENDIX H: PROBE AND DIPOLE CALIBRATION CERTIFICATES		

FCC ID: BCGA2429	 PCTEST Proud to be part of 	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 2 of 114

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GPRS/EDGE 850	Data	824.20 - 848.80 MHz
GPRS/EDGE 1900	Data	1850.20 - 1909.80 MHz
UMTS 850	Data	826.40 - 846.60 MHz
UMTS 1750	Data	1712.4 - 1752.6 MHz
UMTS 1900	Data	1852.4 - 1907.6 MHz
LTE Band 12	Data	699.7 - 715.3 MHz
LTE Band 17	Data	706.5 - 713.5 MHz
LTE Band 13	Data	779.5 - 784.5 MHz
LTE Band 14	Data	790.5 - 795.5 MHz
LTE Band 26 (Cell)	Data	814.7 - 848.3 MHz
LTE Band 5 (Cell)	Data	824.7 - 848.3 MHz
LTE Band 66 (AWS)	Data	1710.7 - 1779.3 MHz
LTE Band 4 (AWS)	Data	1710.7 - 1754.3 MHz
LTE Band 25 (PCS)	Data	1850.7 - 1914.3 MHz
LTE Band 2 (PCS)	Data	1850.7 - 1909.3 MHz
LTE Band 30	Data	2307.5 - 2312.5 MHz
LTE Band 7	Data	2502.5 - 2567.5 MHz
LTE Band 41	Data	2498.5 - 2687.5 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2472 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5720 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz

1.2 Power Reduction for SAR

This device uses the manufacturer's proprietary motion detect mode to determine proximity to the user's body and set the licensed power level accordingly for SAR compliance. When being used in the hand or the body, the output power for licensed transmitters will always be reduced. Per FCC KDB Guidance, SAR testing was performed only using reduced output powers following the test positions in KDB Publication 616217.

This device additionally utilizes a power reduction mechanism for Bluetooth operations. When Bluetooth is operating simultaneously with 5 GHz WLAN, the output power is permanently reduced. SAR evaluations were additionally performed at the maximum allowed output power for these scenarios to evaluate simultaneous transmission compliance.

Detailed descriptions of the power reduction mechanisms are included in the operational description. The power reduction mechanisms were confirmed during the SAR Evaluation. Section 8.5 and Appendix G contains a summary of the verification results.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 3 of 114

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 2G/3G/4G Output Power for Portable Use Conditions

Table 1-1
GPRS/EDGE 850

Antenna	Mode/Band	Data- Burst Average GMSK (in dBm)		Data - Burst Average 8-PSK (in dBm)	
		1 TX Slots	2 TX Slots	1 TX Slots	2 TX Slots
Ant C	Max allowed power	27.75	24.75	24.75	23.75
	Nominal	27.00	24.00	24.00	23.00
Ant D	Max allowed power	28.25	25.50	22.75	21.75
	Nominal	27.50	24.75	22.00	21.00

Table 1-2
GPRS/EDGE 1900

Antenna	Mode/Band	Data- Burst Average GMSK (in dBm)		Data - Burst Average 8-PSK (in dBm)	
		1 TX Slots	2 TX Slots	1 TX Slots	2 TX Slots
Ant C	Max allowed power	21.95	18.95	21.95	18.95
	Nominal	21.20	18.20	21.20	18.20
Ant D	Max allowed power	21.25	18.25	21.25	18.25
	Nominal	20.50	17.50	20.50	17.50

Table 1-3
UMTS B5 (850 MHz)

Antenna	Mode/Band	Modulated Average Output Power (in dBm)			
		3GPP WCDMA Rel 99	3GPP HSDPA Rel 5	3GPP HSUPA Rel 6	3GPP DC- HSDPA Rel 8
Ant C	Max allowed power	17.70	17.70	17.70	17.70
	Nominal	17.20	17.20	17.20	17.20
AntD	Max allowed power	19.20	19.20	19.20	19.20
	Nominal	18.70	18.70	18.70	18.70

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 4 of 114

Table 1-4
UMTS B4 (1750 MHz)

Antenna	Mode/Band	Modulated Average Output Power (in dBm)			
		3GPP WCDMA Rel 99	3GPP HSDPA Rel 5	3GPP HSUPA Rel 6	3GPP DC-HSDPA Rel 8
Ant C	Max allowed power	13.30	13.30	13.30	13.30
	Nominal	12.80	12.80	12.80	12.80
Ant D	Max allowed power	13.20	13.20	13.20	13.20
	Nominal	12.70	12.70	12.70	12.70

Table 1-5
UMTS B2 (1900 MHz)

Antenna	Mode/Band	Modulated Average Output Power (in dBm)			
		3GPP WCDMA Rel 99	3GPP HSDPA Rel 5	3GPP HSUPA Rel 6	3GPP DC- HSDPA Rel 8
Ant C	Max allowed power	13.10	13.10	13.10	13.10
	Nominal	12.60	12.60	12.60	12.60
Ant D	Max allowed power	12.00	12.00	12.00	12.00
	Nominal	11.50	11.50	11.50	11.50

FCC ID: BCGA2429	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 5 of 114

**Table 1-6
LTE Bands**

Mode / Band		Modulated Average Output Power (in dBm)	
		Ant C	Ant D
LTE FDD Band 12	Max allowed power	17.50	17.20
	Nominal	17.00	16.70
LTE FDD Band 17	Max allowed power	17.50	17.20
	Nominal	17.00	16.70
LTE FDD Band 13	Max allowed power	18.10	18.30
	Nominal	17.60	17.80
LTE FDD Band 14	Max allowed power	18.10	18.30
	Nominal	17.60	17.80
LTE FDD Band 26	Max allowed power	18.20	18.20
	Nominal	17.70	17.70
LTE FDD Band 5	Max allowed power	17.70	19.20
	Nominal	17.20	18.70
LTE FDD Band 4	Max allowed power	13.30	13.20
	Nominal	12.80	12.70
LTE FDD Band 66	Max allowed power	13.30	13.20
	Nominal	12.80	12.70
LTE FDD Band 2	Max allowed power	13.10	12.00
	Nominal	12.60	11.50
LTE FDD Band 25	Max allowed power	13.10	12.00
	Nominal	12.60	11.50
LTE FDD Band 30	Max allowed power	13.20	12.80
	Nominal	12.70	12.30
LTE FDD Band 7	Max allowed power	12.40	12.40
	Nominal	11.90	11.90
LTE FDD Band 7 Intra-band ULCA	Max allowed power	12.40	12.40
	Nominal	11.40	11.40
LTE TDD Band 41 (PC3)	Max allowed power	15.40	15.40
	Nominal	14.90	14.90
LTE TDD Band 41 (PC3) Intra-band ULCA	Max allowed power	15.40	15.40
	Nominal	14.40	14.40
LTE TDD Band 41 (PC2)	Max allowed power	15.40	15.40
	Nominal	14.90	14.90

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 6 of 114

1.3.2 Unlicensed Maximum Output Power

Mode/ Band	Channel	IEEE 802.11b (2.4 GHz)		IEEE 802.11g (2.4 GHz)		IEEE 802.11n (2.4 GHz)	
		Maximum	Nominal	Maximum	Nominal	Maximum	Nominal
Modulated Average - Single Tx Chain (dBm) - Antenna A	1	16.00	14.50	15.00	13.50	15.00	13.50
	2	16.00	14.50	16.00	14.50	16.00	14.50
	3	16.00	14.50	16.00	14.50	16.00	14.50
	4	16.00	14.50	16.00	14.50	16.00	14.50
	5	16.00	14.50	16.00	14.50	16.00	14.50
	6	16.00	14.50	16.00	14.50	16.00	14.50
	7	16.00	14.50	16.00	14.50	16.00	14.50
	8	16.00	14.50	16.00	14.50	16.00	14.50
	9	16.00	14.50	16.00	14.50	16.00	14.50
	10	16.00	14.50	16.00	14.50	16.00	14.50
	11	16.00	14.50	14.00	12.50	14.00	12.50
	12	16.00	14.50	11.00	9.50	11.00	9.50
	13	14.00	12.50	2.00	0.50	2.00	0.50

Mode/ Band	Channel	IEEE 802.11g (2.4 GHz)		IEEE 802.11n (2.4 GHz)	
		Maximum	Nominal	Maximum	Nominal
Modulated Average - 2 Tx Chain (dBm) - Antenna A	1	13.50	12.00	13.50	12.00
	2	16.00	14.50	16.00	14.50
	3	16.00	14.50	16.00	14.50
	4	16.00	14.50	16.00	14.50
	5	16.00	14.50	16.00	14.50
	6	16.00	14.50	16.00	14.50
	7	16.00	14.50	16.00	14.50
	8	16.00	14.50	16.00	14.50
	9	16.00	14.50	16.00	14.50
	10	16.00	14.50	16.00	14.50
	11	13.00	11.50	13.00	11.50
	12	10.00	8.50	10.00	8.50
	13	0.00	-1.50	0.00	-1.50

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 7 of 114

Mode/ Band		IEEE 802.11b (2.4 GHz)		IEEE 802.11g (2.4 GHz)		IEEE 802.11n (2.4 GHz)	
	Channel	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal
Modulated Average - Single Tx Chain (dBm) - Antenna B	1	16.00	14.50	15.00	13.50	15.00	13.50
	2	16.00	14.50	16.00	14.50	16.00	14.50
	3	16.00	14.50	16.00	14.50	16.00	14.50
	4	16.00	14.50	16.00	14.50	16.00	14.50
	5	16.00	14.50	16.00	14.50	16.00	14.50
	6	16.00	14.50	16.00	14.50	16.00	14.50
	7	16.00	14.50	16.00	14.50	16.00	14.50
	8	16.00	14.50	16.00	14.50	16.00	14.50
	9	16.00	14.50	16.00	14.50	16.00	14.50
	10	16.00	14.50	16.00	14.50	16.00	14.50
	11	16.00	14.50	14.00	12.50	14.00	12.50
	12	16.00	14.50	11.00	9.50	11.00	9.50
	13	14.00	12.50	2.00	0.50	2.00	0.50

Mode/ Band		IEEE 802.11g (2.4 GHz)		IEEE 802.11n (2.4 GHz)	
	Channel	Maximum	Nominal	Maximum	Nominal
Modulated Average - 2 Tx Chain (dBm) - Antenna B	1	13.50	12.00	13.50	12.00
	2	16.00	14.50	16.00	14.50
	3	16.00	14.50	16.00	14.50
	4	16.00	14.50	16.00	14.50
	5	16.00	14.50	16.00	14.50
	6	16.00	14.50	16.00	14.50
	7	16.00	14.50	16.00	14.50
	8	16.00	14.50	16.00	14.50
	9	16.00	14.50	16.00	14.50
	10	16.00	14.50	16.00	14.50
	11	13.00	11.50	13.00	11.50
	12	10.00	8.50	10.00	8.50
	13	0.00	-1.50	0.00	-1.50

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

Mode / Band		Modulated Average - Single Tx Chain (dBm) - Antenna A
Bluetooth BDR/LE	Maximum	17.00
	Nominal	15.50
Bluetooth EDR	Maximum	12.50
	Nominal	11.00

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 8 of 114

Mode/ Band			IEEE 802.11a (5 GHz)		IEEE 802.11n (5 GHz)		IEEE 802.11ac (5 GHz)	
		Channel	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal
Modulated Average - Single Tx Chain (dBm) - 5GHz Antenna A	20 MHz Bandwidth	36	16.00	14.50	16.00	14.50	16.00	14.50
		40	16.50	15.00	16.50	15.00	16.50	15.00
		44	16.50	15.00	16.50	15.00	16.50	15.00
		48	16.50	15.00	16.50	15.00	16.50	15.00
		52	17.00	15.50	17.00	15.50	17.00	15.50
		56	17.00	15.50	17.00	15.50	17.00	15.50
		60	17.00	15.50	17.00	15.50	17.00	15.50
		64	16.00	14.50	16.00	14.50	16.00	14.50
		100	15.00	13.50	15.00	13.50	15.00	13.50
		104	17.50	16.00	17.50	16.00	17.50	16.00
		108	17.50	16.00	17.50	16.00	17.50	16.00
		112	17.50	16.00	17.50	16.00	17.50	16.00
		116	17.50	16.00	17.50	16.00	17.50	16.00
		120	17.50	16.00	17.50	16.00	17.50	16.00
		124	17.50	16.00	17.50	16.00	17.50	16.00
		128	17.50	16.00	17.50	16.00	17.50	16.00
		132	17.50	16.00	17.50	16.00	17.50	16.00
		136	17.50	16.00	17.50	16.00	17.50	16.00
		140	14.00	12.50	14.00	12.50	14.00	12.50
		144	17.50	16.00	17.50	16.00	17.50	16.00
		149	16.25	14.75	16.25	14.75	16.25	14.75
		153	16.25	14.75	16.25	14.75	16.25	14.75
		157	16.25	14.75	16.25	14.75	16.25	14.75
		161	16.25	14.75	16.25	14.75	16.25	14.75
		165	16.25	14.75	16.25	14.75	16.25	14.75
	40 MHz Bandwidth	38			13.00	11.50	13.00	11.50
		46			16.50	15.00	16.50	15.00
		54			17.00	15.50	17.00	15.50
		62			14.50	13.00	14.50	13.00
		102			12.50	11.00	12.50	11.00
		110			17.50	16.00	17.50	16.00
		118			17.50	16.00	17.50	16.00
		126			17.50	16.00	17.50	16.00
		134			15.00	13.50	15.00	13.50
		142			17.50	16.00	17.50	16.00
		151			16.25	14.75	16.25	14.75
		159			16.25	14.75	16.25	14.75
	80 MHz Bandwidth	42					11.50	10.00
		58					12.00	10.50
		106					12.00	10.50
		122					15.50	14.00
		138					17.50	16.00
		155					15.00	13.50

FCC ID: BCGA2429	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 9 of 114	

Mode/ Band			IEEE 802.11a (5 GHz)		IEEE 802.11n (5 GHz)		IEEE 802.11ac (5 GHz)	
		Channel	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal
Modulated Average - 2 Tx Chain (dBm) CDD - 5GHz Antenna A	20 MHz Bandwidth	36	15.00	13.50	15.00	13.50	15.00	13.50
		40	16.50	15.00	16.50	15.00	16.50	15.00
		44	16.50	15.00	16.50	15.00	16.50	15.00
		48	16.50	15.00	16.50	15.00	16.50	15.00
		52	16.50	15.00	16.50	15.00	16.50	15.00
		56	16.50	15.00	16.50	15.00	16.50	15.00
		60	16.50	15.00	16.50	15.00	16.50	15.00
		64	14.50	13.00	14.50	13.00	14.50	13.00
		100	14.50	13.00	14.50	13.00	14.50	13.00
		104	15.50	14.00	15.50	14.00	15.50	14.00
		108	15.50	14.00	15.50	14.00	15.50	14.00
		112	15.50	14.00	15.50	14.00	15.50	14.00
		116	15.50	14.00	15.50	14.00	15.50	14.00
		120	15.50	14.00	15.50	14.00	15.50	14.00
		124	15.50	14.00	15.50	14.00	15.50	14.00
		128	15.50	14.00	15.50	14.00	15.50	14.00
		132	15.50	14.00	15.50	14.00	15.50	14.00
		136	15.50	14.00	15.50	14.00	15.50	14.00
		140	13.00	11.50	13.00	11.50	13.00	11.50
		144	15.50	14.00	15.50	14.00	15.50	14.00
		149	16.25	14.75	16.25	14.75	16.25	14.75
		153	16.25	14.75	16.25	14.75	16.25	14.75
		157	16.25	14.75	16.25	14.75	16.25	14.75
		161	16.25	14.75	16.25	14.75	16.25	14.75
		165	16.25	14.75	16.25	14.75	16.25	14.75
	40 MHz Bandwidth	38			11.50	10.00	11.50	10.00
		46			16.50	15.00	16.50	15.00
		54			16.00	14.50	16.00	14.50
		62			11.50	10.00	11.50	10.00
		102			11.50	10.00	11.50	10.00
		110			17.00	15.50	17.00	15.50
		118			17.50	16.00	17.50	16.00
		126			17.50	16.00	17.50	16.00
		134			13.00	11.50	13.00	11.50
		142			17.50	16.00	17.50	16.00
	80 MHz Bandwidth	151			16.25	14.75	16.25	14.75
		159			16.25	14.75	16.25	14.75
		42					10.00	8.50
		58					10.50	9.00
		106					10.50	9.00
		122					14.00	12.50
		138					17.50	16.00
		155					14.00	12.50

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 10 of 114

Mode/ Band			IEEE 802.11n (5 GHz)		IEEE 802.11ac (5 GHz)	
		Channel	Maximum	Nominal	Maximum	Nominal
Modulated Average - 2 Tx Chain (dBm) SDM - 5GHz Antenna A	20 MHz Bandwidth	36	15.00	13.50	15.00	13.50
		40	16.50	15.00	16.50	15.00
		44	16.50	15.00	16.50	15.00
		48	16.50	15.00	16.50	15.00
		52	17.00	15.50	17.00	15.50
		56	17.00	15.50	17.00	15.50
		60	17.00	15.50	17.00	15.50
		64	14.50	13.00	14.50	13.00
		100	14.50	13.00	14.50	13.00
		104	17.50	16.00	17.50	16.00
		108	17.50	16.00	17.50	16.00
		112	17.50	16.00	17.50	16.00
		116	17.50	16.00	17.50	16.00
		120	17.50	16.00	17.50	16.00
		124	17.50	16.00	17.50	16.00
		128	17.50	16.00	17.50	16.00
		132	17.50	16.00	17.50	16.00
		136	17.50	16.00	17.50	16.00
		140	13.00	11.50	13.00	11.50
		144	17.50	16.00	17.50	16.00
		149	16.25	14.75	16.25	14.75
		153	16.25	14.75	16.25	14.75
		157	16.25	14.75	16.25	14.75
		161	16.25	14.75	16.25	14.75
		165	16.25	14.75	16.25	14.75
	40 MHz Bandwidth	38	11.50	10.00	11.50	10.00
		46	16.50	15.00	16.50	15.00
		54	16.00	14.50	16.00	14.50
		62	11.50	10.00	11.50	10.00
		102	11.50	10.00	11.50	10.00
		110	17.00	15.50	17.00	15.50
		118	17.50	16.00	17.50	16.00
		126	17.50	16.00	17.50	16.00
		134	13.00	11.50	13.00	11.50
		142	17.50	16.00	17.50	16.00
		151	16.25	14.75	16.25	14.75
		159	16.25	14.75	16.25	14.75
	80 MHz Bandwidth	42			10.00	8.50
		58			10.50	9.00
		106			10.50	9.00
		122			14.00	12.50
		138			17.50	16.00
		155			14.00	12.50

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 11 of 114

Mode/ Band			IEEE 802.11a (5 GHz)		IEEE 802.11n (5 GHz)		IEEE 802.11ac (5 GHz)	
		Channel	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal
Modulated Average - Single Tx Chain (dBm) - 5GHz Antenna B	20 MHz Bandwidth	36	16.00	14.50	16.00	14.50	16.00	14.50
		40	16.25	14.75	16.25	14.75	16.25	14.75
		44	16.25	14.75	16.25	14.75	16.25	14.75
		48	16.25	14.75	16.25	14.75	16.25	14.75
		52	16.75	15.25	16.75	15.25	16.75	15.25
		56	16.75	15.25	16.75	15.25	16.75	15.25
		60	16.75	15.25	16.75	15.25	16.75	15.25
		64	16.00	14.50	16.00	14.50	16.00	14.50
		100	15.00	13.50	15.00	13.50	15.00	13.50
		104	17.25	15.75	17.25	15.75	17.25	15.75
		108	17.25	15.75	17.25	15.75	17.25	15.75
		112	17.25	15.75	17.25	15.75	17.25	15.75
		116	17.25	15.75	17.25	15.75	17.25	15.75
		120	17.25	15.75	17.25	15.75	17.25	15.75
		124	17.25	15.75	17.25	15.75	17.25	15.75
		128	17.25	15.75	17.25	15.75	17.25	15.75
		132	17.25	15.75	17.25	15.75	17.25	15.75
		136	17.25	15.75	17.25	15.75	17.25	15.75
		140	14.00	12.50	14.00	12.50	14.00	12.50
		144	17.25	15.75	17.25	15.75	17.25	15.75
		149	16.50	15.00	16.50	15.00	16.50	15.00
		153	16.50	15.00	16.50	15.00	16.50	15.00
		157	16.50	15.00	16.50	15.00	16.50	15.00
		161	16.50	15.00	16.50	15.00	16.50	15.00
		165	16.50	15.00	16.50	15.00	16.50	15.00
	40 MHz Bandwidth	38			13.00	11.50	13.00	11.50
		46			16.25	14.75	16.25	14.75
		54			16.75	15.25	16.75	15.25
		62			14.50	13.00	14.50	13.00
		102			12.50	11.00	12.50	11.00
		110			17.25	15.75	17.25	15.75
		118			17.25	15.75	17.25	15.75
		126			17.25	15.75	17.25	15.75
		134			15.00	13.50	15.00	13.50
		142			17.25	15.75	17.25	15.75
		151			16.50	15.00	16.50	15.00
		159			16.50	15.00	16.50	15.00
	80 MHz Bandwidth	42					11.50	10.00
		58					12.00	10.50
		106					12.00	10.50
		122					15.50	14.00
		138					17.25	15.75
		155					15.00	13.50

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 12 of 114

Mode/ Band			IEEE 802.11a (5 GHz)		IEEE 802.11n (5 GHz)		IEEE 802.11ac (5 GHz)	
		Channel	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal
Modulated Average - 2 Tx Chain (dBm) CDD - 5GHz Antenna B	20 MHz Bandwidth	36	15.00	13.50	15.00	13.50	15.00	13.50
		40	16.25	14.75	16.25	14.75	16.25	14.75
		44	16.25	14.75	16.25	14.75	16.25	14.75
		48	16.25	14.75	16.25	14.75	16.25	14.75
		52	16.50	15.00	16.50	15.00	16.50	15.00
		56	16.50	15.00	16.50	15.00	16.50	15.00
		60	16.50	15.00	16.50	15.00	16.50	15.00
		64	14.50	13.00	14.50	13.00	14.50	13.00
		100	14.50	13.00	14.50	13.00	14.50	13.00
		104	15.50	14.00	15.50	14.00	15.50	14.00
		108	15.50	14.00	15.50	14.00	15.50	14.00
		112	15.50	14.00	15.50	14.00	15.50	14.00
		116	15.50	14.00	15.50	14.00	15.50	14.00
		120	15.50	14.00	15.50	14.00	15.50	14.00
		124	15.50	14.00	15.50	14.00	15.50	14.00
		128	15.50	14.00	15.50	14.00	15.50	14.00
		132	15.50	14.00	15.50	14.00	15.50	14.00
		136	15.50	14.00	15.50	14.00	15.50	14.00
		140	13.00	11.50	13.00	11.50	13.00	11.50
		144	15.50	14.00	15.50	14.00	15.50	14.00
	40 MHz Bandwidth	149	16.50	15.00	16.50	15.00	16.50	15.00
		153	16.50	15.00	16.50	15.00	16.50	15.00
		157	16.50	15.00	16.50	15.00	16.50	15.00
		161	16.50	15.00	16.50	15.00	16.50	15.00
		165	16.50	15.00	16.50	15.00	16.50	15.00
		38			11.50	10.00	11.50	10.00
		46			16.25	14.75	16.25	14.75
		54			16.00	14.50	16.00	14.50
		62			11.50	10.00	11.50	10.00
		102			11.50	10.00	11.50	10.00
	80 MHz Bandwidth	110			17.00	15.50	17.00	15.50
		118			17.25	15.75	17.25	15.75
		126			17.25	15.75	17.25	15.75
		134			13.00	11.50	13.00	11.50
		142			17.25	15.75	17.25	15.75
		151			16.50	15.00	16.50	15.00
		159			16.50	15.00	16.50	15.00
		42					10.00	8.50
		58					10.50	9.00
		106					10.50	9.00
		122					14.00	12.50
		138					17.25	15.75
		155					14.00	12.50

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 13 of 114

Mode/ Band			IEEE 802.11n (5 GHz)		IEEE 802.11ac (5 GHz)	
		Channel	Maximum	Nominal	Maximum	Nominal
Modulated Average - 2 Tx Chain (dBm) SDM - 5GHz Antenna B	20 MHz Bandwidth	36	15.00	13.50	15.00	13.50
		40	16.25	14.75	16.25	14.75
		44	16.25	14.75	16.25	14.75
		48	16.25	14.75	16.25	14.75
		52	16.75	15.25	16.75	15.25
		56	16.75	15.25	16.75	15.25
		60	16.75	15.25	16.75	15.25
		64	14.50	13.00	14.50	13.00
		100	14.50	13.00	14.50	13.00
		104	17.25	15.75	17.25	15.75
		108	17.25	15.75	17.25	15.75
		112	17.25	15.75	17.25	15.75
		116	17.25	15.75	17.25	15.75
		120	17.25	15.75	17.25	15.75
		124	17.25	15.75	17.25	15.75
		128	17.25	15.75	17.25	15.75
		132	17.25	15.75	17.25	15.75
		136	17.25	15.75	17.25	15.75
		140	13.00	11.50	13.00	11.50
		144	17.25	15.75	17.25	15.75
		149	16.50	15.00	16.50	15.00
		153	16.50	15.00	16.50	15.00
		157	16.50	15.00	16.50	15.00
		161	16.50	15.00	16.50	15.00
		165	16.50	15.00	16.50	15.00
	40 MHz Bandwidth	38	11.50	10.00	11.50	10.00
		46	16.25	14.75	16.25	14.75
		54	16.00	14.50	16.00	14.50
		62	11.50	10.00	11.50	10.00
		102	11.50	10.00	11.50	10.00
		110	17.00	15.50	17.00	15.50
		118	17.25	15.75	17.25	15.75
		126	17.25	15.75	17.25	15.75
		134	13.00	11.50	13.00	11.50
		142	17.25	15.75	17.25	15.75
		151	16.50	15.00	16.50	15.00
		159	16.50	15.00	16.50	15.00
	80 MHz Bandwidth	42			10.00	8.50
		58			10.50	9.00
		106			10.50	9.00
		122			14.00	12.50
		138			17.25	15.75
		155			14.00	12.50

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2429	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 14 of 114

1.3.3 Reduced Output Power

Mode / Band		Modulated Average - Single Tx Chain (dBm) - Antenna A
Bluetooth BDR/LE	Maximum	10.00
	Nominal	8.50
Bluetooth EDR	Maximum	10.00
	Nominal	8.50

Note: Bluetooth operations on Antenna A are reduced in output power when it is operating simultaneously with 5 GHz WLAN. Detailed description of the power reduction mechanism is included in the operational description.

FCC ID: BCGA2429	 PCTEST Proud to be part of 		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 15 of 114

1.4 DUT Antenna Locations

The overall diagonal dimension of the device is > 200 mm. A diagram showing the location of the device antennas can be found in Appendix E. Exact antenna dimensions and separation distances are shown in the Technical Descriptions in the FCC filings

Table 1-1
Device Edges/Sides for SAR Testing

Device Sides/Edges for SAR Testing						
Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850 Antenna C	Yes	No	Yes	No	Yes	No
GPRS 1900 Antenna C	Yes	No	Yes	No	Yes	No
UMTS 850 Antenna C	Yes	No	Yes	No	Yes	No
UMTS 1750 Antenna C	Yes	No	Yes	No	Yes	No
UMTS 1900 Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 12 Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 13 Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 14 Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 5 (Cell) Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 26 (Cell) Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 66 (AWS) Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 25 (PCS) Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 30 Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 7 Antenna C	Yes	No	Yes	No	Yes	No
LTE Band 41 Antenna C	Yes	No	Yes	No	Yes	No
GPRS 850 Antenna D	Yes	No	Yes	No	No	Yes
GPRS 1900 Antenna D	Yes	No	Yes	No	No	Yes
UMTS 850 Antenna D	Yes	No	Yes	No	No	Yes
UMTS 1750 Antenna D	Yes	No	Yes	No	No	Yes
UMTS 1900 Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 12 Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 13 Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 14 Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 5 (Cell) Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 26 (Cell) Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 66 (AWS) Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 25 (PCS) Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 30 Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 7 Antenna D	Yes	No	Yes	No	No	Yes
LTE Band 41 Antenna D	Yes	No	Yes	No	No	Yes
2.4 GHz WLAN Antenna A	Yes	No	No	Yes	No	Yes
2.4 GHz WLAN Antenna B	Yes	No	No	Yes	Yes	No
5 GHz WLAN Antenna A	Yes	No	No	Yes	No	Yes
5 GHz WLAN Antenna B	Yes	No	No	Yes	Yes	No
Bluetooth Antenna A	Yes	No	No	Yes	No	Yes

Note: Per FCC KDB Publication 616217 D04v01r01, particular edges were not required to be evaluated for SAR based on the SAR exclusion threshold in KDB 447498 D01V06. Additional edges may have been evaluated for simultaneous transmission analysis.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 16 of 114

1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds.

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Body
1	Cellular Band + 2.4 GHz WI-FI	Yes
2	Cellular Band + 5 GHz WI-FI	Yes
3	Cellular Band + 2.4 GHz Bluetooth	Yes
4	Cellular Band + 2.4 GHz WI-FI MIMO	Yes
5	Cellular Band + 5 GHz WI-FI MIMO	Yes
6	Cellular Band + 2.4 GHz Bluetooth + 5 GHz WI-FI	Yes
7	Cellular Band + 2.4 GHz Bluetooth + 5 GHz WI-FI MIMO	Yes
8	2.4 GHz Bluetooth + 5 GHz WI-FI	Yes
9	2.4 GHz Bluetooth + 5 GHz WI-FI MIMO	Yes

1. There are no limitations in the above listed simultaneous transmissions scenarios between cellular antennas and BT/WI-FI antennas.
2. 2.4 GHz WLAN and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
3. All licensed modes share the same antenna path and cannot transmit simultaneously.
4. This device supports 2x2 MIMO Tx for WLAN 802.11 a/g/n/ac supports CDD/STBC and 802.11n/ac additionally supports SDM. Each WLAN antenna can transmit independently or together when operating with MIMO.
5. This device support VoWIFI.

1.6 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Based on the maximum allowed power for the respective antennas, U-NII-2A was evaluated for Antenna A and Antenna B SAR. Additional testing for U-NII-1 Antenna A and Antenna B SAR was not required since all reported SAR was less than 1.2 W/kg per FCC KDB Publication 248227 D01v02r02.

The WLAN/Bluetooth chipset in this device is produced by two different suppliers. The electrically identical modules are manufactured with the identical mechanical structure to meet the same specifications and functions. Two device variants are referenced as Variant 1 and Variant 2 in this report. WLAN/Bluetooth SAR

FCC ID: BCGA2429	 PCTEST Proud to be part of 	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 17 of 114

worst case configuration was spotchecked on Variant 1 and Variant 2. The Variant with the highest reported SAR value was evaluated for the remaining WLAN/Bluetooth configurations.

This device supports channel 1-13 for 2.4 GHz WLAN. However, because channel 12/13 targets are not higher than that of channels 1-11, channels 1, 6, and 11 were considered for SAR testing per FCC KDB 248227 D01V02r02

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) TDWR and Band gap channels are supported

(B) Licensed Transmitter(s)

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

This device supports LTE Carrier Aggregation (CA) in the downlink. All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive. The downlink carrier aggregation exclusion analysis can be found in Appendix H.

This device supports LTE capabilities with overlapping transmission frequency ranges. When the supported frequency range of an LTE Band falls completely within an LTE band with a larger transmission frequency range, both LTE bands have the same target power (or the band with the larger transmission frequency range has a higher target power), and both LTE bands share the same transmission path and signal characteristics, SAR was only assessed for the band with the larger transmission frequency range.

This device supports 64QAM on the uplink and 256QAM on the downlink for LTE Operations. Conducted powers for 64QAM uplink configurations were measured per Section 5.1 of FCC KDB Publication 941225 D05v02r05. SAR was not required for 64QAM since the highest maximum output power for 64 QAM is $\leq \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg, per Section 5.2.4 of FCC KDB Publication 941225 D05v02r05.

This device supports both Power Class 2 (PC2) and Power Class 3 (PC3) for LTE Band 41. Per May 2017 TCB Workshop Notes, SAR tests were performed with Power Class 3 (given the specific UL/DL limitations for Power Class 2). Additionally, SAR testing for the power class condition was evaluated for the highest configuration in Power Class 3 for each test configuration to confirm the results were scalable linearly (See Section 13).

This device supports LTE Carrier Aggregation (CA) for LTE Band 7 and LTE Band 41 with two component carriers in the uplink. LTE Band 41 ULCA only supported in PC3. SAR Measurements and conducted powers were evaluated per 2017 Fall TCB Workshop Notes.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 18 of 114

1.7 Guidance Applied

- FCC KDB Publication 941225 D01v03r01, D05v02r04, D05Av01r02, D06v02r01 (2G/3G/4G)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 616217 D04v01r02 (Tablet)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)
- May 2017 TCB Workshop Notes (LTE Band 41 Power Class 2/3)
- April 2018 TCB Workshop Notes (LTE Carrier Aggregation)

1.8 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 10.

FCC ID: BCGA2429	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 19 of 114

LTE Information				
Form Factor	Tablet Device			
Frequency Range of each LTE transmission band	LTE Band 12 (699.7 - 715.3 MHz)			
	LTE Band 17 (706.5 - 713.5 MHz)			
	LTE Band 13 (779.5 - 784.5 MHz)			
	LTE Band 14 (790.5 - 795.5 MHz)			
	LTE Band 26 (Cell) (814.7 - 848.3 MHz)			
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)			
	LTE Band 66 (AWS) (1710.7 - 1779.3 MHz)			
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)			
	LTE Band 25 (PCS) (1850.7 - 1914.3 MHz)			
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)			
	LTE Band 30 (2307.5 - 2312.5 MHz)			
	LTE Band 7 (2502.5 - 2567.5 MHz)			
	LTE Band 41 (2498.5 - 2687.5 MHz)			
Channel Bandwidths	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz			
	LTE Band 17: 5 MHz, 10 MHz			
	LTE Band 13: 5 MHz, 10 MHz			
	LTE Band 14: 5 MHz, 10 MHz			
	LTE Band 26 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz			
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz			
	LTE Band 66 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz			
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz			
	LTE Band 25 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz			
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz			
	LTE Band 30: 5 MHz, 10 MHz			
	LTE Band 7: 5 MHz, 10 MHz, 15 MHz, 20 MHz			
	LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz			
Channel Numbers and Frequencies (MHz)	Low	Low-Mid	Mid	Mid-High
	High			
LTE Band 12: 1.4 MHz	699.7 (23017)	707.5 (23095)	715.3 (23173)	
LTE Band 12: 3 MHz	700.5 (23025)	707.5 (23095)	714.5 (23165)	
LTE Band 12: 5 MHz	701.5 (23035)	707.5 (23095)	713.5 (23155)	
LTE Band 12: 10 MHz	704 (23060)	707.5 (23095)	711 (23130)	
LTE Band 17: 5 MHz	706.5 (23755)	710 (23790)	713.5 (23825)	
LTE Band 17: 10 MHz	709 (23780)	710 (23790)	711 (23800)	
LTE Band 13: 5 MHz	779.5 (23205)	782 (23230)	784.5 (23255)	
LTE Band 13: 10 MHz	N/A	782 (23230)	N/A	
LTE Band 14: 5 MHz	790.5 (23305)	793 (23330)	795.5 (23355)	
LTE Band 14: 10 MHz	N/A	793 (23330)	N/A	
LTE Band 26 (Cell): 1.4 MHz	814.7 (26697)	831.5 (26865)	848.3 (27033)	
LTE Band 26 (Cell): 3 MHz	815.5 (26705)	831.5 (26865)	847.5 (27025)	
LTE Band 26 (Cell): 5 MHz	816.5 (26715)	831.5 (26865)	846.5 (27015)	
LTE Band 26 (Cell): 10 MHz	819 (26740)	831.5 (26865)	844 (26990)	
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)	836.5 (20525)	848.3 (20643)	
LTE Band 5 (Cell): 3 MHz	825.5 (20415)	836.5 (20525)	847.5 (20635)	
LTE Band 5 (Cell): 5 MHz	826.5 (20425)	836.5 (20525)	846.5 (20625)	
LTE Band 5 (Cell): 10 MHz	829 (20450)	836.5 (20525)	844 (20600)	
LTE Band 66 (AWS): 1.4 MHz	1710.7 (131979)	1745 (132322)	1779.3 (132665)	
LTE Band 66 (AWS): 3 MHz	1711.5 (131987)	1745 (132322)	1778.5 (132657)	
LTE Band 66 (AWS): 5 MHz	1712.5 (131997)	1745 (132322)	1777.5 (132647)	
LTE Band 66 (AWS): 10 MHz	1715 (132022)	1745 (132322)	1775 (132622)	
LTE Band 66 (AWS): 15 MHz	1717.5 (132047)	1745 (132322)	1772.5 (132597)	
LTE Band 66 (AWS): 20 MHz	1720 (132072)	1745 (132322)	1770 (132572)	
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)	1732.5 (20175)	1754.3 (20393)	
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)	1732.5 (20175)	1753.5 (20385)	
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)	1732.5 (20175)	1752.5 (20375)	
LTE Band 4 (AWS): 10 MHz	1715 (20000)	1732.5 (20175)	1750 (20350)	
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)	1732.5 (20175)	1747.5 (20325)	
LTE Band 4 (AWS): 20 MHz	1720 (20050)	1732.5 (20175)	1745 (20300)	
LTE Band 25 (PCS): 1.4 MHz	1850.7 (26047)	1882.5 (26365)	1914.3 (26683)	
LTE Band 25 (PCS): 3 MHz	1851.5 (26055)	1882.5 (26365)	1913.5 (26675)	
LTE Band 25 (PCS): 5 MHz	1852.5 (26065)	1882.5 (26365)	1912.5 (26665)	
LTE Band 25 (PCS): 10 MHz	1855 (26090)	1882.5 (26365)	1910 (26640)	
LTE Band 25 (PCS): 15 MHz	1857.5 (26115)	1882.5 (26365)	1907.5 (26615)	
LTE Band 25 (PCS): 20 MHz	1860 (26140)	1882.5 (26365)	1905 (26590)	
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)	1880 (18900)	1909.3 (19193)	
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)	1880 (18900)	1908.5 (19185)	
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)	1880 (18900)	1907.5 (19175)	
LTE Band 2 (PCS): 10 MHz	1855 (18650)	1880 (18900)	1905 (19150)	
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)	1880 (18900)	1902.5 (19125)	
LTE Band 2 (PCS): 20 MHz	1860 (18700)	1880 (18900)	1900 (19100)	
LTE Band 30: 5 MHz	2307.5 (27685)	2310 (27710)	2312.5 (27735)	
LTE Band 30: 10 MHz	N/A	2310 (27710)	N/A	
LTE Band 7: 5 MHz	2502.5 (20775)	2535 (21100)	2567.5 (21425)	
LTE Band 7: 10 MHz	2505 (20800)	2535 (21100)	2566 (21400)	
LTE Band 7: 15 MHz	2507.5 (20825)	2535 (21100)	2562.5 (21375)	
LTE Band 7: 20 MHz	2510 (20850)	2535 (21100)	2560 (21350)	
LTE Band 41: 5 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)
LTE Band 41: 10 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)
LTE Band 41: 15 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)
LTE Band 41: 20 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)
UE Category	DL UE Cat16 (QPSK, 16QAM, 64QAM 256QAM), UL UE Cat13 (QPSK, 16QAM, 64QAM)			
Modulations Supported in UL	QPSK, 16QAM, 64QAM			
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES			
A-MPR (Additional MPR) disabled for SAR Testing?	YES			
LTE Carrier Aggregation Possible Combinations	The technical description includes all the possible carrier aggregation combinations			
LTE Additional Information	This device does not support full CA features on 3GPP Release 13. All uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. The following LTE Release 13 Features are not supported: Relay, HetNet, Enhanced MIMO, eICIC, WiFi Offloading, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.			

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 20 of 114

3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: BCGA2429	 PCTEST Proud to be part of 	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 21 of 114

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
				$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	
≤2 GHz	≤15	≤8	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
2-3 GHz	≤12	≤5	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
3-4 GHz	≤12	≤5	≤4	≤3	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥28
4-5 GHz	≤10	≤4	≤3	≤2.5	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥25
5-6 GHz	≤10	≤4	≤2	≤2	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 22 of 114

5 TEST CONFIGURATION POSITIONS

5.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

5.2 SAR Testing for Tablet per KDB Publication 616217 D04v01r02

Per FCC KDB Publication 616217 D04v01r02, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. The SAR Exclusion Threshold in KDB 447498 D01v06 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

FCC ID: BCGA2429	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 23 of 114

6 RF EXPOSURE LIMITS

6.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

6.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 6-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 24 of 114

7 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

7.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

7.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

7.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

7.4 SAR Measurement Conditions for UMTS

7.4.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

FCC ID: BCGA2429	 PCTEST Proud to be part of 	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 25 of 114

7.4.2 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

7.4.3 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

7.4.4 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

7.4.5 SAR Measurement Conditions for DC-HSDPA

SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

7.5 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

7.5.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

FCC ID: BCGA2429	 PCTEST Proud to be part of 	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 26 of 114

7.5.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

7.5.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

7.5.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

7.5.5 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05v02r04. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

7.5.6 Downlink Only Carrier Aggregation

Conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. Additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band. Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for downlink only carrier aggregation configurations when the average output power with downlink only carrier

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 27 of 114

aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive.

7.6 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

7.6.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

7.6.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

7.6.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

7.6.4 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 28 of 114

- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

7.6.5 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

7.6.6 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 7.6.5).

7.6.7 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required.

7.6.8 MIMO SAR considerations

Per KDB Publication 248227 D01v02r02, the simultaneous SAR provisions in KDB Publication 447498 D01v06 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is < 1.6 W/kg, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 29 of 114

8 RF CONDUCTED POWERS

8.1 GSM Conducted Powers

Table 8-1
Conducted Power Ant C

Maximum Burst-Averaged Output Power					
Band	Channel	GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
		GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	27.59	24.66	24.52	23.62
	190	27.58	24.62	24.48	23.56
	251	27.51	24.58	24.41	23.52
GSM 1900	512	21.74	18.68	21.74	18.64
	661	21.72	18.65	21.73	18.65
	810	21.78	18.51	21.72	18.66

Calculated Maximum Frame-Averaged Output Power					
Band	Channel	GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
		GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	18.39	18.47	15.32	17.43
	190	18.38	18.43	15.28	17.37
	251	18.31	18.39	15.21	17.33
GSM 1900	512	12.54	12.49	12.54	12.45
	661	12.52	12.46	12.53	12.46
	810	12.58	12.32	12.52	12.47

GSM 850	Frame Avg.Targets:	17.80	17.81	14.80	16.81
GSM 1900		12.00	12.01	12.00	12.01

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 30 of 114

Table 8-2
Conducted Power Ant D

Maximum Burst-Averaged Output Power					
		GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
Band	Channel	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	28.23	25.32	22.72	21.57
	190	28.24	25.31	22.73	21.58
	251	28.24	25.34	22.72	21.59
GSM 1900	512	21.15	18.05	21.14	18.02
	661	21.14	18.03	21.12	18.03
	810	21.13	17.80	21.13	18.04

Calculated Maximum Frame-Averaged Output Power					
		GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
Band	Channel	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	19.03	19.13	13.52	15.38
	190	19.04	19.12	13.53	15.39
	251	19.04	19.15	13.52	15.40
GSM 1900	512	11.95	11.86	11.94	11.83
	661	11.94	11.84	11.92	11.84
	810	11.93	11.61	11.93	11.85

GSM 850	Frame Avg. Targets:	18.30	18.56	12.80	14.81
GSM 1900		11.30	11.31	11.30	11.31

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 31 of 114

Note:

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
3. EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8-PSK modulation do not have an impact on output power.




Figure 8-1
Power Measurement Setup

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 32 of 114

8.2 UMTS Conducted Powers

Table 8-3
Conducted Power Ant C

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			MPR [dB]
			4132	4183	4233	1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	17.33	17.25	17.27	13.11	13.05	12.78	12.87	12.84	12.83	-
6	HSDPA	Subtest 1	17.45	17.40	17.39	13.12	13.07	12.87	12.89	12.90	12.94	0
6		Subtest 2	17.45	17.39	17.33	13.14	13.01	12.89	12.94	12.88	12.88	0
6		Subtest 3	17.47	17.39	17.35	13.11	13.00	12.87	12.93	12.88	12.86	0
6		Subtest 4	17.47	17.39	17.33	13.13	12.99	12.85	12.89	12.88	12.85	0
6	HSUPA	Subtest 1	17.42	17.37	17.32	12.99	12.89	12.70	12.91	12.87	12.88	0
6		Subtest 2	17.47	17.44	17.35	13.13	12.95	12.83	12.82	12.81	12.77	0
6		Subtest 3	17.47	17.38	17.33	13.05	12.89	12.75	12.85	12.84	12.78	0
6		Subtest 4	17.44	17.39	17.31	13.12	12.98	12.88	12.86	12.83	12.78	0
6		Subtest 5	17.44	17.38	17.32	13.17	13.18	12.98	12.89	12.79	12.79	0
8	DC-HSDPA	Subtest 1	17.45	17.41	17.36	13.18	13.03	12.88	12.92	12.89	12.87	0
8		Subtest 2	17.46	17.34	17.35	13.14	13.05	12.91	12.93	12.90	12.88	0
8		Subtest 3	17.47	17.40	17.35	13.16	13.02	12.90	12.91	12.88	12.87	0
8		Subtest 4	17.45	17.38	17.33	13.14	13.02	12.85	12.92	12.89	12.85	0

Table 8-4
Conducted Power Ant D

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			MPR [dB]
			4132	4183	4233	1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	19.08	19.12	18.97	12.76	12.83	12.58	11.75	11.73	11.76	-
6	HSDPA	Subtest 1	19.13	19.15	19.02	13.19	13.20	12.98	11.87	11.90	11.98	0
6		Subtest 2	19.12	19.10	18.92	13.05	13.13	12.92	11.84	11.82	11.90	0
6		Subtest 3	19.13	19.12	18.93	13.03	13.16	12.90	11.81	11.81	11.86	0
6		Subtest 4	19.12	19.11	18.93	13.11	13.17	12.91	11.80	11.78	11.88	0
6	HSUPA	Subtest 1	18.92	18.94	18.78	12.92	12.97	12.70	11.85	11.82	11.92	0
6		Subtest 2	19.01	18.97	18.84	12.90	12.97	12.70	11.73	11.75	11.81	0
6		Subtest 3	18.90	18.96	18.81	12.79	12.93	12.68	11.73	11.79	11.85	0
6		Subtest 4	18.74	18.96	18.80	12.81	12.91	12.67	11.80	11.74	11.85	0
6		Subtest 5	18.92	18.93	18.80	12.91	12.96	12.68	11.86	11.82	11.91	0
8	DC-HSDPA	Subtest 1	19.16	19.15	19.06	13.17	13.16	12.98	11.82	11.77	11.75	0
8		Subtest 2	19.11	19.15	19.02	13.13	13.19	12.86	11.91	11.70	11.85	0
8		Subtest 3	19.16	19.14	19.01	13.06	13.07	12.94	11.77	11.75	11.83	0
8		Subtest 4	19.18	19.20	19.08	13.12	13.18	12.93	11.74	11.73	11.81	0

DC-HSDPA considerations

- 3GPP Specification 34.121-1 Release 8 Ver 8.10.0 was used for DC-HSDPA guidance
- H-Set 12 (QPSK) was confirmed to be used during DC-HSDPA measurements
- The DUT supports UE category 24 for HSDPA




Figure 8-2
Power Measurement Setup

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 33 of 114

8.3 LTE Conducted Powers

8.3.1 LTE Band 12

Table 8-5
LTE Band 12 Conducted Powers Ant C - 10 MHz Bandwidth

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	17.32	0	0
	1	25	17.34		0
	1	49	17.27		0
	25	0	17.37	0-1	0
	25	12	17.36		0
	25	25	17.35		0
	50	0	17.32		0
16QAM	1	0	17.36	0-1	0
	1	25	17.20		0
	1	49	17.26		0
	25	0	17.17	0-2	0
	25	12	17.18		0
	25	25	17.19		0
	50	0	17.15		0
64QAM	1	0	17.32	0-2	0
	1	25	17.31		0
	1	49	17.34		0
	25	0	17.14	0-3	0
	25	12	17.16		0
	25	25	17.13		0
	50	0	17.16		0

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-6
LTE Band 12 Conducted Powers Ant C - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.38	17.43	17.37	0	0
	1	12	17.30	17.48	17.33		0
	1	24	17.32	17.44	17.46		0
	12	0	17.38	17.41	17.45	0-1	0
	12	6	17.32	17.42	17.41		0
	12	13	17.39	17.46	17.41		0
	25	0	17.33	17.45	17.42		0
16QAM	1	0	17.03	17.21	17.14	0-1	0
	1	12	17.03	17.27	17.18		0
	1	24	17.01	17.38	17.33		0
	12	0	16.95	16.98	16.97	0-2	0
	12	6	16.88	17.01	16.99		0
	12	13	16.97	17.05	16.96		0
	25	0	16.89	17.00	16.95		0
64QAM	1	0	17.01	17.16	17.35	0-2	0
	1	12	17.09	17.16	17.07		0
	1	24	17.11	17.29	17.25		0
	12	0	16.98	16.96	17.06	0-3	0
	12	6	16.94	17.04	16.95		0
	12	13	17.00	16.90	16.98		0
	25	0	16.88	16.96	16.94		0

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 34 of 114

Table 8-7
LTE Band 12 Conducted Powers Ant C - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.26	17.34	17.26	0	0
	1	7	17.33	17.40	17.33		0
	1	14	17.21	17.39	17.39		0
	8	0	17.37	17.45	17.37	0-1	0
	8	4	17.37	17.44	17.39		0
	8	7	17.31	17.43	17.46		0
	15	0	17.39	17.45	17.41		0
16QAM	1	0	17.12	17.18	17.12	0-1	0
	1	7	16.94	17.22	17.08		0
	1	14	17.02	17.23	17.25		0
	8	0	16.92	17.04	16.91	0-2	0
	8	4	17.00	17.00	16.95		0
	8	7	16.88	16.94	17.03		0
	15	0	16.92	16.97	16.92		0
64QAM	1	0	17.18	17.26	17.12	0-2	0
	1	7	17.22	17.09	17.20		0
	1	14	17.12	17.04	17.16		0
	8	0	17.02	17.10	17.01	0-3	0
	8	4	17.00	17.09	17.05		0
	8	7	16.98	17.07	17.08		0
	15	0	16.97	16.96	16.99		0

Table 8-8
LTE Band 12 Conducted Powers Ant C - 1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.08	17.18	17.31	0	0
	1	2	17.06	17.16	17.28		0
	1	5	17.10	17.16	17.37		0
	3	0	17.12	17.22	17.21		0
	3	2	17.10	17.18	17.19		0
	3	3	17.14	17.19	17.27		0
	6	0	17.11	17.19	17.18	0-1	0
16QAM	1	0	17.04	17.16	17.20	0-1	0
	1	2	17.20	17.29	17.09		0
	1	5	17.06	17.08	17.18		0
	3	0	16.98	17.11	17.03		0
	3	2	17.05	17.10	16.96		0
	3	3	17.03	17.09	17.10		0
	6	0	16.97	17.04	17.07	0-2	0
64QAM	1	0	17.15	17.20	17.25	0-2	0
	1	2	17.17	17.20	17.26		0
	1	5	17.22	17.20	17.31		0
	3	0	17.06	17.06	17.31		0
	3	2	17.10	17.05	17.27		0
	3	3	17.09	17.00	17.34		0
	6	0	16.94	17.05	17.03	0-3	0

FCC ID: BCGA2429	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 35 of 114

Table 8-9
LTE Band 12 Conducted Powers Ant D - 10 MHz Bandwidth

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	17.05	0	0
	1	25	17.01		0
	1	49	16.98		0
	25	0	17.04	0-1	0
	25	12	17.03		0
	25	25	17.01		0
	50	0	17.03		0
16QAM	1	0	16.94	0-1	0
	1	25	16.92		0
	1	49	16.90		0
	25	0	16.70	0-2	0
	25	12	16.60		0
	25	25	16.58		0
	50	0	16.60		0
64QAM	1	0	16.86	0-2	0
	1	25	16.90		0
	1	49	16.94		0
	25	0	16.67	0-3	0
	25	12	16.64		0
	25	25	16.58		0
	50	0	16.60		0

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-10
LTE Band 12 Conducted Powers Ant D - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.14	16.97	17.12	0	0
	1	12	17.15	16.93	17.13		0
	1	24	17.16	16.95	17.18		0
	12	0	17.11	17.09	17.06	0-1	0
	12	6	17.12	17.06	17.03		0
	12	13	17.14	16.98	17.01		0
	25	0	17.13	17.08	17.06		0
16QAM	1	0	17.13	16.88	16.94	0-1	0
	1	12	17.05	16.79	16.84		0
	1	24	16.83	16.76	16.86		0
	12	0	16.71	16.63	16.68	0-2	0
	12	6	16.66	16.62	16.66		0
	12	13	16.74	16.53	16.55		0
	25	0	16.68	16.59	16.61		0
64QAM	1	0	16.72	16.89	16.67	0-2	0
	1	12	16.99	16.83	16.62		0
	1	24	16.73	16.78	16.75		0
	12	0	16.66	16.65	16.64	0-3	0
	12	6	16.68	16.64	16.60		0
	12	13	16.66	16.51	16.54		0
	25	0	16.65	16.61	16.56		0

FCC ID: BCGA2429	 Proud to be part of 	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 36 of 114

Table 8-11
LTE Band 12 Conducted Powers Ant D - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.03	17.01	16.95	0	0
	1	7	17.10	17.02	16.97		0
	1	14	17.08	16.89	16.94		0
	8	0	17.11	17.09	17.05	0-1	0
	8	4	17.11	17.04	17.03		0
	8	7	17.11	16.99	17.08		0
	15	0	17.12	17.08	17.04		0
16QAM	1	0	16.78	16.93	16.73	0-1	0
	1	7	17.10	16.79	16.87		0
	1	14	16.76	16.58	16.91		0
	8	0	16.69	16.68	16.64	0-2	0
	8	4	16.74	16.64	16.60		0
	8	7	16.70	16.55	16.69		0
	15	0	16.69	16.65	16.62		0
64QAM	1	0	16.95	16.62	16.82	0-2	0
	1	7	17.01	16.74	16.77		0
	1	14	16.86	16.63	16.78		0
	8	0	16.69	16.70	16.62	0-3	0
	8	4	16.70	16.56	16.61		0
	8	7	16.71	16.57	16.62		0
	15	0	16.65	16.58	16.59		0

Table 8-12
LTE Band 12 Conducted Powers Ant D - 1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.10	17.08	17.12	0	0
	1	2	17.07	17.01	17.15		0
	1	5	17.10	17.03	17.17		0
	3	0	17.11	17.10	17.09		0
	3	2	17.13	17.05	17.06		0
	3	3	17.14	17.05	17.06		0
	6	0	17.10	17.07	17.05	0-1	0
16QAM	1	0	16.92	16.69	16.63	0-1	0
	1	2	17.04	16.80	16.80		0
	1	5	16.85	16.85	16.80		0
	3	0	16.78	16.71	16.74		0
	3	2	16.77	16.68	16.71		0
	3	3	16.81	16.71	16.76		0
	6	0	16.75	16.71	16.72	0-2	0
64QAM	1	0	16.86	16.96	16.66	0-2	0
	1	2	16.99	16.88	16.79		0
	1	5	16.98	16.80	17.08		0
	3	0	16.74	16.73	16.90		0
	3	2	16.72	16.63	16.85		0
	3	3	16.76	16.67	16.85		0
	6	0	16.63	16.66	16.63	0-3	0

FCC ID: BCGA2429	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 37 of 114

8.3.2 LTE Band 13

Table 8-13
LTE Band 13 Conducted Powers Ant C - 10 MHz Bandwidth

LTE Band 13 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	18.10	0	0
	1	25	17.57		0
	1	49	17.64		0
	25	0	17.79	0-1	0
	25	12	17.69		0
	25	25	17.65		0
	50	0	17.68		0
16QAM	1	0	18.03	0-1	0
	1	25	17.49		0
	1	49	17.63		0
	25	0	17.54	0-2	0
	25	12	17.46		0
	25	25	17.45		0
	50	0	17.70		0
64QAM	1	0	18.07	0-2	0
	1	25	17.60		0
	1	49	17.73		0
	25	0	17.51	0-3	0
	25	12	17.46		0
	25	25	17.39		0
	50	0	17.42		0

Table 8-14
LTE Band 13 Conducted Powers Ant C - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	17.75	0	0
	1	12	17.63		0
	1	24	17.68		0
	12	0	17.65	0-1	0
	12	6	17.69		0
	12	13	17.69		0
	25	0	17.66		0
16QAM	1	0	17.77	0-1	0
	1	12	17.59		0
	1	24	17.71		0
	12	0	17.37	0-2	0
	12	6	17.43		0
	12	13	17.47		0
	25	0	17.39		0
64QAM	1	0	17.84	0-2	0
	1	12	17.67		0
	1	24	17.79		0
	12	0	17.40	0-3	0
	12	6	17.48		0
	12	13	17.54		0
	25	0	17.46		0

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 38 of 114

Table 8-15
LTE Band 13 Conducted Powers Ant D - 10 MHz Bandwidth

LTE Band 13 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	18.30	0	0
	1	25	17.80		0
	1	49	17.78		0
	25	0	18.00	0-1	0
	25	12	17.90		0
	25	25	17.83		0
16QAM	50	0	17.91	0-1	0
	1	0	18.13		0
	1	25	17.72		0
	1	49	17.66	0-2	0
	25	0	17.53		0
	25	12	17.42		0
64QAM	25	25	17.35	0-2	0
	50	0	17.40		0
	1	0	18.12	0-3	0
	1	25	17.57		0
	1	49	17.64		0
	25	0	17.53		0

Table 8-16
LTE Band 13 Conducted Powers Ant D - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	17.99	0	0
	1	12	17.79		0
	1	24	17.85		0
	12	0	17.98	0-1	0
	12	6	17.96		0
	12	13	17.91		0
16QAM	25	0	17.91	0-1	0
	1	0	18.20		0
	1	12	17.89	0-2	0
	1	24	17.92		0
	12	0	17.74		0
	12	6	17.78	0-3	0
64QAM	12	13	17.71		0
	25	0	17.72		0
	1	0	17.97	0-2	0
	1	12	17.69		0
	1	24	17.90		0
	12	0	17.49	0-3	0

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 39 of 114

8.3.3 LTE Band 14

Table 8-17
LTE Band 14 Conducted Powers Ant C - 10 MHz Bandwidth

LTE Band 14 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz) Conducted Power [dBm]		
QPSK	1	0	17.90	0	0
	1	25	17.81		0
	1	49	17.84		0
	25	0	17.98	0-1	0
	25	12	17.89		0
	25	25	17.88		0
	50	0	17.89		0
16QAM	1	0	17.91	0-1	0
	1	25	17.85		0
	1	49	17.90		0
	25	0	17.81	0-2	0
	25	12	17.74		0
	25	25	17.72		0
	50	0	17.68		0
64QAM	1	0	17.91	0-2	0
	1	25	17.92		0
	1	49	17.97		0
	25	0	17.77	0-3	0
	25	12	17.69		0
	25	25	17.70		0
	50	0	17.70		0

Table 8-18
LTE Band 14 Conducted Powers Ant C - 5 MHz Bandwidth

LTE Band 14 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz) Conducted Power [dBm]		
QPSK	1	0	17.88	0	0
	1	12	17.78		0
	1	24	17.75		0
	12	0	17.91	0-1	0
	12	6	17.90		0
	12	13	17.86		0
	25	0	17.90		0
16QAM	1	0	17.98	0-1	0
	1	12	17.93		0
	1	24	17.94		0
	12	0	17.78	0-2	0
	12	6	17.73		0
	12	13	17.76		0
	25	0	17.78		0
64QAM	1	0	18.05	0-2	0
	1	12	17.88		0
	1	24	17.97		0
	12	0	17.74	0-3	0
	12	6	17.77		0
	12	13	17.72		0
	25	0	17.69		0

Note: LTE Band 14 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 40 of 114

Table 8-19
LTE Band 14 Conducted Powers Ant D - 10 MHz Bandwidth

LTE Band 14 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	17.92	0	0
	1	25	17.86		0
	1	49	17.94		0
	25	0	18.02	0-1	0
	25	12	17.95		0
	25	25	17.94		0
16QAM	50	0	17.93	0	0
	1	0	18.00		0
	1	25	17.90		0
	1	49	18.03	0-1	0
	25	0	17.79		0
	25	12	17.71		0
64QAM	25	25	17.73	0-2	0
	50	0	17.72		0
	1	0	17.90		0
	1	25	17.96	0-2	0
	1	49	18.01		0
	25	0	17.80		0
	25	12	17.70	0-3	0
	25	25	17.72		0
	50	0	17.77		0

Table 8-20
LTE Band 14 Conducted Powers Ant D - 5 MHz Bandwidth

LTE Band 14 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	17.76	0	0
	1	12	17.75		0
	1	24	17.80		0
	12	0	17.80	0-1	0
	12	6	17.86		0
	12	13	17.88		0
16QAM	25	0	17.86	0	0
	1	0	17.79		0
	1	12	17.78		0
	1	24	17.95	0-1	0
	12	0	17.62		0
	12	6	17.69		0
64QAM	12	13	17.72	0-2	0
	25	0	17.70		0
	1	0	17.86		0
	1	12	17.84	0-2	0
	1	24	17.91		0
	12	0	17.62		0
	12	6	17.72	0-3	0
	12	13	17.64		0
	25	0	17.69		0

Note: LTE Band 14 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 41 of 114

8.3.4 LTE Band 26

Table 8-21
LTE Band 26 Conducted Powers Ant C - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.83	17.58	17.64	0	0
	1	25	17.70	17.49	17.57		0
	1	49	17.72	17.50	17.60		0
	25	0	17.65	17.63	17.69	0-1	0
	25	12	17.64	17.54	17.58		0
	25	25	17.74	17.52	17.53		0
	50	0	17.72	17.51	17.51		0
16QAM	1	0	18.01	17.97	18.00	0-1	0
	1	25	17.99	17.94	17.82		0
	1	49	17.94	17.99	17.92		0
	25	0	17.48	17.46	17.54	0-2	0
	25	12	17.47	17.42	17.42		0
	25	25	17.53	17.40	17.42		0
	50	0	17.53	17.42	17.38		0
64QAM	1	0	18.20	17.97	18.11	0-2	0
	1	25	18.13	17.91	18.06		0
	1	49	18.09	17.96	18.10		0
	25	0	17.77	17.68	17.77	0-3	0
	25	12	17.74	17.64	17.66		0
	25	25	17.81	17.62	17.66		0
	50	0	17.81	17.65	17.65		0

Table 8-22
LTE Band 26 Conducted Powers Ant C - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.00	17.93	17.88	0	0
	1	12	17.89	17.85	17.89		0
	1	24	17.89	17.87	17.95		0
	12	0	18.07	17.92	17.92	0-1	0
	12	6	17.99	17.89	17.90		0
	12	13	17.98	17.90	17.94		0
	25	0	18.00	17.93	17.91		0
16QAM	1	0	18.13	18.07	18.00	0-1	0
	1	12	18.10	17.98	18.12		0
	1	24	18.06	17.91	17.92		0
	12	0	17.63	17.48	17.47	0-2	0
	12	6	17.54	17.45	17.44		0
	12	13	17.56	17.45	17.49		0
	25	0	17.52	17.43	17.47		0
64QAM	1	0	18.20	18.19	18.20	0-2	0
	1	12	18.12	18.16	18.19		0
	1	24	18.20	18.16	18.20		0
	12	0	17.86	17.71	17.69	0-3	0
	12	6	17.72	17.64	17.69		0
	12	13	17.77	17.66	17.64		0
	25	0	17.74	17.68	17.64		0

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 42 of 114

Table 8-23
LTE Band 26 Conducted Powers Ant C - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.14	17.81	17.89	0	0
	1	7	18.17	17.84	17.95		0
	1	14	18.01	17.78	17.90		0
	8	0	18.10	17.95	17.91	0-1	0
	8	4	18.09	17.92	17.96		0
	8	7	18.03	17.91	17.94		0
	15	0	18.09	17.93	17.98		0
16QAM	1	0	18.20	17.90	17.96	0-1	0
	1	7	18.20	17.97	18.19		0
	1	14	18.00	17.95	18.01		0
	8	0	17.71	17.55	17.55	0-2	0
	8	4	17.72	17.48	17.56		0
	8	7	17.63	17.50	17.50		0
	15	0	17.66	17.49	17.49		0
64QAM	1	0	18.20	18.13	18.20	0-2	0
	1	7	18.19	18.14	18.19		0
	1	14	18.16	17.97	18.16		0
	8	0	17.87	17.75	17.76	0-3	0
	8	4	17.91	17.75	17.73		0
	8	7	17.85	17.79	17.72		0
	15	0	17.84	17.71	17.77		0

Table 8-24
LTE Band 26 Conducted Powers Ant C- 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.20	17.89	18.09	0	0
	1	2	18.17	17.83	18.06		0
	1	5	18.18	17.86	18.09		0
	3	0	18.12	17.94	17.97		0
	3	2	18.12	17.94	17.93		0
	3	3	18.11	17.94	17.94		0
	6	0	18.11	17.95	17.97	0-1	0
16QAM	1	0	18.18	17.96	18.07	0-1	0
	1	2	18.18	17.91	18.10		0
	1	5	18.20	18.06	18.19		0
	3	0	17.80	17.67	17.69		0
	3	2	17.77	17.72	17.72		0
	3	3	17.81	17.69	17.69		0
	6	0	17.65	17.60	17.63	0-2	0
64QAM	1	0	18.20	18.17	18.20	0-2	0
	1	2	18.19	18.14	18.18		0
	1	5	18.20	18.08	18.19		0
	3	0	17.95	17.94	17.89		0
	3	2	18.06	17.87	17.96		0
	3	3	17.97	17.84	17.89		0
	6	0	17.99	17.75	17.86	0-3	0

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 43 of 114

Table 8-25
LTE Band 26 Conducted Powers Ant D- 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.06	18.01	18.14	0	0
	1	25	18.08	17.98	17.86		0
	1	49	18.01	18.11	18.05		0
	25	0	18.00	18.01	18.10	0-1	0
	25	12	18.06	18.06	17.96		0
	25	25	18.18	18.08	18.02		0
16QAM	50	0	18.05	18.06	17.95	0-1	0
	1	0	18.20	18.18	18.14		0
	1	25	18.16	18.05	17.89		0
	1	49	18.19	18.20	18.16	0-2	0
	25	0	17.74	17.76	17.86		0
	25	12	17.78	17.80	17.78		0
64QAM	25	25	17.91	17.83	17.83	0-2	0
	50	0	17.86	17.82	17.71		0
	1	0	18.12	17.90	18.20		0-2
	1	25	18.15	18.10	17.98	0	
	1	49	18.20	18.00	18.13	0-3	
	25	0	17.67	17.76	17.83		0
25	12	17.78	17.81	17.70	0		
64QAM	25	25	17.90	17.86	17.75	0-3	0
	50	0	17.86	17.83	17.69		0

Table 8-26
LTE Band 26 Conducted Powers Ant D - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.08	17.97	17.91	0	0
	1	12	18.10	18.01	17.99		0
	1	24	18.18	18.08	18.04		0
	12	0	18.07	18.02	18.01	0-1	0
	12	6	18.03	18.08	18.05		0
	12	13	18.07	18.07	18.10		0
	25	0	18.04	18.07	18.05		0
16QAM	1	0	18.20	18.06	17.91	0-1	0
	1	12	18.03	18.01	18.07		0
	1	24	18.14	18.13	18.08		0
	12	0	17.86	17.78	17.76	0-2	0
	12	6	17.77	17.81	17.79		0
	12	13	17.85	17.85	17.80		0
	25	0	17.74	17.82	17.73		0
64QAM	1	0	17.99	18.19	17.81	0-2	0
	1	12	17.90	18.07	18.09		0
	1	24	17.85	18.03	18.12		0
	12	0	17.83	17.76	17.72	0-3	0
	12	6	17.75	17.76	17.76		0
	12	13	17.84	17.85	17.77		0
	25	0	17.70	17.87	17.74		0

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 44 of 114

Table 8-27
LTE Band 26 Conducted Powers Ant D - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.03	17.92	17.96	0	0
	1	7	18.00	18.05	18.03		0
	1	14	17.91	18.00	17.98		0
	8	0	18.06	18.04	18.05	0-1	0
	8	4	18.05	18.11	18.08		0
	8	7	18.03	18.10	18.09		0
	15	0	18.05	18.12	18.10		0
16QAM	1	0	18.20	17.97	17.96	0-1	0
	1	7	18.15	18.16	18.17		0
	1	14	18.18	17.94	17.99		0
	8	0	17.90	17.85	17.79	0-2	0
	8	4	17.93	17.92	17.86		0
	8	7	17.85	17.87	17.86		0
	15	0	17.90	17.88	17.84		0
64QAM	1	0	18.16	18.03	18.04	0-2	0
	1	7	18.10	18.03	18.13		0
	1	14	17.98	18.06	18.10		0
	8	0	17.90	17.99	17.86	0-3	0
	8	4	17.87	17.95	17.94		0
	8	7	17.83	17.98	17.90		0
	15	0	17.85	17.93	17.86		0

Table 8-28
LTE Band 26 Conducted Powers Ant D - 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.20	18.02	18.04	0	0
	1	2	18.19	17.99	18.03		0
	1	5	18.17	18.02	18.07		0
	3	0	18.13	18.12	18.08		0
	3	2	18.04	18.11	18.10		0
	3	3	18.05	18.11	18.10		0
	6	0	18.05	18.12	18.08	0-1	0
16QAM	1	0	18.14	18.18	18.17	0-1	0
	1	2	18.03	18.00	18.20		0
	1	5	18.06	18.18	18.20		0
	3	0	18.01	18.07	18.08		0
	3	2	18.05	18.01	18.11		0
	3	3	18.03	18.04	17.97		0
	6	0	17.96	17.96	17.96	0-2	0
64QAM	1	0	18.15	18.02	18.13	0-2	0
	1	2	18.16	17.92	18.07		0
	1	5	18.18	18.01	18.07		0
	3	0	18.07	18.06	18.16		0
	3	2	17.94	17.98	18.10		0
	3	3	18.03	18.00	18.13		0
	6	0	17.86	18.00	17.88	0-3	0

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 45 of 114

8.3.5 LTE Band 5

Table 8-29
LTE Band 5 Conducted Powers Ant C - 10 MHz Bandwidth

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	17.36	0	0
	1	25	17.42		0
	1	49	17.46		0
	25	0	17.43	0-1	0
	25	12	17.41		0
	25	25	17.47		0
	50	0	17.44		0
16QAM	1	0	17.46	0-1	0
	1	25	17.40		0
	1	49	17.34		0
	25	0	17.26	0-2	0
	25	12	17.26		0
	25	25	17.29		0
	50	0	17.26		0
64QAM	1	0	17.44	0-2	0
	1	25	17.46		0
	1	49	17.41		0
	25	0	17.24	0-3	0
	25	12	17.23		0
	25	25	17.28		0
	50	0	17.24		0

Note: LTE Band 5 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-30
LTE Band 5 Conducted Powers Ant C - 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.57	17.67	17.34	0	0
	1	12	17.44	17.61	17.41		0
	1	24	17.48	17.67	17.49		0
	12	0	17.52	17.64	17.42	0-1	0
	12	6	17.49	17.65	17.46		0
	12	13	17.46	17.67	17.53		0
	25	0	17.50	17.67	17.47		0
16QAM	1	0	17.62	17.63	17.45	0-1	0
	1	12	17.61	17.65	17.54		0
	1	24	17.57	17.65	17.47		0
	12	0	17.34	17.37	17.22	0-2	0
	12	6	17.31	17.38	17.20		0
	12	13	17.28	17.48	17.27		0
	25	0	17.33	17.37	17.22		0
64QAM	1	0	17.52	17.42	17.38	0-2	0
	1	12	17.36	17.67	17.30		0
	1	24	17.34	17.54	17.45		0
	12	0	17.35	17.38	17.22	0-3	0
	12	6	17.26	17.41	17.27		0
	12	13	17.28	17.45	17.31		0
	25	0	17.23	17.40	17.19		0

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 46 of 114

Table 8-31
LTE Band 5 Conducted Powers Ant C - 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.50	17.49	17.39	0	0
	1	7	17.45	17.59	17.50		0
	1	14	17.37	17.56	17.46		0
	8	0	17.61	17.66	17.49	0-1	0
	8	4	17.51	17.67	17.53		0
	8	7	17.50	17.69	17.54		0
	15	0	17.52	17.67	17.55		0
16QAM	1	0	17.66	17.65	17.66	0-1	0
	1	7	17.39	17.67	17.57		0
	1	14	17.43	17.50	17.70		0
	8	0	17.40	17.47	17.25	0-2	0
	8	4	17.31	17.45	17.37		0
	8	7	17.31	17.46	17.34		0
	15	0	17.29	17.37	17.25		0
64QAM	1	0	17.63	17.55	17.43	0-2	0
	1	7	17.46	17.54	17.43		0
	1	14	17.46	17.68	17.52		0
	8	0	17.37	17.51	17.32	0-3	0
	8	4	17.31	17.46	17.31		0
	8	7	17.27	17.50	17.37		0
	15	0	17.24	17.41	17.33		0

Table 8-32
LTE Band 5 Conducted Powers Ant C - 1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.53	17.57	17.68	0	0
	1	2	17.51	17.55	17.65		0
	1	5	17.44	17.58	17.70		0
	3	0	17.57	17.66	17.53		0
	3	2	17.56	17.68	17.54		0
	3	3	17.56	17.68	17.57		0
	6	0	17.57	17.67	17.54	0-1	0
16QAM	1	0	17.35	17.39	17.30	0-1	0
	1	2	17.37	17.42	17.32		0
	1	5	17.19	17.63	17.24		0
	3	0	17.23	17.24	17.19		0
	3	2	17.29	17.34	17.21		0
	3	3	17.30	17.25	17.13		0
	6	0	17.15	17.27	17.16	0-2	0
64QAM	1	0	17.41	17.42	17.31	0-2	0
	1	2	17.53	17.59	17.36		0
	1	5	17.56	17.57	17.54		0
	3	0	17.51	17.51	17.44		0
	3	2	17.47	17.62	17.44		0
	3	3	17.40	17.52	17.46		0
	6	0	17.33	17.46	17.34	0-3	0

FCC ID: BCGA2429	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 47 of 114

Table 8-33
LTE Band 5 Conducted Powers Ant D - 10 MHz Bandwidth

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	19.02	0	0
	1	25	19.09		0
	1	49	19.10		0
	25	0	19.14	0-1	0
	25	12	19.16		0
	25	25	19.19		0
16QAM	50	0	19.09	0-1	0
	1	0	19.09		0
	1	25	19.15		0
	1	49	19.20	0-2	0
	25	0	18.92		0
	25	12	18.93		0
	25	25	19.00	0-2	0
	50	0	18.95		0
64QAM	1	0	19.12	0-2	0
	1	25	19.08		0
	1	49	19.09		0
	25	0	18.93	0-3	0
	25	12	18.95		0
	25	25	18.99		0
	50	0	18.95	0-3	0
	1	0	19.12		0
	1	25	19.08		0
	1	49	19.09		0

Note: LTE Band 5 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-34
LTE Band 5 Conducted Powers Ant D - 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.18	19.08	18.88	0	0
	1	12	19.08	19.11	18.91		0
	1	24	19.13	19.16	18.97		0
	12	0	18.99	19.13	18.93	0-1	0
	12	6	18.96	19.14	18.96		0
	12	13	18.95	19.16	19.03		0
	25	0	18.97	19.15	18.96	0	
16QAM	1	0	19.00	19.09	18.90	0-1	0
	1	12	18.95	19.16	19.04		0
	1	24	18.97	19.14	19.08		0
	12	0	18.74	18.94	18.77	0-2	0
	12	6	18.73	18.92	18.78		0
	12	13	18.73	18.97	18.82		0
	25	0	18.73	18.96	18.76	0	
64QAM	1	0	19.17	19.00	18.85	0-2	0
	1	12	18.84	19.10	19.16		0
	1	24	19.16	19.08	18.96		0
	12	0	18.74	18.93	18.75	0-3	0
	12	6	18.78	18.96	18.77		0
	12	13	18.73	18.95	18.80		0
	25	0	18.70	18.94	18.76	0	

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 48 of 114

Table 8-35
LTE Band 5 Conducted Powers Ant D - 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.97	19.03	18.90	0	0
	1	7	18.97	19.10	19.00		0
	1	14	18.89	19.07	18.94		0
	8	0	19.09	19.15	18.99	0-1	0
	8	4	19.03	19.16	19.05		0
	8	7	19.04	19.17	19.07		0
	15	0	18.98	19.17	19.07		0
16QAM	1	0	18.80	19.09	19.09	0-1	0
	1	7	19.07	19.07	19.08		0
	1	14	19.19	18.95	19.13		0
	8	0	18.93	18.97	18.85	0-2	0
	8	4	18.88	18.98	18.84		0
	8	7	18.84	18.99	18.89		0
	15	0	18.76	18.96	18.84		0
64QAM	1	0	19.09	19.09	18.96	0-2	0
	1	7	19.13	18.95	19.09		0
	1	14	19.06	19.01	19.01		0
	8	0	18.90	19.05	18.84	0-3	0
	8	4	18.81	18.97	18.90		0
	8	7	18.82	19.06	18.87		0
	15	0	18.75	18.94	18.85		0

Table 8-36
LTE Band 5 Conducted Powers Ant D - 1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.04	19.18	19.16	0	0
	1	2	19.00	19.17	19.15		0
	1	5	18.99	19.20	19.16		0
	3	0	19.12	19.19	19.05		0
	3	2	19.12	19.20	19.06		0
	3	3	19.13	19.19	19.05		0
	6	0	19.10	19.17	19.04	0-1	0
16QAM	1	0	19.18	19.18	19.12	0-1	0
	1	2	19.10	19.20	19.11		0
	1	5	19.13	19.08	19.14		0
	3	0	19.09	19.11	18.93		0
	3	2	19.08	19.08	18.99		0
	3	3	19.09	19.13	18.95		0
	6	0	19.05	19.05	18.93	0-2	0
64QAM	1	0	19.08	19.12	19.15	0-2	0
	1	2	19.19	18.92	19.02		0
	1	5	19.20	19.16	19.14		0
	3	0	18.96	19.10	19.15		0
	3	2	18.95	19.07	19.10		0
	3	3	18.96	19.12	19.08		0
	6	0	18.86	19.06	18.87	0-3	0

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 49 of 114

8.3.6 LTE Band 66

Table 8-37
LTE Band 66 Conducted Powers Ant C - 20 MHz Bandwidth

LTE Band 66 (AWS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.28	13.16	12.76	0	0
	1	50	13.26	13.21	12.96		0
	1	99	13.13	12.84	12.78		0
	50	0	13.19	13.09	12.89	0-1	0
	50	25	13.14	13.03	12.91		0
	50	50	13.11	12.93	12.82		0
	100	0	13.18	13.05	12.91		0
16QAM	1	0	13.10	13.00	12.76	0-1	0
	1	50	12.99	12.99	13.02		0
	1	99	12.97	13.03	12.76		0
	50	0	12.91	12.87	12.62	0-2	0
	50	25	12.82	12.86	12.61		0
	50	50	12.81	12.64	12.49		0
	100	0	12.86	12.82	12.62		0
64QAM	1	0	13.13	12.85	12.51	0-2	0
	1	50	13.03	12.81	12.55		0
	1	99	12.97	12.68	12.54		0
	50	0	12.67	12.62	12.33	0-3	0
	50	25	12.60	12.53	12.36		0
	50	50	12.61	12.35	12.35		0
	100	0	12.65	12.53	12.35		0

Table 8-38
LTE Band 66 Conducted Powers Ant C - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.28	12.99	13.05	0	0
	1	36	13.21	13.04	12.97		0
	1	74	13.14	12.83	12.95		0
	36	0	13.22	12.96	13.07	0-1	0
	36	18	13.20	12.99	13.01		0
	36	37	13.11	12.90	12.98		0
	75	0	13.22	13.02	13.03		0
16QAM	1	0	13.26	12.90	13.00	0-1	0
	1	36	13.26	13.03	12.94		0
	1	74	13.12	12.81	12.86		0
	36	0	12.81	12.51	12.59	0-2	0
	36	18	12.82	12.51	12.52		0
	36	37	12.68	12.43	12.47		0
	75	0	12.76	12.50	12.53		0
64QAM	1	0	13.20	12.78	12.86	0-2	0
	1	36	13.19	12.89	12.81		0
	1	74	13.02	12.72	12.81		0
	36	0	12.83	12.46	12.56	0-3	0
	36	18	12.80	12.48	12.51		0
	36	37	12.66	12.45	12.45		0
	75	0	12.74	12.47	12.51		0

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 50 of 114

Table 8-39
LTE Band 66 Conducted Powers Ant C - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.24	13.03	13.11	0	0
	1	25	13.19	13.10	13.08		0
	1	49	13.06	12.95	13.04		0
	25	0	13.08	12.93	13.03	0-1	0
	25	12	13.08	12.95	13.02		0
	25	25	13.06	12.97	12.99		0
16QAM	50	0	13.07	12.99	13.01	0-1	0
	1	0	12.91	12.91	12.95		0
	1	25	12.96	12.92	12.94		0
	1	49	12.80	12.88	12.88	0-2	0
	25	0	12.68	12.52	12.51		0
	25	12	12.65	12.50	12.51		0
64QAM	25	25	12.63	12.50	12.44	0-2	0
	50	0	12.63	12.50	12.48		0
	1	0	13.00	12.80	12.87		0-2
	1	25	12.97	12.93	12.89	0	
	1	49	12.81	12.78	12.90	0-3	
	25	0	12.66	12.46	12.55		0
25	12	12.63	12.48	12.52	0		
64QAM	25	25	12.61	12.49	12.48	0-3	0
	50	0	12.60	12.47	12.52		0

Table 8-40
LTE Band 66 Conducted Powers Ant C - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.12	12.81	12.96	0	0
	1	12	13.06	12.87	12.84		0
	1	24	13.08	12.84	12.82		0
	12	0	13.05	12.76	12.87	0-1	0
	12	6	13.00	12.78	12.81		0
	12	13	12.98	12.77	12.82		0
16QAM	25	0	13.03	12.78	12.83	0-1	0
	1	0	13.14	12.79	13.07		0
	1	12	13.07	12.87	12.96		0
	1	24	13.10	12.85	12.96	0-2	0
	12	0	12.83	12.50	12.64		0
	12	6	12.79	12.54	12.59		0
64QAM	12	13	12.77	12.55	12.65	0-2	0
	25	0	12.78	12.53	12.58		0
	1	0	13.11	12.72	12.88	0-2	0
	1	12	13.06	12.82	12.93		0
	1	24	13.11	12.77	12.89	0-3	0
	12	0	12.85	12.51	12.68		0
12	6	12.80	12.56	12.57	0		
12	13	12.78	12.55	12.49	0		
	25	0	12.81	12.55	12.58		0

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 51 of 114

Table 8-41
LTE Band 66 Conducted Powers Ant C - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.17	12.85	12.87	0	0
	1	7	13.22	12.92	12.90		0
	1	14	13.13	12.82	12.79		0
	8	0	13.20	12.80	12.83	0-1	0
	8	4	13.18	12.83	12.84		0
	8	7	13.15	12.82	12.83		0
16QAM	15	0	13.17	12.80	12.84	0-1	0
	1	0	13.07	12.75	12.74		0
	1	7	13.11	12.85	12.86		0
	1	14	13.00	12.75	12.73	0-2	0
	8	0	12.98	12.63	12.62		0
	8	4	12.97	12.66	12.67		0
64QAM	8	7	12.94	12.65	12.66	0-2	0
	15	0	12.94	12.56	12.65		0
	1	0	13.07	12.67	12.78		0-2
	1	7	13.13	12.84	12.85	0	
	1	14	13.03	12.80	12.74	0	
	8	0	12.95	12.61	12.59	0-3	0
8	4	12.90	12.63	12.66	0		
8	7	12.84	12.62	12.60	0		
	15	0	12.88	12.66	12.64		0

Table 8-42
LTE Band 66 Conducted Powers Ant C - 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.09	12.95	12.85	0	0
	1	2	13.07	12.95	12.79		0
	1	5	13.08	12.96	12.78		0
	3	0	13.08	12.87	12.82		0
	3	2	13.07	12.85	12.81		0
	3	3	13.08	12.86	12.82		0
	6	0	13.08	12.88	12.83	0-1	0
16QAM	1	0	13.18	13.08	13.01	0-1	0
	1	2	13.15	13.04	13.00		0
	1	5	13.13	13.06	12.97		0
	3	0	12.83	12.74	12.69		0
	3	2	12.89	12.73	12.71		0
	3	3	12.88	12.75	12.69		0
	6	0	12.90	12.72	12.68	0-2	0
64QAM	1	0	13.10	13.01	12.86	0-2	0
	1	2	13.02	13.03	12.93		0
	1	5	13.10	13.00	12.93		0
	3	0	12.90	12.80	12.70		0
	3	2	12.89	12.77	12.72		0
	3	3	12.88	12.71	12.60		0
	6	0	12.89	12.72	12.66	0-3	0

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 52 of 114

Table 8-43
LTE Band 66 Conducted Powers Ant D - 20 MHz Bandwidth

LTE Band 66 (AWS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.12	13.11	12.99	0	0
	1	50	13.04	13.09	12.98		0
	1	99	13.01	12.95	12.98		0
	50	0	13.08	13.07	12.97	0-1	0
	50	25	13.13	13.01	12.90		0
	50	50	13.12	12.91	12.91		0
	100	0	13.06	13.01	12.93		0
16QAM	1	0	13.10	13.12	12.91	0-1	0
	1	50	13.04	12.97	12.98		0
	1	99	12.93	12.93	12.80		0
	50	0	12.87	12.83	12.73	0-2	0
	50	25	12.87	12.71	12.71		0
	50	50	12.83	12.65	12.65		0
	100	0	12.90	12.80	12.76		0
64QAM	1	0	13.13	12.76	12.70	0-2	0
	1	50	13.02	12.94	12.76		0
	1	99	12.98	12.60	12.51		0
	50	0	12.52	12.58	12.40	0-3	0
	50	25	12.51	12.49	12.39		0
	50	50	12.54	12.42	12.37		0
	100	0	12.56	12.47	12.40		0

Table 8-44
LTE Band 66 Conducted Powers Ant D - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.09	12.98	12.83	0	0
	1	36	13.08	13.12	12.95		0
	1	74	13.16	12.84	12.80		0
	36	0	13.15	13.12	12.98	0-1	0
	36	18	13.17	13.11	12.97		0
	36	37	13.09	12.99	12.93		0
	75	0	13.14	13.00	12.97		0
16QAM	1	0	13.20	13.20	12.90	0-1	0
	1	36	13.20	13.19	13.00		0
	1	74	13.08	12.99	12.88		0
	36	0	12.85	12.85	12.76	0-2	0
	36	18	12.89	12.85	12.75		0
	36	37	12.78	12.78	12.69		0
	75	0	12.86	12.82	12.73		0
64QAM	1	0	13.20	12.83	12.80	0-2	0
	1	36	13.08	13.20	12.97		0
	1	74	12.94	13.06	12.83		0
	36	0	12.87	12.86	12.82	0-3	0
	36	18	12.87	12.85	12.77		0
	36	37	12.78	12.81	12.77		0
	75	0	12.85	12.84	12.73		0

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 53 of 114

Table 8-45
LTE Band 66 Conducted Powers Ant D - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.11	13.02	12.96	0	0
	1	25	13.11	13.00	12.86		0
	1	49	13.08	12.86	12.86		0
	25	0	13.12	13.02	12.98	0-1	0
	25	12	13.13	13.04	12.95		0
	25	25	13.11	13.03	12.92		0
16QAM	50	0	13.13	13.05	12.97	0-1	0
	1	0	13.16	13.07	13.17		0
	1	25	13.18	13.02	13.02		0
	1	49	13.13	13.02	12.90	0-2	0
	25	0	12.82	12.79	12.70		0
	25	12	12.87	12.78	12.68		0
64QAM	25	25	12.87	12.76	12.66	0-2	0
	50	0	12.81	12.76	12.66		0
	1	0	13.11	13.18	13.12		0-2
	1	25	13.12	13.06	13.01	0	
	1	49	13.17	13.08	12.95	0	
	64QAM	25	0	12.84	12.84	12.73	0-3
25		12	12.83	12.81	12.66	0	
25		25	12.88	12.77	12.67	0	
50		0	12.88	12.78	12.70		0

Table 8-46
LTE Band 66 Conducted Powers Ant D - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.19	13.09	12.85	0	0
	1	12	13.19	13.07	12.84		0
	1	24	13.20	13.05	12.81		0
	12	0	13.13	13.11	12.96	0-1	0
	12	6	13.08	13.11	12.92		0
	12	13	13.11	13.06	12.92		0
16QAM	25	0	13.10	13.10	12.94	0-1	0
	1	0	12.83	12.80	12.90		0
	1	12	13.07	13.20	12.92		0
	1	24	13.16	13.12	13.09	0-2	0
	12	0	12.94	12.98	12.75		0
	12	6	12.88	12.90	12.72		0
64QAM	12	13	12.95	12.88	12.74	0-2	0
	25	0	12.87	12.81	12.70		0
	1	0	12.91	13.13	12.76		0-2
	1	12	12.92	13.05	12.86	0	
	1	24	13.20	13.04	12.86	0	
	12	0	12.90	12.89	12.68	0-3	0
12	6	12.86	12.92	12.69	0		
12	13	12.92	12.85	12.61	0		
	25	0	12.86	12.87	12.57		0

FCC ID: BCGA2429	 PCTEST Proud to be part of the Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 54 of 114

Table 8-47
LTE Band 66 Conducted Powers Ant D - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.02	12.98	12.85	0	0
	1	7	13.09	13.06	12.88		0
	1	14	13.02	12.93	12.83		0
	8	0	13.17	13.11	12.97	0-1	0
	8	4	13.17	13.14	12.98		0
	8	7	13.14	13.11	12.98		0
16QAM	15	0	13.15	13.10	12.98	0-1	0
	1	0	13.16	13.16	13.02		0
	1	7	13.20	13.10	12.99		0
	1	14	13.12	12.96	12.93	0-2	0
	8	0	12.97	12.93	12.73		0
	8	4	13.03	12.91	12.85		0
64QAM	8	7	12.88	12.87	12.85	0-2	0
	15	0	12.96	12.92	12.78		0
	1	0	13.18	13.04	12.92		0-2
	1	7	13.20	12.91	12.96	0	
	1	14	13.15	13.09	12.82	0	
	8	0	13.06	13.02	12.81	0-3	0
8	4	13.00	13.00	12.82	0		
8	7	12.98	12.91	12.84	0		
	15	0	12.99	12.89	12.78		0

Table 8-48
LTE Band 66 Conducted Powers Ant D - 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.07	13.07	13.08	0	0
	1	2	13.06	13.04	13.06		0
	1	5	13.10	13.07	13.09		0
	3	0	13.19	13.11	12.94		0
	3	2	13.16	13.11	12.94		0
	3	3	13.18	13.12	12.96		0
	6	0	13.17	13.14	12.92	0-1	0
16QAM	1	0	13.20	13.11	12.88	0-1	0
	1	2	13.18	12.94	12.91		0
	1	5	13.20	13.18	12.82		0
	3	0	13.20	13.00	12.79		0
	3	2	13.11	13.01	12.72		0
	3	3	13.08	13.02	12.88		0
	6	0	13.03	12.93	12.84	0-2	0
64QAM	1	0	13.09	13.00	13.01	0-2	0
	1	2	13.17	12.98	13.11		0
	1	5	13.20	13.03	13.01		0
	3	0	13.04	13.01	13.04		0
	3	2	13.09	12.94	13.10		0
	3	3	13.06	13.00	13.06		0
	6	0	12.94	13.05	12.81	0-3	0

FCC ID: BCGA2429	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 55 of 114

8.3.7 LTE Band 25

Table 8-49
LTE Band 25 Conducted Powers Ant C - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.01	12.86	12.92	0	0
	1	50	12.80	12.82	13.00		0
	1	99	12.81	12.93	12.91		0
	50	0	13.04	12.74	12.93	0-1	0
	50	25	12.91	12.84	12.92		0
	50	50	12.92	12.87	12.85		0
	100	0	12.96	12.95	12.97		0
16QAM	1	0	12.96	12.85	12.76	0-1	0
	1	50	12.75	12.92	12.77		0
	1	99	12.68	12.68	12.66		0
	50	0	12.82	12.65	12.63	0-2	0
	50	25	12.72	12.59	12.69		0
	50	50	12.71	12.54	12.57		0
	100	0	12.73	12.49	12.64		0
64QAM	1	0	12.98	13.02	12.89	0-2	0
	1	50	12.85	12.89	12.91		0
	1	99	12.90	13.01	12.86		0
	50	0	12.85	12.48	12.67	0-3	0
	50	25	12.68	12.62	12.63		0
	50	50	12.68	12.63	12.57		0
	100	0	12.72	12.64	12.70		0

Table 8-50
LTE Band 25 Conducted Powers Ant C - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.84	12.97	12.97	0	0
	1	36	12.90	13.00	12.96		0
	1	74	12.85	13.04	12.80		0
	36	0	12.99	12.86	12.98	0-1	0
	36	18	12.95	12.90	13.01		0
	36	37	12.91	12.92	12.97		0
	75	0	12.94	12.96	12.98		0
16QAM	1	0	12.87	12.80	12.88	0-1	0
	1	36	12.89	12.72	12.87		0
	1	74	12.80	12.76	12.71		0
	36	0	12.57	12.42	12.59	0-2	0
	36	18	12.53	12.47	12.66		0
	36	37	12.51	12.46	12.59		0
	75	0	12.53	12.58	12.61		0
64QAM	1	0	13.03	12.99	12.92	0-2	0
	1	36	12.99	12.96	13.03		0
	1	74	12.85	13.00	12.97		0
	36	0	12.90	12.61	12.79	0-3	0
	36	18	12.70	12.69	12.75		0
	36	37	12.67	12.74	12.79		0
	75	0	12.67	12.70	12.74		0

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 56 of 114

Table 8-51
LTE Band 25 Conducted Powers Ant C - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.92	12.87	12.99	0	0
	1	25	12.87	12.82	12.90		0
	1	49	12.79	12.90	12.87		0
	25	0	12.91	12.94	13.02	0-1	0
	25	12	12.95	12.86	12.97		0
	25	25	12.89	12.89	12.99		0
	50	0	12.93	12.95	12.99		0
16QAM	1	0	12.94	12.61	12.86	0-1	0
	1	25	12.89	12.76	12.55		0
	1	49	12.70	12.69	12.80		0
	25	0	12.54	12.48	12.45	0-2	0
	25	12	12.56	12.39	12.50		0
	25	25	12.43	12.48	12.51		0
	50	0	12.58	12.50	12.53		0
64QAM	1	0	12.94	12.91	12.95	0-2	0
	1	25	12.95	12.92	12.99		0
	1	49	12.81	12.95	12.87		0
	25	0	12.80	12.66	12.84	0-3	0
	25	12	12.83	12.66	12.80		0
	25	25	12.71	12.74	12.65		0
	50	0	12.82	12.76	12.78		0

Table 8-52
LTE Band 25 Conducted Powers Ant C - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.08	12.94	12.78	0	0
	1	12	13.05	12.90	12.80		0
	1	24	13.10	12.93	12.81		0
	12	0	13.04	12.94	12.96	0-1	0
	12	6	12.99	12.89	12.96		0
	12	13	13.01	12.93	13.02		0
	25	0	12.99	12.97	12.97		0
16QAM	1	0	13.01	12.78	12.73	0-1	0
	1	12	12.88	12.72	12.78		0
	1	24	12.95	12.73	12.74		0
	12	0	12.64	12.48	12.52	0-2	0
	12	6	12.64	12.45	12.56		0
	12	13	12.64	12.47	12.57		0
	25	0	12.55	12.45	12.59		0
64QAM	1	0	12.82	12.81	13.01	0-2	0
	1	12	12.97	12.83	12.94		0
	1	24	12.94	12.99	12.72		0
	12	0	12.82	12.73	12.75	0-3	0
	12	6	12.86	12.72	12.80		0
	12	13	12.85	12.72	12.77		0
	25	0	12.82	12.77	12.73		0

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 57 of 114

Table 8-53
LTE Band 25 Conducted Powers Ant C - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.84	12.74	12.84	0	0
	1	7	12.95	12.82	12.94		0
	1	14	12.86	12.74	12.78		0
	8	0	12.99	12.88	12.94	0-1	0
	8	4	13.02	12.91	13.01		0
	8	7	12.96	12.90	13.01		0
	15	0	13.03	12.92	13.03		0
16QAM	1	0	12.84	12.55	12.88	0-1	0
	1	7	13.00	12.76	12.90		0
	1	14	12.85	12.55	12.65		0
	8	0	12.55	12.44	12.52	0-2	0
	8	4	12.61	12.49	12.56		0
	8	7	12.58	12.48	12.58		0
	15	0	12.58	12.47	12.57		0
64QAM	1	0	12.84	13.00	12.99	0-2	0
	1	7	12.96	12.84	12.99		0
	1	14	12.89	13.02	12.78		0
	8	0	12.90	12.70	12.78	0-3	0
	8	4	12.86	12.74	12.83		0
	8	7	12.84	12.74	12.81		0
	15	0	12.81	12.72	12.82		0

Table 8-54
LTE Band 25 Conducted Powers Ant C - 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.91	12.80	13.08	0	0
	1	2	12.92	12.74	13.09		0
	1	5	12.97	12.82	13.03		0
	3	0	13.01	12.86	12.99		0
	3	2	13.02	12.89	13.00		0
	3	3	13.05	12.89	12.91		0
	6	0	13.02	12.90	13.00	0-1	0
16QAM	1	0	12.80	12.67	12.75	0-1	0
	1	2	12.80	12.65	12.74		0
	1	5	12.82	12.69	12.73		0
	3	0	12.62	12.53	12.63		0
	3	2	12.60	12.58	12.59		0
	3	3	12.65	12.56	12.57		0
	6	0	12.59	12.49	12.58	0-2	0
64QAM	1	0	12.88	12.90	12.92	0-2	0
	1	2	12.90	12.81	12.98		0
	1	5	12.96	12.93	12.95		0
	3	0	12.86	12.81	12.84		0
	3	2	12.86	12.82	12.84		0
	3	3	12.89	12.72	12.78		0
	6	0	12.80	12.77	12.80	0-3	0

FCC ID: BCGA2429	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 58 of 114

Table 8-55
LTE Band 25 Conducted Powers Ant D - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.97	11.96	11.98	0	0
	1	50	11.80	11.84	11.97		0
	1	99	11.96	11.97	11.97		0
	50	0	11.95	11.82	12.00	0-1	0
	50	25	11.91	11.79	11.94		0
	50	50	11.93	11.91	11.95		0
	100	0	11.92	11.90	11.94		0
16QAM	1	0	11.76	11.73	11.82	0-1	0
	1	50	11.57	11.61	11.86		0
	1	99	11.59	11.62	11.95		0
	50	0	11.55	11.45	11.71	0-2	0
	50	25	11.48	11.46	11.64		0
	50	50	11.51	11.55	11.66		0
	100	0	11.52	11.59	11.64		0
64QAM	1	0	11.82	11.58	11.75	0-2	0
	1	50	11.70	11.32	11.71		0
	1	99	11.67	11.49	11.62		0
	50	0	11.27	11.21	11.52	0-3	0
	50	25	11.20	11.24	11.46		0
	50	50	11.28	11.25	11.42		0
	100	0	11.21	11.36	11.45		0

Table 8-56
LTE Band 25 Conducted Powers Ant D - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.00	11.89	11.94	0	0
	1	36	11.89	11.76	11.96		0
	1	74	11.82	11.92	11.96		0
	36	0	11.89	11.75	11.85	0-1	0
	36	18	11.84	11.72	11.88		0
	36	37	11.76	11.83	11.89		0
	75	0	11.83	11.84	11.93		0
16QAM	1	0	11.85	11.52	11.78	0-1	0
	1	36	11.75	11.64	11.65		0
	1	74	11.63	11.65	11.71		0
	36	0	11.45	11.26	11.36	0-2	0
	36	18	11.38	11.32	11.41		0
	36	37	11.37	11.39	11.47		0
	75	0	11.41	11.40	11.49		0
64QAM	1	0	11.78	11.43	11.63	0-2	0
	1	36	11.57	11.40	11.52		0
	1	74	11.50	11.54	11.58		0
	36	0	11.44	11.24	11.40	0-3	0
	36	18	11.37	11.23	11.41		0
	36	37	11.28	11.33	11.40		0
	75	0	11.35	11.31	11.40		0

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 59 of 114

Table 8-57
LTE Band 25 Conducted Powers Ant D - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.00	11.87	11.97	0	0
	1	25	11.98	11.81	11.95		0
	1	49	11.85	11.90	11.99		0
	25	0	11.88	11.69	11.82	0-1	0
	25	12	11.88	11.62	11.78		0
	25	25	11.79	11.69	11.88		0
	50	0	11.85	11.75	11.90		0
16QAM	1	0	11.59	11.41	11.61	0-1	0
	1	25	11.56	11.38	11.51		0
	1	49	11.45	11.51	11.60		0
	25	0	11.64	11.45	11.63	0-2	0
	25	12	11.65	11.38	11.60		0
	25	25	11.53	11.48	11.63		0
	50	0	11.66	11.52	11.62		0
64QAM	1	0	11.81	11.36	11.47	0-2	0
	1	25	11.67	11.30	11.43		0
	1	49	11.53	11.43	11.59		0
	25	0	11.32	11.21	11.28	0-3	0
	25	12	11.34	11.15	11.27		0
	25	25	11.25	11.26	11.35		0
	50	0	11.35	11.23	11.35		0

Table 8-58
LTE Band 25 Conducted Powers Ant D - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.00	11.85	11.97	0	0
	1	12	11.99	11.81	12.00		0
	1	24	11.93	11.82	12.00		0
	12	0	11.93	11.69	11.88	0-1	0
	12	6	11.89	11.65	11.92		0
	12	13	11.82	11.72	11.94		0
	25	0	11.91	11.70	11.93		0
16QAM	1	0	11.63	11.39	11.70	0-1	0
	1	12	11.69	11.46	11.65		0
	1	24	11.68	11.48	11.73		0
	12	0	11.67	11.43	11.64	0-2	0
	12	6	11.63	11.42	11.66		0
	12	13	11.66	11.50	11.70		0
	25	0	11.66	11.54	11.64		0
64QAM	1	0	11.63	11.45	11.60	0-2	0
	1	12	11.44	11.43	11.62		0
	1	24	11.55	11.60	11.64		0
	12	0	11.50	11.20	11.42	0-3	0
	12	6	11.46	11.16	11.42		0
	12	13	11.49	11.27	11.45		0
	25	0	11.46	11.28	11.39		0

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 60 of 114

Table 8-59
LTE Band 25 Conducted Powers Ant D - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055	26365	26675		
			(1851.5 MHz)	(1882.5 MHz)	(1913.5 MHz)		
Conducted Power [dBm]							
QPSK	1	0	12.00	11.72	11.96	0	0
	1	7	12.00	11.78	12.00		0
	1	14	11.94	11.75	11.96		0
	8	0	11.97	11.71	11.94	0-1	0
	8	4	11.98	11.71	11.94		0
	8	7	11.92	11.70	11.95		0
	15	0	12.00	11.70	11.93		0
16QAM	1	0	11.62	11.43	11.64	0-1	0
	1	7	11.69	11.51	11.77		0
	1	14	11.73	11.45	11.62		0
	8	0	11.69	11.43	11.67	0-2	0
	8	4	11.71	11.49	11.72		0
	8	7	11.70	11.49	11.72		0
	15	0	11.73	11.50	11.74		0
64QAM	1	0	11.75	11.35	11.59	0-2	0
	1	7	11.76	11.35	11.62		0
	1	14	11.64	11.35	11.59		0
	8	0	11.57	11.23	11.43	0-3	0
	8	4	11.56	11.29	11.42		0
	8	7	11.48	11.26	11.48		0
	15	0	11.51	11.26	11.44		0

Table 8-60
LTE Band 25 Conducted Powers Ant D - 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047	26365	26683		
			(1850.7 MHz)	(1882.5 MHz)	(1914.3 MHz)		
Conducted Power [dBm]							
QPSK	1	0	12.00	11.71	11.99	0	0
	1	2	12.00	11.66	11.98		0
	1	5	11.99	11.76	12.00		0
	3	0	11.95	11.64	11.91		0
	3	2	11.89	11.69	11.90		0
	3	3	11.90	11.70	11.92		0
	6	0	11.91	11.73	11.95	0-1	0
16QAM	1	0	11.69	11.43	11.75	0-1	0
	1	2	11.73	11.35	11.74		0
	1	5	11.78	11.45	11.72		0
	3	0	11.65	11.40	11.71		0
	3	2	11.69	11.47	11.68		0
	3	3	11.69	11.46	11.71		0
	6	0	11.67	11.44	11.72	0-2	0
64QAM	1	0	11.82	11.37	11.64	0-2	0
	1	2	11.86	11.28	11.61		0
	1	5	11.74	11.38	11.64		0
	3	0	11.66	11.22	11.69		0
	3	2	11.56	11.31	11.59		0
	3	3	11.60	11.38	11.67		0
	6	0	11.50	11.34	11.45	0-3	0

FCC ID: BCGA2429	 PCTEST Proud to be part of the Element	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 61 of 114

8.3.1 LTE Band 30

Table 8-61
LTE Band 30 Conducted Powers Ant C - 10 MHz Bandwidth

LTE Band 30 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz) Conducted Power [dBm]		
QPSK	1	0	13.07	0	0
	1	25	12.96		0
	1	49	13.00		0
	25	0	13.02	0-1	0
	25	12	13.05		0
	25	25	13.01		0
	50	0	13.03		0
16QAM	1	0	12.93	0-1	0
	1	25	12.86		0
	1	49	12.88		0
	25	0	12.55	0-2	0
	25	12	12.47		0
	25	25	12.46		0
	50	0	12.52		0
64QAM	1	0	13.05	0-2	0
	1	25	12.77		0
	1	49	12.68		0
	25	0	12.50	0-3	0
	25	12	12.43		0
	25	25	12.36		0
	50	0	12.44		0

Table 8-62
LTE Band 30 Conducted Powers Ant C - 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz) Conducted Power [dBm]		
QPSK	1	0	13.03	0	0
	1	12	13.09		0
	1	24	13.11		0
	12	0	13.09	0-1	0
	12	6	13.06		0
	12	13	13.07		0
	25	0	13.15		0
16QAM	1	0	12.92	0-1	0
	1	12	12.88		0
	1	24	12.87		0
	12	0	12.65	0-2	0
	12	6	12.64		0
	12	13	12.59		0
	25	0	12.64		0
64QAM	1	0	12.99	0-2	0
	1	12	12.93		0
	1	24	12.92		0
	12	0	12.63	0-3	0
	12	6	12.55		0
	12	13	12.54		0
	25	0	12.64		0

Note: LTE Band 30 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 62 of 114

Table 8-63
LTE Band 30 Conducted Powers Ant D - 10 MHz Bandwidth

LTE Band 30 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz) Conducted Power [dBm]		
QPSK	1	0	12.76	0	0
	1	25	12.63		0
	1	49	12.68		0
	25	0	12.78	0-1	0
	25	12	12.70		0
	25	25	12.68		0
	50	0	12.73		0
16QAM	1	0	12.68	0-1	0
	1	25	12.52		0
	1	49	12.51		0
	25	0	12.25	0-2	0
	25	12	12.15		0
	25	25	12.14		0
	50	0	12.15		0
64QAM	1	0	12.63	0-2	0
	1	25	12.45		0
	1	49	12.68		0
	25	0	12.19	0-3	0
	25	12	12.20		0
	25	25	12.17		0
	50	0	12.18		0

Table 8-64
LTE Band 30 Conducted Powers Ant D - 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz) Conducted Power [dBm]		
QPSK	1	0	12.77	0	0
	1	12	12.73		0
	1	24	12.77		0
	12	0	12.74	0-1	0
	12	6	12.66		0
	12	13	12.69		0
	25	0	12.68		0
16QAM	1	0	12.60	0-1	0
	1	12	12.46		0
	1	24	12.55		0
	12	0	12.38	0-2	0
	12	6	12.35		0
	12	13	12.33		0
	25	0	12.36		0
64QAM	1	0	12.60	0-2	0
	1	12	12.46		0
	1	24	12.55		0
	12	0	12.38	0-3	0
	12	6	12.35		0
	12	13	12.33		0
	25	0	12.36		0

Note: LTE Band 30 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: BCGA2429	 PCTEST Proud to be part of Telemet	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 63 of 114

8.3.2 LTE Band 7

Table 8-65
LTE Band 7 Conducted Powers Ant C - 20 MHz Bandwidth

LTE Band 7							
20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20850 (2510.0 MHz)	21100 (2535.0 MHz)	21350 (2560.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.08	12.30	11.93	0	0
	1	50	12.18	12.25	11.97		0
	1	99	12.33	12.22	11.95		0
	50	0	12.17	12.20	12.08	0-1	0
	50	25	12.14	12.21	12.14		0
	50	50	12.25	12.21	12.02		0
	100	0	12.16	12.23	12.15		0
16QAM	1	0	12.01	12.25	11.76	0-1	0
	1	50	12.03	12.15	11.74		0
	1	99	12.02	12.13	12.02		0
	50	0	11.91	12.05	11.78	0-2	0
	50	25	11.92	12.06	11.88		0
	50	50	11.96	12.04	11.85		0
	100	0	11.98	12.02	11.85		0
64QAM	1	0	11.95	12.27	11.64	0-2	0
	1	50	11.87	12.28	11.77		0
	1	99	11.86	12.22	11.78		0
	50	0	11.68	11.82	11.55	0-3	0
	50	25	11.68	11.83	11.53		0
	50	50	11.70	11.72	11.54		0
	100	0	11.75	11.80	11.60		0

Table 8-66
LTE Band 7 Conducted Powers Ant C - 15 MHz Bandwidth

LTE Band 7							
15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825	21100	21375		
			(2507.5 MHz)	(2535.0 MHz)	(2562.5 MHz)		
Conducted Power [dBm]							
QPSK	1	0	12.01	12.21	11.98	0	0
	1	36	12.00	12.19	11.96		0
	1	74	12.09	12.11	11.99		0
	36	0	12.01	12.28	12.03	0-1	0
	36	18	12.08	12.33	11.99		0
	36	37	12.07	12.32	11.98		0
	75	0	12.08	12.29	12.01		0
16QAM	1	0	12.06	12.24	11.96	0-1	0
	1	36	12.17	12.35	12.09		0
	1	74	12.26	12.13	12.22		0
	36	0	11.77	12.07	11.91	0-2	0
	36	18	11.92	12.11	11.94		0
	36	37	11.94	12.11	11.86		0
	75	0	11.92	12.03	11.86		0
64QAM	1	0	12.15	12.23	11.96	0-2	0
	1	36	11.99	12.20	12.15		0
	1	74	12.19	12.06	12.00		0
	36	0	11.78	12.09	11.94	0-3	0
	36	18	11.92	12.09	11.97		0
	36	37	11.98	12.09	11.93		0
	75	0	11.91	12.03	11.90		0

FCC ID: BCGA2429	 PCTEST Proud to be part of		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 64 of 114

Table 8-67
LTE Band 7 Conducted Powers Ant C - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.99	12.28	11.94	0	0
	1	25	11.76	12.27	11.88		0
	1	49	12.02	12.29	11.93		0
	25	0	11.91	12.29	12.12	0-1	0
	25	12	11.89	12.30	12.03		0
	25	25	11.98	12.34	12.03		0
16QAM	50	0	11.98	12.32	12.01	0-1	0
	1	0	12.18	12.25	11.90		0
	1	25	11.85	12.17	11.97		0
	1	49	12.25	12.36	12.04	0-2	0
	25	0	11.77	12.09	11.84		0
	25	12	11.76	12.03	11.80		0
64QAM	25	25	11.84	12.12	11.89	0-2	0
	50	0	11.78	12.03	11.82		0
	1	0	12.02	12.12	11.87		0-2
	1	25	11.90	12.18	11.98	0	
	1	49	12.13	12.27	12.04	0-3	
	25	0	11.71	12.04	11.87		0
25	12	11.71	12.08	11.85	0		
64QAM	25	25	11.75	12.11	11.89	0-3	0
	50	0	11.68	12.05	11.83		0

Table 8-68
LTE Band 7 Conducted Powers Ant C - 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.18	12.14	11.91	0	0
	1	12	11.93	12.15	11.92		0
	1	24	11.95	12.18	11.97		0
	12	0	12.09	12.18	12.01	0-1	0
	12	6	11.93	12.18	12.00		0
	12	13	11.90	12.23	12.05		0
16QAM	25	0	11.97	12.20	12.03	0-1	0
	1	0	12.35	12.21	12.11		0
	1	12	12.09	12.03	11.98		0
	1	24	11.93	12.24	12.11	0-2	0
	12	0	11.94	12.04	11.90		0
	12	6	11.76	12.03	11.88		0
64QAM	12	13	11.73	12.10	11.87	0-2	0
	25	0	11.72	12.04	11.88		0
	1	0	11.96	12.29	12.06		0-2
	1	12	11.75	12.28	12.12	0	
	1	24	11.84	12.40	12.11	0-3	
	12	0	11.86	12.07	11.88		0
12	6	11.71	12.13	11.89	0		
64QAM	12	13	11.68	12.13	11.86	0-3	0
	25	0	11.74	12.12	11.84		0

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 65 of 114

Table 8-69
LTE Band 7 Conducted Powers Ant D - 20 MHz Bandwidth

LTE Band 7 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20850 (2510.0 MHz)	21100 (2535.0 MHz)	21350 (2560.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.78	11.92	11.79	0	0
	1	50	11.79	11.91	11.83		0
	1	99	11.73	11.90	11.80		0
	50	0	11.70	11.95	11.78	0-1	0
	50	25	11.78	11.94	11.82		0
	50	50	11.86	11.93	11.81		0
	100	0	11.84	11.83	11.80		0
16QAM	1	0	11.91	11.94	11.81	0-1	0
	1	50	11.85	11.88	11.78		0
	1	99	11.92	11.81	11.77		0
	50	0	11.76	11.89	11.68	0-2	0
	50	25	11.75	11.87	11.66		0
	50	50	11.81	11.82	11.66		0
	100	0	11.84	11.79	11.63		0
64QAM	1	0	12.12	12.06	11.99	0-2	0
	1	50	12.10	12.05	11.92		0
	1	99	12.18	12.00	11.86		0
	50	0	11.74	11.91	11.76	0-3	0
	50	25	11.76	11.90	11.77		0
	50	50	11.80	11.75	11.75		0
	100	0	11.88	11.78	11.77		0

Table 8-70
LTE Band 7 Conducted Powers Ant D - 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.06	11.97	11.91	0	0
	1	36	11.99	12.11	12.07		0
	1	74	12.03	12.01	12.03		0
	36	0	11.92	12.09	11.84	0-1	0
	36	18	11.99	12.2	11.92		0
	36	37	12.01	12.2	11.88		0
16QAM	75	0	12.04	12.19	11.94	0-1	0
	1	0	11.96	12.14	11.97		0
	1	36	11.86	12.17	12.07		0
	1	74	11.95	12.14	12.06	0-2	0
	36	0	11.69	11.85	11.66		0
	36	18	11.79	11.96	11.72		0
64QAM	36	37	11.78	11.96	11.67	0-2	0
	75	0	11.8	11.93	11.71		0
	1	0	11.97	12.03	12.08		0-2
	1	36	11.87	12.15	12.1	0	
	1	74	11.98	12.1	12.16	0-3	
	36	0	11.65	11.89	11.71		0
36	18	11.73	11.97	11.79	0		
64QAM	36	37	11.78	11.98	11.72	0-3	0
	75	0	11.74	11.95	11.78		0

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 66 of 114

Table 8-71
LTE Band 7 Conducted Powers Ant D - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.15	12.03	12.03	0	0
	1	25	11.91	12.01	12.02		0
	1	49	12.01	12.1	12.11		0
	25	0	11.94	12.07	11.95	0-1	0
	25	12	11.88	12.09	11.9		0
	25	25	11.92	12.11	11.93		0
	50	0	11.91	12.07	11.92		0
16QAM	1	0	11.98	12.15	12.09	0-1	0
	1	25	12.02	12.14	12.08		0
	1	49	11.88	12.17	12.07		0
	25	0	11.71	11.91	11.77	0-2	0
	25	12	11.59	11.95	11.74		0
	25	25	11.7	11.95	11.78		0
	50	0	11.63	11.84	11.74		0
64QAM	1	0	11.98	12.16	11.88	0-2	0
	1	25	12.17	12.15	11.91		0
	1	49	11.91	12.2	12.12		0
	25	0	11.67	11.87	11.81	0-3	0
	25	12	11.63	11.89	11.71		0
	25	25	11.69	11.91	11.76		0
	50	0	11.65	11.94	11.72		0

Table 8-72
LTE Band 7 Conducted Powers Ant D - 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.99	12.08	11.97	0	0
	1	12	11.78	12.1	11.98		0
	1	24	11.8	12.14	12.05		0
	12	0	12.03	12.14	11.88	0-1	0
	12	6	11.89	12.13	11.9		0
	12	13	11.88	12.16	11.93		0
16QAM	25	0	11.97	12.16	11.93	0-1	0
	1	0	12.03	12.03	12.05		0
	1	12	11.85	11.84	12.04		0
	1	24	11.94	11.9	12.12	0-2	0
	12	0	11.79	11.95	11.7		0
	12	6	11.72	11.9	11.71		0
64QAM	12	13	11.68	11.99	11.79	0-2	0
	25	0	11.71	11.92	11.73		0
	1	0	12.1	12.02	12		0-3
	1	12	12.01	11.87	12.03	0	
	1	24	11.93	11.9	12.07	0	
	12	0	11.79	11.92	11.71	0-3	0
12	6	11.8	11.93	11.77	0		
12	13	11.67	11.92	11.85	0		
	25	0	11.71	11.9	11.72		0

FCC ID: BCGA2429	 PCTEST Proud to be part of the Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 67 of 114

8.3.3 LTE Band 41

Table 8-73
LTE Band 41 Conducted Powers Ant C - 20 MHz Bandwidth

LTE Band 41 20 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	15.37	15.40	15.18	15.27	15.14	0	0	
	1	50	15.38	15.33	15.20	15.23	15.16		0-1	0
	1	99	15.34	15.26	15.17	15.13	15.09			0
	50	0	15.34	15.37	15.17	15.20	15.05	0		
	50	25	15.29	15.33	15.21	15.18	15.06	0		
	50	50	15.34	15.30	15.19	15.15	15.04	0		
	100	0	15.32	15.34	15.23	15.22	15.09	0		
16QAM	1	0	14.92	15.18	14.84	15.01	14.87	0-1	0	
	1	50	14.87	14.95	14.82	15.02	14.92		0-2	0
	1	99	14.98	14.97	14.93	14.84	15.04			0
	50	0	14.95	14.97	14.89	14.89	14.78	0		
	50	25	14.96	14.90	14.92	14.86	14.80	0		
	50	50	14.99	14.88	14.88	14.83	14.79	0		
	100	0	14.97	14.91	14.93	14.90	14.82	0		
64QAM	1	0	15.03	15.08	14.86	15.13	14.92	0-2	0	
	1	50	14.98	14.92	15.01	15.02	14.80		0-3	0
	1	99	15.01	15.10	15.03	15.01	14.85			0
	50	0	14.98	14.96	14.88	14.83	14.77	0		
	50	25	14.97	14.92	14.89	14.82	14.77	0		
	50	50	14.96	14.91	14.90	14.83	14.78	0		
	100	0	15.02	14.92	14.92	14.85	14.82	0		

Table 8-74
LTE Band 41 Conducted Powers Ant C - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.05	15.30	14.92	15.20	14.98	0	0
	1	36	15.19	15.24	15.02	15.28	15.05		0
	1	74	15.07	15.10	14.97	15.15	14.92		0
	36	0	15.07	15.28	14.90	15.18	14.95	0-1	0
	36	18	15.09	15.23	14.93	15.19	14.99		0
	36	37	15.04	15.17	14.91	15.14	14.96		0
	75	0	15.03	15.21	14.93	15.18	15.00		0
16QAM	1	0	15.25	15.35	14.92	15.20	15.02	0-1	0
	1	36	15.29	15.23	14.98	15.26	15.04		0
	1	74	15.24	15.14	14.97	15.10	14.96		0
	36	0	15.24	15.31	14.97	15.18	14.95	0-2	0
	36	18	15.32	15.27	15.04	15.26	14.97		0
	36	37	15.30	15.22	15.03	15.20	14.96		0
	75	0	15.27	15.24	15.04	15.24	14.98		0
64QAM	1	0	15.22	15.23	14.99	15.21	14.94	0-2	0
	1	36	15.30	15.20	15.01	15.38	14.99		0
	1	74	15.24	15.10	14.98	15.08	14.88		0
	36	0	15.21	15.28	14.96	15.14	14.93	0-3	0
	36	18	15.26	15.21	15.02	15.21	14.97		0
	36	37	15.24	15.18	15.00	15.17	14.94		0
	75	0	15.19	15.20	15.01	15.20	14.95		0

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 68 of 114

Table 8-75
LTE Band 41 Conducted Powers Ant C - 10 MHz Bandwidth

LTE Band 41									
10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.09	15.21	14.98	15.15	15.02	0	0
	1	25	15.16	15.32	15.05	15.21	15.05		0
	1	49	15.23	15.30	15.11	15.20	15.07		0
	25	0	15.04	15.28	14.97	15.14	15.02	0-1	0
	25	12	15.07	15.19	14.96	15.14	15.00		0
	25	25	15.03	15.18	14.98	15.12	14.99		0
	50	0	15.01	15.21	14.98	15.15	15.02		0
16QAM	1	0	15.24	15.26	15.00	15.21	14.99	0-1	0
	1	25	15.20	15.19	14.99	15.13	14.95		0
	1	49	15.35	15.18	15.01	15.11	15.02		0
	25	0	15.26	15.33	14.99	15.12	14.96	0-2	0
	25	12	15.28	15.27	14.98	15.18	14.95		0
	25	25	15.29	15.27	14.99	15.19	14.97		0
	50	0	15.24	15.29	15.00	15.20	14.96		0
64QAM	1	0	14.95	15.00	14.76	14.96	14.63	0-2	0
	1	25	14.86	14.83	14.80	14.89	14.64		0
	1	49	14.93	14.89	14.82	14.93	14.64		0
	25	0	14.95	15.01	14.76	14.90	14.65	0-3	0
	25	12	14.99	14.94	14.77	14.97	14.64		0
	25	25	15.01	14.91	14.78	14.94	14.68		0
	50	0	14.95	14.92	14.77	14.97	14.67		0

Table 8-76
LTE Band 41 Conducted Powers Ant C - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.23	15.26	15.01	15.19	14.95	0	0
	1	12	15.31	15.24	15.09	15.29	15.03		0
	1	24	15.40	15.25	15.12	15.30	15.08		0
	12	0	15.26	15.24	15.00	15.11	14.93	0-1	0
	12	6	15.28	15.24	14.99	15.22	14.93		0
	12	13	15.25	15.23	15.00	15.21	14.95		0
	25	0	15.24	15.25	15.01	15.22	14.95		0
16QAM	1	0	15.21	15.40	15.00	15.21	15.05	0-1	0
	1	12	15.30	15.25	15.03	15.25	15.02		0
	1	24	15.38	15.29	15.05	15.29	15.00		0
	12	0	15.27	15.30	14.99	15.18	14.93	0-2	0
	12	6	15.29	15.24	15.00	15.16	14.93		0
	12	13	15.24	15.29	14.99	15.22	14.94		0
	25	0	15.22	15.30	15.01	15.25	14.92		0
64QAM	1	0	14.94	15.16	14.78	14.94	14.60	0-2	0
	1	12	15.09	14.92	15.03	15.19	14.85		0
	1	24	15.03	14.86	14.80	15.03	14.74		0
	12	0	14.93	14.94	14.80	14.89	14.67	0-3	0
	12	6	15.05	14.91	14.84	15.01	14.68		0
	12	13	15.00	14.95	14.74	14.97	14.67		0
	25	0	14.94	14.95	14.77	14.96	14.68		0

FCC ID: BCGA2429	 PCTEST Proud to be part of  element	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 69 of 114

Table 8-77
LTE Band 41 Conducted Powers Ant D - 20 MHz Bandwidth

LTE Band 41 20 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.11	15.22	15.12	15.17	14.95	0	0
	1	50	15.10	15.24	15.12	15.16	14.91		0
	1	99	15.06	15.16	15.08	15.08	14.86		0
	50	0	15.04	15.23	14.99	15.12	14.86	0-1	0
	50	25	15.05	15.21	14.98	15.13	14.78		0
	50	50	15.01	15.16	14.96	15.09	14.79		0
	100	0	15.03	15.17	14.95	15.10	14.79		0
16QAM	1	0	15.02	15.22	15.17	15.09	14.86	0-1	0
	1	50	15.05	15.19	15.10	15.10	14.85		0
	1	99	14.96	15.08	15.08	15.02	14.80		0
	50	0	14.96	15.15	14.96	15.08	14.80	0-2	0
	50	25	14.96	15.14	14.96	15.06	14.77		0
	50	50	14.95	15.08	14.93	15.03	14.75		0
	100	0	14.94	15.11	14.95	15.06	14.77		0
64QAM	1	0	15.02	15.37	15.17	15.27	15.11	0-2	0
	1	50	15.09	15.29	15.12	15.26	14.97		0
	1	99	15.12	15.24	15.02	15.14	14.76		0
	50	0	14.97	15.17	14.97	15.19	14.78	0-3	0
	50	25	14.92	15.18	14.96	15.07	14.77		0
	50	50	14.90	15.12	14.93	15.05	14.75		0
	100	0	14.91	15.11	14.96	15.07	14.78		0

Table 8-78
LTE Band 41 Conducted Powers Ant D - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.08	15.21	15.00	15.18	14.99	0	0
	1	36	15.17	15.20	15.06	15.25	14.99		0
	1	74	15.10	15.08	14.96	15.09	14.88		0
	36	0	15.16	15.13	15.03	15.14	15.01	0-1	0
	36	18	15.16	15.10	15.06	15.23	15.01		0
	36	37	15.12	15.05	15.01	15.15	14.93		0
	75	0	15.10	15.09	15.05	15.22	15.00		0
16QAM	1	0	15.17	15.37	14.86	15.20	14.89	0-1	0
	1	36	15.20	15.20	15.09	15.24	15.00		0
	1	74	15.16	15.19	15.01	15.23	15.11		0
	36	0	15.13	15.16	15.06	15.11	14.99	0-2	0
	36	18	15.15	15.07	15.05	15.21	14.98		0
	36	37	15.10	15.02	15.00	15.14	14.93		0
	75	0	15.10	15.09	15.04	15.20	14.99		0
64QAM	1	0	15.07	15.05	15.12	15.12	15.17	0-2	0
	1	36	15.36	15.03	15.23	15.13	15.17		0
	1	74	15.31	15.02	15.01	15.07	14.97		0
	36	0	15.14	15.11	15.02	15.10	14.97	0-3	0
	36	18	15.13	15.10	15.04	15.21	14.99		0
	36	37	15.08	15.04	14.98	15.12	14.90		0
	75	0	15.07	15.06	15.05	15.19	14.97		0

FCC ID: BCGA2429	 PCTEST Proud to be part of 	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 70 of 114

Table 8-79
LTE Band 41 Conducted Powers Ant D - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.22	15.06	15.16	15.30	14.95	0	0
	1	25	15.13	15.08	15.11	15.32	15.02		0
	1	49	15.25	15.08	15.12	15.27	15.00		0
	25	0	15.08	15.13	15.03	15.11	14.96	0-1	0
	25	12	15.11	15.05	15.02	15.18	14.93		0
	25	25	15.09	15.04	15.01	15.18	14.90		0
	50	0	15.07	15.07	15.03	15.20	14.95		0
16QAM	1	0	15.21	15.17	15.18	15.22	15.13	0-1	0
	1	25	15.13	15.10	15.14	15.22	15.05		0
	1	49	15.21	15.13	15.15	15.23	15.00		0
	25	0	15.06	15.05	15.01	15.10	14.92	0-2	0
	25	12	15.09	14.97	15.00	15.14	14.90		0
	25	25	15.07	14.96	15.00	15.12	14.89		0
	50	0	15.05	14.98	15.01	15.17	14.91		0
64QAM	1	0	15.09	15.22	15.18	15.07	15.14	0-2	0
	1	25	14.96	15.12	15.14	15.09	15.05		0
	1	49	15.08	15.13	15.11	15.10	15.03		0
	25	0	15.06	15.05	15.01	15.07	14.93	0-3	0
	25	12	15.07	15.04	14.99	15.15	14.91		0
	25	25	15.05	14.96	15.01	15.13	14.88		0
	50	0	15.02	14.99	15.01	15.15	14.91		0

Table 8-80
LTE Band 41 Conducted Powers Ant D - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.23	15.06	15.19	15.17	14.99	0	0
	1	12	15.16	15.16	15.17	15.25	15.11		0
	1	24	15.22	15.14	15.19	15.24	15.11		0
	12	0	15.09	15.06	15.05	15.19	14.99	0-1	0
	12	6	15.10	15.02	15.04	15.25	14.99		0
	12	13	15.06	15.02	15.05	15.22	14.97		0
	25	0	15.05	15.04	15.06	15.23	14.98		0
16QAM	1	0	15.26	15.04	15.14	15.25	14.94	0-1	0
	1	12	15.31	15.31	15.08	15.25	14.98		0
	1	24	15.33	15.34	15.13	15.22	14.93		0
	12	0	15.12	15.03	15.01	15.13	15.00	0-2	0
	12	6	15.07	15.02	15.00	15.21	14.98		0
	12	13	15.04	14.96	15.00	15.21	14.93		0
	25	0	15.06	15.03	15.05	15.24	14.92		0
64QAM	1	0	15.20	14.98	15.27	15.19	14.96	0-2	0
	1	12	15.19	15.16	15.03	15.32	15.07		0
	1	24	15.23	15.26	15.18	15.34	15.22		0
	12	0	15.12	15.06	15.04	15.13	15.02	0-3	0
	12	6	15.14	15.06	15.01	15.18	14.95		0
	12	13	15.09	15.03	15.12	15.21	15.01		0
	25	0	15.06	15.00	15.04	15.21	14.97		0

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 71 of 114

8.3.4 LTE Band 41 PC2

Table 8-81
LTE Band 41 PC2 Conducted Powers Ant C - 20 MHz Bandwidth

LTE Band 41									
20 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.16	15.20	15.31	15.15	14.85	0	0
	1	50	15.13	15.10	15.20	15.02	14.79		0
	1	99	15.24	15.11	15.25	14.98	14.88		0
	50	0	15.15	15.20	15.01	15.10	14.82	0-1	0
	50	25	15.19	15.23	14.99	15.06	14.81		0
	50	50	15.15	15.18	15.04	15.02	14.82		0
	100	0	15.18	15.16	15.04	15.09	14.87		0

Table 8-82
LTE Band 41 PC2 Conducted Powers Ant D - 20 MHz Bandwidth

LTE Band 41 20 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	15.07	15.35	15.01	15.18	15.02	0	0
	1	50	15.01	15.33	14.94	15.10	14.94		0
	1	99	15.07	15.22	14.86	14.99	14.84		0
	50	0	15.02	15.24	14.97	15.09	14.88	0-1	0
	50	25	14.96	15.18	14.93	15.07	14.83		0
	50	50	15.00	15.14	14.89	15.01	14.76		0
	100	0	14.99	15.13	14.92	15.11	14.87		0

8.3.5 LTE Uplink Carrier Aggregation Conducted Powers

Table 8-83
LTE Uplink Carrier Aggregation Conducted Powers – Antenna C

Combination	PCC Band	PCC Bandwidth [MHz]	PCC UL Channel	PCC UL Frequency [MHz]	PCC DL Channel	PCC DL Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	SCC Band	SCC Bandwidth [MHz]	SCC UL Channel	SCC UL Frequency [MHz]	SCC DL Channel	SCC DL Frequency [MHz]	Modulation	SCC UL# RB	SCC UL RB Offset	LTE Tx.Power with UL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_7C (1)	LTE B7	20	21350	2560.0	3350	2680.0	QPSK	1	0	LTE B7	20	21152	2540.2	3152	2660.2	QPSK	1	99	12.30	11.93
Combination	PCC Band	PCC Bandwidth [MHz]	PCC (UL/DL) Channel	PCC (UL/DL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	SCC Band	SCC Bandwidth [MHz]	SCC (UL/DL) Channel	SCC (UL/DL) Frequency [MHz]	Modulation	SCC UL# RB	SCC UL RB Offset	LTE Tx.Power with UL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)				
CA_41C	LTE B41	20	41490	2680.0	QPSK	1	0	LTE B41	20	41292	2660.2	QPSK	1	99	15.05	15.14				

Table 8-84
LTE Uplink Carrier Aggregation Conducted Powers – Antenna D

Combination	PCC Band	PCC Bandwidth [MHz]	PCC UL Channel	PCC UL Frequency [MHz]	PCC DL Channel	PCC DL Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	SCC Band	SCC Bandwidth [MHz]	SCC UL Channel	SCC UL Frequency [MHz]	SCC DL Channel	SCC DL Frequency [MHz]	Modulation	SCC UL# RB	SCC UL RB Offset	LTE Tx.Power with UL CA Enabled (dbm)	LTE Single Carrier Tx Power (dbm)
CA_7C (1)	LTE B7	20	21350	2560.0	3350	2680.0	QPSK	50	0	LTE B7	20	21152	2540.2	3152	2660.2	QPSK	50	50	12.10	11.78
Combination	PCC Band	PCC Bandwidth [MHz]	PCC (UL/DL) Channel	PCC (UL/DL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	SCC Band	SCC Bandwidth [MHz]	SCC (UL/DL) Channel	SCC (UL/DL) Frequency [MHz]	Modulation	SCC UL# RB	SCC UL RB Offset	LTE Tx.Power with UL CA Enabled (dbm)	LTE Single Carrier Tx Power (dbm)				
CA_41C	LTE B41	20	40620	2593.0	QPSK	50	0	LTE B41	20	40422	2573.2	QPSK	50	50	14.81	14.99				

FCC ID: BCGA2429		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 72 of 114

Notes:

1. This device supports uplink carrier aggregation for LTE CA_7C and LTE CA_41C with a maximum of two 20 MHz component carriers. For intraband contiguous carrier aggregation scenarios, 3GPP 36.101 Table 6.2.2A-1 specifies that the aggregate maximum allowed output power is equivalent to the single carrier scenario. 3GPP 36.101 6.2.3A allows for several dB of MPR to be applied when non-contiguous RB allocation is implemented. The conducted powers and MPR settings in this device are permanently implemented per the above 3GPP requirements.
2. Per FCC Guidance, the output power with uplink CA active was measured for the configuration with the highest reported SAR with single carrier for each exposure condition. The power was measured with wideband signal integration over both component carriers.
3. Uplink carrier aggregation is only possible when the device is operating with Power Class 3 for LTE Band 41.



Figure 8-3
Power Measurement Setup

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 73 of 114

8.4 WLAN Conducted Powers

8.4.1 Variant 1

Table 8-85
2.4 GHz WLAN Maximum Average RF Power – Antenna A

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	15.21	14.91	14.98
2417	2	N/A	15.16	15.12
2437	6	15.06	14.90	15.15
2457	10	N/A	14.78	15.01
2462	11	15.04	13.00	13.10

Table 8-86
2.4 GHz WLAN Maximum Average RF Power – Antenna B

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	15.11	14.82	14.65
2417	2	N/A	15.07	14.82
2437	6	15.13	14.90	14.52
2457	10	N/A	14.82	14.63
2462	11	15.14	13.00	12.70

FCC ID: BCGA2429	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 74 of 114

Table 8-87
5 GHz WLAN Maximum Average RF Power – Antenna A

5GHz (40MHz) Conducted Power [dBm]			
Freq [MHz]	Channel	IEEE Transmission Mode	
		802.11n	802.11ac
		Average	Average
5190	38	12.94	12.86
5230	46	15.60	15.51
5270	54	16.01	15.97
5310	62	13.62	13.55
5755	151	15.23	15.24
5795	159	15.20	15.22

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
		Average
5530	106	10.93
5610	122	14.65
5690	138	16.69

Table 8-88
5 GHz WLAN Maximum Average RF Power – Antenna B

5GHz (40MHz) Conducted Power [dBm]			
Freq [MHz]	Channel	IEEE Transmission Mode	
		802.11n	802.11ac
		Average	Average
5190	38	12.99	12.96
5230	46	15.20	15.14
5270	54	16.02	16.10
5310	62	13.51	13.43
5755	151	15.52	15.50
5795	159	15.48	15.45

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
		Average
5530	106	11.03
5610	122	14.64
5690	138	16.40

FCC ID: BCGA2429	 PCTEST Proud to be part of  eSolutions	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 75 of 114

8.4.2 Variant 2

Table 8-89
2.4 GHz WLAN Maximum Average RF Power – Antenna A

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	15.14	14.73	14.23
2417	2	N/A	15.14	15.26
2437	6	15.15	15.05	15.20
2457	10	N/A	15.15	14.98
2462	11	15.12	13.00	13.95

Table 8-90
2.4 GHz WLAN Maximum Average RF Power – Antenna B

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	15.22	14.10	14.00
2417	2	N/A	15.00	15.06
2437	6	15.24	15.05	14.91
2457	10	N/A	14.74	14.85
2462	11	15.23	13.62	13.76

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 76 of 114

Table 8-91
5 GHz WLAN Maximum Average RF Power – Antenna A

5GHz (40MHz) Conducted Power [dBm]			
Freq [MHz]	Channel	IEEE Transmission Mode	
		802.11n	802.11ac
		Average	Average
5190	38	12.92	12.98
5230	46	15.35	15.29
5270	54	15.97	15.91
5310	62	13.60	13.54
5755	151	15.27	15.26
5795	159	15.12	15.15

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
		Average
5530	106	10.91
5610	122	14.36
5690	138	16.41

Table 8-92
5 GHz WLAN Maximum Average RF Power – Antenna B

5GHz (40MHz) Conducted Power [dBm]			
Freq [MHz]	Channel	IEEE Transmission Mode	
		802.11n	802.11ac
		Average	Average
5190	38	12.98	12.97
5230	46	15.35	15.31
5270	54	15.98	15.92
5310	62	13.40	13.35
5755	151	15.39	15.35
5795	159	15.40	15.40

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
		Average
5530	106	10.87
5610	122	14.49
5690	138	16.20

FCC ID: BCGA2429	 PCTEST Proud to be part of  eSpectrum	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 77 of 114

8.4.3 Notes for WLAN

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The WLAN chipset in this device is produced by two different suppliers. The electrically identical modules are manufactured with the identical mechanical structure to meet the same specifications and functions. Two device variants are referenced as Variant 1 and Variant 2 in this report.
- WLAN SAR worst case configuration was evaluated for Variant 1 and Variant 2. The Variant with the highest reported SAR value was evaluated for the remaining WLAN configurations.
- Full power measurements were performed for Variant 1 and Variant 2 per FCC KDB Procedures 248227.




Figure 8-4
Power Measurement Setup

8.5 Bluetooth Conducted Powers

Table 8-93
Maximum Bluetooth Average RF Power – Antenna A Variant 1

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2402	GFSK	1.0	0	16.17	41.400
2441	GFSK	1.0	39	16.25	42.170
2480	GFSK	1.0	78	15.00	31.623

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 78 of 114

Table 8-94
Maximum Bluetooth Average RF Power – Antenna A Variant 2

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2402	GFSK	1.0	0	15.70	37.154
2441	GFSK	1.0	39	16.14	41.115
2480	GFSK	1.0	78	16.17	41.400

Table 8-95
Reduced Bluetooth Average RF Power – Antenna A Variant 1

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2402	GFSK	1.0	0	9.80	9.550
2441	GFSK	1.0	39	9.61	9.141
2480	GFSK	1.0	78	9.62	9.162

Table 8-96
Reduced Bluetooth Average RF Power – Antenna A Variant 2

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2402	GFSK	1.0	0	9.56	9.036
2441	GFSK	1.0	39	9.68	9.290
2480	GFSK	1.0	78	9.40	8.710

FCC ID: BCGA2429	 Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 79 of 114




Figure 8-5
Bluetooth Transmission Plot & Duty Cycle Calculation – Antenna A Variant 1

Equation 8-1
Bluetooth Duty Cycle Calculation

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{2.897\text{ms}}{3.756\text{ms}} * 100\% = 77.1\%$$

FCC ID: BCGA2429	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 80 of 114




Figure 8-6
Bluetooth Transmission Plot & Duty Cycle Calculation – Antenna A Variant 2

Equation 8-2
Bluetooth Duty Cycle Calculation

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{2.897\text{ms}}{3.756\text{ms}} * 100\% = 77.1\%$$

FCC ID: BCGA2429	 PCTEST Proud to be part of  Lument	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 81 of 114

8.5.1 Bluetooth Power Reduction Verification Summary

Table 8-97
Bluetooth Power Reduction Verification

Antenna	Mode/Band	Condition (s)	Maximum Target Power [dBm]	Reduced Target Power [dBm]	Maximum Measured Power	Reduced Measured Power	Verdict
			(Tolerance [dB])	(Tolerance [dB])	[dBm]	[dBm]	
A	2.4 GHz Bluetooth	5 GHz WLAN ON Antenna A	15.50 (+1.5/-2.0)	8.50 (+1.5/-2.0)	15.21	8.43	Pass
	2.4 GHz Bluetooth	5 GHz WLAN ON Antenna B	15.50 (+1.5/-2.0)	8.50 (+1.5/-2.0)	15.24	8.35	Pass
	2.4 GHz Bluetooth	5 GHz WLAN ON Antenna A & Antenna B	15.50 (+1.5/-2.0)	8.50 (+1.5/-2.0)	15.24	8.35	Pass

8.5.2 Notes for Bluetooth

- The Bluetooth chipset in this device is produced by two different suppliers. The electrically identical modules are manufactured with the identical mechanical structure to meet the same specifications and functions. Two device variants are referenced as Variant 1 and Variant 2 in this report.
- Bluetooth SAR worst case configuration was evaluated for Variant 1 and Variant 2. The Variant with the highest reported SAR value was evaluated for the remaining Bluetooth configurations.
- Full power measurements were performed for Variant 1 and Variant 2 per FCC KDB Procedures 248227.




Figure 8-7
Power Measurement Setup

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 82 of 114

9 SYSTEM VERIFICATION

9.1 Tissue Verification

**Table 9-1
Measured Tissue Properties**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
6/16/2020	750B	21.9	680	0.950	53.632	0.958	55.904	-0.84%	-3.89%
			695	0.954	53.804	0.959	55.745	-0.52%	-3.84%
			700	0.956	53.594	0.959	55.726	-0.31%	-3.83%
			710	0.960	53.578	0.960	55.687	0.00%	-3.79%
			720	0.964	53.563	0.961	55.648	0.31%	-3.75%
			725	0.966	53.553	0.961	55.629	0.52%	-3.73%
			740	0.973	53.519	0.963	55.570	1.04%	-3.69%
			755	0.978	53.481	0.964	55.512	1.45%	-3.66%
			770	0.983	53.444	0.965	55.453	1.87%	-3.62%
			785	0.988	53.402	0.966	55.395	2.28%	-3.59%
			800	0.993	53.357	0.967	55.336	2.69%	-3.56%
			800	0.996	54.727	0.967	55.336	-1.14%	-1.10%
6/10/2020	835B	24.0	820	0.975	54.532	0.969	55.258	0.62%	-1.31%
			835	0.990	54.391	0.970	55.200	2.06%	-1.47%
			850	1.003	54.252	0.988	55.154	1.52%	-1.64%
			820	0.969	54.668	0.969	55.258	0.00%	-1.07%
6/15/2020	835B	22.7	835	0.984	54.529	0.970	55.200	1.44%	-1.22%
			850	0.998	54.396	0.988	55.154	1.01%	-1.37%
6/17/2020	835B	22.6	820	0.974	54.630	0.969	55.258	0.52%	-1.14%
			835	0.989	54.479	0.970	55.200	1.96%	-1.31%
7/4/2020	835B	22.1	850	1.004	54.331	0.988	55.154	1.62%	-1.49%
			820	0.969	53.552	0.969	55.258	0.00%	-3.89%
6/15/2020	1750B	22.1	835	0.984	53.393	0.970	55.200	1.44%	-3.27%
			850	0.998	53.279	0.988	55.154	1.01%	-3.40%
			1710	1.492	51.895	1.463	53.537	1.98%	-3.44%
			1750	1.532	51.596	1.488	53.432	2.96%	-3.44%
6/8/2020	1900B	21.4	1790	1.568	51.459	1.514	53.326	3.57%	-3.50%
			1850	1.466	51.862	1.520	53.300	-3.55%	-2.70%
			1880	1.499	51.761	1.520	53.300	-1.38%	-2.89%
			1910	1.532	51.672	1.520	53.300	0.79%	-3.05%
6/10/2020	1900B	22.4	1850	1.527	52.077	1.520	53.300	0.46%	-2.29%
			1880	1.560	51.962	1.520	53.300	2.63%	-2.51%
			1910	1.591	51.867	1.520	53.300	4.67%	-2.69%
			2300	1.893	52.922	1.809	52.900	4.64%	-0.59%
6/15/2020	2300B	21.7	2310	1.904	52.569	1.816	52.887	4.85%	-0.60%
			2320	1.915	52.543	1.826	52.873	4.87%	-0.63%
			2400	1.936	52.521	1.902	52.767	1.79%	-0.47%
			2450	2.003	52.345	1.950	52.700	2.72%	-0.67%
6/18/2020	2450B-2600B	22.1	2500	2.076	52.171	2.021	52.636	2.72%	-0.88%
			2550	2.146	51.972	2.092	52.573	2.58%	-1.14%
			2600	2.221	51.804	2.163	52.509	2.68%	-1.34%
			2650	2.294	51.583	2.234	52.445	2.69%	-1.64%
6/21/2020	2450B	22.8	2700	2.368	51.391	2.305	52.382	2.65%	-1.89%
			2400	1.927	51.445	1.902	52.767	1.31%	-2.51%
			2450	1.990	51.242	1.950	52.700	2.05%	-2.77%
			2500	2.063	51.059	2.021	52.636	2.08%	-3.00%
6/23/2020	2450B-2600B	22.6	2400	1.953	51.951	1.902	52.767	2.68%	-1.55%
			2450	2.025	51.793	1.950	52.700	3.85%	-1.72%
			2500	2.089	51.568	2.021	52.636	3.36%	-2.03%
			2550	2.164	51.391	2.092	52.573	3.44%	-2.25%
7/20/2020	2450B	22.6	2600	2.229	51.150	2.163	52.509	3.05%	-2.59%
			2650	2.300	50.979	2.234	52.445	2.95%	-2.80%
			2700	2.368	50.730	2.305	52.382	2.73%	-3.15%
			2400	1.935	51.473	1.902	52.767	1.74%	-2.45%
6/7/2020	5200B-5800B	21.5	2450	1.997	51.287	1.950	52.700	2.41%	-2.68%
			2500	2.066	51.101	2.021	52.636	2.23%	-2.92%
			5180	5.397	47.743	5.276	49.041	2.29%	-2.65%
			5200	5.426	47.727	5.299	49.014	2.40%	-2.63%
			5220	5.450	47.701	5.323	48.987	2.39%	-2.63%
			5240	5.475	47.653	5.346	48.960	2.41%	-2.67%
			5260	5.504	47.615	5.369	48.933	2.51%	-2.69%
			5280	5.537	47.573	5.393	48.906	2.67%	-2.73%
			5300	5.562	47.549	5.416	48.879	2.70%	-2.72%
			5320	5.585	47.522	5.439	48.851	2.68%	-2.72%
			5500	5.831	47.209	5.650	48.607	3.20%	-2.88%
			5520	5.856	47.174	5.673	48.580	3.23%	-2.89%
			5540	5.887	47.139	5.696	48.553	3.35%	-2.91%
			5560	5.915	47.099	5.720	48.526	3.41%	-2.95%
			5580	5.946	47.068	5.743	48.499	3.53%	-2.95%
			5600	5.971	47.050	5.766	48.471	3.56%	-2.93%
			5620	5.994	47.012	5.790	48.444	3.52%	-2.96%
			5640	6.028	46.961	5.813	48.417	3.70%	-3.01%
			5660	6.059	46.920	5.837	48.390	3.80%	-3.04%
			5680	6.085	46.914	5.860	48.363	3.84%	-3.00%
			5700	6.108	46.899	5.883	48.336	3.82%	-3.01%
			5745	6.174	46.775	5.936	48.275	4.01%	-3.11%
			5765	6.203	46.740	5.959	48.248	4.09%	-3.13%
			5785	6.227	46.726	5.982	48.220	4.10%	-3.10%
			5800	6.246	46.696	6.000	48.200	4.10%	-3.12%
			5805	6.254	46.687	6.006	48.193	4.13%	-3.12%
			5825	6.280	46.646	6.029	48.166	4.16%	-3.16%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: BCGA2429		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 83 of 114	

9.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix D.

Table 9-2
System Verification Results – 1g

SAR System #	Tissue Frequency (MHz)	Tissue Type	Date	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)	DAE
AM8	750	BODY	06/16/2020	21.0	21.9	0.200	1057	7532	1.790	8.640	8.950	3.59%	501
AM4	835	BODY	06/10/2020	21.9	22.1	0.200	4d040	7421	1.990	9.530	9.950	4.41%	604
AM4	835	BODY	06/15/2020	22.1	21.8	0.200	4d040	7421	2.040	9.530	10.200	7.03%	604
AM4	835	BODY	06/17/2020	21.3	22.6	0.200	4d180	7421	2.030	9.590	10.150	5.84%	604
AM4	835	BODY	07/04/2020	23.4	22.2	0.200	4d180	7421	2.040	9.590	10.200	6.36%	604
AM1	1750	BODY	06/15/2020	23.3	22.0	0.100	1104	7427	3.930	36.600	39.300	7.38%	1403
AM8	1900	BODY	06/08/2020	22.4	22.0	0.100	5d026	7532	4.030	39.900	40.300	1.00%	501
AM8	1900	BODY	06/10/2020	22.8	20.4	0.100	5d180	7532	4.080	39.500	40.800	3.29%	501
AM8	2300	BODY	06/15/2020	20.8	21.7	0.100	1038	7532	4.480	46.700	44.800	-4.07%	501
AM5	2450	BODY	06/18/2020	23.1	22.1	0.100	921	7491	5.330	50.800	53.300	4.92%	1402
AM3	2450	BODY	06/21/2020	21.2	21.8	0.100	921	3949	4.980	50.800	49.800	-1.97%	1408
AM3	2450	BODY	06/23/2020	23.5	22.4	0.100	921	3949	5.250	50.800	52.500	3.35%	1408
AM3	2450	BODY	07/20/2020	23.1	22.7	0.100	921	3949	5.290	50.800	52.900	4.13%	1408
AM5	2600	BODY	06/18/2020	23.1	22.1	0.100	1069	7491	5.380	55.300	53.800	-2.71%	1402
AM3	2600	BODY	06/23/2020	23.5	22.4	0.100	1069	3949	5.850	55.300	58.500	5.79%	1408
AM2	5250	BODY	06/07/2020	23.7	21.0	0.050	1163	7420	3.590	77.700	71.800	-7.59%	1213
AM2	5600	BODY	06/07/2020	23.7	21.0	0.050	1163	7420	4.160	80.100	83.200	3.87%	1213
AM2	5750	BODY	06/07/2020	23.7	21.0	0.050	1163	7420	3.590	77.800	71.800	-7.71%	1213




Figure 9-1
System Verification Setup Diagram



Figure 9-2
System Verification Setup Photo

FCC ID: BCGA2429		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 84 of 114

10 SAR DATA SUMMARY

10.1 Standalone Hotspot SAR Data

Table 10-1
GPRS 850 MHz Ant C Body SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	(W/kg)	(W/kg)	
824.20	128	GSM 850	GPRS	24.75	24.66	0.04	0 mm	Ant C	F9FCN020Q7LC	2	1:4.15	back	0.894	1.021	0.913	0.443	0.452	
836.60	190	GSM 850	GPRS	24.75	24.62	-0.05	0 mm	Ant C	F9FCN020Q7LC	2	1:4.15	back	0.840	1.030	0.865	0.418	0.431	
848.80	251	GSM 850	GPRS	24.75	24.58	-0.04	0 mm	Ant C	F9FCN020Q7LC	2	1:4.15	back	0.770	1.040	0.801	0.389	0.405	
836.60	190	GSM 850	GPRS	24.75	24.62	0.03	0 mm	Ant C	F9FCN020Q7LC	2	1:4.15	top	0.345	1.030	0.355	0.198	0.204	
836.60	190	GSM 850	GPRS	24.75	24.62	0.01	0 mm	Ant C	F9FCN020Q7LC	2	1:4.15	bottom	0.012	1.030	0.012	0.007	0.007	
836.60	190	GSM 850	GPRS	24.75	24.62	0.05	0 mm	Ant C	F9FCN020Q7LC	2	1:4.15	right	0.063	1.030	0.065	0.032	0.033	
836.60	190	GSM 850	GPRS	24.75	24.62	-0.21	0 mm	Ant C	F9FCN020Q7LC	2	1:4.15	left	0.009	1.030	0.009	0.005	0.005	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 10-2
GPRS 850 MHz Ant D Body SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	(W/kg)		
824.20	128	GSM 850	GPRS	25.50	25.32	-0.01	0 mm	Ant D	F9FCN020Q7LC	2	1:4.15	back	1.040	1.042	1.084	0.509	0.530	A1
836.60	190	GSM 850	GPRS	25.50	25.31	-0.01	0 mm	Ant D	F9FCN020Q7LC	2	1:4.15	back	0.965	1.045	1.008	0.479	0.501	
848.80	251	GSM 850	GPRS	25.50	25.34	-0.03	0 mm	Ant D	F9FCN020Q7LC	2	1:4.15	back	0.912	1.038	0.947	0.451	0.468	
836.60	190	GSM 850	GPRS	25.50	25.31	0.21	0 mm	Ant D	F9FCN020Q7LC	2	1:4.15	top	0.390	1.045	0.408	0.222	0.232	
836.60	190	GSM 850	GPRS	25.50	25.31	0.03	0 mm	Ant D	F9FCN020Q7LC	2	1:4.15	bottom	0.010	1.045	0.010	0.006	0.006	
836.60	190	GSM 850	GPRS	25.50	25.31	0.21	0 mm	Ant D	F9FCN020Q7LC	2	1:4.15	right	0.009	1.045	0.009	0.005	0.005	
836.60	190	GSM 850	GPRS	25.50	25.31	0.05	0 mm	Ant D	F9FCN020Q7LC	2	1:4.15	left	0.049	1.045	0.051	0.027	0.028	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 10-3
GPRS 1900 MHz Ant C Body SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	(W/kg)		
1850.20	512	GSM 1900	GSM	18.95	18.68	-0.03	0 mm	Ant C	F9FCN02HQ7L9	2	1:4.15	back	0.827	1.064	0.880	0.367	0.390	
1880.00	661	GSM 1900	GSM	18.95	18.65	0.03	0 mm	Ant C	F9FCN02HQ7L9	2	1:4.15	back	0.882	1.072	0.946	0.394	0.422	
1909.80	810	GSM 1900	GSM	18.95	18.51	0.04	0 mm	Ant C	F9FCN02HQ7L9	2	1:4.15	back	0.904	1.107	1.001	0.407	0.451	A2
1880.00	661	GSM 1900	GPRS	18.95	18.65	-0.03	0 mm	Ant C	F9FCN02HQ7L9	2	1:4.15	top	0.590	1.072	0.632	0.272	0.292	
1880.00	661	GSM 1900	GPRS	18.95	18.65	0.00	0 mm	Ant C	F9FCN02HQ7L9	2	1:4.15	bottom	0.000	1.072	0.000	0.000	0.000	
1880.00	661	GSM 1900	GPRS	18.95	18.65	-0.18	0 mm	Ant C	F9FCN02HQ7L9	2	1:4.15	right	0.066	1.072	0.071	0.030	0.032	
1880.00	661	GSM 1900	GPRS	18.95	18.65	0.10	0 mm	Ant C	F9FCN02HQ7L9	2	1:4.15	left	0.021	1.072	0.023	0.009	0.010	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 85 of 114

Table 10-4
GPRS 1900 MHz Ant D Body SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	(W/kg)		
1850.20	512	GSM 1900	GPRS	18.25	18.05	-0.01	0 mm	Ant D	F9FCN02SQ7L9	2	1:4.15	back	0.750	1.047	0.785	0.314	0.329	
1880.00	661	GSM 1900	GPRS	18.25	18.03	0.04	0 mm	Ant D	F9FCN02SQ7L9	2	1:4.15	back	0.794	1.052	0.835	0.333	0.350	
1909.80	810	GSM 1900	GPRS	18.25	17.80	0.00	0 mm	Ant D	F9FCN02SQ7L9	2	1:4.15	back	0.902	1.109	1.000	0.380	0.421	
1880.00	661	GSM 1900	GPRS	18.25	18.03	0.01	0 mm	Ant D	F9FCN02SQ7L9	2	1:4.15	top	0.552	1.052	0.581	0.249	0.262	
1880.00	661	GSM 1900	GPRS	18.25	18.03	0.00	0 mm	Ant D	F9FCN02SQ7L9	2	1:4.15	bottom	0.000	1.052	0.000	0.000	0.000	
1880.00	661	GSM 1900	GPRS	18.25	18.03	0.11	0 mm	Ant D	F9FCN02SQ7L9	2	1:4.15	right	0.009	1.052	0.009	0.003	0.003	
1880.00	661	GSM 1900	GPRS	18.25	18.03	0.20	0 mm	Ant D	F9FCN02SQ7L9	2	1:4.15	left	0.051	1.052	0.054	0.022	0.023	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 10-5
UMTS 850 MHz Ant C Body SAR

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	(W/kg)	(W/kg)	
826.40	4132	UMTS 850	RMC	17.70	17.33	-0.04	0 mm	Ant C	F9FCN00HQ7LC	1:1	back	0.958	1.089	1.043	0.469	0.511	
836.60	4183	UMTS 850	RMC	17.70	17.25	0.00	0 mm	Ant C	F9FCN00HQ7LC	1:1	back	0.867	1.109	0.962	0.433	0.480	
846.60	4233	UMTS 850	RMC	17.70	17.27	0.01	0 mm	Ant C	F9FCN00HQ7LC	1:1	back	0.857	1.104	0.946	0.428	0.473	
836.60	4183	UMTS 850	RMC	17.70	17.25	-0.03	0 mm	Ant C	F9FCN00HQ7LC	1:1	top	0.618	1.109	0.685	0.351	0.389	
836.60	4183	UMTS 850	RMC	17.70	17.25	-0.08	0 mm	Ant C	F9FCN00HQ7LC	1:1	bottom	0.018	1.109	0.020	0.010	0.011	
836.60	4183	UMTS 850	RMC	17.70	17.25	0.09	0 mm	Ant C	F9FCN00HQ7LC	1:1	right	0.095	1.109	0.105	0.047	0.052	
836.60	4183	UMTS 850	RMC	17.70	17.25	0.03	0 mm	Ant C	F9FCN00HQ7LC	1:1	left	0.013	1.109	0.014	0.007	0.008	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram									

Table 10-6
UMTS 850 MHz Ant D Body SAR

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	(W/kg)		
826.40	4132	UMTS 850	RMC	19.20	19.08	-0.01	0 mm	Ant D	F9FCN020Q7LC	1:1	back	1.050	1.028	1.079	0.508	0.522	A3
836.60	4183	UMTS 850	RMC	19.20	19.12	-0.01	0 mm	Ant D	F9FCN020Q7LC	1:1	back	0.936	1.019	0.954	0.474	0.483	
846.60	4233	UMTS 850	RMC	19.20	18.97	-0.02	0 mm	Ant D	F9FCN020Q7LC	1:1	back	0.890	1.054	0.938	0.452	0.476	
836.60	4183	UMTS 850	RMC	19.20	19.12	-0.03	0 mm	Ant D	F9FCN020Q7LC	1:1	top	0.776	1.019	0.791	0.424	0.432	
836.60	4183	UMTS 850	RMC	19.20	19.12	0.15	0 mm	Ant D	F9FCN020Q7LC	1:1	bottom	0.019	1.019	0.019	0.010	0.010	
836.60	4183	UMTS 850	RMC	19.20	19.12	0.04	0 mm	Ant D	F9FCN020Q7LC	1:1	right	0.016	1.019	0.016	0.007	0.007	
836.60	4183	UMTS 850	RMC	19.20	19.12	-0.06	0 mm	Ant D	F9FCN020Q7LC	1:1	left	0.150	1.019	0.153	0.078	0.079	
826.40	4132	UMTS 850	RMC	19.20	19.08	-0.03	0 mm	Ant D	F9FCN020Q7LC	1:1	back	0.973	1.028	1.000	0.481	0.494	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram									

Note: Blue entry represents variability measurement.

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 86 of 114

Table 10-7
UMTS 1750 MHz Ant C Body SAR

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	(W/kg)	(W/kg)	
1712.40	1312	UMTS 1750	RMC	13.30	13.11	-0.10	0 mm	Ant C	F9FCN02HQ7L9	1:1	back	0.878	1.045	0.918	0.408	0.426	
1732.40	1412	UMTS 1750	RMC	13.30	13.05	-0.04	0 mm	Ant C	F9FCN02HQ7L9	1:1	back	0.899	1.059	0.952	0.419	0.444	A4
1752.60	1513	UMTS 1750	RMC	13.30	12.78	-0.03	0 mm	Ant C	F9FCN02HQ7L9	1:1	back	0.872	1.127	0.983	0.409	0.461	
1732.40	1412	UMTS 1750	RMC	13.30	13.05	-0.01	0 mm	Ant C	F9FCN02HQ7L9	1:1	top	0.563	1.059	0.596	0.271	0.287	
1732.40	1412	UMTS 1750	RMC	13.30	13.05	0.05	0 mm	Ant C	F9FCN02HQ7L9	1:1	bottom	0.001	1.059	0.001	0.000	0.000	
1732.40	1412	UMTS 1750	RMC	13.30	13.05	0.07	0 mm	Ant C	F9FCN02HQ7L9	1:1	right	0.075	1.059	0.079	0.036	0.038	
1732.40	1412	UMTS 1750	RMC	13.30	13.05	0.03	0 mm	Ant C	F9FCN02HQ7L9	1:1	left	0.027	1.059	0.029	0.013	0.014	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram										

Table 10-8
UMTS 1750 MHz Ant D Body SAR

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	(W/kg)	(W/kg)	
1712.40	1312	UMTS 1750	RMC	13.20	12.76	-0.11	0 mm	Ant D	F9FCN00JQ7LC	1:1	back	0.726	1.107	0.804	0.316	0.350	
1732.40	1412	UMTS 1750	RMC	13.20	12.83	0.01	0 mm	Ant D	F9FCN00JQ7LC	1:1	back	0.784	1.089	0.854	0.340	0.370	
1752.60	1513	UMTS 1750	RMC	13.20	12.58	-0.03	0 mm	Ant D	F9FCN00JQ7LC	1:1	back	0.869	1.153	1.002	0.375	0.432	
1732.40	1412	UMTS 1750	RMC	13.20	12.83	-0.04	0 mm	Ant D	F9FCN00JQ7LC	1:1	top	0.530	1.089	0.577	0.245	0.267	
1732.40	1412	UMTS 1750	RMC	13.20	12.83	-0.03	0 mm	Ant D	F9FCN00JQ7LC	1:1	bottom	0.001	1.089	0.001	0.000	0.000	
1732.40	1412	UMTS 1750	RMC	13.20	12.83	0.06	0 mm	Ant D	F9FCN00JQ7LC	1:1	right	0.011	1.089	0.012	0.005	0.005	
1732.40	1412	UMTS 1750	RMC	13.20	12.83	0.14	0 mm	Ant D	F9FCN00JQ7LC	1:1	left	0.073	1.089	0.079	0.033	0.036	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram									

Table 10-9
UMTS 1900 MHz Ant C Body SAR

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	(W/kg)		
1852.40	9262	UMTS 1900	RMC	13.10	12.87	0.03	0 mm	Ant C	F9FCN02HQ7L9	1:1	back	0.942	1.054	0.993	0.428	0.451	
1880.00	9400	UMTS 1900	RMC	13.10	12.84	0.02	0 mm	Ant C	F9FCN02HQ7L9	1:1	back	0.972	1.062	1.032	0.442	0.469	
1907.60	9538	UMTS 1900	RMC	13.10	12.83	0.00	0 mm	Ant C	F9FCN02HQ7L9	1:1	back	0.982	1.064	1.045	0.444	0.472	A5
1880.00	9400	UMTS 1900	RMC	13.10	12.84	0.02	0 mm	Ant C	F9FCN02HQ7L9	1:1	top	0.672	1.062	0.714	0.310	0.329	
1880.00	9400	UMTS 1900	RMC	13.10	12.84	0.00	0 mm	Ant C	F9FCN02HQ7L9	1:1	bottom	0.000	1.062	0.000	0.000	0.000	
1880.00	9400	UMTS 1900	RMC	13.10	12.84	0.19	0 mm	Ant C	F9FCN02HQ7L9	1:1	right	0.083	1.062	0.088	0.038	0.040	
1880.00	9400	UMTS 1900	RMC	13.10	12.84	0.02	0 mm	Ant C	F9FCN02HQ7L9	1:1	left	0.032	1.062	0.034	0.014	0.015	
1907.60	9538	UMTS 1900	RMC	13.10	12.83	0.00	0 mm	Ant C	F9FCN02HQ7L9	1:1	back	0.973	1.064	1.035	0.441	0.469	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram									

Note: Blue entry represents variability measurement.

FCC ID: BCGA2429		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 87 of 114

Table 10-10
UMTS 1900 MHz Ant D Body SAR

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	(W/kg)		
1852.40	9262	UMTS 1900	RMC	12.00	11.75	0.02	0 mm	Ant D	F9FCN02QQ7L9	1:1	back	0.826	1.059	0.875	0.355	0.376	
1880.00	9400	UMTS 1900	RMC	12.00	11.73	0.02	0 mm	Ant D	F9FCN02QQ7L9	1:1	back	0.887	1.064	0.944	0.380	0.404	
1907.60	9538	UMTS 1900	RMC	12.00	11.76	0.03	0 mm	Ant D	F9FCN02QQ7L9	1:1	back	0.925	1.057	0.978	0.395	0.418	
1880.00	9400	UMTS 1900	RMC	12.00	11.73	-0.01	0 mm	Ant D	F9FCN02QQ7L9	1:1	top	0.659	1.064	0.701	0.295	0.314	
1880.00	9400	UMTS 1900	RMC	12.00	11.73	0.00	0 mm	Ant D	F9FCN02QQ7L9	1:1	bottom	0.000	1.064	0.000	0.000	0.000	
1880.00	9400	UMTS 1900	RMC	12.00	11.73	0.09	0 mm	Ant D	F9FCN02QQ7L9	1:1	right	0.010	1.064	0.011	0.004	0.004	
1880.00	9400	UMTS 1900	RMC	12.00	11.73	0.10	0 mm	Ant D	F9FCN02QQ7L9	1:1	left	0.061	1.064	0.065	0.027	0.029	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram									

Table 10-11
LTE Band 12 Ant C Body SAR

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
707.50	23095	Mid	LTE Band 12	10	17.50	17.34	0.03	0	Ant C	F9FCN00HQ7LC	QPSK	1	25	0 mm	back	1:1	0.859	1.038	0.892	0.415	0.431	A6
707.50	23095	Mid	LTE Band 12	10	17.50	17.37	0.00	0	Ant C	F9FCN00HQ7LC	QPSK	25	0	0 mm	back	1:1	0.899	1.030	0.926	0.429	0.442	
707.50	23095	Mid	LTE Band 12	10	17.50	17.32	0.02	0	Ant C	F9FCN00HQ7LC	QPSK	50	0	0 mm	back	1:1	0.861	1.042	0.897	0.417	0.435	
707.50	23095	Mid	LTE Band 12	10	17.50	17.34	-0.03	0	Ant C	F9FCN00HQ7LC	QPSK	1	25	0 mm	top	1:1	0.467	1.038	0.485	0.249	0.258	
707.50	23095	Mid	LTE Band 12	10	17.50	17.37	-0.07	0	Ant C	F9FCN00HQ7LC	QPSK	25	0	0 mm	top	1:1	0.481	1.030	0.495	0.254	0.262	
707.50	23095	Mid	LTE Band 12	10	17.50	17.34	0.02	0	Ant C	F9FCN00HQ7LC	QPSK	1	25	0 mm	bottom	1:1	0.013	1.038	0.013	0.007	0.007	
707.50	23095	Mid	LTE Band 12	10	17.50	17.37	-0.06	0	Ant C	F9FCN00HQ7LC	QPSK	25	0	0 mm	bottom	1:1	0.016	1.030	0.016	0.009	0.009	
707.50	23095	Mid	LTE Band 12	10	17.50	17.34	0.01	0	Ant C	F9FCN00HQ7LC	QPSK	1	25	0 mm	right	1:1	0.083	1.038	0.086	0.039	0.040	
707.50	23095	Mid	LTE Band 12	10	17.50	17.37	0.17	0	Ant C	F9FCN00HQ7LC	QPSK	25	0	0 mm	right	1:1	0.075	1.030	0.077	0.035	0.036	
707.50	23095	Mid	LTE Band 12	10	17.50	17.34	0.05	0	Ant C	F9FCN00HQ7LC	QPSK	1	25	0 mm	left	1:1	0.027	1.038	0.028	0.011	0.011	
707.50	23095	Mid	LTE Band 12	10	17.50	17.37	0.21	0	Ant C	F9FCN00HQ7LC	QPSK	25	0	0 mm	left	1:1	0.026	1.030	0.027	0.011	0.011	
707.50	23095	Mid	LTE Band 12	10	17.50	17.37	-0.03	0	Ant C	F9FCN00HQ7LC	QPSK	25	0	0 mm	back	1:1	0.864	1.030	0.890	0.425	0.438	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram														

Note: Blue entry represents variability measurement.

Table 10-12
LTE Band 12 Ant D Body SAR

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
707.50	23095	Mid	LTE Band 12	10	17.20	17.05	-0.06	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	back	1:1	0.792	1.035	0.820	0.381	0.394	
707.50	23095	Mid	LTE Band 12	10	17.20	17.04	-0.05	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	back	1:1	0.817	1.038	0.848	0.390	0.405	
707.50	23095	Mid	LTE Band 12	10	17.20	17.03	-0.05	0	Ant D	F9FCN02QQ7L9	QPSK	50	0	0 mm	back	1:1	0.785	1.040	0.816	0.376	0.391	
707.50	23095	Mid	LTE Band 12	10	17.20	17.05	0.10	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	top	1:1	0.422	1.035	0.437	0.225	0.233	
707.50	23095	Mid	LTE Band 12	10	17.20	17.04	0.14	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	top	1:1	0.422	1.038	0.438	0.224	0.233	
707.50	23095	Mid	LTE Band 12	10	17.20	17.05	0.06	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	bottom	1:1	0.013	1.035	0.013	0.007	0.007	
707.50	23095	Mid	LTE Band 12	10	17.20	17.04	0.06	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	bottom	1:1	0.013	1.038	0.013	0.008	0.008	
707.50	23095	Mid	LTE Band 12	10	17.20	17.05	-0.03	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	right	1:1	0.009	1.035	0.009	0.004	0.004	
707.50	23095	Mid	LTE Band 12	10	17.20	17.04	0.14	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	right	1:1	0.012	1.038	0.012	0.007	0.007	
707.50	23095	Mid	LTE Band 12	10	17.20	17.05	0.09	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	left	1:1	0.060	1.035	0.062	0.029	0.030	
707.50	23095	Mid	LTE Band 12	10	17.20	17.04	0.03	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	left	1:1	0.068	1.038	0.071	0.032	0.033	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram														

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 88 of 114

Table 10-13
LTE Band 13 Ant C Body SAR

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
782.00	23230	Mid	LTE Band 13	10	18.10	18.10	-0.01	0	Ant C	F9FCN02SQ7L9	QPSK	1	0	0 mm	back	1:1	0.835	1.000	0.835	0.411	0.411	
782.00	23230	Mid	LTE Band 13	10	18.10	17.79	-0.01	0	Ant C	F9FCN02SQ7L9	QPSK	25	0	0 mm	back	1:1	0.758	1.074	0.814	0.375	0.403	
782.00	23230	Mid	LTE Band 13	10	18.10	17.68	0.01	0	Ant C	F9FCN02SQ7L9	QPSK	50	0	0 mm	back	1:1	0.727	1.102	0.801	0.359	0.396	
782.00	23230	Mid	LTE Band 13	10	18.10	18.10	-0.05	0	Ant C	F9FCN02SQ7L9	QPSK	1	0	0 mm	top	1:1	0.410	1.000	0.410	0.210	0.210	
782.00	23230	Mid	LTE Band 13	10	18.10	17.79	-0.05	0	Ant C	F9FCN02SQ7L9	QPSK	25	0	0 mm	top	1:1	0.401	1.074	0.431	0.204	0.219	
782.00	23230	Mid	LTE Band 13	10	18.10	18.10	0.04	0	Ant C	F9FCN02SQ7L9	QPSK	1	0	0 mm	bottom	1:1	0.022	1.000	0.022	0.012	0.012	
782.00	23230	Mid	LTE Band 13	10	18.10	17.79	0.07	0	Ant C	F9FCN02SQ7L9	QPSK	25	0	0 mm	bottom	1:1	0.022	1.074	0.024	0.012	0.013	
782.00	23230	Mid	LTE Band 13	10	18.10	18.10	-0.09	0	Ant C	F9FCN02SQ7L9	QPSK	1	0	0 mm	right	1:1	0.126	1.000	0.126	0.063	0.063	
782.00	23230	Mid	LTE Band 13	10	18.10	17.79	-0.06	0	Ant C	F9FCN02SQ7L9	QPSK	25	0	0 mm	right	1:1	0.110	1.074	0.118	0.055	0.059	
782.00	23230	Mid	LTE Band 13	10	18.10	18.10	0.03	0	Ant C	F9FCN02SQ7L9	QPSK	1	0	0 mm	left	1:1	0.014	1.000	0.014	0.008	0.008	
782.00	23230	Mid	LTE Band 13	10	18.10	17.79	0.18	0	Ant C	F9FCN02SQ7L9	QPSK	25	0	0 mm	left	1:1	0.012	1.074	0.013	0.006	0.006	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram														

Table 10-14
LTE Band 13 Ant D Body SAR

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
782.00	23230	Mid	LTE Band 13	10	18.30	18.30	0.05	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	back	1:1	0.873	1.000	0.873	0.425	0.425	A7
782.00	23230	Mid	LTE Band 13	10	18.30	18.00	-0.03	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	back	1:1	0.791	1.072	0.848	0.388	0.416	
782.00	23230	Mid	LTE Band 13	10	18.30	17.91	-0.05	0	Ant D	F9FCN02QQ7L9	QPSK	50	0	0 mm	back	1:1	0.779	1.094	0.852	0.382	0.418	
782.00	23230	Mid	LTE Band 13	10	18.30	18.30	0.01	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	top	1:1	0.726	1.000	0.726	0.394	0.394	
782.00	23230	Mid	LTE Band 13	10	18.30	18.00	0.02	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	top	1:1	0.666	1.072	0.714	0.360	0.386	
782.00	23230	Mid	LTE Band 13	10	18.30	18.30	0.05	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	bottom	1:1	0.016	1.000	0.016	0.009	0.009	
782.00	23230	Mid	LTE Band 13	10	18.30	18.00	0.07	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	bottom	1:1	0.016	1.072	0.017	0.008	0.009	
782.00	23230	Mid	LTE Band 13	10	18.30	18.30	0.04	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	right	1:1	0.023	1.000	0.023	0.011	0.011	
782.00	23230	Mid	LTE Band 13	10	18.30	18.00	0.05	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	right	1:1	0.023	1.072	0.025	0.011	0.012	
782.00	23230	Mid	LTE Band 13	10	18.30	18.30	0.06	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	left	1:1	0.137	1.000	0.137	0.066	0.066	
782.00	23230	Mid	LTE Band 13	10	18.30	18.00	0.11	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	left	1:1	0.129	1.072	0.138	0.062	0.066	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram														

Table 10-15
LTE Band 14 Ant C Body SAR

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
793.00	23330	Mid	LTE Band 14	10	18.10	17.90	0.00	0	Ant C	F9FCN02HQ7L9	QPSK	1	0	0 mm	back	1:1	0.732	1.047	0.766	0.364	0.381	
793.00	23330	Mid	LTE Band 14	10	18.10	17.98	0.02	0	Ant C	F9FCN02HQ7L9	QPSK	25	0	0 mm	back	1:1	0.758	1.028	0.779	0.374	0.384	
793.00	23330	Mid	LTE Band 14	10	18.10	17.89	-0.01	0	Ant C	F9FCN02HQ7L9	QPSK	50	0	0 mm	back	1:1	0.760	1.050	0.798	0.375	0.394	A8
793.00	23330	Mid	LTE Band 14	10	18.10	17.90	0.07	0	Ant C	F9FCN02HQ7L9	QPSK	1	0	0 mm	top	1:1	0.516	1.047	0.540	0.271	0.284	
793.00	23330	Mid	LTE Band 14	10	18.10	17.98	0.10	0	Ant C	F9FCN02HQ7L9	QPSK	25	0	0 mm	top	1:1	0.522	1.028	0.537	0.274	0.282	
793.00	23330	Mid	LTE Band 14	10	18.10	17.90	0.03	0	Ant C	F9FCN02HQ7L9	QPSK	1	0	0 mm	bottom	1:1	0.026	1.047	0.027	0.013	0.014	
793.00	23330	Mid	LTE Band 14	10	18.10	17.98	0.08	0	Ant C	F9FCN02HQ7L9	QPSK	25	0	0 mm	bottom	1:1	0.025	1.028	0.026	0.012	0.012	
793.00	23330	Mid	LTE Band 14	10	18.10	17.90	-0.18	0	Ant C	F9FCN02HQ7L9	QPSK	1	0	0 mm	right	1:1	0.119	1.047	0.125	0.057	0.060	
793.00	23330	Mid	LTE Band 14	10	18.10	17.98	-0.06	0	Ant C	F9FCN02HQ7L9	QPSK	25	0	0 mm	right	1:1	0.110	1.028	0.113	0.054	0.056	
793.00	23330	Mid	LTE Band 14	10	18.10	17.90	0.04	0	Ant C	F9FCN02HQ7L9	QPSK	1	0	0 mm	left	1:1	0.020	1.047	0.021	0.009	0.009	
793.00	23330	Mid	LTE Band 14	10	18.10	17.98	0.04	0	Ant C	F9FCN02HQ7L9	QPSK	25	0	0 mm	left	1:1	0.019	1.028	0.020	0.009	0.009	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram														

FCC ID: BCGA2429	 PCTEST Proud to be part of the	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 89 of 114

Table 10-16
LTE Band 14 Ant D Body SAR

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
793.00	23330	Mid	LTE Band 14	10	18.30	17.94	-0.04	0	Ant D	F9FCN02QQ7L9	QPSK	1	49	0 mm	back	1:1	0.670	1.086	0.728	0.331	0.359	
793.00	23330	Mid	LTE Band 14	10	18.30	18.02	-0.06	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	back	1:1	0.729	1.067	0.778	0.357	0.381	
793.00	23330	Mid	LTE Band 14	10	18.30	17.93	-0.08	0	Ant D	F9FCN02QQ7L9	QPSK	50	0	0 mm	back	1:1	0.694	1.089	0.756	0.342	0.372	
793.00	23330	Mid	LTE Band 14	10	18.30	17.94	0.00	0	Ant D	F9FCN02QQ7L9	QPSK	1	49	0 mm	top	1:1	0.584	1.086	0.634	0.317	0.344	
793.00	23330	Mid	LTE Band 14	10	18.30	18.02	-0.03	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	top	1:1	0.641	1.067	0.684	0.349	0.372	
793.00	23330	Mid	LTE Band 14	10	18.30	17.94	0.03	0	Ant D	F9FCN02QQ7L9	QPSK	1	49	0 mm	bottom	1:1	0.019	1.086	0.021	0.010	0.011	
793.00	23330	Mid	LTE Band 14	10	18.30	18.02	0.01	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	bottom	1:1	0.026	1.067	0.028	0.013	0.014	
793.00	23330	Mid	LTE Band 14	10	18.30	17.94	0.01	0	Ant D	F9FCN02QQ7L9	QPSK	1	49	0 mm	right	1:1	0.029	1.086	0.031	0.015	0.016	
793.00	23330	Mid	LTE Band 14	10	18.30	18.02	0.06	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	right	1:1	0.028	1.067	0.030	0.014	0.015	
793.00	23330	Mid	LTE Band 14	10	18.30	17.94	0.21	0	Ant D	F9FCN02QQ7L9	QPSK	1	49	0 mm	left	1:1	0.126	1.086	0.137	0.061	0.066	
793.00	23330	Mid	LTE Band 14	10	18.30	18.02	0.10	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	left	1:1	0.146	1.067	0.156	0.070	0.075	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

Table 10-17
LTE Band 26 (Cell) Ant C Body SAR

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	17.83	-0.19	0	Ant C	F9FCN02TQ7L9	QPSK	1	0	0 mm	back	1:1	1.010	1.089	1.100	0.514	0.560	A9
831.50	26865	Mid	LTE Band 26 (Cell)	10	18.20	17.58	0.00	0	Ant C	F9FCN02TQ7L9	QPSK	1	0	0 mm	back	1:1	0.918	1.153	1.058	0.464	0.535	
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	17.64	-0.19	0	Ant C	F9FCN02TQ7L9	QPSK	1	0	0 mm	back	1:1	0.897	1.138	1.021	0.455	0.518	
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	17.74	-0.02	0	Ant C	F9FCN02TQ7L9	QPSK	25	25	0 mm	back	1:1	0.953	1.112	1.060	0.481	0.535	
831.50	26865	Mid	LTE Band 26 (Cell)	10	18.20	17.63	-0.17	0	Ant C	F9FCN02TQ7L9	QPSK	25	0	0 mm	back	1:1	0.957	1.140	1.091	0.485	0.553	
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	17.69	-0.19	0	Ant C	F9FCN02TQ7L9	QPSK	25	0	0 mm	back	1:1	0.904	1.125	1.017	0.458	0.515	
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	17.72	-0.02	0	Ant C	F9FCN02TQ7L9	QPSK	50	0	0 mm	back	1:1	0.961	1.117	1.073	0.488	0.545	
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	17.83	-0.07	0	Ant C	F9FCN02TQ7L9	QPSK	1	0	0 mm	top	1:1	0.570	1.089	0.621	0.322	0.351	
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	17.74	-0.04	0	Ant C	F9FCN02TQ7L9	QPSK	25	25	0 mm	top	1:1	0.582	1.112	0.647	0.330	0.367	
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	17.83	0.04	0	Ant C	F9FCN02TQ7L9	QPSK	1	0	0 mm	bottom	1:1	0.019	1.089	0.021	0.010	0.011	
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	17.74	-0.05	0	Ant C	F9FCN02TQ7L9	QPSK	25	25	0 mm	bottom	1:1	0.017	1.112	0.019	0.009	0.010	
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	17.83	-0.05	0	Ant C	F9FCN02TQ7L9	QPSK	1	0	0 mm	right	1:1	0.086	1.089	0.094	0.046	0.050	
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	17.74	0.01	0	Ant C	F9FCN02TQ7L9	QPSK	25	25	0 mm	right	1:1	0.081	1.112	0.090	0.044	0.049	
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	17.83	0.06	0	Ant C	F9FCN02TQ7L9	QPSK	1	0	0 mm	left	1:1	0.004	1.089	0.004	0.001	0.001	
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	17.74	0.04	0	Ant C	F9FCN02TQ7L9	QPSK	25	25	0 mm	left	1:1	0.004	1.112	0.004	0.001	0.001	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																						
Spatial Peak								Body														
Uncontrolled Exposure/General Population								1.6 W/kg (mW/g) averaged over 1 gram														

FCC ID: BCGA2429	 PCTEST Proud to be part of  element	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 90 of 114

Table 10-18
LTE Band 26 (Cell) Ant D Body SAR

FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)		
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	18.08	-0.01	0	Ant D	F9FCN02TQ7L9	QPSK	1	25	0 mm	back	1:1	0.922	1.028	0.948	0.462	0.475
831.50	26865	Mid	LTE Band 26 (Cell)	10	18.20	18.11	-0.01	0	Ant D	F9FCN02TQ7L9	QPSK	1	49	0 mm	back	1:1	0.810	1.021	0.827	0.407	0.416
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	18.14	-0.01	0	Ant D	F9FCN02TQ7L9	QPSK	1	0	0 mm	back	1:1	0.769	1.014	0.780	0.385	0.390
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	18.18	0.00	0	Ant D	F9FCN02TQ7L9	QPSK	25	25	0 mm	back	1:1	0.863	1.005	0.867	0.432	0.434
831.50	26865	Mid	LTE Band 26 (Cell)	10	18.20	18.08	0.00	0	Ant D	F9FCN02TQ7L9	QPSK	25	25	0 mm	back	1:1	0.814	1.028	0.837	0.406	0.417
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	18.10	-0.02	0	Ant D	F9FCN02TQ7L9	QPSK	25	0	0 mm	back	1:1	0.769	1.023	0.787	0.385	0.394
831.50	26865	Mid	LTE Band 26 (Cell)	10	18.20	18.06	0.00	0	Ant D	F9FCN02TQ7L9	QPSK	50	0	0 mm	back	1:1	0.905	1.033	0.935	0.450	0.465
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	18.14	0.02	0	Ant D	F9FCN02TQ7L9	QPSK	1	0	0 mm	top	1:1	0.705	1.014	0.715	0.385	0.390
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	18.18	-0.01	0	Ant D	F9FCN02TQ7L9	QPSK	25	25	0 mm	top	1:1	0.763	1.005	0.767	0.427	0.429
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	18.14	-0.10	0	Ant D	F9FCN02TQ7L9	QPSK	1	0	0 mm	bottom	1:1	0.016	1.014	0.016	0.008	0.008
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	18.18	0.13	0	Ant D	F9FCN02TQ7L9	QPSK	25	25	0 mm	bottom	1:1	0.021	1.005	0.021	0.011	0.011
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	18.14	0.20	0	Ant D	F9FCN02TQ7L9	QPSK	1	0	0 mm	right	1:1	0.011	1.014	0.011	0.005	0.005
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	18.18	0.10	0	Ant D	F9FCN02TQ7L9	QPSK	25	25	0 mm	right	1:1	0.012	1.005	0.012	0.006	0.006
844.00	26990	High	LTE Band 26 (Cell)	10	18.20	18.14	-0.01	0	Ant D	F9FCN02TQ7L9	QPSK	1	0	0 mm	left	1:1	0.129	1.014	0.131	0.064	0.065
819.00	26740	Low	LTE Band 26 (Cell)	10	18.20	18.18	0.04	0	Ant D	F9FCN02TQ7L9	QPSK	25	25	0 mm	left	1:1	0.101	1.005	0.102	0.050	0.050
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body													
Spatial Peak								1.6 W/kg (mW/g)													
Uncontrolled Exposure/General Population								averaged over 1 gram													

Table 10-19
LTE Band 5 (Cell) Ant C Body SAR

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.46	-0.11	0	Ant C	F9FCN00HQ7LC	QPSK	1	49	0 mm	back	1:1	0.946	1.057	1.000	0.466	0.493	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.47	0.02	0	Ant C	F9FCN00HQ7LC	QPSK	25	25	0 mm	back	1:1	0.917	1.054	0.967	0.460	0.485	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.44	0.02	0	Ant C	F9FCN00HQ7LC	QPSK	50	0	0 mm	back	1:1	0.919	1.062	0.976	0.460	0.489	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.46	-0.12	0	Ant C	F9FCN00HQ7LC	QPSK	1	49	0 mm	top	1:1	0.628	1.057	0.664	0.365	0.386	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.47	-0.02	0	Ant C	F9FCN00HQ7LC	QPSK	25	25	0 mm	top	1:1	0.630	1.054	0.664	0.363	0.383	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.46	-0.05	0	Ant C	F9FCN00HQ7LC	QPSK	1	49	0 mm	bottom	1:1	0.024	1.057	0.025	0.013	0.014	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.47	0.03	0	Ant C	F9FCN00HQ7LC	QPSK	25	25	0 mm	bottom	1:1	0.023	1.054	0.024	0.013	0.014	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.46	0.00	0	Ant C	F9FCN00HQ7LC	QPSK	1	49	0 mm	right	1:1	0.105	1.057	0.111	0.055	0.058	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.47	-0.03	0	Ant C	F9FCN00HQ7LC	QPSK	25	25	0 mm	right	1:1	0.106	1.054	0.112	0.055	0.058	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.46	0.12	0	Ant C	F9FCN00HQ7LC	QPSK	1	49	0 mm	left	1:1	0.019	1.057	0.020	0.011	0.012	
836.50	20525	Mid	LTE Band 5 (Cell)	10	17.70	17.47	0.00	0	Ant C	F9FCN00HQ7LC	QPSK	25	25	0 mm	left	1:1	0.015	1.054	0.016	0.009	0.009	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 91 of 114

Table 10-20
LTE Band 5 (Cell) Ant D Body SAR

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.10	0.00	0	Ant D	F9FCN02QQ7L9	QPSK	1	49	0 mm	back	1:1	0.914	1.023	0.935	0.460	0.471	A10
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.19	0.00	0	Ant D	F9FCN02QQ7L9	QPSK	25	25	0 mm	back	1:1	0.927	1.002	0.929	0.466	0.467	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.09	-0.02	0	Ant D	F9FCN02QQ7L9	QPSK	50	0	0 mm	back	1:1	0.951	1.026	0.976	0.478	0.490	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.10	0.01	0	Ant D	F9FCN02QQ7L9	QPSK	1	49	0 mm	top	1:1	0.927	1.023	0.948	0.508	0.520	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.19	-0.03	0	Ant D	F9FCN02QQ7L9	QPSK	25	25	0 mm	top	1:1	0.942	1.002	0.944	0.516	0.517	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.09	-0.01	0	Ant D	F9FCN02QQ7L9	QPSK	50	0	10 mm	top	1:1	0.939	1.026	0.963	0.520	0.534	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.10	0.16	0	Ant D	F9FCN02QQ7L9	QPSK	1	49	0 mm	bottom	1:1	0.018	1.023	0.018	0.010	0.010	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.19	-0.02	0	Ant D	F9FCN02QQ7L9	QPSK	25	25	0 mm	bottom	1:1	0.017	1.002	0.017	0.009	0.009	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.10	0.04	0	Ant D	F9FCN02QQ7L9	QPSK	1	49	0 mm	right	1:1	0.015	1.023	0.015	0.007	0.007	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.19	0.04	0	Ant D	F9FCN02QQ7L9	QPSK	25	25	0 mm	right	1:1	0.013	1.002	0.013	0.005	0.005	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.10	0.01	0	Ant D	F9FCN02QQ7L9	QPSK	1	49	0 mm	left	1:1	0.183	1.023	0.187	0.093	0.095	
836.50	20525	Mid	LTE Band 5 (Cell)	10	19.20	19.19	0.04	0	Ant D	F9FCN02QQ7L9	QPSK	25	25	0 mm	left	1:1	0.189	1.002	0.189	0.095	0.095	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram														

Table 10-21
LTE Band 66 (AWS) Ant C Body SAR

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.28	-0.03	0	Ant C	F9FCN02HQ7L9	QPSK	1	0	0 mm	back	1:1	0.891	1.005	0.895	0.421	0.423	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	13.30	13.21	-0.02	0	Ant C	F9FCN02HQ7L9	QPSK	1	50	0 mm	back	1:1	0.869	1.021	0.887	0.412	0.421	
1770.00	132572	High	LTE Band 66 (AWS)	20	13.30	12.96	-0.01	0	Ant C	F9FCN02HQ7L9	QPSK	1	50	0 mm	back	1:1	0.875	1.107	0.946	0.416	0.461	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.19	-0.03	0	Ant C	F9FCN02HQ7L9	QPSK	50	0	0 mm	back	1:1	0.874	1.026	0.897	0.411	0.422	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	13.30	13.09	-0.02	0	Ant C	F9FCN02HQ7L9	QPSK	50	0	0 mm	back	1:1	0.876	1.050	0.920	0.417	0.438	
1770.00	132572	High	LTE Band 66 (AWS)	20	13.30	12.91	0.00	0	Ant C	F9FCN02HQ7L9	QPSK	50	25	0 mm	back	1:1	0.870	1.094	0.952	0.412	0.451	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.18	-0.01	0	Ant C	F9FCN02HQ7L9	QPSK	100	0	0 mm	back	1:1	0.895	1.028	0.920	0.422	0.434	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.28	-0.01	0	Ant C	F9FCN02HQ7L9	QPSK	1	0	0 mm	top	1:1	0.506	1.005	0.509	0.243	0.244	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.19	0.00	0	Ant C	F9FCN02HQ7L9	QPSK	50	0	0 mm	top	1:1	0.490	1.026	0.503	0.236	0.242	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.28	0.03	0	Ant C	F9FCN02HQ7L9	QPSK	1	0	0 mm	bottom	1:1	0.000	1.005	0.000	0.000	0.000	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.19	0.09	0	Ant C	F9FCN02HQ7L9	QPSK	50	0	0 mm	bottom	1:1	0.001	1.026	0.001	0.000	0.000	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.28	0.08	0	Ant C	F9FCN02HQ7L9	QPSK	1	0	0 mm	right	1:1	0.061	1.005	0.061	0.029	0.029	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.19	0.15	0	Ant C	F9FCN02HQ7L9	QPSK	50	0	0 mm	right	1:1	0.059	1.026	0.061	0.027	0.028	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.28	0.03	0	Ant C	F9FCN02HQ7L9	QPSK	1	0	0 mm	left	1:1	0.025	1.005	0.025	0.012	0.012	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.30	13.19	0.14	0	Ant C	F9FCN02HQ7L9	QPSK	50	0	0 mm	left	1:1	0.024	1.026	0.025	0.011	0.011	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak								Body 1.6 W/kg (mW/g) averaged over 1 gram														
Uncontrolled Exposure/General Population																						

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 92 of 114

Table 10-22
LTE Band 66 (AWS) Ant D Body SAR

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.12	0.05	0	Ant D	F9FCN00JQ7LC	QPSK	1	0	0 mm	back	1:1	0.825	1.019	0.841	0.363	0.370	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	13.20	13.11	0.06	0	Ant D	F9FCN00JQ7LC	QPSK	1	0	0 mm	back	1:1	0.851	1.021	0.869	0.373	0.381	
1770.00	132572	High	LTE Band 66 (AWS)	20	13.20	12.99	-0.08	0	Ant D	F9FCN00JQ7LC	QPSK	1	0	0 mm	back	1:1	0.884	1.050	0.928	0.381	0.400	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.13	0.04	0	Ant D	F9FCN00JQ7LC	QPSK	50	25	0 mm	back	1:1	0.809	1.016	0.822	0.355	0.361	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	13.20	13.07	0.05	0	Ant D	F9FCN00JQ7LC	QPSK	50	0	0 mm	back	1:1	0.857	1.030	0.883	0.375	0.386	
1770.00	132572	High	LTE Band 66 (AWS)	20	13.20	12.97	0.05	0	Ant D	F9FCN00JQ7LC	QPSK	50	0	0 mm	back	1:1	0.905	1.054	0.954	0.388	0.409	A11
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.06	0.03	0	Ant D	F9FCN00JQ7LC	QPSK	100	0	0 mm	back	1:1	0.824	1.033	0.851	0.362	0.374	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.12	-0.04	0	Ant D	F9FCN00JQ7LC	QPSK	1	0	0 mm	top	1:1	0.473	1.019	0.482	0.221	0.225	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.13	-0.01	0	Ant D	F9FCN00JQ7LC	QPSK	50	25	0 mm	top	1:1	0.468	1.016	0.475	0.219	0.223	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.12	0.05	0	Ant D	F9FCN00JQ7LC	QPSK	1	0	0 mm	bottom	1:1	0.000	1.019	0.000	0.000	0.000	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.13	0.18	0	Ant D	F9FCN00JQ7LC	QPSK	50	25	0 mm	bottom	1:1	0.001	1.016	0.001	0.000	0.000	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.12	0.06	0	Ant D	F9FCN00JQ7LC	QPSK	1	0	0 mm	right	1:1	0.007	1.019	0.007	0.003	0.003	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.13	0.10	0	Ant D	F9FCN00JQ7LC	QPSK	50	25	0 mm	right	1:1	0.008	1.016	0.008	0.004	0.004	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.12	-0.05	0	Ant D	F9FCN00JQ7LC	QPSK	1	0	0 mm	left	1:1	0.063	1.019	0.064	0.029	0.030	
1720.00	132072	Low	LTE Band 66 (AWS)	20	13.20	13.13	0.06	0	Ant D	F9FCN00JQ7LC	QPSK	50	25	0 mm	left	1:1	0.063	1.016	0.064	0.029	0.029	
1770.00	132572	High	LTE Band 66 (AWS)	20	13.20	12.97	0.05	0	Ant D	F9FCN00JQ7LC	QPSK	50	0	0 mm	back	1:1	0.884	1.054	0.932	0.386	0.407	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

Note: Blue entry represents variability measurement.

Table 10-23
LTE Band 25 (PCS) Ant C Body SAR

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
1860.00	26140	Low	LTE Band 25 (PCS)	20	13.10	13.01	0.02	0	Ant C	F9FCN02HQ7L9	QPSK	1	0	0 mm	back	1:1	0.942	1.021	0.962	0.421	0.430	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	13.10	12.93	0.02	0	Ant C	F9FCN02HQ7L9	QPSK	1	99	0 mm	back	1:1	0.949	1.040	0.987	0.424	0.441	
1905.00	26590	High	LTE Band 25 (PCS)	20	13.10	13.00	0.01	0	Ant C	F9FCN02HQ7L9	QPSK	1	50	0 mm	back	1:1	0.944	1.023	0.966	0.422	0.432	
1860.00	26140	Low	LTE Band 25 (PCS)	20	13.10	13.04	0.01	0	Ant C	F9FCN02HQ7L9	QPSK	50	0	0 mm	back	1:1	0.941	1.014	0.954	0.419	0.425	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	13.10	12.87	0.02	0	Ant C	F9FCN02HQ7L9	QPSK	50	50	0 mm	back	1:1	0.924	1.054	0.974	0.412	0.434	
1905.00	26590	High	LTE Band 25 (PCS)	20	13.10	12.93	0.04	0	Ant C	F9FCN02HQ7L9	QPSK	50	0	0 mm	back	1:1	0.971	1.040	1.010	0.436	0.453	A12
1905.00	26590	High	LTE Band 25 (PCS)	20	13.10	12.97	0.02	0	Ant C	F9FCN02HQ7L9	QPSK	100	0	0 mm	back	1:1	0.958	1.030	0.987	0.427	0.440	
1860.00	26140	Low	LTE Band 25 (PCS)	20	13.10	13.01	0.00	0	Ant C	F9FCN02HQ7L9	QPSK	1	0	0 mm	top	1:1	0.611	1.021	0.624	0.284	0.290	
1860.00	26140	Low	LTE Band 25 (PCS)	20	13.10	13.04	0.02	0	Ant C	F9FCN02HQ7L9	QPSK	50	0	0 mm	top	1:1	0.600	1.014	0.608	0.278	0.282	
1860.00	26140	Low	LTE Band 25 (PCS)	20	13.10	13.01	0.00	0	Ant C	F9FCN02HQ7L9	QPSK	1	0	0 mm	bottom	1:1	0.000	1.021	0.000	0.000	0.000	
1860.00	26140	Low	LTE Band 25 (PCS)	20	13.10	13.04	0.00	0	Ant C	F9FCN02HQ7L9	QPSK	50	0	0 mm	bottom	1:1	0.000	1.014	0.000	0.000	0.000	
1860.00	26140	Low	LTE Band 25 (PCS)	20	13.10	13.01	0.03	0	Ant C	F9FCN02HQ7L9	QPSK	1	0	0 mm	right	1:1	0.084	1.021	0.086	0.038	0.039	
1860.00	26140	Low	LTE Band 25 (PCS)	20	13.10	13.04	0.17	0	Ant C	F9FCN02HQ7L9	QPSK	50	0	0 mm	right	1:1	0.083	1.014	0.084	0.037	0.038	
1860.00	26140	Low	LTE Band 25 (PCS)	20	13.10	13.01	0.05	0	Ant C	F9FCN02HQ7L9	QPSK	1	0	0 mm	left	1:1	0.029	1.021	0.030	0.013	0.013	
1860.00	26140	Low	LTE Band 25 (PCS)	20	13.10	13.04	0.05	0	Ant C	F9FCN02HQ7L9	QPSK	50	0	0 mm	left	1:1	0.031	1.014	0.031	0.014	0.014	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 93 of 114

Table 10-24
LTE Band 25 (PCS) Ant D Body SAR

MEASUREMENT RESULTS																						
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.																(W/kg)		(W/kg)	(W/kg)		
1860.00	26140	Low	LTE Band 25 (PCS)	20	12.00	11.97	-0.08	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	back	1:1	0.821	1.007	0.827	0.341	0.343	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	12.00	11.97	-0.03	0	Ant D	F9FCN02QQ7L9	QPSK	1	99	0 mm	back	1:1	0.839	1.007	0.845	0.348	0.350	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.98	-0.03	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	back	1:1	0.885	1.005	0.889	0.365	0.367	
1860.00	26140	Low	LTE Band 25 (PCS)	20	12.00	11.95	-0.04	0	Ant D	F9FCN02QQ7L9	QPSK	50	0	0 mm	back	1:1	0.792	1.012	0.802	0.330	0.334	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	12.00	11.91	-0.03	0	Ant D	F9FCN02QQ7L9	QPSK	50	50	0 mm	back	1:1	0.842	1.021	0.860	0.348	0.355	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	12.00	-0.06	0	Ant D	F9FCN02QQ7L9	QPSK	50	0	0 mm	back	1:1	0.890	1.000	0.890	0.367	0.367	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.94	-0.01	0	Ant D	F9FCN02QQ7L9	QPSK	100	0	0 mm	back	1:1	0.894	1.014	0.907	0.373	0.378	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.98	0.02	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	top	1:1	0.680	1.005	0.683	0.308	0.310	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	12.00	0.01	0	Ant D	F9FCN02QQ7L9	QPSK	50	0	0 mm	top	1:1	0.667	1.000	0.667	0.301	0.301	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.98	0.00	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	bottom	1:1	0.000	1.005	0.000	0.000	0.000	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	12.00	0.00	0	Ant D	F9FCN02QQ7L9	QPSK	50	0	0 mm	bottom	1:1	0.000	1.000	0.000	0.000	0.000	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.98	0.17	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	right	1:1	0.008	1.005	0.008	0.003	0.003	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	12.00	0.18	0	Ant D	F9FCN02QQ7L9	QPSK	50	0	0 mm	right	1:1	0.008	1.000	0.008	0.003	0.003	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	11.98	-0.10	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	left	1:1	0.049	1.005	0.049	0.021	0.021	
1905.00	26590	High	LTE Band 25 (PCS)	20	12.00	12.00	-0.05	0	Ant D	F9FCN02QQ7L9	QPSK	50	0	0 mm	left	1:1	0.051	1.000	0.051	0.022	0.022	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																						
Spatial Peak								Body														
Uncontrolled Exposure/General Population								1.6 W/kg (mW/g)														
								averaged over 1 gram														

Table 10-25
LTE Band 30 Ant C Body SAR

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
2310.00	27710	Mid	LTE Band 30	10	13.20	13.07	-0.11	0	Ant C	F9FCN02SQ7L9	QPSK	1	0	0 mm	back	1:1	0.719	1.030	0.741	0.309	0.318	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.05	-0.09	0	Ant C	F9FCN02SQ7L9	QPSK	25	12	0 mm	back	1:1	0.695	1.035	0.719	0.298	0.308	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.07	-0.04	0	Ant C	F9FCN02SQ7L9	QPSK	1	0	0 mm	top	1:1	0.761	1.030	0.784	0.337	0.347	A13
2310.00	27710	Mid	LTE Band 30	10	13.20	13.05	0.00	0	Ant C	F9FCN02SQ7L9	QPSK	25	12	0 mm	top	1:1	0.707	1.035	0.732	0.312	0.323	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.07	0.00	0	Ant C	F9FCN02SQ7L9	QPSK	1	0	0 mm	bottom	1:1	0.000	1.030	0.000	0.000	0.000	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.05	0.00	0	Ant C	F9FCN02SQ7L9	QPSK	25	12	0 mm	bottom	1:1	0.000	1.035	0.000	0.000	0.000	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.07	-0.04	0	Ant C	F9FCN02SQ7L9	QPSK	1	0	0 mm	right	1:1	0.102	1.030	0.105	0.043	0.044	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.05	0.00	0	Ant C	F9FCN02SQ7L9	QPSK	25	12	0 mm	right	1:1	0.096	1.035	0.099	0.040	0.041	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.07	0.04	0	Ant C	F9FCN02SQ7L9	QPSK	1	0	0 mm	left	1:1	0.014	1.030	0.014	0.006	0.006	
2310.00	27710	Mid	LTE Band 30	10	13.20	13.05	0.10	0	Ant C	F9FCN02SQ7L9	QPSK	25	12	0 mm	left	1:1	0.015	1.035	0.016	0.007	0.007	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 94 of 114

Table 10-26
LTE Band 30 Ant D Body SAR

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
2310.00	27710	Mid	LTE Band 30	10	12.80	12.76	0.13	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	back	1:1	0.650	1.009	0.656	0.300	0.303	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.78	-0.01	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	back	1:1	0.626	1.005	0.629	0.289	0.290	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.76	0.02	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	top	1:1	0.563	1.009	0.568	0.248	0.250	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.78	-0.05	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	top	1:1	0.552	1.005	0.555	0.243	0.244	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.76	-0.12	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	bottom	1:1	0.000	1.009	0.000	0.000	0.000	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.78	0.00	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	bottom	1:1	0.000	1.005	0.000	0.000	0.000	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.76	0.02	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	right	1:1	0.027	1.009	0.027	0.012	0.012	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.78	0.05	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	right	1:1	0.028	1.005	0.028	0.012	0.012	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.76	-0.07	0	Ant D	F9FCN02QQ7L9	QPSK	1	0	0 mm	left	1:1	0.105	1.009	0.106	0.045	0.045	
2310.00	27710	Mid	LTE Band 30	10	12.80	12.78	-0.02	0	Ant D	F9FCN02QQ7L9	QPSK	25	0	0 mm	left	1:1	0.102	1.005	0.103	0.043	0.043	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body														
Spatial Peak								1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population								averaged over 1 gram														

Table 10-27
LTE Band 7 Ant C Body SAR

MEASUREMENT RESULTS																								
1 CC Uplink / 2CC Uplink	Component Carrier	FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #	
		MHz	Ch.															(W/kg)		(W/kg)	(W/kg)			
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.33	-0.03	0	Ant C	F9FCN02Q7LC	QPSK	1	99	0 mm	back	1:1	0.798	1.016	0.811	0.320	0.325	
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	12.30	-0.03	0	Ant C	F9FCN02Q7LC	QPSK	1	0	0 mm	back	1:1	0.774	1.023	0.792	0.309	0.316	
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.40	11.97	-0.04	0	Ant C	F9FCN02Q7LC	QPSK	1	50	0 mm	back	1:1	0.759	1.104	0.838	0.301	0.332	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.25	-0.02	0	Ant C	F9FCN02Q7LC	QPSK	50	50	0 mm	back	1:1	0.785	1.035	0.812	0.315	0.326	
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	12.21	-0.04	0	Ant C	F9FCN02Q7LC	QPSK	50	25	0 mm	back	1:1	0.768	1.045	0.803	0.306	0.320	
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.40	12.14	-0.04	0	Ant C	F9FCN02Q7LC	QPSK	50	25	0 mm	back	1:1	0.767	1.062	0.815	0.304	0.323	
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	12.23	-0.03	0	Ant C	F9FCN02Q7LC	QPSK	100	0	0 mm	back	1:1	0.770	1.040	0.801	0.307	0.319	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.33	-0.03	0	Ant C	F9FCN02Q7LC	QPSK	1	99	0 mm	top	1:1	0.820	1.016	0.833	0.349	0.355	
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	12.30	0.01	0	Ant C	F9FCN02Q7LC	QPSK	1	0	0 mm	top	1:1	0.825	1.023	0.844	0.350	0.358	
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.40	11.93	-0.02	0	Ant C	F9FCN02Q7LC	QPSK	1	0	0 mm	top	1:1	0.812	1.114	0.905	0.348	0.388	
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.40	11.97	-0.02	0	Ant C	F9FCN02Q7LC	QPSK	1	50	0 mm	top	1:1	0.824	1.104	0.910	0.348	0.384	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.25	-0.05	0	Ant C	F9FCN02Q7LC	QPSK	50	50	0 mm	top	1:1	0.810	1.035	0.838	0.345	0.357	
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	12.21	-0.01	0	Ant C	F9FCN02Q7LC	QPSK	50	25	0 mm	top	1:1	0.790	1.045	0.826	0.335	0.350	
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.40	12.14	0.03	0	Ant C	F9FCN02Q7LC	QPSK	50	25	0 mm	top	1:1	0.815	1.062	0.866	0.344	0.365	
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	12.23	-0.07	0	Ant C	F9FCN02Q7LC	QPSK	100	0	0 mm	top	1:1	0.787	1.040	0.818	0.334	0.347	
2 CC Uplink	PCC	2560.00	21350	High	LTE Band 7	20	12.40	12.30	-0.04	0	Ant C	F9FCN02Q7LC	QPSK	1	0	0 mm	top	1:1	0.858	1.023	0.878	0.366	0.374	A14
2 CC Uplink	SCC	2540.20	21152	High	LTE Band 7	20		0	Ant C	F9FCN02Q7LC	QPSK	1	99	99										
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.33	0.00	0	Ant C	F9FCN02Q7LC	QPSK	1	99	0 mm	bottom	1:1	0.000	1.016	0.000	0.000	0.000	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.25	0.00	0	Ant C	F9FCN02Q7LC	QPSK	50	50	0 mm	bottom	1:1	0.000	1.035	0.000	0.000	0.000	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.33	0.12	0	Ant C	F9FCN02Q7LC	QPSK	1	99	0 mm	right	1:1	0.108	1.016	0.110	0.043	0.044	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.25	0.10	0	Ant C	F9FCN02Q7LC	QPSK	50	50	0 mm	right	1:1	0.104	1.035	0.108	0.041	0.042	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.33	-0.04	0	Ant C	F9FCN02Q7LC	QPSK	1	99	0 mm	left	1:1	0.021	1.016	0.021	0.008	0.008	
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	12.25	0.04	0	Ant C	F9FCN02Q7LC	QPSK	50	50	0 mm	left	1:1	0.020	1.035	0.021	0.007	0.007	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Body														
Spatial Peak										1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population										averaged over 1 gram														

FCC ID: BCGA2429		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 95 of 114

Table 10-28
LTE Band 7 Ant D Body SAR

M+E2:Z4065EASUREMENT RESULTS																							
1 CC Uplink / 2CC Uplink	Component Carrier	FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
		MHz	Ch.															(W/kg)		(W/kg)	(W/kg)		
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	11.79	0.02	0	Ant D	F9FCN020Q7LC	QPSK	1	50	0 mm	back	1:1	0.701	1.151	0.807	0.303	0.349
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	11.92	-0.03	0	Ant D	F9FCN020Q7LC	QPSK	1	0	0 mm	back	1:1	0.675	1.117	0.754	0.289	0.323
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.40	11.83	-0.01	0	Ant D	F9FCN020Q7LC	QPSK	1	50	0 mm	back	1:1	0.631	1.140	0.719	0.268	0.306
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	11.86	-0.05	0	Ant D	F9FCN020Q7LC	QPSK	50	50	0 mm	back	1:1	0.696	1.132	0.788	0.300	0.340
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	11.95	-0.01	0	Ant D	F9FCN020Q7LC	QPSK	50	0	0 mm	back	1:1	0.669	1.109	0.742	0.284	0.315
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.40	11.82	0.00	0	Ant D	F9FCN020Q7LC	QPSK	50	25	0 mm	back	1:1	0.633	1.143	0.724	0.267	0.305
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	11.84	0.01	0	Ant D	F9FCN020Q7LC	QPSK	100	0	0 mm	back	1:1	0.718	1.138	0.817	0.308	0.351
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	11.79	-0.09	0	Ant D	F9FCN020Q7LC	QPSK	1	50	0 mm	top	1:1	0.766	1.151	0.882	0.318	0.366
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	11.92	0.00	0	Ant D	F9FCN020Q7LC	QPSK	1	0	0 mm	top	1:1	0.782	1.117	0.873	0.322	0.360
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.40	11.83	-0.01	0	Ant D	F9FCN020Q7LC	QPSK	1	50	0 mm	top	1:1	0.790	1.140	0.901	0.324	0.369
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	11.86	-0.09	0	Ant D	F9FCN020Q7LC	QPSK	50	50	0 mm	top	1:1	0.772	1.132	0.874	0.320	0.362
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	11.95	-0.01	0	Ant D	F9FCN020Q7LC	QPSK	50	0	0 mm	top	1:1	0.781	1.109	0.866	0.323	0.358
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.40	11.78	-0.01	0	Ant D	F9FCN020Q7LC	QPSK	50	0	0 mm	top	1:1	0.796	1.153	0.918	0.327	0.377
1 CC Uplink	N/A	2560.00	21350	High	LTE Band 7	20	12.40	11.82	-0.01	0	Ant D	F9FCN020Q7LC	QPSK	50	25	0 mm	top	1:1	0.795	1.143	0.909	0.325	0.371
1 CC Uplink	N/A	2510.00	20850	Low	LTE Band 7	20	12.40	11.84	-0.03	0	Ant D	F9FCN020Q7LC	QPSK	100	0	0 mm	top	1:1	0.777	1.138	0.884	0.323	0.368
2 CC Uplink	PCC	2560.00	21350	High	LTE Band 7	20	12.40	12.10	0.02	0	Ant D	F9FCN020Q7LC	QPSK	50	0	0 mm	top	1:1	0.827	1.072	0.887	0.338	0.362
2 CC Uplink	SCC	2540.20	21152	High	LTE Band 7	20		50	50														
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	11.92	0.00	0	Ant D	F9FCN020Q7LC	QPSK	1	0	0 mm	bottom	1:1	0.000	1.117	0.000	0.000	0.000
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	11.95	0.00	0	Ant D	F9FCN020Q7LC	QPSK	50	0	0 mm	bottom	1:1	0.000	1.109	0.000	0.000	0.000
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	11.92	0.08	0	Ant D	F9FCN020Q7LC	QPSK	1	0	0 mm	right	1:1	0.011	1.117	0.012	0.004	0.004
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	11.95	0.10	0	Ant D	F9FCN020Q7LC	QPSK	50	0	0 mm	right	1:1	0.011	1.109	0.012	0.004	0.004
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	11.92	0.00	0	Ant D	F9FCN020Q7LC	QPSK	1	0	0 mm	left	1:1	0.139	1.117	0.155	0.056	0.063
1 CC Uplink	N/A	2535.00	21100	Mid	LTE Band 7	20	12.40	11.95	0.03	0	Ant D	F9FCN020Q7LC	QPSK	50	0	0 mm	left	1:1	0.137	1.109	0.152	0.054	0.060
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram													

FCC ID: BCGA2429	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 96 of 114

Table 10-29
LTE Band 41 Ant C Body SAR

M+E2:Z4065EASUREMENT RESULTS																								
1 CC Uplink / 2CC Uplink, Power class	Component Carrier	FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drit [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (lg)	Scaling Factor	Reported SAR (lg)	SAR (lg)	Reported SAR (lg)	Plot #	
		MHz	Ch.															(W/kg)		(W/kg)	(W/kg)	(W/kg)		
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.38	0.00	0	Ant C	F9FCN02TQ7L9	QPSK	1	50	0 mm	back	1:1.58	1.050	1.005	1.055	0.407	0.409	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.40	0.02	0	Ant C	F9FCN02TQ7L9	QPSK	1	0	0 mm	back	1:1.58	1.070	1.000	1.070	0.401	0.401	
1 CC Uplink - Power Class 3	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	15.20	0.06	0	Ant C	F9FCN02TQ7L9	QPSK	1	50	0 mm	back	1:1.58	1.010	1.047	1.057	0.382	0.400	
1 CC Uplink - Power Class 3	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	15.27	0.08	0	Ant C	F9FCN02TQ7L9	QPSK	1	0	0 mm	back	1:1.58	0.971	1.030	1.000	0.361	0.372	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	15.16	0.08	0	Ant C	F9FCN02TQ7L9	QPSK	1	50	0 mm	back	1:1.58	0.862	1.057	0.911	0.315	0.333	
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.34	0.03	0	Ant C	F9FCN02TQ7L9	QPSK	50	0	0 mm	back	1:1.58	1.060	1.014	1.075	0.410	0.416	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.37	0.02	0	Ant C	F9FCN02TQ7L9	QPSK	50	0	0 mm	back	1:1.58	1.090	1.007	1.098	0.414	0.417	A15
1 CC Uplink - Power Class 3	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	15.21	0.03	0	Ant C	F9FCN02TQ7L9	QPSK	50	25	0 mm	back	1:1.58	0.852	1.045	0.890	0.327	0.342	
1 CC Uplink - Power Class 3	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	15.20	0.02	0	Ant C	F9FCN02TQ7L9	QPSK	50	0	0 mm	back	1:1.58	0.956	1.047	1.001	0.352	0.369	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	15.06	0.02	0	Ant C	F9FCN02TQ7L9	QPSK	50	25	0 mm	back	1:1.58	0.859	1.081	0.929	0.312	0.337	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.34	0.19	0	Ant C	F9FCN02TQ7L9	QPSK	100	0	0 mm	back	1:1.58	1.090	1.014	1.105	0.408	0.414	
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.38	-0.13	0	Ant C	F9FCN02TQ7L9	QPSK	1	50	0 mm	top	1:1.58	0.996	1.005	1.001	0.425	0.427	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.40	-0.07	0	Ant C	F9FCN02TQ7L9	QPSK	1	0	0 mm	top	1:1.58	0.963	1.000	0.963	0.397	0.397	
1 CC Uplink - Power Class 3	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	15.20	-0.04	0	Ant C	F9FCN02TQ7L9	QPSK	1	50	0 mm	top	1:1.58	1.060	1.047	1.110	0.439	0.460	
1 CC Uplink - Power Class 3	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	15.27	-0.04	0	Ant C	F9FCN02TQ7L9	QPSK	1	0	0 mm	top	1:1.58	1.000	1.030	1.030	0.409	0.421	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	15.14	-0.01	0	Ant C	F9FCN02TQ7L9	QPSK	1	0	0 mm	top	1:1.58	1.040	1.062	1.104	0.423	0.449	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	15.16	-0.05	0	Ant C	F9FCN02TQ7L9	QPSK	1	50	0 mm	top	1:1.58	1.060	1.057	1.120	0.420	0.444	
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.34	0.03	0	Ant C	F9FCN02TQ7L9	QPSK	50	0	0 mm	top	1:1.58	0.940	1.014	0.953	0.406	0.412	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.37	0.03	0	Ant C	F9FCN02TQ7L9	QPSK	50	0	0 mm	top	1:1.58	0.991	1.007	0.998	0.401	0.404	
1 CC Uplink - Power Class 3	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	15.21	-0.09	0	Ant C	F9FCN02TQ7L9	QPSK	50	25	0 mm	top	1:1.58	1.040	1.045	1.087	0.433	0.452	
1 CC Uplink - Power Class 3	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	15.20	-0.16	0	Ant C	F9FCN02TQ7L9	QPSK	50	0	0 mm	top	1:1.58	1.060	1.047	1.110	0.434	0.454	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	15.06	-0.13	0	Ant C	F9FCN02TQ7L9	QPSK	50	25	0 mm	top	1:1.58	1.010	1.081	1.092	0.416	0.450	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.34	-0.09	0	Ant C	F9FCN02TQ7L9	QPSK	100	0	0 mm	top	1:1.58	0.968	1.014	0.982	0.409	0.415	
1 CC Uplink - Power Class 2	N/A	2680.00	41490	High	LTE Band 41	20	15.40	14.79	-0.02	0	Ant C	F9FCN02TQ7L9	QPSK	1	50	0 mm	top	1:2.31	0.658	1.151	0.757	0.272	0.313	
2 CC Uplink - Power Class 3	PCC	2680.00	41490	High	LTE Band 41	20	15.40	15.05	-0.10	0	Ant C	F9FCN02TQ7L9	QPSK	1	0	0 mm	top	1:1.58	1.030	1.084	1.117	0.417	0.452	
2 CC Uplink - Power Class 3	SCC	2660.20	41292	High	LTE Band 41	20								1	99									
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.40	0.00	0	Ant C	F9FCN02TQ7L9	QPSK	1	0	0 mm	bottom	1:1.58	0.000	1.000	0.000	0.000	0.000	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.37	0.00	0	Ant C	F9FCN02TQ7L9	QPSK	50	0	0 mm	bottom	1:1.58	0.000	1.007	0.000	0.000	0.000	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.40	0.06	0	Ant C	F9FCN02TQ7L9	QPSK	1	0	0 mm	right	1:1.58	0.135	1.000	0.135	0.054	0.054	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.37	0.07	0	Ant C	F9FCN02TQ7L9	QPSK	50	0	0 mm	right	1:1.58	0.109	1.007	0.110	0.043	0.043	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.40	0.09	0	Ant C	F9FCN02TQ7L9	QPSK	1	0	0 mm	left	1:1.58	0.036	1.000	0.036	0.014	0.014	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.37	0.14	0	Ant C	F9FCN02TQ7L9	QPSK	50	0	0 mm	left	1:1.58	0.021	1.007	0.021	0.007	0.007	
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.34	0.08	0	Ant C	F9FCN02TQ7L9	QPSK	50	0	0 mm	back	1:1.58	0.931	1.014	0.944	0.376	0.381	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.37	-0.05	0	Ant C	F9FCN02TQ7L9	QPSK	50	0	0 mm	back	1:1.58	0.927	1.007	0.933	0.368	0.371	
ANSI / IEEE C65.1 1992 - SAFETY LIMIT												Body 1.6 W/kg (mW/g) averaged over 1 gram												
Spatial Peak Uncontrolled Exposure/General Population																								

Note: Blue entry represents variability measurement.

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 97 of 114

Table 10-30
LTE Band 41 Ant D Body SAR

M+E2:Z4065EASUREMENT RESULTS																								
1 CC Uplink / 2CC Uplink, Power class	Component Carrier	FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Antenna Config.	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	SAR (10g) (W/kg)	Reported SAR (10g) (W/kg)	Plot #	
		MHz	Ch.																					
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.11	-0.02	0	Ant D	F9FCN02TQ7L9	QPSK	1	0	0 mm	back	1:1.58	0.879	1.069	0.940	0.366	0.391	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.24	-0.02	0	Ant D	F9FCN02TQ7L9	QPSK	1	50	0 mm	back	1:1.58	0.765	1.038	0.794	0.318	0.330	
1 CC Uplink - Power Class 3	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	15.12	-0.02	0	Ant D	F9FCN02TQ7L9	QPSK	1	50	0 mm	back	1:1.58	0.722	1.067	0.770	0.300	0.320	
1 CC Uplink - Power Class 3	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	15.17	-0.01	0	Ant D	F9FCN02TQ7L9	QPSK	1	0	0 mm	back	1:1.58	0.623	1.054	0.657	0.254	0.268	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	14.95	-0.05	0	Ant D	F9FCN02TQ7L9	QPSK	1	0	0 mm	back	1:1.58	0.549	1.109	0.609	0.222	0.246	
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.05	0.14	0	Ant D	F9FCN02TQ7L9	QPSK	50	25	0 mm	back	1:1.58	0.699	1.084	0.758	0.318	0.345	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.23	0.01	0	Ant D	F9FCN02TQ7L9	QPSK	50	0	0 mm	back	1:1.58	0.760	1.040	0.790	0.319	0.332	
1 CC Uplink - Power Class 3	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	14.99	-0.03	0	Ant D	F9FCN02TQ7L9	QPSK	50	0	0 mm	back	1:1.58	0.699	1.099	0.768	0.290	0.319	
1 CC Uplink - Power Class 3	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	15.13	-0.05	0	Ant D	F9FCN02TQ7L9	QPSK	50	25	0 mm	back	1:1.58	0.578	1.064	0.615	0.236	0.251	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	14.86	-0.08	0	Ant D	F9FCN02TQ7L9	QPSK	50	0	0 mm	back	1:1.58	0.531	1.132	0.601	0.214	0.242	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.17	-0.01	0	Ant D	F9FCN02TQ7L9	QPSK	100	0	0 mm	back	1:1.58	0.747	1.054	0.787	0.316	0.333	
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.11	0.00	0	Ant D	F9FCN02TQ7L9	QPSK	1	0	0 mm	top	1:1.58	0.882	1.069	0.943	0.371	0.397	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.24	-0.03	0	Ant D	F9FCN02TQ7L9	QPSK	1	50	0 mm	top	1:1.58	0.908	1.038	0.943	0.375	0.389	
1 CC Uplink - Power Class 3	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	15.12	0.00	0	Ant D	F9FCN02TQ7L9	QPSK	1	50	0 mm	top	1:1.58	0.926	1.067	0.988	0.380	0.405	
1 CC Uplink - Power Class 3	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	15.17	-0.02	0	Ant D	F9FCN02TQ7L9	QPSK	1	0	0 mm	top	1:1.58	0.965	1.054	1.017	0.388	0.409	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	14.95	0.01	0	Ant D	F9FCN02TQ7L9	QPSK	1	0	0 mm	top	1:1.58	0.867	1.109	0.962	0.348	0.386	
1 CC Uplink - Power Class 3	N/A	2506.00	39750	Low	LTE Band 41	20	15.40	15.05	-0.02	0	Ant D	F9FCN02TQ7L9	QPSK	50	25	0 mm	top	1:1.58	0.880	1.084	0.954	0.364	0.395	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.23	-0.01	0	Ant D	F9FCN02TQ7L9	QPSK	50	0	0 mm	top	1:1.58	0.917	1.040	0.954	0.378	0.393	
1 CC Uplink - Power Class 3	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	14.99	-0.20	0	Ant D	F9FCN02TQ7L9	QPSK	50	0	0 mm	top	1:1.58	0.934	1.099	1.026	0.381	0.419	
1 CC Uplink - Power Class 3	N/A	2636.50	41055	Mid-High	LTE Band 41	20	15.40	15.13	-0.03	0	Ant D	F9FCN02TQ7L9	QPSK	50	25	0 mm	top	1:1.58	0.919	1.064	0.978	0.366	0.389	
1 CC Uplink - Power Class 3	N/A	2680.00	41490	High	LTE Band 41	20	15.40	14.86	-0.15	0	Ant D	F9FCN02TQ7L9	QPSK	50	0	0 mm	top	1:1.58	0.867	1.132	0.981	0.330	0.374	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.17	-0.01	0	Ant D	F9FCN02TQ7L9	QPSK	100	0	0 mm	top	1:1.58	0.901	1.054	0.950	0.370	0.390	
1 CC Uplink - Power Class 2	N/A	2593.00	40620	Mid	LTE Band 41	20	15.40	14.97	-0.02	0	Ant D	F9FCN02TQ7L9	QPSK	50	0	0 mm	top	12:31	0.621	1.104	0.686	0.250	0.276	
2 CC Uplink - Power Class 3	PCC	2593.00	40620	Mid	LTE Band 41	20	15.40	14.81	-0.01	0	Ant D	F9FCN02TQ7L9	QPSK	50	0	0 mm	top	1:1.58	0.852	1.146	0.976	0.345	0.395	
2 CC Uplink - Power Class 3	SCC	2573.20	40422	Mid	LTE Band 41	20									50		50							
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.24	-0.05	0	Ant D	F9FCN02TQ7L9	QPSK	1	50	0 mm	bottom	1:1.58	0.000	1.038	0.000	0.000	0.000	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.23	0.14	0	Ant D	F9FCN02TQ7L9	QPSK	50	0	0 mm	bottom	1:1.58	0.000	1.040	0.000	0.000	0.000	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.24	0.05	0	Ant D	F9FCN02TQ7L9	QPSK	1	50	0 mm	right	1:1.58	0.023	1.038	0.024	0.009	0.009	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.23	0.03	0	Ant D	F9FCN02TQ7L9	QPSK	50	0	0 mm	right	1:1.58	0.020	1.040	0.021	0.008	0.008	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.24	0.13	0	Ant D	F9FCN02TQ7L9	QPSK	1	50	0 mm	left	1:1.58	0.147	1.038	0.153	0.060	0.062	
1 CC Uplink - Power Class 3	N/A	2549.50	40185	Low-Mid	LTE Band 41	20	15.40	15.23	0.07	0	Ant D	F9FCN02TQ7L9	QPSK	50	0	0 mm	left	1:1.58	0.147	1.040	0.153	0.060	0.062	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Body														
Spatial Peak										1.6 W/kg (mW/g)														
Uncontrolled Exposure/General Population										averaged over 1 gram														

Table 10-31
2.4 GHz WLAN Ant A Body SAR

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.														(W/kg)			(W/kg)	(W/kg)		
2437	6	802.11b	DSSS	22	16.00	15.15	0.14	0 mm	Ant A	V2	F9FCN00JQ7LC	1	back	100.0	0.052	1.216	1.000	0.063	0.026	0.032	
2437	6	802.11b	DSSS	22	16.00	15.15	-0.20	0 mm	Ant A	V2	F9FCN00JQ7LC	1	top	100.0	0.010	1.216	1.000	0.012	0.004	0.005	
2412	1	802.11b	DSSS	22	16.00	15.14	0.10	0 mm	Ant A	V2	F9FCN00JQ7LC	1	bottom	100.0	0.651	1.219	1.000	0.794	0.209	0.255	
2437	6	802.11b	DSSS	22	16.00	15.15	0.05	0 mm	Ant A	V2	F9FCN00JQ7LC	1	bottom	100.0	0.714	1.216	1.000	0.868	0.228	0.277	A16
2437	6	802.11b	DSSS	22	16.00	15.06	0.06	0 mm	Ant A	V1	F9FCN02TQ7L9	1	bottom	100.0	0.582	1.242	1.000	0.723	0.195	0.242	
2462	11	802.11b	DSSS	22	16.00	15.12	0.01	0 mm	Ant A	V2	F9FCN00JQ7LC	1	bottom	100.0	0.666	1.225	1.000	0.816	0.213	0.261	
2437	6	802.11b	DSSS	22	16.00	15.15	0.19	0 mm	Ant A	V2	F9FCN00JQ7LC	1	right	100.0	0.001	1.216	1.000	0.001	0.000	0.000	
2437	6	802.11b	DSSS	22	16.00	15.15	0.09	0 mm	Ant A	V2	F9FCN00JQ7LC	1	left	100.0	0.112	1.216	1.000	0.136	0.052	0.063	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body													
Spatial Peak								1.6 W/kg (mW/g)													
Uncontrolled Exposure/General Population								averaged over 1 gram													

FCC ID: BCGA2429		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 98 of 114

Table 10-32
2.4 GHz WLAN Ant B Body SAR

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Pilot #
MHz	Ch.														(W/kg)			(W/kg)		(W/kg)	
2437	6	802.11b	DSSS	22	16.00	15.24	0.05	0 mm	Ant B	V2	F9FCN020Q7LC	1	back	100.0	0.038	1.191	1.000	0.045	0.018	0.021	
2437	6	802.11b	DSSS	22	16.00	15.24	0.12	0 mm	Ant B	V2	F9FCN020Q7LC	1	top	100.0	0.009	1.191	1.000	0.011	0.003	0.004	
2412	1	802.11b	DSSS	22	16.00	15.22	-0.06	0 mm	Ant B	V2	F9FCN020Q7LC	1	bottom	100.0	0.615	1.197	1.000	0.736	0.202	0.242	
2437	6	802.11b	DSSS	22	16.00	15.24	-0.13	0 mm	Ant B	V2	F9FCN020Q7LC	1	bottom	100.0	0.626	1.191	1.000	0.746	0.206	0.245	
2462	11	802.11b	DSSS	22	16.00	15.14	0.03	0 mm	Ant B	V1	F9FCN02TQ7L9	1	bottom	100.0	0.609	1.219	1.000	0.742	0.200	0.244	
2462	11	802.11b	DSSS	22	16.00	15.23	-0.08	0 mm	Ant B	V2	F9FCN020Q7LC	1	bottom	100.0	0.698	1.194	1.000	0.833	0.227	0.271	
2437	6	802.11b	DSSS	22	16.00	15.24	0.10	0 mm	Ant B	V2	F9FCN020Q7LC	1	right	100.0	0.091	1.191	1.000	0.108	0.042	0.050	
2437	6	802.11b	DSSS	22	16.00	15.24	0.02	0 mm	Ant B	V2	F9FCN020Q7LC	1	left	100.0	0.004	1.191	1.000	0.005	0.002	0.002	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body 1.6 W/kg (mW/g) averaged over 1 gram													
Spatial Peak																					
Uncontrolled Exposure/General Population																					

Table 10-33
5 GHz WLAN Ant A Body SAR

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Pilot #
MHz	Ch.														(W/kg)			(W/kg)	(W/kg)		
5270	54	802.11n	OFDM	40	17.00	15.97	-0.02	0 mm	Ant A	V2	F9FCN020Q7LC	13.5	back	97.3	0.035	1.268	1.028	0.046	0.014	0.018	
5270	54	802.11n	OFDM	40	17.00	15.97	-0.08	0 mm	Ant A	V2	F9FCN020Q7LC	13.5	top	97.3	0.018	1.268	1.028	0.023	0.005	0.007	
5270	54	802.11n	OFDM	40	17.00	15.97	-0.03	0 mm	Ant A	V2	F9FCN020Q7LC	13.5	bottom	97.3	0.494	1.268	1.028	0.644	0.166	0.216	
5270	54	802.11n	OFDM	40	17.00	16.01	-0.15	0 mm	Ant A	V1	F9FCN02Q7L9	13.5	bottom	97.6	0.433	1.256	1.025	0.557	0.148	0.191	
5310	62	802.11n	OFDM	40	14.50	13.60	-0.21	0 mm	Ant A	V2	F9FCN020Q7LC	13.5	bottom	97.3	0.296	1.230	1.028	0.374	0.099	0.125	
5270	54	802.11n	OFDM	40	17.00	15.97	-0.04	0 mm	Ant A	V2	F9FCN020Q7LC	13.5	right	97.3	0.002	1.268	1.028	0.003	0.000	0.000	
5270	54	802.11n	OFDM	40	17.00	15.97	0.01	0 mm	Ant A	V2	F9FCN020Q7LC	13.5	left	97.3	0.070	1.268	1.028	0.091	0.027	0.035	
5690	138	802.11ac	OFDM	80	17.50	16.41	0.04	0 mm	Ant A	V2	F9FCN020Q7LC	29.3	back	95.4	0.060	1.285	1.048	0.081	0.020	0.027	
5690	138	802.11ac	OFDM	80	17.50	16.41	-0.19	0 mm	Ant A	V2	F9FCN020Q7LC	29.3	top	95.4	0.028	1.285	1.048	0.038	0.009	0.012	
5530	106	802.11ac	OFDM	80	12.00	10.91	-0.09	0 mm	Ant A	V2	F9FCN020Q7LC	29.3	bottom	95.4	0.327	1.285	1.048	0.440	0.111	0.149	
5610	122	802.11ac	OFDM	80	15.50	14.36	-0.09	0 mm	Ant A	V2	F9FCN020Q7LC	29.3	bottom	95.4	0.637	1.300	1.048	0.868	0.218	0.297	
5690	138	802.11ac	OFDM	80	17.50	16.69	-0.20	0 mm	Ant A	V1	F9FCN02Q7L9	29.3	bottom	95.4	0.836	1.205	1.048	1.056	0.283	0.357	A17
5690	138	802.11ac	OFDM	80	17.50	16.41	-0.07	0 mm	Ant A	V2	F9FCN020Q7LC	29.3	bottom	95.4	0.791	1.285	1.048	1.065	0.269	0.362	
5690	138	802.11ac	OFDM	80	17.50	16.41	0.06	0 mm	Ant A	V2	F9FCN020Q7LC	29.3	right	95.4	0.003	1.285	1.048	0.004	0.000	0.000	
5690	138	802.11ac	OFDM	80	17.50	16.41	-0.14	0 mm	Ant A	V2	F9FCN020Q7LC	29.3	left	95.4	0.092	1.285	1.048	0.124	0.032	0.043	
5755	151	802.11n	OFDM	40	16.25	15.23	0.08	0 mm	Ant A	V1	F9FCN02Q7L9	13.5	back	97.6	0.045	1.265	1.025	0.058	0.014	0.018	
5755	151	802.11n	OFDM	40	16.25	15.23	0.04	0 mm	Ant A	V1	F9FCN02Q7L9	13.5	top	97.6	0.019	1.265	1.025	0.025	0.007	0.009	
5755	151	802.11n	OFDM	40	16.25	15.23	0.07	0 mm	Ant A	V1	F9FCN02Q7L9	13.5	bottom	97.6	0.705	1.265	1.025	0.914	0.233	0.302	
5795	159	802.11n	OFDM	40	16.25	15.20	-0.08	0 mm	Ant A	V1	F9FCN02Q7L9	13.5	bottom	97.6	0.723	1.274	1.025	0.944	0.237	0.309	
5795	159	802.11n	OFDM	40	16.25	15.12	0.03	0 mm	Ant A	V2	F9FCN020Q7LC	13.5	bottom	97.3	0.645	1.297	1.028	0.860	0.208	0.277	
5755	151	802.11n	OFDM	40	16.25	15.23	0.00	0 mm	Ant A	V1	F9FCN02Q7L9	13.5	right	97.6	0.000	1.265	1.025	0.000	0.000	0.000	
5755	151	802.11n	OFDM	40	16.25	15.23	0.21	0 mm	Ant A	V1	F9FCN02Q7L9	13.5	left	97.6	0.086	1.265	1.025	0.112	0.029	0.038	
5690	138	802.11ac	OFDM	80	17.50	16.69	0.02	0 mm	Ant A	V1	F9FCN02Q7L9	29.3	bottom	95.4	0.823	1.205	1.048	1.039	0.274	0.346	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body													
Spatial Peak								1.6 W/kg (mW/g)													
Uncontrolled Exposure/General Population								averaged over 1 gram													

Note: Blue entry represents variability measurement.

FCC ID: BCGA2429	 PCTEST Proud to be part of the	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 99 of 114

Table 10-34
5 GHz WLAN Ant B Body SAR

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.														(W/kg)			(W/kg)	(W/kg)		
5270	54	802.11n	OFDM	40	16.75	16.02	-0.07	0 mm	Ant B	V1	F9FCN02QQ7L9	13.5	back	97.7	0.048	1.183	1.024	0.058	0.019	0.023	
5270	54	802.11n	OFDM	40	16.75	16.02	-0.06	0 mm	Ant B	V1	F9FCN02QQ7L9	13.5	top	97.7	0.019	1.183	1.024	0.023	0.006	0.007	
5270	54	802.11n	OFDM	40	16.75	16.02	-0.03	0 mm	Ant B	V1	F9FCN02QQ7L9	13.5	bottom	97.7	0.730	1.183	1.024	0.884	0.237	0.287	
5270	54	802.11n	OFDM	40	16.75	15.98	-0.10	0 mm	Ant B	V2	F9FCN020Q7LC	13.5	bottom	97.3	0.613	1.194	1.028	0.752	0.206	0.253	
5310	62	802.11n	OFDM	40	14.50	13.51	-0.05	0 mm	Ant B	V1	F9FCN02QQ7L9	13.5	bottom	97.7	0.421	1.256	1.024	0.541	0.136	0.175	
5270	54	802.11n	OFDM	40	16.75	16.02	0.16	0 mm	Ant B	V1	F9FCN02QQ7L9	13.5	right	97.7	0.083	1.183	1.024	0.101	0.033	0.040	
5270	54	802.11n	OFDM	40	16.75	16.02	-0.03	0 mm	Ant B	V1	F9FCN02QQ7L9	13.5	left	97.7	0.001	1.183	1.024	0.001	0.000	0.000	
5690	138	802.11ac	OFDM	80	17.25	16.20	-0.09	0 mm	Ant B	V2	F9FCN020Q7LC	29.3	back	95.4	0.049	1.274	1.048	0.065	0.019	0.025	
5690	138	802.11ac	OFDM	80	17.25	16.20	0.05	0 mm	Ant B	V2	F9FCN020Q7LC	29.3	top	95.4	0.026	1.274	1.048	0.035	0.009	0.012	
5530	106	802.11ac	OFDM	80	12.00	10.87	-0.06	0 mm	Ant B	V2	F9FCN020Q7LC	29.3	bottom	95.4	0.255	1.297	1.048	0.347	0.086	0.117	
5610	122	802.11ac	OFDM	80	15.50	14.49	-0.06	0 mm	Ant B	V2	F9FCN020Q7LC	29.3	bottom	95.4	0.630	1.262	1.048	0.833	0.220	0.291	
5690	138	802.11ac	OFDM	80	17.25	16.40	0.05	0 mm	Ant B	V1	F9FCN02QQ7L9	29.3	bottom	95.4	0.691	1.216	1.048	0.881	0.249	0.317	
5690	138	802.11ac	OFDM	80	17.25	16.20	-0.08	0 mm	Ant B	V2	F9FCN020Q7LC	29.3	bottom	95.4	0.711	1.274	1.048	0.949	0.252	0.336	
5690	138	802.11ac	OFDM	80	17.25	16.20	-0.18	0 mm	Ant B	V2	F9FCN020Q7LC	29.3	right	95.4	0.094	1.274	1.048	0.126	0.035	0.047	
5690	138	802.11ac	OFDM	80	17.25	16.20	-0.06	0 mm	Ant B	V2	F9FCN020Q7LC	29.3	left	95.4	0.000	1.274	1.048	0.000	0.000	0.000	
5795	159	802.11n	OFDM	40	16.50	15.40	0.10	0 mm	Ant B	V2	F9FCN020Q7LC	13.5	back	97.3	0.051	1.288	1.028	0.068	0.018	0.024	
5795	159	802.11n	OFDM	40	16.50	15.40	0.02	0 mm	Ant B	V2	F9FCN020Q7LC	13.5	top	97.3	0.014	1.288	1.028	0.019	0.003	0.004	
5755	151	802.11n	OFDM	40	16.50	15.39	-0.03	0 mm	Ant B	V2	F9FCN020Q7LC	13.5	bottom	97.3	0.657	1.291	1.028	0.872	0.225	0.299	
5795	159	802.11n	OFDM	40	16.50	15.40	0.09	0 mm	Ant B	V2	F9FCN020Q7LC	13.5	bottom	97.3	0.688	1.288	1.028	0.911	0.234	0.310	
5795	159	802.11n	OFDM	40	16.50	15.48	-0.13	0 mm	Ant B	V1	F9FCN02HQ7L9	13.5	bottom	97.7	0.576	1.265	1.024	0.746	0.198	0.256	
5795	159	802.11n	OFDM	40	16.50	15.40	0.08	0 mm	Ant B	V2	F9FCN020Q7LC	13.5	right	97.3	0.081	1.288	1.028	0.107	0.026	0.034	
5795	159	802.11n	OFDM	40	16.50	15.40	0.00	0 mm	Ant B	V2	F9FCN020Q7LC	13.5	left	97.3	0.000	1.288	1.028	0.000	0.000	0.000	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body													
Spatial Peak								1.6 W/kg (mW/g)													
Uncontrolled Exposure/General Population								averaged over 1 gram													

Table 10-35
Bluetooth Ant A Body SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate [Mbps]	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.													(W/kg)			(W/kg)	(W/kg)		
2441	39	Bluetooth	FHSS	17.00	16.25	-0.03	0 mm	Ant A	V1	F9FCN02QQ7L9	1	back	77.1	0.038	1.189	1.005	0.045	0.017	0.020	
2441	39	Bluetooth	FHSS	17.00	16.25	-0.20	0 mm	Ant A	V1	F9FCN02QQ7L9	1	top	77.1	0.003	1.189	1.005	0.004	0.001	0.001	
2402	0	Bluetooth	FHSS	17.00	16.17	-0.18	0 mm	Ant A	V1	F9FCN02QQ7L9	1	bottom	77.1	0.740	1.211	1.005	0.901	0.240	0.292	A18
2402	0	Bluetooth	FHSS	17.00	15.70	-0.03	0 mm	Ant A	V2	F9FCN00JQ7LC	1	bottom	77.1	0.559	1.349	1.005	0.758	0.179	0.243	
2402	0	Bluetooth	FHSS	10.00	9.80	-0.04	0 mm	Ant A	V1	F9FCN02QQ7L9	1	bottom	77.1	0.226	1.047	1.005	0.238	0.071	0.075	
2441	39	Bluetooth	FHSS	17.00	16.25	-0.01	0 mm	Ant A	V1	F9FCN02QQ7L9	1	bottom	77.1	0.654	1.189	1.005	0.781	0.215	0.257	
2480	78	Bluetooth	FHSS	17.00	15.00	0.05	0 mm	Ant A	V1	F9FCN02QQ7L9	1	bottom	77.1	0.468	1.585	1.005	0.745	0.153	0.244	
2441	39	Bluetooth	FHSS	17.00	16.25	-0.03	0 mm	Ant A	V1	F9FCN02QQ7L9	1	right	77.1	0.001	1.189	1.005	0.001	0.000	0.000	
2441	39	Bluetooth	FHSS	17.00	16.25	0.02	0 mm	Ant A	V1	F9FCN02QQ7L9	1	left	77.1	0.101	1.189	1.005	0.121	0.046	0.055	
2402	0	Bluetooth	FHSS	10.00	9.80	0.04	0 mm	Ant A	V1	F9FCN02QQ7L9	1	left	77.1	0.021	1.047	1.005	0.022	0.008	0.008	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body													
Spatial Peak							1.6 W/kg (mW/g)													
Uncontrolled Exposure/General Population							averaged over 1 gram													

Note: The reported SAR was scaled to the 77.5% transmission duty factor to determine compliance since the duty factor of the device is permanently limited to 77.5% per the manufacturer.

FCC ID: BCGA2429	 PCTEST Proud to be part of the	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 100 of 114

10.2 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 12 for variability analysis.
7. FCC KDB Publication 616217 D04v01r02 Section 4.3, SAR tests are required for the back surface and edges of the tablet with the tablet touching the phantom. The SAR Exclusion Threshold in FCC KDB 447498 D01v06 was applied to determine SAR test exclusion for adjacent edge configurations.

GSM Test Notes:

1. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

UMTS Notes:

1. UMTS mode was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 7.5.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 and MCC=001 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 101 of 114

4. Per FCC KDB Publication 447498 D01v06, when the reported LTE Band 41 SAR measured at the highest output power channel in a given a test configuration was > 0.6 W/kg for 1g evaluations, testing at the other channels was required for such test configurations.
5. TDD LTE was tested per the guidance provided in FCC KDB Publication 941225 D05v02r04. Testing was performed using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using extended cyclic prefix only and special subframe configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.
6. Per KDB Publication 941225 D05Av01r02, SAR for downlink only LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.
7. This device supports Power Class 2 and Power Class 3 operations for LTE Band 41. The highest available duty cycle for Power Class 2 operations is 43.3 % using UL-DL configuration 1. Per FCC Guidance, all SAR tests were performed using Power Class 3. SAR with power class 2 at the available duty factor was additionally performed for the power class 3 configuration with the highest SAR configuration for each exposure conditions. Please see Section 13 for linearity results.
8. For LTE Band 41 PC3 and LTE Band 7, per FCC guidance, SAR was first measured with only a single carrier active in the uplink (carrier aggregation not active). For each exposure condition, the uplink CA scenario with two component carriers was additionally tested for the configuration with the highest SAR when carrier aggregation was not active. The SCC was configured with the closest available contiguous channel. The two component carriers were configured so the resource blocks are physically allocated side by side to achieve the maximum output power.

WLAN Notes:

1. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n/ax) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 7.6.4 for more information.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg for 1g evaluations. See Section 7.6.5 for more information.
3. Per KDB Publication 248227 D01v02r02, SAR for MIMO was evaluated by following the simultaneous SAR provisions from KDB Publication 447498 D01v06 by either evaluating the sum of the 1g SAR values of each antenna transmitting independently or making a SAR measurement with both antennas transmitting simultaneously. Please see Section 11 for complete analysis.
4. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg for 1g evaluations or all test channels were measured.
5. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

Bluetooth Notes

1. Bluetooth SAR was evaluated with a test mode with hopping disabled with DH5 operation. The reported SAR was scaled to the 77.5% transmission duty factor to determine compliance since the duty factor of the device is limited to 77.5% per the manufacturer. See Section 8.6 for the time domain plot and calculation for the duty factor of the device.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 102 of 114

11 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

11.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

11.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g.

Note: ** The SAR distributions for at least one of the antennas are spatially separated from the other antennas per FCC KDB Publication 248227 Section 6.1 procedures. Therefore, the simultaneous transmission were treated independently for this configuration. See Section 11.4 for more information about the Spatial Separation Analysis.

For each position, the highest SAR value across all modes for the applicable cellular band antenna was considered for summation to determine simultaneous SAR test exclusion.

11.3 Body Simultaneous Transmission Analysis

Table 11-1
Cellular Band Antenna C Simultaneous Transmission Scenario with 2.4 GHz WLAN

Simult Tx	Configuration	Cellular Band Ant C SAR (W/kg)	2.4 GHz WLAN Ant A SAR (W/kg)	2.4 GHz WLAN Ant B SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body SAR	Back	1.105	0.063	0.045	1.168	1.150	1.213
	Top	1.120	0.012	0.011	1.132	1.131	1.143
	Bottom	0.027	0.868	0.833	0.895	0.860	0.895*
	Right	0.135	0.001	0.108	0.136	0.243	0.244
	Left	0.036	0.136	0.005	0.172	0.041	0.177

Table 11-2
Cellular Band Antenna D Simultaneous Transmission Scenario with 2.4 GHz WLAN

Simult Tx	Configuration	Cellular Band Ant D SAR (W/kg)	2.4 GHz WLAN Ant A SAR (W/kg)	2.4 GHz WLAN Ant B SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body SAR	Back	1.084	0.063	0.045	1.147	1.129	1.192
	Top	1.026	0.012	0.011	1.038	1.037	1.049
	Bottom	0.028	0.868	0.833	0.896	0.861	0.896*
	Right	0.031	0.001	0.108	0.032	0.139	0.140
	Left	0.189	0.136	0.005	0.325	0.194	0.330

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 103 of 114

Table 11-3
Cellular Band Antenna C Simultaneous Transmission Scenario with 5 GHz WLAN

Simult Tx	Configuration	Cellular Band Ant C SAR (W/kg)	5 GHz WLAN Ant A SAR (W/kg)	5 GHz WLAN Ant B SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body SAR	Back	1.105	0.081	0.068	1.186	1.173	1.254
	Top	1.120	0.038	0.035	1.158	1.155	1.193
	Bottom	0.027	1.065	0.949	1.092	0.976	1.092*
	Right	0.135	0.004	0.126	0.139	0.261	0.265
	Left	0.036	0.124	0.001	0.160	0.037	0.161

Table 11-4
Cellular Band Antenna D Simultaneous Transmission Scenario with 5 GHz WLAN

Simult Tx	Configuration	Cellular Band Ant D SAR (W/kg)	5 GHz WLAN Ant A SAR (W/kg)	5 GHz WLAN Ant B SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body SAR	Back	1.084	0.081	0.068	1.165	1.152	1.233
	Top	1.026	0.038	0.035	1.064	1.061	1.099
	Bottom	0.028	1.065	0.949	1.093	0.977	1.093*
	Right	0.031	0.004	0.126	0.035	0.157	0.161
	Left	0.189	0.124	0.001	0.313	0.190	0.314

Table 11-5
Cellular Band Antenna C Simultaneous Transmission Scenario with Bluetooth

Simult Tx	Configuration	Cellular Band Ant C SAR (W/kg)	Bluetooth Ant A SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body SAR	Back	1.105	0.045	1.150
	Top	1.120	0.004	1.124
	Bottom	0.027	0.901	0.928
	Right	0.135	0.001	0.136
	Left	0.036	0.121	0.157

Table 11-6
Cellular Band Antenna WF5 Simultaneous Transmission Scenario with Bluetooth

Simult Tx	Configuration	Cellular Band Ant D SAR (W/kg)	Bluetooth Ant A SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body SAR	Back	1.084	0.045	1.129
	Top	1.026	0.004	1.030
	Bottom	0.028	0.901	0.929
	Right	0.031	0.001	0.032
	Left	0.189	0.121	0.310

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 104 of 114

Table 11-7

Cellular Band Antenna C Simultaneous Transmission Scenario with Bluetooth and 5 GHz WLAN

Simult Tx	Configuration	Cellular Band Ant C SAR (W/kg)	Bluetooth Ant A at 10 dBm SAR (W/kg)	5 GHz WLAN Ant A SAR (W/kg)	5 GHz WLAN Ant B SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	4	1+2+3	1+2+4	1+2+3+4
Body SAR	Back	1.105	0.045	0.081	0.068	1.231	1.218	1.299
	Top	1.120	0.004	0.038	0.035	1.162	1.159	1.197
	Bottom	0.027	0.238	1.065	0.949	1.330	1.214	1.330*
	Right	0.135	0.001	0.004	0.126	0.140	0.262	0.266
	Left	0.036	0.022	0.124	0.001	0.182	0.059	0.183

Table 11-8

Cellular Band Antenna D Simultaneous Transmission Scenario with Bluetooth and 5 GHz WLAN

Simult Tx	Configuration	Cellular Band Ant D SAR (W/kg)	Bluetooth Ant A at 10 dBm SAR (W/kg)	5 GHz WLAN Ant A SAR (W/kg)	5 GHz WLAN Ant B SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	4	1+2+3	1+2+4	1+2+3+4
Body SAR	Back	1.084	0.045	0.081	0.068	1.210	1.197	1.278
	Top	1.026	0.004	0.038	0.035	1.068	1.065	1.103
	Bottom	0.028	0.238	1.065	0.949	1.331	1.215	1.331*
	Right	0.031	0.001	0.004	0.126	0.036	0.158	0.162
	Left	0.189	0.022	0.124	0.001	0.335	0.212	0.336

FCC ID: BCGA2429	 PCTEST Proud to be part of  LUMENT		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 105 of 114

11.4 Spatial Separation Analysis

Per FCC KDB Publication 248227, antennas may be considered spatially separated when the aggregate SAR from multiple antennas at any location in the combined SAR distribution is either ≤ 1.2 W/kg where at least 90% of the SAR is attributed to a single SAR distribution or ≤ 0.4 W/kg where no more than one SAR distribution is contributing > 0.1 W/kg.

Spatial separation was determined by inspection of the area scan SAR distributions to confirm that at all locations, SAR was < 1.2 W/kg, where at least 90% of the SAR is attributed to a single SAR distribution. See below for illustrations of the spatial separated antennas considered.

11.4.1 Bottom Edge Spatial Separation Analysis




Figure 11-1
Bottom Edge Spatial Separation for Antenna A and Antenna B

11.5 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: BCGA2429	 PCTEST Proud to be part of	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 106 of 114

12 SAR MEASUREMENT VARIABILITY

12.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Table 12-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS														
Band	FREQUENCY		Mode	Service	Data Rate (Mbps)	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.						(W/kg)	(W/kg)		(W/kg)		(W/kg)	
750	707.50	23095	LTE Band 12, 10 MHz Bandwidth, Antenna C	QPSK, 25 RB, 0 RB Offset	N/A	back	0 mm	0.899	0.864	1.04	N/A	N/A	N/A	N/A
835	826.40	4132	UMTS 850, Antenna D	RMC	N/A	back	0 mm	1.050	0.973	1.08	N/A	N/A	N/A	N/A
1750	1770.00	132572	LTE Band 66 (AWS), 20 MHz Bandwidth, Antenna D	QPSK, 50 RB, 0 RB Offset	N/A	back	0 mm	0.905	0.884	1.02	N/A	N/A	N/A	N/A
1900	1907.60	9538	UMTS 1900, Antenna C	RMC	N/A	back	0 mm	0.982	0.973	1.01	N/A	N/A	N/A	N/A
2450	2506.00	39750	LTE Band 41, 20 MHz Bandwidth, Antenna C	QPSK, 50 RB, 0 RB Offset	N/A	back	0 mm	1.060	0.931	1.14	N/A	N/A	N/A	N/A
2600	2549.50	40185	LTE Band 41, 20 MHz Bandwidth, Antenna C	QPSK, 50 RB, 0 RB Offset	N/A	back	0 mm	1.090	0.927	1.18	N/A	N/A	N/A	N/A
5750	5690.00	138	802.11ac, 80 MHz Bandwidth, Antenna A	OFDM	29.3	bottom	0 mm	0.836	0.823	1.02	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body 1.6 W/kg (mW/g) averaged over 1 gram							
Spatial Peak														
Uncontrolled Exposure/General Population														

12.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for 1g for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 107 of 114

13 ADDITIONAL TESTING PER FCC GUIDANCE


13.1 LTE Band 41 Power Class 2 and Power Class 3 Linearity

This device supports Power Class 2 and Power Class 3 operations for LTE Band 41. The highest available duty cycle for Power Class 2 operations is 43.3 % using UL-DL configuration 1. Per May 2017 TCB Workshop Notes based on the device behavior, all SAR tests were performed using Power Class 3. SAR with Power Class 2 at the highest power and available duty factor was additionally performed for the Power Class 3 configuration with the highest SAR for each exposure condition. The linearity between the Power Class 2 and Power Class 3 SAR results and the respective frame averaged powers was calculated to determine that the results were linear. Per May 2017 TCB Workshop, no additional SAR measurements were required since the linearity between power classes was < 10% and all reported SAR values were < 1.4 W/kg for 1g and < 3.5 W/kg for 10g.

LTE Band 41 SAR testing with power class 2 at the highest power and available duty factor was additionally performed for the power class 3 configuration with the highest SAR for each exposure condition.

Table 13-1
LTE Band 41 Body Linearity Data – Antenna C


	LTE Band 41 PC3	LTE Band 41 PC2
Maximum Allowed Output Power (dBm)	15.4	15.4
Measured Output Power (dBm)	15.16	14.79
Measured SAR (W/kg)	1.06	0.658
Measured Power (mW)	32.81	30.13
Duty Cycle	63.3%	43.3%
Frame Averaged Output Power (mW)	20.77	13.05
% deviation from expected linearity		-1.18%



FCC ID: BCGA2429	 PCTEST Proud to be part of the 	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 108 of 114

Table 13-2
LTE Band 41 Body Linearity Data – Antenna D

	LTE Band 41 PC3	LTE Band 41 PC2
Maximum Allowed Output Power (dBm)	15.4	15.4
Measured Output Power (dBm)	14.99	14.97
Measured SAR (W/kg)	0.934	0.621
Measured Power (mW)	31.55	31.41
Duty Cycle	63.3%	43.3%
Frame Averaged Output Power (mW)	19.97	13.60
% deviation from expected linearity		-2.35%



FCC ID: BCGA2429	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 109 of 114

14 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Control Company	4352	Ultra Long Stem Thermometer	8/2/2018	Biennial	8/2/2020	181292054
Control Company	4040	Therm./ Clock/ Humidity Monitor	10/9/2018	Biennial	10/9/2020	181647811
Control Company	4352	Ultra Long Stem Thermometer	8/2/2018	Biennial	8/2/2020	181292061
Insize	1108-150	Digital Caliper	1/17/2020	Biennial	1/17/2022	409193536
Amplifier Research	150A100C	Amplifier	CBT	N/A	CBT	350132
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	343972
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Agilent	85033E	3.5mm Standard Calibration Kit	6/6/2020	Annual	6/6/2021	MY53402352
Agilent	8753E5	S-Parameter Network Analyzer	1/16/2020	Annual	1/16/2021	US39170118
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
Rohde & Schwarz	CMW500	Radio Communication Tester	8/20/2019	Annual	8/20/2020	106578
Rohde & Schwarz	CMW500	Radio Communication Tester	5/13/2020	Annual	5/13/2021	167284
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	8/8/2019	Annual	8/8/2020	145663
SPEAG	D1750V2	1750 MHz SAR Dipole	9/7/2017	Triennial	9/7/2020	1104
SPEAG	D1900V2	1900 MHz SAR Dipole	8/16/2017	Triennial	8/16/2020	5d180
SPEAG	D1900V2	1900 MHz SAR Dipole	5/14/2018	Biennial	5/14/2021	5d026
SPEAG	D2300V2	2300 MHz SAR Dipole	3/7/2018	Biennial	3/7/2021	1038
SPEAG	D2450V2	2450 MHz SAR Dipole	11/12/2018	Biennial	11/12/2020	921
SPEAG	D2600V2	2600 MHz SAR Dipole	9/11/2017	Triennial	9/11/2020	1069
SPEAG	D5GHZV2	5 GHz SAR Dipole	9/13/2018	Biennial	9/13/2020	1163
SPEAG	D750V3	750 MHz SAR Dipole	6/20/2019	Biennial	6/20/2021	1057
SPEAG	D835V2	835 MHz SAR Dipole	5/18/2018	Triennial	5/18/2021	4d180
SPEAG	D835V2	835 MHz SAR Dipole	6/20/2019	Biennial	6/20/2021	4d040
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/12/2019	Annual	8/12/2020	1408
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/13/2019	Annual	11/13/2020	1213
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/15/2020	Annual	4/15/2021	501
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/19/2020	Annual	3/19/2021	604
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/13/2020	Annual	2/13/2021	1403
SPEAG	DAE4	Dasy Data Acquisition Electronics	7/10/2019	Annual	7/10/2020	1402
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/12/2020	Annual	5/12/2021	1070
Agilent	E4438C	ESG Vector Signal Generator	9/30/2019	Annual	9/30/2020	US41460739
SPEAG	EX3DV4	SAR Probe	8/29/2019	Annual	8/29/2020	3949
SPEAG	EX3DV4	SAR Probe	11/21/2019	Annual	11/21/2020	7420
SPEAG	EX3DV4	SAR Probe	7/16/2019	Annual	7/16/2020	7491
SPEAG	EX3DV4	SAR Probe	2/19/2020	Annual	2/19/2021	7427
SPEAG	EX3DV4	SAR Probe	3/20/2020	Annual	3/20/2021	7421
SPEAG	EX3DV4	SAR Probe	4/20/2020	Annual	4/20/2021	7532
Anritsu	MA24106A	USB Power Sensor	2/27/2020	Annual	2/27/2021	1520503
Anritsu	MA24106A	USB Power Sensor	2/27/2020	Annual	2/27/2021	1520501
Anritsu	MA24106A	USB Power Sensor	8/27/2019	Annual	8/27/2020	1827531
Anritsu	MA24106A	USB Power Sensor	8/5/2019	Annual	8/5/2020	1827528
Anritsu	ML2495A	Power Meter	11/15/2019	Annual	11/15/2020	1039008
Anritsu	ML2495A	Power Meter	11/15/2019	Annual	11/15/2020	1039008
Anritsu	ML2496A	Power Meter	12/17/2019	Annual	12/17/2020	1138001
Anritsu	ML2496A	Power Meter	12/17/2019	Annual	12/17/2020	1138001
Anritsu	MT8821C	Radio Communication Analyzer	8/16/2019	Annual	8/16/2020	6201144418
Agilent	N5182A	MXG Vector Signal Generator	8/19/2019	Annual	8/19/2020	MY47420837
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Mini-Circuits	VHF-3100+	High Pass Filter	CBT	N/A	CBT	N/A

Note: All equipment was used strictly during calibration date.

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 110 of 114

15 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)	RSS					11.5	11.3	60
Expanded Uncertainty (95% CONFIDENCE LEVEL)	k=2					23.0	22.6	

FCC ID: BCGA2429	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device		Page 111 of 114

16 CONCLUSION

16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: BCGA2429	 PCTEST Proud to be part of 	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 112 of 114

17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 113 of 114

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: BCGA2429	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N 1C2004270034-01.BCG	Test Dates: 06/07/2020-07/20/2020	DUT Type: Tablet Device	Page 114 of 114