## APPENDIX D: SAR SYSTEM VALIDATION

FCC ID: BCGA2568	element	Approved by: Quality Manager	
Test Dates:	DUT Type:		APPENDIX: D
07/13/2021	Tablet Device		Page 1 of 2

© 2023 REV 21.4 M 09/11/2019

Per FCC KDB Publication 865664 D02v01r02, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

> Table D-1 SAR System Validation Summary - 1g

	or are operations a summary and													
SAR		Freq.	Broho	Probe			Cond.	Perm.	CW VALIDATION			MOD. VALIDATION		
	System	(MHz)	Date	SN	Probe C	al Point	(σ)	em. (εr)	SENSITIVITY	PROBE	PROBE	MOD.	DUTY	PAR
	Оузісні	(1411 12)		5			(0) (21)	SENSITIVITI	LINEARITY	ISOTROPY	TYPE	FACTOR	FAR	
	AM4A	3500	3/4/2021	7427	3500	Body	3.178	49.64	PASS	PASS	PASS	TDD	PASS	N/A
Ì	AM4A	3700	3/4/2021	7427	3700	Body	3.178	49.64	PASS	PASS	PASS	TDD	PASS	N/A

NOTE: Probes have been calibrated for both CW and modulated signals. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01r04 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to FCC KDB Publication 865664 D01v01r04.

FCC ID: BCGA2568	element	SAR EVALUATION REPORT	Approved by: Quality Manager
Test Dates:	DUT Type:		APPENDIX: D
07/13/2021	Tablet Device		Page 2 of 2
© 2023	•		REV 21.4 M