

APPENDIX E: SAR SYSTEM VALIDATION

FCC ID BCGA2898	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX E: Page 1 of 2

Per FCC KDB Publication 865664 D02v01r02, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

**Table E-1
SAR System Validation Summary**

SAR System	Freq. (MHz)	Date	Probe SN	DAE	Probe Cal Point		Cond. (σ)	Perm. (ϵ_r)	CW VALIDATION			MOD. VALIDATION		
									SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
AM14	13	07/27/2023	7360	534	13	Head	0.731	54.392	PASS	PASS	PASS	N/A	N/A	N/A
AM8	2450	03/31/2023	7421	604	2450	Head	1.838	40.418	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
AM9	5250	11/14/2023	3746	1237	5250	Head	4.523	36.656	PASS	PASS	PASS	OFDM	N/A	PASS
AM9	5600	11/15/2023	3746	1237	5600	Head	4.925	36.045	PASS	PASS	PASS	OFDM	N/A	PASS
AM9	5750	11/15/2023	3746	1237	5750	Head	5.104	35.790	PASS	PASS	PASS	OFDM	N/A	PASS
AM11	6500	12/10/2023	7682	1683	6500	Head	5.799	33.842	PASS	PASS	PASS	OFDM	N/A	PASS

NOTE: While the probes have been calibrated for both CW and modulated signals, all measurements were performed using communication systems calibrated for CW signals only. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01r04 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to FCC KDB Publication 865664 D01v01r04

FCC ID BCGA2898	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX E: Page 2 of 2