


Plot 7-152. Radiated Spurious Emissions 1-18GHz Antenna WF7a (HDR4, ePA – 5789MHz)

Mode: HDR4
 Data Rate: 4Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5789MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 11578.00	Average	V	-	-	-79.24	7.44	35.20	53.98	-18.78
* 11578.00	Peak	V	-	-	-67.58	7.44	46.86	73.98	-27.12
17367.00	Peak	V	-	-	-71.72	14.88	50.16	68.20	-18.04

Table 7-32. Radiated Spurious Emissions Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 121 of 151




Plot 7-153. Radiated Spurious Emissions 1-18GHz Antenna WF7a (HDR4, ePA – 5844MHz)

Mode: HDR4
 Data Rate: 4Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5844MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 11688.00	Average	V	-	-	-79.66	7.86	35.20	53.98	-18.78
* 11688.00	Peak	V	-	-	-68.46	7.86	46.40	73.98	-27.58
17532.00	Peak	V	-	-	-72.08	15.50	50.42	68.20	-17.78

Table 7-33. Radiated Spurious Emissions Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 122 of 151




Plot 7-154. Radiated Spurious Emissions 1-18GHz TxBF (HDR4, ePA – 5162MHz)

Mode: HDR4
 Data Rate: 4Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5162MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
10324.00	Peak	V	-	-	-67.15	5.91	45.76	68.20	-22.44
* 15486.00	Average	V	-	-	-81.91	12.24	37.33	53.98	-16.65
* 15486.00	Peak	V	-	-	-70.36	12.24	48.88	73.98	-25.10

Table 7-34. Radiated Spurious Emissions Measurements TxBF

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 123 of 151




Plot 7-155. Radiated Spurious Emissions 1-18GHz TxBF (HDR4, ePA – 5204MHz)

Mode: HDR4
 Data Rate: 4Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5204MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10408.00	Peak	V	-	-	-67.90	6.27	45.37	68.20	-22.83
* 15612.00	Average	V	-	-	-81.70	12.66	37.96	53.98	-16.02
* 15612.00	Peak	V	-	-	-70.28	12.66	49.38	73.98	-24.60


Table 7-35. Radiated Spurious Emissions Measurements TxBF

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 124 of 151



Plot 7-156. Radiated Spurious Emissions Above 18GHz TxBF (HDR4, ePA – 5204MHz)

FCC ID: BCGA2902 IC: 579C-A2902	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 125 of 151




Plot 7-157. Radiated Spurious Emissions 1-18GHz TxBF (HDR4, ePA – 5245MHz)

Mode: HDR4
 Data Rate: 4Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5245MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
10490.00	Peak	V	-	-	-68.07	6.51	45.44	68.20	-22.76
* 15735.00	Average	V	-	-	-82.06	13.10	38.04	53.98	-15.94
* 15735.00	Peak	V	-	-	-70.93	13.10	49.17	73.98	-24.81

Table 7-36. Radiated Spurious Emissions Measurements TxBF

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 126 of 151




Plot 7-158. Radiated Spurious Emissions 1-18GHz TxBF (HDR4, ePA – 5733MHz)

Mode: HDR4
 Data Rate: 4Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5733MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
* 11466.00	Average	V	-	-	-79.72	7.47	34.75	53.98	-19.23
* 11466.00	Peak	V	-	-	-68.44	7.47	46.03	73.98	-27.95
17199.00	Peak	V	-	-	-71.66	14.96	50.30	68.20	-17.90

Table 7-37. Radiated Spurious Emissions Measurements TxBF

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 127 of 151




Plot 7-159. Radiated Spurious Emissions 1-18GHz TxBF (HDR4 – 5789MHz)

Mode: HDR4
 Data Rate: 4Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5789MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 11578.00	Average	V	-	-	-79.30	7.44	35.14	53.98	-18.84
* 11578.00	Peak	V	-	-	-67.90	7.44	46.54	73.98	-27.44
17367.00	Peak	V	-	-	-71.71	14.88	50.17	68.20	-18.03


Table 7-38. Radiated Spurious Emissions Measurements TxBF

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 128 of 151



Plot 7-160. Radiated Spurious Emissions Above 18GHz TxBF (HDR4, ePA - 5789MHz)

FCC ID: BCGA2902 IC: 579C-A2902	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 129 of 151



Plot 7-161. Radiated Spurious Emissions 1-18GHz TxBF (HDR4, ePA – 5844MHz)

Mode: HDR4
 Data Rate: 4Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5844MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 11688.00	Average	V	-	-	-79.70	7.86	35.16	53.98	-18.82
* 11688.00	Peak	V	-	-	-68.48	7.86	46.38	73.98	-27.60
17532.00	Peak	V	-	-	-72.39	15.50	50.11	68.20	-18.09

Table 7-39. Radiated Spurious Emissions Measurements TxBF


FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 130 of 151

7.6.2 Radiated Band Edge Measurements

§15.407(b.1) §15.205 §15.209; RSS-Gen [8.9]


Antenna WF8

Mode: HDR4
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5162MHz



Plot 7-162. Radiated Lower Band Edge Measurement Antenna WF8


Mode: HDR8
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5162MHz



Plot 7-163. Radiated Lower Band Edge Measurement Antenna WF8


FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 131 of 151

Mode: HDR4
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5733MHz



Plot 7-164. Radiated Lower Band Edge Measurement Antenna WF8


Mode: HDR8
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5733MHz



Plot 7-165. Radiated Lower Band Edge Measurement Antenna WF8


FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 132 of 151

Mode: HDR4
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5844MHz



Plot 7-166. Radiated Upper Band Edge Measurement Antenna WF8

Mode: HDR8
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5844MHz




Plot 7-167. Radiated Upper Band Edge Measurement Antenna WF8

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 133 of 151


Antenna WF7a

Mode: HDR4
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5162MHz



Plot 7-168. Radiated Lower Band Edge Measurement Antenna WF7a


Mode: HDR8
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5162MHz



Plot 7-169. Radiated Lower Band Edge Measurement Antenna WF7a


FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 134 of 151

Mode: HDR4
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5733MHz



Plot 7-170. Radiated Lower Band Edge Measurement Antenna WF7a


Mode: HDR8
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5733MHz



Plot 7-171. Radiated Lower Band Edge Measurement Antenna WF7a


FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 135 of 151

Mode: HDR4
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5844MHz



Plot 7-172. Radiated Upper Band Edge Measurement Antenna WF7a

Mode: HDR8
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5844MHz




Plot 7-173. Radiated Upper Band Edge Measurement Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 136 of 151


TxBF

Mode: HDR4
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5162MHz



Plot 7-174. Radiated Lower Band Edge Measurement TxBF


Mode: HDR8
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5162MHz



Plot 7-175. Radiated Lower Band Edge Measurement TxBF


FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 137 of 151

Mode: HDR4
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5733MHz



Plot 7-176. Radiated Lower Band Edge Measurement TxBF


Mode: HDR8
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5733MHz



Plot 7-177. Radiated Lower Band Edge Measurement TxBF


FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 138 of 151

Mode: HDR4
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5844MHz



Plot 7-178. Radiated Upper Band Edge Measurement TxBF

Mode: HDR8
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5844MHz



Plot 7-179. Radiated Upper Band Edge Measurement TxBF

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 139 of 151

7.7 Radiated Spurious Emissions – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-40 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-40. Radiated Limits

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 140 of 151

V 10.5 12/15/2021

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-6. Radiated Test Setup < 30MHz




Figure 7-7. Radiated Test Setup < 1GHz

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 141 of 151

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen(8.10) are below the limit shown in Table 7-40.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes. For below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector for emissions within 6dB of the limit.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. All supported modulation and power schemes have been tested on the unit and only worst case configuration is reported.
10. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor to USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger

Sample Calculations


Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]} - \text{Preamplifier Gain }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 142 of 151

TxBF Radiated Spurious Emissions (Below 1GHz)

§15.209; RSS-Gen [8.9]




Plot 7-180. Radiated Spurious Emissions Below 1GHz TxBF (HDR4, ePA – 5204MHz), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
36.31	Max-Peak	V	100	196	-67.33	-15.40	24.27	40.00	-15.73
50.86	Max-Peak	V	100	43	-69.00	-13.12	24.88	40.00	-15.12
152.22	Max-Peak	H	100	232	-68.85	-20.10	18.05	43.52	-25.47
190.49	Max-Peak	H	100	219	-62.23	-17.43	27.34	43.52	-16.18
297.48	Max-Peak	H	100	0	-69.24	-14.54	23.22	46.02	-22.80
931.95	Max-Peak	V	300	206	-79.83	-2.73	24.44	46.02	-21.58

Table 7-41. Radiated Spurious Emissions Below 1GHz TxBF (HDR4, ePA – 5204MHz), with AC/DC Adapter

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 143 of 151



Plot 7-181 Radiated Spurious Emissions Below 1GHz TxBF (HDR4, ePA – 5789MHz), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
37.61	Max-Peak	V	100	296	-67.05	-15.09	24.86	40.00	-15.14
51.83	Max-Peak	V	100	12	-69.02	-13.13	24.85	40.00	-15.15
145.96	Max-Peak	V	100	173	-69.74	-20.54	16.72	43.52	-26.80
194.37	Max-Peak	H	200	244	-65.30	-16.85	24.85	43.52	-18.67
341.03	Max-Peak	H	100	27	-72.92	-12.98	21.10	46.02	-24.92
855.81	Max-Peak	H	300	324	-79.27	-3.55	24.18	46.02	-21.84

Table 7-42. Radiated Spurious Emissions Below 1GHz TxBF (HDR4, ePA – 5789MHz), with AC/DC Adapter

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 144 of 151

7.8 AC Line Conducted Emissions Measurement

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted spurious emissions. All data rates and modes were investigated for AC Line conducted spurious emissions.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-43. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Subclause 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 145 of 151

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-8. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
2. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor to USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger
3. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207.
4. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
5. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Correction Factor (dB)}$
6. $\text{Margin (dB)} = \text{QP/AV Level (dB}\mu\text{V)} - \text{QP/AV Limit (dB}\mu\text{V)}$
7. Traces shown in plots are made using quasi-peak and average detectors.
8. Deviations to the Specifications: None.

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 146 of 151

V 10.5 12/15/2021




Plot 7-182. AC Line Conducted Plot TxBF (HDR4, ePA – 5204MHz) (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.159	FINAL	—	38.84	55.52	-16.68	L1	GND
0.159	FINAL	54.9	—	65.52	-10.58	L1	GND
0.233	FINAL	—	30.83	52.33	-21.51	L1	GND
0.233	FINAL	48.3	—	62.33	-14.05	L1	GND
1.320	FINAL	—	16.03	46.00	-29.97	L1	GND
1.320	FINAL	31.0	—	56.00	-25.03	L1	GND
4.488	FINAL	32.4	—	56.00	-23.56	L1	GND
4.488	FINAL	—	19.38	46.00	-26.62	L1	GND
16.409	FINAL	16.8	—	60.00	-43.17	L1	GND
16.409	FINAL	—	12.11	50.00	-37.89	L1	GND
29.967	FINAL	—	9.12	50.00	-40.88	L1	GND
29.967	FINAL	15.2	—	60.00	-44.78	L1	GND

Table 7-44. AC Line Conducted TxBF (HDR4, ePA – 5204MHz) (L1) with AC/DC Adapter

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 147 of 151




Plot 7-183. AC Line Conducted Plot TxBF (HDR4, ePA – 5204MHz) (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.157	FINAL	—	34.24	55.63	-21.40	N	GND
0.157	FINAL	50.7	—	65.63	-14.90	N	GND
0.231	FINAL	—	26.64	52.41	-25.78	N	GND
0.231	FINAL	44.3	—	62.41	-18.14	N	GND
1.257	FINAL	—	15.49	46.00	-30.51	N	GND
1.257	FINAL	30.1	—	56.00	-25.91	N	GND
4.490	FINAL	31.7	—	56.00	-24.33	N	GND
4.493	FINAL	—	17.80	46.00	-28.20	N	GND
16.413	FINAL	14.5	—	60.00	-45.46	N	GND
16.413	FINAL	—	9.12	50.00	-40.88	N	GND
29.965	FINAL	—	5.18	50.00	-44.82	N	GND
29.965	FINAL	11.5	—	60.00	-48.53	N	GND

Table 7-45. AC Line Conducted TxBF (HDR4, ePA – 5204MHz) (N) with AC/DC Adapter

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 148 of 151




Plot 7-184. AC Line Conducted Plot TxBF (HDR4, ePA – 5789MHz) (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.152	FINAL	—	33.30	55.88	-22.58	L1	GND
0.152	FINAL	50.0	—	65.88	-15.93	L1	GND
0.229	FINAL	—	28.90	52.50	-23.59	L1	GND
0.229	FINAL	45.8	—	62.50	-16.74	L1	GND
0.663	FINAL	—	21.72	46.00	-24.28	L1	GND
0.663	FINAL	38.6	—	56.00	-17.40	L1	GND
2.434	FINAL	25.7	—	56.00	-30.34	L1	GND
2.434	FINAL	—	13.84	46.00	-32.16	L1	GND
4.747	FINAL	35.2	—	56.00	-20.84	L1	GND
4.747	FINAL	—	23.04	46.00	-22.96	L1	GND
29.243	FINAL	—	7.25	50.00	-42.75	L1	GND
29.243	FINAL	13.4	—	60.00	-46.60	L1	GND

Table 7-46. AC Line Conducted TxBF (HDR4, ePA – 5789MHz) (L1) with AC/DC Adapter

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 149 of 151



Plot 7-185. AC Line Conducted Plot TxBF (HDR4, ePA – 5789MHz) (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.152	FINAL	—	28.42	55.88	-27.45	N	GND
0.152	FINAL	45.9	—	65.88	-19.97	N	GND
0.211	FINAL	—	25.58	53.18	-27.60	N	GND
0.211	FINAL	43.5	—	63.18	-19.68	N	GND
0.330	FINAL	—	18.99	49.45	-30.47	N	GND
0.330	FINAL	37.2	—	59.45	-22.26	N	GND
2.164	FINAL	19.0	—	56.00	-36.96	N	GND
2.164	FINAL	—	11.01	46.00	-34.99	N	GND
5.080	FINAL	27.4	—	60.00	-32.58	N	GND
5.080	FINAL	—	17.51	50.00	-32.49	N	GND
17.693	FINAL	—	4.79	50.00	-45.21	N	GND
17.693	FINAL	10.6	—	60.00	-49.38	N	GND

Table 7-47. AC Line Conducted TxBF (HDR4, ePA – 5789MHz) (N) with AC/DC Adapter

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 150 of 151

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Tablet Device FCC ID: BCGA2902** and **IC: 579C-A2902** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCGA2902 IC: 579C-A2902	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2311270063-09.BCG	Test Dates: 11/29/2023 - 3/5/2024	EUT Type: Tablet Device	Page 151 of 151

V 10.5 12/15/2021