



Plot 7-577. Radiated Spurious Emissions above 1GHz Antenna WF8 (802.11ax(SU) - Ch. 40)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5200MHz
Channel:	40

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10400.00	Peak	Н	-	-	-69.14	9.98	47.84	68.20	-20.36
*	15600.00	Average	н	-	-	-81.13	15.64	41.51	53.98	-12.47
*	15600.00	Peak	Н	-	-	-70.13	15.64	52.51	73.98	-21.47

Table 7-157. Radiated Measurements Antenna WF8

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dago 202 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 202 01 307
			V 10.5 12/15/2021







Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5240MHz
Channel:	48

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10480.00	Peak	Н	-	-	-69.56	10.26	47.70	68.20	-20.50
*	15720.00	Average	Н	-	-	-80.98	15.00	41.02	53.98	-12.96
*	15720.00	Peak	Н	-	-	-70.38	15.00	51.62	73.98	-22.36

Table 7-158. Radiated Measurements Antenna WF8

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 202 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 203 01 307
			V 10.5 12/15/2021





Plot 7-579. Radiated Spurious Emissions above 1GHz Antenna WF8 (802.11ax(SU) - Ch. 52)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5260MHz
Channel:	52

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10520.00	Peak	Н	-	-	-69.52	10.50	47.98	68.20	-20.22
*	15780.00	Average	Н	-	-	-77.95	14.71	43.76	53.98	-10.21
*	15780.00	Peak	Н	-	-	-67.12	14.71	54.59	73.98	-19.38

Table 7-159. Radiated Measurements Antenna WF8

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 204 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 204 01 387
			V 10.5 12/15/2021







Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5280MHz
Channel:	56

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10560.00	Peak	Н	-	-	-69.00	10.03	48.03	68.20	-20.17
*	15840.00	Average	Н	-	-	-78.36	14.88	43.52	53.98	-10.46
*	15840.00	Peak	Н	-	-	-68.21	14.88	53.67	73.98	-20.31

Table 7-160. Radiated Measurements Antenna WF8

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 205 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 205 01 387
			V 10.5 12/15/2021





Plot 7-581. Radiated Spurious Emissions above 1GHz Antenna WF8 (802.11ax(SU) - Ch. 64)

Mode:	802.11ax(SU)		
Data Rate:	MCS0		
Distance of Measurements:	3 Meters		
Operating Frequency:	5320MHz		
Channel:	64		

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	10640.00	Average	Н	-	-	-79.64	10.23	37.59	53.98	-16.39
*	10640.00	Peak	Н	-	-	-68.29	10.23	48.94	73.98	-25.04
*	15960.00	Average	Н	-	-	-78.25	15.20	43.95	53.98	-10.03
*	15960.00	Peak	Н	-	-	-67.55	15.20	54.65	73.98	-19.33

 Table 7-161. Radiated Measurements Antenna WF8

FCC ID: BCGA2902 IC: 579C-A2902	element 🕞	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dage 200 of 207	
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 206 of 387	
			V/ 10 5 12/15/2021	





Plot 7-582. Radiated Spurious Emissions above 1GHz Antenna WF8 (802.11ax(SU) - Ch. 100)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5500MHz
Channel:	100

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11000.00	Average	Н	-	-	-80.03	10.92	37.89	53.98	-16.09
*	11000.00	Peak	Н	-	-	-69.73	10.92	48.19	73.98	-25.79
	16500.00	Peak	Н	-	-	-71.38	17.71	53.33	68.20	-14.87

Table 7-162. Radiated Measurements Antenna WF8

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 207 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 207 01 307
			V 10.5 12/15/2021





Plot 7-583. Radiated Spurious Emissions above 1GHz Antenna WF8 (802.11ax(SU) - Ch. 116)

Mode:	802.11ax(SU)		
Data Rate:	MCS0		
Distance of Measurements:	3 Meters		
Operating Frequency:	5580MHz		
Channel:	116		

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11160.00	Average	Н	-	-	-79.38	10.30	37.92	53.98	-16.06
*	11160.00	Peak	Н	-	-	-69.20	10.30	48.10	73.98	-25.88
	16740.00	Peak	Н	-	-	-69.75	17.30	54.55	68.20	-13.65

Table 7-163. Radiated Measurements Antenna WF8

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 200 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 208 01 387
			V 10.5 12/15/2021





Plot 7-584. Radiated Spurious Emissions above 1GHz Antenna WF8 (802.11ax(SU) - Ch. 144)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5720MHz
Channel:	144

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11440.00	Average	Н	-	-	-79.61	10.73	38.12	53.98	-15.86
*	11440.00	Peak	Н	-	-	-69.88	10.73	47.85	73.98	-26.13
	17160.00	Peak	Н	-	-	-70.33	18.32	54.99	68.20	-13.21

Table 7-164. Radiated Measurements Antenna WF8

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dago 200 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 209 01 367
			V 10.5 12/15/2021





Plot 7-585. Radiated Spurious Emissions above 1GHz Antenna WF8 (802.11ax(SU) - Ch. 149)

Mode:	802.11ax(SU)		
Data Rate:	MCS0		
Distance of Measurements:	3 Meters		
Operating Frequency:	5745MHz		
Channel:	149		

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11490.00	Average	Н	-	-	-80.29	10.78	37.49	53.98	-16.49
*	11490.00	Peak	Н	-	-	-69.76	10.78	48.02	73.98	-25.96
	17235.00	Peak	Н	-	-	-70.63	18.10	54.47	68.20	-13.73

Table 7-165. Radiated Measurements Antenna WF8

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dogo 210 of 297	
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 210 01 387	
			V 10.5 12/15/2021	





Plot 7-586. Radiated Spurious Emissions above 1GHz Antenna WF8 (802.11ax(SU) - Ch. 157)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5785MHz
Channel:	157

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11570.00	Average	Н	-	-	-80.04	10.96	37.92	53.98	-16.06
*	11570.00	Peak	Н	-	-	-69.86	10.96	48.10	73.98	-25.88
	17355.00	Peak	Н	-	-	-71.26	18.81	54.55	68.20	-13.65

Table 7-166. Radiated Measurements Antenna WF8

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 011 of 007
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 211 01 387
			V 10.5 12/15/2021





Plot 7-587. Radiated Spurious Emissions above 1GHz Antenna WF8 (802.11ax(SU) - Ch. 165)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5825MHz
Channel:	165

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11650.00	Average	Н	-	-	-79.96	11.08	38.12	53.98	-15.86
*	11650.00	Peak	Н	-	-	-70.23	11.08	47.85	73.98	-26.13
	17475.00	Peak	Н	-	-	-73.10	21.09	54.99	68.20	-13.21

Table 7-167. Radiated Measurements Antenna WF8

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 010 of 007
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 212 01 387
			V 10.5 12/15/2021





7.6.2 Antenna WF7a Radiated Spurious Emission



Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10360.00	Peak	Н	-	-	-68.97	10.20	48.23	68.20	-19.97
*	15540.00	Average	н	-	-	-84.17	16.09	38.92	53.98	-15.06
*	15540.00	Peak	н	-	-	-70.30	16.09	52.79	73.98	-21.19

Table 7-168. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 012 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 213 01 307
			V 10.5 12/15/2021





Plot 7-589. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11n - Ch. 40)

Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5200MHz
Channel:	40

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10400.00	Peak	Н	-	-	-68.09	9.98	48.89	68.20	-19.31
*	15600.00	Average	Н	-	-	-84.55	15.64	38.09	53.98	-15.89
*	15600.00	Peak	Н	-	-	-70.69	15.64	51.95	73.98	-22.03

Table 7-169. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 214 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Faye 214 01 307
			V 10.5 12/15/2021





Plot 7-590. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11n - Ch. 48)

802.11n
MCS0
3 Meters
5240MHz
48

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10480.00	Peak	Н	-	-	-69.29	10.26	47.97	68.20	-20.23
*	15720.00	Average	Н	-	-	-80.43	15.00	41.57	53.98	-12.41
*	15720.00	Peak	Н	-	-	-70.20	15.00	51.80	73.98	-22.18

Table 7-170. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 215 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 215 01 567
			V 10.5 12/15/2021





Plot 7-591. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11n - Ch. 52)

Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5260MHz
Channel:	52

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10520.00	Peak	Н	-	-	-69.96	10.50	47.54	68.20	-20.66
*	15780.00	Average	Н	-	-	-83.59	14.71	38.12	53.98	-15.86
*	15780.00	Peak	Н	-	-	-69.58	14.71	52.13	73.98	-21.85

Table 7-171. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 216 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Faye 210 01 307
			V 10.5 12/15/2021





Plot 7-592. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11n - Ch. 56)

Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5280MHz
Channel:	56

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10560.00	Peak	Н	-	-	-69.00	10.03	48.03	68.20	-20.17
*	15840.00	Average	Н	-	-	-81.34	14.88	40.54	53.98	-13.44
*	15840.00	Peak	Н	-	-	-70.37	14.88	51.51	73.98	-22.47

Table 7-172. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 217 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 217 01 307
			V 10.5 12/15/2021





Plot 7-593. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11n - Ch. 64)

Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5320MHz
Channel:	64

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	10640.00	Average	Н	-	-	-79.78	10.23	37.45	53.98	-16.53
*	10640.00	Peak	Н	-	-	-69.03	10.23	48.20	73.98	-25.78
*	15960.00	Average	Н	-	-	-81.02	15.20	41.18	53.98	-12.80
*	15960.00	Peak	Н	-	-	-70.28	15.20	51.92	73.98	-22.06

 Table 7-173. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 219 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 210 01 307
			V 10.5 12/15/2021





Plot 7-594. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11n - Ch. 100)

Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5500MHz
Channel:	100

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11000.00	Average	Н	-	-	-81.03	10.92	36.89	53.98	-17.09
*	11000.00	Peak	Н	-	-	-70.28	10.92	47.64	73.98	-26.34
	16500.00	Peak	Н	-	-	-70.70	17.71	54.01	68.20	-14.19

Table 7-174. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 210 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Faye 219 01 307
			V 10.5 12/15/2021





Plot 7-595. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11n - Ch. 116)

Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5580MHz
Channel:	116

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11160.00	Average	Н	-	-	-79.34	10.30	37.96	53.98	-16.02
*	11160.00	Peak	Н	-	-	-69.97	10.30	47.33	73.98	-26.65
	16740.00	Peak	Н	-	-	-68.44	17.30	55.86	68.20	-12.34

 Table 7-175. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 220 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 220 01 387
			V 10.5 12/15/2021





Plot 7-596. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11n - Ch. 144)

802.11n
MCS0
3 Meters
5720MHz
144

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11440.00	Average	Н	-	-	-79.18	10.73	38.55	53.98	-15.43
*	11440.00	Peak	Н	-	-	-70.01	10.73	47.72	73.98	-26.26
	17160.00	Peak	Н	-	-	-71.20	18.32	54.12	68.20	-14.08

Table 7-176. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 221 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 221 01 307
			V 10.5 12/15/2021





Plot 7-597. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11n - Ch. 149)

Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5745MHz
Channel:	149

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11490.00	Average	Н	-	-	-80.73	10.78	37.05	53.98	-16.93
*	11490.00	Peak	Н	-	-	-70.14	10.78	47.64	73.98	-26.34
	17235.00	Peak	Н	-	-	-71.09	18.10	54.01	68.20	-14.19

Table 7-177. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 222 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Paye 222 01 307
			V 10.5 12/15/2021





Plot 7-598. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11n - Ch. 157)

Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5785MHz
Channel:	157

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11570.00	Average	Н	-	-	-80.51	10.96	37.45	53.98	-16.53
*	11570.00	Peak	Н	-	-	-70.63	10.96	47.33	73.98	-26.65
	17355.00	Peak	Н	-	-	-69.95	18.81	55.86	68.20	-12.34

 Table 7-178. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 222 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 223 01 387
			V 10.5 12/15/2021





Plot 7-599. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11n - Ch. 165)

11n
50
eters
5MHz

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11650.00	Average	Н	-	-	-80.50	11.08	37.58	53.98	-16.40
*	11650.00	Peak	Н	-	-	-70.36	11.08	47.72	73.98	-26.26
	17475.00	Peak	Н	-	-	-73.97	21.09	54.12	68.20	-14.08

Table 7-179. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 224 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 224 01 387
			V 10.5 12/15/2021





Plot 7-600. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11ax(SU) - Ch. 36)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10360.00	Peak	Н	-	-	-69.50	10.20	47.70	68.20	-20.50
*	15540.00	Average	Н	-	-	-80.91	16.09	42.18	53.98	-11.80
*	15540.00	Peak	Н	-	-	-70.35	16.09	52.74	73.98	-21.24

 Table 7-180. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 205 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 225 01 567
			V 10.5 12/15/2021





Plot 7-601. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11ax(SU) - Ch. 40)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5200MHz
Channel:	40

Unanner.										
	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10400.00	Peak	н	-	-	-69.11	9.98	47.87	68.20	-20.33
*	15600.00	Average	Н	-	-	-80.46	15.64	42.18	53.98	-11.80
*	15600.00	Peak	н	-	-	-70.72	15.64	51.92	73.98	-22.06

Table 7-181. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 226 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Faye 220 01 307
			V 10.5 12/15/2021





Plot 7-602. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11ax(SU) - Ch. 48)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5240MHz
Channel:	48

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10480.00	Peak	Н	-	-	-69.99	10.26	47.27	68.20	-20.93
*	15720.00	Average	Н	-	-	-80.59	15.00	41.41	53.98	-12.57
*	15720.00	Peak	н	-	-	-70.01	15.00	51.99	73.98	-21.99

Table 7-182. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 227 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 227 01 387
			V 10.5 12/15/2021





Plot 7-603. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11ax(SU) - Ch. 52)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5260MHz
Channel:	52

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10520.00	Peak	Н	-	-	-69.69	10.50	47.81	68.20	-20.39
*	15780.00	Average	Н	-	-	-81.32	14.71	40.39	53.98	-13.59
*	15780.00	Peak	Н	-	-	-69.69	14.71	52.02	73.98	-21.96

Table 7-183. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dogo 229 of 297	
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 228 01 387	
			V 10.5 12/15/2021	





Plot 7-604. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11ax(SU) - Ch. 56)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5280MHz
Channel:	56

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10560.00	Peak	Н	-	-	-69.00	10.03	48.03	68.20	-20.17
*	15840.00	Average	Н	-	-	-81.03	14.88	40.85	53.98	-13.13
*	15840.00	Peak	Н	-	-	-70.71	14.88	51.17	73.98	-22.81

Table 7-184. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 220 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 229 01 387
			V 10.5 12/15/2021





Plot 7-605. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11ax(SU) - Ch. 64)

Mode:	802.11ax(SU)		
Data Rate:	MCS0		
Distance of Measurements:	3 Meters		
Operating Frequency:	5320MHz		
Channel:	64		

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	10640.00	Average	Н	-	-	-79.64	10.23	37.59	53.98	-16.39
*	10640.00	Peak	Н	-	-	-68.29	10.23	48.94	73.98	-25.04
*	15960.00	Average	Н	-	-	-81.02	15.20	41.18	53.98	-12.80
*	15960.00	Peak	Н	-	-	-70.95	15.20	51.25	73.98	-22.73

 Table 7-185. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 220 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 230 01 367
			V 10.5 12/15/2021





Plot 7-606. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11ax(SU) - Ch. 100)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5500MHz
Channel:	100

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11000.00	Average	Н	-	-	-80.76	10.92	37.16	53.98	-16.82
*	11000.00	Peak	Н	-	-	-70.01	10.92	47.91	73.98	-26.07
	16500.00	Peak	Н	-	-	-70.52	17.71	54.19	68.20	-14.01

Table 7-186. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 221 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 231 01 307
			V 10.5 12/15/2021





Plot 7-607. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11ax(SU) - Ch. 116)

Mode:	802.11ax(SU)		
Data Rate:	MCS0		
Distance of Measurements:	3 Meters		
Operating Frequency:	5580MHz		
Channel:	116		

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11160.00	Average	Н	-	-	-80.49	10.30	36.81	53.98	-17.17
*	11160.00	Peak	Н	-	-	-69.72	10.30	47.58	73.98	-26.40
	16740.00	Peak	Н	-	-	-69.85	17.30	54.45	68.20	-13.75

 Table 7-187. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 222 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 232 01 387
			V 10.5 12/15/2021





Plot 7-608. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11ax(SU) - Ch. 144)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5720MHz
Channel:	144

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11440.00	Average	Н	-	-	-80.62	10.73	37.11	53.98	-16.87
*	11440.00	Peak	Н	-	-	-69.66	10.73	48.07	73.98	-25.91
	17160.00	Peak	Н	-	-	-71.12	18.32	54.20	68.20	-14.00

Table 7-188. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 222 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	raye 200 01 307
			V 10.5 12/15/2021





Plot 7-609. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11ax(SU) - Ch. 149)

Mode:	802.11ax(SU)		
Data Rate:	MCS0		
Distance of Measurements:	3 Meters		
Operating Frequency:	5745MHz		
Channel:	149		

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11490.00	Average	Н	-	-	-80.40	10.78	37.38	53.98	-16.60
*	11490.00	Peak	Н	-	-	-70.34	10.78	47.44	73.98	-26.54
	17235.00	Peak	Н	-	-	-70.67	18.10	54.43	68.20	-13.77

Table 7-189. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 224 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 234 01 307
			V 10.5 12/15/2021





Plot 7-610. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11ax(SU) - Ch. 157)

Mode:	802.11ax(SU)		
Data Rate:	MCS0		
Distance of Measurements:	3 Meters		
Operating Frequency:	5785MHz		
Channel:	157		

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11570.00	Average	Н	-	-	-80.41	10.96	37.55	53.98	-16.43
*	11570.00	Peak	Н	-	-	-70.31	10.96	47.65	73.98	-26.33
	17355.00	Peak	Н	-	-	-69.96	18.81	55.85	68.20	-12.35

 Table 7-190. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 225 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 235 01 387
			V 10.5 12/15/2021





Plot 7-611. Radiated Spurious Emissions above 1GHz Antenna WF7a (802.11ax(SU) - Ch. 165)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5825MHz
Channel:	165

	One			10	0						
	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]	
*	11650.00	Average	Н	-	-	-79.97	11.08	38.11	53.98	-15.87	
*	11650.00	Peak	Н	-	-	-70.14	11.08	47.94	73.98	-26.04	
	17475.00	Peak	Н	-	-	-71.48	21.09	56.61	68.20	-11.59	

Table 7-191. Radiated Measurements Antenna WF7a

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dogo 226 of 297	
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 230 01 387	
			V 10.5 12/15/2021	



7.6.3 CDD/SDM Radiated Spurious Emission





Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10360.00	Peak	Н	-	-	-69.27	10.20	47.93	68.20	-20.27
*	15540.00	Average	н	-	-	-80.97	16.09	42.12	53.98	-11.86
*	15540.00	Peak	н	-	-	-70.14	16.09	52.95	73.98	-21.03

Table 7-192. Radiated Measurements CDD

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dage 007 of 007	
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 237 of 387	
			V/ 10 5 12/15/2021	









Plot 7-614. Radiated Spurious Emissions 18GHz - 40GHz CDD (802.11n - Ch. 40)

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 220 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 238 01 387
			V 10.5 12/15/2021



Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5200MHz
Channel:	40

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10400.00	Peak	Н	-	-	-69.47	9.98	47.51	68.20	-20.69
*	15600.00	Average	Н	-	-	-80.54	15.64	42.10	53.98	-11.88
*	15600.00	Peak	Н	-	-	-70.09	15.64	52.55	73.98	-21.43

Table 7-193. Radiated Measurements CDD

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 220 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 239 01 367
			V/ 40 E 40/4E/0004







02.11n
ICS0
Meters
240MHz
8

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10480.00	Peak	Н	-	-	-69.70	10.26	47.56	68.20	-20.64
*	15720.00	Average	Н	-	-	-80.53	15.00	41.47	53.98	-12.51
k	15720.00	Peak	н	-	-	-70.27	15.00	51.73	73.98	-22.25

Table 7-194. Radiated Measurements CDD

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 240 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Faye 240 01 307
			V 10.5 12/15/2021







Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5260MHz
Channel:	52

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10520.00	Peak	Н	-	-	-69.54	10.50	47.96	68.20	-20.24
*	15780.00	Average	Н	-	-	-81.05	14.71	40.66	53.98	-13.32
*	15780.00	Peak	Н	-	-	-70.58	14.71	51.13	73.98	-22.85

Table 7-195. Radiated Measurements CDD

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 241 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 241 01 307
			V 10.5 12/15/2021









Plot 7-618. Radiated Spurious Emissions 18GHz – 40GHz CDD (802.11n – Ch. 56)

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 242 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Faye 242 01 307
			V/ 10 5 12/15/2021



Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5280MHz
Channel:	56

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10560.00	Peak	Н	-	-	-69.21	10.03	47.82	68.20	-20.38
*	15840.00	Average	Н	-	-	-81.00	14.88	40.88	53.98	-13.10
*	15840.00	Peak	Н	-	-	-70.58	14.88	51.30	73.98	-22.68

Table 7-196. Radiated Measurements CDD

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dogo 242 of 297	
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 243 01 387	
			V/ 40 E 40/4E/2024	





Plot 7-619. Radiated Spurious Emissions above 1GHz CDD (802.11n - Ch. 64)

802.11n		
MCS0		
3 Meters		
5320MHz		
64		

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	10640.00	Average	Н	-	-	-79.92	10.23	37.31	53.98	-16.67
*	10640.00	Peak	Н	-	-	-68.82	10.23	48.41	73.98	-25.57
*	15960.00	Average	Н	-	-	-80.98	15.20	41.22	53.98	-12.76
*	15960.00	Peak	Н	-	-	-71.03	15.20	51.17	73.98	-22.81

Table 7-197. Radiated Measurements CDD

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dogo 244 of 297	
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Page 244 01 387	
			V 10.5 12/15/2021	







Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5500MHz
Channel:	100

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11000.00	Average	Н	-	-	-80.61	10.92	37.31	53.98	-16.67
*	11000.00	Peak	Н	-	-	-69.47	10.92	48.45	73.98	-25.53
	16500.00	Peak	Н	-	-	-70.99	17.71	53.72	68.20	-14.48

Table 7-198. Radiated Measurements CDD

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 245 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 245 01 567
			V 10.5 12/15/2021









Plot 7-622. Radiated Spurious Emissions 18GHz - 40GHz CDD (802.11n - Ch. 116)

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 246 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 246 01 367
			V/ 10 5 12/15/2021



Mode:	802.11n		
Data Rate:	MCS0		
Distance of Measurements:	3 Meters		
Operating Frequency:	5580MHz		
Channel:	116		

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11160.00	Average	Н	-	-	-79.65	10.30	37.65	53.98	-16.33
*	11160.00	Peak	Н	-	-	-70.00	10.30	47.30	73.98	-26.68
	16740.00	Peak	н	-	-	-69.93	17.30	54.37	68.20	-13.83

Table 7-199. Radiated Measurements CDD

FCC ID: BCGA2902 IC: 579C-A2902		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Page 2/7 of 387	
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	1 age 247 01 307	
			1110 5 1015 0001	







Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5720MHz
Channel:	144

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11440.00	Average	Н	-	-	-79.81	10.73	37.92	53.98	-16.06
*	11440.00	Peak	Н	-	-	-70.34	10.73	47.39	73.98	-26.59
	17160.00	Peak	н	-	-	-70.70	18.32	54.62	68.20	-13.58

Table 7-200. Radiated Measurements CDD

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dogo 249 of 297	
1C2311270063-11.BCG	CG 11/29/2023 - 1/15/2024 Tablet Device		Page 246 of 387	
			V 10.5 12/15/2021	







Mode:	802.11n		
Data Rate:	MCS0		
Distance of Measurements:	3 Meters		
Operating Frequency:	5745MHz		
Channel:	149		

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11490.00	Average	Н	-	-	-80.53	10.78	37.25	53.98	-16.73
*	11490.00	Peak	Н	-	-	-70.14	10.78	47.64	73.98	-26.34
	17235.00	Peak	Н	-	-	-71.36	18.10	53.74	68.20	-14.46

Table 7-201. Radiated Measurements CDD

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 240 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	1/15/2024 Tablet Device	
			V 10.5 12/15/2021









Plot 7-626. Radiated Spurious Emissions 18GHz - 40GHz CDD (802.11n - Ch. 157)

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dago 250 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 250 01 567
			V/ 10 5 12/15/2021



Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5785MHz
Channel:	157

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11570.00	Average	Н	-	-	-80.03	10.96	37.93	53.98	-16.05
*	11570.00	Peak	Н	-	-	-69.53	10.96	48.43	73.98	-25.55
	17355.00	Peak	н	-	-	-71.55	18.81	54.26	68.20	-13.94

Table 7-202. Radiated Measurements CDD

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 251 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 251 01 507
			V/ 40 E 40/4E/2024







Mode:	802.11n		
Data Rate:	MCS0		
Distance of Measurements:	3 Meters		
Operating Frequency:	5825MHz		
Channel:	165		

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11650.00	Average	Н	-	-	-79.95	11.08	38.13	53.98	-15.85
*	11650.00	Peak	Н	-	-	-69.55	11.08	48.53	73.98	-25.45
	17475.00	Peak	Н	-	-	-71.28	21.09	56.81	68.20	-11.39

Table 7-203. Radiated Measurements CDD

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 252 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 252 01 567
			V 10.5 12/15/2021





Plot 7-628. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) - Ch. 36)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10360.00	Peak	Н	-	-	-69.68	10.20	47.52	68.20	-20.68
*	15540.00	Average	Н	-	-	-81.08	16.09	42.01	53.98	-11.97
*	15540.00	Peak	Н	-	-	-70.31	16.09	52.78	73.98	-21.20

Table 7-204. Radiated Measurements CDD

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 252 of 207
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 255 01 567
			V 10.5 12/15/2021









Plot 7-630. Radiated Spurious Emissions above 18-40GHz CDD (802.11ax(SU) - Ch. 40)

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 254 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 254 01 567
			V/ 10 5 12/15/2021



Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5200MHz
Channel:	40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10400.00	Peak	Н	-	-	-68.88	9.98	48.10	68.20	-20.10
15600.00	Average	н	-	-	-79.76	15.64	42.88	53.98	-11.10
15600.00	Peak	н	-	-	-70.62	15.64	52.02	73.98	-21.96

Table 7-205. Radiated Measurements CDD

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 255 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 255 01 567
			V/ 40 E 40/4E/0004





Plot 7-631. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) - Ch. 48)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5240MHz
Channel:	48

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10480.00	Peak	Н	-	-	-69.57	10.26	47.69	68.20	-20.51
*	15720.00	Average	н	-	-	-80.33	15.00	41.67	53.98	-12.31
*	15720.00	Peak	н	-	-	-70.16	15.00	51.84	73.98	-22.14

Table 7-206. Radiated Measurements CDD

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 256 of 297
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 200 01 307
			V 10.5 12/15/2021





Plot 7-632. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) - Ch. 52)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5260MHz
Channel:	52

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	10520.00	Peak	Н	-	-	-69.64	10.50	47.86	68.20	-20.34
*	15780.00	Average	Н	-	-	-81.06	14.71	40.65	53.98	-13.33
*	15780.00	Peak	Н	-	-	-70.23	14.71	51.48	73.98	-22.50

Table 7-207. Radiated Measurements CDD

FCC ID: BCGA2902 IC: 579C-A2902	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dogo 257 of 297	
1C2311270063-11.BCG	11/29/2023 - 1/15/2024	Tablet Device	Fage 237 01 387	
			V 10.5 12/15/2021	