

7.7 Radiated Spurious Emissions – Above 1 GHz §15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-47 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]		
Above 960.0 MHz	500	3		

Table 7-47. Radiated Limits

Test Procedures Used

ANSI C63.10-2020 – Subclause 6.6.4.3 KDB 558074 D01 v05r02 – Sections 8.6, 8.7

Test Settings

Average Field Strength Measurements

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = power average (RMS)
- 5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
- 6. Sweep time = auto
- 7. Trace (RMS) averaging was performed over at least 100 traces

Peak Field Strength Measurements

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 270 of 424
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Fage 270 01 431
			V 10.6 09/14/2023



Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-6. Radiated Measurement Setup

Test Notes

- The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 558074 D01 v05r02 were not used to evaluate this device for compliance to radiated limits. All Radiated Spurious Emissions levels were measured in a radiated test setup.
- 2. All emissions lying in restricted bands specified in Section 15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-47.
- 3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
- 4. This unit was tested with its standard battery.
- 5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas.
- 6. D is the measurement test distance and emissions 1-18GHz were measured at a 3 meters test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
- 8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
- 9. All antenna configurations were investigated and only the worst case is reported.
- 10. The unit was tested with all possible modes and only the highest emission is reported.

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 271 of /31
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	1 age 27 1 01 431
			V 10.6 09/14/2023



Sample Calculations

Determining Spurious Emissions Levels

- \circ Field Strength Level [dBµV/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB] Preamplifier Gain [dB]
- ο Margin [dB] = Field Strength Level [dBμV/m] Limit [dBμV/m]

Radiated Band Edge Measurement Offset

The amplitude offset shown in the radiated restricted band edge plots in Section 7.7.4, 7.7.5, and
 7.7.6 were calculated using the formula:

Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

FCC ID: BCGA2993	element	MEASUREMENT REPORT	Approved by:
IC: 579C-A2993		(CERTIFICATION)	Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 272 of 431
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	
	•	·	V/ 10 6 00/14/2023



7.7.1 Antenna WF8 Radiated Spurious Emission Measurements §15.247(d) §15.205 & §15.209; RSS-Gen [8.9]





Mode:	802.11b
Data Rate:	11Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	1

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4824.00	Avg	Н	-	-	-78.35	4.54	33.19	53.98	-20.79
4824.00	Peak	Н	-	-	-66.70	4.54	44.84	73.98	-29.14
12060.00	Avg	Н	-	-	-81.46	13.52	39.06	53.98	-14.92
12060.00	Peak	Н	-	-	-70.42	13.52	50.10	73.98	-23.88

Table 7-48. Radiated Spurious Emission Measurements Antenna WF8

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 072 of 424
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Page 273 01 431
			V 10.6 09/14/2023







Mode:	802.11b
Data Rate:	11Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2437MHz
Channel:	6

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4874.00	Avg	Н	-	-	-78.08	4.68	33.60	53.98	-20.38
4874.00	Peak	Н	-	-	-66.69	4.68	44.99	73.98	-28.99
7311.00	Avg	V	-	-	-79.61	9.55	36.94	53.98	-17.04
7311.00	Peak	V	-	-	-67.67	9.55	48.88	73.98	-25.10
12185.00	Avg	н	-	-	-81.33	14.59	40.26	53.98	-13.72
12185.00	Peak	н	-	-	-71.03	14.59	50.56	73.98	-23.42

 Table 7-49. Radiated Spurious Emission Measurements Antenna WF8

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 074 of 404
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Page 274 01 431
			V 10.6 09/14/2023





Plot 7-443. Radiated Spurious Emissions above 1GHz Antenna WF8 (802.11b - Ch. 11)

Mode:	802.11b
Data Rate:	11Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2462MHz
Channel:	11

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4924.00	Avg	Н	-	-	-78.77	5.02	33.25	53.98	-20.73
4924.00	Peak	Н	-	-	-67.32	5.02	44.70	73.98	-29.28
7386.00	Avg	V	-	-	-79.54	9.73	37.19	53.98	-16.79
7386.00	Peak	V	-	-	-68.28	9.73	48.45	73.98	-25.53
12310.00	Avg	Н	-	-	-81.59	14.64	40.05	53.98	-13.93
12310.00	Peak	Н	-	-	-71.31	14.64	50.33	73.98	-23.65

 Table 7-50. Radiated Spurious Emission Measurements Antenna WF8

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dago 275 of 424
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Page 275 of 431
	•		V 10.6 09/14/2023





Plot 7-444. Radiated Spurious Emissions above 1GHz Antenna WF8 (802.11ax(SU) - Ch. 1)

Mode:	_802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	1

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4824.00	Avg	V	-	-	-80.25	7.30	34.05	53.98	-19.93
4824.00	Peak	V	-	-	-69.27	7.30	45.03	73.98	-28.95
12060.00	Avg	V	-	-	-83.59	18.09	41.50	53.98	-12.48
12060.00	Peak	V	-	-	-72.24	18.09	52.85	73.98	-21.13

Table 7-51. Radiated Spurious Emission Measurements Antenna WF8

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dago 276 of 424
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Page 276 of 431
			V 10.6 09/14/2023





Plot 7-445. Radiated Spurious Emissions above 1GHz Antenna WF8 (802.11ax(SU) - Ch. 6)

Mode:	_802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2437MHz
Channel:	6

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4874.00	Avg	V	-	-	-80.61	7.37	33.76	53.98	-20.22
4874.00	Peak	V	-	-	-69.33	7.37	45.04	73.98	-28.94
7311.00	Avg	V	-	-	-82.00	10.87	35.87	53.98	-18.11
7311.00	Peak	V	-	-	-70.89	10.87	46.98	73.98	-27.00
12185.00	Avg	V	-	-	-83.90	18.82	41.92	53.98	-12.06
12185.00	Peak	V	-	-	-72.74	18.82	53.08	73.98	-20.90

 Table 7-52. Radiated Spurious Emission Measurements Antenna WF8

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 077 of 404
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Page 277 01 431
			V 10.6 09/14/2023





Plot 7-446. Radiated Spurious Emissions above 1GHz Antenna WF8 (802.11ax(SU) – Ch. 11)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2462MHz
Channel:	11

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4924.00	Avg	V	-	-	-80.35	7.30	33.95	53.98	-20.03
4924.00	Peak	V	-	-	-69.54	7.30	44.76	73.98	-29.22
7386.00	Avg	V	-	-	-81.63	10.68	36.05	53.98	-17.93
7386.00	Peak	V	-	-	-70.13	10.68	47.55	73.98	-26.43
12310.00	Avg	V	-	-	-83.92	18.92	42.00	53.98	-11.98
12310.00	Peak	V	-	-	-73.11	18.92	52.81	73.98	-21.17

 Table 7-53. Radiated Spurious Emission Measurements Antenna WF8

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dama 070 of 404
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Page 278 of 431
			V 10.6 09/14/2023



7.7.2 Antenna WF7 Radiated Spurious Emission Measurements §15.247(d) §15.205 & §15.209; RSS-Gen [8.9]





Mode:	802.11b
Data Rate:	11Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	1

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4824.00	Avg	V	-	-	-78.30	4.54	33.24	53.98	-20.74
4824.00	Peak	V	-	-	-66.96	4.54	44.58	73.98	-29.40
12060.00	Avg	V	-	-	-81.54	13.52	38.98	53.98	-15.00
12060.00	Peak	V	-	-	-70.88	13.52	49.64	73.98	-24.34

Table 7-54. Radiated Spurious Emission Measurements Antenna WF7

FCC ID: BCGA2993 IC: 579C-A2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 270 of 421
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Fage 279 01 431
			V/ 10 6 00/14/2023







Mode:	802.11b
Data Rate:	11Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2437MHz
Channel:	6

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4874.00	Avg	V	-	-	-78.30	4.68	33.38	53.98	-20.60
4874.00	Peak	V	-	-	-66.96	4.68	44.72	73.98	-29.26
7311.00	Avg	V	-	-	-79.62	9.55	36.93	53.98	-17.05
7311.00	Peak	V	-	-	-68.07	9.55	48.48	73.98	-25.50
12185.00	Avg	V	-	-	-81.56	14.59	40.03	53.98	-13.95
12185.00	Peak	V	-	-	-70.89	14.59	50.70	73.98	-23.28

Table 7-55. Radiated Spurious Emission Measurements Antenna WF7

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 280 of 431
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Fage 200 01 431
			V 10.6 09/14/2023





Plot 7-449. Radiated Spurious Emissions above 1GHz Antenna WF7 (802.11b - Ch. 11)

Mode:	802.11b
Data Rate:	11Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2462MHz
Channel:	11

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4924.00	Avg	V	-	-	-78.78	5.02	33.24	53.98	-20.74
4924.00	Peak	V	-	-	-66.74	5.02	45.28	73.98	-28.70
7386.00	Avg	V	-	-	-79.81	9.73	36.92	53.98	-17.06
7386.00	Peak	V	-	-	-68.39	9.73	48.34	73.98	-25.64
12310.00	Avg	V	-	-	-81.83	14.64	39.81	53.98	-14.17
12310.00	Peak	V	-	-	-70.39	14.64	51.25	73.98	-22.73

Table 7-56. Radiated Spurious Emission Measurements Antenna WF7

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 201 of 421
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Page 281 of 431
	•		V 10.6 09/14/2023





Plot 7-450. Radiated Spurious Emissions above 1GHz Antenna WF7 (802.11ax(SU) - Ch. 1)

Mode:	_802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	1

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4824.00	Avg	V	-	-	-80.16	7.30	34.14	53.98	-19.84
4824.00	Peak	V	-	-	-69.39	7.30	44.91	73.98	-29.07
12060.00	Avg	V	-	-	-83.96	18.95	41.99	53.98	-11.99
12060.00	Peak	V	-	-	-73.15	18.95	52.80	73.98	-21.18

Table 7-57. Radiated Spurious Emission Measurements Antenna WF7

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dama 000 of 404
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Page 282 of 431
		·	V 10.6 09/14/2023





Plot 7-451. Radiated Spurious Emissions above 1GHz Antenna WF7 (802.11ax(SU) – Ch. 6)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2437MHz
Channel:	6

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4874.00	Avg	V	-	-	-82.30	9.22	33.92	53.98	-20.06
4874.00	Peak	V	-	-	-71.50	9.22	44.72	73.98	-29.26
7311.00	Avg	V	-	-	-81.83	10.87	36.04	53.98	-17.94
7311.00	Peak	V	-	-	-70.72	10.87	47.15	73.98	-26.83
12185.00	Avg	V	-	-	-83.83	18.76	41.93	53.98	-12.05
12185.00	Peak	V	-	-	-72.36	18.76	53.40	73.98	-20.58

Table 7-58. Radiated Spurious Emission Measurements Antenna WF7

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 292 of 421
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Fage 203 01 431
			V 10.6 09/14/2023





Plot 7-452. Radiated Spurious Emissions above 1GHz Antenna WF7 (802.11ax(SU) – Ch. 11)

Mode:	802.11ax(SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2462MHz
Channel:	11

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4924.00	Avg	V	-	-	-80.63	7.16	33.53	53.98	-20.45
4924.00	Peak	V	-	-	-68.66	7.16	45.50	73.98	-28.48
7386.00	Avg	V	-	-	-81.41	10.68	36.27	53.98	-17.71
7386.00	Peak	V	-	-	-70.69	10.68	46.99	73.98	-26.99
12310.00	Avg	V	-	-	-83.54	18.48	41.94	53.98	-12.04
12310.00	Peak	V	-	-	-72.36	18.48	53.12	73.98	-20.86

Table 7-59. Radiated Spurious Emission Measurements Antenna WF7

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 294 of 421
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Page 264 01 431
			V 10.6 09/14/2023



7.7.3 CDD Radiated Spurious Emission Measurements §15.247(d) §15.205 & §15.209; RSS-Gen [8.9]





Mode:	802.11n
Data Rate:	MCS8
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	1

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4824.00	Avg	Н	-	-	-80.03	6.94	33.91	53.98	-20.07
4824.00	Peak	Н	-	-	-68.55	6.94	45.39	73.98	-28.59
12060.00	Avg	Н	-	-	-83.39	18.18	41.79	53.98	-12.19
12060.00	Peak	Н	-	-	-72.64	18.18	52.54	73.98	-21.44

Table 7-60. Radiated Spurious Emission Measurements CDD

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 205 of 424
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Page 265 01 431
			V/ 10 6 00/14/2023









Plot 7-455. Radiated Spurious Emissions above 18GHz CDD (802.11n - Ch.6)

FCC ID: BCGA2993 IC: 579C-A2993	element 🤤	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 286 of 431
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Fage 200 01 431
			V 10 6 09/14/2023



Mode:	802.11n
Data Rate:	MCS8
Distance of Measurements:	3 Meters
Operating Frequency:	2437MHz
Channel:	6

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4874.00	Avg	Н	-	-	-80.50	7.29	33.79	53.98	-20.19
4874.00	Peak	н	-	-	-69.33	7.29	44.96	73.98	-29.02
7311.00	Avg	н	-	-	-81.84	10.87	36.03	53.98	-17.95
7311.00	Peak	н	-	-	-70.56	10.87	47.31	73.98	-26.67
12185.00	Avg	н	-	-	-83.69	18.82	42.13	53.98	-11.85
12185.00	Peak	н	-	-	-73.17	18.82	52.65	73.98	-21.33

Table 7-61. Radiated Spurious Emission Measurements CDD

FCC ID: BCGA2993	element	MEASUREMENT REPORT	Approved by:
IC: 579C-A2993		(CERTIFICATION)	Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 287 of 431
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	
		·	V/ 10 6 00/14/2023







Mode:	802.11n
Data Rate:	MCS8
Distance of Measurements:	3 Meters
Operating Frequency:	2462MHz
Channel:	11

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4924.00	Avg	Н	-	-	-80.40	7.16	33.76	53.98	-20.22
4924.00	Peak	Н	-	-	-69.43	7.16	44.73	73.98	-29.25
7386.00	Avg	Н	-	-	-81.93	10.98	36.05	53.98	-17.93
7386.00	Peak	Н	-	-	-70.61	10.98	47.37	73.98	-26.61
12310.00	Avg	Н	-	-	-83.47	18.48	42.01	53.98	-11.97
12310.00	Peak	Н	-	-	-72.37	18.48	53.11	73.98	-20.87

 Table 7-62. Radiated Spurious Emission Measurements CDD

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dage 200 of 424	
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Page 288 of 431	
			V 10.6 09/14/2023	







Mode:	_802.11ax (SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	1

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4824.00	Avg	V	-	-	-80.19	7.29	34.10	53.98	-19.88
4824.00	Peak	V	-	-	-69.22	7.29	45.07	73.98	-28.91
12060.00	Avg	V	-	-	-83.76	18.62	41.86	53.98	-12.12
12060.00	Peak	V	-	-	-72.49	18.62	53.13	73.98	-20.85

Table 7-63. Radiated Spurious Emission Measurements CDD

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 200 of 424
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Page 289 of 431
			V 10.6 09/14/2023









Plot 7-459. Radiated Spurious Emissions above 18GHz CDD (802.11ax (SU) - Ch.6)

FCC ID: BCGA2993 IC: 579C-A2993	element 🤤	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 200 of 431
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Fage 250 01 431
			V 10 6 00/17/2023



Mode:	802.11ax (SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2437MHz
Channel:	6

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4874.00	Avg	V	-	-	-80.44	7.28	33.84	53.98	-20.14
4874.00	Peak	V	-	-	-69.32	7.28	44.96	73.98	-29.02
7311.00	Avg	V	-	-	-81.71	10.68	35.97	53.98	-18.01
7311.00	Peak	V	-	-	-70.56	10.68	47.12	73.98	-26.86
12185.00	Avg	V	-	-	-83.92	18.82	41.90	53.98	-12.08
12185.00	Peak	V	-	-	-72.84	18.82	52.98	73.98	-21.00

Table 7-64. Radiated Spurious Emission Measurements CDD

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200017-03-R1.BCG	Test Dates: 5/20/2024 - 7/01/2024	EUT Type: Tablet Device	Page 291 of 431
	•	·	V/ 10 6 00/14/2023







Mode:	802.11ax (SU)
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2462MHz
Channel:	11

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4924.00	Avg	V	-	-	-80.62	7.13	33.51	53.98	-20.47
4924.00	Peak	V	-	-	-69.47	7.13	44.66	73.98	-29.32
7386.00	Avg	V	-	-	-81.62	10.79	36.17	53.98	-17.81
7386.00	Peak	V	-	-	-69.84	10.79	47.95	73.98	-26.03
12310.00	Avg	V	-	-	-83.68	18.48	41.80	53.98	-12.18
12310.00	Peak	V	-	-	-72.13	18.48	53.35	73.98	-20.63

Table 7-65. Radiated Spurious Emission Measurements CDD

FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 202 of /31
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	1 age 232 01 431
			V 10.6 09/14/2023



7.7.4 Antenna WF8 Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]















FCC ID: BCGA2993	element MEASUREMENT REPORT		Approved by:
IC: 579C-A2993	(CERTIFICATION)		Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 293 of 431
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	
			N/ 40 0 00/4 1/0000



Mode	802.11b
Data Rate	11Mbps
Distance of Measurement	3 Meters
Operating Frequency	2467MHz
Channel	12





Mode Data Rate **Distance of Measurement Operating Frequency** Channel







FCC ID: BCGA2993	element MEASUREMENT REPORT		Approved by:
IC: 579C-A2993	(CERTIFICATION)		Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 294 of 431
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	
			V/ 40 0 00/4 4/0000



Mode	802.11n
Data Rate	MCS2
Distance of Measurement	3 Meters
Operating Frequency	2412MHz
Channel	1



Plot 7-465 Radiated Restricted Lower Band Edge Measurement Antenna WF8

Mode Data Rate **Distance of Measurement Operating Frequency** Channel







FCC ID: BCGA2993 IC: 579C-A2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 205 of 421
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Fage 295 01 451
			V/ 10 6 00/14/2022



Mode	802.11n
Data Rate	MCS7
Distance of Measurement	3 Meters
Operating Frequency	2412MHz
Channel	1



Plot 7-467 Radiated Restricted Lower Band Edge Measurement Antenna WF8

Mode Data Rate Distance of Measurement Operating Frequency Channel







FCC ID: BCGA2993 IC: 579C-A2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 206 of 421
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Faye 230 01 431
			V/ 40 C 00/4 4/2022



Mode	802.11n
Data Rate	MCS4
Distance of Measurement	3 Meters
Operating Frequency	2417MHz
Channel	2



Plot 7-469 Radiated Restricted Lower Band Edge Measurement Antenna WF8

Mode Data Rate **Distance of Measurement Operating Frequency** Channel







FCC ID: BCGA2993	element MEASUREMENT REPORT		Approved by:
IC: 579C-A2993	(CERTIFICATION)		Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 297 of 431
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	
			1/ 10 0 00/1 1/0000



Mode	802.11n
Data Rate	MCS2
Distance of Measurement	3 Meters
Operating Frequency	2422MHz
Channel	3





Mode Data Rate **Distance of Measurement Operating Frequency** Channel

	802.11n	
	MCS4	
t	3 Meters	
	2422MHz	
	3	





FCC ID: BCGA2993 IC: 579C-A2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 298 of 431
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	1 age 200 01 401
			V 10.6 09/14/2023



Mode	802.11n
Data Rate	MCS7
Distance of Measurement	3 Meters
Operating Frequency	2422MHz
Channel	3





Mode Data Rate **Distance of Measurement Operating Frequency** Channel







FCC ID: BCGA2993 IC: 579C-A2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 200 of 421
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Fage 299 01 431
			V/ 10 C 00/14/2022



Mode	802.11n
Data Rate	MCS4
Distance of Measurement	3 Meters
Operating Frequency	2427MHz
Channel	4





Mode Data Rate **Distance of Measurement Operating Frequency** Channel







FCC ID: BCGA2993	element MEASUREMENT REPORT		Approved by:
IC: 579C-A2993	(CERTIFICATION)		Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 300 of 431
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	
			V/ 40, 0, 00/4 4/0000



Mode	802.11n
Data Rate	MCS2
Distance of Measurement	3 Meters
Operating Frequency	2432MHz
Channel	5





Mode Data Rate Distance of Measurement Operating Frequency Channel







FCC ID: BCGA2993	element MEASUREMENT REPORT		Approved by:
IC: 579C-A2993	(CERTIFICATION)		Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 301 of 431
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	
			V/ 40, 0, 00/4 4/0000



Mode	802.11n
Data Rate	MCS7
Distance of Measurement	3 Meters
Operating Frequency	2432MHz
Channel	5





Mode Data Rate **Distance of Measurement Operating Frequency** Channel







FCC ID: BCGA2993	element MEASUREMENT REPORT		Approved by:
IC: 579C-A2993	(CERTIFICATION)		Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 302 of 431
1C2405200017-03-R1 BCG	5/20/2024 - 7/01/2024	Tablet Device	
	1		N/ 40, 0, 00/4 4/0000



Mode	802.11n
Data Rate	MCS4
Distance of Measurement	3 Meters
Operating Frequency	2437MHz
Channel	6





Mode Data Rate Distance of Measurement Operating Frequency Channel







FCC ID: BCGA2993 IC: 579C-A2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 202 of 421
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	Fage 505 01 451
			V/ 10 6 00/14/2022



Mode	802.11n
Data Rate	MCS2
Distance of Measurement	3 Meters
Operating Frequency	2437MHz
Channel	6





Mode Data Rate **Distance of Measurement Operating Frequency** Channel

802.11n
MCS4
3 Meters
2437MHz
6





Test Report S/N: Test Dates: EUT Type: 1C2405200017_02_R1_RCC 5/20/2024 - 7/01/2024 Tablet Davies Page 304	IT REPORT Approved by: ATION) Technical Manager	nent MEASUREMENT REPORT (CERTIFICATION)		FCC ID: BCGA2993 IC: 579C-A2993
	Page 304 of 431	EUT Type: Tablet Device	Test Dates: 5/20/2024 - 7/01/2024	Test Report S/N: 1C2405200017-03-R1.BCG



Mode	802.11n
Data Rate	MCS7
Distance of Measurement	3 Meters
Operating Frequency	2437MHz
Channel	6





Mode Data Rate **Distance of Measurement Operating Frequency** Channel







Test Report S/N: Test Dates: EUT Type: Page 305 of 431 1C2405200017-03-R1.BCG 5/20/2024 - 7/01/2024 Tablet Device Page 305 of 431	FCC ID: BCGA2993 IC: 579C-A2993	element	ement MEASUREMENT REPORT (CERTIFICATION)	
	Test Report S/N: 1C2405200017-03-R1.BCG	Test Dates: 5/20/2024 - 7/01/2024	EUT Type: Tablet Device	Page 305 of 431



Mode	802.11n
Data Rate	MCS4
Distance of Measurement	3 Meters
Operating Frequency	2442MHz
Channel	7





Mode Data Rate **Distance of Measurement Operating Frequency** Channel







FCC ID: BCGA2993	element MEASUREMENT REPORT		Approved by:
IC: 579C-A2993	(CERTIFICATION)		Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 306 of 431
1C2405200017-03-R1.BCG	5/20/2024 - 7/01/2024	Tablet Device	
			V/ 40 C 00/4 4/2022



Mode	802.11n
Data Rate	MCS2
Distance of Measurement	3 Meters
Operating Frequency	2447MHz
Channel	8





Mode Data Rate **Distance of Measurement Operating Frequency** Channel







FCC ID: BCGA2993 IC: 579C-A2993	element	element MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N: 1C2405200017-03-R1.BCG	Test Dates: 5/20/2024 - 7/01/2024	EUT Type: Tablet Device	Page 307 of 431