




Plot 7-1177. VLP In-Band Emission Plot Antenna WF2 (40MHz 802.11ax RU106 (UNII Band 7) – Ch. 155)




Plot 7-1180. VLP In-Band Emission Plot Antenna WF2 (40MHz 802.11ax RU484 (UNII Band 7) – Ch. 155)




Plot 7-1178. VLP In-Band Emission Plot Antenna WF2 (40MHz 802.11ax RU106 (UNII Band 7) - Ch. 155)



Plot 7-1181. VLP In-Band Emission Plot Antenna WF2 (80MHz 802.11ax RU106 (UNII Band 7) – Ch. 151)




Plot 7-1179. VLP In-Band Emission Plot Antenna WF2 (40MHz 802.11ax RU106 (UNII Band 7) – Ch. 155)




Plot 7-1182. VLP In-Band Emission Plot Antenna WF2 (80MHz 802.11ax RU106 (UNII Band 7) – Ch. 151)

FCC ID: BCGA2993	element	element MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N:	Test Dates:	EUT Type:	Dogg 202 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 302 of 464







Plot 7-1183. VLP In-Band Emission Plot Antenna WF2 (80MHz 802.11ax RU106 (UNII Band 7) - Ch. 151)




Plot 7-1186. VLP In-Band Emission Plot Antenna WF2 (160MHz 802.11ax RU106 (UNII Band 7) - Ch. 143)




Plot 7-1184. VLP In-Band Emission Plot Antenna WF2 (80MHz 802.11ax RU996 (UNII Band 7) - Ch. 151)



Plot 7-1187. VLP In-Band Emission Plot Antenna WF2 (160MHz 802.11ax RU106 (UNII Band 7) - Ch. 143)



Plot 7-1185. VLP In-Band Emission Plot Antenna WF2 (160MHz 802.11ax RU106 (UNII Band 7) – Ch. 143)




Plot 7-1188. VLP In-Band Emission Plot Antenna WF2 (160MHz 802.11ax RU996x2 (UNII Band 7) – Ch. 143)


FCC ID: BCGA2993	element	element MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N:	Test Dates:	EUT Type:	Page 303 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Fage 303 01 464




7.5.9 SDM VLP In-Band Emission Measurements




Plot 7-1189. VLP In-Band Emission Plot SDM Antenna WF5T (20MHz 802.11ax RU242 (UNII Band 5) - Ch. 61)




Plot 7-1192. VLP In-Band Emission Plot SDM Antenna WF2 (40MHz 802.11ax RU242 (UNII Band 5) - Ch. 59)




Plot 7-1190. VLP In-Band Emission Plot SDM Antenna WF2 (20MHz 802.11ax RU242 (UNII Band 5) – Ch. 61)



Plot 7-1193. VLP In-Band Emission Plot SDM Antenna WF5T (40MHz 802.11ax RU242 (UNII Band 5) - Ch. 59)




Plot 7-1191. VLP In-Band Emission Plot SDM Antenna WF5T (40MHz 802.11ax RU242 (UNII Band 5) – Ch. 59)




Plot 7-1194. VLP In-Band Emission Plot SDM Antenna WF2 (40MHz 802.11ax RU242 (UNII Band 5) – Ch. 59)

FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 204 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 304 of 464







Plot 7-1195. VLP In-Band Emission Plot SDM Antenna WF5T (40MHz 802.11ax RU484 (UNII Band 5) - Ch. 59)




Plot 7-1198. VLP In-Band Emission Plot SDM Antenna WF2 (80MHz 802.11ax RU242 (UNII Band 5) – Ch. 55)




Plot 7-1196. VLP In-Band Emission Plot SDM Antenna WF2 (40MHz 802.11ax RU484 (UNII Band 5) - Ch. 59)



Plot 7-1199. VLP In-Band Emission Plot SDM Antenna WF5T (80MHz 802.11ax RU242 (UNII Band 5) - Ch. 55)



Plot 7-1197. VLP In-Band Emission Plot SDM Antenna WF5T (80MHz 802.11ax RU242 (UNII Band 5) – Ch. 55)




Plot 7-1200. VLP In-Band Emission Plot SDM Antenna WF2 (80MHz 802.11ax RU242 (UNII Band 5) – Ch. 55)

FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 205 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 305 of 464



Pass

-20




Plot 7-1201. VLP In-Band Emission Plot SDM Antenna WF5T (80MHz 802.11ax RU242 (UNII Band 5) - Ch. 55)

Trace/Detector: AVG/RMS RBW/VBW: 0.82MHz/3.00MHz Sweep Time: 1.0ms




Plot 7-1202. VLP In-Band Emission Plot SDM Antenna WF2 (80MHz 802.11ax RU242 (UNII Band 5) - Ch. 55)




Plot 7-1203. VLP In-Band Emission Plot SDM Antenna WF5T (80MHz 802.11ax RU996 (UNII Band 5) - Ch. 55)



Plot 7-1204. VLP In-Band Emission Plot SDM Antenna WF2 (80MHz 802.11ax RU996 (UNII Band 5) – Ch. 55)




Plot 7-1205. VLP In-Band Emission Plot SDM Antenna WF5T (160MHz 802.11ax RU242 (UNII Band 5) - Ch. 47)




Plot 7-1206. VLP In-Band Emission Plot SDM Antenna WF2 (160MHz 802.11ax RU242 (UNII Band 5) – Ch. 47)

FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogg 200 of 404
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 306 of 464







Plot 7-1207. VLP In-Band Emission Plot SDM Antenna WF5T (160MHz 802.11ax RU242 (UNII Band 5) – Ch. 47)




Plot 7-1210. VLP In-Band Emission Plot SDM Antenna WF2 (160MHz 802.11ax RU242 (UNII Band 5) – Ch. 47)




Plot 7-1208. VLP In-Band Emission Plot SDM Antenna WF2 (160MHz 802.11ax RU242 (UNII Band 5) - Ch. 47)



Plot 7-1211. VLP In-Band Emission Plot SDM Antenna WF5T (160MHz 802.11ax RU996x2 (UNII Band 5) - Ch. 47)




Plot 7-1209. VLP In-Band Emission Plot SDM Antenna WF5T (160MHz 802.11ax RU242 (UNII Band 5) – Ch. 47)




Plot 7-1212. VLP In-Band Emission Plot SDM Antenna WF2 (160MHz 802.11ax RU996x2 (UNII Band 5) – Ch. 47)

FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 207 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 307 of 464







Plot 7-1213. VLP In-Band Emission Plot SDM Antenna WF5T (20MHz 802.11ax RU242 (UNII Band 7) – Ch. 149)




Plot 7-1216. VLP In-Band Emission Plot SDM Antenna WF2 (40MHz 802.11ax RU242 (UNII Band 7) - Ch. 155)




Plot 7-1214. VLP In-Band Emission Plot SDM Antenna WF2 (20MHz 802.11ax RU242 (UNII Band 7) - Ch. 149)



Plot 7-1217. VLP In-Band Emission Plot SDM Antenna WF5T (40MHz 802.11ax RU242 (UNII Band 7) – Ch. 155)




Plot 7-1215. VLP In-Band Emission Plot SDM Antenna WF5T (40MHz 802.11ax RU242 (UNII Band 7) – Ch. 155)




Plot 7-1218. VLP In-Band Emission Plot SDM Antenna WF2 (40MHz 802.11ax RU242 (UNII Band 7) - Ch. 155)

FCC ID: BCGA2993	element	element MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N:	Test Dates:	EUT Type:	Dogg 200 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 308 of 464







Plot 7-1219. VLP In-Band Emission Plot SDM Antenna WF5T (40MHz 802.11ax RU484 (UNII Band 7) – Ch. 155)




Plot 7-1220. VLP In-Band Emission Plot SDM Antenna WF2 (40MHz 802.11ax RU484 (UNII Band 7) – Ch. 155)




Plot 7-1221. VLP In-Band Emission Plot SDM Antenna WF5T (80MHz 802.11ax RU242 (UNII Band 7) - Ch. 151)



Plot 7-1222. VLP In-Band Emission Plot SDM Antenna WF2 (80MHz 802.11ax RU242 (UNII Band 7) – Ch. 151)




Plot 7-1223. VLP In-Band Emission Plot SDM Antenna WF5T (80MHz 802.11ax RU242 (UNII Band 7) – Ch. 151)




Plot 7-1224. VLP In-Band Emission Plot SDM Antenna WF2 (80MHz 802.11ax RU242 (UNII Band 7) – Ch. 151)

FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogg 200 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 309 of 464







Plot 7-1225. VLP In-Band Emission Plot SDM Antenna WF5T (80MHz 802.11ax RU242 (UNII Band 7) – Ch. 151)




Plot 7-1228. VLP In-Band Emission Plot SDM Antenna WF2 (80MHz 802.11ax RU996 (UNII Band 7) – Ch. 151)




Plot 7-1226. VLP In-Band Emission Plot SDM Antenna WF2 (80MHz 802.11ax RU242 (UNII Band 7) - Ch. 151)



Plot 7-1229. VLP In-Band Emission Plot SDM Antenna WF5T (160MHz 802.11ax RU242 (UNII Band 7) – Ch. 143)




Plot 7-1227. VLP In-Band Emission Plot SDM Antenna WF5T (80MHz 802.11ax RU996 (UNII Band 7) – Ch. 151)




Plot 7-1230. VLP In-Band Emission Plot SDM Antenna WF2 (160MHz 802.11ax RU242 (UNII Band 7) – Ch. 143)

FCC ID: BCGA2993	element	element MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N:	Test Dates:	EUT Type:	Dogo 240 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 310 of 464







Plot 7-1231. VLP In-Band Emission Plot SDM Antenna WF5T (160MHz 802.11ax RU242 (UNII Band 7) – Ch. 143)




Plot 7-1234. VLP In-Band Emission Plot SDM Antenna WF2 (160MHz 802.11ax RU242 (UNII Band 7) – Ch. 143)




Plot 7-1232. VLP In-Band Emission Plot SDM Antenna WF2 (160MHz 802.11ax RU242 (UNII Band 7) – Ch. 143)



Plot 7-1235. VLP In-Band Emission Plot SDM Antenna WF5T (160MHz 802.11ax RU996x2 (UNII Band 7) - Ch. 143)



Plot 7-1233. VLP In-Band Emission Plot SDM Antenna WF5T (160MHz 802.11ax RU242 (UNII Band 7) – Ch. 143)



Plot 7-1236. VLP In-Band Emission Plot SDM Antenna WF2 (160MHz 802.11ax RU996x2 (UNII Band 7) – Ch. 143)

FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 244 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 311 of 464



7.6 Contention Based Protocol §15.407(d)(6)

Test Overview and Limit

Indoor access points, subordinate devices and client devices operating in the 5.925-7.125 GHz band (herein referred to as unlicensed devices) are required to use technologies that include a contention-based protocol to avoid co-channel interference with incumbent devices sharing the band. To ensure incumbent co-channel operations are detected in a technology-agnostic manner, unlicensed devices are required to detect co-channel radio frequency energy (energy detect) and avoid simultaneous transmission.

Unlicensed indoor low-power devices must detect co-channel radio frequency power that is at least -62 dBm or lower. Upon detection of energy in the band, unlicensed low power indoor devices must vacate the channel and stay off the channel as long as detected radio frequency power is equal to or greater than the threshold (-62 dBm). The -62 dBm (or lower) threshold is referenced to a 0 dBi antenna gain.

To ensure incumbent operations are reliably detected in the band, low power indoor devices must detect RF energy throughout their intended operating channel.

Test Procedure Used

ANSI C63.10-2020 – Section 12.4.2.2 KDB 987594 D02 v02r01 – Section I

Test Settings

- 1. Configure the EUT to transmit with a constant duty cycle.
- 2. Set the operating parameters of the EUT including power level, operating frequency, modulation and bandwidth
- 3. Set the signal analyzer center frequency to the nominal EUT channel center frequency. The span range of the signal analyzer shall be between two times and five times the OBW of the EUT.
- 4. Connect the output port of the EUT to the signal analyzer 2, as shown in Figure 2. Ensure that the attenuator 2 provides enough attenuation to not overload the signal analyzer 2 receiver.
- 5. Monitoring the signal analyzer 2, verify the EUT is operating and transmitting with the parameters set at step two.
- 6. Using an AWGN signal source, generate (but do not transmit, i.e., RF OFF) a 10 MHz-wide AWGN signal. Use Table 1 to determine the center frequency of the 10 MHz AWGN signal relative to the EUT's channel bandwidth and center frequency.
- 7. Set the AWGN signal power to an extremely low level (more than 20 dB below the -62 dBm threshold). Connect the AWGN signal source, via a 3-dB splitter, to the signal analyzer 1 and the EUT as shown in Figure 2.
- 8. Transmit the AWGN signal (RF ON) and verify its characteristics on the signal analyzer 1.
- 9. Monitor the signal analyzer 2 to verify if the AWGN signal has been detected and the EUT has ceased transmission. If the EUT continues to transmit, then incrementally increase the AWGN signal power level until the EUT stops transmitting.
- 10. Including all losses in the RF paths) Determine and record the AWGN signal power level (at the EUT's antenna port) at which the EUT ceased transmission. Repeat the procedure at least 10 times to verify the EUT can detect an AWGN signal with 90% (or better) level of certainty.
- 11. Refer to Table 1 to determine number of times the detection threshold testing needs to be repeated. If testing is required more than once, then go back to step 5, choose a different center frequency for the AWGN signal and repeat the process.

FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dags 242 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 312 of 464



Test Setup




Figure 2. Contention-based protocol test setup, conducted method Step-by-Step Procedure, Conducted Setup

Test Notes

- 1. Per guidance from KDB 987594 D02 v02r01, contention based protocol was tested using an AWGN signal with a bandwidth of 10MHz. The amplitude of the signal was increased until detected by the EUT, signaled by the ceasing of transmission, marker indicates the point at which the AWGN signal is introduced.
- 2. 15 trials were ran in order to assure that at least 90% of certainty was met.
- 3. Per Guidance from KDB 987594 D04 v02, contention based protocol was tested with receiver with the lowest antenna gain.
- 4. The EUT does not support channel puncturing.

Detection Level = Injected AWGN Power (dBm) - Antenna Gain (dBi) + Path Loss (dB)

Equation 7-1. Incumbent Detection Level Calculation

FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dags 242 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 313 of 464



Band	Channel	Channel Frquency [MHz]	Channel BW [MHz]	Incumbent Frequency [MHz]	Injected (AWGN) [dBm]	Antenna Gain [dBi]	Adjusted Power Level [dBm]	Detection Limit [dBm]	Margin [dB]
	53	6215	20	6215	-73.53	-0.90	-72.63	-62.0	-10.63
UNII				6110	-66.48	-0.90	-65.58	-62.0	-3.58
Band 5	47	6185	160	6185	-70.74	-0.90	-69.84	-62.0	-7.84
				6260	-65.13	-0.90	-64.23	-62.0	-2.23
	101	6455	20	6455	-72.56	-0.90	-71.66	-62.0	-9.66
UNII				6430	-69.86	-0.90	-68.96	-62.0	-6.96
Band 6	111	6505	160	6505	-71.51	-0.90	-70.61	-62.0	-8.61
				6580	-68.55	-0.90	-67.65	-62.0	-5.65
	149	6695	20	6695	-72.36	-0.90	-71.46	-62.0	-9.46
UNII				6590	-68.90	-0.90	-68.00	-62.0	-6.00
Band 7	143	6665	160	6665	-72.84	-0.90	-71.94	-62.0	-9.94
				6740	-64.83	-0.90	-63.93	-62.0	-1.93
	197	6935	20	6935	-74.39	-0.90	-73.49	-62.0	-11.49
UNII				6910	-69.81	-0.90	-68.91	-62.0	-6.91
Band 8	Band 8 207	6985	160	6985	-71.18	-0.90	-70.28	-62.0	-8.28
				7060	-65.21	-0.90	-64.31	-62.0	-2.31

Table 7-140. Contention Based Protocol LPI - Incumbent Detection Results

		Channel	Channel	Incumbent	EUT Tra	nsmission	Status
Band	Channel	Frquency	BW	Frequency	Adjusted A	AWGN Powe	er (dBm)
		[MHz]	[MHz]	[MHz]	Normal	Minimal	Ceased
	53	6215	20	6215	-83.81	-73.88	-72.63
UNII				6110	-76.76	-66.83	-65.58
Band 5	47	6185	160	6185	-81.02	-71.09	-69.84
				6260	-75.41	-65.48	-64.23
	101	6455	20	6455	-82.84	-72.91	-71.66
UNII				6430	-80.14	-70.21	-68.96
Band 6	111	6505	160	6505	-81.79	-71.86	-70.61
				6580	-78.83	-68.90	-67.65
	149	6695	20	6695	-82.44	-72.68	-71.46
UNII				6750	-78.98	-69.22	-68.00
Band 7	143	6665	160	6825	-82.92	-73.16	-71.94
				6900	-74.91	-65.15	-63.93
	197	6935	20	6935	-84.47	-74.71	-73.49
UNII				6910	-79.89	-70.13	-68.91
Band 8	207	6985	160	6985	-81.26	-71.50	-70.28
				7060	-75.29	-65.53	-64.31

Table 7-141. Contention Based Protocol LPI - Detection Results - All Tx Cases

FCC ID: BCGA2993	element	element Measurement Report (CERTIFICATION)			
Test Report S/N:	Test Dates:	EUT Type:	Dags 244 of 464		
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 314 of 464		



								CB	P Detection	(1 = Detect	ion, Blank =	No Detect	ion)								
and	Channel	Channel Frquency [MHz]	Channel BW [MHz]	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Detection Rate [%]	Limit [%]	Pass/Fail
	53	6215	20	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
UNII				1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
Band 5	47	6185	160	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
				1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
	101	6455	20	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
UNII				1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
Band 6	111	6505	160	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
				1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
	149	6695	20	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
UNII				1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
Band 7	175	6665	160	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
				1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
	197	6935	20	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
UNII				1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
Band 8	207	6985	160	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
				1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass

Table 7-142. Contention Based Protocol – Incumbent Detection Trial Results

Band	Channel	Channel Frquency [MHz]	Channel BW [MHz]	Incumbent Frequency [MHz]	Injected (AWGN) [dBm]	Antenna Gain [dBi]	Adjusted Power Level [dBm]	Detection Limit [dBm]	Margin [dB]
	53	6215	20	6215	-69.45	-0.90	-68.55	-62.0	-6.55
UNII				6115	-67.53	-0.90	-66.63	-62.0	-4.63
Band 5	47	6185	160	6185	-71.16	-0.90	-70.26	-62.0	-8.26
				6260	-67.19	-0.90	-66.29	-62.0	-4.29
	149	6695	20	6695	-69.42	-0.90	-68.52	-62.0	-6.52
UNII				6590	-69.53	-0.90	-68.63	-62.0	-6.63
Band 7	143	6665	160	6665	-70.86	-0.90	-69.96	-62.0	-7.96
				6740	-68.55	-0.90	-67.65	-62.0	-5.65

Table 7-143. Contention Based Protocol VLP - Incumbent Detection Results

		Channel	Channel	Incumbent	EUT Tra	nsmissior	Status
Band	Channel	Frquency	BW	Frequency	Adjusted	Adjusted AWGN Pow	
		[MHz]	[MHz]	[MHz]	Normal	Minimal	Ceased
	53	6215	20	6215	-79.73	-69.80	-68.55
UNII				6110	-77.81	-67.88	-66.63
Band 5	47	6185	160	6185	-81.44	-71.51	-70.26
				6260	-77.47	-67.54	-66.29
	149	6695	20	6695	-79.50	-69.74	-68.52
UNII				6750	-79.61	-69.85	-68.63
Band 7	175	6665	160	6825	-80.94	-71.18	-69.96
				6900	-78.63	-68.87	-67.65

Table 7-144. Contention Based Protocol VLP - Detection Results - All Tx Cases

FCC ID: BCGA2993	element	element Measurement Report (CERTIFICATION)			
Test Report S/N:	Test Dates:	EUT Type:	Dags 245 of 464		
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 315 of 464		




								СВ	P Detection	(1 = Detect	ion, Blank =	No Detect	ion)								
Band	Channel	Channel Frquency [MHz]	Channel BW [MHz]	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Detection Rate [%]		Pass/Fail
	53	6215	20	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
UNII				1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
Band 5	47	6185	160	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
				1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
	149	6695	20	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
UNII				1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
Band 7	175	6665	160	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass
				1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	Pass

Table 7-145. Contention Based Protocol VLP - Incumbent Detection Trial Results


FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 246 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 316 of 464



AWGN Plots



Plot 7-1237. AWGN Signal - UNII 5 - 20MHz




Plot 7-1238. AWGN Signal - UNII 5 - 160MHz - Low

FCC ID: BCGA2993	element	element MEASUREMENT REPORT (CERTIFICATION)			
Test Report S/N:	Test Dates:	EUT Type:	Dags 247 of 464		
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 317 of 464		








13:21:42 04.06.2024

Plot 7-1239. AWGN Signal - UNII 5 - 160MHz - Mid




Plot 7-1240. AWGN Signal - UNII 5 - 160MHz - High

FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dags 240 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 318 of 464








12:45:14 04.06.2024

Plot 7-1241. AWGN Signal - UNII 6 - 20MHz




Plot 7-1242. AWGN Signal - UNII 6 - 160MHz - Low

FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dags 240 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 319 of 464








12:46:21 04.06.2024

Plot 7-1243. AWGN Signal - UNII 6 - 160MHz - Mid




Plot 7-1244. AWGN Signal - UNII 6 - 160MHz - High

FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dags 220 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 320 of 464








12:47:29 04.06.2024

Plot 7-1245. AWGN Signal - UNII 7 - 20MHz




Plot 7-1246. AWGN Signal - UNII 7 - 160MHz - Low

FCC ID: BCGA2993	element	element MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N:	Test Dates:	EUT Type:	Dags 224 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 321 of 464








12:48:45 04.06.2024

Plot 7-1247. AWGN Signal - UNII 7 - 160MHz - Mid




Plot 7-1248. AWGN Signal - UNII 7 - 160MHz - High

FCC ID: BCGA2993	element	element MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N:	Test Dates:	EUT Type:	Dags 222 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 322 of 464








12:50:18 04.06.2024

Plot 7-1249. AWGN Signal - UNII 8 - 20MHz




Plot 7-1250. AWGN Signal - UNII 8 - 160MHz - Low

FCC ID: BCGA2993	element	element MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N:	Test Dates:	EUT Type:	Dags 222 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 323 of 464








12:52:00 04.06.2024

Plot 7-1251. AWGN Signal - UNII 8 - 160MHz - Mid




Plot 7-1252. AWGN Signal - UNII 8 - 160MHz - High


FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 224 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 324 of 464



Contention-Based Protocol Timing Plots



Plot 7-1253. LPI Contention Based Protocol Timing Plot - UNII 5 - 20MHz Channel 53




Plot 7-1254. LPI Contention Based Protocol Timing Plot - UNII 5 - 160MHz Channel 47 - Low


FCC ID: BCGA2993	element	element MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N:	Test Dates:	EUT Type:	Dogg 205 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 325 of 464



08:07:08 04.06.2024




Plot 7-1255. LPI Contention Based Protocol Timing Plot - UNII 5 - 160MHz Channel 47 - Mid




Plot 7-1256. LPI Contention Based Protocol Timing Plot – UNII 5 – 160MHz Channel 47 – High

FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dog 200 of 404
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 326 of 464






Plot 7-1257. LPI Contention Based Protocol Timing Plot – UNII 6 – 20MHz Channel 101




Plot 7-1258. LPI Contention Based Protocol Timing Plot - UNII 6 - 160MHz Channel 111 - Low

FCC ID: BCGA2993	element	element MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N:	Test Dates:	EUT Type:	Dags 227 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 327 of 464






Plot 7-1259. LPI Contention Based Protocol Timing Plot - UNII 6 - 160MHz Channel 111 - Mid




Plot 7-1260. LPI Contention Based Protocol Timing Plot - UNII 6 - 160MHz Channel 111 - High

FCC ID: BCGA2993	element	element MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N:	Test Dates:	EUT Type:	Dogg 200 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 328 of 464






Plot 7-1261. LPI Contention Based Protocol Timing Plot – UNII 7 – 20MHz Channel 149




Plot 7-1262. LPI Contention Based Protocol Timing Plot – UNII 7 – 160MHz Channel 143 – Low

FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 220 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 329 of 464






Plot 7-1263. LPI Contention Based Protocol Timing Plot - UNII 7 - 160MHz Channel 143 - Mid




Plot 7-1264. LPI Contention Based Protocol Timing Plot – UNII 7 – 160MHz Channel 143 – High

FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogg 220 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 330 of 464






Plot 7-1265. LPI Contention Based Protocol Timing Plot - UNII 8 - 20MHz Channel 197




Plot 7-1266. LPI Contention Based Protocol Timing Plot – UNII 8 – 160MHz Channel 207 – Low

FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 224 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 331 of 464





Plot 7-1267. LPI Contention Based Protocol Timing Plot - UNII 8 - 160MHz Channel 207 - Mid




Plot 7-1268. LPI Contention Based Protocol Timing Plot - UNII 8 - 160MHz Channel 207 - High


FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogg 222 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 332 of 464



16:29:41 18.06.2024




Plot 7-1269. VLP Contention Based Protocol Timing Plot – UNII 5 – 20MHz Channel 53




Plot 7-1270. VLP Contention Based Protocol Timing Plot – UNII 5 – 160MHz Channel 47 – Low

FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dags 222 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 333 of 464






Plot 7-1271. VLP Contention Based Protocol Timing Plot – UNII 5 – 160MHz Channel 47 – Mid




Plot 7-1272. VLP Contention Based Protocol Timing Plot – UNII 5 – 160MHz Channel 47 – High

FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Daga 224 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 334 of 464





Plot 7-1273. VLP Contention Based Protocol Timing Plot – UNII 7 – 20MHz Channel 149




Plot 7-1274. VLP Contention Based Protocol Timing Plot – UNII 7 – 160MHz Channel 143 – Low


FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 225 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 335 of 464



16:19:57 18.06.2024



Plot 7-1275. VLP Contention Based Protocol Timing Plot – UNII 7 – 160MHz Channel 143 – Mid




Plot 7-1276. VLP Contention Based Protocol Timing Plot – UNII 7 – 160MHz Channel 143 – High


FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dags 226 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 336 of 464



CBP Bandwidth Reduction Plots



Plot 7-1277. 160MHz Bandwidth - Before AWGN Signal Injected - Channel 47




Plot 7-1278. 160MHz Bandwidth - AWGN Signal Injected at Low End - Channel 47


FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dags 227 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 337 of 464







Plot 7-1279. 160MHz Bandwidth - AWGN Signal Injected at Center - Channel 47



Plot 7-1280. 160MHz Bandwidth - AWGN Signal Injected at High End - Channel 47

FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dags 220 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 338 of 464



7.7 Radiated Spurious Emissions – Above 1GHz §15.407(b) §15.205 §15.209

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2020 and KDB 789033 D02 v02r01, and at the appropriate frequencies. All channels, modes (e.g. RU26, RU52, RU106, RU242, RU484, RU996 and RU996x2) and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

For transmitters operating in the 5.925-7.125 GHz band: All emissions outside of the 5.925-7.125 GHz band shall not exceed an EIRP of -27 dBm/MHz. Emissions found in a restricted band are subject to the limits of 15.209 as shown in the table below.

Frequency	Field Strength [µV/m]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-146. Radiated Limits

Test Procedures Used

ANSI C63.10-2020 – Sections 12.7.7.2, 12.7.6, 12.7.5 KDB 789033 D02 v02r01 – Section G

Test Settings

Average Field Strength Measurements

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = power average (RMS)
- 5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
- Averaging type = power (RMS)
- 7. Sweep time = auto couple
- 8. Trace was averaged over 100 sweeps

Peak Field Strength Measurements

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

FCC ID: BCGA2993 element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 339 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Fage 339 01 464



Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup

FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 240 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 340 of 464



Test Notes

- 1. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 are below the limit shown in Table 7-146.
- 2. All spurious emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 7-146. All spurious emissions that do not lie in a restricted band are subject to a limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBμV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dBμV/m.
- 3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
- 4. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas.
- 5. D is the measurement test distance and emissions 1-18GHz were measured at a 3 meters test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 6. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
- 7. All data rates were investigated and only the worse case is reported
- 8. The unit was tested with all possible modes and only the highest emission is reported.
- 9. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
- 10. All radiated measurements were tested at the highest supported power setting per band.

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level [dBμV/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- O AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB] Preamplifier Gain [dB]
- O Margin [dB] = Field Strength Level [dBμV/m] Limit [dBμV/m]

Radiated Band Edge Measurement Offset

The amplitude offset shown in the radiated restricted band edge plots in Section 7.7.4 to 7.7.15 was calculated using the formula:


Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) - Preamplifier Gain

FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dags 244 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 341 of 464



7.7.1 Antenna WF5T Radiated Spurious Emission

RU26



Plot 7-1281. Radiated Spurious Emissions above 1GHz Antenna WF5T (802.11ax - Ch. 1 - RU26)

Mode: 802.11ax

Data Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5955MHz


Channel: 1

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	11910.00	Average	V	-	ı	-85.58	20.24	41.66	53.98	-12.32
*	11910.00	Peak	V	-	ı	-74.00	20.24	53.24	73.98	-20.74
*	17865.00	Average	V	-	-	-81.56	17.94	43.38	53.98	-10.60
*	17865.00	Peak	V	-	-	-70.92	17.94	54.02	73.98	-19.96

Table 7-147. Radiated Spurious Emission Measurements Antenna WF5T – RU26

FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dags 242 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 342 of 464





Plot 7-1282. Radiated Spurious Emissions above 1GHz Antenna WF5T (802.11ax - Ch. 45 - RU26)

Mode: 802.11ax

Data Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 6175MHz


Channel: 45

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	12350.00	Average	Н	-	-	-85.78	21.25	42.46	53.98	-11.52
*	12350.00	Peak	Н	-	-	-74.44	21.09	53.65	73.98	-20.33

Table 7-148. Radiated Spurious Emission Measurements Antenna WF5T - RU26

FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dags 242 of 464	
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 343 of 464	





Plot 7-1283. Radiated Spurious Emissions above 1GHz Antenna WF5T (802.11ax - Ch. 93 - RU26)


Mode:802.11axData Rate:MCS0Distance of Measurements:3 MetersOperating Frequency:6415MHzChannel:93

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
12830.00	Average	Н	-	-	-85.81	22.36	43.54	68.23	-24.69
12830.00	Peak	Н	-	-	-74.49	22.36	54.87	88.23	-33.36

Table 7-149. Radiated Spurious Emission Measurements Antenna WF5T - RU26

FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 244 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 344 of 464





Plot 7-1284. Radiated Spurious Emissions above 1GHz Antenna WF5T (802.11ax - Ch. 97 - RU26)

Mode: 802.11ax

Data Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 6435MHz


Channel: 97

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
12870.00	Average	V	-	-	-85.62	22.00	43.38	68.23	-24.85
12870.00	Peak	V	-	-	-73.18	21.73	55.55	88.23	-32.68

Table 7-150. Radiated Spurious Emission Measurements Antenna WF5T - RU26

FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dogo 245 of 464	
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 345 of 464	





Plot 7-1285. Radiated Spurious Emissions above 1GHz Antenna WF5T (802.11ax - Ch. 105 - RU26)

Mode: 802.11ax

Data Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 6475MHz


Channel: 105

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
12950.00	Average	Н	-	-	-85.73	22.26	43.52	68.23	-24.71
12950.00	Peak	Н	-	-	-74.22	22.26	55.04	88.23	-33.19

Table 7-151. Radiated Spurious Emission Measurements Antenna WF5T - RU26

FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dags 246 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 346 of 464





Plot 7-1286. Radiated Spurious Emissions above 1GHz Antenna WF5T (802.11ax - Ch. 113 - RU26)


Mode:802.11axData Rate:MCS0Distance of Measurements:3 MetersOperating Frequency:6515MHzChannel:113

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
13030.00	Average	Н	-	-	-85.33	22.36	44.03	68.23	-24.20
13030.00	Peak	Н	-	-	-74.24	22.37	55.12	88.23	-33.11

Table 7-152. Radiated Spurious Emission Measurements Antenna WF5T - RU26

FCC ID: BCGA2993	element	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dags 247 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 347 of 464





Plot 7-1287. Radiated Spurious Emissions above 1GHz Antenna WF5T (802.11ax - Ch. 117 - RU26)

Mode: 802.11ax

Data Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 6535MHz


Channel: 117

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
13070.00	Average	Н	-	-	-85.27	22.20	43.94	68.23	-24.29
13070.00	Peak	Н	-	-	-74.81	22.20	54.39	88.23	-33.84

Table 7-153. Radiated Spurious Emission Measurements Antenna WF5T - RU26

FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dags 240 of 464	
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 348 of 464	





Plot 7-1288. Radiated Spurious Emissions above 1GHz Antenna WF5T (802.11ax - Ch. 149 - RU26)

Mode: 802.11ax

Data Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 6695MHz


Channel: 149

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
*	13390.00	Average	Н	-	-	-85.76	22.04	43.29	53.98	-10.69
*	13390.00	Peak	Н	-	-	-74.06	22.02	54.96	73.98	-19.02

Table 7-154. Radiated Spurious Emission Measurements Antenna WF5T - RU26

FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Daga 240 of 464
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 349 of 464





Plot 7-1289. Radiated Spurious Emissions above 1GHz Antenna WF5T (802.11ax - Ch. 185 - RU26)

Mode: 802.11ax

Data Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 6875MHz


Channel: 185

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
13750.00	Average	V	-	-	-86.17	21.80	42.63	68.23	-25.60
13750.00	Peak	V	-	-	-75.09	21.80	53.71	88.23	-34.52

Table 7-155. Radiated Spurious Emission Measurements Antenna WF5T – RU26

FCC ID: BCGA2993	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dogo 250 of 464	
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 350 of 464	





Plot 7-1290. Radiated Spurious Emissions above 1GHz Antenna WF5T (802.11ax - Ch. 189 - RU26)


Mode:802.11axData Rate:MCS0Distance of Measurements:3 MetersOperating Frequency:6895MHzChannel:189

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Δzimuth	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
13790.00	Average	Н	-	-	-86.09	22.00	42.91	68.23	-25.32
13790.00	Peak	Н	-	-	-74.74	22.00	54.26	88.23	-33.97

Table 7-156. Radiated Spurious Emission Measurements Antenna WF5T - RU26

FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Dags 254 of 464	
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 351 of 464	





Plot 7-1291. Radiated Spurious Emissions above 1GHz Antenna WF5T (802.11ax - Ch. 209 - RU26)


Mode:802.11axData Rate:MCS0Distance of Measurements:3 MetersOperating Frequency:6995MHzChannel:209

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
13990.00	Average	Н	-	-	-86.66	22.31	42.65	68.23	-25.58
13990.00	Peak	Н	-	-	-74.94	22.15	54.21	88.23	-34.02

Table 7-157. Radiated Spurious Emission Measurements Antenna WF5T - RU26

FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Daga 252 of 464	
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 352 of 464	





Plot 7-1292. Radiated Spurious Emissions above 1GHz Antenna WF5T (802.11ax - Ch. 229 - RU26)

Mode: 802.11ax

Data Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 7095MHz

Channel: 229

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
5322.00	Average	V	161	194	-63.37	15.59	59.22	68.23	-9.01
5322.00	Peak	V	161	194	-59.36	15.59	63.23	88.23	-25.00
14190.00	Average	Н	-	ı	-82.85	16.31	40.46	68.23	-27.77
14190.00	Peak	Н	-	-	-71.30	16.31	52.01	88.23	-36.22

Table 7-158. Radiated Spurious Emission Measurements Antenna WF5T - RU26

FCC ID: BCGA2993	element MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	Daga 252 of 464	
1C2405200017-14-R3.BCG	5/20/2024 - 10/1/2024	Tablet Device	Page 353 of 464	