

MEASUREMENT REPORT
FCC PART 15.407 UNII 802.11ax OFDMA WIFI 6E

Applicant Name:
 Apple Inc.
 One Apple Park Way
 Cupertino, CA 95014
 United States

Date of Testing:
 5/20/2024 - 10/1/2024
Test Report Issue Date:
 10/2/2024
Test Site/Location:
 Element Materials Technology, Morgan Hill, CA, USA
Test Report Serial No.:
 1C2405200018-25-R1.BCG


FCC ID:	BCGA2995
APPLICANT:	Apple Inc.

Application Type: Certification
Model: A2995, A2996
EUT Type: Tablet Device
Frequency Range: 5955 – 7115MHz
Modulation Type: OFDMA
FCC Classification: 15E 6GHz Low Power Dual Client (6CD)
 15E 6GHz Very Low Power Device (6VL)
FCC Rule Part(s): Part 15 Subpart E (15.407)
Test Procedure(s): ANSI C63.10-2020, KDB 789033 D02 v02r01
 KDB 662911 D01 v02r01, KDB 987594 D02 v02r01
 KDB 987594 D04 v02

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2020 and KDB 789033 D02 v02r01. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1C2405200018-25-R1.BCG) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.




RJ Ortanez
 Executive Vice President

Prepared by: WKR0000010245


Reviewed by: WKR0000005849




FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 1 of 693


T A B L E O F C O N T E N T S

1.0	INTRODUCTION	4
1.1	Scope	4
1.2	Element Materials Technology Test Location	4
1.3	Test Facility / Accreditations	4
2.0	PRODUCT INFORMATION	5
2.1	Equipment Description	5
2.2	Device Capabilities	5
2.3	Antenna Description	9
2.4	Test Support Equipment	9
2.5	Test Configuration	10
2.6	Software and Firmware	10
2.7	EMI Suppression Device(s)/Modifications	10
3.0	DESCRIPTION OF TESTS	11
3.1	Evaluation Procedure	11
3.2	AC Line Conducted Emissions	11
3.3	Radiated Emissions	12
3.4	Environmental Conditions	12
4.0	ANTENNA REQUIREMENTS	13
5.0	MEASUREMENT UNCERTAINTY	14
6.0	TEST EQUIPMENT CALIBRATION DATA	15
7.0	TEST RESULTS	16
7.1	Summary	16
7.2	26dB & 99% Bandwidth Measurement	18
7.3	Conducted Output Power and Max EIRP Measurement	106
7.4	Maximum Power Spectral Density	170
7.5	In-Band Emissions	334
7.6	Contention Based Protocol	464
7.7	Radiated Spurious Emissions – Above 1GHz	491
7.8	Radiated Spurious Emissions – Below 1GHz	670
7.9	AC Line-Conducted Emissions Measurement	677
7.10	Proper Power Adjustment, Client Devices Connected to a Standard Power Access Point	687
7.11	Dual Client Test, Demonstration of Proper Power Adjustment based on Associated AP	691
8.0	CONCLUSION	693

FCC ID: BCGA2995	 MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device
		Page 2 of 693



MEASUREMENT REPORT



UNII Band	Channel Bandwidth (MHz)	Mode	Tx Frequency (MHz)	SISO						SDM Primary		SDM Diversity	
				Antenna 5T		Antenna 3b		Antenna 1b		Summed		Summed	
				Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)	Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)	Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)	Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)	Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)
5	20	802.11ax	5955 - 6415	7.780	8.91	3.819	5.82	4.169	6.20	7.228	8.59	7.345	8.66
6		802.11ax	6435 - 6515	6.839	8.35	3.105	4.92	4.581	6.61	5.848	7.67	6.668	8.24
7		802.11ax	6535 - 6875	6.808	8.33	3.350	5.25	3.451	5.38	6.471	8.11	6.457	8.10
8		802.11ax	6895 - 7095	6.295	7.99	3.741	5.73	2.812	4.49	6.501	8.13	5.848	7.67
5	40	802.11ax	5965 - 6405	16.520	12.18	7.482	8.74	8.414	9.25	15.524	11.91	15.668	11.95
6		802.11ax	6445 - 6525	13.521	11.31	6.653	8.23	9.183	9.63	12.503	10.97	13.646	11.35
7		802.11ax	6565 - 6845	13.868	11.42	7.079	8.50	6.950	8.42	13.092	11.17	12.912	11.11
8		802.11ax	6885 - 7085	13.152	11.19	7.727	8.88	5.495	7.40	13.213	11.21	11.535	10.62
5	80	802.11ax	5985 - 6385	32.211	15.08	15.596	11.93	15.382	11.87	30.269	14.81	30.200	14.80
6		802.11ax	6465	26.122	14.17	11.588	10.64	17.378	12.40	23.014	13.62	26.607	14.25
7		802.11ax	6545 - 6865	27.925	14.46	14.093	11.49	13.646	11.35	26.485	14.23	25.704	14.10
8		802.11ax	6945 - 7025	26.546	14.24	15.311	11.85	10.990	10.41	26.485	14.23	23.442	13.70
5	160	802.11ax	6025 - 6345	53.827	17.31	26.607	14.25	30.200	14.80	51.168	17.09	54.325	17.35
6		802.11ax	6505	43.351	16.37	20.464	13.11	29.512	14.70	39.719	15.99	46.026	16.63
7		802.11ax	6665 - 6825	48.084	16.82	24.717	13.93	24.889	13.96	46.238	16.65	45.499	16.58
8		802.11ax	6985	45.814	16.61	26.062	14.16	18.923	12.77	44.566	16.49	41.687	16.20


EUT Overview – LPI Power

UNII Band	Channel Bandwidth (MHz)	Mode	Tx Frequency (MHz)	SISO						CDD Primary		CDD Diversity	
				Antenna 5T		Antenna 3b		Antenna 1b		Summed		Summed	
				Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)	Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)	Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)	Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)	Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)
5	20	802.11ax	5955 - 6415	147.231	21.68	68.865	18.38	72.444	18.60	291.743	24.65	289.734	24.62
7		802.11ax	6535 - 6855	139.959	21.46	72.111	18.58	68.391	18.35	272.898	24.36	271.644	24.34
5	40	802.11ax	5965 - 6405	147.231	21.68	71.779	18.56	75.509	18.78	289.734	24.62	289.068	24.61
7		802.11ax	6565 - 6845	139.959	21.46	71.614	18.55	70.632	18.49	276.058	24.41	271.644	24.34
5	80	802.11ax	5985 - 6385	146.218	21.65	71.779	18.56	75.509	18.78	291.072	24.64	284.446	24.54
7		802.11ax	6625 - 6785	138.676	21.42	71.285	18.53	70.146	18.46	279.898	24.47	272.898	24.36
5	160	802.11ax	6025 - 6345	143.549	21.57	72.444	18.60	75.509	18.78	289.068	24.61	291.072	24.64
7		802.11ax	6665	132.130	21.21	70.146	18.46	66.988	18.26	271.019	24.33	269.153	24.30

EUT Overview – Standard Power

UNII Band	Channel Bandwidth (MHz)	Mode	Tx Frequency (MHz)	SISO						SDM Primary		SDM Diversity	
				Antenna 5T		Antenna 3b		Antenna 1b		Summed		Summed	
				Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)	Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)	Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)	Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)	Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)
5	20	802.11ax	6115 - 6415	3.076	4.88	1.479	1.70	1.687	2.27	2.958	4.71	3.034	4.82
7		802.11ax	6535 - 6855	2.805	4.48	1.426	1.54	1.374	1.38	2.673	4.27	2.612	4.17
5	40	802.11ax	6125 - 6405	6.427	8.08	3.048	4.84	3.177	5.02	5.861	7.68	5.888	7.70
7		802.11ax	6565 - 6845	5.521	7.42	2.825	4.51	2.773	4.43	5.093	7.07	5.105	7.08
5	80	802.11ax	6145 - 6385	12.331	10.91	6.324	8.01	6.622	8.21	11.912	10.76	12.331	10.91
7		802.11ax	6625 - 6785	10.864	10.36	5.636	7.51	5.572	7.46	10.568	10.24	10.280	10.12
5	160	802.11ax	6185 - 6345	22.182	13.46	10.965	10.40	11.668	10.67	20.654	13.15	21.330	13.29
7		802.11ax	6665	19.861	12.98	9.886	9.95	9.354	9.71	17.742	12.49	17.701	12.48

EUT Overview – VLP Power

FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 3 of 693

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.


1.2 Element Materials Technology Test Location

These measurement tests were conducted at the Element Materials Technology facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element Materials Technology.

- Element Materials Technology is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Materials Technology facility is a registered (22831) test laboratory with the site description on file with ISED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

FCC ID: BCGA2995			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device		Page 4 of 693

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Tablet Device FCC ID: BCGA2995**. The test data contained in this report pertains only to the emissions due to the EUT's UNII transmitter while operating in the 6GHz band.

Test Device Serial No.: Y4D3WW1C9V, GW373NWX36, GXD3JTXYXM, J2DT9VW3FP, WH6226Y7R5, H9HH4U0007A0000R51

2.2 Device Capabilities

This device contains the following capabilities:

850/1700/1900 WCDMA/HSPA, Multi-band LTE, 5G NR (FR1), 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII, 802.11a/ax WIFI 6E, 802.15.4, Bluetooth (1x, EDR, LE1M, LE2M, HDR4, HDR8), NB UNII (1x, HDR4, HDR8), WPT

This device supports BT Beamforming.


Standard Power (SP) and Very Low Power (VLP) modes are supported in U-NII Bands 5 and 7, while Lower Power Indoor (LPI) mode is supported in U-NII Bands 5, 6, 7, and 8. Throughout the report, data is labeled as SP for Standard Power, LPI for Lower Power Indoor, and VLP for Very Low Power. VLP channels below 6105 MHz in the U-NII-5 band are disabled in the US and its territories.

Band 5		Band 6		Band 7		Band 8	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
1	5955	97	6435	117	6535	189	6895
:	:	:	:	:	:	:	:
45	6175	105	6475	149	6695	209	6995
:	:	:	:	:	:	:	:
93	6415	113	6515	185	6875	229	7095

Table 2-1. 802.11a / 802.11ax (20MHz) Frequency / Channel Operations

Band 5		Band 6		Band 7		Band 8	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
3	5965	99	6445	123	6565	187	6885
:	:	:	:	:	:	:	:
43	6165	107	6485	155	6725	211	7005
:	:	:	:	:	:	:	:
91	6405	115	6525	179	6845	227	7085

Table 2-2. 802.11ax (40MHz BW) Frequency / Channel Operations

FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 5 of 693

Band 5		Band 6		Band 7		Band 8	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
7	5985	103	6465	119	6545	199	6945
:	:			:	:	:	:
39	6145			151	6705	215	7025
:	:			:	:		
87	6385			183	6865		

Table 2-3. 802.11ax (80MHz BW) Frequency / Channel Operations

Band 5		Band 6		Band 7		Band 8	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
15	6025	111	6505	143	6665	207	6985
:	:			:	:		
47	6185			175	6825		
:	:						
79	6345						


Table 2-4. 802.11ax (160MHz BW) Frequency / Channel Operations

Notes:

1. 6GHz NII operation is possible in 20MHz, 40MHz, 80MHz and 160MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section B)2)b) KDB 789033 D02 v02r01 and ANSI C63.10-2020. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

802.11 Mode / Band		Duty Cycle [%]				
		Antenna 5T	Antenna 3b	Antenna 1b	CDD/SDM Primary	CDD/SDM Diversity
6GHz	11ax(RU26) (20MHz)	88.72	88.10	88.72	88.72	88.92
	11ax(RU242) (20MHz)	85.70	86.30	86.90	86.70	86.50
	11ax(RU26) (40MHz)	88.51	88.51	88.51	88.51	88.10
	11ax(RU484) (40MHz)	91.83	92.04	92.68	91.83	92.47
	11ax(RU26) (80MHz)	88.51	88.10	88.72	88.72	88.92
	11ax(RU996) (80MHz)	86.10	85.90	87.50	87.10	87.10
	11ax(RU26) (160MHz)	88.51	88.72	88.51	88.10	88.92
	11ax(RU996x2) (160MHz)	85.11	80.91	81.28	81.85	81.28

Table 2-5. Measured Duty Cycles

FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 6 of 693

2. The device employs MIMO technology. Below are the possible configurations.

WiFi Configurations		SISO			CDD			SDM			STBC		
		Antenna 5T	Antenna 3b	Antenna 1b	Antenna 5T	Antenna 3b	Antenna 1b	Antenna 5T	Antenna 3b	Antenna 1b	Antenna 5T	Antenna 3b	Antenna 1b
6GHz	11ax(RU) (20MHz)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	11ax(RU) (40MHz)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	11ax(RU) (80MHz)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	11ax(RU) (160MHz)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

Table 2-6. WIFI Configurations

✓ = Support ; ✗ = NOT Support

SISO = Single Input Single Output

SDM = Spatial Diversity Multiplexing – MIMO function


CDD = Cyclic Delay Diversity - 2Tx Function

STBC = Space-Time Block Coding – 2Tx Function

3. The device supports the following data rates (shown in Mbps):

MCS Index	Spatial Stream	MU-OFDMA (802.11ax)																				
		26-tone RU			52-tone RU			106-tone RU			242-tone RU			484-tone RU			996-tone RU			2x996-tone RU		
		0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI
0	1	0.9	0.8	0.8	1.8	1.7	1.5	3.8	3.5	3.2	8.6	8.1	7.3	17.2	16.3	14.6	36	34	30.6	72.1	68.1	61.3
1	1	1.8	1.7	1.5	3.5	3.3	3	7.5	7.1	6.4	17.2	16.3	14.6	34.4	32.5	29.3	72.1	68.1	61.3	144.1	136.1	122.5
2	1	2.6	2.5	2.3	5.3	5	4.5	11.3	10.6	9.6	25.8	24.4	21.9	51.6	48.8	43.9	108.1	102.1	91.9	216.2	204.2	183.8
3	1	3.5	3.3	3	7.1	6.7	6	15	14.2	12.8	34.4	32.5	29.3	68.8	65	58.5	144.1	136.1	122.5	288.2	272.2	245
4	1	5.3	5	4.5	10.6	10	9	22.5	21.3	19.1	51.6	48.8	43.9	103.2	97.5	87.8	216.2	204.2	183.8	432.4	408.3	367.5
5	1	7.1	6.7	6	14.1	13.3	12	30	28.3	25.5	68.8	65	58.5	137.6	130	117	288.2	272.2	245	576.5	544.4	490
6	1	7.9	7.5	6.8	15.9	15	13.5	33.8	31.9	28.7	77.4	73.1	65.8	154.9	146.3	131.6	324.3	306.3	275.6	648.5	612.5	551.3
7	1	8.8	8.3	7.5	17.6	16.7	15	37.5	35.4	31.9	86	81.3	73.1	172.1	162.5	146.3	360.3	340.3	306.3	720.6	680.6	612.5
8	1	10.6	10	9	21.2	20	18	45	42.5	38.3	103.2	97.5	87.8	206.5	195	175.5	432.4	408.3	367.5	864.7	816.7	735
9	1	11.8	11.1	10	23.5	22.2	20	50	47.2	42.5	114.7	108.3	97.5	229.4	216.7	195	480.4	453.7	408.3	960.8	907.4	816.7
10	1	13.2	12.5	11.3	26.5	25	22.5	56.3	53.1	47.8	129	121.9	109.7	258.1	243.8	219.4	540.4	510.4	459.4	1080.9	1020.8	918.8
11	1	14.7	13.9	12.5	29.4	27.8	25	62.5	59	53.1	143.4	135.4	121.9	286.8	270.8	243.8	600.5	567.1	510.4	1201	1134.3	1020.8
0	2	1.8	1.7	1.5	3.5	3.3	3	7.5	7.1	6.4	17.2	16.3	14.6	34.4	32.5	29.3	72.1	68.1	61.3	144.1	136.1	122.5
1	2	3.5	3.3	3	7.1	6.7	6	15	14.2	12.8	34.4	32.5	29.3	68.8	65	58.5	144.1	136.1	122.5	288.2	272.2	245
2	2	5.3	5	4.5	10.6	10	9	22.5	21.3	19.1	51.6	48.8	43.9	103.2	97.5	87.8	216.2	204.2	183.8	432.4	408.3	367.5
3	2	7.1	6.7	6	14.1	13.3	12	30	28.3	25.5	68.8	65	58.5	137.6	130	117	288.2	272.2	245	576.5	544.4	490
4	2	10.6	10	9	21.2	20	18	45	42.5	38.3	103.2	97.5	87.8	206.5	195	175.5	432.4	408.3	367.5	864.7	816.7	735
5	2	14.1	13.3	12	28.2	26.7	24	60	56.7	51	137.6	130	117	273.3	260	234	576.5	544.4	490	1152.9	1088.9	980
6	2	15.9	15	13.5	31.8	30	27	67.5	63.8	57.4	154.9	146.3	131.6	309.7	292.5	263.3	648.5	612.5	551.3	1297.1	1225	1102.5
7	2	17.6	16.7	15	35.3	33.3	30	75	70.8	63.8	172.1	162.5	146.3	344.1	325	292.5	720.6	680.6	612.5	1729.1	1225	1102.5
8	2	21.2	20	18	42.4	40	36	90	85	76.5	206.5	195	175.5	412.9	390	351	864.7	816.7	735	1729.4	1633.3	1470
9	2	23.5	22.2	20	47.1	44.4	40	100	94.4	85	229.4	216.7	195	458.8	433.3	390	960.8	907.4	816.7	1921.6	1814.8	1633.3
10	2	26.5	25	22.5	52.9	50	45	112.5	106.3	95.6	258.1	243.8	219.4	516.2	487.5	438.8	1080.9	1020.8	918.8	2161.8	2041.7	1837.5
11	2	29.4	27.8	25	58.8	55.6	50	125	118.1	106.3	286.8	270.8	243.8	573.5	541.7	487.5	1201	1134.3	1020.8	2402	2268.5	2041.7

Table 2-7. Supported Data Rates

FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 7 of 693

4. This device supports simultaneous transmission operations, which allows for multiple transmitters to transmit simultaneously on the same antenna. The table below shows all configurations possible.


Antenna	Simultaneous Tx Config	Bluetooth 2.4GHz	Thread	NB UNII	WLAN	WIFI 5GHz	WIFI 6GHz	LTE / FR1 NR		
		BDR, EDR, HDR4/8, LE1/2M	802.15.4	BDR, HDR4/8	802.11 b/g/n/ax	802.11 a/n/ac/ax	802.11 a/ax	LB	MB/HB	Ultra High Band
1a	Config 1	✓	✗	✗	✗	✗	✗	✗	✗	✓
1a	Config 2	✗	✗	✗	✓	✗	✗	✗	✗	✓
1a	Config 3	✗	✓	✗	✗	✗	✗	✗	✗	✓
1b	Config 4	✗	✗	✓	✗	✗	✗	✗	✓	✗
1b	Config 5	✗	✗	✗	✗	✓	✗	✗	✓	✗
1b	Config 6	✗	✗	✗	✗	✗	✓	✗	✓	✗
3a	Config 7	✗	✗	✗	✓	✗	✗	✗	✗	✓
3a	Config 8	✓	✗	✗	✗	✗	✗	✗	✗	✓
3a	Config 9	✗	✓	✗	✗	✗	✗	✗	✗	✓
3b	Config 10	✗	✗	✓	✗	✗	✗	✗	✓	✗
3b	Config 11	✗	✗	✗	✗	✓	✗	✗	✓	✗
3b	Config 12	✗	✗	✗	✗	✗	✓	✗	✓	✗
4	Config 13	✓	✗	✗	✗	✗	✗	✓	✗	✗
4	Config 14	✓	✗	✗	✗	✗	✗	✗	✓	✗
4	Config 15	✓	✗	✗	✗	✗	✗	✗	✗	✓
4	Config 16	✗	✓	✗	✗	✗	✗	✓	✗	✗
4	Config 17	✗	✓	✗	✗	✗	✗	✗	✓	✗
4	Config 18	✗	✓	✗	✗	✗	✗	✗	✗	✓

Table 2-8. Simultaneous Transmission Configurations

✓ = Support; ✗ = Not Support

All the above simultaneous transmission configurations have been tested and the worst-case configuration was found to be Config 14 and reported in RF Bluetooth and RF Part 27b.

5. Specific 2.4GHz Wi-Fi antenna that can only transmit simultaneously with 2.4GHz Bluetooth antenna is listed in the SAR test report. For BT (2.4GHz) in connected mode and Wi-Fi (2.4GHz) - Wi-Fi max power will not exceed minimum of (13.5dBm, SAR max cap, Reg max cap) power. For BT (2.4GHz) in disconnected mode and Wi-Fi (2.4GHz) - BT will be using iPA only and Wi-Fi max power will not exceed minimum of (13.5dBm SAR max cap, Reg max cap) power. Bluetooth can simultaneously transmit with IEEE 802.11a/n/ac/ax 5/6 GHz on separate antenna.

FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 8 of 693

2.3 Antenna Description

Following antenna gains were provided by the manufacturer.


UNII Band	Tx Frequency (MHz)	Highest Antenna Gain (dBi)			Lowest Antenna Gain (dBi)		
		Antenna 5T	Antenna 3b	Antenna 1b	Antenna 5T	Antenna 3b	Antenna 1b
5	5925 - 6415	3.7	0.6	0.8	2.8	-0.5	-0.4
6	6435 - 6515	3.1	-0.2	1.5	3.1	-0.2	1.5
7	6535 - 6875	3.5	0.6	0.5	2.8	-0.9	-0.9
8	6895 - 7115	3.3	0.9	-0.4	1.8	0.0	-1.1

Table 2-9. Antenna Gain

2.4 Test Support Equipment

1	Apple MacBook Pro w/AC/DC Adapter	Model: A2141 Model: A2166	S/N: C02H604EQ05D S/N: C4H042705ZNP0WA6
2	Apple USB-C Cable	Model: Spartan	S/N: GXK1336018XKTR024
3	USB-C Cable w/ AC Adapter	Model: A246C Model: A2305	S/N: DWH80115BK826GV19 S/N: C4H95160004PF4F4V
4	Apple Pencil	Model: A2538	S/N: KJ26TCFXJW
5	DC Power Supply	Model: KPS3010D	S/N: N/A
6	Netgear	Model: RAXE500	S/N: 6JX215GA10A5
7	Broadcom AP	Model: N/A	S/N: N/A

Table 2-10. Test Support Equipment List

FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 9 of 693

2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2020, KDB 789033 D02 v02r01 and KDB 987594 D02 v02r01. ANSI C63.10-2020 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, and 7.5 for antenna port conducted emissions test setups.

There are two vendors of the WiFi/Bluetooth radio modules, variant 1 and variant 2. Both radio modules have the same mechanical outline, same on-board antenna matching circuit, identical antenna structure, and are built and tested to conform to the same specifications and to operate within the same tolerances. The worst case configuration was found between the two variants. The EUT was also investigated with and without charger.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz and above 18GHz were tested with the highest transmitting power and the worst case channel.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

For AC line conducted and radiated test below 1GHz, the following configurations were investigated and the worst case was reported.

- EUT powered by AC/DC adaptor via USB-C cable with wire charger
- EUT powered by host PC via USB-C cable with wire charger


For 802.11ax-SU test results, see separate UNII 6E OFDM report, 1C2405200018-24.BCG.

2.6 Software and Firmware

The test was conducted with firmware version 22A312 installed on the EUT.

2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: BCGA2995	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 10 of 693

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2020) and the guidance provided in KDB 789033 D02 v02r01 were used in the measurement of the EUT.

Deviation from measurement procedure.....None


3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-6. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is EPCOS 2X60A Power Line Filter (100dB Attenuation, 14kHz-18GHz) and the two EPCOs 2X48A filters (100dB Minimum Insertion Loss, 14kHz - 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.9. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.50.40.

FCC ID: BCGA2995	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 11 of 693

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.


Per KDB 414788, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was used while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: BCGA2995	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 12 of 693

4.0 ANTENNA REQUIREMENTS


Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.


FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 13 of 693

V 10.6 10/27/2023

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	2.07
Line Conducted Disturbance	1.91
Radiated Disturbance (<30MHz)	4.12
Radiated Disturbance (30MHz - 1GHz)	4.85
Radiated Disturbance (1 - 18GHz)	5.08
Radiated Disturbance (>18GHz)	5.22

FCC ID: BCGA2995	 MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device
		Page 14 of 693

V 10.6 10/27/2023

6.0 TEST EQUIPMENT CALIBRATION DATA


Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Rohde & Schwarz	FSW67	Signal and Spectrum Analyzer (2Hz-67GHz)	7/5/2024	Annual	7/5/2025	101366
ATM	180-442A-KF	20dB Nominal Gain Horn Antenna	3/14/2024	Annual	3/14/2025	T058701-01
ESPEC	SU-241	Tabletop Temperature Chamber	11/17/2023	Annual	11/17/2024	92009574
ETS-Lindgren	3117	Double Ridged Guide Antenna (1-18 GHz)	4/9/2024	Annual	4/9/2025	00218555
Fairview Microwave	FMCA1975-36	30MHz-40GHz Conducted Cable *	6/10/2024	Annual	6/10/2025	-
Fairview Microwave/MCL	1975-36/BW-K10-	30MHz-40GHz Conducted Cable/Attenuator *	6/10/2024	Annual	6/10/2025	-
Keysight Technology	N9040B	UXA Signal Analyzer	5/28/2024	Annual	5/28/2025	MY57212015
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	8/15/2023	Annual	8/15/2024	101639
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	8/14/2024	Annual	8/15/2025	101648
Rohde & Schwarz	FSV40	Signal Analyzer (10Hz-40GHz)	5/29/2024	Annual	5/29/2025	101619
Rohde & Schwarz	ESW44	EMI Test Receiver	5/1/2024	Annual	5/1/2025	101867
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	7/3/2024	Annual	7/3/2025	102356
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	11/30/2023	Annual	11/30/2024	161616
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	12/27/2023	Annual	12/27/2024	164715
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	6/10/2024	Annual	6/10/2025	100057
Rohde & Schwarz	HFH2-Z2	Loop Antenna	6/21/2024	Annual	6/21/2025	100519
Rohde & Schwarz	ENV216	Two-Line V-Network	4/24/2024	Annual	4/24/2025	101364
Schwarzbeck	VULB 9162	Bilog Antenna (30MHz - 6GHz)	4/29/2024	Annual	4/29/2025	00304

Table 6-1. Test Equipment List

Note:

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. * denotes passive equipment that have been internally verified/calibrated.

FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 15 of 693


7.0 TEST RESULTS

7.1 Summary

Company Name: Apple Inc.
 FCC ID: BCGA2995
 FCC Classification: 15E 6GHz Low Power Dual Client (6CD)
15E 6GHz Very Low Power Device (6VL)


FCC Part Section(s) / KDB Reference	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049, 15.407(a)(10)	Occupied Bandwidth/ 26dB Bandwidth	99% of the occupied bandwidth of any channel must be contained within each of its respective U-NII sub bands < 320MHz (5.925 - 7.125GHz)	CONDUCTED	PASS	Section 7.2
15.407(a)(9)	Maximum Power Spectral Density	< -5dBm/MHz e.i.r.p.for Very Low Power		PASS	Section 7.4
15.407(a)(8)		< -1dBm/MHz e.i.r.p.for Low Power Indoor		PASS	
15.407(a)(7)		< 17dBm/MHz e.i.r.p. for Standard Power		PASS	
15.407(a)(9)	Maximum EIRP	< 14dBm over the frequency band of operation for Very Low Power		PASS	Section 7.3
15.407(a)(8)		< 24dBm over the frequency band of operation for Lower Power Indoor		PASS	
15.407(a)(7)		< 30dBm over the frequency band of operation for Standard Power		PASS	
15.407(b)(7)	In-Band Emissions	EUT must meet the limits detailed in 15.407(b)(7)		PASS	Section 7.5
15.407(d)(6)	Contention Based Protocol	EUT must detect AWGN signal with 90% (or better) certainty		PASS	Section 7.6
15.407(d.10)	Transmit Power Control	EUT must employ a TPC mechanism to operate 6dB below the maximum EIRP PSD detailed in 15.407 (a.9)		PASS	See UNII 6e OFDM Report (1C24052000 18-24)
15.407(a)(7)	Proper Power Adjustment, Client Devices Connected to a Standard Power Access Point	EUT maintains its power level at least 6 dB lower than that of the standard-power access point		PASS	Section 7.10
987594 D02 v02r01	Dual Client Test, Demonstration of Proper Power Adjustment based on Associated AP	EUT maximum power level shall not exceed 30dBm EIRP when connected to Standard Power AP, and 24dBm EIRP when connected to Low Power Indoor AP		PASS	Section 7.11
15.407(b)(6)	Undesirable Emissions	< -27dBm/MHz e.i.r.p. outside of the 5.925 – 7.125GHz band		RADIATED	PASS
15.205, 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	PASS		Section 7.7, 7.8
15.407(b)(8)	AC Conducted Emissions (150kHz – 30MHz)	< FCC 15.207 limits	LINE CONDUCTED	PASS	Section 7.9

Table 7-1. Summary of Test Results

FCC ID: BCGA2995	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 16 of 693

Notes:

- 1) All channels, modes, and modulations/data rates were investigated among all UNII bands. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Conducted Automation," Version 1.1.0.
- 5) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Chamber Automation," Version 3.0.0.
- 6) All radiated measurements were tested at the highest supported power setting per band.

FCC ID: BCGA2995	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 17 of 693

7.2 26dB & 99% Bandwidth Measurement

\$2.1049; \$15.407

Test Overview and Limit

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2020 and KDB 789033 D02 v02r01, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 26dB bandwidth.

Test Procedure Used

ANSI C63.10-2020 – Section 12.5.2
KDB 789033 D02 v02r01 – Section C

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 26. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold

Test Setup


The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

1. All antenna configurations, power modes and data rates were investigated and only the worst case are reported.
2. All RU's were investigated and only worst case partially-loaded and fully-loaded RU's were reported.
3. Low, mid, and high channels were tested and tabular data has been reported. Only mid channel bandwidth plots have been reported.


FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 18 of 693

V 10.6 10/27/2023

7.2.1 Antenna 5T SP 26dB & 99% Bandwidth Measurements


	Frequency [MHz]	Channel	802.11 MODE	RU Size	RU Index	Data Rate [Mbps]	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail
Band 5	5955	1	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.21	19.64	320	Pass
	5955	1	ax (20MHz)	26	4	12.5/14.7 (MCS11)	17.03	18.14	320	Pass
	5955	1	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.33	19.62	320	Pass
	6175	45	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.25	19.59	320	Pass
	6175	45	ax (20MHz)	26	4	12.5/14.7 (MCS11)	17.04	18.19	320	Pass
	6175	45	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.29	19.58	320	Pass
	6415	93	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.24	19.60	320	Pass
	6415	93	ax (20MHz)	26	4	12.5/14.7 (MCS11)	17.01	18.10	320	Pass
	6415	93	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.32	19.52	320	Pass
	5965	3	ax (40MHz)	26	0	12.5/14.7 (MCS11)	18.13	19.59	320	Pass
	5965	3	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.90	21.34	320	Pass
	5965	3	ax (40MHz)	26	17	12.5/14.7 (MCS11)	18.23	19.73	320	Pass
	6165	43	ax (40MHz)	26	0	12.5/14.7 (MCS11)	18.07	19.59	320	Pass
	6165	43	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.94	22.44	320	Pass
	6165	43	ax (40MHz)	26	17	12.5/14.7 (MCS11)	18.23	19.89	320	Pass
	6405	91	ax (40MHz)	26	0	12.5/14.7 (MCS11)	18.03	19.56	320	Pass
	6405	91	ax (40MHz)	26	8	12.5/14.7 (MCS11)	20.02	21.92	320	Pass
	6405	91	ax (40MHz)	26	17	12.5/14.7 (MCS11)	18.22	19.77	320	Pass
	5985	7	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.10	19.62	320	Pass
	5985	7	ax (80MHz)	26	18	12.5/14.7 (MCS11)	37.14	38.52	320	Pass
	5985	7	ax (80MHz)	26	36	12.5/14.7 (MCS11)	18.17	19.64	320	Pass
	6145	39	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.04	19.52	320	Pass
	6145	39	ax (80MHz)	26	18	12.5/14.7 (MCS11)	37.07	38.57	320	Pass
	6145	39	ax (80MHz)	26	36	12.5/14.7 (MCS11)	18.12	19.47	320	Pass
	6385	87	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.02	19.47	320	Pass
	6385	87	ax (80MHz)	26	18	12.5/14.7 (MCS11)	37.20	38.55	320	Pass
	6385	87	ax (80MHz)	26	36	12.5/14.7 (MCS11)	18.21	19.66	320	Pass
	6025	15 (L)	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.47	20.77	320	Pass
	6025		ax (160MHz)	26	36	12.5/14.7 (MCS11)	21.23	23.26	320	Pass
	6025	15 (U)	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.78	20.78	320	Pass
	6185	47 (L)	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.54	20.35	320	Pass
	6185		ax (160MHz)	26	36	12.5/14.7 (MCS11)	21.36	23.11	320	Pass
	6185	47 (U)	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.70	20.80	320	Pass
	6345	79 (L)	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.48	20.36	320	Pass
6345	ax (160MHz)		26	36	12.5/14.7 (MCS11)	21.43	23.26	320	Pass	
6345	79 (U)	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.87	20.93	320	Pass	
Band 7	6535	117	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.27	19.67	320	Pass
	6535	117	ax (20MHz)	26	4	12.5/14.7 (MCS11)	17.02	18.10	320	Pass
	6535	117	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.34	19.64	320	Pass
	6695	149	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.25	19.61	320	Pass
	6695	149	ax (20MHz)	26	4	12.5/14.7 (MCS11)	17.02	18.25	320	Pass
	6695	149	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.32	19.56	320	Pass
	6855	181	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.23	19.53	320	Pass
	6855	181	ax (20MHz)	26	4	12.5/14.7 (MCS11)	17.02	18.11	320	Pass
	6855	181	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.32	19.61	320	Pass
	6565	123	ax (40MHz)	26	0	12.5/14.7 (MCS11)	18.03	19.80	320	Pass
	6565	123	ax (40MHz)	26	8	12.5/14.7 (MCS11)	20.01	22.41	320	Pass
	6565	123	ax (40MHz)	26	17	12.5/14.7 (MCS11)	18.22	19.85	320	Pass
	6725	155	ax (40MHz)	26	0	12.5/14.7 (MCS11)	18.05	19.69	320	Pass
	6725	155	ax (40MHz)	26	8	12.5/14.7 (MCS11)	20.05	21.96	320	Pass
	6725	155	ax (40MHz)	26	17	12.5/14.7 (MCS11)	18.22	20.10	320	Pass
	6845	179	ax (40MHz)	26	0	12.5/14.7 (MCS11)	18.08	19.52	320	Pass
	6845	179	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.70	21.83	320	Pass
	6845	179	ax (40MHz)	26	17	12.5/14.7 (MCS11)	18.20	19.80	320	Pass
	6625	135	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.03	19.30	320	Pass
	6625	135	ax (80MHz)	26	18	12.5/14.7 (MCS11)	37.24	38.73	320	Pass
	6625	135	ax (80MHz)	26	36	12.5/14.7 (MCS11)	18.16	19.62	320	Pass
	6705	151	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.11	19.50	320	Pass
	6705	151	ax (80MHz)	26	18	12.5/14.7 (MCS11)	37.34	38.67	320	Pass
	6705	151	ax (80MHz)	26	36	12.5/14.7 (MCS11)	18.16	19.68	320	Pass
	6785	167	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.96	19.44	320	Pass
	6785	167	ax (80MHz)	26	18	12.5/14.7 (MCS11)	37.18	38.55	320	Pass
	6785	167	ax (80MHz)	26	36	12.5/14.7 (MCS11)	18.24	19.57	320	Pass
	6665	143 (L)	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.33	20.21	320	Pass
	6665		ax (160MHz)	26	36	12.5/14.7 (MCS11)	21.85	23.77	320	Pass
	6665	143 (U)	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.96	21.02	320	Pass


Table 7-2. Conducted Bandwidth Measurements Antenna 5T SP (RU26)

FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 19 of 693


	Frequency [MHz]	Channel	802.11 MODE	RU Size	RU Index	Data Rate [Mbps]	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail
Band 5	5955	1	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.04	21.34	320	Pass
	6175	45	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.02	21.06	320	Pass
	6415	93	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.05	21.25	320	Pass
	5965	3	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.97	41.39	320	Pass
	6165	43	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.94	41.51	320	Pass
	6405	91	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.98	41.12	320	Pass
	5985	7	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.24	82.50	320	Pass
	6145	39	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.28	82.74	320	Pass
	6385	87	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.32	82.59	320	Pass
	6025	15	ax (160MHz)	996x2	68	1020.8/1201 (MCS11)	158.33	304.66	320	Pass
Band 7	6185	47	ax (160MHz)	996x2	68	1020.8/1201 (MCS11)	159.02	307.01	320	Pass
	6345	79	ax (160MHz)	996x2	68	1020.8/1201 (MCS11)	158.52	304.82	320	Pass
	6535	117	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.01	21.10	320	Pass
	6695	149	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.06	21.19	320	Pass
	6855	181	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.06	21.30	320	Pass
	6565	123	ax (40MHz)	484	65	243.8/286.8 (MCS11)	38.01	41.40	320	Pass
	6725	155	ax (40MHz)	484	65	243.8/286.8 (MCS11)	38.02	41.38	320	Pass
	6845	179	ax (40MHz)	484	65	243.8/286.8 (MCS11)	38.12	41.53	320	Pass
	6625	135	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.30	83.10	320	Pass
	6705	151	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.42	98.97	320	Pass
6785	167	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.46	99.04	320	Pass	
6665	143	ax (160MHz)	996x2	68	1020.8/1201 (MCS11)	158.92	304.82	320	Pass	

Table 7-3. Conducted Bandwidth Measurements Antenna 5T SP (Fully – Loaded RU)


FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 20 of 693




Plot 7-1. 26dB & 99% Bandwidth Plot Antenna 5T SP (20MHz 802.11ax RU26 (UNII Band 5) – Ch. 45)




Plot 7-4. 26dB & 99% Bandwidth Plot Antenna 5T SP (20MHz 802.11ax RU242 (UNII Band 5) – Ch. 45)




Plot 7-2. 26dB & 99% Bandwidth Plot Antenna 5T SP (20MHz 802.11ax RU26 (UNII Band 5) – Ch. 45)



Plot 7-5. 26dB & 99% Bandwidth Plot Antenna 5T SP (40MHz 802.11ax RU26 (UNII Band 5) – Ch. 43)




Plot 7-3. 26dB & 99% Bandwidth Plot Antenna 5T SP (20MHz 802.11ax RU26 (UNII Band 5) – Ch. 45)




Plot 7-6. 26dB & 99% Bandwidth Plot Antenna 5T SP (40MHz 802.11ax RU26 (UNII Band 5) – Ch. 43)


FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 21 of 693




Plot 7-7. 26dB & 99% Bandwidth Plot Antenna 5T SP (40MHz 802.11ax RU26 (UNII Band 5) – Ch. 43)




Plot 7-10. 26dB & 99% Bandwidth Plot Antenna 5T SP (80MHz 802.11ax RU26 (UNII Band 5) – Ch. 39)




Plot 7-8. 26dB & 99% Bandwidth Plot Antenna 5T SP (40MHz 802.11ax RU484 (UNII Band 5) – Ch. 43)



Plot 7-11. 26dB & 99% Bandwidth Plot Antenna 5T SP (80MHz 802.11ax RU26 (UNII Band 5) – Ch. 39)




Plot 7-9. 26dB & 99% Bandwidth Plot Antenna 5T SP (80MHz 802.11ax RU26 (UNII Band 5) – Ch. 39)




Plot 7-12. 26dB & 99% Bandwidth Plot Antenna 5T SP (80MHz 802.11ax RU996 (UNII Band 5) – Ch. 39)


FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 22 of 693




Plot 7-13. 26dB & 99% Bandwidth Plot Antenna 5T SP (160MHz 802.11ax RU26 (UNII Band 5) – Ch. 47)




Plot 7-16. 26dB & 99% Bandwidth Plot Antenna 5T SP (160MHz 802.11ax RU996x2 (UNII Band 5) – Ch. 47)




Plot 7-14. 26dB & 99% Bandwidth Plot Antenna 5T SP (160MHz 802.11ax RU26 (UNII Band 5) – Ch. 47)



Plot 7-17. 26dB & 99% Bandwidth Plot Antenna 5T SP (20MHz 802.11ax RU26 (UNII Band 7) – Ch. 149)




Plot 7-15. 26dB & 99% Bandwidth Plot Antenna 5T SP (160MHz 802.11ax RU26 (UNII Band 5) – Ch. 47)




Plot 7-18. 26dB & 99% Bandwidth Plot Antenna 5T SP (20MHz 802.11ax RU26 (UNII Band 7) – Ch. 149)


FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 23 of 693




Plot 7-19. 26dB & 99% Bandwidth Plot Antenna 5T SP (20MHz 802.11ax RU26 (UNII Band 7) – Ch. 149)




Plot 7-22. 26dB & 99% Bandwidth Plot Antenna 5T SP (40MHz 802.11ax RU26 (UNII Band 7) – Ch. 155)




Plot 7-20. 26dB & 99% Bandwidth Plot Antenna 5T SP (20MHz 802.11ax RU242 (UNII Band 7) – Ch. 149)



Plot 7-23. 26dB & 99% Bandwidth Plot Antenna 5T SP (40MHz 802.11ax RU26 (UNII Band 7) – Ch. 155)




Plot 7-21. 26dB & 99% Bandwidth Plot Antenna 5T SP (40MHz 802.11ax RU26 (UNII Band 7) – Ch. 155)




Plot 7-24. 26dB & 99% Bandwidth Plot Antenna 5T SP (40MHz 802.11ax RU484 (UNII Band 7) – Ch. 155)


FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 24 of 693




Plot 7-25. 26dB & 99% Bandwidth Plot Antenna 5T SP (80MHz 802.11ax RU26 (UNII Band 7) – Ch. 151)




Plot 7-28. 26dB & 99% Bandwidth Plot Antenna 5T SP (80MHz 802.11ax RU996 (UNII Band 7) – Ch. 151)




Plot 7-26. 26dB & 99% Bandwidth Plot Antenna 5T SP (80MHz 802.11ax RU26 (UNII Band 7) – Ch. 151)



Plot 7-29. 26dB & 99% Bandwidth Plot Antenna 5T SP (160MHz 802.11ax RU26 (UNII Band 7) – Ch. 143)




Plot 7-27. 26dB & 99% Bandwidth Plot Antenna 5T SP (80MHz 802.11ax RU26 (UNII Band 7) – Ch. 151)




Plot 7-30. 26dB & 99% Bandwidth Plot Antenna 5T SP (160MHz 802.11ax RU26 (UNII Band 7) – Ch. 143)

FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 25 of 693



Plot 7-31. 26dB & 99% Bandwidth Plot Antenna 5T SP (160MHz 802.11ax RU26 (UNII Band 7) – Ch. 143)




Plot 7-32. 26dB & 99% Bandwidth Plot Antenna 5T SP (160MHz 802.11ax RU996x2 (UNII Band 7) – Ch. 143)

FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 26 of 693

7.2.2 Antenna 3b SP 26dB & 99% Bandwidth Measurements


	Frequency [MHz]	Channel	802.11 MODE	RU Size	RU Index	Data Rate [Mbps]	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail
Band 5	5955	1	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.26	19.52	320	Pass
	5955	1	ax (20MHz)	26	4	12.5/14.7 (MCS11)	17.03	18.12	320	Pass
	5955	1	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.29	19.50	320	Pass
	6175	45	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.23	19.68	320	Pass
	6175	45	ax (20MHz)	26	4	12.5/14.7 (MCS11)	17.05	18.23	320	Pass
	6175	45	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.33	19.62	320	Pass
	6415	93	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.24	19.57	320	Pass
	6415	93	ax (20MHz)	26	4	12.5/14.7 (MCS11)	17.00	18.11	320	Pass
	6415	93	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.36	19.56	320	Pass
	5965	3	ax (40MHz)	26	0	12.5/14.7 (MCS11)	18.06	19.65	320	Pass
	5965	3	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.81	22.22	320	Pass
	5965	3	ax (40MHz)	26	17	12.5/14.7 (MCS11)	18.15	19.84	320	Pass
	6165	43	ax (40MHz)	26	0	12.5/14.7 (MCS11)	18.07	19.72	320	Pass
	6165	43	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.70	21.90	320	Pass
	6165	43	ax (40MHz)	26	17	12.5/14.7 (MCS11)	18.20	19.82	320	Pass
	6405	91	ax (40MHz)	26	0	12.5/14.7 (MCS11)	18.05	19.60	320	Pass
	6405	91	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.74	21.88	320	Pass
	6405	91	ax (40MHz)	26	17	12.5/14.7 (MCS11)	18.25	20.18	320	Pass
	5985	7	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.18	19.88	320	Pass
	5985	7	ax (80MHz)	26	18	12.5/14.7 (MCS11)	37.20	38.62	320	Pass
	5985	7	ax (80MHz)	26	36	12.5/14.7 (MCS11)	18.14	19.68	320	Pass
	6145	39	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.19	19.71	320	Pass
	6145	39	ax (80MHz)	26	18	12.5/14.7 (MCS11)	37.26	38.62	320	Pass
	6145	39	ax (80MHz)	26	36	12.5/14.7 (MCS11)	18.17	19.79	320	Pass
	6385	87	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.01	19.56	320	Pass
	6385	87	ax (80MHz)	26	18	12.5/14.7 (MCS11)	37.28	38.51	320	Pass
	6385	87	ax (80MHz)	26	36	12.5/14.7 (MCS11)	18.15	19.57	320	Pass
	6025	15 (L)	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.55	20.48	320	Pass
	6025		ax (160MHz)	26	36	12.5/14.7 (MCS11)	21.85	24.09	320	Pass
	6025	15 (U)	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.76	20.78	320	Pass
	6185	47 (L)	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.43	20.33	320	Pass
	6185		ax (160MHz)	26	36	12.5/14.7 (MCS11)	21.16	23.40	320	Pass
	6185	47 (U)	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.84	20.94	320	Pass
6345	79 (L)	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.49	20.47	320	Pass	
6345		ax (160MHz)	26	36	12.5/14.7 (MCS11)	20.91	23.30	320	Pass	
6345	79 (U)	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.83	20.98	320	Pass	
Band 7	6535	117	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.26	19.59	320	Pass
	6535	117	ax (20MHz)	26	4	12.5/14.7 (MCS11)	17.00	18.05	320	Pass
	6535	117	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.30	19.53	320	Pass
	6695	149	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.25	19.65	320	Pass
	6695	149	ax (20MHz)	26	4	12.5/14.7 (MCS11)	17.04	18.20	320	Pass
	6695	149	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.30	19.56	320	Pass
	6855	181	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.21	19.64	320	Pass
	6855	181	ax (20MHz)	26	4	12.5/14.7 (MCS11)	17.03	18.12	320	Pass
	6855	181	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.30	19.54	320	Pass
	6565	123	ax (40MHz)	26	0	12.5/14.7 (MCS11)	18.05	19.86	320	Pass
	6565	123	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.74	21.62	320	Pass
	6565	123	ax (40MHz)	26	17	12.5/14.7 (MCS11)	18.19	19.66	320	Pass
	6725	155	ax (40MHz)	26	0	12.5/14.7 (MCS11)	18.09	19.69	320	Pass
	6725	155	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.98	22.45	320	Pass
	6725	155	ax (40MHz)	26	17	12.5/14.7 (MCS11)	18.22	19.85	320	Pass
	6845	179	ax (40MHz)	26	0	12.5/14.7 (MCS11)	18.05	19.78	320	Pass
	6845	179	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.89	22.51	320	Pass
	6845	179	ax (40MHz)	26	17	12.5/14.7 (MCS11)	18.19	19.59	320	Pass
	6625	135	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.07	19.62	320	Pass
	6625	135	ax (80MHz)	26	18	12.5/14.7 (MCS11)	37.40	38.69	320	Pass
	6625	135	ax (80MHz)	26	36	12.5/14.7 (MCS11)	18.15	19.58	320	Pass
	6705	151	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.00	19.52	320	Pass
	6705	151	ax (80MHz)	26	18	12.5/14.7 (MCS11)	37.21	38.74	320	Pass
	6705	151	ax (80MHz)	26	36	12.5/14.7 (MCS11)	18.22	19.66	320	Pass
	6785	167	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.04	19.51	320	Pass
	6785	167	ax (80MHz)	26	18	12.5/14.7 (MCS11)	37.29	38.58	320	Pass
	6785	167	ax (80MHz)	26	36	12.5/14.7 (MCS11)	18.17	19.64	320	Pass
	6665	143 (L)	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.39	19.93	320	Pass
	6665		ax (160MHz)	26	36	12.5/14.7 (MCS11)	21.52	23.27	320	Pass
	6665	143 (U)	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.95	21.36	320	Pass


Table 7-4. Conducted Bandwidth Measurements Antenna 3b SP (RU26)

FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 27 of 693


	Frequency [MHz]	Channel	802.11 MODE	RU Size	RU Index	Data Rate [Mbps]	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail	
Band 5	5955	1	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.07	21.46	320	Pass	
	6175	45	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.08	21.05	320	Pass	
	6415	93	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.04	21.16	320	Pass	
	5965	3	ax (40MHz)	484	65	243.8/286.8 (MCS11)	38.20	45.80	320	Pass	
	6165	43	ax (40MHz)	484	65	243.8/286.8 (MCS11)	38.11	41.83	320	Pass	
	6405	91	ax (40MHz)	484	65	243.8/286.8 (MCS11)	38.00	41.42	320	Pass	
	5985	7	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.38	99.30	320	Pass	
	6145	39	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.41	82.69	320	Pass	
	6385	87	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.32	98.56	320	Pass	
	6025	15	ax (160MHz)	996x2	68	1020.8/1201 (MCS11)	158.94	310.99	320	Pass	
	6185	47	ax (160MHz)	996x2	68	1020.8/1201 (MCS11)	159.62	308.04	320	Pass	
	6345	79	ax (160MHz)	996x2	68	1020.8/1201 (MCS11)	159.46	308.17	320	Pass	
	Band 7	6535	117	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.02	21.28	320	Pass
		6695	149	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.04	21.45	320	Pass
6855		181	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.07	21.39	320	Pass	
6565		123	ax (40MHz)	484	65	243.8/286.8 (MCS11)	38.12	41.52	320	Pass	
6725		155	ax (40MHz)	484	65	243.8/286.8 (MCS11)	38.15	47.82	320	Pass	
6845		179	ax (40MHz)	484	65	243.8/286.8 (MCS11)	38.25	59.88	320	Pass	
6625		135	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.35	99.46	320	Pass	
6705		151	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.50	99.39	320	Pass	
6785		167	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.59	100.13	320	Pass	
6665		143	ax (160MHz)	996x2	68	1020.8/1201 (MCS11)	159.18	306.65	320	Pass	

Table 7-5. Conducted Bandwidth Measurements Antenna 3b SP (Fully – Loaded RU)


FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 28 of 693




Plot 7-33. 26dB & 99% Bandwidth Plot Antenna 3b SP (20MHz 802.11ax RU26 (UNII Band 5) – Ch. 45)




Plot 7-36. 26dB & 99% Bandwidth Plot Antenna 3b SP (20MHz 802.11ax RU242 (UNII Band 5) – Ch. 45)




Plot 7-34. 26dB & 99% Bandwidth Plot Antenna 3b SP (20MHz 802.11ax RU26 (UNII Band 5) – Ch. 45)



Plot 7-37. 26dB & 99% Bandwidth Plot Antenna 3b SP (40MHz 802.11ax RU26 (UNII Band 5) – Ch. 43)




Plot 7-35. 26dB & 99% Bandwidth Plot Antenna 3b SP (20MHz 802.11ax RU26 (UNII Band 5) – Ch. 45)




Plot 7-38. 26dB & 99% Bandwidth Plot Antenna 3b SP (40MHz 802.11ax RU26 (UNII Band 5) – Ch. 43)


FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 29 of 693




Plot 7-39. 26dB & 99% Bandwidth Plot Antenna 3b SP (40MHz 802.11ax RU26 (UNII Band 5) – Ch. 43)




Plot 7-42. 26dB & 99% Bandwidth Plot Antenna 3b SP (80MHz 802.11ax RU26 (UNII Band 5) – Ch. 39)




Plot 7-40. 26dB & 99% Bandwidth Plot Antenna 3b SP (40MHz 802.11ax RU484 (UNII Band 5) – Ch. 43)



Plot 7-43. 26dB & 99% Bandwidth Plot Antenna 3b SP (80MHz 802.11ax RU26 (UNII Band 5) – Ch. 39)




Plot 7-41. 26dB & 99% Bandwidth Plot Antenna 3b SP (80MHz 802.11ax RU26 (UNII Band 5) – Ch. 39)




Plot 7-44. 26dB & 99% Bandwidth Plot Antenna 3b SP (80MHz 802.11ax RU996 (UNII Band 5) – Ch. 39)


FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 30 of 693




Plot 7-45. 26dB & 99% Bandwidth Plot Antenna 3b SP (160MHz 802.11ax RU26 (UNII Band 5) – Ch. 47)




Plot 7-48. 26dB & 99% Bandwidth Plot Antenna 3b SP (160MHz 802.11ax RU996x2 (UNII Band 5) – Ch. 47)




Plot 7-46. 26dB & 99% Bandwidth Plot Antenna 3b SP (160MHz 802.11ax RU26 (UNII Band 5) – Ch. 47)



Plot 7-49. 26dB & 99% Bandwidth Plot Antenna 3b SP (20MHz 802.11ax RU26 (UNII Band 7) – Ch. 149)




Plot 7-47. 26dB & 99% Bandwidth Plot Antenna 3b SP (160MHz 802.11ax RU26 (UNII Band 5) – Ch. 47)




Plot 7-50. 26dB & 99% Bandwidth Plot Antenna 3b SP (20MHz 802.11ax RU26 (UNII Band 7) – Ch. 149)


FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 31 of 693




Plot 7-51. 26dB & 99% Bandwidth Plot Antenna 3b SP (20MHz 802.11ax RU26 (UNII Band 7) – Ch. 149)




Plot 7-54. 26dB & 99% Bandwidth Plot Antenna 3b SP (40MHz 802.11ax RU26 (UNII Band 7) – Ch. 155)




Plot 7-52. 26dB & 99% Bandwidth Plot Antenna 3b SP (20MHz 802.11ax RU242 (UNII Band 7) – Ch. 149)



Plot 7-55. 26dB & 99% Bandwidth Plot Antenna 3b SP (40MHz 802.11ax RU26 (UNII Band 7) – Ch. 155)



Plot 7-53. 26dB & 99% Bandwidth Plot Antenna 3b SP (40MHz 802.11ax RU26 (UNII Band 7) – Ch. 155)



Plot 7-56. 26dB & 99% Bandwidth Plot Antenna 3b SP (40MHz 802.11ax RU484 (UNII Band 7) – Ch. 155)

FCC ID: BCGA2995		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2405200018-25-R1.BCG	Test Dates: 5/20/2024 - 10/1/2024	EUT Type: Tablet Device	Page 32 of 693