






Apple Keyboard Antenna Gain Plots

Model: A3118



BT 2.4 GHz Plots

Frequency (MHz)	
2402	<p data-bbox="911 390 1081 411">Max(H,V) (Theta 135.0)</p>  <p>A polar plot showing the radiation pattern for 2402 MHz. The plot is circular with concentric grid lines representing signal strength. The angular axis is labeled from 0° to 315° in 45° increments. A red line traces the radiation pattern, showing a primary lobe pointing towards 135° and a secondary lobe pointing towards 45°. The plot is titled 'Max(H,V) (Theta 135.0)'.</p>
2441	<p data-bbox="911 760 1081 781">Max(H,V) (Theta 135.0)</p>  <p>A polar plot showing the radiation pattern for 2441 MHz. The plot is circular with concentric grid lines representing signal strength. The angular axis is labeled from 0° to 315° in 45° increments. A red line traces the radiation pattern, showing a primary lobe pointing towards 135° and a secondary lobe pointing towards 45°. The plot is titled 'Max(H,V) (Theta 135.0)'.</p>
2480	<p data-bbox="911 1129 1081 1150">Max(H,V) (Theta 135.0)</p>  <p>A polar plot showing the radiation pattern for 2480 MHz. The plot is circular with concentric grid lines representing signal strength. The angular axis is labeled from 0° to 315° in 45° increments. A red line traces the radiation pattern, showing a primary lobe pointing towards 135° and a secondary lobe pointing towards 45°. The plot is titled 'Max(H,V) (Theta 135.0)'.</p>