



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	-		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU26 LPI	Duty Cycle (%):	97.3
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.12
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.85
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU26.0)	-	-4.36	-	-	-4.36	0.71	-3.65	-1.00	-2.65
6175 (RU26.0)	-	-4.91	-	-	-4.91	1.37	-3.54	-1.00	-2.54
6415 (RU26.8)	-	-5.72	-	-	-5.72	1.63	-4.09	-1.00	-3.09
6435 (RU26.0)	-	-5.18	-	-	-5.18	1.37	-3.81	-1.00	-2.81
6475 (RU26.0)	-	-5.32	-	-	-5.32	1.37	-3.95	-1.00	-2.95
6515 (RU26.8)	-	-4.62	-	-	-4.62	1.37	-3.25	-1.00	-2.25
6535 (RU26.0)	-	-5.42	-	-	-5.42	1.62	-3.80	-1.00	-2.80
6695 (RU26.0)	-	-5.33	-	-	-5.33	1.62	-3.71	-1.00	-2.71
6855 (RU26.8)	-	-5.27	-	-	-5.27	1.62	-3.65	-1.00	-2.65
6875 (RU26.3)	-	-5.66	-	-	-5.66	1.62	-4.04	-1.00	-3.04
6875 (RU26.5)	-	-5.51	-	-	-5.51	1.85	-3.66	-1.00	-2.66
6895 (RU26.0)	-	-5.46	-	-	-5.46	1.85	-3.61	-1.00	-2.61
6995 (RU26.0)	-	-5.68	-	-	-5.68	1.85	-3.83	-1.00	-2.83
7095 (RU26.8)	-	-5.68	-	-	-5.68	1.85	-3.83	-1.00	-2.83

Table 195 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	-		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU52 LPI	Duty Cycle (%):	97.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.13
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.85
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU52.37)	-	-3.86	-	-	-3.86	0.71	-3.15	-1.00	-2.15
6175 (RU52.37)	-	-4.40	-	-	-4.40	1.37	-3.03	-1.00	-2.03
6415 (RU52.40)	-	-4.99	-	-	-4.99	1.63	-3.36	-1.00	-2.36
6435 (RU52.37)	-	-4.40	-	-	-4.40	1.37	-3.03	-1.00	-2.03
6475 (RU52.37)	-	-4.55	-	-	-4.55	1.37	-3.18	-1.00	-2.18
6515 (RU52.40)	-	-4.30	-	-	-4.30	1.37	-2.93	-1.00	-1.93
6535 (RU52.37)	-	-4.67	-	-	-4.67	1.62	-3.05	-1.00	-2.05
6695 (RU52.37)	-	-5.28	-	-	-5.28	1.62	-3.66	-1.00	-2.66
6855 (RU52.40)	-	-4.72	-	-	-4.72	1.62	-3.10	-1.00	-2.10
6875 (RU52.38)	-	-5.56	-	-	-5.56	1.62	-3.94	-1.00	-2.94
6875 (RU52.39)	-	-4.96	-	-	-4.96	1.85	-3.11	-1.00	-2.11
6895 (RU52.37)	-	-5.46	-	-	-5.46	1.85	-3.61	-1.00	-2.61
6995 (RU52.37)	-	-5.36	-	-	-5.36	1.85	-3.51	-1.00	-2.51
7095 (RU52.40)	-	-5.46	-	-	-5.46	1.85	-3.61	-1.00	-2.61

Table 196 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	-		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU106 LPI	Duty Cycle (%):	98.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.09
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.85
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU106.53)	-	-4.08	-	-	-4.08	0.71	-3.37	-1.00	-2.37
6175 (RU106.53)	-	-4.13	-	-	-4.13	1.37	-2.76	-1.00	-1.76
6415 (RU106.54)	-	-4.90	-	-	-4.90	1.63	-3.27	-1.00	-2.27
6435 (RU106.53)	-	-4.19	-	-	-4.19	1.37	-2.82	-1.00	-1.82
6475 (RU106.53)	-	-4.72	-	-	-4.72	1.37	-3.35	-1.00	-2.35
6515 (RU106.54)	-	-4.32	-	-	-4.32	1.37	-2.95	-1.00	-1.95
6535 (RU106.53)	-	-4.69	-	-	-4.69	1.62	-3.07	-1.00	-2.07
6695 (RU106.53)	-	-4.78	-	-	-4.78	1.62	-3.16	-1.00	-2.16
6855 (RU106.54)	-	-4.67	-	-	-4.67	1.62	-3.05	-1.00	-2.05
6875 (RU106.53)	-	-4.80	-	-	-4.80	1.62	-3.18	-1.00	-2.18
6875 (RU106.54)	-	-4.61	-	-	-4.61	1.85	-2.76	-1.00	-1.76
6895 (RU106.53)	-	-4.68	-	-	-4.68	1.85	-2.83	-1.00	-1.83
6995 (RU106.53)	-	-5.31	-	-	-5.31	1.85	-3.46	-1.00	-2.46
7095 (RU106.54)	-	-5.29	-	-	-5.29	1.85	-3.44	-1.00	-2.44

Table 197 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU26 SP	Duty Cycle (%):	97.2
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.12
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.63
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU26.0)	-	10.08	-	-	10.08	0.71	10.79	17.00	-6.21
6175 (RU26.0)	-	10.30	-	-	10.30	1.37	11.67	17.00	-5.33
6415 (RU26.8)	-	10.14	-	-	10.14	1.63	11.77	17.00	-5.23
6435 (RU26.0)	-	10.25	-	-	10.25	1.37	11.62	17.00	-5.38
6475 (RU26.0)	-	9.82	-	-	9.82	1.37	11.19	17.00	-5.81
6515 (RU26.8)	-	10.26	-	-	10.26	1.37	11.63	17.00	-5.37
6535 (RU26.0)	-	10.40	-	-	10.40	1.62	12.02	17.00	-4.98
6695 (RU26.0)	-	10.42	-	-	10.42	1.62	12.04	17.00	-4.96
6855 (RU26.8)	-	10.41	-	-	10.41	1.62	12.03	17.00	-4.97

Table 198 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU52 SP	Duty Cycle (%):	97.2
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.12
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.63
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU52.37)	-	10.29	-	-	10.29	0.71	11.00	17.00	-6.00
6175 (RU52.37)	-	10.99	-	-	10.99	1.37	12.36	17.00	-4.64
6415 (RU52.40)	-	10.65	-	-	10.65	1.63	12.28	17.00	-4.72
6435 (RU52.37)	-	10.90	-	-	10.90	1.37	12.27	17.00	-4.73
6475 (RU52.37)	-	10.22	-	-	10.22	1.37	11.59	17.00	-5.41
6515 (RU52.40)	-	10.83	-	-	10.83	1.37	12.20	17.00	-4.80
6535 (RU52.37)	-	10.64	-	-	10.64	1.62	12.26	17.00	-4.74
6695 (RU52.37)	-	10.51	-	-	10.51	1.62	12.13	17.00	-4.87
6855 (RU52.40)	-	10.69	-	-	10.69	1.62	12.31	17.00	-4.69

Table 199 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU106 SP	Duty Cycle (%):	97.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.09
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.63
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU106.53)	-	10.63	-	-	10.63	0.71	11.34	17.00	-5.66
6175 (RU106.53)	-	10.68	-	-	10.68	1.37	12.05	17.00	-4.95
6415 (RU106.54)	-	10.79	-	-	10.79	1.63	12.42	17.00	-4.58
6435 (RU106.53)	-	10.68	-	-	10.68	1.37	12.05	17.00	-4.95
6475 (RU106.53)	-	10.34	-	-	10.34	1.37	11.71	17.00	-5.29
6515 (RU106.54)	-	10.95	-	-	10.95	1.37	12.32	17.00	-4.68
6535 (RU106.53)	-	10.94	-	-	10.94	1.62	12.56	17.00	-4.44
6695 (RU106.53)	-	10.93	-	-	10.93	1.62	12.55	17.00	-4.45
6855 (RU106.54)	-	11.02	-	-	11.02	1.62	12.64	17.00	-4.36

Table 200 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz	Band:	U-NII-5
Limit Clause(s):	15.407(a)(9)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	-		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU52 VLP	Duty Cycle (%):	97.5
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.11
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.37
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115 (RU52.37)	-	-8.39	-	-	-8.39	1.37	-7.02	-5.00	-2.02
6195 (RU52.37)	-	-8.46	-	-	-8.46	1.37	-7.09	-5.00	-2.09
6255 (RU52.40)	-	-8.70	-	-	-8.70	1.37	-7.33	-5.00	-2.33

Table 201 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(9)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	-		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU106 VLP	Duty Cycle (%):	98.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.09
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.63
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115 (RU106.53)	-	-8.28	-	-	-8.28	1.37	-6.91	-5.00	-1.91
6275 (RU106.53)	-	-8.94	-	-	-8.94	1.63	-7.31	-5.00	-2.31
6415 (RU106.54)	-	-9.02	-	-	-9.02	1.63	-7.39	-5.00	-2.39
6535 (RU106.53)	-	-8.58	-	-	-8.58	1.62	-6.96	-5.00	-1.96
6695 (RU106.53)	-	-8.92	-	-	-8.92	1.62	-7.30	-5.00	-2.30
6855 (RU106.54)	-	-8.75	-	-	-8.75	1.62	-7.13	-5.00	-2.13

Table 202 - Maximum Power Spectral Density Results



MIMO CDD

Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 SU LPI	Duty Cycle (%):	96.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.17
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955	-11.27	-10.66	-	-	-7.95	3.48	-4.46	-1.00	-3.46
6175	-11.18	-10.72	-	-	-7.93	3.89	-4.04	-1.00	-3.04
6415	-10.86	-10.67	-	-	-7.75	3.80	-3.96	-1.00	-2.96
6435	-11.14	-10.89	-	-	-8.00	3.88	-4.13	-1.00	-3.13
6475	-10.81	-10.85	-	-	-7.82	3.88	-3.95	-1.00	-2.95
6515	-10.73	-10.86	-	-	-7.78	3.88	-3.91	-1.00	-2.91
6535	-11.03	-10.85	-	-	-7.93	4.27	-3.66	-1.00	-2.66
6695	-10.77	-11.63	-	-	-8.17	4.27	-3.90	-1.00	-2.90
6855	-10.85	-12.27	-	-	-8.49	4.27	-4.23	-1.00	-3.23
6875	-11.26	-12.38	-	-	-8.77	4.27	-4.51	-1.00	-3.51
6895	-10.00	-11.35	-	-	-7.61	3.51	-4.11	-1.00	-3.11
6995	-10.20	-11.76	-	-	-7.90	3.51	-4.39	-1.00	-3.39
7095	-10.52	-11.71	-	-	-8.06	3.51	-4.56	-1.00	-3.56

Table 203 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE40 SU LPI	Duty Cycle (%):	96.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.18
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	-10.26	-10.22	-	-	-7.23	3.48	-3.75	-1.00	-2.75
6165	-10.51	-10.09	-	-	-7.29	3.89	-3.39	-1.00	-2.39
6405	-11.03	-10.65	-	-	-7.82	3.80	-4.03	-1.00	-3.03
6445	-10.82	-10.42	-	-	-7.61	3.88	-3.73	-1.00	-2.73
6485	-10.34	-10.51	-	-	-7.41	3.88	-3.54	-1.00	-2.54
6525	-10.76	-10.83	-	-	-7.79	4.27	-3.52	-1.00	-2.52
6565	-11.03	-10.79	-	-	-7.89	4.27	-3.63	-1.00	-2.63
6685	-11.13	-10.95	-	-	-8.03	4.27	-3.76	-1.00	-2.76
6845	-10.81	-10.64	-	-	-7.72	4.27	-3.45	-1.00	-2.45
6885	-10.52	-10.69	-	-	-7.59	4.27	-3.32	-1.00	-2.32
6925	-10.26	-10.36	-	-	-7.30	3.51	-3.80	-1.00	-2.80
7005	-10.65	-10.25	-	-	-7.44	3.51	-3.93	-1.00	-2.93
7085	-10.49	-10.39	-	-	-7.43	3.51	-3.92	-1.00	-2.92

Table 204 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE80 SU LPI	Duty Cycle (%):	95.6
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.19
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	-9.78	-9.51	-	-	-6.63	3.48	-3.15	-1.00	-2.15
6145	-10.60	-10.34	-	-	-7.46	3.89	-3.56	-1.00	-2.56
6385	-10.48	-10.04	-	-	-7.24	3.80	-3.45	-1.00	-2.45
6465	-10.25	-10.08	-	-	-7.16	3.88	-3.28	-1.00	-2.28
6545	-10.71	-10.68	-	-	-7.69	4.27	-3.42	-1.00	-2.42
6625	-10.43	-10.96	-	-	-7.68	4.27	-3.41	-1.00	-2.41
6705	-10.08	-10.70	-	-	-7.37	4.27	-3.10	-1.00	-2.10
6785	-10.35	-10.73	-	-	-7.53	4.27	-3.26	-1.00	-2.26
6865	-10.79	-10.39	-	-	-7.58	4.27	-3.31	-1.00	-2.31
6945	-10.34	-10.27	-	-	-7.30	3.51	-3.79	-1.00	-2.79
7025	-10.08	-9.83	-	-	-6.94	3.51	-3.44	-1.00	-2.44

Table 205 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE160 SU LPI	Duty Cycle (%):	92.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.32
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	-9.38	-9.43	-	-	-6.39	3.48	-2.91	-1.00	-1.91
6185	-10.26	-9.90	-	-	-7.07	3.89	-3.17	-1.00	-2.17
6345	-9.91	-9.77	-	-	-6.83	3.80	-3.04	-1.00	-2.04
6505	-10.23	-10.20	-	-	-7.21	4.27	-2.94	-1.00	-1.94
6665	-10.36	-10.43	-	-	-7.38	4.27	-3.12	-1.00	-2.12
6825	-10.40	-9.91	-	-	-7.14	4.27	-2.87	-1.00	-1.87
6985	-9.86	-9.65	-	-	-6.74	3.51	-3.24	-1.00	-2.24

Table 206 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 SU SP	Duty Cycle (%):	96.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.17
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955	7.79	7.68	-	-	10.74	3.48	14.23	17.00	-2.77
6175	7.32	7.59	-	-	10.47	3.89	14.36	17.00	-2.64
6415	6.95	7.18	-	-	10.08	3.80	13.87	17.00	-3.13
6435	6.67	7.10	-	-	9.90	3.88	13.78	17.00	-3.22
6475	6.85	7.18	-	-	10.03	3.88	13.90	17.00	-3.10
6515	7.07	7.34	-	-	10.22	3.88	14.09	17.00	-2.91
6535	6.68	6.99	-	-	9.84	4.27	14.11	17.00	-2.89
6695	6.74	6.78	-	-	9.77	4.27	14.04	17.00	-2.96
6855	6.94	7.03	-	-	9.99	4.27	14.26	17.00	-2.74

Table 207 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE40 SU SP	Duty Cycle (%):	96.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.18
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	6.35	6.42	-	-	9.40	3.48	12.88	17.00	-4.12
6165	6.75	6.43	-	-	9.60	3.89	13.50	17.00	-3.50
6405	6.08	6.60	-	-	9.35	3.80	13.15	17.00	-3.85
6445	6.28	6.31	-	-	9.31	3.88	13.18	17.00	-3.82
6485	6.35	6.39	-	-	9.38	3.88	13.25	17.00	-3.75
6525	6.69	6.80	-	-	9.75	4.27	14.02	17.00	-2.98
6565	6.53	6.51	-	-	9.53	4.27	13.80	17.00	-3.20
6685	6.46	6.26	-	-	9.37	4.27	13.64	17.00	-3.36
6845	6.61	6.51	-	-	9.57	4.27	13.84	17.00	-3.16

Table 208 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	95.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.18
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	3.62	3.66	-	-	6.65	3.48	10.13	17.00	-6.87
6145	3.66	3.55	-	-	6.61	3.89	10.51	17.00	-6.49
6385	3.48	3.56	-	-	6.53	3.80	10.33	17.00	-6.67
6465	3.61	3.58	-	-	6.61	3.88	10.48	17.00	-6.52
6545	3.90	3.66	-	-	6.79	4.27	11.06	17.00	-5.94
6625	3.76	3.69	-	-	6.73	4.27	11.00	17.00	-6.00
6705	3.96	3.67	-	-	6.83	4.27	11.10	17.00	-5.90
6785	3.90	4.09	-	-	7.01	4.27	11.28	17.00	-5.72

Table 209 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE160 SU SP	Duty Cycle (%):	93.2
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.30
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	-0.67	-0.72	-	-	2.32	3.48	5.80	17.00	-11.20
6185	-1.29	-0.48	-	-	2.14	3.89	6.04	17.00	-10.96
6345	-1.17	-0.59	-	-	2.14	3.80	5.93	17.00	-11.07
6505	-1.33	-1.29	-	-	1.70	4.27	5.97	17.00	-11.03
6665	-1.58	-1.29	-	-	1.58	4.27	5.85	17.00	-11.15

Table 210 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(9)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 SU VLP	Duty Cycle (%):	96.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.18
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115	-15.02	-15.00	-	-	-12.00	3.89	-8.10	-5.00	-3.10
6275	-14.76	-14.74	-	-	-11.74	3.80	-7.94	-5.00	-2.94
6415	-15.01	-14.96	-	-	-11.97	3.80	-8.18	-5.00	-3.18
6535	-15.47	-15.38	-	-	-12.41	4.27	-8.14	-5.00	-3.14
6695	-15.06	-15.73	-	-	-12.37	4.27	-8.11	-5.00	-3.11
6855	-15.34	-16.47	-	-	-12.86	4.27	-8.59	-5.00	-3.59

Table 211 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(9)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE40 SU VLP	Duty Cycle (%):	96.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.18
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6125	-15.14	-15.22	-	-	-12.17	3.89	-8.28	-5.00	-3.28
6285	-15.25	-15.26	-	-	-12.24	3.80	-8.45	-5.00	-3.45
6405	-15.10	-15.27	-	-	-12.17	3.80	-8.37	-5.00	-3.37
6565	-15.33	-15.23	-	-	-12.27	4.27	-8.00	-5.00	-3.00
6685	-15.40	-15.88	-	-	-12.62	4.27	-8.35	-5.00	-3.35
6845	-15.41	-16.47	-	-	-12.90	4.27	-8.63	-5.00	-3.63

Table 212 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(9)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE80 SU VLP	Duty Cycle (%):	95.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.18
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145	-14.46	-14.55	-	-	-11.49	3.89	-7.60	-5.00	-2.60
6225	-14.12	-14.14	-	-	-11.12	3.89	-7.23	-5.00	-2.23
6385	-14.40	-14.32	-	-	-11.35	3.80	-7.55	-5.00	-2.55
6625	-14.74	-14.75	-	-	-11.73	4.27	-7.47	-5.00	-2.47
6705	-15.14	-15.79	-	-	-12.44	4.27	-8.17	-5.00	-3.17
6785	-14.92	-15.73	-	-	-12.30	4.27	-8.03	-5.00	-3.03

Table 213 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(9)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE160 SU VLP	Duty Cycle (%):	93.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.31
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185	-13.81	-13.98	-	-	-10.88	3.89	-6.99	-5.00	-1.99
6345	-14.00	-14.02	-	-	-11.00	3.80	-7.20	-5.00	-2.20
6665	-14.53	-14.73	-	-	-11.62	4.27	-7.35	-5.00	-2.35

Table 214 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU26 LPI	Duty Cycle (%):	97.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.13
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU26.0)	-9.54	-8.74	-	-	-6.11	3.48	-2.63	-1.00	-1.63
6175 (RU26.0)	-11.02	-9.61	-	-	-7.25	3.89	-3.35	-1.00	-2.35
6415 (RU26.8)	-10.99	-10.71	-	-	-7.83	3.80	-4.04	-1.00	-3.04
6435 (RU26.0)	-11.14	-10.74	-	-	-7.93	3.88	-4.05	-1.00	-3.05
6475 (RU26.0)	-10.77	-10.92	-	-	-7.84	3.88	-3.96	-1.00	-2.96
6515 (RU26.8)	-10.85	-10.73	-	-	-7.78	3.88	-3.90	-1.00	-2.90
6535 (RU26.0)	-11.38	-11.03	-	-	-8.19	4.27	-3.92	-1.00	-2.92
6695 (RU26.0)	-11.19	-11.67	-	-	-8.41	4.27	-4.14	-1.00	-3.14
6855 (RU26.8)	-10.96	-12.63	-	-	-8.70	4.27	-4.43	-1.00	-3.43
6875 (RU26.3)	-10.97	-12.59	-	-	-8.70	4.27	-4.43	-1.00	-3.43
6875 (RU26.5)	-10.86	-11.94	-	-	-8.36	3.51	-4.85	-1.00	-3.85
6895 (RU26.0)	-10.12	-11.32	-	-	-7.67	3.51	-4.16	-1.00	-3.16
6995 (RU26.0)	-9.01	-11.06	-	-	-6.90	3.51	-3.40	-1.00	-2.40
7095 (RU26.8)	-10.46	-11.70	-	-	-8.03	3.51	-4.52	-1.00	-3.52

Table 215 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU52 LPI	Duty Cycle (%):	97.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.13
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU52.37)	-10.17	-9.16	-	-	-6.63	3.48	-3.14	-1.00	-2.14
6175 (RU52.37)	-10.63	-10.24	-	-	-7.42	3.89	-3.53	-1.00	-2.53
6415 (RU52.40)	-10.09	-9.25	-	-	-6.64	3.80	-2.84	-1.00	-1.84
6435 (RU52.37)	-9.87	-10.12	-	-	-6.98	3.88	-3.11	-1.00	-2.11
6475 (RU52.37)	-9.67	-9.39	-	-	-6.51	3.88	-2.64	-1.00	-1.64
6515 (RU52.40)	-10.17	-10.41	-	-	-7.28	3.88	-3.40	-1.00	-2.40
6535 (RU52.37)	-10.69	-10.61	-	-	-7.64	4.27	-3.37	-1.00	-2.37
6695 (RU52.37)	-10.62	-11.57	-	-	-8.06	4.27	-3.79	-1.00	-2.79
6855 (RU52.40)	-10.76	-11.03	-	-	-7.88	4.27	-3.61	-1.00	-2.61
6875 (RU52.38)	-9.46	-10.57	-	-	-6.97	4.27	-2.70	-1.00	-1.70
6875 (RU52.39)	-9.53	-10.35	-	-	-6.91	3.51	-3.40	-1.00	-2.40
6895 (RU52.37)	-10.27	-10.77	-	-	-7.50	3.51	-4.00	-1.00	-3.00
6995 (RU52.37)	-9.53	-10.37	-	-	-6.92	3.51	-3.41	-1.00	-2.41
7095 (RU52.40)	-9.61	-10.59	-	-	-7.06	3.51	-3.56	-1.00	-2.56

Table 216 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU106 LPI	Duty Cycle (%):	97.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.09
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU106.53)	-10.26	-9.53	-	-	-6.87	3.48	-3.39	-1.00	-2.39
6175 (RU106.53)	-10.79	-10.10	-	-	-7.42	3.89	-3.53	-1.00	-2.53
6415 (RU106.54)	-10.82	-10.79	-	-	-7.79	3.80	-4.00	-1.00	-3.00
6435 (RU106.53)	-10.61	-10.34	-	-	-7.46	3.88	-3.58	-1.00	-2.58
6475 (RU106.53)	-10.12	-10.41	-	-	-7.25	3.88	-3.37	-1.00	-2.37
6515 (RU106.54)	-9.69	-9.65	-	-	-6.66	3.88	-2.78	-1.00	-1.78
6535 (RU106.53)	-10.59	-10.63	-	-	-7.60	4.27	-3.33	-1.00	-2.33
6695 (RU106.53)	-10.70	-11.50	-	-	-8.07	4.27	-3.80	-1.00	-2.80
6855 (RU106.54)	-10.41	-11.47	-	-	-7.90	4.27	-3.63	-1.00	-2.63
6875 (RU106.53)	-10.52	-11.19	-	-	-7.83	4.27	-3.56	-1.00	-2.56
6875 (RU106.54)	-10.68	-11.64	-	-	-8.12	3.51	-4.61	-1.00	-3.61
6895 (RU106.53)	-9.74	-11.06	-	-	-7.34	3.51	-3.84	-1.00	-2.84
6995 (RU106.53)	-9.54	-11.00	-	-	-7.20	3.51	-3.69	-1.00	-2.69
7095 (RU106.54)	-9.75	-10.77	-	-	-7.22	3.51	-3.71	-1.00	-2.71

Table 217 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU26 SP	Duty Cycle (%):	97.2
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.12
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU26.0)	7.25	7.61	-	-	10.44	3.48	13.93	17.00	-3.07
6175 (RU26.0)	7.18	7.18	-	-	10.19	3.89	14.08	17.00	-2.92
6415 (RU26.8)	6.70	6.91	-	-	9.82	3.80	13.61	17.00	-3.39
6435 (RU26.0)	6.95	7.58	-	-	10.29	3.88	14.16	17.00	-2.84
6475 (RU26.0)	6.33	7.15	-	-	9.77	3.88	13.64	17.00	-3.36
6515 (RU26.8)	7.00	7.37	-	-	10.20	3.88	14.08	17.00	-2.92
6535 (RU26.0)	6.64	7.13	-	-	9.90	4.27	14.17	17.00	-2.83
6695 (RU26.0)	6.55	7.08	-	-	9.83	4.27	14.10	17.00	-2.90
6855 (RU26.8)	6.77	6.99	-	-	9.89	4.27	14.16	17.00	-2.84

Table 218 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU52 SP	Duty Cycle (%):	97.2
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.12
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU52.37)	7.75	8.12	-	-	10.95	3.48	14.43	17.00	-2.57
6175 (RU52.37)	7.37	7.76	-	-	10.58	3.89	14.47	17.00	-2.53
6415 (RU52.40)	6.73	7.51	-	-	10.15	3.80	13.94	17.00	-3.06
6435 (RU52.37)	7.01	7.74	-	-	10.40	3.88	14.27	17.00	-2.73
6475 (RU52.37)	6.67	7.31	-	-	10.01	3.88	13.89	17.00	-3.11
6515 (RU52.40)	7.14	7.73	-	-	10.46	3.88	14.33	17.00	-2.67
6535 (RU52.37)	6.89	7.26	-	-	10.09	4.27	14.36	17.00	-2.64
6695 (RU52.37)	7.26	7.14	-	-	10.21	4.27	14.48	17.00	-2.52
6855 (RU52.40)	7.06	7.28	-	-	10.18	4.27	14.45	17.00	-2.55

Table 219 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)f)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU106 SP	Duty Cycle (%):	97.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.09
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU106.53)	8.11	7.95	-	-	11.04	3.48	14.53	17.00	-2.47
6175 (RU106.53)	8.21	7.97	-	-	11.10	3.89	15.00	17.00	-2.00
6415 (RU106.54)	7.35	7.93	-	-	10.66	3.80	14.46	17.00	-2.54
6435 (RU106.53)	7.13	7.67	-	-	10.42	3.88	14.30	17.00	-2.70
6475 (RU106.53)	7.09	7.61	-	-	10.37	3.88	14.25	17.00	-2.75
6515 (RU106.54)	7.88	8.08	-	-	10.99	3.88	14.87	17.00	-2.13
6535 (RU106.53)	7.09	7.54	-	-	10.33	4.27	14.60	17.00	-2.40
6695 (RU106.53)	7.07	6.87	-	-	9.98	4.27	14.25	17.00	-2.75
6855 (RU106.54)	7.18	7.52	-	-	10.36	4.27	14.63	17.00	-2.37

Table 220 - Maximum Power Spectral Density Results



MIMO SDM

Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 SU LPI	Duty Cycle (%):	93.5
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.29
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955	-6.79	-6.91	-	-	-3.84	0.48	-3.36	-1.00	-2.36
6175	-7.25	-7.18	-	-	-4.20	0.90	-3.30	-1.00	-2.30
6415	-7.81	-7.50	-	-	-4.64	0.83	-3.81	-1.00	-2.81
6435	-7.86	-7.38	-	-	-4.60	0.88	-3.72	-1.00	-2.72
6475	-7.59	-7.34	-	-	-4.45	0.88	-3.57	-1.00	-2.57
6515	-7.18	-6.81	-	-	-3.98	0.88	-3.10	-1.00	-2.10
6535	-7.77	-7.47	-	-	-4.61	1.27	-3.34	-1.00	-2.34
6695	-7.52	-7.42	-	-	-4.46	1.27	-3.19	-1.00	-2.19
6855	-7.63	-7.38	-	-	-4.49	1.27	-3.23	-1.00	-2.23
6875	-7.27	-7.70	-	-	-4.47	1.27	-3.20	-1.00	-2.20
6895	-6.81	-6.85	-	-	-3.82	0.62	-3.20	-1.00	-2.20
6995	-7.37	-6.68	-	-	-4.00	0.62	-3.39	-1.00	-2.39
7095	-6.85	-7.11	-	-	-3.97	0.62	-3.35	-1.00	-2.35

Table 221 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE40 SU LPI	Duty Cycle (%):	93.4
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.30
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	-7.16	-6.96	-	-	-4.05	0.48	-3.57	-1.00	-2.57
6165	-7.53	-7.48	-	-	-4.50	0.90	-3.60	-1.00	-2.60
6405	-8.11	-7.70	-	-	-4.89	0.83	-4.06	-1.00	-3.06
6445	-7.97	-7.58	-	-	-4.76	0.88	-3.88	-1.00	-2.88
6485	-7.57	-7.62	-	-	-4.58	0.88	-3.70	-1.00	-2.70
6525	-7.49	-7.83	-	-	-4.64	1.27	-3.37	-1.00	-2.37
6565	-7.82	-8.03	-	-	-4.91	1.27	-3.65	-1.00	-2.65
6685	-8.21	-8.31	-	-	-5.25	1.27	-3.98	-1.00	-2.98
6845	-7.75	-8.08	-	-	-4.90	1.27	-3.63	-1.00	-2.63
6885	-7.89	-8.22	-	-	-5.04	1.27	-3.77	-1.00	-2.77
6925	-7.54	-7.31	-	-	-4.41	0.62	-3.80	-1.00	-2.80
7005	-7.47	-7.02	-	-	-4.23	0.62	-3.61	-1.00	-2.61
7085	-7.62	-7.09	-	-	-4.34	0.62	-3.72	-1.00	-2.72

Table 222 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE80 SU LPI	Duty Cycle (%):	93.1
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.31
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	-6.74	-6.72	-	-	-3.72	0.48	-3.25	-1.00	-2.25
6145	-7.54	-7.12	-	-	-4.31	0.90	-3.42	-1.00	-2.42
6385	-7.48	-7.07	-	-	-4.26	0.83	-3.43	-1.00	-2.43
6465	-7.55	-7.25	-	-	-4.39	0.88	-3.50	-1.00	-2.50
6545	-7.91	-7.70	-	-	-4.79	1.27	-3.53	-1.00	-2.53
6625	-8.01	-8.04	-	-	-5.02	1.27	-3.75	-1.00	-2.75
6705	-7.72	-7.77	-	-	-4.74	1.27	-3.47	-1.00	-2.47
6785	-7.58	-7.69	-	-	-4.62	1.27	-3.36	-1.00	-2.36
6865	-7.84	-7.55	-	-	-4.68	1.27	-3.42	-1.00	-2.42
6945	-7.21	-7.15	-	-	-4.17	0.62	-3.55	-1.00	-2.55
7025	-7.09	-7.27	-	-	-4.17	0.62	-3.55	-1.00	-2.55

Table 223 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE160 SU LPI	Duty Cycle (%):	89.4
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.48
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	-6.55	-6.63	-	-	-3.58	0.48	-3.10	-1.00	-2.10
6185	-6.94	-6.61	-	-	-3.76	0.90	-2.86	-1.00	-1.86
6345	-7.26	-6.94	-	-	-4.09	0.83	-3.26	-1.00	-2.26
6505	-7.08	-7.40	-	-	-4.23	1.27	-2.96	-1.00	-1.96
6665	-7.66	-7.65	-	-	-4.64	1.27	-3.38	-1.00	-2.38
6825	-7.44	-7.27	-	-	-4.34	1.27	-3.07	-1.00	-2.07
6985	-6.58	-7.01	-	-	-3.78	0.62	-3.16	-1.00	-2.16

Table 224 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 SU SP	Duty Cycle (%):	93.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.28
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955	9.15	9.21	-	-	12.19	0.48	12.66	17.00	-4.34
6175	9.29	9.25	-	-	12.28	0.90	13.18	17.00	-3.82
6415	8.89	9.10	-	-	12.00	0.83	12.84	17.00	-4.16
6435	8.66	9.34	-	-	12.03	0.88	12.91	17.00	-4.09
6475	8.70	8.92	-	-	11.82	0.88	12.70	17.00	-4.30
6515	9.19	9.32	-	-	12.27	0.88	13.15	17.00	-3.85
6535	9.34	9.45	-	-	12.40	1.27	13.67	17.00	-3.33
6695	9.31	9.01	-	-	12.18	1.27	13.44	17.00	-3.56
6855	9.36	9.64	-	-	12.51	1.27	13.78	17.00	-3.22

Table 225 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE40 SU SP	Duty Cycle (%):	93.6
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.29
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	6.37	6.64	-	-	9.52	0.48	9.99	17.00	-7.01
6165	6.55	6.41	-	-	9.49	0.90	10.39	17.00	-6.61
6405	6.30	6.64	-	-	9.48	0.83	10.31	17.00	-6.69
6445	6.53	6.08	-	-	9.32	0.88	10.20	17.00	-6.80
6485	6.43	6.38	-	-	9.42	0.88	10.30	17.00	-6.70
6525	6.64	6.88	-	-	9.77	1.27	11.04	17.00	-5.96
6565	6.75	6.48	-	-	9.63	1.27	10.89	17.00	-6.11
6685	6.45	6.41	-	-	9.44	1.27	10.70	17.00	-6.30
6845	6.72	6.67	-	-	9.71	1.27	10.97	17.00	-6.03

Table 226 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	93.4
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.30
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	3.76	3.86	-	-	6.82	0.48	7.30	17.00	-9.70
6145	3.63	3.66	-	-	6.65	0.90	7.55	17.00	-9.45
6385	3.37	3.70	-	-	6.55	0.83	7.38	17.00	-9.62
6465	3.67	3.51	-	-	6.60	0.88	7.48	17.00	-9.52
6545	3.84	3.58	-	-	6.72	1.27	7.99	17.00	-9.01
6625	3.91	3.49	-	-	6.72	1.27	7.98	17.00	-9.02
6705	4.24	3.98	-	-	7.12	1.27	8.39	17.00	-8.61
6785	4.34	3.82	-	-	7.10	1.27	8.36	17.00	-8.64

Table 227 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE160 SU SP	Duty Cycle (%):	89.9
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.46
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	-1.12	-1.11	-	-	1.90	0.48	2.37	17.00	-14.63
6185	-1.06	-0.62	-	-	2.18	0.90	3.08	17.00	-13.92
6345	-1.04	-0.80	-	-	2.09	0.83	2.92	17.00	-14.08
6505	-1.28	-0.84	-	-	1.96	1.27	3.23	17.00	-13.77
6665	-1.66	-1.69	-	-	1.33	1.27	2.60	17.00	-14.40

Table 228 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(9)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 SU VLP	Duty Cycle (%):	93.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.28
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115	-11.97	-11.84	-	-	-8.90	0.90	-8.00	-5.00	-3.00
6275	-11.51	-11.71	-	-	-8.60	0.83	-7.77	-5.00	-2.77
6415	-11.33	-11.46	-	-	-8.38	0.83	-7.55	-5.00	-2.55
6535	-11.90	-11.93	-	-	-8.91	1.27	-7.64	-5.00	-2.64
6695	-11.63	-12.59	-	-	-9.07	1.27	-7.80	-5.00	-2.80
6855	-12.20	-14.02	-	-	-10.01	1.27	-8.74	-5.00	-3.74

Table 229 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(9)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE40 SU VLP	Duty Cycle (%):	93.8
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.28
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6125	-11.49	-11.21	-	-	-8.34	0.90	-7.44	-5.00	-2.44
6285	-11.74	-11.59	-	-	-8.65	0.83	-7.82	-5.00	-2.82
6405	-12.06	-11.60	-	-	-8.81	0.83	-7.98	-5.00	-2.98
6565	-12.42	-12.25	-	-	-9.32	1.27	-8.06	-5.00	-3.06
6685	-11.94	-11.97	-	-	-8.95	1.27	-7.68	-5.00	-2.68
6845	-11.37	-11.78	-	-	-8.56	1.27	-7.30	-5.00	-2.30

Table 230 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(9)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE80 SU VLP	Duty Cycle (%):	93.0
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.31
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145	-11.55	-11.41	-	-	-8.47	0.90	-7.57	-5.00	-2.57
6225	-11.04	-11.17	-	-	-8.10	0.90	-7.20	-5.00	-2.20
6385	-11.46	-11.25	-	-	-8.35	0.83	-7.51	-5.00	-2.51
6625	-11.49	-11.94	-	-	-8.70	1.27	-7.43	-5.00	-2.43
6705	-11.69	-11.77	-	-	-8.72	1.27	-7.45	-5.00	-2.45
6785	-11.72	-11.73	-	-	-8.72	1.27	-7.45	-5.00	-2.45

Table 231 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(9)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE160 SU VLP	Duty Cycle (%):	89.5
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.48
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185	-11.59	-11.28	-	-	-8.42	0.90	-7.52	-5.00	-2.52
6345	-11.97	-11.44	-	-	-8.69	0.83	-7.86	-5.00	-2.86
6665	-11.75	-11.90	-	-	-8.81	1.27	-7.55	-5.00	-2.55

Table 232 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU26 LPI	Duty Cycle (%):	97.2
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.12
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU26.0)	-6.66	-5.80	-	-	-3.20	0.48	-2.72	-1.00	-1.72
6175 (RU26.0)	-7.09	-6.41	-	-	-3.73	0.90	-2.83	-1.00	-1.83
6415 (RU26.8)	-7.03	-6.36	-	-	-3.67	0.83	-2.84	-1.00	-1.84
6435 (RU26.0)	-7.21	-6.04	-	-	-3.57	0.88	-2.69	-1.00	-1.69
6475 (RU26.0)	-6.48	-6.33	-	-	-3.39	0.88	-2.51	-1.00	-1.51
6515 (RU26.8)	-7.42	-7.74	-	-	-4.57	0.88	-3.69	-1.00	-2.69
6535 (RU26.0)	-7.06	-6.89	-	-	-3.96	1.27	-2.70	-1.00	-1.70
6695 (RU26.0)	-6.95	-7.39	-	-	-4.15	1.27	-2.89	-1.00	-1.89
6855 (RU26.8)	-6.61	-7.56	-	-	-4.05	1.27	-2.78	-1.00	-1.78
6875 (RU26.3)	-6.84	-7.03	-	-	-3.92	1.27	-2.66	-1.00	-1.66
6875 (RU26.5)	-6.60	-7.00	-	-	-3.79	0.62	-3.17	-1.00	-2.17
6895 (RU26.0)	-6.13	-6.72	-	-	-3.40	0.62	-2.78	-1.00	-1.78
6995 (RU26.0)	-5.97	-6.35	-	-	-3.14	0.62	-2.53	-1.00	-1.53
7095 (RU26.8)	-5.98	-6.70	-	-	-3.32	0.62	-2.70	-1.00	-1.70

Table 233 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU52 LPI	Duty Cycle (%):	97.0
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.13
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU52.37)	-7.64	-6.88	-	-	-4.24	0.48	-3.76	-1.00	-2.76
6175 (RU52.37)	-8.00	-7.03	-	-	-4.47	0.90	-3.58	-1.00	-2.58
6415 (RU52.40)	-7.87	-7.74	-	-	-4.79	0.83	-3.96	-1.00	-2.96
6435 (RU52.37)	-7.91	-7.29	-	-	-4.58	0.88	-3.70	-1.00	-2.70
6475 (RU52.37)	-7.25	-6.79	-	-	-4.00	0.88	-3.12	-1.00	-2.12
6515 (RU52.40)	-7.33	-7.13	-	-	-4.22	0.88	-3.34	-1.00	-2.34
6535 (RU52.37)	-8.13	-7.64	-	-	-4.87	1.27	-3.60	-1.00	-2.60
6695 (RU52.37)	-8.02	-8.89	-	-	-5.42	1.27	-4.16	-1.00	-3.16
6855 (RU52.40)	-7.49	-8.35	-	-	-4.89	1.27	-3.62	-1.00	-2.62
6875 (RU52.38)	-7.77	-7.82	-	-	-4.79	1.27	-3.52	-1.00	-2.52
6875 (RU52.39)	-7.73	-8.96	-	-	-5.29	0.62	-4.67	-1.00	-3.67
6895 (RU52.37)	-6.90	-7.76	-	-	-4.30	0.62	-3.68	-1.00	-2.68
6995 (RU52.37)	-6.76	-7.99	-	-	-4.32	0.62	-3.70	-1.00	-2.70
7095 (RU52.40)	-6.79	-7.75	-	-	-4.23	0.62	-3.62	-1.00	-2.62

Table 234 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU106 LPI	Duty Cycle (%):	97.9
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.09
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU106.53)	-6.78	-6.56	-	-	-3.66	0.48	-3.18	-1.00	-2.18
6175 (RU106.53)	-7.24	-7.15	-	-	-4.18	0.90	-3.28	-1.00	-2.28
6415 (RU106.54)	-7.84	-7.35	-	-	-4.58	0.83	-3.75	-1.00	-2.75
6435 (RU106.53)	-7.64	-7.17	-	-	-4.39	0.88	-3.51	-1.00	-2.51
6475 (RU106.53)	-7.22	-7.23	-	-	-4.21	0.88	-3.33	-1.00	-2.33
6515 (RU106.54)	-7.08	-6.85	-	-	-3.95	0.88	-3.07	-1.00	-2.07
6535 (RU106.53)	-7.34	-7.69	-	-	-4.50	1.27	-3.24	-1.00	-2.24
6695 (RU106.53)	-7.50	-8.73	-	-	-5.06	1.27	-3.80	-1.00	-2.80
6855 (RU106.54)	-7.54	-8.45	-	-	-4.96	1.27	-3.70	-1.00	-2.70
6875 (RU106.53)	-7.66	-8.85	-	-	-5.20	1.27	-3.94	-1.00	-2.94
6875 (RU106.54)	-7.65	-8.85	-	-	-5.20	0.62	-4.58	-1.00	-3.58
6895 (RU106.53)	-7.03	-7.82	-	-	-4.40	0.62	-3.78	-1.00	-2.78
6995 (RU106.53)	-6.78	-7.61	-	-	-4.16	0.62	-3.55	-1.00	-2.55
7095 (RU106.54)	-7.06	-8.01	-	-	-4.50	0.62	-3.88	-1.00	-2.88

Table 235 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU26 SP	Duty Cycle (%):	97.2
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.12
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU26.0)	10.33	10.43	-	-	13.39	0.48	13.87	17.00	-3.13
6175 (RU26.0)	10.38	10.22	-	-	13.31	0.90	14.21	17.00	-2.79
6415 (RU26.8)	9.54	10.27	-	-	12.93	0.83	13.76	17.00	-3.24
6435 (RU26.0)	9.18	10.20	-	-	12.73	0.88	13.61	17.00	-3.39
6475 (RU26.0)	9.30	9.88	-	-	12.61	0.88	13.49	17.00	-3.51
6515 (RU26.8)	10.10	10.35	-	-	13.24	0.88	14.12	17.00	-2.88
6535 (RU26.0)	9.54	9.88	-	-	12.72	1.27	13.99	17.00	-3.01
6695 (RU26.0)	9.50	9.65	-	-	12.59	1.27	13.85	17.00	-3.15
6855 (RU26.8)	9.77	10.05	-	-	12.92	1.27	14.19	17.00	-2.81

Table 236 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU52 SP	Duty Cycle (%):	97.2
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.12
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU52.37)	10.14	10.85	-	-	13.52	0.48	14.00	17.00	-3.00
6175 (RU52.37)	10.33	10.94	-	-	13.66	0.90	14.56	17.00	-2.44
6415 (RU52.40)	9.86	10.73	-	-	13.33	0.83	14.16	17.00	-2.84
6435 (RU52.37)	9.97	10.59	-	-	13.30	0.88	14.19	17.00	-2.81
6475 (RU52.37)	9.75	10.35	-	-	13.07	0.88	13.95	17.00	-3.05
6515 (RU52.40)	10.11	10.79	-	-	13.47	0.88	14.35	17.00	-2.65
6535 (RU52.37)	9.81	10.26	-	-	13.05	1.27	14.32	17.00	-2.68
6695 (RU52.37)	10.40	9.82	-	-	13.13	1.27	14.40	17.00	-2.60
6855 (RU52.40)	9.74	9.95	-	-	12.86	1.27	14.12	17.00	-2.88

Table 237 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU106 SP	Duty Cycle (%):	97.9
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.09
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU106.53)	10.29	10.55	-	-	13.43	0.48	13.91	17.00	-3.09
6175 (RU106.53)	10.79	10.98	-	-	13.90	0.90	14.79	17.00	-2.21
6415 (RU106.54)	10.43	10.69	-	-	13.58	0.83	14.41	17.00	-2.59
6435 (RU106.53)	10.29	10.52	-	-	13.41	0.88	14.29	17.00	-2.71
6475 (RU106.53)	10.30	10.85	-	-	13.59	0.88	14.48	17.00	-2.52
6515 (RU106.54)	10.79	11.20	-	-	14.01	0.88	14.89	17.00	-2.11
6535 (RU106.53)	10.46	10.28	-	-	13.38	1.27	14.65	17.00	-2.35
6695 (RU106.53)	10.47	10.02	-	-	13.26	1.27	14.53	17.00	-2.47
6855 (RU106.54)	10.15	10.34	-	-	13.26	1.27	14.52	17.00	-2.48

Table 238 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(9)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU106 VLP	Duty Cycle (%):	97.9
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.09
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115 (RU106.53)	-11.08	-10.92	-	-	-7.99	0.90	-7.09	-5.00	-2.09
6275 (RU106.53)	-11.76	-11.55	-	-	-8.64	0.83	-7.81	-5.00	-2.81
6415 (RU106.54)	-11.67	-11.68	-	-	-8.67	0.83	-7.83	-5.00	-2.83
6535 (RU106.53)	-11.69	-11.57	-	-	-8.62	1.27	-7.36	-5.00	-2.36
6695 (RU106.53)	-11.94	-11.45	-	-	-8.68	1.27	-7.41	-5.00	-2.41
6855 (RU106.54)	-11.47	-10.82	-	-	-8.12	1.27	-6.86	-5.00	-1.86

Table 239 - Maximum Power Spectral Density Results



TxBF

Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		

DUT Configuration			
Mode:	802.11ax HE20 SU LPI	Duty Cycle (%):	90.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.45
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955	-10.32	-9.67	-	-	-6.97	3.48	-3.49	-1.00	-2.49
6175	-11.53	-10.72	-	-	-8.09	3.89	-4.20	-1.00	-3.20
6415	-9.79	-9.83	-	-	-6.80	3.80	-3.00	-1.00	-2.00
6435	-9.74	-9.91	-	-	-6.81	3.88	-2.93	-1.00	-1.93
6475	-9.83	-10.64	-	-	-7.21	3.88	-3.33	-1.00	-2.33
6515	-9.95	-10.55	-	-	-7.23	3.88	-3.35	-1.00	-2.35
6535	-9.97	-10.56	-	-	-7.24	4.27	-2.97	-1.00	-1.97
6695	-10.62	-11.08	-	-	-7.83	4.27	-3.56	-1.00	-2.56
6855	-10.23	-10.91	-	-	-7.55	4.27	-3.28	-1.00	-2.28
6875	-10.37	-11.21	-	-	-7.76	4.27	-3.49	-1.00	-2.49
6895	-10.19	-10.35	-	-	-7.26	3.51	-3.75	-1.00	-2.75
6995	-9.62	-10.65	-	-	-7.09	3.51	-3.58	-1.00	-2.58
7095	-10.14	-11.68	-	-	-7.83	3.51	-4.32	-1.00	-3.32

Table 240 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE40 SU LPI	Duty Cycle (%):	61.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	2.15
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	-9.50	-10.12	-	-	-6.79	3.48	-3.30	-1.00	-2.30
6165	-10.43	-10.42	-	-	-7.41	3.89	-3.52	-1.00	-2.52
6405	-9.72	-9.84	-	-	-6.77	3.80	-2.98	-1.00	-1.98
6445	-9.70	-9.65	-	-	-6.67	3.88	-2.79	-1.00	-1.79
6485	-10.18	-9.95	-	-	-7.06	3.88	-3.18	-1.00	-2.18
6525	-9.30	-8.73	-	-	-5.99	3.88	-2.12	-1.00	-1.12
6565	-9.89	-9.47	-	-	-6.66	4.27	-2.39	-1.00	-1.39
6685	-9.43	-9.51	-	-	-6.46	4.27	-2.19	-1.00	-1.19
6845	-10.91	-10.74	-	-	-7.81	4.27	-3.54	-1.00	-2.54
6885	-10.96	-10.74	-	-	-7.70	4.27	-3.43	-1.00	-2.43
6925	-9.00	-9.19	-	-	-6.08	3.51	-2.58	-1.00	-1.58
7005	-8.38	-8.98	-	-	-5.66	3.51	-2.15	-1.00	-1.15
7085	-9.28	-9.85	-	-	-6.54	3.51	-3.04	-1.00	-2.04

Table 241 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE80 SU LPI	Duty Cycle (%):	87.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.56
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	-10.05	-10.24	-	-	-7.14	3.48	-3.65	-1.00	-2.65
6145	-10.55	-10.25	-	-	-7.39	3.89	-3.49	-1.00	-2.49
6385	-9.80	-10.06	-	-	-6.92	3.80	-3.12	-1.00	-2.12
6465	-10.46	-10.34	-	-	-7.39	3.88	-3.51	-1.00	-2.51
6545	-10.37	-10.51	-	-	-7.43	4.27	-3.16	-1.00	-2.16
6625	-10.70	-10.92	-	-	-7.80	4.27	-3.53	-1.00	-2.53
6705	-9.76	-10.58	-	-	-7.14	4.27	-2.87	-1.00	-1.87
6785	-10.37	-10.52	-	-	-7.43	4.27	-3.16	-1.00	-2.16
6865	-10.83	-10.10	-	-	-7.44	4.27	-3.17	-1.00	-2.17
6945	-10.05	-9.80	-	-	-6.91	3.51	-3.41	-1.00	-2.41
7025	-10.24	-10.12	-	-	-7.17	3.51	-3.66	-1.00	-2.66

Table 242 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 SU SP	Duty Cycle (%):	87.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.56
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955	7.25	7.46	-	-	10.36	3.48	13.85	17.00	-3.15
6175	7.07	6.84	-	-	9.96	3.89	13.86	17.00	-3.14
6415	7.73	7.73	-	-	10.74	3.80	14.54	17.00	-2.46
6435	7.46	7.40	-	-	10.44	3.88	14.32	17.00	-2.68
6475	7.20	7.33	-	-	10.28	3.88	14.16	17.00	-2.84
6515	7.69	7.80	-	-	10.76	3.88	14.63	17.00	-2.37
6535	7.36	7.23	-	-	10.30	4.27	14.57	17.00	-2.43
6695	7.11	6.91	-	-	10.02	4.27	14.29	17.00	-2.71
6855	7.41	7.19	-	-	10.31	4.27	14.58	17.00	-2.42

Table 243 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE40 SU SP	Duty Cycle (%):	89.5
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.48
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	6.27	6.59	-	-	9.44	3.48	12.93	17.00	-4.07
6165	5.69	5.76	-	-	8.74	3.89	12.63	17.00	-4.37
6405	6.85	6.61	-	-	9.74	3.80	13.54	17.00	-3.46
6445	6.84	6.78	-	-	9.82	3.88	13.69	17.00	-3.31
6485	6.77	6.95	-	-	9.87	3.88	13.75	17.00	-3.25
6525	6.71	7.03	-	-	9.88	3.88	13.76	17.00	-3.24
6565	6.94	6.73	-	-	9.85	4.27	14.11	17.00	-2.89
6685	6.97	6.83	-	-	9.91	4.27	14.18	17.00	-2.82
6845	6.86	7.32	-	-	10.10	4.27	14.37	17.00	-2.63

Table 244 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	89.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.51
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	3.79	3.84	-	-	6.82	3.48	10.31	17.00	-6.69
6145	3.57	3.26	-	-	6.43	3.89	10.32	17.00	-6.68
6385	4.23	3.87	-	-	7.06	3.80	10.86	17.00	-6.14
6465	3.36	3.74	-	-	6.57	3.88	10.44	17.00	-6.56
6545	3.99	3.82	-	-	6.91	4.27	11.18	17.00	-5.82
6625	4.41	3.53	-	-	7.00	4.27	11.27	17.00	-5.73
6705	4.41	4.20	-	-	7.32	4.27	11.59	17.00	-5.41
6785	4.58	3.92	-	-	7.27	4.27	11.54	17.00	-5.46

Table 245 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(9)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE80 SU VLP	Duty Cycle (%):	87.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.57
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	4.27
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145	-14.42	-14.67	-	-	-11.53	3.89	-7.64	-5.00	-2.64
6225	-14.12	-14.65	-	-	-11.37	3.89	-7.47	-5.00	-2.47
6385	-14.47	-14.47	-	-	-11.46	3.80	-7.66	-5.00	-2.66
6625	-14.51	-15.51	-	-	-11.97	4.27	-7.70	-5.00	-2.70
6705	-14.22	-15.31	-	-	-11.72	4.27	-7.45	-5.00	-2.45
6785	-14.86	-15.10	-	-	-11.97	4.27	-7.70	-5.00	-2.70

Table 246 - Maximum Power Spectral Density Results



FCC 47 CFR Part 15E, Limit Clause 15.407(a)(7)

For client devices, except for fixed client devices as defined in this subpart, operating under the control of a standard power access point in 5.925–6.425 GHz and 6.525–6.875 GHz bands, the maximum power spectral density must not exceed 17 dBm e.i.r.p. in any 1-megahertz band, and the maximum e.i.r.p. over the frequency band of operation must not exceed 30 dBm and the device must limit its power to no more than 6 dB below its associated standard power access point's authorized transmit power.

ISED RSS-248, Limit Clause 4.5.5

The following limits shall apply to standard client devices:

- a) the maximum e.i.r.p. spectral density shall not exceed 17 dBm/MHz
- b) the maximum e.i.r.p. over the 5925-6875 MHz frequency band shall not exceed 30 dBm and
- c) the maximum power limits shall remain at least 6 dB below the power levels authorized for the associated standard-power access point

FCC 47 CFR Part 15E, Limit Clause 15.407(a)(8)

For client devices operating under the control of an indoor access point in the 5.925-7.125 GHz bands, the maximum power spectral density must not exceed -1 dBm e.i.r.p. in any 1-megahertz band, and the maximum e.i.r.p. over the frequency band of operation must not exceed 24 dBm.

ISED RSS-248, Limit Clause 4.5.3

The following limits shall apply to low-power client devices.

- a) the maximum e.i.r.p. spectral density shall not exceed -1 dBm/MHz; and
- b) the maximum e.i.r.p. over the 5925-7125 MHz frequency band shall not exceed 24 dBm.

FCC 47 CFR Part 15E, Limit Clause 15.407(a)(9)

For very low power devices operating in the 5.925-6.425 GHz and 6.525-6.875 GHz bands, the maximum power spectral density must not exceed -5 dBm e.i.r.p. in any 1-megahertz band and the maximum e.i.r.p. must not exceed 14 dBm.



2.4.7 Test Location and Test Equipment Used

This test was carried out in RF Chamber 18 and RF Laboratory 14.

Instrument	Manufacturer	Type No.	TE No.	Calibration Period (months)	Calibration Expiry Date
Hygrometer	Rotronic	I-1000	3068	12	07-Nov-2024
1800-6000 MHz Power Splitter	Mini-Circuits	ZN2PD-63-S+	4055	-	O/P Mon
AC Programmable Power Supply	iTech	IT7324	5225	-	O/P Mon
Attenuator 5W 30dB DC-18GHz	Aaren	AT40A-4041-D18-30	5505	12	22-Feb-2025
MXA Signal Analyser	Keysight Technologies	N9020B	5529	24	13-Dec-2024
2-Way Power Divider (2-8 GHz)	Aaren	AT30A-TE0208-2-AF	5685	12	02-Jan-2025
1500VA AC Power Supply	iTech	IT7324	5907	-	O/P Mon
MXA Signal Analyser	Keysight Technologies	N9020B	5919	24	18-Mar-2026
Digital Multimeter	Fluke	115	6145	12	06-Jun-2025
Cable (SMA to SMA 1m)	Junkosha	MWX221/B	6305	12	20-May-2025
Cable (SMA to SMA 3m)	Junkosha	MWX221-03000AMSAMS/A	6317	12	23-May-2025
MXA Signal Analyser	Keysight Technologies	N9020B	6417	24	26-Feb-2025
MXA Signal Analyser	Keysight Technologies	N9020B	6419	24	28-Feb-2025
Signal Conditioning Unit	TUV SUD	SPECTRUM_SCU001	6426	12	07-Feb-2025
Directional Coupler 2-8GHz	RF-Lambda	RFDC2G8G10	6447	-	O/P Mon
Directional Coupler 2-8GHz	RF-Lambda	RFDC2G8G10	6448	-	O/P Mon
Signal Conditioning Unit	TUV SUD	SPECTRUM_SCU001	6517	12	22-Feb-2025
Signal Conditioning Unit	TUV SUD	SPECTRUM_SCU001	6518	12	16-Feb-2025
Signal Conditioning Unit	TUV SUD	SPECTRUM_SCU001	6519	12	08-Feb-2025
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6520	12	09-Feb-2025
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6521	12	09-Feb-2025
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6526	12	22-Feb-2025
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6527	12	05-Mar-2025
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6529	12	16-Feb-2025
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6530	12	16-Feb-2025
AC Programmable Power Supply	iTech	IT7324	6662	-	O/P Mon
AC Programmable Power Supply	iTech	IT7324	6665	-	O/P Mon
WiFi 6E Tri-Band Gaming Router	Asus	GT-AXE110000	6694	-	TU



Instrument	Manufacturer	Type No.	TE No.	Calibration Period (months)	Calibration Expiry Date
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6752	12	06-Feb-2025
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6753	12	06-Feb-2025
Hygrometer	Fluke	971	6838	12	27-Aug-2025
Cable	SpecTech	PE300-60	6869	-	O/P Mon
Cable	SpecTech	PE300-60	6870	-	O/P Mon

Table 247

TU - Traceability Unscheduled

O/P Mon - Output Monitored using calibrated equipment



2.5 Authorised Band Edges

2.5.1 Specification Reference

FCC 47 CFR Part 15E, Clause 15.407 (b)
ISED RSS-248, Clause 4.6
ISED RSS-GEN, Clause 6.13

2.5.2 Equipment Under Test and Modification State

A3143, S/N: P44KN4197F - Modification State 0
A3143, S/N: VCXLW6763J - Modification State 0
A3143, S/N: JHJ0Q3L9N0 - Modification State 0
A3143, S/N: K36DT67Y70 - Modification State 0
A3143, S/N: QWX9XGVV4Q - Modification State 0

2.5.3 Date of Test

15-July-2024 to 30-July-2024

2.5.4 Test Method

The test was performed in accordance with ANSI C63.10, clause 6.6.

For U-NII-5-8 channels, the limit line on the following plots equated to -27 dBm/MHz. EIRP and was converted to field strength at 3 m using the following formula:

Field Strength (dBμV/m at 3 m) = EIRP (dBm) + 95.2 dB

As per KDB 987594, In addition, 15.35(b) applies where the peak emissions must be limited to no more than 20 dB above the average limit.

Authorised band edge measurements were performed, with the device operating in SISO and MIMO configurations, across the various modes supported by the device.

The measurements displayed within this report, have been limited to those modes which have been shown to be worst case.

Further measurements are held on file by TÜV SÜD and are available if required.

2.5.5 Environmental Conditions

Ambient Temperature	22.0 - 23.7 °C
Relative Humidity	37.6 - 54.4 %

2.5.6 Test Results

6 GHz WLAN

20 MHz Bandwidth - Core 0 (SISO)

Mode	Data Rate/ MCS	Resource Size	Resource Index	TX Frequency (MHz)	Band Edge Frequency (MHz)	Peak Level (dBμV/m)	Average Level (dBμV/m)
802.11a	54 Mbps	-	-	5955	5925	68.15	52.05
802.11ax HE20	MCS 4x1	SU	-	5955	5925	72.37	55.54
802.11ax HE20	MCS 11x1	106	54	5955	5925	65.30	46.36
802.11a	24 Mbps	-	-	7095	7125	70.66	55.66
802.11a	54 Mbps	-	-	7115	7125	81.77	65.58
802.11ax HE20	MCS 2x1	SU	-	7095	7125	72.64	58.29
802.11ax HE20	MCS 11x1	106	54	7095	7125	69.89	49.06
802.11ax HE20	MCS 4x1	SU	-	7115	7125	75.80	65.66
802.11ax HE20	MCS 11x1	26	0	7115	7125	83.58	63.92

Table 248 - SISO Authorised Band Edge Results






Figure 186 - 802.11a, SISO, Core 0 - 5955 MHz
Band Edge Frequency 5925 MHz



**Figure 187 - 802.11ax HE20, SU, SISO, Core 0 - 5955 MHz
Band Edge Frequency 5925 MHz**



**Figure 188 - 802.11ax HE20, RU 106-54, SISO, Core 0 - 5955 MHz
Band Edge Frequency 5925 MHz**




Figure 189 - 802.11a, SISO, Core 0 - 7095 MHz
Band Edge Frequency 7125 MHz






Figure 190 - 802.11a, SISO, Core 0 - 7115 MHz
Band Edge Frequency 7125 MHz



**Figure 191 - 802.11ax HE20, SU, SISO, Core 0 - 7095 MHz
Band Edge Frequency 7125 MHz**



**Figure 192 - 802.11ax HE20, RU 106-54, SISO, Core 0 - 7095 MHz
Band Edge Frequency 7125 MHz**




Figure 193 - 802.11ax HE20, SU, SISO, Core 0 - 7115 MHz
Band Edge Frequency 7125 MHz





Figure 194 - 802.11ax HE20, RU 26-0, SISO, Core 0 - 7115 MHz
Band Edge Frequency 7125 MHz


20 MHz Bandwidth - Core 1 (SISO)

Mode	Data Rate/ MCS	Resource Size	Resource Index	TX Frequency (MHz)	Band Edge Frequency (MHz)	Peak Level (dBμV/m)	Average Level (dBμV/m)
802.11a	54 Mbps	-	-	5955	5925	66.45	51.94
802.11ax HE20	MCS 4x1	SU	-	5955	5925	73.20	55.82
802.11ax HE20	MCS 11x1	106	53	5955	5925	66.13	46.94
802.11a	24 Mbps	-	-	7095	7125	68.38	54.28
802.11a	54 Mbps	-	-	7115	7125	83.02	65.62
802.11ax HE20	MCS 2x1	SU	-	7095	7125	71.45	57.48
802.11ax HE20	MCS 11x1	106	54	7095	7125	67.75	47.70
802.11ax HE20	MCS 2x1	SU	-	7115	7125	76.12	65.69
802.11ax HE20	MCS 11x1	106	53	7115	7125	83.67	60.40


Table 249 - SISO Authorised Band Edge Results



**Figure 195 - 802.11a, SISO, Core 1 - 5955 MHz
Band Edge Frequency 5925 MHz**



**Figure 196 - 802.11ax HE20, SU, SISO, Core 1 - 5955 MHz
Band Edge Frequency 5925 MHz**



**Figure 197 - 802.11ax HE20, RU 106-53, SISO, Core 1 - 5955 MHz
Band Edge Frequency 5925 MHz**




Figure 198 - 802.11a, SISO, Core 1 - 7095 MHz
Band Edge Frequency 7125 MHz






Figure 199 - 802.11a, SISO, Core 1 - 7115 MHz
Band Edge Frequency 7125 MHz



**Figure 200 - 802.11ax HE20, SU, SISO, Core 1 - 7095 MHz
Band Edge Frequency 7125 MHz**



**Figure 201 - 802.11ax HE20, RU 106-54, SISO, Core 1 - 7095 MHz
Band Edge Frequency 7125 MHz**




Figure 202 - 802.11ax HE20, SU, SISO, Core 1 - 7115 MHz
Band Edge Frequency 7125 MHz




Figure 203 - 802.11ax HE20, RU 106-53, SISO, Core 1 - 7115 MHz
Band Edge Frequency 7125 MHz

20 MHz Bandwidth - Core 0 - Core 1 (CDD)

Mode	Data Rate/ MCS	Resource Size	Resource Index	TX Frequency (MHz)	Band Edge Frequency (MHz)	Peak Level (dBμV/m)	Average Level (dBμV/m)
802.11ax HE20	MCS 11x1	SU	-	5955	5925	72.03	55.26
802.11ax HE20	MCS 11x1	106	54	5955	5925	65.61	45.30
802.11ax HE20	MCS 4x1	SU	-	7095	7125	74.62	60.44
802.11ax HE20	MCS 11x1	106	54	7095	7125	70.10	48.79
802.11ax HE20	MCS 4x1	SU	-	7115	7125	79.16	65.11
802.11ax HE20	MCS 11x1	26	0	7115	7125	83.61	61.93

Table 250 - CDD Authorised Band Edge Results




Figure 204 - 802.11ax HE20, SU, CDD, Core 0 - Core 1 - 5955 MHz
Band Edge Frequency 5925 MHz






Figure 205 - 802.11ax HE20, RU 106-54, CDD, Core 0 - Core 1 - 5955 MHz
Band Edge Frequency 5925 MHz



**Figure 206 - 802.11ax HE20, SU, CDD, Core 0 - Core 1 - 7095 MHz
Band Edge Frequency 7125 MHz**



**Figure 207 - 802.11ax HE20, RU 106-54, CDD, Core 0 - Core 1 - 7095 MHz
Band Edge Frequency 7125 MHz**




Figure 208 - 802.11ax HE20, SU, CDD, Core 0 - Core 1 - 7115 MHz
Band Edge Frequency 7125 MHz




Figure 209 - 802.11ax HE20, RU 26-0, CDD, Core 0 - Core 1 - 7115 MHz
Band Edge Frequency 7125 MHz

20 MHz Bandwidth - Core 0 - Core 1 (SDM)

Mode	Data Rate/ MCS	Resource Size	Resource Index	TX Frequency (MHz)	Band Edge Frequency (MHz)	Peak Level (dBμV/m)	Average Level (dBμV/m)
802.11ax HE20	MCS 4x2	SU	-	5955	5925	71.66	56.48
802.11ax HE20	MCS 11x2	106	53	5955	5925	66.02	46.61
802.11ax HE20	MCS 2x2	SU	-	7095	7125	71.63	58.68
802.11ax HE20	MCS 11x2	106	53	7095	7125	70.71	49.70
802.11ax HE20	MCS 11x2	SU	-	7115	7125	76.74	65.68
802.11ax HE20	MCS 11x2	52	37	7115	7125	83.60	63.58

Table 251 - SDM Authorised Band Edge Results




Figure 210 - 802.11ax HE20, SU, SDM, Core 0 - Core 1 - 5955 MHz
Band Edge Frequency 5925 MHz







Figure 211 - 802.11ax HE20, RU 106-53, SDM, Core 0 - Core 1 - 5955 MHz
Band Edge Frequency 5925 MHz




**Figure 212 - 802.11ax HE20, SU, SDM, Core 0 - Core 1 - 7095 MHz
Band Edge Frequency 7125 MHz**



**Figure 213 - 802.11ax HE20, RU 106-53, SDM, Core 0 - Core 1 - 7095 MHz
Band Edge Frequency 7125 MHz**



**Figure 214 - 802.11ax HE20, SU, SDM, Core 0 - Core 1 - 7115 MHz
Band Edge Frequency 7125 MHz**




**Figure 215 - 802.11ax HE20, RU 52-37, SDM, Core 0 - Core 1 - 7115 MHz
Band Edge Frequency 7125 MHz**


20 MHz Bandwidth - Core 0 - Core 1 (TxBF)

Mode	Data Rate/ MCS	Resource Size	Resource Index	TX Frequency (MHz)	Band Edge Frequency (MHz)	Peak Level (dBμV/m)	Average Level (dBμV/m)
802.11ax HE20	MCS 4x1	SU	-	5955	5925	73.04	55.12
802.11ax HE20	MCS 11x1	SU	-	7075	7125	66.63	49.07
802.11ax HE20	MCS 11x1	SU	-	7095	7125	76.21	58.45


Table 252 - TxBF Authorised Band Edge Results



**Figure 216 - 802.11ax HE20, SU, TxBF, Core 0 - Core 1 - 5955 MHz
Band Edge Frequency 5925 MHz**



**Figure 217 - 802.11ax HE20, SU, TxBF, Core 0 - Core 1 - 7075 MHz
Band Edge Frequency 7125 MHz**



**Figure 218 - 802.11ax HE20, SU, TxBF, Core 0 - Core 1 - 7095 MHz
Band Edge Frequency 7125 MHz**

40 MHz Bandwidth - Core 0 (SISO)

Mode	Data Rate/ MCS	Resource Size	Resource Index	TX Frequency (MHz)	Band Edge Frequency (MHz)	Peak Level (dBμV/m)	Average Level (dBμV/m)
802.11ax HE40	MCS 11x1	SU	-	5965	5925	81.31	65.54
802.11ax HE40	MCS 11x1	106	53	5965	5925	57.20	45.70
802.11ax HE40	MCS 11x1	SU	-	7085	7125	83.62	65.60
802.11ax HE40	MCS 11x1	26	0	7085	7125	69.71	48.82

Table 253 - SISO Authorised Band Edge Results




Figure 219 - 802.11ax HE40, SU, SISO, Core 0 - 5965 MHz
Band Edge Frequency 5925 MHz






Figure 220 - 802.11ax HE40, RU 106-53, SISO, Core 0 - 5965 MHz
Band Edge Frequency 5925 MHz



**Figure 221 - 802.11ax HE40, SU, SISO, Core 0 - 7085 MHz
Band Edge Frequency 7125 MHz**



**Figure 222 - 802.11ax HE40, RU 26-0, SISO, Core 0 - 7085 MHz
Band Edge Frequency 7125 MHz**



40 MHz Bandwidth - Core 1 (SISO)

Mode	Data Rate/ MCS	Resource Size	Resource Index	TX Frequency (MHz)	Band Edge Frequency (MHz)	Peak Level (dBμV/m)	Average Level (dBμV/m)
802.11ax HE40	MCS 4x1	SU	-	5965	5925	78.47	62.85
802.11ax HE40	MCS 11x1	106	56	5965	5925	57.03	45.86
802.11ax HE40	MCS 11x1	SU	-	7085	7125	83.61	65.16
802.11ax HE40	MCS 11x1	52	37	7085	7125	67.99	48.82

Table 254 - SISO Authorised Band Edge Results




Figure 223 - 802.11ax HE40, SU, SISO, Core 1 - 5965 MHz
Band Edge Frequency 5925 MHz






Figure 224 - 802.11ax HE40, RU 106-56, SISO, Core 1 - 5965 MHz
Band Edge Frequency 5925 MHz



**Figure 225 - 802.11ax HE40, SU, SISO, Core 1 - 7085 MHz
Band Edge Frequency 7125 MHz**



**Figure 226 - 802.11ax HE40, RU 52-37, SISO, Core 1 - 7085 MHz
Band Edge Frequency 7125 MHz**