



Test Configuration			
Frequency Range:	5.725-5.850 GHz	Band:	U-NII-3
Limit Clause(s):	15.407 (a)(3) RSS-247 6.2.4.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11n HT20	Duty Cycle (%):	95.8
Modulation Coding Scheme:	MCS10	DCCF (dB):	0.19
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	3.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / 500 kHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5720	0.80	1.28	-	-	4.06	30.00	-25.94
5745	8.19	8.21	-	-	11.21	30.00	-18.79
5785	7.93	7.83	-	-	10.89	30.00	-19.11
5825	8.05	7.92	-	-	10.99	30.00	-19.01

Table 648 - Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	5.725-5.850 GHz	Band:	U-NII-3
Limit Clause(s):	15.407 (a)(3) RSS-247 6.2.4.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11n HT40	Duty Cycle (%):	92.6
Modulation Coding Scheme:	MCS10	DCCF (dB):	0.33
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	3.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / 500 kHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5710	-0.28	-0.00	-	-	2.87	30.00	-27.13
5755	5.05	5.25	-	-	8.17	30.00	-21.83
5795	5.39	4.95	-	-	8.18	30.00	-21.82

Table 649 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.725-5.850 GHz	Band:	U-NII-3
Limit Clause(s):	15.407 (a)(3) RSS-247 6.2.4.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ac VHT80	Duty Cycle (%):	89.0
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.51
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	3.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / 500 kHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5690	-2.52	-2.87	-	-	0.32	30.00	-29.68
5775	0.93	1.04	-	-	4.00	30.00	-26.00

Table 650 - Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	5.725-5.850 GHz	Band:	U-NII-3
Limit Clause(s):	15.407 (a)(3) RSS-247 6.2.4.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 SU	Duty Cycle (%):	97.3
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.12
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	3.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / 500 kHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5720	0.52	1.07	-	-	3.81	30.00	-26.19
5745	7.83	8.14	-	-	11.00	30.00	-19.00
5785	7.69	7.82	-	-	10.77	30.00	-19.23
5825	7.43	7.91	-	-	10.69	30.00	-19.31

Table 651 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.725-5.850 GHz	Band:	U-NII-3
Limit Clause(s):	15.407 (a)(3) RSS-247 6.2.4.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE40 SU	Duty Cycle (%):	96.8
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.14
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	3.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / 500 kHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5710	-0.81	-0.29	-	-	2.47	30.00	-27.53
5755	5.08	5.10	-	-	8.10	30.00	-21.90
5795	4.90	4.71	-	-	7.82	30.00	-22.18

Table 652 - Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	5.725-5.850 GHz	Band:	U-NII-3
Limit Clause(s):	15.407 (a)(3) RSS-247 6.2.4.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE80 SU	Duty Cycle (%):	96.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.15
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	3.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / 500 kHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5690	-2.90	-2.88	-	-	0.12	30.00	-29.88
5775	0.45	0.72	-	-	3.60	30.00	-26.40

Table 653 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.150-5.250 GHz	Band:	U-NII-1
Limit Clause(s):	15.407 (a)(1)(iv)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU26	Duty Cycle (%):	98.5
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.07
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	4.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5180 (RU26.0)	5.53	5.31	-	-	8.43	11.00	-2.57
5220 (RU26.0)	5.54	5.48	-	-	8.52	11.00	-2.48
5240 (RU26.8)	5.39	5.21	-	-	8.31	11.00	-2.69

Table 654 - FCC Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	5.150-5.250 GHz	Band:	U-NII-1
Limit Clause(s):	15.407 (a)(1)(iv)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU52	Duty Cycle (%):	98.6
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.06
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	4.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5180 (RU52.37)	5.04	5.57	-	-	8.32	11.00	-2.68
5220 (RU52.37)	5.57	5.66	-	-	8.63	11.00	-2.37
5240 (RU52.40)	5.67	5.70	-	-	8.70	11.00	-2.30

Table 655 - FCC Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.150-5.250 GHz	Band:	U-NII-1
Limit Clause(s):	15.407 (a)(1)(iv)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU106	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.06
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	4.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5180 (RU106.53)	5.65	5.77	-	-	8.72	11.00	-2.28
5220 (RU106.53)	5.46	5.94	-	-	8.72	11.00	-2.28
5240 (RU106.54)	6.00	5.79	-	-	8.91	11.00	-2.09

Table 656 - FCC Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	5.150-5.250 GHz	Band:	U-NII-1
Limit Clause(s):	RSS-247 6.2.1.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU26	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.06
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	4.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5180 (RU26.0)	0.20	-0.09	-	-	3.07	4.00	7.07	10.00	-2.93
5220 (RU26.0)	0.71	0.58	-	-	3.66	4.00	7.66	10.00	-2.34
5240 (RU26.8)	0.74	0.52	-	-	3.64	4.00	7.64	10.00	-2.36

Table 657 - ISED Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.150-5.250 GHz	Band:	U-NII-1
Limit Clause(s):	RSS-247 6.2.1.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU52	Duty Cycle (%):	98.5
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.07
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	4.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5180 (RU52.37)	0.63	0.50	-	-	3.58	4.00	7.58	10.00	-2.42
5220 (RU52.37)	0.19	0.51	-	-	3.36	4.00	7.36	10.00	-2.64
5240 (RU52.40)	0.20	0.94	-	-	3.59	4.00	7.59	10.00	-2.41

Table 658 - ISED Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	5.150-5.250 GHz	Band:	U-NII-1
Limit Clause(s):	RSS-247 6.2.1.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU106	Duty Cycle (%):	99.3
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.03
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	4.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5180 (RU106.53)	0.54	0.80	-	-	3.68	4.00	7.68	10.00	-2.32
5220 (RU106.53)	0.23	1.16	-	-	3.73	4.00	7.73	10.00	-2.27
5240 (RU106.54)	0.80	0.81	-	-	3.82	4.00	7.82	10.00	-2.18

Table 659 - ISED Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.250-5.350 GHz	Band:	U-NII-2A
Limit Clause(s):	15.407 (a)(2) RSS-247 6.2.2.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU52	Duty Cycle (%):	97.8
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.09
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	4.65
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5260 (RU52.37)	5.22	5.30	-	-	8.27	11.00	-2.73
5300 (RU52.37)	5.27	5.92	-	-	8.62	11.00	-2.38
5320 (RU52.40)	5.51	5.48	-	-	8.51	11.00	-2.49

Table 660 - Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	5.250-5.350 GHz	Band:	U-NII-2A
Limit Clause(s):	15.407 (a)(2) RSS-247 6.2.2.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU106	Duty Cycle (%):	98.1
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.08
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	4.65
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5260 (RU106.53)	5.31	5.63	-	-	8.48	11.00	-2.52
5300 (RU106.53)	5.07	5.76	-	-	8.44	11.00	-2.56
5320 (RU106.54)	5.68	5.36	-	-	8.53	11.00	-2.47

Table 661 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.470-5.725 GHz	Band:	U-NII-2C
Limit Clause(s):	15.407 (a)(2) RSS-247 6.2.3.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU52	Duty Cycle (%):	97.4
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.11
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	3.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5500 (RU52.37)	5.07	5.81	-	-	8.46	11.00	-2.54
5580 (RU52.37)	5.74	5.83	-	-	8.79	11.00	-2.21
5700 (RU52.40)	5.10	5.72	-	-	8.43	11.00	-2.57
5720 (RU52.39)	5.33	5.71	-	-	8.53	11.00	-2.47

Table 662 - Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	5.470-5.725 GHz	Band:	U-NII-2C
Limit Clause(s):	15.407 (a)(2) RSS-247 6.2.3.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU106	Duty Cycle (%):	98.0
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.09
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	3.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5500 (RU106.53)	5.08	5.90	-	-	8.52	11.00	-2.48
5580 (RU106.53)	5.74	6.04	-	-	8.90	11.00	-2.10
5700 (RU106.54)	5.95	5.99	-	-	8.98	11.00	-2.02
5720 (RU106.53)	5.43	5.95	-	-	8.71	11.00	-2.29

Table 663 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.725-5.850 GHz	Band:	U-NII-3
Limit Clause(s):	15.407 (a)(3) RSS-247 6.2.4.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU26	Duty Cycle (%):	97.6
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.11
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	3.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / 500 kHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5745 (RU26.0)	7.75	7.66	-	-	10.72	30.00	-19.28
5785 (RU26.0)	7.75	7.62	-	-	10.70	30.00	-19.30
5825 (RU26.8)	7.42	7.11	-	-	10.28	30.00	-19.72

Table 664 - Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	5.725-5.850 GHz	Band:	U-NII-3
Limit Clause(s):	15.407 (a)(3) RSS-247 6.2.4.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU52	Duty Cycle (%):	97.4
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.11
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	3.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / 500 kHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5720 (RU52.40)	2.30	2.83	-	-	5.58	30.00	-24.42
5745 (RU52.37)	7.80	8.03	-	-	10.93	30.00	-19.07
5785 (RU52.37)	7.82	8.10	-	-	10.97	30.00	-19.03
5825 (RU52.40)	7.14	7.79	-	-	10.49	30.00	-19.51

Table 665 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.725-5.850 GHz	Band:	U-NII-3
Limit Clause(s):	15.407 (a)(3) RSS-247 6.2.4.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU106	Duty Cycle (%):	98.3
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	0.08
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	3.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / 500 kHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5720 (RU106.54)	2.45	2.89	-	-	5.69	30.00	-24.31
5745 (RU106.53)	7.43	7.95	-	-	10.71	30.00	-19.29
5785 (RU106.53)	7.51	8.13	-	-	10.84	30.00	-19.16
5825 (RU106.54)	8.28	8.31	-	-	11.30	30.00	-18.70

Table 666 - Maximum Power Spectral Density Results



TxBF:

Test Configuration			
Frequency Range:	5.150-5.250 GHz	Band:	U-NII-1
Limit Clause(s):	15.407 (a)(1)(iv)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ac VHT20	Duty Cycle (%):	92.5
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.34
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	7.01
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5180	4.01	4.52	-	-	7.29	9.99	-2.70
5220	4.28	4.33	-	-	7.31	9.99	-2.68
5240	4.67	4.24	-	-	7.47	9.99	-2.52

Table 667 - FCC Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	5.150-5.250 GHz	Band:	U-NII-1
Limit Clause(s):	15.407 (a)(1)(iv)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ac VHT40	Duty Cycle (%):	93.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.32
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	7.01
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5190	1.33	1.74	-	-	4.55	9.99	-5.44
5230	4.15	4.69	-	-	7.44	9.99	-2.55

Table 668 - FCC Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.150-5.250 GHz	Band:	U-NII-1
Limit Clause(s):	15.407 (a)(1)(iv)	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ac VHT80	Duty Cycle (%):	67.2
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	1.72
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	7.01
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5210	-0.13	-0.04	-	-	2.93	9.99	-7.06

Table 669 - FCC Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	5.150-5.250 GHz	Band:	U-NII-1
Limit Clause(s):	RSS-247 6.2.1.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ac VHT20	Duty Cycle (%):	96.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.18
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	7.01
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5180	-2.93	-2.94	-	-	0.08	7.01	7.09	10.00	-2.91
5220	-3.50	-2.22	-	-	0.20	7.01	7.21	10.00	-2.79
5240	-2.53	-2.41	-	-	0.54	7.01	7.55	10.00	-2.45

Table 670 - ISED Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.150-5.250 GHz	Band:	U-NII-1
Limit Clause(s):	RSS-247 6.2.1.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ac VHT40	Duty Cycle (%):	93.3
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.30
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	7.01
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5190	-3.24	-3.06	-	-	-0.14	7.01	6.87	10.00	-3.13
5230	-2.91	-2.95	-	-	0.08	7.01	7.09	10.00	-2.91

Table 671 - ISED Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	5.150-5.250 GHz	Band:	U-NII-1
Limit Clause(s):	RSS-247 6.2.1.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ac VHT80	Duty Cycle (%):	93.8
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.28
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	7.01
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5210	-3.78	-3.41	-	-	-0.58	7.01	6.43	10.00	-3.57

Table 672 - ISED Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.250-5.350 GHz	Band:	U-NII-2A
Limit Clause(s):	15.407 (a)(2) RSS-247 6.2.2.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ac VHT20	Duty Cycle (%):	92.6
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.33
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	7.66
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5260	3.60	4.38	-	-	7.02	9.34	-2.32
5300	3.72	4.26	-	-	7.01	9.34	-2.33
5320	4.65	3.91	-	-	7.31	9.34	-2.03

Table 673 - FCC Maximum Power Spectral Density Results

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5260	3.60	4.38	-	-	7.02	11.00	-3.98
5300	3.72	4.26	-	-	7.01	11.00	-3.99
5320	4.65	3.91	-	-	7.31	11.00	-3.69

Table 674 - ISED Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.250-5.350 GHz	Band:	U-NII-2A
Limit Clause(s):	15.407 (a)(2) RSS-247 6.2.2.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ac VHT40	Duty Cycle (%):	91.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.38
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	7.66
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5270	3.59	4.16	-	-	6.90	9.34	-2.44
5310	0.02	-0.52	-	-	2.77	9.34	-6.57

Table 675 - FCC Maximum Power Spectral Density Results

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5270	3.59	4.16	-	-	6.90	11.00	-4.10
5310	0.02	-0.52	-	-	2.77	11.00	-8.23

Table 676 - ISED Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.250-5.350 GHz	Band:	U-NII-2A
Limit Clause(s):	15.407 (a)(2) RSS-247 6.2.2.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ac VHT80	Duty Cycle (%):	93.6
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.29
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	7.66
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5290	-2.95	-2.64	-	-	0.22	9.34	-9.12

Table 677 - FCC Maximum Power Spectral Density Results

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5290	-2.95	-2.64	-	-	0.22	11.00	-10.78

Table 678 - ISED Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.470-5.725 GHz	Band:	U-NII-2C
Limit Clause(s):	15.407 (a)(2) RSS-247 6.2.3.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ac VHT20	Duty Cycle (%):	83.5
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.79
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	6.61
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5500	5.40	5.31	-	-	8.36	10.39	-2.02
5580	5.50	5.25	-	-	8.39	10.39	-2.00
5700	5.29	2.79	-	-	7.23	10.39	-3.16
5720	6.57	5.83	-	-	9.22	10.39	-1.16

Table 679 - FCC Maximum Power Spectral Density Results

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5500	5.40	5.31	-	-	8.36	11.00	-2.64
5580	5.50	5.25	-	-	8.39	11.00	-2.61
5700	5.29	2.79	-	-	7.23	11.00	-3.77
5720	6.57	5.83	-	-	9.22	11.00	-1.78

Table 680 - ISED Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.470-5.725 GHz	Band:	U-NII-2C
Limit Clause(s):	15.407 (a)(2) RSS-247 6.2.3.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ac VHT40	Duty Cycle (%):	92.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.36
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	6.61
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5510	-0.04	0.04	-	-	3.01	10.39	-7.37
5550	4.38	4.92	-	-	7.66	10.39	-2.72
5670	4.31	4.68	-	-	7.51	10.39	-2.88
5710	5.13	4.37	-	-	7.78	10.39	-2.61

Table 681 - FCC Maximum Power Spectral Density Results

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5510	-0.04	0.04	-	-	3.01	11.00	-7.99
5550	4.38	4.92	-	-	7.66	11.00	-3.34
5670	4.31	4.68	-	-	7.51	11.00	-3.49
5710	5.13	4.37	-	-	7.78	11.00	-3.22

Table 682 - ISED Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.470-5.725 GHz	Band:	U-NII-2C
Limit Clause(s):	15.407 (a)(2) RSS-247 6.2.3.1	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ac VHT80	Duty Cycle (%):	92.2
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.35
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	6.61
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5530	-3.20	-3.35	-	-	-0.26	10.39	-10.65
5610	3.11	2.29	-	-	5.73	10.39	-4.66
5690	3.29	2.80	-	-	6.06	10.39	-4.33

Table 683 - FCC Maximum Power Spectral Density Results

Test Frequency (MHz)	PSD (dBm / MHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5530	-3.20	-3.35	-	-	-0.26	11.00	-11.26
5690	3.29	2.80	-	-	6.06	11.00	-4.94

Table 684 - ISED Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.725-5.850 GHz	Band:	U-NII-3
Limit Clause(s):	15.407 (a)(3)(i) RSS-247 6.2.4.2	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ac VHT20	Duty Cycle (%):	96.4
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.16
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	6.61
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / 500 kHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5720	1.60	1.94	-	-	4.78	29.39	-24.61
5745	8.56	9.68	-	-	12.16	29.79	-17.63
5785	9.03	8.76	-	-	11.90	29.79	-17.88
5825	9.50	6.19	-	-	11.16	29.79	-18.63

Table 685 - Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	5.725-5.850 GHz	Band:	U-NII-3
Limit Clause(s):	15.407 (a)(3)(i) RSS-247 6.2.4.2	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ac VHT40	Duty Cycle (%):	94.5
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.24
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	6.61
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / 500 kHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5710	-2.48	-0.68	-	-	1.53	29.39	-27.86
5755	6.32	5.79	-	-	9.08	29.79	-20.71
5795	7.15	6.11	-	-	9.67	29.79	-20.12

Table 686 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	5.725-5.850 GHz	Band:	U-NII-3
Limit Clause(s):	15.407 (a)(3)(i) RSS-247 6.2.4.2	Test Method(s):	C63.10 12.4.2.4 C63.10 12.6
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ac VHT80	Duty Cycle (%):	93.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.27
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	6.61
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	PSD (dBm / 500 kHz)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
5690	-3.87	-3.29	-	-	-0.56	29.39	-29.95
5775	0.17	0.62	-	-	3.41	29.79	-26.38

Table 687 - Maximum Power Spectral Density Results



FCC 47 CFR Part 15E, Limit Clause 15.407(a)

Condition of Operation	Frequency Range (MHz)			
	5150-5250	5250-5350	5470-5725	5725-5850
Max Conducted Power Spectral Density	17 dBm/MHz for master device 11 dBm/MHz for mobile/portable client device	11 dBm/MHz		30 dBm/500 kHz

Table 688

ISED RSS-247, Limit Clause 6.2.1.1, 6.2.2.1, 6.2.3.1, 6.2.4.1 and 6.2.5.2

Device	Frequency Range (MHz)				
	5150-5250	5250-5350	5470-5725	5725-5850	5850-5895
OEM installed in vehicles	-	-	-	-	-
Other	≤10 dBm/MHz*	≤11 dBm/MHz	≤11 dBm/MHz	≤30 dBm/500kHz	Fixed Outdoor Access Point: 23 dBm/MHz* Fixed Outdoor Client: 17 dBm/MHz Indoor Access Point: 20 dBm/MHz Indoor Subordinate: 20 dBm/MHz Indoor Client: 14 dBm/MHz

Table 689

*Maximum power spectral density specified as EIRP.



2.4.7 Test Location and Test Equipment Used

This test was carried out in RF Chamber 18 and RF Laboratory 14.

Instrument	Manufacturer	Type No.	TE No.	Calibration Period (months)	Calibration Expiry Date
Hygrometer	Rotronic	I-1000	3068	12	07-Nov-2024
1800-6000 MHz Power Splitter	Mini-Circuits	ZN2PD-63-S+	4055	-	O/P Mon
AC Programmable Power Supply	iTech	IT7324	5225	-	O/P Mon
Attenuator 5W 30dB DC-18GHz	Aaren	AT40A-4041-D18-30	5505	12	22-Feb-2025
2-Way Power Divider (2-8 GHz)	Aaren	AT30A-TE0208-2-AF	5685	12	02-Jan-2025
USB Power Sensor	Boonton	RTP5008	5820	12	07-Feb-2025
USB Power Sensor	Boonton	RTP5008	5821	12	07-Feb-2025
Digital Multimeter	Fluke	115	6145	12	06-Jun-2025
MXA Signal Analyser	Keysight Technologies	N9020B	6417	24	26-Feb-2025
MXA Signal Analyser	Keysight Technologies	N9020B	6419	24	28-Feb-2025
Signal Conditioning Unit	TUV SUD	SPECTRUM_SCU001	6426	12	07-Feb-2025
Directional Coupler 2-8GHz	RF-Lambda	RFDC2G8G10	6447	-	O/P Mon
Directional Coupler 2-8GHz	RF-Lambda	RFDC2G8G10	6448	-	O/P Mon
Signal Conditioning Unit	TUV SUD	SPECTRUM_SCU001	6517	12	22-Feb-2025
Signal Conditioning Unit	TUV SUD	SPECTRUM_SCU001	6518	12	16-Feb-2025
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6526	12	22-Feb-2025
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6527	12	05-Mar-2025
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6529	12	16-Feb-2025
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6530	12	16-Feb-2025
USB Wideband Power Sensor	Boonton	RTP5008	6585	12	20-Feb-2025
USB Wideband Power Sensor	Boonton	RTP5008	6586	12	20-Feb-2025
USB Wideband Power Sensor	Boonton	RTP5008	6587	12	13-Feb-2025
USB Wideband Power Sensor	Boonton	RTP5008	6588	12	13-Feb-2025
AC Programmable Power Supply	iTech	IT7324	6662	-	O/P Mon
AC Programmable Power Supply	iTech	IT7324	6665	-	O/P Mon
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6752	12	06-Feb-2025
SCU Cable Assembly	TUV SUD	SPECTRUM_SCU_CA	6753	12	06-Feb-2025

Table 690

O/P Mon - Output Monitored using calibrated equipment



2.5 Authorised Band Edges

2.5.1 Specification Reference

FCC 47 CFR Part 15E, Clause 15.407 (b)
ISED RSS-247, Clause 6.2

2.5.2 Equipment Under Test and Modification State

A3238, S/N: NQMK2V7Q9C - Modification State 0
A3238, S/N: V4KFHR9J44 - Modification State 0
A3238, S/N: QMQLY9FYFQ - Modification State 0
A3238, S/N: N4N7KFP797 - Modification State 0

2.5.3 Date of Test

27-May-2024 to 06-Sept-2024

2.5.4 Test Method

The test was performed in accordance with ANSI C63.10, clause 6.6.

EIRP limits were converted to field strength at 3 m using the following formula:

Field Strength (dB μ V/m at 3 m) = EIRP (dBm) + 95.2 dB

Authorised band edge measurements were performed, with the device operating in SISO and MIMO configurations, across the various modes supported by the device.

The measurements displayed within this report, have been limited to those modes which have been shown to be worst case.

Further measurements are held on file by TÜV SÜD and are available if required.

2.5.5 Environmental Conditions

Ambient Temperature 21.9 - 24.3 °C
Relative Humidity 38.1 - 53.0 %



2.5.6 Test Results

5 GHz WLAN

20 MHz Bandwidth - Core 0 (SISO)

Mode	Data Rate/ MCS	Resource Size	Resource Index	TX Frequency (MHz)	Band Edge Frequency (MHz)	Peak Level (dBµV/m)
802.11a	24 Mbps	-	-	5500	5470	63.70
802.11a	54 Mbps	-	-	5520	5470	60.99
802.11n HT20	MCS 7	-	-	5500	5470	62.49
802.11n HT20	MCS 7	-	-	5520	5470	62.84
802.11ax HE20	MCS 2x1	SU	-	5500	5470	63.50
802.11ax HE20	MCS 11x1	106	54	5500	5470	63.51
802.11ax HE20	MCS 11x1	SU	-	5520	5470	63.56
802.11ax HE20	MCS 11x1	106	54	5520	5470	56.60
802.11a	24 Mbps	-	-	5745	5725	58.55
802.11a	12 Mbps	-	-	5765	5725	57.80
802.11n HT20	MCS 4	-	-	5745	5725	58.02
802.11n HT20	MCS 2	-	-	5765	5725	58.19
802.11ax HE20	MCS 4x1	SU	-	5745	5725	57.82
802.11ax HE20	MCS 11x1	106	54	5745	5725	57.11
802.11ax HE20	MCS 2x1	SU	-	5765	5725	57.65
802.11a	54 Mbps	-	-	5680	5725	60.96
802.11a	12 Mbps	-	-	5700	5725	63.61
802.11n HT20	MCS 7	-	-	5680	5725	63.25
802.11n HT20	MCS 2	-	-	5700	5725	63.57
802.11ax HE20	MCS 11x1	SU	-	5680	5725	63.67
802.11ax HE20	MCS 11x1	106	54	5680	5725	57.27
802.11ax HE20	MCS 11x1	SU	-	5700	5725	63.59
802.11ax HE20	MCS 11x1	106	54	5700	5725	63.26
802.11a	24 Mbps	-	-	5720	5850	56.46
802.11a	12 Mbps	-	-	5805	5850	57.64
802.11a	12 Mbps	-	-	5825	5850	58.20
802.11n HT20	MCS 2	-	-	5720	5850	56.25
802.11n HT20	MCS 4	-	-	5805	5850	57.23
802.11n HT20	MCS 2	-	-	5825	5850	58.24
802.11ax HE20	MCS 4x1	SU	-	5720	5850	56.16
802.11ax HE20	MCS 11x1	106	54	5720	5850	55.65
802.11ax HE20	MCS 4x1	SU	-	5805	5850	58.13
802.11ax HE20	MCS 2x1	SU	-	5825	5850	57.77
802.11ax HE20	MCS 11x1	106	54	5825	5850	57.06

Table 691 - SISO Authorised Band Edge Results




Figure 348 - 802.11a, SISO, Core 0 - 5500 MHz
Band Edge Frequency 5470 MHz




Figure 349 - 802.11a, SISO, Core 0 - 5520 MHz
Band Edge Frequency 5470 MHz




Figure 350 - 802.11n HT20, SISO, Core 0 - 5500 MHz
Band Edge Frequency 5470 MHz







Figure 351 - 802.11n HT20, SISO, Core 0 - 5520 MHz
Band Edge Frequency 5470 MHz




**Figure 352 - 802.11ax HE20, SU, SISO, Core 0 - 5500 MHz
Band Edge Frequency 5470 MHz**




**Figure 353 - 802.11ax HE20, RU 106-54, SISO, Core 0 - 5500 MHz
Band Edge Frequency 5470 MHz**




**Figure 354 - 802.11ax HE20, SU, SISO, Core 0 - 5520 MHz
Band Edge Frequency 5470 MHz**




**Figure 355 - 802.11ax HE20, RU 106-54, SISO, Core 0 - 5520 MHz
Band Edge Frequency 5470 MHz**




**Figure 356 - 802.11a, SISO, Core 0 - 5745 MHz
Band Edge Frequency 5725 MHz**




**Figure 357 - 802.11a, SISO, Core 0 - 5765 MHz
Band Edge Frequency 5725 MHz**




**Figure 358 - 802.11n HT20, SISO, Core 0 - 5745 MHz
Band Edge Frequency 5725 MHz**




**Figure 359 - 802.11n HT20, SISO, Core 0 - 5765 MHz
Band Edge Frequency 5725 MHz**




**Figure 360 - 802.11ax HE20, SU, SISO, Core 0 - 5745 MHz
Band Edge Frequency 5725 MHz**




**Figure 361 - 802.11ax HE20, RU 106-54, SISO, Core 0 - 5745 MHz
Band Edge Frequency 5725 MHz**




**Figure 362 - 802.11ax HE20, SU, SISO, Core 0 - 5765 MHz
Band Edge Frequency 5725 MHz**




**Figure 363 - 802.11a, SISO, Core 0 - 5680 MHz
Band Edge Frequency 5725 MHz**




**Figure 364 - 802.11a, SISO, Core 0 - 5700 MHz
Band Edge Frequency 5725 MHz**




**Figure 365 - 802.11n HT20, SISO, Core 0 - 5680 MHz
Band Edge Frequency 5725 MHz**




**Figure 366 - 802.11n HT20, SISO, Core 0 - 5700 MHz
Band Edge Frequency 5725 MHz**




**Figure 367 - 802.11ax HE20, SU, SISO, Core 0 - 5680 MHz
Band Edge Frequency 5725 MHz**




**Figure 368 - 802.11ax HE20, RU 106-54, SISO, Core 0 - 5680 MHz
Band Edge Frequency 5725 MHz**




**Figure 369 - 802.11ax HE20, SU, SISO, Core 0 - 5700 MHz
Band Edge Frequency 5725 MHz**




**Figure 370 - 802.11ax HE20, RU 106-54, SISO, Core 0 - 5700 MHz
Band Edge Frequency 5725 MHz**




**Figure 371 - 802.11a, SISO, Core 0 - 5720 MHz
Band Edge Frequency 5850 MHz**




**Figure 372 - 802.11a, SISO, Core 0 - 5805 MHz
Band Edge Frequency 5850 MHz**




**Figure 373 - 802.11a, SISO, Core 0 - 5825 MHz
Band Edge Frequency 5850 MHz**




**Figure 374 - 802.11n HT20, SISO, Core 0 - 5720 MHz
Band Edge Frequency 5850 MHz**




**Figure 375 - 802.11n HT20, SISO, Core 0 - 5805 MHz
Band Edge Frequency 5850 MHz**




**Figure 376 - 802.11n HT20, SISO, Core 0 - 5825 MHz
Band Edge Frequency 5850 MHz**




**Figure 377 - 802.11ax HE20, SU, SISO, Core 0 - 5720 MHz
Band Edge Frequency 5850 MHz**




**Figure 378 - 802.11ax HE20, RU 106-54, SISO, Core 0 - 5720 MHz
Band Edge Frequency 5850 MHz**



**Figure 379 - 802.11ax HE20, SU, SISO, Core 0 - 5805 MHz
Band Edge Frequency 5850 MHz**



**Figure 380 - 802.11ax HE20, SU, SISO, Core 0 - 5825 MHz
Band Edge Frequency 5850 MHz**



**Figure 381 - 802.11ax HE20, RU 106-54, SISO, Core 0 - 5825 MHz
Band Edge Frequency 5850 MHz**



20 MHz Bandwidth - Core 1 (SISO)

Mode	Data Rate/ MCS	Resource Size	Resource Index	TX Frequency (MHz)	Band Edge Frequency (MHz)	Peak Level (dBμV/m)
802.11a	12 Mbps	-	-	5500	5470	63.43
802.11a	54 Mbps	-	-	5520	5470	59.63
802.11n HT20	MCS 7	-	-	5500	5470	63.59
802.11n HT20	MCS 7	-	-	5520	5470	60.16
802.11ax HE20	MCS 11x1	SU	-	5500	5470	63.38
802.11ax HE20	MCS 11x1	106	54	5500	5470	62.57
802.11ax HE20	MCS 11x1	SU	-	5520	5470	63.26
802.11ax HE20	MCS 11x1	106	54	5520	5470	55.82
802.11a	54 Mbps	-	-	5745	5725	57.22
802.11a	54 Mbps	-	-	5765	5725	57.10
802.11n HT20	MCS 4	-	-	5745	5725	57.25
802.11n HT20	MCS 2	-	-	5765	5725	56.99
802.11ax HE20	MCS 2x1	SU	-	5745	5725	57.67
802.11ax HE20	MCS 11x1	52	37	5745	5725	56.79
802.11ax HE20	MCS 2x1	SU	-	5765	5725	57.09
802.11a	54 Mbps	-	-	5680	5725	62.32
802.11a	24 Mbps	-	-	5700	5725	63.49
802.11n HT20	MCS 7	-	-	5680	5725	63.65
802.11n HT20	MCS 2	-	-	5700	5725	63.40
802.11ax HE20	MCS 4x1	SU	-	5680	5725	63.32
802.11ax HE20	MCS 11x1	106	54	5680	5725	56.69
802.11ax HE20	MCS 2x1	SU	-	5700	5725	63.61
802.11ax HE20	MCS 11x1	106	54	5700	5725	63.18
802.11a	54 Mbps	-	-	5720	5850	56.22
802.11a	24 Mbps	-	-	5805	5850	58.79
802.11a	54 Mbps	-	-	5825	5850	58.38
802.11n HT20	MCS 7	-	-	5720	5850	56.71
802.11n HT20	MCS 2	-	-	5805	5850	57.90
802.11n HT20	MCS 4	-	-	5825	5850	58.13
802.11ax HE20	MCS 4x1	SU	-	5720	5850	56.05
802.11ax HE20	MCS 11x1	52	37	5720	5850	56.12
802.11ax HE20	MCS 2x1	SU	-	5805	5850	58.14
802.11ax HE20	MCS 11x1	SU	-	5825	5850	57.61
802.11ax HE20	MCS 11x1	106	54	5825	5850	58.73

Table 692 - SISO Authorised Band Edge Results




Figure 382 - 802.11a, SISO, Core 1 - 5500 MHz
Band Edge Frequency 5470 MHz







Figure 383 - 802.11a, SISO, Core 1 - 5520 MHz
Band Edge Frequency 5470 MHz




**Figure 384 - 802.11n HT20, SISO, Core 1 - 5500 MHz
Band Edge Frequency 5470 MHz**



**Figure 385 - 802.11n HT20, SISO, Core 1 - 5520 MHz
Band Edge Frequency 5470 MHz**



**Figure 386 - 802.11ax HE20, SU, SISO, Core 1 - 5500 MHz
Band Edge Frequency 5470 MHz**



**Figure 387 - 802.11ax HE20, RU 106-54, SISO, Core 1 - 5500 MHz
Band Edge Frequency 5470 MHz**




Figure 388 - 802.11ax HE20, SU, SISO, Core 1 - 5520 MHz
Band Edge Frequency 5470 MHz







Figure 389 - 802.11ax HE20, RU 106-54, SISO, Core 1 - 5520 MHz
Band Edge Frequency 5470 MHz




**Figure 390 - 802.11a, SISO, Core 1 - 5745 MHz
Band Edge Frequency 5725 MHz**




**Figure 391 - 802.11a, SISO, Core 1 - 5765 MHz
Band Edge Frequency 5725 MHz**




**Figure 392 - 802.11n HT20, SISO, Core 1 - 5745 MHz
Band Edge Frequency 5725 MHz**




**Figure 393 - 802.11n HT20, SISO, Core 1 - 5765 MHz
Band Edge Frequency 5725 MHz**




**Figure 394 - 802.11ax HE20, SU, SISO, Core 1 - 5745 MHz
Band Edge Frequency 5725 MHz**




**Figure 395 - 802.11ax HE20, RU 52-37, SISO, Core 1 - 5745 MHz
Band Edge Frequency 5725 MHz**




**Figure 396 - 802.11ax HE20, SU, SISO, Core 1 - 5765 MHz
Band Edge Frequency 5725 MHz**




**Figure 397 - 802.11a, SISO, Core 1 - 5680 MHz
Band Edge Frequency 5725 MHz**




**Figure 398 - 802.11a, SISO, Core 1 - 5700 MHz
Band Edge Frequency 5725 MHz**




**Figure 399 - 802.11n HT20, SISO, Core 1 - 5680 MHz
Band Edge Frequency 5725 MHz**




**Figure 400 - 802.11n HT20, SISO, Core 1 - 5700 MHz
Band Edge Frequency 5725 MHz**




**Figure 401 - 802.11ax HE20, SU, SISO, Core 1 - 5680 MHz
Band Edge Frequency 5725 MHz**




**Figure 402 - 802.11ax HE20, RU 106-54, SISO, Core 1 - 5680 MHz
Band Edge Frequency 5725 MHz**




**Figure 403 - 802.11ax HE20, SU, SISO, Core 1 - 5700 MHz
Band Edge Frequency 5725 MHz**




**Figure 404 - 802.11ax HE20, RU 106-54, SISO, Core 1 - 5700 MHz
Band Edge Frequency 5725 MHz**




**Figure 405 - 802.11a, SISO, Core 1 - 5720 MHz
Band Edge Frequency 5850 MHz**




**Figure 406 - 802.11a, SISO, Core 1 - 5805 MHz
Band Edge Frequency 5850 MHz**




**Figure 407 - 802.11a, SISO, Core 1 - 5825 MHz
Band Edge Frequency 5850 MHz**




**Figure 408 - 802.11n HT20, SISO, Core 1 - 5720 MHz
Band Edge Frequency 5850 MHz**



**Figure 409 - 802.11n HT20, SISO, Core 1 - 5805 MHz
Band Edge Frequency 5850 MHz**



**Figure 410 - 802.11n HT20, SISO, Core 1 - 5825 MHz
Band Edge Frequency 5850 MHz**



**Figure 411 - 802.11ax HE20, SU, SISO, Core 1 - 5720 MHz
Band Edge Frequency 5850 MHz**