

RF Exposure Exemption Report

Apple Inc
Model: A3247

In accordance with FCC CFR 47 Pt 1.1307

Prepared for: Apple Inc
One Apple Park Way
Cupertino, California
95014, USA



**Add value.
Inspire trust.**

COMMERCIAL-IN-CONFIDENCE

FCC ID: BCGA3247

Document 75960544-14 Issue: 03

SIGNATURE			
NAME	JOB TITLE	RESPONSIBLE FOR	ISSUE DATE
Matthew Russell	Chief Engineer (RF)	Authorised Signatory	14-October-2024

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD document control rules.

FCC Accreditation
90987 Octagon House, Fareham Test Laboratory

EXECUTIVE SUMMARY

The wireless devices described within this report are compliant with the exemption criteria related to human exposure to electromagnetic fields laid out in FCC CFR 47 Part 1.1307.

		DISCLAIMER AND COPYRIGHT This non-binding report has been prepared by TÜV SÜD with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD. No part of this document may be reproduced without the prior written approval of TÜV SÜD. © 2024 TÜV SÜD. This report relates only to the actual item/items tested.
ACCREDITATION Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation. Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited).		

TÜV SÜD
is a trading name of TÜV SÜD Ltd
Registered in Scotland at East Kilbride,
Glasgow G75 0QF, United Kingdom
Registered number: SC215164

TÜV SÜD Ltd is a
TÜV SÜD Group Company

Phone: +44 (0) 1489 558100
Fax: +44 (0) 1489 558101
www.tuvsud.com/en

TÜV SÜD
Octagon House
Concorde Way
Fareham
Hampshire PO15 5RL
United Kingdom



Contents

1	Report Summary	2
1.1	Report Modification Record.....	2
1.2	Introduction.....	2
1.3	Brief Summary of Results	3
1.4	Product Information	4
2	Assessment Details	7
2.1	Single RF Source options for determination of exemption.....	7
2.2	Multiple RF Sources options for determination of exemption.	8
2.3	Individual Antenna Port Exposure Results.....	9
2.4	Combined Antenna Port RF Exposure Results using "1.1307(b)(3)(i)(B) SAR / MPE Exemption".....	12



1 Report Summary

1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
1	First Issue	24-July-2024
2	6 GHz WLAN evaluated using FCC 1.1307(b)(3)(i)(C) 'Option C' (MPE Based Exemption)	08-October-2024
3	Re-evaluated based on "Mobile" device	14-October-2024

Table 1

1.2 Introduction

Applicant	Apple Inc
Manufacturer	Apple Inc
Model Number(s)	A3247
Hardware Version(s)	REV1.0
Software Version(s)	N/A
Specification/Issue/Date	FCC 47 CFR Part 1.1307: 2022
Related Document(s)	<ul style="list-style-type: none">• KDB 447498 D04 v01



1.3 Brief Summary of Results

The wireless device described within this report was compliant with the restrictions related to human exposure to electromagnetic fields for both general public and worker/occupational exposures for a separation distance of 20.1 cm.

The calculations shown in this report were made in accordance with the procedures specified in the applied test specification(s).



1.4 Product Information

1.4.1 Technical Description

The equipment under test (EUT) was a desktop computer.

1.4.2 Transmitter Description

The following radio access technologies and frequency bands are supported by the equipment under test.

Radio Access Technology	Frequency Band (MHz)	Minimum Frequency (MHz)	Output Power (dBm)	Duty Cycle (%)
Bluetooth (SISO) Core 0	2400-2483.5	2402	17.5	100
Bluetooth (SISO) Core 1	2400-2483.5	2402	17	100
Bluetooth (SISO) Core 2	2400-2483.5	2402	12	100
Bluetooth (2x2 (MIMO) Core 0 and Core 1	2400-2483.5	2402	20.5	100
Thread (SISO) Core 0	2400-2483.5	2405	19.5	100
Thread (SISO) Core 1	2400-2483.5	2405	20	100
Thread (SISO) Core 2	2400-2483.5	2405	12.5	100
2.4 GHz WLAN (SISO) Core 0	2400-2483.5	2412	22.5	100
2.4 GHz WLAN (SISO) Core 1	2400-2483.5	2412	22.5	100
2.4 GHz WLAN (2x2 MIMO) Core 0 and Core 1	2400-2483.5	2412	25.5	100
5 GHz WLAN (SISO) Core 0	5150-5850	5180	21.5	100
5 GHz WLAN (SISO) Core 1	5150-5850	5180	21.5	100
5 GHz WLAN (2x2 MIMO) Core 0 and Core 1	5150-5850	5180	24.5	100
6 GHz WLAN (SISO) Core 0	5925-7125	5955	21.5	100
6 GHz WLAN (SISO) Core 1	5925-7125	5955	21.5	100
6 GHz WLAN (2x2 MIMO) Core 0 and Core 1	5925-7125	5955	24.5	100
NB Core 0	UNII-1	5162	14	100
NB Core 1	UNII-1	5162	12	100
NB Core 0 and Core 1	UNII-1	5162	12	100
NB Core 0	UNII-3	5733	14	100
NB Core 1	UNII-3	5733	14	100
NB Core 0 and Core 1	UNII-3	5733	17	100

Table 2 – Transmitter Description - FCC

Note: Transmitter power includes upper bounds of uncertainty therefore maximum values are used.



1.4.3 Antenna Description

The following antennas are supported by the equipment under test.

Radio Access Technology	Antenna Model	Frequency Band (MHz)	Gain (dBi)	Antenna length (cm)	Minimum Separation Distance (cm)
Bluetooth / Thread / 2.4 GHz WLAN – Core 0	Not Specified	2400-2483.5	2.60	5.17	20.1
Bluetooth / Thread / 2.4 GHz WLAN – Core 1	Not Specified	2400-2483.5	2.30	3.11	20.1
Bluetooth / Thread / 2.4 GHz WLAN – Core 2	Not Specified	2400-2483.5	1.40	4.82	20.1
5 GHz WLAN – Core 0	Not Specified	5150-5850	4.60	5.17	20.1
5 GHz WLAN – Core 1	Not Specified	5150-5850	6.40	3.11	20.1
6 GHz WLAN – Core 0	Not Specified	5925-7125	3.6	5.17	20.1
6 GHz WLAN – Core 1	Not Specified	5925-7125	4.9	3.11	20.1
NB UNII-1 Core 0	Not Specified	5150-5250	4.3	5.17	20.1
NB UNII-1 Core 1	Not Specified	5150-5250	5.9	3.11	20.1
NB UNII-3 Core 0	Not Specified	5725-5850	4.3	5.17	20.1
NB UNII-3 Core 1	Not Specified	5725-5850	4.1	3.11	20.1

Table 3 – Antenna Description

In the case of more than one type of antenna being supported by the equipment, the calculation is based on the maximum of the antenna gains. If other antennas can be used that have greater gains, the minimum separation distances will need to be recalculated.

Note: Antenna gain includes upper bounds of uncertainty therefore maximum values are used.



1.4.4 Equipment Configuration

The device supports the following modes:-

- Bluetooth can operate in SISO modes on Core 0, 1, 2 & MIMO Mode on Core 0 – 1
- Thread can operate in SISO modes on Core 0, 1, 2
- WLAN can operate in SISO modes on Core 0, 1 & MIMO Mode on Core 0 – 1
- NB can operate in SISO modes on Core 0, 1 & MIMO Mode on Core 0 – 1

The device supports simultaneous operation in the following modes:

- Bluetooth or Thread and 5 GHz / 6 GHz WLAN
- Narrowband (Core 0) and 2.4 GHz WLAN (Core 1)
- Narrowband (Core 1) and 2.4 GHz WLAN (Core 0)

Worst case configurations for simultaneous transmission were identified as;

Combination 1 - Bluetooth (2x2 MIMO on Core 0 & 1) + 6 GHz WLAN (2x2 MIMO on Core 0 & 1)

Combination 2 - 2.4 GHz WLAN (SISO) Core 0 + NB Core 1



2 Assessment Details

2.1 Single RF Source options for determination of exemption.

Option	Reference	RF Exposure Test Exemptions for Single Source												
A (1-mW Test Exemption)	FCC 1.1307(b)(3)(i)(A)	The available maximum time averaged power is no more than 1 mW, regardless of separation distance.												
B (SAR-Based Exemption)	FCC 1.1307(b)(3)(i)(B)	<p>The available maximum timeaveraged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:</p> $P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$ <p>Where</p> $x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$ <p>and</p> $ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$ <p><i>d</i> = the separation distance (cm);</p>												
C (MPE-Based Exemption)	FCC 1.1307(b)(3)(i)(C)	<p>Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).</p> <p>TABLE 1 TO § 1.1307(b)(3)(i)(C)—SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION</p> <table border="1"> <thead> <tr> <th>RF Source frequency (MHz)</th> <th>Threshold ERP (watts)</th> </tr> </thead> <tbody> <tr> <td>0.3–1.34</td> <td>1,920 R².</td> </tr> <tr> <td>1.34–30</td> <td>3,450 R²/f².</td> </tr> <tr> <td>30–300</td> <td>3.83 R².</td> </tr> <tr> <td>300–1,500</td> <td>0.0128 R²f.</td> </tr> <tr> <td>1,500–100,000</td> <td>19.2R².</td> </tr> </tbody> </table>	RF Source frequency (MHz)	Threshold ERP (watts)	0.3–1.34	1,920 R ² .	1.34–30	3,450 R ² /f ² .	30–300	3.83 R ² .	300–1,500	0.0128 R ² f.	1,500–100,000	19.2R ² .
RF Source frequency (MHz)	Threshold ERP (watts)													
0.3–1.34	1,920 R ² .													
1.34–30	3,450 R ² /f ² .													
30–300	3.83 R ² .													
300–1,500	0.0128 R ² f.													
1,500–100,000	19.2R ² .													



2.2 Multiple RF Sources options for determination of exemption.

Option	Reference	
A 1-mW Test Exemption for Multiple Sources	FCC 1.1307(b)(3)(ii)(A)	The available maximum time averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those is paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).
B Simultaneous Transmission with both SAR-based and MPE- Based Test Exemptions	FCC 1.1307(b)(3)(ii)(B)	in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation. $\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$



2.3 Individual Antenna Port Exposure Results

2.3.1 Calculation of Exposure at Specified Separation Distance

The frequencies shown in the tables below have been chosen based on the lowest possible frequency that the EUT can transmit. A full list of the regional requirements is shown in Annex A.

RAT	Frequency (MHz)	Conducted Power Output mW	Duty Cycle %	Time Average Conducted Power Output mW	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Minimum Antenna to User Separation Distance (mm)	Pth (mW) 1.1307 (b)(3)(i)(B)	Greater of Max time averaged conducted power or ERP? mW	1.1307(b)(3)(i)(B) Exemption (Yes/No) (300 MHz to 6 GHz, 0.5 cm to 40 cm)
Bluetooth (SISO) Core 0	2402	56.234	100	56.234	1.820	102.282	62.367	201	3060	62.367	Yes
Bluetooth (SISO) Core 1	2402	50.119	100	50.119	1.698	85.114	51.899	201	3060	51.899	Yes
Bluetooth (SISO) Core 2	2402	15.849	100	15.849	1.380	21.878	13.340	201	3060	15.849	Yes
Bluetooth (2x2 (MIMO) Core 0 and Core 1	2402	112.202	100	112.202	1.820	204.174	124.496	201	3060	124.496	Yes
Thread (SISO) Core 0	2405	89.125	100	89.125	1.820	162.181	98.891	201	3060	98.891	Yes
Thread (SISO) Core 1	2405	100.000	100	100.000	1.698	169.824	103.551	201	3060	103.551	Yes
Thread (SISO) Core 2	2405	17.783	100	17.783	1.380	24.547	14.968	201	3060	17.783	Yes
2.4 GHz WLAN (SISO) Core 0	2412	177.828	100	177.828	1.820	323.594	197.313	201	3060	197.313	Yes
2.4 GHz WLAN (SISO) Core 1	2412	177.828	100	177.828	1.698	301.995	184.143	201	3060	184.143	Yes
2.4 GHz WLAN (2x2 MIMO) Core 0 and Core 1	2412	354.813	100	354.813	1.820	645.654	393.692	201	3060	393.692	Yes
5 GHz WLAN (SISO) Core 0	5180	141.254	100	141.254	2.884	407.380	248.403	201	3060	248.403	Yes
5 GHz WLAN (SISO) Core 1	5180	141.254	100	141.254	4.365	616.595	375.973	201	3060	375.973	Yes
5 GHz WLAN (2x2 MIMO) Core 0 and Core 1	5180	281.838	100	281.838	4.365	1230.269	750.164	201	3060	750.164	Yes
NB Core 0	5162	25.119	100	25.119	2.692	67.608	41.225	201	3060	41.225	Yes
NB Core 1	5162	15.849	100	15.849	3.890	61.660	37.597	201	3060	37.597	Yes
NB Core 0 and Core 1	5162	15.849	100	15.849	2.692	42.658	26.011	201	3060	26.011	Yes



RAT	Frequency (MHz)	Conducted Power Output mW	Duty Cycle %	Time Average Conducted Power Output mW	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Minimum Antenna to User Separation Distance (mm)	Pth (mW) 1.1307 (b)(3)(i)(B)	Greater of Max time averaged conducted power or ERP? mW	1.1307(b)(3)(i)(B) Exemption (Yes/No) (300 MHz to 6 GHz, 0.5 cm to 40 cm)
NB Core 0	5733	25.119	100	25.119	2.692	67.608	41.225	201	3060	41.225	Yes
NB Core 1	5733	25.119	100	25.119	2.570	64.565	39.369	201	3060	39.369	Yes
NB Core 0 and Core 1	5733	50.119	100	50.119	2.692	134.896	82.254	201	3060	82.254	Yes

Table 4 – Transmitter Result

The calculations show that the individual transmitters comply with FCC 1.1307(b)(3)(i)(B) SAR-based exemption at a minimum distance of 0.201 m.



2.3.2 Single Source Calculation of Exposure at Specified Separation Distance FCC 1.1307(b)(3)(i)(C) ‘Option C’ (MPE Based Exemption)

RAT	Frequency (MHz)	Conducted Power Output (mW)	Duty Cycle %	Time Average Conducted Power Output (mW)	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Minimum separation distance for MPE evaluation $\lambda/2$ π mm	Actual Distance (mm)	Threshold ERP (mW)	1.1307(b)(3)(i)(C) Exemption (Yes/No) (300 kHz to 100 GHz)
6 GHz WLAN (SISO) Core 0	5955	141.254	100	141.254	3.090	436.516	266.168	8.0	201	776	Yes
6 GHz WLAN (SISO) Core 1	5955	141.254	100	141.254	3.090	436.516	266.168	8.0	201	776	Yes
6 GHz WLAN (2x2 MIMO) Core 0 and Core 1	5955	281.838	100	281.838	3.090	870.964	531.08	8.0	201	776	Yes

Table 5 – Transmitter Result

The calculations show that the individual transmitters comply with FCC 1.1307(b)(3)(i)(C) MPE-based exception at a minimum distance of 0.201 m.



2.4 Combined Antenna Port RF Exposure Results using “1.1307(b)(3)(i)(B) SAR / MPE Exemption”

2.4.1 Combination 1 - Bluetooth (2x2 MIMO on Core 0 & 1) + 6 GHz WLAN (2x2 MIMO on Core 0 & 1)

RAT Core	Frequency (MHz)	Conducted Power Output mW	Duty Cycle %	Time Average Conducted Power Output mW	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Test Separation Distance (mm)	ERPj / Max of time averaged conducted power or ERPth
Bluetooth (2x2 (MIMO) Core 0 and Core 1)	2402	112.202	100	112.202	1.820	204.174	124.496	201	0.0407
6 GHz WLAN (2x2 MIMO) Core 0 and Core 1	5955	281.838	100	281.838	3.090	870.964	531.075	201	0.6846
Calculated RF exposure level at minimum compliance boundary of 0.201 m as a fraction of the limit									0.7253

Table 6 – Transmitter Result

2.4.2 Combination 2 - 2.4 GHz WLAN (Core 0) + NB (Core 1)

RAT	Frequency (MHz)	Conducted Power Output mW	Duty Cycle %	Time Average Conducted Power Output mW	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Test Separation Distance (mm)	ERPj / Max of time averaged conducted power or ERPth
2.4 GHz WLAN (SISO) Core 0	2412	177.828	100	177.828	1.820	323.594	197.313	201	0.0645
NB Core 1	5733	25.119	100	25.119	2.570	64.565	39.369	201	0.0129
Calculated RF exposure level at minimum compliance boundary of 0.201 m as a fraction of the limit									0.0774

Table 7 – Transmitter Result