

APPENDIX G: 802.11AX RU SAR EXCLUSION

G.1 IEEE 802.11ax RU SAR Exclusion

To make the most efficient use of the additional available subcarriers (data tones), IEEE 802.11ax can utilize Orthogonal Frequency-Division Multiple Access (OFDMA) which divides the existing 802.11 channels into smaller subchannels called Resource Units (RUs). Possible RU sizes are: 26T, 52T, 106T, 242T, 484T and 996T.

Per FCC Guidance, 802.11ax was considered a higher order 802.11 mode when compared to a/b/g/n/ac to apply KDB Publication 248227 D01v02r02 for OFDM mode selection. Therefore, SAR tests were not required for 802.11ax based on the maximum allowed output powers of OFDM modes and the reported SAR values. Per FCC Guidance, maximum conducted powers were performed for each RU size to demonstrate that the output powers would not be higher than the other OFDM 802.11 modes.

G.2 IEEE 802.11ax RU Target Powers

G.2.1 Maximum 802.11ax RU WLAN Output Power

Index		GSI REG-21 (Reinforcement in Effect) - Positive WBS															
		Chaparral								Tropicana							
		SISO	SISO	SISO	SISO	SISO	SISO	SISO	SISO	MIMO	MIMO	MIMO	MIMO	MIMO	MIMO	MIMO	
24 Main Bus Assemblies		REF (Normal)	REF (Normal)	REF (Normal)	REF (Normal)	REF (Normal)	REF (Normal)	REF (Normal)	REF (Normal)	REF (Normal)	REF (Normal)	REF (Normal)	REF (Normal)	REF (Normal)	REF (Normal)	REF (Normal)	
	1	11:00	12:00	13:00	14:00	15:00	16:00	17:00	18:00	19:00	20:00	21:00	22:00	23:00	24:00	25:00	
	2	11:00	12:00	13:00	14:00	15:00	16:00	17:00	18:00	19:00	20:00	21:00	22:00	23:00	24:00	25:00	
	3	11:00	12:00	13:00	14:00	15:00	16:00	17:00	18:00	19:00	20:00	21:00	22:00	23:00	24:00	25:00	
	4	11:00	12:00	13:00	14:00	15:00	16:00	17:00	18:00	19:00	20:00	21:00	22:00	23:00	24:00	25:00	
	5	11:00	12:00	13:00	14:00	15:00	16:00	17:00	18:00	19:00	20:00	21:00	22:00	23:00	24:00	25:00	
	6	11:00	12:00	13:00	14:00	15:00	16:00	17:00	18:00	19:00	20:00	21:00	22:00	23:00	24:00	25:00	
24 Main Bus Assemblies	7	11:00	12:00	13:00	14:00	15:00	16:00	17:00	18:00	19:00	20:00	21:00	22:00	23:00	24:00	25:00	
	8	11:00	12:00	13:00	14:00	15:00	16:00	17:00	18:00	19:00	20:00	21:00	22:00	23:00	24:00	25:00	
	9	11:00	12:00	13:00	14:00	15:00	16:00	17:00	18:00	19:00	20:00	21:00	22:00	23:00	24:00	25:00	
	10	11:00	12:00	13:00	14:00	15:00	16:00	17:00	18:00	19:00	20:00	21:00	22:00	23:00	24:00	25:00	
	(1)	11:00	12:00	13:00	14:00	15:00	16:00	17:00	18:00	19:00	20:00	21:00	22:00	23:00	24:00	25:00	
	(2)	11:00	12:00	13:00	14:00	15:00	16:00	17:00	18:00	19:00	20:00	21:00	22:00	23:00	24:00	25:00	
	(3)	11:00	12:00	13:00	14:00	15:00	16:00	17:00	18:00	19:00	20:00	21:00	22:00	23:00	24:00	25:00	

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

[illegible]

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

Mode	Channel	101 MHz (3.0MHz) or above Antenna Wires																
		S10	S10	S10	S10	S10	S10	S10	S10	S10	S10	S10	S10	S10	S10	S10	S10	
5 GHz WiFi 20 MHz Bandwidth		267 (Maximum)	267 (Nominal)	267 (Nominal)	267 (Nominal)	2687 (Maximum)	2687 (Nominal)	2687 (Nominal)	2687 (Nominal)	Tones		2687 (Nominal)	4847 (Maximum)	4847 (Nominal)	2687 (Maximum)	2687 (Nominal)	2687*2 (Maximum)	2687*2 (Nominal)
	36				14.00		14.00		14.00			14.00						
	40	11.50	10.00	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	44	11.50	10.00	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	48	11.50	10.00	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	52	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	56	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	60	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	64	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	68	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	72	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	76	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	80	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	84	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	88	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	92	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
5 GHz WiFi 40 MHz Bandwidth	100	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	104	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	108	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	112	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	116	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	120	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	124	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	128	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	132	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	136	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	140	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	144	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	148	11.50	10.00	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	152	11.50	10.00	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	156	11.50	10.00	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	160	11.50	10.00	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
5 GHz WiFi 80 MHz Bandwidth	168	11.50	10.00	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	172	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	176	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	180	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	184	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	188	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	192	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	196	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	200	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	204	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	208	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	212	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	216	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	220	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	224	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	228	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
5GHz WiFi 160MHz Bandwidth	232	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	236	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	240	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					
	244	N/A	N/A	14.50	13.00	12.00	13.50	17.00	15.50			17.00	15.50					

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 1 of 41

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz.

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz.

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 2 of 41

Mode	Channel	IEEE 802.11 (Maximum in dBm) - Antenna Watts															
		SISO		MISO		SISO		SISO		SISO		SISO		SISO		SISO	
		2dBT (Maximum)	2dBT (Nominal)	3dBT (Maximum)	3dBT (Nominal)	5dBT (Maximum)	5dBT (Nominal)	2dBT (Maximum)	2dBT (Nominal)	4dBT (Maximum)	4dBT (Nominal)	9dBT (Maximum)	9dBT (Nominal)	9dBT*2 (Maximum)	9dBT*2 (Nominal)		
1 GHz WRT 20 MHz Bandwidth	36	11.50	10.00	14.50	13.00	15.75	14.25	15.75	14.25								
	40	11.50	10.00	14.50	13.00	15.75	14.25	15.75	14.25								
	44	11.50	10.00	14.50	13.00	15.75	14.25	15.75	14.25								
	48	11.50	10.00	14.50	13.00	15.75	14.25	15.75	14.25								
	52	N/A	N/A	N/A	N/A	14.50	13.75	14.25	13.75								
	56	N/A	N/A	N/A	N/A	14.50	13.75	14.25	13.75								
	60	N/A	N/A	N/A	N/A	14.50	13.75	14.25	13.75								
	64	N/A	N/A	N/A	N/A	14.50	13.75	14.25	13.75								
	68	N/A	N/A	N/A	N/A	14.50	13.75	14.25	13.75								
	72	N/A	N/A	N/A	N/A	14.50	13.75	14.25	13.75								
	76	N/A	N/A	N/A	N/A	14.50	13.75	14.25	13.75								
	80	N/A	N/A	N/A	N/A	14.50	13.75	14.25	13.75								
	84	N/A	N/A	N/A	N/A	14.50	13.75	14.25	13.75								
	88	N/A	N/A	N/A	N/A	14.50	13.75	14.25	13.75								
	92	N/A	N/A	N/A	N/A	14.50	13.75	14.25	13.75								
	96	N/A	N/A	N/A	N/A	14.50	13.75	14.25	13.75								
	100	N/A	N/A	N/A	N/A	14.50	13.75	14.25	13.75								
	1 GHz WRT 40 MHz Bandwidth	112	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00							
		116	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00							
120		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
124		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
128		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
132		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
136		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
140		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
144		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
148		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
152		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
156		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
160		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
164		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
168		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
172		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
176		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
180		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
1 GHz WRT 80 MHz Bandwidth		188	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00							
	192	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
	196	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
	200	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
	204	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
	208	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
	212	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
	216	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
	220	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
	224	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
	228	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
	232	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
	236	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
	240	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
	244	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
	248	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
	252	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
	1 GHz WRT 160 MHz Bandwidth	268	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00							
		272	N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00							
276		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
280		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
284		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
288		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
292		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
296		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
300		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
304		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
308		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
312		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
316		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
320		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
324		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
328		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
332		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								
336		N/A	N/A	N/A	N/A	14.50	13.00	13.00	13.00								

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz.

Mode	Channel	IEEE 802.11 (Maximum in dBm) - Antenna Watts															
		MIMO CSD	MIMO CSD	MIMO CSD	MIMO CSD	MIMO CSD	MIMO CSD	MIMO CSD	TxPower		MIMO CSD	MIMO CSD	MIMO CSD	MIMO CSD	MIMO CSD	MIMO CSD	
		2dBT (Maximum)	2dBT (Nominal)	3dBT (Maximum)	3dBT (Nominal)	5dBT (Maximum)	5dBT (Nominal)	2dBT (Maximum)	2dBT (Nominal)	4dBT (Maximum)	4dBT (Nominal)	9dBT (Maximum)	9dBT (Nominal)	9dBT*2 (Maximum)	9dBT*2 (Nominal)		
1 GHz WRT 20 MHz Bandwidth	36	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
	40	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
	44	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
	48	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
	52	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	56	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	60	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	64	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	68	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	72	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	76	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	80	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	84	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	88	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	92	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	96	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	100	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	1 GHz WRT 40 MHz Bandwidth	36	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50							
		40	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50							
44		9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
48		9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
52		N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
56		N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
60		N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
64		N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
68		N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
72		N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
76		N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
80		N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
84		N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
88		N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
92		N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
96		N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
100		N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
1 GHz WRT 80 MHz Bandwidth		36	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50							
		40	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50							
	44	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
	48	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
	52	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	56	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	60	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	64	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	68	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	72	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	76	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	80	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	84	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	88	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	92	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	96	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	100	N/A	N/A	12.00	10.50	13.00	11.50	13.00	11.50								
	5 GHz WRT 30 MHz Bandwidth	112	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50							
		116	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50							
120		9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
5 GHz WRT 60 MHz Bandwidth	112	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
	116	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
	120	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
5 GHz WRT 90 MHz Bandwidth	112	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
	116	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
	120	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
5 GHz WRT 120 MHz Bandwidth	112	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
	116	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								
	120	9.00	7.50	12.00	10.50	13.00	11.50	13.00	11.50								

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 4 of 41

Mode	Channel	IEEE 802.11 (Maximum in dBm) - Antenna WEP															
		MIMO CDD	MIMO CDD	MIMO CDD	MIMO CDD	MIMO CDD	MIMO CDD	MIMO CDD	MIMO CDD	MIMO CDD	MIMO CDD	MIMO CDD	MIMO CDD	MIMO CDD	MIMO CDD	MIMO CDD	MIMO CDD
		Transmit															
8 GHz WEP (20MHz WEP) LP	2	28T (Maximum)	28T (Nominal)	52T (Maximum)	52T (Nominal)	108T (Maximum)	108T (Nominal)	242T (Maximum)	242T (Nominal)	484T (Maximum)	484T (Nominal)	996T (Maximum)	996T (Nominal)	996T*2 (Maximum)	996T*2 (Nominal)		
	1	NS	NS	NS	NS	NS	NS	NS	NS								
	3	NS	NS	NS	NS	NS	NS	NS	NS								
	5	NS	NS	NS	NS	NS	NS	NS	NS								
	9.25	NS	NS	NS	NS	NS	NS	NS	NS								
	13.5	NS	NS	NS	NS	NS	NS	NS	NS								
	15.5	NS	NS	NS	NS	NS	NS	NS	NS								
	17	NS	NS	NS	NS	NS	NS	NS	NS								
	17.113	NS	NS	NS	NS	NS	NS	NS	NS								
	17.125	NS	NS	NS	NS	NS	NS	NS	NS								
8 GHz WEP (20MHz WEP) LP	21	NS	NS	NS	NS	NS	NS	NS	NS								
	23	NS	NS	NS	NS	NS	NS	NS	NS								
	25.5	NS	NS	NS	NS	NS	NS	NS	NS								
	27.5	NS	NS	NS	NS	NS	NS	NS	NS								
	28	NS	NS	NS	NS	NS	NS	NS	NS								
	28.125	NS	NS	NS	NS	NS	NS	NS	NS								
	28.137	NS	NS	NS	NS	NS	NS	NS	NS								
	28.15	NS	NS	NS	NS	NS	NS	NS	NS								
	28.167	NS	NS	NS	NS	NS	NS	NS	NS								
	28.175	NS	NS	NS	NS	NS	NS	NS	NS								
8 GHz WEP (20MHz WEP) LP	29	NS	NS	NS	NS	NS	NS	NS	NS								
	31	NS	NS	NS	NS	NS	NS	NS	NS								
	33	NS	NS	NS	NS	NS	NS	NS	NS								
	35.5	NS	NS	NS	NS	NS	NS	NS	NS								
	37	NS	NS	NS	NS	NS	NS	NS	NS								
	37.125	NS	NS	NS	NS	NS	NS	NS	NS								
	37.137	NS	NS	NS	NS	NS	NS	NS	NS								
	37.15	NS	NS	NS	NS	NS	NS	NS	NS								
	37.167	NS	NS	NS	NS	NS	NS	NS	NS								
	37.175	NS	NS	NS	NS	NS	NS	NS	NS								
8 GHz WEP (20MHz WEP) LP	39	NS	NS	NS	NS	NS	NS	NS	NS								
	41	NS	NS	NS	NS	NS	NS	NS	NS								
	43	NS	NS	NS	NS	NS	NS	NS	NS								
	45.5	NS	NS	NS	NS	NS	NS	NS	NS								
	47	NS	NS	NS	NS	NS	NS	NS	NS								
	47.125	NS	NS	NS	NS	NS	NS	NS	NS								
	47.137	NS	NS	NS	NS	NS	NS	NS	NS								
	47.15	NS	NS	NS	NS	NS	NS	NS	NS								
	47.167	NS	NS	NS	NS	NS	NS	NS	NS								
	47.175	NS	NS	NS	NS	NS	NS	NS	NS								
8 GHz WEP (20MHz WEP) LP	49	NS	NS	NS	NS	NS	NS	NS	NS								
	51	NS	NS	NS	NS	NS	NS	NS	NS								
	53	NS	NS	NS	NS	NS	NS	NS	NS								
	55.5	NS	NS	NS	NS	NS	NS	NS	NS								
	57	NS	NS	NS	NS	NS	NS	NS	NS								
	57.125	NS	NS	NS	NS	NS	NS	NS	NS								
	57.137	NS	NS	NS	NS	NS	NS	NS	NS								
	57.15	NS	NS	NS	NS	NS	NS	NS	NS								
	57.167	NS	NS	NS	NS	NS	NS	NS	NS								
	57.175	NS	NS	NS	NS	NS	NS	NS	NS								
8 GHz WEP (20MHz WEP) LP	59	NS	NS	NS	NS	NS	NS	NS	NS								
	61	NS	NS	NS	NS	NS	NS	NS	NS								
	63	NS	NS	NS	NS	NS	NS	NS	NS								
	65.5	NS	NS	NS	NS	NS	NS	NS	NS								
	67	NS	NS	NS	NS	NS	NS	NS	NS								
	67.125	NS	NS	NS	NS	NS	NS	NS	NS								
	67.137	NS	NS	NS	NS	NS	NS	NS	NS								
	67.15	NS	NS	NS	NS	NS	NS	NS	NS								
	67.167	NS	NS	NS	NS	NS	NS	NS	NS								
	67.175	NS	NS	NS	NS	NS	NS	NS	NS								

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz.

Mode	Channel	IEEE 802.11 (Maximum in dBm) - Antenna WEP															
		Transmit														Receive	
		MIMO SISO	MIMO SISO	MIMO SISO	MIMO SISO	MIMO SISO	MIMO SISO	MIMO SISO	MIMO SISO	MIMO SISO	MIMO SISO	MIMO SISO	MIMO SISO	MIMO SISO	MIMO SISO	MIMO SISO	MIMO SISO
8 GHz WEP (20MHz WEP) LP	2	28T (Maximum)	28T (Nominal)	52T (Maximum)	52T (Nominal)	108T (Maximum)	108T (Nominal)	242T (Maximum)	242T (Nominal)	484T (Maximum)	484T (Nominal)	996T (Maximum)	996T (Nominal)	996T*2 (Maximum)	996T*2 (Nominal)		
	1	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	3	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	5	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	9.25	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	13.5	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	15.5	-6.50	-10.50	-3.50	-3.50	-0.50	-0.50	-2.00	-2.00	1.50	1.50						
	17	-6.50	-10.50	-3.50	-3.50	-0.50	-0.50	-2.00	-2.00	1.50	1.50						
	17.113	-6.25	-10.25	-3.25	-3.25	-0.25	-0.25	-1.75	-1.75	1.25	1.25						
	17.125	-6.25	-10.25	-3.25	-3.25	-0.25	-0.25	-1.75	-1.75	1.25	1.25						
8 GHz WEP (20MHz WEP) LP	21	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	23	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	25.5	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	27.5	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	28	-6.50	-10.50	-3.50	-3.50	-0.50	-0.50	-2.00	-2.00	1.50	1.50						
	28.125	-6.25	-10.25	-3.25	-3.25	-0.25	-0.25	-1.75	-1.75	1.25	1.25						
	28.137	-6.25	-10.25	-3.25	-3.25	-0.25	-0.25	-1.75	-1.75	1.25	1.25						
	28.15	-6.50	-10.50	-3.50	-3.50	-0.50	-0.50	-2.00	-2.00	1.50	1.50						
	28.167	-6.25	-10.25	-3.25	-3.25	-0.25	-0.25	-1.75	-1.75	1.25	1.25						
	28.175	-6.25	-10.25	-3.25	-3.25	-0.25	-0.25	-1.75	-1.75	1.25	1.25						
8 GHz WEP (20MHz WEP) LP	29	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	31	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	33	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	35.5	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	37	-6.50	-10.50	-3.50	-3.50	-0.50	-0.50	-2.00	-2.00	1.50	1.50						
	37.125	-6.25	-10.25	-3.25	-3.25	-0.25	-0.25	-1.75	-1.75	1.25	1.25						
	37.137	-6.25	-10.25	-3.25	-3.25	-0.25	-0.25	-1.75	-1.75	1.25	1.25						
	37.15	-6.50	-10.50	-3.50	-3.50	-0.50	-0.50	-2.00	-2.00	1.50	1.50						
	37.167	-6.25	-10.25	-3.25	-3.25	-0.25	-0.25	-1.75	-1.75	1.25	1.25						
	37.175	-6.25	-10.25	-3.25	-3.25	-0.25	-0.25	-1.75	-1.75	1.25	1.25						
8 GHz WEP (20MHz WEP) LP	39	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	41	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	43	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	45.5	-7.75	-12.25	-4.75	-4.75	-1.75	-1.75	-3.25	-3.25	1.75	1.75						
	47	-6.50	-10.50	-3.50	-3.50	-0.50	-0.50	-2.00	-2.00	1.50	1.50						

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 6 of 41

Mode	Channel	IEEE 802.11 (Maximum in dBm) - Antenna WPA													
		MIMO C20	MIMO C20	MIMO C20	MIMO C20	MIMO C20	MIMO C20	MIMO C20	MIMO C20	MIMO C20	MIMO C20	MIMO C20	MIMO C20	MIMO C20	MIMO C20
		20T (Maximum)	20T (Nominal)	52T (Maximum)	52T (Nominal)	100T (Maximum)	100T (Nominal)	242T (Maximum)	242T (Nominal)	404T (Maximum)	404T (Nominal)	996T (Maximum)	996T (Nominal)	996T*2 (Maximum)	996T*2 (Nominal)
6 GHz WRT (20MHz WRT) SP	2	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
	3	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	4	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	5-20	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	21-22	6.25	4.75	9.25	7.75	12.25	10.75	14.25	13.00	18.00	16.50	22.00	20.50	26.00	24.50
	23-24	6.50	5.00	9.50	8.00	13.00	11.50	15.00	13.75	18.75	17.25	23.25	21.75	27.25	25.75
	25-30	6.50	5.00	9.50	8.00	13.00	11.50	15.00	13.75	18.75	17.25	23.25	21.75	27.25	25.75
	31	8.50	7.00	11.50	10.00	14.50	13.00	17.50	16.25	22.50	21.25	27.50	26.25	32.50	31.25
	32	8.50	7.00	11.50	10.00	14.50	13.00	17.50	16.25	22.50	21.25	27.50	26.25	32.50	31.25
	33-113	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
6 GHz WRT (20MHz WRT) SP	114-200	8.75	7.25	11.75	10.25	15.25	13.75	18.25	17.00	23.50	22.25	28.50	27.25	34.00	32.75
	201	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
	202-220	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
	221	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
	222	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
	223	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
	224	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	225	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	226-230	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
	231	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
6 GHz WRT (20MHz WRT) SP	232	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	233	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	234	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	235-240	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
	241	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	242	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	243	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	244	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	245	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	246	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
6 GHz WRT (100MHz WRT) SP	247	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	248	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	249	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	250	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	251	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	252	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	253	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	254	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	255	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00
	256	7.25	5.75	10.25	8.75	13.25	11.75	15.75	14.50	19.50	18.00	24.50	23.00	29.50	28.00

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

Mode	Channel	IEEE 802.11 (Maximum in dBm) - Antenna WPA															
		MIMO C20		MIMO C20		MIMO C20		MIMO C20		MIMO C20		MIMO C20		MIMO C20		MIMO C20	
		20T (Maximum)	20T (Nominal)	52T (Maximum)	52T (Nominal)	100T (Maximum)	100T (Nominal)	242T (Maximum)	242T (Nominal)	404T (Maximum)	404T (Nominal)	996T (Maximum)	996T (Nominal)	996T*2 (Maximum)	996T*2 (Nominal)		
6 GHz WRT (20MHz WRT) SP	2	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS		
	3	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	4	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	5-20	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	21-22	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	23-24	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	25-30	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	31	11.00	9.50	14.00	12.50	17.50	16.25	21.25	19.75	25.75	24.25	31.25	29.75	36.25	34.75		
	32	11.00	9.50	14.00	12.50	17.50	16.25	21.25	19.75	25.75	24.25	31.25	29.75	36.25	34.75		
	33-113	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS		
6 GHz WRT (20MHz WRT) SP	114-200	11.00	9.50	14.00	12.50	17.50	16.25	21.25	19.75	25.75	24.25	31.25	29.75	36.25	34.75		
	201	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS		
	202-220	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS		
	221	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS		
	222	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS		
	223	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS		
	224	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	225	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	226-230	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS		
	231	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
6 GHz WRT (20MHz WRT) SP	232	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	233	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	234	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	235-240	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS		
	241	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	242	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	243	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	244	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	245	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	246	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
6 GHz WRT (100MHz WRT) SP	247	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	248	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	249	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	250	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		
	251	10.25	8.75	13.25	11.75	16.25	14.75	19.25	18.00	24.50	23.25	30.00	28.75	35.00	33.75		

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 9 of 41

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.
Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 10 of 41

G.3 IEEE 802.11ax Measured Powers

Table G-1
Maximum 2.4 GHz 802.11ax RU Output Power – Ant WF8

Freq [MHz]	Channel	Tones	Avg Conducted Powers (dBm)		
			Ru Index		
			0	4	8
2412	1	26T	12.32	12.01	11.96
2437	6	26T	12.21	12.04	11.87
2462	11	26T	12.13	12.05	11.83
Freq [MHz]	Channel	Tones	Avg Conducted Powers (dBm)		
			Ru Index		
			37	38	40
2412	1	52T	13.92	13.86	13.58
2437	6	52T	15.31	15.05	15.04
2462	11	52T	13.59	13.73	13.52
Freq [MHz]	Channel	Tones	Avg Conducted Powers (dBm)		
			Ru Index		
			53	54	x
2412	1	106T	13.88	13.68	
2437	6	106T	16.96	16.85	
2462	11	106T	13.76	13.60	
Freq [MHz]	Channel	Tones	Avg Conducted Powers (dBm)		
			Ru Index		
			61	x	x
2412	1	242T	13.88		
2437	6	242T	16.91		
2462	11	242T	13.66		

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 11 of 41

Table G-2
Maximum 2.4 GHz 802.11ax RU Output Power – Ant WF7b

Freq [MHz]	Channel	Tones	Avg Conducted Powers (dBm)		
			Ru Index		
			0	4	8
2412	1	26T	12.05	12.11	11.88
2437	6	26T	11.99	11.79	11.80
2462	11	26T	11.63	11.92	11.68
Freq [MHz]	Channel	Tones	Avg Conducted Powers (dBm)		
			Ru Index		
			37	38	40
2412	1	52T	13.44	13.68	13.44
2437	6	52T	14.99	15.22	15.03
2462	11	52T	13.45	13.24	13.03
Freq [MHz]	Channel	Tones	Avg Conducted Powers (dBm)		
			Ru Index		
			53	54	x
2412	1	106T	13.73	13.59	
2437	6	106T	17.93	17.82	
2462	11	106T	13.22	13.10	
Freq [MHz]	Channel	Tones	Avg Conducted Powers (dBm)		
			Ru Index		
			61	x	x
2412	1	242T	13.50		
2437	6	242T	18.11		
2462	11	242T	13.15		

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 12 of 41

Table G-3
Maximum 5 GHz 802.11ax RU Output Power – Ant WF8

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	4	8
20MHz BW	1	5180	36	26T	10.31	10.25	10.45
		5200	40	26T	10.45	10.30	10.49
		5220	44	26T	10.52	10.39	10.60
		5240	48	26T	10.58	10.44	10.68
	3	5745	149	26T	10.32	10.44	10.45
		5785	157	26T	10.24	10.08	10.34
		5825	165	26T	10.42	10.29	10.53
20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	39	40
	1	5180	36	52T	13.25	13.32	13.30
		5200	40	52T	13.29	13.38	13.33
		5220	44	52T	13.36	13.47	13.44
		5240	48	52T	13.46	13.53	13.50
	2A	5260	52	52T	13.49	13.57	13.55
		5280	56	52T	13.49	13.70	13.58
		5300	60	52T	13.56	13.50	13.61
		5320	64	52T	13.44	13.50	13.47
	2C	5500	100	52T	13.44	13.36	13.51
		5600	120	52T	13.48	13.41	13.52
		5580	124	52T	13.42	13.54	13.52
		5720	144	52T	13.36	13.51	13.71
	3	5745	149	52T	13.40	13.49	13.48
		5785	157	52T	13.47	13.53	13.57
		5825	165	52T	13.19	13.35	13.24

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 13 of 41

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	54	N/A
	1	5180	36	106T	15.01	15.04	
		5200	40	106T	16.07	16.09	
		5220	44	106T	16.16	16.23	
		5240	48	106T	16.23	16.24	
	2A	5260	52	106T	16.25	16.26	
		5280	56	106T	16.34	16.39	
		5300	60	106T	16.43	16.43	
		5320	64	106T	15.17	15.19	
	2C	5500	100	106T	14.20	14.25	
		5600	120	106T	15.43	15.46	
		5620	124	106T	15.25	15.29	
		5720	144	106T	15.34	15.72	
	3	5745	149	106T	16.70	16.76	
		5785	157	106T	16.47	16.55	
		5825	165	106T	16.32	16.42	
20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	N/A	N/A
	1	5180	36	242T	15.08		
		5200	40	242T	15.81		
		5220	44	242T	15.74		
		5240	48	242T	15.77		
	2A	5260	52	242T	15.79		
		5280	56	242T	15.94		
		5300	60	242T	16.00		
		5320	64	242T	15.36		
	2C	5500	100	242T	14.27		
		5600	120	242T	14.99		
		5620	124	242T	14.9		
		5720	144	242T	15.15		
	3	5745	149	242T	16.3		
		5785	157	242T	16.27		
		5825	165	242T	15.96		

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 14 of 41

40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	8	17
	1	5190	38	26T	10.40	10.54	10.68
		5230	46	26T	10.57	10.71	10.72
	3	5755	151	26T	10.64	10.53	10.59
		5795	159	26T	10.44	10.40	10.52
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	40	44
	1	5190	38	52T	12.80	12.88	12.91
		5230	46	52T	13.60	13.27	13.74
	2A	5270	54	52T	13.56	13.57	13.64
		5310	62	52T	13.55	13.47	13.75
	2C	5550	110	52T	13.63	13.45	13.81
		5590	118	52T	13.51	13.32	13.66
		5630	126	52T	13.35	13.43	13.78
		5710	142	52T	13.41	13.45	13.64
	3	5755	151	52T	13.52	13.42	13.68
		5795	159	52T	13.57	13.49	13.53
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	54	56
	1	5190	38	106T	12.95	13.09	13.03
		5230	46	106T	16.37	16.19	16.08
	2A	5270	54	106T	16.58	16.42	16.16
		5310	62	106T	14.74	14.65	14.55
	2C	5550	110	106T	15.35	15.38	15.22
		5590	118	106T	15.49	15.47	15.36
		5670	126	106T	15.34	15.59	15.25
		5710	142	106T	15.50	15.43	15.30
	3	5755	151	106T	16.63	16.61	16.65
		5795	159	106T	16.33	16.45	16.46

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 15 of 41

40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	N/A
	1	5190	38	242T	13.04	12.97	
		5230	46	242T	15.99	16.27	
	2A	5270	54	242T	16.31	16.30	
		5310	62	242T	14.68	14.72	
	2C	5550	110	242T	15.30	15.37	
		5590	118	242T	15.42	15.50	
		5670	126	242T	15.30	15.38	
		5710	142	242T	13.59	13.58	
	3	5755	151	242T	16.51	16.61	
		5795	159	242T	16.53	16.47	
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	N/A	N/A
	1	5190	38	484T	12.63		
		5230	46	484T	15.57		
	2A	5270	54	484T	15.61		
		5310	62	484T	14.18		
	2C	5550	110	484T	14.94		
		5590	118	484T	14.85		
		5630	126	484T	14.94		
		5710	142	484T	14.89		
	3	5755	151	484T	15.87		
		5795	159	484T	15.99		
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	18	36
	1	5210	42	26T	10.40	10.17	10.79
	3	5775	155	26T	10.40	10.38	10.60

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 16 of 41

80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	44	52
	1	5210	42	52T	10.84	11.08	11.23
	2A	5290	58	52T	13.16	13.21	13.65
	2C	5530	106	52T	12.11	12.18	12.37
		5610	122	52T	13.30	13.26	13.68
		5690	138	52T	13.38	13.34	13.40
	3	5775	155	52T	13.19	13.31	13.48
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	56	60
	1	5210	42	106T	10.98	11.17	11.35
	2A	5290	58	106T	14.12	14.31	14.40
	2C	5530	106	106T	12.21	12.23	12.50
		5610	122	106T	15.19	15.27	15.35
		5690	138	106T	15.35	15.27	15.35
	3	5775	155	106T	15.23	15.24	15.70
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	64
	1	5210	42	242T	11.22	11.00	11.30
	2A	5290	58	242T	14.35	14.16	14.35
	2C	5530	106	242T	12.28	12.10	12.42
		5610	122	242T	15.36	15.12	15.27
		5690	138	242T	13.51	13.30	13.58
	3	5775	155	242T	15.41	15.46	15.32
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	66	N/A
	1	5210	42	484T	10.79	11.03	
	2A	5290	58	484T	13.83	14.27	
	2C	5530	106	484T	11.91	12.20	
		5610	122	484T	14.95	15.31	
		5690	138	484T	14.15	14.55	
	3	5775	155	484T	15.24	15.28	

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 17 of 41

80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67	N/A	N/A
	1	5210	42	996T	10.75		
	2A	5290	58	996T	13.81		
	2C	5530	106	996T	11.81		
		5610	122	996T	14.88		
		5690	138	996T	14.87		
	3	5775	155	996T	15.10		
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	44	52
	1	5250	50	52T	9.71	10.09	10.06
	2C	5570	114	52T	9.26	9.31	9.65
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	56	60
	1	5250	50	106T	9.84	9.90	10.35
	2C	5570	114	106T	9.36	9.28	9.68
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	64
	1	5250	50	242T	9.92	10.08	10.37
	2C	5570	114	242T	9.40	9.56	9.64
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	66	N/A
	1	5250	50	484T	9.85	10.31	
	2C	5570	114	484T	9.33	9.75	

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 18 of 41

160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67	N/A	N/A
	1	5250	50	996T	9.96		
160MHz BW	2C	5570	114	996T	9.38		
	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67	N/A	N/A
	1	5250	50	996Tx2	9.96		
160MHz BW	2C	5570	114	996Tx2	9.38		

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 19 of 41

Table G-4
Maximum 5 GHz 802.11ax RU Output Power – Ant WF7a

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	4	8
20MHz BW	1	5180	36	26T	10.43	10.25	10.01
		5200	40	26T	10.27	10.26	9.95
		5220	44	26T	10.43	10.39	9.90
		5240	48	26T	10.35	10.32	10.14
	3	5745	149	26T	10.49	10.60	10.39
		5785	157	26T	10.61	10.47	10.28
		5825	165	26T	10.46	10.58	10.37
	20MHz BW	1	36	52T	Avg Conducted Power (dBm)		
					RU Index		
					37	39	40
					13.36	12.97	12.91
		1	40	52T	13.31	13.16	12.91
					13.26	13.11	13.12
					13.18	13.07	13.17
					13.69	13.37	13.30
		2A	52	52T	13.70	13.39	13.23
					13.67	13.34	13.41
					13.63	13.26	13.35
					13.32	13.09	13.06
		2C	100	52T	13.60	13.19	13.36
					13.59	13.21	13.17
					13.41	13.23	13.20
					13.91	13.59	13.55
		3	149	52T	13.79	13.48	13.46
					13.67	13.58	13.51

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 20 of 41

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	54	N/A
20MHz BW	1	5180	36	106T	14.61	14.57	
		5200	40	106T	14.51	14.51	
		5220	44	106T	14.50	14.47	
		5240	48	106T	14.29	14.82	
	2A	5260	52	106T	14.82	14.78	
		5280	56	106T	14.78	14.78	
		5300	60	106T	14.74	14.75	
		5320	64	106T	14.69	14.67	
	2C	5500	100	106T	13.90	13.89	
		5600	120	106T	13.85	13.86	
		5620	124	106T	13.95	13.98	
		5720	144	106T	13.72	13.74	
	3	5745	149	106T	14.34	14.37	
		5785	157	106T	14.26	14.30	
		5825	165	106T	14.34	14.34	
20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	N/A	N/A
20MHz BW	1	5180	36	242T	15.21		
		5200	40	242T	15.06		
		5220	44	242T	14.97		
		5240	48	242T	14.99		
	2A	5260	52	242T	15.14		
		5280	56	242T	15.17		
		5300	60	242T	15.15		
		5320	64	242T	15.68		
	2C	5500	100	242T	14.71		
		5600	120	242T	14.43		
		5620	124	242T	14.3		
		5720	144	242T	14.31		
	3	5745	149	242T	14.33		
		5785	157	242T	14.18		
		5825	165	242T	14.58		

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 21 of 41

40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	8	17
	1	5190	38	26T	10.47	10.50	10.21
		5230	46	26T	10.59	10.38	10.14
	3	5755	151	26T	10.54	10.69	10.38
		5795	159	26T	10.81	10.59	10.40
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	40	44
	1	5190	38	52T	12.74	12.85	12.69
		5230	46	52T	13.09	13.29	13.08
	2A	5270	54	52T	13.42	13.36	13.55
		5310	62	52T	13.30	13.50	13.48
	2C	5550	110	52T	13.58	13.48	13.60
		5590	118	52T	13.51	13.43	13.51
		5630	126	52T	13.49	13.39	13.50
		5710	142	52T	13.48	13.43	13.56
	3	5755	151	52T	13.76	13.78	13.78
		5795	159	52T	13.46	13.71	13.59
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	54	56
	1	5190	38	106T	12.87	12.85	12.83
		5230	46	106T	14.68	14.59	14.98
	2A	5270	54	106T	14.86	14.65	14.76
		5310	62	106T	14.38	14.40	14.53
	2C	5550	110	106T	13.94	13.78	14.08
		5590	118	106T	14.03	14.09	14.01
		5670	126	106T	13.84	14.08	14.01
		5710	142	106T	13.84	13.73	13.91
	3	5755	151	106T	14.47	14.62	14.48
		5795	159	106T	14.38	14.34	14.47

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 22 of 41

40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	N/A
	1	5190	38	242T	12.83	12.77	
		5230	46	242T	14.50	14.49	
	2A	5270	54	242T	14.64	14.59	
		5310	62	242T	14.39	14.49	
	2C	5550	110	242T	13.86	13.93	
		5590	118	242T	13.94	13.92	
		5670	126	242T	13.78	14.02	
		5710	142	242T	13.32	13.37	
	3	5755	151	242T	14.39	14.40	
		5795	159	242T	14.31	14.36	
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	N/A	N/A
	1	5190	38	484T	12.85		
		5230	46	484T	15.03		
	2A	5270	54	484T	15.26		
		5310	62	484T	14.46		
	2C	5550	110	484T	14.41		
		5590	118	484T	14.42		
		5630	126	484T	14.39		
		5710	142	484T	14.33		
	3	5755	151	484T	14.37		
		5795	159	484T	14.55		
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	18	36
	1	5210	42	26T	10.27	10.22	10.64
	3	5775	155	26T	10.18	10.02	10.91

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 23 of 41

80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	44	52
	1	5210	42	52T	10.99	11.04	11.11
80MHz BW	2A	5290	58	52T	13.36	13.32	13.46
	2C	5530	106	52T	11.99	12.30	12.04
		5610	122	52T	13.40	13.48	13.54
		5690	138	52T	13.14	13.31	13.36
	3	5775	155	52T	13.60	13.55	13.69
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	56	60
	1	5210	42	106T	11.15	11.08	11.28
80MHz BW	2A	5290	58	106T	14.19	14.29	14.53
	2C	5530	106	106T	12.15	12.03	12.22
		5610	122	106T	14.01	13.96	14.07
		5690	138	106T	13.84	13.84	14.05
	3	5775	155	106T	14.46	14.36	14.47
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	64
	1	5210	42	242T	11.08	10.74	11.12
80MHz BW	2A	5290	58	242T	14.13	13.88	14.36
	2C	5530	106	242T	12.04	11.92	12.28
		5610	122	242T	14.00	13.86	14.08
		5690	138	242T	13.31	13.28	13.44
	3	5775	155	242T	14.38	13.91	14.36
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	66	N/A
	1	5210	42	484T	10.96	11.28	
80MHz BW	2A	5290	58	484T	13.96	14.39	
	2C	5530	106	484T	12.04	12.22	
		5610	122	484T	13.98	14.30	
		5690	138	484T	13.94	14.23	
	3	5775	155	484T	14.02	14.17	

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 24 of 41

80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67	N/A	N/A
	1	5210	42	996T	11.58		
160MHz BW	2A	5290	58	996T	14.72		
	2C	5530	106	996T	12.64		
		5610	122	996T	14.48		
		5690	138	996T	14.05		
160MHz BW	3	5775	155	996T	14.14		
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	44	52
	1	5250	50	52T	10.23	10.07	10.35
160MHz BW	2C	5570	114	52T	9.33	9.18	9.40
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	56	60
	1	5250	50	106T	10.33	10.29	10.13
160MHz BW	2C	5570	114	106T	9.55	9.41	9.41
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	64
	1	5250	50	242T	10.34	9.97	10.36
160MHz BW	2C	5570	114	242T	9.44	9.22	9.62
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	66	N/A
	1	5250	50	484T	9.93	10.02	
160MHz BW	2C	5570	114	484T	9.13	9.53	
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67	N/A	N/A
	1	5250	50	996T	9.54		
160MHz BW	2C	5570	114	996T	9.01		

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 25 of 41

160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67	N/A	N/A
	1	5250	50	996Tx2	9.54		
	2C	5570	114	996Tx2	9.01		

Table G-5
Maximum 6 GHz 802.11ax RU Output Power – Ant WF8

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	4	8
	5	5955	1	26T	10.57	10.60	10.19
		6175	45	26T	10.52	10.57	10.20
		6195	49	26T	10.57	10.59	10.20
		6415	93	26T	10.56	10.53	10.21
	6	6435	97	26T	-5.47	-5.51	-5.49
		6475	105	26T	-5.17	-5.15	-5.18
		6515	113	26T	-5.15	-5.17	-5.19
	7	6535	117	26T	9.95	9.92	9.96
		6695	149	26T	10.30	10.35	10.34
		6875	185	26T	-4.68	-4.70	-4.66
	8	6895	189	26T	-3.17	-3.20	-3.23
		6995	209	26T	-3.36	-3.28	-3.33
		7015	213	26T	-3.61	-3.63	-3.59
		7115	233	26T	NS	NS	NS

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	39	40
	5	5955	1	52T	12.44	12.39	12.40
		6195	49	52T	12.52	12.66	12.65
		6415	93	52T	12.27	12.51	12.50
	6	6435	97	52T	-3.09	-3.11	-3.05
		6475	105	52T	-2.31	-2.29	-2.28
		6515	113	52T	-2.33	-2.27	-2.25
	7	6535	117	52T	10.33	10.32	10.31
		6695	149	52T	10.45	10.43	10.44
		6875	185	52T	-2.01	-2.02	-2.00
	8	6895	189	52T	-1.09	-0.53	-1.10
		6995	209	52T	-1.11	-1.15	-1.21
		7015	213	52T	-0.90	-0.92	-0.93
		7115	233	52T	NS	NS	NS

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 26 of 41

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	54	N/A
	5	5955	1	106T	13.07	13.04	
		6175	45	106T	13.05	13.04	
		6195	49	106T	13.09	13.07	
		6415	93	106T	13.61	13.60	
	6	6435	97	106T	1.25	1.22	
		6475	105	106T	1.19	1.15	
		6515	113	106T	1.12	1.12	
	7	6535	117	106T	10.34	10.31	
		6695	149	106T	10.44	10.45	
		6875	185	106T	1.78	1.70	
	8	6895	189	106T	1.96	2.14	
		6995	209	106T	2.37	2.38	
		7015	213	106T	2.31	2.32	
		7115	233	106T	NS	NS	
20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	N/A	N/A
	5	5955	1	242T	13.35		
		6175	45	242T	13.32		
		6195	49	242T	13.37		
		6415	93	242T	13.78		
	6	6435	97	242T	3.55		
		6475	105	242T	3.59		
		6515	113	242T	3.50		
	7	6535	117	242T	10.98		
		6695	149	242T	11.28		
		6875	185	242T	4.27		
	8	6895	189	242T	6.06		
		6995	209	242T	6.18		
		7015	213	242T	6.17		
		7115	233	242T	NS		

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 27 of 41

40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	8	17
	5	5965	3	26T	10.37	10.07	10.05
		6165	43	26T	10.07	10.07	10.08
		6205	51	26T	10.07	10.33	10.12
		6405	91	26T	10.03	10.10	10.09
	6	6445	99	26T	-4.85	-4.84	-4.87
		6485	107	26T	-4.54	-4.53	-4.50
		6525	115	26T	-4.89	-4.92	-4.55
	7	6565	123	26T	10.15	10.10	10.16
		6685	147	26T	10.09	10.10	10.08
		6845	179	26T	10.16	10.34	10.11
	8	6885	187	26T	-4.57	-4.56	-4.83
		6965	203	26T	-3.08	-3.03	-3.05
		7005	211	26T	-3.03	-3.06	-3.01
		7085	227	26T	-3.04	-3.07	-3.01
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	40	44
	5	5965	3	52T	13.17	13.14	13.20
		6165	43	52T	13.11	13.13	13.14
		6205	51	52T	13.19	13.20	13.21
		6405	91	52T	13.22	13.24	13.26
	6	6445	99	52T	-2.01	-1.97	-2.03
		6485	107	52T	-2.07	-2.06	-2.04
		6525	115	52T	-2.03	-2.13	-2.07
	7	6565	123	52T	11.32	11.20	11.30
		6685	147	52T	11.23	11.29	11.19
		6725	155	52T	11.22	11.22	11.19
		6845	179	52T	11.23	11.22	11.29
	8	6885	187	52T	-2.09	-2.03	-2.06
		6965	203	52T	-0.94	-0.97	-0.98
		7005	211	52T	-0.92	-0.95	-0.93
		7085	227	52T	-0.95	-0.93	-1.02

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 28 of 41

40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	54	56
	5	5965	3	106T	13.81	13.73	13.71
		6165	43	106T	13.71	13.74	13.77
		6205	51	106T	13.70	13.72	13.72
		6405	91	106T	14.33	14.31	14.38
	6	6445	99	106T	0.13	0.08	0.11
		6485	107	106T	-0.38	-0.37	0.10
		6525	115	106T	-0.33	-0.35	-0.37
	7	6565	123	106T	11.28	11.18	11.29
		6685	147	106T	11.24	11.23	11.27
		6725	155	106T	11.23	11.22	11.20
		6845	179	106T	11.23	11.23	11.23
	8	6885	187	106T	1.86	1.97	1.85
		6965	203	106T	3.03	3.02	3.02
		7005	211	106T	3.03	3.03	3.04
		7085	227	106T	3.01	2.99	3.01
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	N/A
	5	5965	3	242T	13.77	13.72	
		6165	43	242T	13.71	13.73	
		6205	51	242T	13.73	13.73	
		6405	91	242T	14.39	14.42	
	6	6445	99	242T	4.28	4.26	
		6485	107	242T	4.31	4.25	
		6525	115	242T	4.27	4.32	
	7	6565	123	242T	11.26	11.24	
		6685	147	242T	11.28	11.24	
		6725	155	242T	11.23	11.24	
		6845	179	242T	11.25	11.27	
	8	6885	187	242T	4.66	4.67	
		6965	203	242T	6.56	6.53	
		7005	211	242T	6.56	6.58	
		7085	227	242T	6.58	6.60	

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 29 of 41

40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	N/A	N/A
	5	5965	3	484T	13.45		
		6165	43	484T	13.41		
		6205	51	484T	13.39		
		6405	91	484T	14.22		
	6	6445	99	484T	6.71		
		6485	107	484T	6.69		
		6525	115	484T	6.65		
	7	6565	123	484T	11.03		
		6685	147	484T	11.00		
		6725	155	484T	10.97		
		6845	179	484T	10.95		
	8	6885	187	484T	7.33		
		6965	203	484T	9.27		
		7005	211	484T	9.20		
		7085	227	484T	9.28		
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	18	36
	5	5985	7	26T	9.77	9.69	9.74
		6145	39	26T	9.72	9.73	9.72
		6225	55	26T	9.72	9.72	9.76
		6385	87	26T	9.54	9.54	9.55
	6	6465	103	26T	-5.25	-5.29	-5.33
	7	6545	119	26T	-4.97	-4.95	-4.93
		6705	151	26T	9.95	9.96	9.94
		6865	183	26T	-4.36	-4.33	-4.38
	8	6945	199	26T	-2.84	-2.80	-2.77
		7025	215	26T	-3.23	-3.17	-3.12
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	44	52
	5	5985	7	52T	12.65	12.62	12.63
		6145	39	52T	12.70	12.70	12.69
		6225	55	52T	12.72	12.70	12.71
		6385	87	52T	12.70	12.69	12.70
	6	6465	103	52T	-1.79	-1.77	-1.73
	7	6545	119	52T	-1.98	-1.97	-1.93
		6705	151	52T	10.78	10.75	10.76
		6865	183	52T	-1.20	-1.23	-1.25
	8	6945	199	52T	0.71	0.69	0.67
		7025	215	52T	0.27	0.32	0.30

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 30 of 41

80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	56	60
	5	5985	7	106T	13.12	13.23	13.27
		6145	39	106T	13.26	13.26	13.24
		6225	55	106T	13.34	13.36	13.35
		6385	87	106T	13.86	13.84	13.85
	6	6465	103	106T	0.06	0.07	0.05
	7	6545	119	106T	0.54	0.50	0.57
		6705	151	106T	10.75	10.76	10.77
		6865	183	106T	1.01	1.14	1.00
	8	6945	199	106T	2.79	2.79	2.78
		7025	215	106T	2.50	2.51	2.50
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	64
	5	5985	7	242T	13.30	13.25	13.25
		6145	39	242T	13.26	13.25	13.24
		6225	55	242T	13.34	13.33	13.35
		6385	87	242T	13.83	13.84	13.82
	6	6465	103	242T	3.81	3.88	3.80
	7	6545	119	242T	3.97	3.99	3.97
		6705	151	242T	10.75	10.73	10.73
		6865	183	242T	4.75	4.78	4.76
	8	6945	199	242T	6.36	6.38	6.37
		7025	215	242T	6.08	6.08	6.10
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	66	N/A
	5	5985	7	484T	13.04	13.03	
		6145	39	484T	13.25	13.24	
		6225	55	484T	13.34	13.25	
		6385	87	484T	13.85	13.85	
	6	6465	103	484T	6.54	6.54	
	7	6545	119	484T	6.85	6.86	
		6705	151	484T	10.74	10.74	
		6865	183	484T	7.50	7.50	
	8	6945	199	484T	9.30	9.31	
		7025	215	484T	8.90	8.90	

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 31 of 41

80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67	N/A	N/A
	5	5985	7	996T	14.01		
		6145	39	996T	13.96		
		6225	55	996T	13.94		
		6385	87	996T	13.79		
	6	6465	103	996T	9.84		
	7	6545	119	996T	9.72		
		6705	151	996T	11.32		
		6865	183	996T	10.40		
	8	6945	199	996T	11.46		
		7025	215	996T	11.21		
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	18	36
	5	6025	15	26T	9.43	9.46	9.44
		6185	47	26T	9.63	9.61	9.62
		6345	79	26T	9.39	9.31	9.35
	6	6505	111	26T	-6.09	-6.11	-6.01
	7	6665	143	26T	9.55	9.55	9.57
		6825	175	26T	-5.71	-5.82	-5.03
	8	6985	207	26T	-3.25	-3.24	-3.15
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	44	52
	5	6025	15	52T	12.41	12.34	12.35
		6185	47	52T	12.36	12.37	12.34
		6345	79	52T	12.19	12.18	12.15
	6	6505	111	52T	-2.64	-2.52	-2.51
	7	6665	143	52T	12.48	12.44	12.46
		6825	175	52T	-2.24	-2.19	-2.23
	8	6985	207	52T	-1.20	-1.19	-1.10
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	56	60
	5	6025	15	106T	12.79	12.76	12.76
		6185	47	106T	12.93	12.90	12.90
		6345	79	106T	13.41	13.39	13.41
	6	6505	111	106T	0.31	0.30	0.41
	7	6665	143	106T	12.84	12.83	12.86
		6825	175	106T	0.63	0.51	0.64
	8	6985	207	106T	2.62	2.62	2.61

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 32 of 41

160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	64
	5	6025	15	242T	12.74	12.71	12.70
		6185	47	242T	12.91	12.92	12.89
		6345	79	242T	13.45	13.41	13.38
	6	6505	111	242T	3.58	3.61	3.58
	7	6665	143	242T	12.83	12.85	12.84
		6825	175	242T	4.47	4.48	4.45
	8	6985	207	242T	5.91	5.91	5.91
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	66	N/A
	5	6025	15	484T	12.77	12.73	
		6185	47	484T	12.90	12.90	
		6345	79	484T	13.37	13.45	
	6	6505	111	484T	6.35	6.37	
	7	6665	143	484T	12.85	12.89	
		6825	175	484T	7.12	7.16	
	8	6985	207	484T	8.72	8.69	
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67(L)	N/A	N/A
	5	6025	15	996T	14.15		
		6185	47	996T	14.09		
		6345	79	996T	14.21		
	6	6505	111	996T	10.00		
	7	6665	143	996T	13.96		
		6825	175	996T	10.27		
	8	6985	207	996T	10.25		
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67(L)	N/A	N/A
	5	6025	15	996Tx2	14.15		
		6185	47	996Tx2	14.25		
		6345	79	996Tx2	14.12		
	6	6505	111	996Tx2	9.99		
	7	6665	143	996Tx2	13.96		
		6825	175	996Tx2	10.24		
	8	6985	207	996Tx2	10.19		

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 33 of 41

Table G-6
Maximum 6 GHz 802.11ax RU Output Power – Ant WF7a

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	4	8
20MHz BW	5	5955	1	26T	10.43	10.44	10.41
		6175	45	26T	10.26	10.23	10.30
		6195	49	26T	10.23	10.11	10.17
		6415	93	26T	9.90	9.99	9.97
	6	6435	97	26T	-5.64	-5.63	-5.57
		6475	105	26T	-5.20	-5.25	-5.24
		6515	113	26T	-5.20	-5.25	-5.19
	7	6535	117	26T	10.35	10.39	10.36
		6695	149	26T	10.26	10.23	10.28
		6875	185	26T	-4.37	-4.73	-4.36
	8	6895	189	26T	-4.01	-3.97	-4.03
		6995	209	26T	-4.16	-4.13	-4.17
		7015	213	26T	-4.10	-4.11	-3.43
		7115	233	26T	NS	NS	NS
20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	39	40
20MHz BW	5	5955	1	52T	11.71	11.67	11.81
		6195	49	52T	11.62	11.61	11.62
		6415	93	52T	10.77	10.78	10.77
	6	6435	97	52T	-2.62	-2.64	-2.65
		6475	105	52T	-2.52	-2.48	-2.50
		6515	113	52T	-2.36	-2.33	-2.41
	7	6535	117	52T	10.05	10.02	10.03
		6695	149	52T	10.25	10.30	10.27
		6875	185	52T	-2.26	-2.24	-2.21
	8	6895	189	52T	-1.06	-0.99	-1.00
		6995	209	52T	-1.21	-1.25	-1.22
		7015	213	52T	-0.95	-0.51	-0.96
		7115	233	52T	NS	NS	NS

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 34 of 41

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	54	N/A
	5	5955	1	106T	11.71	11.68	
		6175	45	106T	11.79	11.81	
		6195	49	106T	11.62	11.63	
		6415	93	106T	10.76	10.88	
	6	6435	97	106T	0.39	-0.20	
		6475	105	106T	0.01	0.47	
		6515	113	106T	0.23	0.69	
	7	6535	117	106T	10.02	10.02	
		6695	149	106T	10.27	10.27	
		6875	185	106T	0.64	0.71	
	8	6895	189	106T	2.03	2.03	
		6995	209	106T	2.41	2.37	
		7015	213	106T	2.27	2.27	
		7115	233	106T	NS	NS	
20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	N/A	N/A
	5	5955	1	242T	12.82		
		6175	45	242T	12.69		
		6195	49	242T	12.65		
		6415	93	242T	11.93		
	6	6435	97	242T	4.34		
		6475	105	242T	4.22		
		6515	113	242T	4.37		
	7	6535	117	242T	11.27		
		6695	149	242T	11.30		
		6875	185	242T	4.87		
	8	6895	189	242T	6.59		
		6995	209	242T	6.80		
		7015	213	242T	6.83		
		7115	233	242T	NS		

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 35 of 41

40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	8	17
	5	5965	3	26T	10.22	10.19	10.18
		6165	43	26T	10.29	10.21	10.21
		6205	51	26T	10.20	10.20	10.19
		6405	91	26T	10.21	10.16	10.19
	6	6445	99	26T	-4.92	-5.40	-5.48
		6485	107	26T	-4.78	-4.82	-5.30
		6525	115	26T	-4.53	-5.21	-4.67
	7	6565	123	26T	10.24	10.20	10.25
		6685	147	26T	10.22	10.22	10.22
		6845	179	26T	10.23	10.20	10.24
	8	6885	187	26T	-4.62	-4.65	-4.60
		6965	203	26T	-4.06	-4.07	-4.02
		7005	211	26T	-3.65	-3.75	-3.77
		7085	227	26T	-4.19	-3.58	-4.23
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	40	44
	5	5965	3	52T	12.74	12.68	12.69
		6165	43	52T	12.66	12.68	12.70
		6205	51	52T	12.69	12.70	12.71
		6405	91	52T	11.95	11.96	11.98
	6	6445	99	52T	-2.87	-2.96	-2.87
		6485	107	52T	-2.89	-2.90	-2.95
		6525	115	52T	-2.18	-2.21	-2.16
	7	6565	123	52T	11.10	11.09	11.10
		6685	147	52T	11.06	11.10	11.09
		6725	155	52T	11.09	11.09	11.09
	8	6845	179	52T	11.08	11.07	11.06
		6885	187	52T	-2.07	-2.05	-2.21
		6965	203	52T	-0.86	-0.81	-0.88
		7005	211	52T	-0.49	-0.53	-0.50
	8	7085	227	52T	-0.95	-0.97	-0.99

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 36 of 41

40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	54	56
	5	5965	3	106T	12.77	12.68	12.66
		6165	43	106T	12.68	12.64	12.70
		6205	51	106T	12.66	12.68	12.69
		6405	91	106T	11.93	11.95	11.94
	6	6445	99	106T	-0.37	-0.34	-0.36
		6485	107	106T	-0.43	-0.39	-0.45
		6525	115	106T	0.31	0.35	0.45
	7	6565	123	106T	11.12	11.08	11.11
		6685	147	106T	11.05	11.08	11.10
		6725	155	106T	11.10	11.09	11.06
		6845	179	106T	11.10	11.07	11.07
	8	6885	187	106T	0.78	0.83	0.79
		6965	203	106T	3.00	2.97	2.96
		7005	211	106T	2.98	2.95	2.98
		7085	227	106T	2.98	2.99	2.98
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	N/A
	5	5965	3	242T	12.73	12.69	
		6165	43	242T	12.70	12.72	
		6205	51	242T	12.65	12.68	
		6405	91	242T	11.96	11.95	
	6	6445	99	242T	4.32	4.32	
		6485	107	242T	4.34	4.28	
		6525	115	242T	4.32	4.34	
	7	6565	123	242T	11.08	11.05	
		6685	147	242T	11.07	11.06	
		6725	155	242T	11.04	11.07	
		6845	179	242T	11.10	11.07	
	8	6885	187	242T	4.78	4.78	
		6965	203	242T	6.63	6.62	
		7005	211	242T	6.57	6.59	
		7085	227	242T	6.61	6.61	

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 37 of 41

40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	N/A	N/A
	5	5965	3	484T	13.05		
		6165	43	484T	13.09		
		6205	51	484T	13.06		
		6405	91	484T	12.10		
	6	6445	99	484T	7.32		
		6485	107	484T	7.36		
		6525	115	484T	7.51		
	7	6565	123	484T	11.55		
		6685	147	484T	11.63		
		6725	155	484T	11.49		
		6845	179	484T	11.78		
	8	6885	187	484T	8.31		
		6965	203	484T	9.95		
		7005	211	484T	10.06		
		7085	227	484T	9.95		
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	18	36
	5	5985	7	26T	9.79	9.76	9.78
		6145	39	26T	9.66	9.67	9.66
		6225	55	26T	9.67	9.67	9.87
		6385	87	26T	9.16	9.15	9.15
	6	6465	103	26T	-5.81	-5.83	-5.76
	7	6545	119	26T	-6.01	-5.98	-5.96
		6705	151	26T	9.68	9.65	9.66
		6865	183	26T	-4.55	-5.15	-5.18
	8	6945	199	26T	-4.20	-4.17	-4.18
		7025	215	26T	-3.49	-3.53	-3.52
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	44	52
	5	5985	7	52T	12.14	12.11	12.10
		6145	39	52T	11.98	11.99	11.98
		6225	55	52T	12.19	12.20	12.16
		6385	87	52T	11.12	11.12	11.12
	6	6465	103	52T	-3.23	-3.21	-3.26
	7	6545	119	52T	-3.05	-3.08	-3.05
		6705	151	52T	11.43	11.54	11.66
		6865	183	52T	-1.99	-2.01	-1.92
	8	6945	199	52T	-1.13	-1.11	-1.06
		7025	215	52T	-0.80	-0.88	-0.86

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 38 of 41

80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	56	60
	5	5985	7	106T	12.17	12.12	12.11
		6145	39	106T	11.99	12.00	11.99
		6225	55	106T	12.20	12.20	12.19
		6385	87	106T	11.11	11.11	11.11
	6	6465	103	106T	-0.23	-0.22	-0.25
	7	6545	119	106T	0.14	0.27	0.19
		6705	151	106T	11.43	11.64	11.64
		6865	183	106T	1.05	0.99	1.08
	8	6945	199	106T	3.04	3.04	3.04
		7025	215	106T	2.83	2.80	2.83
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	64
	5	5985	7	242T	12.15	12.11	12.09
		6145	39	242T	11.98	11.99	11.98
		6225	55	242T	12.20	12.20	12.20
		6385	87	242T	11.12	11.12	11.13
	6	6465	103	242T	3.15	3.16	3.16
	7	6545	119	242T	3.35	3.49	3.41
		6705	151	242T	11.63	11.64	11.64
		6865	183	242T	4.53	4.52	4.51
	8	6945	199	242T	6.48	6.46	6.49
		7025	215	242T	6.24	6.22	6.21
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	66	N/A
	5	5985	7	484T	12.13	12.12	
		6145	39	484T	11.99	11.98	
		6225	55	484T	12.19	12.19	
		6385	87	484T	11.12	11.11	
	6	6465	103	484T	6.15	6.15	
	7	6545	119	484T	6.31	6.32	
		6705	151	484T	11.63	11.63	
		6865	183	484T	7.48	7.50	
	8	6945	199	484T	9.39	9.40	
		7025	215	484T	9.07	9.07	

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 39 of 41

80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67	N/A	N/A
	5	5985	7	996T	13.19		
		6145	39	996T	12.97		
		6225	55	996T	12.92		
		6385	87	996T	12.06		
	6	6465	103	996T	9.98		
	7	6545	119	996T	9.93		
		6705	151	996T	12.50		
		6865	183	996T	10.47		
	8	6945	199	996T	12.36		
		7025	215	996T	12.07		
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	18	36
	5	6025	15	26T	10.68	10.60	10.59
		6185	47	26T	10.65	10.67	10.68
		6345	79	26T	10.75	10.72	10.75
	6	6505	111	26T	-6.15	-6.22	-5.87
	7	6665	143	26T	9.28	9.25	9.30
		6825	175	26T	-5.51	-5.48	-5.49
	8	6985	207	26T	-4.02	-3.92	-3.90
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	44	52
	5	6025	15	52T	11.52	11.68	11.70
		6185	47	52T	11.59	11.76	11.62
		6345	79	52T	10.75	10.77	10.76
	6	6505	111	52T	-3.28	-3.29	-3.26
	7	6665	143	52T	11.21	11.20	11.20
		6825	175	52T	-2.59	-2.53	-2.62
	8	6985	207	52T	-0.77	-0.93	-0.91
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	56	60
	5	6025	15	106T	11.52	11.71	11.68
		6185	47	106T	11.60	11.71	11.70
		6345	79	106T	10.76	10.77	10.79
	6	6505	111	106T	-0.15	-0.20	-0.23
	7	6665	143	106T	11.21	11.19	11.20
		6825	175	106T	0.29	0.98	0.31
	8	6985	207	106T	2.49	2.47	2.48

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 40 of 41

160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	64
	5	6025	15	242T	11.52	11.68	11.71
		6185	47	242T	11.62	11.67	11.77
		6345	79	242T	10.77	10.76	10.78
	6	6505	111	242T	4.76	4.82	4.69
	7	6665	143	242T	11.19	11.33	11.19
		6825	175	242T	4.18	4.18	4.19
	8	6985	207	242T	5.97	5.95	5.95
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	66	N/A
	5	6025	15	484T	11.76	11.72	
		6185	47	484T	11.72	11.65	
		6345	79	484T	10.76	10.78	
	6	6505	111	484T	7.63	7.66	
	7	6665	143	484T	11.16	11.19	
		6825	175	484T	7.03	7.07	
	8	6985	207	484T	8.67	8.68	
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67(L)	N/A	N/A
	5	6025	15	996T	13.06		
		6185	47	996T	13.27		
		6345	79	996T	12.32		
	6	6505	111	996T	10.03		
	7	6665	143	996T	12.83		
		6825	175	996T	10.93		
	8	6985	207	996T	12.47		
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67(L)	N/A	N/A
	5	6025	15	996Tx2	13.03		
		6185	47	996Tx2	13.24		
		6345	79	996Tx2	12.37		
	6	6505	111	996Tx2	10.02		
	7	6665	143	996Tx2	12.80		
		6825	175	996Tx2	10.92		
	8	6985	207	996Tx2	12.43		

FCC ID: BCGA3266	RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX G: Page 41 of 41