



### 8.3.9. LTE BAND 26 (PART 90S)




LTE B26 1.4MHz QPSK Low Channel RB1-0




LTE B26 1.4MHz 16QAM Low Channel RB1-0




LTE B26 1.4MHz QPSK Middle Channel RB1-0




LTE B26 1.4MHz 16QAM Middle Channel RB1-0




LTE B26 1.4MHz QPSK High Channel RB1-0




LTE B26 1.4MHz 16QAM High Channel RB1-0










### 8.3.10. LTE BAND 30










### 8.3.11. LTE BAND 41














### 8.3.12. LTE BAND 66







LTE B66 3MHz QPSK Low Channel RB1-0




LTE B66 3MHz 16QAM Low Channel RB1-0




LTE B66 3MHz QPSK Middle Channel RB1-0




LTE B66 3MHz 16QAM Middle Channel RB1-0





LTE B66 3MHz QPSK High Channel RB1-0




LTE B66 3MHz 16QAM High Channel RB1-0















### 8.3.13. LTE BAND 71









## 8.4. FREQUENCY STABILITY

### RULE PART(S)

§2.1055, §22.355, §24.235, §27.54, §90.213 and §90.539

### LIMITS

§22.355, §90.213

The carrier frequency shall not depart from the reference frequency in excess of  $\pm 2.5$  ppm for mobile stations.

§90.539

(e) The frequency stability of mobile, portable and control transmitters operating in the wideband segment must be 1.25 ppm or better when AFC is locked to a base station, and 5 ppm or better when AFC is not locked.

§24.235 & §27.54

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

### TEST PROCEDURE

Use CMW 500 with Frequency Error measurement capability.

- Temp. =  $-30^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$
- Voltage = (85% - 115%)

Low voltage, 3.23VDC, Normal, 3.8VDC and High voltage, 4.37VDC.

End Voltage, 3.2VDC.

### **Frequency Stability vs Temperature:**

The EUT is placed inside a temperature chamber. The temperature is set to  $20^{\circ}\text{C}$  and allowed to stabilize. After sufficient soak time, the transmitting frequency error is measured. The temperature is increased by 10 degrees, allowed to stabilize and soak, and then the measurement is repeated. This is repeated until  $+50^{\circ}\text{C}$  is reached.

### **Frequency Stability vs Voltage:**

The peak frequency error is recorded (worst-case).

### MODES TESTED

- LTE Band 2
- LTE Band 5
- LTE Band 7
- LTE Band 12
- LTE Band 13
- LTE Band 14
- LTE Band 17
- LTE Band 25
- LTE Band 26
- LTE Band 30
- LTE Band 41
- LTE Band 66
- LTE Band 71

### RESULTS

See the following pages.

### 8.4.1. LTE BAND 2

|            |               |              |        |
|------------|---------------|--------------|--------|
| <b>ID:</b> | 44410 / 50893 | <b>Date:</b> | 3/8/18 |
|------------|---------------|--------------|--------|

#### QPSK, (20MHz BANDWIDTH)

| Limit          |           | 1850              | 1910               | Delta<br>(Hz) | Frequency<br>Stability<br>(ppm) |
|----------------|-----------|-------------------|--------------------|---------------|---------------------------------|
| Condition      |           | F low @<br>-13dBm | F high @<br>-13dBm |               |                                 |
| Temperature    | Voltage   | (MHz)             | (MHz)              |               |                                 |
| Normal (20C)   | Normal    | 1850.8090         | 1909.1940          |               |                                 |
| Extreme (50C)  |           | 1850.8090         | 1909.1940          | 37.5          | 0.020                           |
| Extreme (40C)  |           | 1850.8090         | 1909.1940          | 33.3          | 0.018                           |
| Extreme (30C)  |           | 1850.8090         | 1909.1940          | 11.0          | 0.006                           |
| Extreme (10C)  |           | 1850.8090         | 1909.1940          | 34.0          | 0.018                           |
| Extreme (0C)   |           | 1850.8091         | 1909.1941          | 67.0          | 0.036                           |
| Extreme (-10C) |           | 1850.8089         | 1909.1939          | -78.1         | -0.042                          |
| Extreme (-20C) |           | 1850.8091         | 1909.1941          | 116.1         | 0.062                           |
| Extreme (-30C) |           | 1850.8088         | 1909.1938          | -204.0        | -0.108                          |
|                |           |                   |                    |               |                                 |
| 20C            | 15%       | 1850.8090         | 1909.1940          | 49.7          | 0.026                           |
|                | -15%      | 1850.8090         | 1909.1940          | 47.2          | 0.025                           |
|                | End Point | 1850.8090         | 1909.1940          | 45.4          | 0.024                           |

### 8.4.2. LTE BAND 5

|            |               |              |        |
|------------|---------------|--------------|--------|
| <b>ID:</b> | 44410 / 50893 | <b>Date:</b> | 3/8/18 |
|------------|---------------|--------------|--------|

#### QPSK, (10MHz BANDWIDTH)

| Limit          |           | 824                        | 849                         | Delta<br>(Hz) | Frequency<br>Stability<br>(ppm) |
|----------------|-----------|----------------------------|-----------------------------|---------------|---------------------------------|
| Condition      |           | F low @<br>-13dBm<br>(MHz) | F high @<br>-13dBm<br>(MHz) |               |                                 |
| Temperature    | Voltage   |                            |                             |               |                                 |
| Normal (20C)   | Normal    | 824.3071                   | 848.7052                    |               |                                 |
| Extreme (50C)  |           | 824.3071                   | 848.7052                    | 12.0          | 0.014                           |
| Extreme (40C)  |           | 824.3071                   | 848.7052                    | 11.5          | 0.014                           |
| Extreme (30C)  |           | 824.3071                   | 848.7052                    | 10.3          | 0.012                           |
| Extreme (10C)  |           | 824.3071                   | 848.7052                    | 11.7          | 0.014                           |
| Extreme (0C)   |           | 824.3071                   | 848.7052                    | 12.0          | 0.014                           |
| Extreme (-10C) |           | 824.3071                   | 848.7052                    | 16.5          | 0.020                           |
| Extreme (-20C) |           | 824.3071                   | 848.7052                    | 13.4          | 0.016                           |
| Extreme (-30C) |           | 824.3071                   | 848.7052                    | 13.8          | 0.016                           |
|                |           |                            |                             |               |                                 |
| 20C            | 15%       | 824.3071                   | 848.7052                    | 11.0          | 0.013                           |
|                | -15%      | 824.3071                   | 848.7052                    | 15.7          | 0.019                           |
|                | End Point | 824.3071                   | 848.7052                    | 11.2          | 0.013                           |

### 8.4.3. LTE BAND 7

|            |               |              |        |
|------------|---------------|--------------|--------|
| <b>ID:</b> | 44410 / 50893 | <b>Date:</b> | 3/8/18 |
|------------|---------------|--------------|--------|

#### QPSK, (20MHz BANDWIDTH)

| Limit          |           | 2500                       | 2570                        | Delta<br>(Hz) | Frequency<br>Stability<br>(ppm) |
|----------------|-----------|----------------------------|-----------------------------|---------------|---------------------------------|
| Condition      |           | F low @<br>-13dBm<br>(MHz) | F high @<br>-13dBm<br>(MHz) |               |                                 |
| Temperature    | Voltage   |                            |                             |               |                                 |
| Normal (20C)   | Normal    | 2500.8477                  | 2569.1289                   |               |                                 |
| Extreme (50C)  |           | 2500.8477                  | 2569.1289                   | 23.9          | 0.009                           |
| Extreme (40C)  |           | 2500.8477                  | 2569.1289                   | 22.2          | 0.009                           |
| Extreme (30C)  |           | 2500.8477                  | 2569.1289                   | 18.4          | 0.007                           |
| Extreme (10C)  |           | 2500.8477                  | 2569.1289                   | 16.8          | 0.007                           |
| Extreme (0C)   |           | 2500.8477                  | 2569.1289                   | 22.7          | 0.009                           |
| Extreme (-10C) |           | 2500.8477                  | 2569.1289                   | 20.5          | 0.008                           |
| Extreme (-20C) |           | 2500.8477                  | 2569.1289                   | 17.8          | 0.007                           |
| Extreme (-30C) |           | 2500.8477                  | 2569.1289                   | 19.3          | 0.008                           |
|                |           |                            |                             |               |                                 |
| 20C            | 15%       | 2500.8477                  | 2569.1289                   | 22.2          | 0.009                           |
|                | -15%      | 2500.8477                  | 2569.1289                   | 23.4          | 0.009                           |
|                | End Point | 2500.8477                  | 2569.1289                   | 26.8          | 0.011                           |

### 8.4.4. LTE BAND 12

|            |               |              |        |
|------------|---------------|--------------|--------|
| <b>ID:</b> | 44410 / 50893 | <b>Date:</b> | 3/8/18 |
|------------|---------------|--------------|--------|

#### QPSK, (10MHz BANDWIDTH)

| Limit          |           | 699                        | 716                         | Delta<br>(Hz) | Frequency<br>Stability<br>(ppm) |
|----------------|-----------|----------------------------|-----------------------------|---------------|---------------------------------|
| Condition      |           | F low @<br>-13dBm<br>(MHz) | F high @<br>-13dBm<br>(MHz) |               |                                 |
| Temperature    | Voltage   |                            |                             |               |                                 |
| Normal (20C)   | Normal    | 699.8591                   | 715.6711                    |               |                                 |
| Extreme (50C)  |           | 699.8591                   | 715.6711                    | 27.4          | 0.039                           |
| Extreme (40C)  |           | 699.8591                   | 715.6711                    | 25.3          | 0.036                           |
| Extreme (30C)  |           | 699.8591                   | 715.6711                    | 9.2           | 0.013                           |
| Extreme (10C)  |           | 699.8591                   | 715.6711                    | 20.7          | 0.029                           |
| Extreme (0C)   |           | 699.8591                   | 715.6711                    | 31.6          | 0.045                           |
| Extreme (-10C) |           | 699.8591                   | 715.6711                    | 28.4          | 0.040                           |
| Extreme (-20C) |           | 699.8591                   | 715.6711                    | 30.1          | 0.043                           |
| Extreme (-30C) |           | 699.8591                   | 715.6711                    | 33.0          | 0.047                           |
|                |           |                            |                             |               |                                 |
| 20C            | 15%       | 699.8591                   | 715.6711                    | 19.2          | 0.027                           |
|                | -15%      | 699.8591                   | 715.6711                    | 17.6          | 0.025                           |
|                | End Point | 699.8591                   | 715.6711                    | 18.5          | 0.026                           |



#### 8.4.5. LTE BAND 13

|            |               |              |        |
|------------|---------------|--------------|--------|
| <b>ID:</b> | 44410 / 50893 | <b>Date:</b> | 3/8/18 |
|------------|---------------|--------------|--------|

##### QPSK, (10MHz BANDWIDTH)

| Limit          |           | 777                        | 787                         | Delta<br>(Hz) | Frequency<br>Stability<br>(ppm) |
|----------------|-----------|----------------------------|-----------------------------|---------------|---------------------------------|
| Condition      |           | F low @<br>-13dBm<br>(MHz) | F high @<br>-13dBm<br>(MHz) |               |                                 |
| Temperature    | Voltage   |                            |                             |               |                                 |
| Normal (20C)   | Normal    | 777.1143                   | 786.9004                    |               |                                 |
| Extreme (50C)  |           | 777.1143                   | 786.9004                    | 38.6          | 0.049                           |
| Extreme (40C)  |           | 777.1143                   | 786.9004                    | -29.8         | -0.038                          |
| Extreme (30C)  |           | 777.1143                   | 786.9004                    | 16.3          | 0.021                           |
| Extreme (10C)  |           | 777.1143                   | 786.9004                    | 26.4          | 0.034                           |
| Extreme (0C)   |           | 777.1143                   | 786.9004                    | -30.8         | -0.039                          |
| Extreme (-10C) |           | 777.1143                   | 786.9004                    | 37.5          | 0.048                           |
| Extreme (-20C) |           | 777.1143                   | 786.9004                    | -30.2         | -0.039                          |
| Extreme (-30C) |           | 777.1143                   | 786.9004                    | 33.0          | 0.042                           |
|                |           |                            |                             |               |                                 |
| 20C            | 15%       | 777.1143                   | 786.9004                    | 26.0          | 0.033                           |
|                | -15%      | 777.1143                   | 786.9004                    | 23.1          | 0.030                           |
|                | End Point | 777.1143                   | 786.9004                    | 25.4          | 0.032                           |

#### 8.4.6. LTE BAND 14

|            |               |              |        |
|------------|---------------|--------------|--------|
| <b>ID:</b> | 44410 / 50893 | <b>Date:</b> | 3/8/18 |
|------------|---------------|--------------|--------|

##### QPSK, (10MHz BANDWIDTH)

| Limit          |           | 788                        | 798                         | Delta<br>(Hz) | Frequency<br>Stability<br>(ppm) |
|----------------|-----------|----------------------------|-----------------------------|---------------|---------------------------------|
| Condition      |           | F low @<br>-13dBm<br>(MHz) | F high @<br>-13dBm<br>(MHz) |               |                                 |
| Temperature    | Voltage   |                            |                             |               |                                 |
| Normal (20C)   | Normal    | 788.1201                   | 797.8906                    |               |                                 |
| Extreme (50C)  |           | 788.1201                   | 797.8906                    | 22.2          | 0.028                           |
| Extreme (40C)  |           | 788.1201                   | 797.8906                    | 19.1          | 0.024                           |
| Extreme (30C)  |           | 788.1201                   | 797.8906                    | 15.0          | 0.019                           |
| Extreme (10C)  |           | 788.1201                   | 797.8906                    | 21.4          | 0.027                           |
| Extreme (0C)   |           | 788.1201                   | 797.8906                    | 27.7          | 0.035                           |
| Extreme (-10C) |           | 788.1202                   | 797.8907                    | 95.5          | 0.120                           |
| Extreme (-20C) |           | 788.1201                   | 797.8906                    | 23.6          | 0.030                           |
| Extreme (-30C) |           | 788.1201                   | 797.8906                    | 27.9          | 0.035                           |
|                |           |                            |                             |               |                                 |
| 20C            | 15%       | 788.1201                   | 797.8906                    | 26.7          | 0.034                           |
|                | -15%      | 788.1201                   | 797.8906                    | -29.2         | -0.037                          |
|                | End Point | 788.1202                   | 797.8907                    | 50.4          | 0.064                           |

#### 8.4.7. LTE BAND 17

|            |               |              |        |
|------------|---------------|--------------|--------|
| <b>ID:</b> | 44410 / 50893 | <b>Date:</b> | 3/8/18 |
|------------|---------------|--------------|--------|

##### QPSK, (10MHz BANDWIDTH)

| Limit          |           | 699                  | 716                   | Delta (Hz) | Frequency Stability (ppm) |
|----------------|-----------|----------------------|-----------------------|------------|---------------------------|
| Condition      |           | F low @ -13dBm (MHz) | F high @ -13dBm (MHz) |            |                           |
| Temperature    | Voltage   |                      |                       |            |                           |
| Normal (20C)   | Normal    | 699.2908             | 715.7033              |            |                           |
| Extreme (50C)  |           | 699.2908             | 715.7033              | 27.4       | 0.039                     |
| Extreme (40C)  |           | 699.2908             | 715.7033              | 25.3       | 0.036                     |
| Extreme (30C)  |           | 699.2908             | 715.7033              | 9.2        | 0.013                     |
| Extreme (10C)  |           | 699.2908             | 715.7033              | 20.7       | 0.029                     |
| Extreme (0C)   |           | 699.2908             | 715.7033              | 31.6       | 0.045                     |
| Extreme (-10C) |           | 699.2908             | 715.7033              | 28.4       | 0.040                     |
| Extreme (-20C) |           | 699.2908             | 715.7033              | 30.1       | 0.043                     |
| Extreme (-30C) |           | 699.2908             | 715.7033              | 33.0       | 0.047                     |
|                |           |                      |                       |            |                           |
| 20C            | 15%       | 699.2908             | 715.7033              | 19.2       | 0.027                     |
|                | -15%      | 699.2908             | 715.7033              | 17.6       | 0.025                     |
|                | End Point | 699.2908             | 715.7033              | 18.5       | 0.026                     |

#### 8.4.8. LTE BAND 25

|            |               |              |        |
|------------|---------------|--------------|--------|
| <b>ID:</b> | 44410 / 50893 | <b>Date:</b> | 3/8/18 |
|------------|---------------|--------------|--------|

##### QPSK, (20MHz BANDWIDTH)

| Limit          |           | 1850                       | 1910                        | Delta<br>(Hz) | Frequency<br>Stability<br>(ppm) |
|----------------|-----------|----------------------------|-----------------------------|---------------|---------------------------------|
| Condition      |           | F low @<br>-13dBm<br>(MHz) | F high @<br>-13dBm<br>(MHz) |               |                                 |
| Temperature    | Voltage   |                            |                             |               |                                 |
| Normal (20C)   | Normal    | 1859.8429                  | 1909.1552                   |               |                                 |
| Extreme (50C)  |           | 1859.8429                  | 1909.1552                   | 37.5          | 0.020                           |
| Extreme (40C)  |           | 1859.8429                  | 1909.1552                   | 33.3          | 0.018                           |
| Extreme (30C)  |           | 1859.8429                  | 1909.1552                   | 11.0          | 0.006                           |
| Extreme (10C)  |           | 1859.8429                  | 1909.1552                   | 34.0          | 0.018                           |
| Extreme (0C)   |           | 1859.8430                  | 1909.1553                   | 67.0          | 0.036                           |
| Extreme (-10C) |           | 1859.8428                  | 1909.1551                   | -78.1         | -0.042                          |
| Extreme (-20C) |           | 1859.8430                  | 1909.1553                   | 116.1         | 0.062                           |
| Extreme (-30C) |           | 1859.8427                  | 1909.1550                   | -204.0        | -0.108                          |
|                |           |                            |                             |               |                                 |
| 20C            | 15%       | 1859.8429                  | 1909.1552                   | 49.7          | 0.026                           |
|                | -15%      | 1859.8429                  | 1909.1552                   | 47.2          | 0.025                           |
|                | End Point | 1859.8429                  | 1909.1552                   | 45.4          | 0.024                           |

#### 8.4.9. LTE BAND 26 (PART 90S)

|     |               |       |        |
|-----|---------------|-------|--------|
| ID: | 44410 / 50893 | Date: | 3/8/18 |
|-----|---------------|-------|--------|

##### QPSK, (10MHz BANDWIDTH)

| Limit          |           | 814                        | 824                         | Delta<br>(Hz) | Frequency<br>Stability<br>(ppm) |
|----------------|-----------|----------------------------|-----------------------------|---------------|---------------------------------|
| Condition      |           | F low @<br>-13dBm<br>(MHz) | F high @<br>-13dBm<br>(MHz) |               |                                 |
| Temperature    | Voltage   |                            |                             |               |                                 |
| Normal (20C)   | Normal    | 814.3176                   | 823.7120                    |               |                                 |
| Extreme (50C)  |           | 814.3176                   | 823.7120                    | 12.0          | 0.015                           |
| Extreme (40C)  |           | 814.3176                   | 823.7120                    | 11.5          | 0.014                           |
| Extreme (30C)  |           | 814.3176                   | 823.7120                    | 10.3          | 0.013                           |
| Extreme (10C)  |           | 814.3176                   | 823.7120                    | 11.7          | 0.014                           |
| Extreme (0C)   |           | 814.3176                   | 823.7120                    | 12.0          | 0.015                           |
| Extreme (-10C) |           | 814.3176                   | 823.7121                    | 16.5          | 0.020                           |
| Extreme (-20C) |           | 814.3176                   | 823.7120                    | 13.4          | 0.016                           |
| Extreme (-30C) |           | 814.3176                   | 823.7120                    | 13.8          | 0.017                           |
|                |           |                            |                             |               |                                 |
| 20C            | 15%       | 814.3176                   | 823.7120                    | 11.0          | 0.013                           |
|                | -15%      | 814.3176                   | 823.7121                    | 15.7          | 0.019                           |
|                | End Point | 814.3176                   | 823.7120                    | 11.2          | 0.014                           |

#### 8.4.10. LTE BAND 30

|     |               |       |        |
|-----|---------------|-------|--------|
| ID: | 44410 / 50893 | Date: | 3/8/18 |
|-----|---------------|-------|--------|

##### QPSK, (10MHz BANDWIDTH)

| Limit          |           | 2305                       | 2315                        | Delta<br>(Hz) | Frequency<br>Stability<br>(ppm) |
|----------------|-----------|----------------------------|-----------------------------|---------------|---------------------------------|
| Condition      |           | F low @<br>-13dBm<br>(MHz) | F high @<br>-13dBm<br>(MHz) |               |                                 |
| Temperature    | Voltage   |                            |                             |               |                                 |
| Normal (20C)   | Normal    | 2305.3139                  | 2314.6762                   |               |                                 |
| Extreme (50C)  |           | 2305.3138                  | 2314.6761                   | -115.8        | -0.050                          |
| Extreme (40C)  |           | 2305.3140                  | 2314.6763                   | 121.8         | 0.053                           |
| Extreme (30C)  |           | 2305.3139                  | 2314.6762                   | 47.7          | 0.021                           |
| Extreme (10C)  |           | 2305.3140                  | 2314.6763                   | 135.2         | 0.059                           |
| Extreme (0C)   |           | 2305.3141                  | 2314.6764                   | 237.4         | 0.103                           |
| Extreme (-10C) |           | 2305.3144                  | 2314.6767                   | 515.6         | 0.223                           |
| Extreme (-20C) |           | 2305.3143                  | 2314.6766                   | 432.3         | 0.187                           |
| Extreme (-30C) |           | 2305.3140                  | 2314.6763                   | 147.3         | 0.064                           |
|                |           |                            |                             |               |                                 |
| 20C            | 15%       | 2305.3140                  | 2314.6763                   | 69.9          | 0.030                           |
|                | -15%      | 2305.3140                  | 2314.6763                   | 66.2          | 0.029                           |
|                | End Point | 2305.3139                  | 2314.6762                   | 48.6          | 0.021                           |

#### 8.4.11. LTE BAND 41

|            |       |              |        |
|------------|-------|--------------|--------|
| <b>ID:</b> | 50893 | <b>Date:</b> | 3/8/18 |
|------------|-------|--------------|--------|

##### QPSK, (20MHz BANDWIDTH)

| Limit          |           | 2496                       | 2690                        | Delta<br>(Hz) | Frequency<br>Stability<br>(ppm) |
|----------------|-----------|----------------------------|-----------------------------|---------------|---------------------------------|
| Condition      |           | F low @<br>-13dBm<br>(MHz) | F high @<br>-13dBm<br>(MHz) |               |                                 |
| Temperature    | Voltage   |                            |                             |               |                                 |
| Normal (20C)   | Normal    | 2496.8593                  | 2689.1013                   |               |                                 |
| Extreme (50C)  |           | 2496.8593                  | 2689.1013                   | -40.4         | -0.016                          |
| Extreme (40C)  |           | 2496.8593                  | 2689.1013                   | -44.0         | -0.017                          |
| Extreme (30C)  |           | 2496.8593                  | 2689.1013                   | -42.1         | -0.016                          |
| Extreme (10C)  |           | 2496.8593                  | 2689.1013                   | -33.8         | -0.013                          |
| Extreme (0C)   |           | 2496.8593                  | 2689.1013                   | -36.5         | -0.014                          |
| Extreme (-10C) |           | 2496.8593                  | 2689.1013                   | -38.3         | -0.015                          |
| Extreme (-20C) |           | 2496.8593                  | 2689.1013                   | -37.4         | -0.014                          |
| Extreme (-30C) |           | 2496.8593                  | 2689.1013                   | -33.1         | -0.013                          |
|                |           |                            |                             |               |                                 |
| 20C            | 15%       | 2496.8592                  | 2689.1012                   | -56.4         | -0.022                          |
|                | -15%      | 2496.8592                  | 2689.1012                   | -52.8         | -0.020                          |
|                | End Point | 2496.8593                  | 2689.1013                   | 47.0          | 0.018                           |

#### 8.4.12. LTE BAND 66

|            |               |              |        |
|------------|---------------|--------------|--------|
| <b>ID:</b> | 44410 / 50893 | <b>Date:</b> | 3/8/18 |
|------------|---------------|--------------|--------|

##### QPSK, (20MHz BANDWIDTH)

| Limit          |           | 1710                       | 1780                        | Delta<br>(Hz) | Frequency<br>Stability<br>(ppm) |
|----------------|-----------|----------------------------|-----------------------------|---------------|---------------------------------|
| Condition      |           | F low @<br>-13dBm<br>(MHz) | F high @<br>-13dBm<br>(MHz) |               |                                 |
| Temperature    | Voltage   |                            |                             |               |                                 |
| Normal (20C)   | Normal    | 1710.8300                  | 1779.1717                   |               |                                 |
| Extreme (50C)  |           | 1710.8300                  | 1779.1717                   | 26.2          | 0.015                           |
| Extreme (40C)  |           | 1710.8300                  | 1779.1717                   | 21.5          | 0.012                           |
| Extreme (30C)  |           | 1710.8300                  | 1779.1717                   | 16.1          | 0.009                           |
| Extreme (10C)  |           | 1710.8300                  | 1779.1717                   | 24.7          | 0.014                           |
| Extreme (0C)   |           | 1710.8300                  | 1779.1717                   | 21.7          | 0.012                           |
| Extreme (-10C) |           | 1710.8300                  | 1779.1717                   | 21.4          | 0.012                           |
| Extreme (-20C) |           | 1710.8300                  | 1779.1717                   | 23.8          | 0.014                           |
| Extreme (-30C) |           | 1710.8300                  | 1779.1717                   | 25.1          | 0.014                           |
|                |           |                            |                             |               |                                 |
| 20C            | 15%       | 1710.8300                  | 1779.1717                   | 16.8          | 0.010                           |
|                | -15%      | 1710.8300                  | 1779.1717                   | 19.9          | 0.011                           |
|                | End Point | 1710.8300                  | 1779.1717                   | 22.6          | 0.013                           |

### 8.4.13. LTE BAND 71

|            |               |              |        |
|------------|---------------|--------------|--------|
| <b>ID:</b> | 44410 / 50893 | <b>Date:</b> | 3/8/18 |
|------------|---------------|--------------|--------|

#### QPSK, (20MHz BANDWIDTH)

| Limit          |           | 663               | 698                | Delta<br>(Hz) | Frequency<br>Stability<br>(ppm) |
|----------------|-----------|-------------------|--------------------|---------------|---------------------------------|
| Condition      |           | F low @<br>-13dBm | F high @<br>-13dBm |               |                                 |
| Temperature    | Voltage   | (MHz)             | (MHz)              |               |                                 |
| Normal (20C)   | Normal    | 663.8816          | 697.1902           |               |                                 |
| Extreme (50C)  |           | 663.8816          | 697.1902           | 18.9          | 0.028                           |
| Extreme (40C)  |           | 663.8816          | 697.1902           | 17.6          | 0.026                           |
| Extreme (30C)  |           | 663.8816          | 697.1902           | 15.1          | 0.022                           |
| Extreme (10C)  |           | 663.8816          | 697.1902           | -20.8         | -0.031                          |
| Extreme (0C)   |           | 663.8816          | 697.1902           | 26.0          | 0.038                           |
| Extreme (-10C) |           | 663.8816          | 697.1902           | -25.9         | -0.038                          |
| Extreme (-20C) |           | 663.8816          | 697.1902           | 23.0          | 0.034                           |
| Extreme (-30C) |           | 663.8816          | 697.1902           | -33.8         | -0.050                          |
|                |           |                   |                    |               |                                 |
| 20C            | 15%       | 663.8816          | 697.1902           | 30.8          | 0.045                           |
|                | -15%      | 663.8816          | 697.1902           | -22.3         | -0.033                          |
|                | End Point | 663.8816          | 697.1902           | -23.5         | -0.035                          |

## 8.5. PEAK-TO-AVERAGE POWER RATIO

### LIMIT

In addition, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time and shall use a signal corresponding to the highest PAPR during periods of continuous transmission.

### MODES TESTED

- LTE Band 2
- LTE Band 5
- LTE Band 7
- LTE Band 12
- LTE Band 13
- LTE Band 14
- LTE Band 17
- LTE Band 25
- LTE Band 26
- LTE Band 30
- LTE Band 41
- LTE Band 66
- LTE Band 71

### RESULT

Ant 1 was used to measure as the worst case; full resource block (FRB) for each bandwidth was used to measure as the worst case. The results from all CCDF measurements are passed with 13dB peak-to-average power ratio criteria.

|            |      |              |        |
|------------|------|--------------|--------|
| <b>ID:</b> | 9467 | <b>Date:</b> | 6/6/18 |
|------------|------|--------------|--------|

## 8.5.1. LTE BAND 2










## 8.5.2. LTE BAND 5






### 8.5.3. LTE BAND 7






## 8.5.4. LTE BAND 12






## 8.5.5. LTE BAND 13




## 8.5.6. LTE BAND 14





## 8.5.7. LTE BAND 17




## 8.5.8. LTE BAND 25





### 8.5.9. LTE BAND 26 (PART 90S)





## 8.5.10. LTE BAND 30



### 8.5.11. LTE BAND 41

|            |       |              |        |
|------------|-------|--------------|--------|
| <b>ID:</b> | 10646 | <b>Date:</b> | 6/6/18 |
|------------|-------|--------------|--------|

| Band                                                                                       | Bandwidth (MHz) | Frequency (MHz) | RB Allocation | RB OffSet | Modulation | Conducted Power (dBm) |         | Peak-to-Average Power Ratio (dB) |
|--------------------------------------------------------------------------------------------|-----------------|-----------------|---------------|-----------|------------|-----------------------|---------|----------------------------------|
|                                                                                            |                 |                 |               |           |            | Peak                  | Average |                                  |
| Band 41                                                                                    | 5MHz            | 2593.0          | 25            | 0         | QPSK       | 34.17                 | 20.04   | 7.14                             |
|                                                                                            |                 |                 |               |           | 16QAM      | 34.13                 | 19.04   | 8.10                             |
|                                                                                            | 10MHz           |                 | 50            | 0         | QPSK       | 33.98                 | 20.04   | 6.95                             |
|                                                                                            |                 |                 |               |           | 16QAM      | 33.92                 | 19.13   | 7.80                             |
|                                                                                            | 15MHz           |                 | 75            | 0         | QPSK       | 33.90                 | 19.46   | 7.45                             |
|                                                                                            |                 |                 |               |           | 16QAM      | 33.88                 | 19.01   | 7.88                             |
|                                                                                            | 20MHz           |                 | 100           | 0         | QPSK       | 33.63                 | 19.93   | 6.71                             |
|                                                                                            |                 |                 |               |           | 16QAM      | 33.50                 | 18.96   | 7.55                             |
| Duty Cycle Correction Factor (dB) =                                                        |                 |                 | 6.99          |           |            |                       |         |                                  |
| Peak-to-Average Power Ratio= Peak Reading - Average Reading - Duty Cycle Correction Factor |                 |                 |               |           |            |                       |         |                                  |


## 8.5.12. LTE BAND 66








### 8.5.13. LTE BAND 71





## 9. RADIATED TEST RESULTS

### RULE PART(S)

§2.1053, §22.917, §24.238, §27.53, §90.691, and §90.543

### LIMIT

§22.917(a), §24.238(a), §27.53 (g), (h), §90.691

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

§27.53 (Band 13)

(c) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

(f) Emissions in the band 1559-1610 MHz shall be limited to  $-70$  dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals. ( $-70$  dBW/MHz =  $-40$  dBm/MHz).

§90.543 Emission Limitations. (Band 14)

(e) For operations in the 758-768 MHz and the 788-798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least  $43 + 10 \log (P)$  dB.

(f) For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to  $-70$  dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and  $-80$  dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

§27.53 (a) (Band 30, Band 40)

For mobile and portable stations operating in the 2305-2315 MHz: by a factor of not less than  $43 + 10 \log (P)$  dB on all frequencies between 2360 and 2365 MHz, and not less than  $70 + 10 \log (P)$  dB above 2365 MHz.

§27.53 (m) (Band 7, 41)

At least  $55 + 10 \log (P)$  dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section.

### TEST PROCEDURE

KDB 971168 D01 v03r01/ D02 v02r01

### MODES TESTED

- LTE Band 2
- LTE Band 5
- LTE Band 7
- LTE Band 12
- LTE Band 13
- LTE Band 14
- LTE Band 17
- LTE Band 25
- LTE Band 26
- LTE Band 30
- LTE Band 41
- LTE Band 66
- LTE Band 71

---

**RESULTS**



### 9.1.3. LTE BAND 7

**High Frequency Substitution Measurement**  
UL Fremont Radiated Chamber

Company:  
Project #:  
Date: 06/16/18  
Test Engineer: 19429  
Configuration: EUT only  
Mode: LTE Band 7, 20MHz QPSK

Test Equipment:  
Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber  
3m Chamber E

Pre-amplifier  
3m Chamber E

Filter  
Filter

Limit  
EIRP

| Frequency (GHz)               | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
|-------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| <b>Low Channel (2510MHz)</b>  |                  |                 |          |                         |        |            |       |       |       |       |
| 5.02                          | -72.5            | H               | 3.0      | -19.6                   | 38.7   | 1.0        | -57.3 | -13.0 | -44.3 |       |
| 7.53                          | -75.7            | H               | 3.0      | -17.9                   | 37.7   | 1.0        | -54.6 | -13.0 | -41.6 |       |
| 10.04                         | -71.8            | H               | 3.0      | -17.0                   | 36.2   | 1.0        | -52.1 | -13.0 | -39.1 |       |
| 5.02                          | -69.9            | V               | 3.0      | -17.3                   | 38.7   | 1.0        | -55.0 | -13.0 | -42.0 |       |
| 7.53                          | -75.6            | V               | 3.0      | -17.9                   | 37.7   | 1.0        | -54.7 | -13.0 | -41.7 |       |
| 10.04                         | -77.5            | V               | 3.0      | -16.7                   | 36.2   | 1.0        | -51.8 | -13.0 | -38.8 |       |
| <b>Mid Channel (2535MHz)</b>  |                  |                 |          |                         |        |            |       |       |       |       |
| 5.07                          | -70.5            | H               | 3.0      | -16.9                   | 38.7   | 1.0        | -54.6 | -13.0 | -41.6 |       |
| 7.61                          | -74.8            | H               | 3.0      | -17.6                   | 37.7   | 1.0        | -54.3 | -13.0 | -41.3 |       |
| 10.14                         | -77.5            | H               | 3.0      | -16.6                   | 36.2   | 1.0        | -51.8 | -13.0 | -38.8 |       |
| 5.07                          | -72.2            | V               | 3.0      | -19.4                   | 38.7   | 1.0        | -57.1 | -13.0 | -44.1 |       |
| 7.61                          | -73.8            | V               | 3.0      | -16.1                   | 37.7   | 1.0        | -52.8 | -13.0 | -39.8 |       |
| 10.14                         | -77.7            | V               | 3.0      | -16.8                   | 36.2   | 1.0        | -52.0 | -13.0 | -39.0 |       |
| <b>High Channel (2560MHz)</b> |                  |                 |          |                         |        |            |       |       |       |       |
| 5.12                          | -70.6            | H               | 3.0      | -17.5                   | 38.7   | 1.0        | -55.1 | -13.0 | -42.1 |       |
| 7.68                          | -72.3            | H               | 3.0      | -14.3                   | 37.6   | 1.0        | -51.0 | -13.0 | -38.0 |       |
| 10.24                         | -76.1            | H               | 3.0      | -15.1                   | 36.3   | 1.0        | -50.4 | -13.0 | -37.4 |       |
| 5.12                          | -70.6            | V               | 3.0      | -17.8                   | 38.7   | 1.0        | -55.5 | -13.0 | -42.5 |       |
| 7.68                          | -74.4            | V               | 3.0      | -16.6                   | 37.6   | 1.0        | -53.3 | -13.0 | -40.3 |       |
| 10.24                         | -77.8            | V               | 3.0      | -15.9                   | 36.3   | 1.0        | -51.2 | -13.0 | -38.2 |       |

Rev 05.21.15

LTE B7 20MHz QPSK

**High Frequency Substitution Measurement**  
UL Fremont Radiated Chamber

Company:  
Project #:  
Date: 06/16/18  
Test Engineer: 19429  
Configuration: EUT only  
Mode: LTE Band 7, 20MHz 16QAM

Test Equipment:  
Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber  
3m Chamber E

Pre-amplifier  
3m Chamber E

Filter  
Filter

Limit  
EIRP

| Frequency (GHz)               | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
|-------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| <b>Low Channel (2510MHz)</b>  |                  |                 |          |                         |        |            |       |       |       |       |
| 5.02                          | -70.3            | H               | 3.0      | -17.4                   | 38.7   | 1.0        | -55.1 | -13.0 | -42.1 |       |
| 7.53                          | -73.0            | H               | 3.0      | -15.2                   | 37.7   | 1.0        | -51.9 | -13.0 | -38.9 |       |
| 10.04                         | -76.8            | H               | 3.0      | -15.9                   | 36.2   | 1.0        | -51.1 | -13.0 | -38.1 |       |
| 5.02                          | -70.9            | V               | 3.0      | -18.3                   | 38.7   | 1.0        | -56.0 | -13.0 | -43.0 |       |
| 7.53                          | -74.9            | V               | 3.0      | -17.3                   | 37.7   | 1.0        | -54.0 | -13.0 | -41.0 |       |
| 10.04                         | -76.0            | V               | 3.0      | -15.2                   | 36.2   | 1.0        | -50.3 | -13.0 | -37.3 |       |
| <b>Mid Channel (2535MHz)</b>  |                  |                 |          |                         |        |            |       |       |       |       |
| 5.07                          | -69.6            | H               | 3.0      | -16.6                   | 38.7   | 1.0        | -54.3 | -13.0 | -41.3 |       |
| 7.61                          | -73.0            | H               | 3.0      | -15.0                   | 37.7   | 1.0        | -51.7 | -13.0 | -38.7 |       |
| 10.14                         | -74.8            | H               | 3.0      | -13.9                   | 36.2   | 1.0        | -49.1 | -13.0 | -36.1 |       |
| 5.07                          | -70.3            | V               | 3.0      | -17.6                   | 38.7   | 1.0        | -55.3 | -13.0 | -42.3 |       |
| 7.61                          | -73.9            | V               | 3.0      | -16.2                   | 37.7   | 1.0        | -52.9 | -13.0 | -39.9 |       |
| 10.14                         | -76.8            | V               | 3.0      | -15.9                   | 36.2   | 1.0        | -51.1 | -13.0 | -38.1 |       |
| <b>High Channel (2560MHz)</b> |                  |                 |          |                         |        |            |       |       |       |       |
| 5.12                          | -70.3            | H               | 3.0      | -17.2                   | 38.7   | 1.0        | -54.9 | -13.0 | -41.9 |       |
| 7.68                          | -72.6            | H               | 3.0      | -14.6                   | 37.6   | 1.0        | -51.2 | -13.0 | -38.2 |       |
| 10.24                         | -76.3            | H               | 3.0      | -15.3                   | 36.3   | 1.0        | -50.6 | -13.0 | -37.6 |       |
| 5.12                          | -70.4            | V               | 3.0      | -17.6                   | 38.7   | 1.0        | -55.3 | -13.0 | -42.3 |       |
| 7.68                          | -74.3            | V               | 3.0      | -16.5                   | 37.6   | 1.0        | -53.2 | -13.0 | -40.2 |       |
| 10.24                         | -76.5            | V               | 3.0      | -15.5                   | 36.3   | 1.0        | -50.7 | -13.0 | -37.7 |       |

Rev 05.21.15

LTE B7 20MHz 16QAM

## 9.1.4. LTE BAND 12

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                                                                                                    |                  |                 |          |                         |        |            |       |       |       |       |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/15/18<br>Test Engineer: 19429<br>Configuration: EUT Only<br>Mode: LTE Band 12, 10MHz QPSK<br>Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable |                  |                 |          |                         |        |            |       |       |       |       |
| Chamber                                                                                                                                                                                                   |                  | Pre-amplifier   |          | Filter                  |        | Limit      |       |       |       |       |
| 3m Chamber C                                                                                                                                                                                              |                  | 3m Chamber C    |          | Filter                  |        | EIRP       |       |       |       |       |
| Frequency (GHz)                                                                                                                                                                                           | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
| Low Channel (704MHz)                                                                                                                                                                                      |                  |                 |          |                         |        |            |       |       |       |       |
| 1.41                                                                                                                                                                                                      | -67.5            | H               | 3.0      | -27.2                   | 36.7   | 1.0        | -62.9 | -13.0 | -49.9 |       |
| 2.11                                                                                                                                                                                                      | -68.0            | H               | 3.0      | -23.1                   | 35.8   | 1.0        | -57.9 | -13.0 | -44.9 |       |
| 2.82                                                                                                                                                                                                      | -66.4            | H               | 3.0      | -19.2                   | 35.0   | 1.0        | -53.2 | -13.0 | -40.2 |       |
| 1.41                                                                                                                                                                                                      | -66.5            | V               | 3.0      | -25.4                   | 36.7   | 1.0        | -61.1 | -13.0 | -48.1 |       |
| 2.11                                                                                                                                                                                                      | -67.7            | V               | 3.0      | -22.0                   | 35.8   | 1.0        | -56.8 | -13.0 | -43.8 |       |
| 2.82                                                                                                                                                                                                      | -65.1            | V               | 3.0      | -17.3                   | 35.0   | 1.0        | -51.4 | -13.0 | -38.4 |       |
| Mid Channel (707.5MHz)                                                                                                                                                                                    |                  |                 |          |                         |        |            |       |       |       |       |
| 1.42                                                                                                                                                                                                      | -67.7            | H               | 3.0      | -27.4                   | 36.7   | 1.0        | -63.1 | -13.0 | -50.1 |       |
| 2.12                                                                                                                                                                                                      | -67.4            | H               | 3.0      | -22.4                   | 35.7   | 1.0        | -57.2 | -13.0 | -44.2 |       |
| 2.83                                                                                                                                                                                                      | -66.9            | H               | 3.0      | -19.6                   | 35.0   | 1.0        | -53.6 | -13.0 | -40.6 |       |
| 1.42                                                                                                                                                                                                      | -66.6            | V               | 3.0      | -24.9                   | 36.7   | 1.0        | -60.5 | -13.0 | -47.5 |       |
| 2.12                                                                                                                                                                                                      | -66.9            | V               | 3.0      | -21.2                   | 35.7   | 1.0        | -56.9 | -13.0 | -43.9 |       |
| 2.83                                                                                                                                                                                                      | -65.5            | V               | 3.0      | -18.6                   | 35.0   | 1.0        | -52.7 | -13.0 | -39.7 |       |
| High Channel (711MHz)                                                                                                                                                                                     |                  |                 |          |                         |        |            |       |       |       |       |
| 1.42                                                                                                                                                                                                      | -67.0            | H               | 3.0      | -26.8                   | 36.7   | 1.0        | -62.4 | -13.0 | -49.4 |       |
| 2.13                                                                                                                                                                                                      | -67.1            | H               | 3.0      | -22.2                   | 35.7   | 1.0        | -56.9 | -13.0 | -43.9 |       |
| 2.84                                                                                                                                                                                                      | -65.3            | H               | 3.0      | -18.0                   | 35.0   | 1.0        | -52.0 | -13.0 | -39.0 |       |
| 1.42                                                                                                                                                                                                      | -66.5            | V               | 3.0      | -25.8                   | 36.7   | 1.0        | -61.5 | -13.0 | -48.5 |       |
| 2.13                                                                                                                                                                                                      | -67.0            | V               | 3.0      | -21.3                   | 35.7   | 1.0        | -56.0 | -13.0 | -43.0 |       |
| 2.84                                                                                                                                                                                                      | -67.3            | V               | 3.0      | -19.3                   | 35.0   | 1.0        | -53.4 | -13.0 | -40.4 |       |
| Rev. 05.21.15                                                                                                                                                                                             |                  |                 |          |                         |        |            |       |       |       |       |

LTE B12 10MHz QPSK

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                                                                                                     |                  |                 |          |                         |        |            |       |       |       |       |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/15/18<br>Test Engineer: 19429<br>Configuration: EUT Only<br>Mode: LTE Band 12, 10MHz 16QAM<br>Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable |                  |                 |          |                         |        |            |       |       |       |       |
| Chamber                                                                                                                                                                                                    |                  | Pre-amplifier   |          | Filter                  |        | Limit      |       |       |       |       |
| 3m Chamber C                                                                                                                                                                                               |                  | 3m Chamber C    |          | Filter                  |        | EIRP       |       |       |       |       |
| Frequency (GHz)                                                                                                                                                                                            | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
| Low Channel (704MHz)                                                                                                                                                                                       |                  |                 |          |                         |        |            |       |       |       |       |
| 1.41                                                                                                                                                                                                       | -65.6            | H               | 3.0      | -25.4                   | 36.7   | 1.0        | -61.1 | -13.0 | -48.1 |       |
| 2.11                                                                                                                                                                                                       | -67.1            | H               | 3.0      | -22.2                   | 35.8   | 1.0        | -57.0 | -13.0 | -44.0 |       |
| 2.82                                                                                                                                                                                                       | -66.9            | H               | 3.0      | -19.7                   | 35.0   | 1.0        | -53.7 | -13.0 | -40.7 |       |
| 1.41                                                                                                                                                                                                       | -66.7            | V               | 3.0      | -26.0                   | 36.7   | 1.0        | -61.7 | -13.0 | -48.7 |       |
| 2.11                                                                                                                                                                                                       | -67.3            | V               | 3.0      | -21.5                   | 35.0   | 1.0        | -56.3 | -13.0 | -43.3 |       |
| 2.82                                                                                                                                                                                                       | -67.3            | V               | 3.0      | -19.5                   | 35.0   | 1.0        | -53.6 | -13.0 | -40.6 |       |
| Mid Channel (707.5MHz)                                                                                                                                                                                     |                  |                 |          |                         |        |            |       |       |       |       |
| 1.42                                                                                                                                                                                                       | -66.4            | H               | 3.0      | -26.1                   | 36.7   | 1.0        | -61.8 | -13.0 | -48.8 |       |
| 2.12                                                                                                                                                                                                       | -66.8            | H               | 3.0      | -21.9                   | 35.7   | 1.0        | -56.6 | -13.0 | -43.6 |       |
| 2.83                                                                                                                                                                                                       | -65.6            | H               | 3.0      | -18.3                   | 35.0   | 1.0        | -52.3 | -13.0 | -39.3 |       |
| 1.42                                                                                                                                                                                                       | -67.6            | V               | 3.0      | -26.9                   | 36.7   | 1.0        | -62.6 | -13.0 | -49.6 |       |
| 2.12                                                                                                                                                                                                       | -67.7            | V               | 3.0      | -22.0                   | 35.7   | 1.0        | -56.7 | -13.0 | -43.7 |       |
| 2.83                                                                                                                                                                                                       | -67.4            | V               | 3.0      | -19.6                   | 35.0   | 1.0        | -53.6 | -13.0 | -40.6 |       |
| High Channel (711MHz)                                                                                                                                                                                      |                  |                 |          |                         |        |            |       |       |       |       |
| 1.42                                                                                                                                                                                                       | -67.2            | H               | 3.0      | -26.9                   | 36.7   | 1.0        | -62.6 | -13.0 | -49.6 |       |
| 2.13                                                                                                                                                                                                       | -66.1            | H               | 3.0      | -21.2                   | 35.7   | 1.0        | -56.9 | -13.0 | -43.9 |       |
| 2.84                                                                                                                                                                                                       | -66.0            | H               | 3.0      | -18.6                   | 35.0   | 1.0        | -52.7 | -13.0 | -39.7 |       |
| 1.42                                                                                                                                                                                                       | -66.2            | V               | 3.0      | -27.5                   | 36.7   | 1.0        | -63.1 | -13.0 | -50.1 |       |
| 2.13                                                                                                                                                                                                       | -67.3            | V               | 3.0      | -21.6                   | 35.7   | 1.0        | -56.3 | -13.0 | -43.3 |       |
| 2.84                                                                                                                                                                                                       | -66.4            | V               | 3.0      | -18.5                   | 35.0   | 1.0        | -52.5 | -13.0 | -39.5 |       |
| Rev. 05.21.15                                                                                                                                                                                              |                  |                 |          |                         |        |            |       |       |       |       |

LTE B12 10MHz 16QAM

## 9.1.5. LTE BAND 13

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                                                                                                    |                  |                 |          |                         |        |            |       |       |       |       |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/15/18<br>Test Engineer: 19429<br>Configuration: EUT Only<br>Mode: LTE Band 13, 10MHz QPSK<br>Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable |                  |                 |          |                         |        |            |       |       |       |       |
| Chamber                                                                                                                                                                                                   |                  | Pre-amplifier   |          | Filter                  |        | Limit      |       |       |       |       |
| 3m Chamber C                                                                                                                                                                                              |                  | 3m Chamber C    |          | Filter                  |        | LTE B13    |       |       |       |       |
| Frequency (GHz)                                                                                                                                                                                           | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
| Mid Channel (726MHz)                                                                                                                                                                                      |                  |                 |          |                         |        |            |       |       |       |       |
| 1.96                                                                                                                                                                                                      | -66.9            | H               | 3.0      | -25.8                   | 36.6   | 1.0        | -61.5 | -40.0 | -21.5 |       |
| 2.39                                                                                                                                                                                                      | -66.0            | H               | 3.0      | -20.7                   | 35.3   | 1.0        | -55.0 | -13.0 | -42.0 |       |
| 3.13                                                                                                                                                                                                      | -66.5            | H               | 3.0      | -18.1                   | 34.8   | 1.0        | -51.9 | -13.0 | -38.9 |       |
| 1.96                                                                                                                                                                                                      | -66.5            | V               | 3.0      | -24.7                   | 36.6   | 1.0        | -60.4 | -40.0 | -20.4 |       |
| 2.39                                                                                                                                                                                                      | -67.0            | V               | 3.0      | -21.6                   | 35.3   | 1.0        | -55.8 | -13.0 | -42.8 |       |
| 3.13                                                                                                                                                                                                      | -66.1            | V               | 3.0      | -18.9                   | 34.8   | 1.0        | -50.8 | -13.0 | -37.8 |       |
| Rev. 05.21.15                                                                                                                                                                                             |                  |                 |          |                         |        |            |       |       |       |       |

LTE B13 10MHz QPSK

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                                                                                                     |                  |                 |          |                         |        |            |       |       |       |       |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/15/18<br>Test Engineer: 19429<br>Configuration: EUT Only<br>Mode: LTE Band 13, 10MHz 16QAM<br>Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable |                  |                 |          |                         |        |            |       |       |       |       |
| Chamber                                                                                                                                                                                                    |                  | Pre-amplifier   |          | Filter                  |        | Limit      |       |       |       |       |
| 3m Chamber C                                                                                                                                                                                               |                  | 3m Chamber C    |          | Filter                  |        | LTE B13    |       |       |       |       |
| Frequency (GHz)                                                                                                                                                                                            | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
| Mid Channel (726MHz)                                                                                                                                                                                       |                  |                 |          |                         |        |            |       |       |       |       |
| 1.96                                                                                                                                                                                                       | -66.3            | H               | 3.0      | -25.2                   | 36.5   | 1.0        | -60.8 | -40.0 | -20.8 |       |
| 2.39                                                                                                                                                                                                       | -66.7            | H               | 3.0      | -21.4                   | 35.3   | 1.0        | -56.7 | -13.0 | -43.7 |       |
| 3.13                                                                                                                                                                                                       | -66.0            | H               | 3.0      | -17.6                   | 34.8   | 1.0        | -51.4 | -13.0 | -38.4 |       |
| 1.96                                                                                                                                                                                                       | -67.5            | V               | 3.0      | -25.7                   | 36.6   | 1.0        | -61.3 | -40.0 | -21.3 |       |
| 2.39                                                                                                                                                                                                       | -67.5            | V               | 3.0      | -22.0                   | 35.3   | 1.0        | -56.3 | -13.0 | -43.3 |       |
| 3.13                                                                                                                                                                                                       | -66.4            | V               | 3.0      | -17.3                   | 34.8   | 1.0        | -51.1 | -13.0 | -38.1 |       |
| Rev. 05.21.15                                                                                                                                                                                              |                  |                 |          |                         |        |            |       |       |       |       |

LTE B13 10MHz 16QAM



## 9.1.6. LTE BAND 14

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                       |                  |                 |          |                         |        |            |       |       |       |       |
|------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/17/18<br>Test Engineer: 19429<br>Configuration: EUT Only<br>Mode: LTE Band 14, 10MHz QPSK |                  |                 |          |                         |        |            |       |       |       |       |
| Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable                                                    |                  |                 |          |                         |        |            |       |       |       |       |
| Chamber: 3m Chamber E<br>Pre-amplifier: 3m Chamber E<br>Filter: Filter<br>Limit: EIRP                                        |                  |                 |          |                         |        |            |       |       |       |       |
| Frequency (GHz)                                                                                                              | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
| Mid Channel (750MHz)                                                                                                         |                  |                 |          |                         |        |            |       |       |       |       |
| 1.99                                                                                                                         | -66.2            | H               | 3.0      | -23.9                   | 37.8   | 1.0        | -60.7 | -40.0 | -20.7 |       |
| 2.38                                                                                                                         | -65.7            | H               | 3.0      | -21.2                   | 38.2   | 1.0        | -58.3 | -13.0 | -45.3 |       |
| 3.17                                                                                                                         | -66.4            | H               | 3.0      | -17.8                   | 38.4   | 1.0        | -55.2 | -13.0 | -42.2 |       |
| 1.99                                                                                                                         | -66.5            | V               | 3.0      | -24.7                   | 37.8   | 1.0        | -61.5 | -40.0 | -21.5 |       |
| 2.38                                                                                                                         | -66.3            | V               | 3.0      | -21.6                   | 38.2   | 1.0        | -58.7 | -13.0 | -45.7 |       |
| 3.17                                                                                                                         | -65.7            | V               | 3.0      | -17.4                   | 38.4   | 1.0        | -54.8 | -13.0 | -41.8 |       |
| Rev. 05.21.15                                                                                                                |                  |                 |          |                         |        |            |       |       |       |       |
| LTE B14 10MHz QPSK                                                                                                           |                  |                 |          |                         |        |            |       |       |       |       |

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                        |                  |                 |          |                         |        |            |       |       |       |       |
|-------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/17/18<br>Test Engineer: 19429<br>Configuration: EUT Only<br>Mode: LTE Band 14, 10MHz 16QAM |                  |                 |          |                         |        |            |       |       |       |       |
| Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable                                                     |                  |                 |          |                         |        |            |       |       |       |       |
| Chamber: 3m Chamber E<br>Pre-amplifier: 3m Chamber E<br>Filter: Filter<br>Limit: EIRP                                         |                  |                 |          |                         |        |            |       |       |       |       |
| Frequency (GHz)                                                                                                               | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
| Mid Channel (750MHz)                                                                                                          |                  |                 |          |                         |        |            |       |       |       |       |
| 1.99                                                                                                                          | -66.3            | H               | 3.0      | -24.0                   | 37.8   | 1.0        | -60.8 | -40.0 | -20.8 |       |
| 2.38                                                                                                                          | -65.6            | H               | 3.0      | -21.1                   | 38.2   | 1.0        | -58.2 | -13.0 | -45.2 |       |
| 3.17                                                                                                                          | -65.5            | H               | 3.0      | -18.9                   | 38.4   | 1.0        | -54.3 | -13.0 | -41.3 |       |
| 1.99                                                                                                                          | -65.8            | V               | 3.0      | -24.0                   | 37.8   | 1.0        | -60.8 | -40.0 | -20.8 |       |
| 2.38                                                                                                                          | -65.7            | V               | 3.0      | -21.0                   | 38.2   | 1.0        | -58.1 | -13.0 | -45.1 |       |
| 3.17                                                                                                                          | -64.6            | V               | 3.0      | -16.3                   | 38.4   | 1.0        | -53.7 | -13.0 | -40.7 |       |
| Rev. 05.21.15                                                                                                                 |                  |                 |          |                         |        |            |       |       |       |       |
| LTE B14 10MHz 16QAM                                                                                                           |                  |                 |          |                         |        |            |       |       |       |       |

## 9.1.7. LTE BAND 17

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                       |                  |                 |          |                         |        |            |       |       |       |       |
|------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/15/18<br>Test Engineer: 19429<br>Configuration: EUT Only<br>Mode: LTE Band 17, 10MHz QPSK |                  |                 |          |                         |        |            |       |       |       |       |
| Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable                                                    |                  |                 |          |                         |        |            |       |       |       |       |
| Chamber: 3m Chamber C<br>Pre-amplifier: 3m Chamber C<br>Filter: Filter<br>Limit: EIRP                                        |                  |                 |          |                         |        |            |       |       |       |       |
| Frequency (GHz)                                                                                                              | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
| Mid Channel (710MHz)                                                                                                         |                  |                 |          |                         |        |            |       |       |       |       |
| 1.42                                                                                                                         | -68.1            | H               | 3.0      | -27.8                   | 35.7   | 1.0        | -63.5 | -13.0 | -50.5 |       |
| 2.13                                                                                                                         | -67.3            | H               | 3.0      | -22.4                   | 35.7   | 1.0        | -57.1 | -13.0 | -44.1 |       |
| 2.84                                                                                                                         | -67.3            | H               | 3.0      | -20.0                   | 35.0   | 1.0        | -54.0 | -13.0 | -41.0 |       |
| 1.42                                                                                                                         | -67.2            | V               | 3.0      | -26.5                   | 36.7   | 1.0        | -62.2 | -13.0 | -49.2 |       |
| 2.13                                                                                                                         | -66.0            | V               | 3.0      | -20.3                   | 35.7   | 1.0        | -55.0 | -13.0 | -42.0 |       |
| 2.84                                                                                                                         | -66.6            | V               | 3.0      | -18.7                   | 35.0   | 1.0        | -52.7 | -13.0 | -39.7 |       |
| Rev. 05.21.15                                                                                                                |                  |                 |          |                         |        |            |       |       |       |       |
| LTE B17 10MHz QPSK                                                                                                           |                  |                 |          |                         |        |            |       |       |       |       |

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                        |                  |                 |          |                         |        |            |       |       |       |       |
|-------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/15/18<br>Test Engineer: 19429<br>Configuration: EUT Only<br>Mode: LTE Band 17, 10MHz 16QAM |                  |                 |          |                         |        |            |       |       |       |       |
| Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable                                                     |                  |                 |          |                         |        |            |       |       |       |       |
| Chamber: 3m Chamber C<br>Pre-amplifier: 3m Chamber C<br>Filter: Filter<br>Limit: EIRP                                         |                  |                 |          |                         |        |            |       |       |       |       |
| Frequency (GHz)                                                                                                               | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
| Mid Channel (710MHz)                                                                                                          |                  |                 |          |                         |        |            |       |       |       |       |
| 1.42                                                                                                                          | -68.4            | H               | 3.0      | -26.2                   | 35.7   | 1.0        | -61.9 | -13.0 | -48.9 |       |
| 2.13                                                                                                                          | -67.6            | H               | 3.0      | -22.7                   | 35.7   | 1.0        | -57.4 | -13.0 | -44.4 |       |
| 2.84                                                                                                                          | -66.1            | H               | 3.0      | -18.7                   | 35.0   | 1.0        | -52.8 | -13.0 | -39.8 |       |
| 1.42                                                                                                                          | -67.3            | V               | 3.0      | -26.5                   | 36.7   | 1.0        | -62.2 | -13.0 | -49.2 |       |
| 2.13                                                                                                                          | -67.6            | V               | 3.0      | -21.8                   | 35.7   | 1.0        | -56.6 | -13.0 | -43.6 |       |
| 2.84                                                                                                                          | -66.6            | V               | 3.0      | -18.7                   | 35.0   | 1.0        | -52.8 | -13.0 | -39.8 |       |
| Rev. 05.21.15                                                                                                                 |                  |                 |          |                         |        |            |       |       |       |       |
| LTE B17 10MHz 16QAM                                                                                                           |                  |                 |          |                         |        |            |       |       |       |       |

## 9.1.8. LTE BAND 25

High Frequency Substitution Measurement

UL Fremont Radiated Chamber

Company:

Project #:

Date: 06/15/18

Test Engineer: 19429

Configuration: EUT Only

Mode: LTE Band 25, 20MHz QPSK

Test Equipment:

Substitution: Horn T59 Substitution, and 8T SMA Cable

Chamber

3m Chamber F

Pre-amplifier

3m Chamber F

Filter

Filter

Limit

ERP

| Frequency (GHz)         | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
|-------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Low Channel (1860MHz)   |                  |                 |          |                         |        |            |       |       |       |       |
| 3.72                    | -69.2            | H               | 3.0      | -19.4                   | 34.4   | 1.0        | -52.8 | -13.0 | -39.8 |       |
| 5.98                    | -70.9            | H               | 3.0      | -17.4                   | 34.1   | 1.0        | -50.5 | -13.0 | -37.5 |       |
| 7.44                    | -73.0            | H               | 3.0      | -16.6                   | 33.6   | 1.0        | -49.2 | -13.0 | -36.2 |       |
| 3.72                    | -70.6            | V               | 3.0      | -20.1                   | 34.4   | 1.0        | -53.5 | -13.0 | -40.5 |       |
| 5.98                    | -70.0            | V               | 3.0      | -18.3                   | 34.1   | 1.0        | -49.5 | -13.0 | -36.5 |       |
| 7.44                    | -72.2            | V               | 3.0      | -16.1                   | 33.6   | 1.0        | -48.7 | -13.0 | -35.7 |       |
| Mid Channel (1882.5MHz) |                  |                 |          |                         |        |            |       |       |       |       |
| 3.77                    | -70.7            | H               | 3.0      | -20.7                   | 34.4   | 1.0        | -54.1 | -13.0 | -41.1 |       |
| 5.98                    | -70.2            | H               | 3.0      | -18.6                   | 34.1   | 1.0        | -49.7 | -13.0 | -36.7 |       |
| 7.53                    | -72.7            | H               | 3.0      | -16.2                   | 33.5   | 1.0        | -48.7 | -13.0 | -35.7 |       |
| 3.77                    | -70.5            | V               | 3.0      | -20.4                   | 34.4   | 1.0        | -53.8 | -13.0 | -40.8 |       |
| 5.98                    | -70.1            | V               | 3.0      | -18.5                   | 34.1   | 1.0        | -49.7 | -13.0 | -36.7 |       |
| 7.53                    | -72.4            | V               | 3.0      | -16.1                   | 33.5   | 1.0        | -48.6 | -13.0 | -35.6 |       |
| High Channel (1905MHz)  |                  |                 |          |                         |        |            |       |       |       |       |
| 3.81                    | -70.3            | H               | 3.0      | -20.1                   | 34.4   | 1.0        | -53.5 | -13.0 | -40.5 |       |
| 5.72                    | -71.0            | H               | 3.0      | -17.2                   | 34.1   | 1.0        | -50.4 | -13.0 | -37.4 |       |
| 7.62                    | -72.7            | H               | 3.0      | -16.1                   | 33.4   | 1.0        | -48.5 | -13.0 | -35.5 |       |
| 3.81                    | -70.2            | V               | 3.0      | -20.0                   | 34.4   | 1.0        | -53.3 | -13.0 | -40.3 |       |
| 5.72                    | -71.4            | V               | 3.0      | -17.6                   | 34.1   | 1.0        | -50.7 | -13.0 | -37.7 |       |
| 7.62                    | -72.5            | V               | 3.0      | -16.1                   | 33.4   | 1.0        | -48.5 | -13.0 | -35.5 |       |

Rev. 05.21.15

High Frequency Substitution Measurement

UL Fremont Radiated Chamber

Company:

Project #:

Date: 06/15/18

Test Engineer: 19429

Configuration: EUT Only

Mode: LTE Band 25, 20MHz 16QAM

Test Equipment:

Substitution: Horn T59 Substitution, and 8T SMA Cable

Chamber

3m Chamber F

Pre-amplifier

3m Chamber F

Filter

Filter

Limit

ERP

| Frequency (GHz)         | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
|-------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Low Channel (1860MHz)   |                  |                 |          |                         |        |            |       |       |       |       |
| 3.72                    | -67.7            | H               | 3.0      | -17.9                   | 34.4   | 1.0        | -51.3 | -13.0 | -38.3 |       |
| 5.98                    | -70.9            | H               | 3.0      | -17.3                   | 34.1   | 1.0        | -50.4 | -13.0 | -37.4 |       |
| 7.44                    | -71.3            | H               | 3.0      | -14.9                   | 33.6   | 1.0        | -47.5 | -13.0 | -34.5 |       |
| 3.72                    | -69.6            | V               | 3.0      | -19.9                   | 34.4   | 1.0        | -53.3 | -13.0 | -40.3 |       |
| 5.98                    | -69.4            | V               | 3.0      | -15.7                   | 34.1   | 1.0        | -48.9 | -13.0 | -35.9 |       |
| 7.44                    | -71.0            | V               | 3.0      | -16.8                   | 33.6   | 1.0        | -49.4 | -13.0 | -36.4 |       |
| Mid Channel (1882.5MHz) |                  |                 |          |                         |        |            |       |       |       |       |
| 3.77                    | -69.2            | H               | 3.0      | -19.2                   | 34.4   | 1.0        | -52.6 | -13.0 | -39.6 |       |
| 5.98                    | -71.1            | H               | 3.0      | -17.5                   | 34.1   | 1.0        | -50.6 | -13.0 | -37.6 |       |
| 7.53                    | -72.2            | H               | 3.0      | -16.7                   | 33.9   | 1.0        | -48.2 | -13.0 | -35.2 |       |
| 3.77                    | -70.1            | V               | 3.0      | -20.0                   | 34.4   | 1.0        | -53.4 | -13.0 | -40.4 |       |
| 5.98                    | -70.8            | V               | 3.0      | -17.0                   | 34.1   | 1.0        | -50.1 | -13.0 | -37.1 |       |
| 7.53                    | -72.4            | V               | 3.0      | -16.1                   | 33.5   | 1.0        | -48.6 | -13.0 | -35.6 |       |
| High Channel (1905MHz)  |                  |                 |          |                         |        |            |       |       |       |       |
| 3.81                    | -70.0            | H               | 3.0      | -19.8                   | 34.4   | 1.0        | -52.2 | -13.0 | -39.2 |       |
| 5.72                    | -71.0            | H               | 3.0      | -17.3                   | 34.1   | 1.0        | -50.4 | -13.0 | -37.4 |       |
| 7.62                    | -72.9            | H               | 3.0      | -16.3                   | 33.4   | 1.0        | -48.7 | -13.0 | -35.7 |       |
| 3.81                    | -70.2            | V               | 3.0      | -20.0                   | 34.4   | 1.0        | -53.4 | -13.0 | -40.4 |       |
| 5.72                    | -72.2            | V               | 3.0      | -18.4                   | 34.1   | 1.0        | -51.5 | -13.0 | -38.5 |       |
| 7.62                    | -70.9            | V               | 3.0      | -16.6                   | 33.4   | 1.0        | -49.0 | -13.0 | -36.0 |       |

Rev. 05.21.15

LTE B25 20MHz QPSK

LTE B25 20MHz 16QAM

## 9.1.9. LTE BAND 26 (PART 90S)

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

06/15/18

19429

EUT Only

LTE Band 26 (90S), 10MHz QPSK

Test Equipment:

Substitution: Horn T59 Substitution, and 8T SMA Cable

Chamber

3m Chamber E

Pre-amplifier

3m Chamber E

Filter

Filter

Limit

EIRP

| Frequency (GHz)      | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
|----------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Mid Channel (819MHz) |                  |                 |          |                         |        |            |       |       |       |       |
| 1.94                 | -61.8            | H               | 3.0      | -19.4                   | 37.8   | 1.0        | -56.2 | -13.0 | -43.2 |       |
| 2.46                 | -64.2            | H               | 3.0      | -19.3                   | 38.4   | 1.0        | -56.7 | -13.0 | -43.7 |       |
| 3.28                 | -63.0            | H               | 3.0      | -14.1                   | 38.5   | 1.0        | -51.5 | -13.0 | -38.5 |       |
| 1.94                 | -62.5            | V               | 3.0      | -20.4                   | 37.8   | 1.0        | -57.2 | -13.0 | -44.2 |       |
| 2.46                 | -62.8            | V               | 3.0      | -17.7                   | 38.4   | 1.0        | -55.1 | -13.0 | -42.1 |       |
| 3.28                 | -63.3            | V               | 3.0      | -14.7                   | 38.5   | 1.0        | -52.2 | -13.0 | -39.2 |       |

Rev. 05.21.15

LTE B26 10MHz QPSK

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

06/15/18

19429

EUT Only

LTE Band 26 (90S), 10MHz 16QAM

Test Equipment:

Substitution: Horn T59 Substitution, and 8T SMA Cable

Chamber

3m Chamber E

Pre-amplifier

3m Chamber E

Filter

Filter

Limit

EIRP

| Frequency (GHz)      | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
|----------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Mid Channel (819MHz) |                  |                 |          |                         |        |            |       |       |       |       |
| 1.94                 | -62.5            | H               | 3.0      | -20.1                   | 37.8   | 1.0        | -56.9 | -13.0 | -43.9 |       |
| 2.46                 | -63.1            | H               | 3.0      | -18.2                   | 38.4   | 1.0        | -55.6 | -13.0 | -42.6 |       |
| 3.28                 | -61.4            | H               | 3.0      | -14.5                   | 38.5   | 1.0        | -52.0 | -13.0 | -39.0 |       |
| 1.94                 | -62.7            | V               | 3.0      | -20.7                   | 37.8   | 1.0        | -57.5 | -13.0 | -44.5 |       |
| 2.46                 | -62.9            | V               | 3.0      | -16.9                   | 38.4   | 1.0        | -54.3 | -13.0 | -41.3 |       |
| 3.28                 | -63.5            | V               | 3.0      | -14.9                   | 38.5   | 1.0        | -52.4 | -13.0 | -39.4 |       |

Rev. 05.21.15

LTE B26 10MHz 16QAM

## 9.1.10. LTE BAND 30

**High Frequency Substitution Measurement**  
UL Fremont Radiated Chamber

Company:  
Project #: 061618  
Date: 19429  
Test Engineer: EUT Only  
Configuration: LTE Band 30, 10MHz QPSK  
Mode:

**Test Equipment:**  
Substitution: Horn T59 Substitution, and 8T SMA Cable

Chamber  
3m Chamber E

Pre-amplifier  
3m Chamber E

Filter  
Filter

Limit  
ERP

| Frequency (GHz)             | SA reading (dBm) | Ant. Pol. (H/V) | Distance | ERP @ TX Ant End (dBm) | Preamp | Attenuator | ERP   | Limit | Delta | Notes |
|-----------------------------|------------------|-----------------|----------|------------------------|--------|------------|-------|-------|-------|-------|
| <b>Mid Channel (230MHz)</b> |                  |                 |          |                        |        |            |       |       |       |       |
| 4.62                        | -70.2            | H               | 3.0      | -16.4                  | 37.9   | 1.0        | -53.3 | -13.0 | -40.3 |       |
| 6.93                        | -73.1            | H               | 3.0      | -14.5                  | 36.5   | 1.0        | -49.9 | -13.0 | -36.9 |       |
| 9.24                        | -75.5            | H               | 3.0      | -14.4                  | 34.9   | 1.0        | -49.2 | -13.0 | -35.2 |       |
| 4.62                        | -68.1            | V               | 3.0      | -14.4                  | 37.9   | 1.0        | -51.3 | -13.0 | -38.3 |       |
| 6.93                        | -72.1            | V               | 3.0      | -12.6                  | 36.5   | 1.0        | -48.1 | -13.0 | -35.1 |       |
| 9.24                        | -74.1            | V               | 3.0      | -12.4                  | 34.9   | 1.0        | -46.2 | -13.0 | -33.2 |       |

LTE B30 10MHz QPSK

**High Frequency Substitution Measurement**  
UL Fremont Radiated Chamber

Company:  
Project #: 061618  
Date: 19429  
Test Engineer: EUT Only  
Configuration: LTE Band 30, 10MHz 16QAM  
Mode:

**Test Equipment:**  
Substitution: Horn T59 Substitution, and 8T SMA Cable

Chamber  
3m Chamber E

Pre-amplifier  
3m Chamber E

Filter  
Filter

Limit  
ERP

| Frequency (GHz)             | SA reading (dBm) | Ant. Pol. (H/V) | Distance | ERP @ TX Ant End (dBm) | Preamp | Attenuator | ERP   | Limit | Delta | Notes |
|-----------------------------|------------------|-----------------|----------|------------------------|--------|------------|-------|-------|-------|-------|
| <b>Mid Channel (230MHz)</b> |                  |                 |          |                        |        |            |       |       |       |       |
| 4.62                        | -69.6            | H               | 3.0      | -15.9                  | 37.9   | 1.0        | -52.8 | -13.0 | -39.8 |       |
| 6.93                        | -71.8            | H               | 3.0      | -15.1                  | 36.5   | 1.0        | -50.6 | -13.0 | -37.6 |       |
| 9.24                        | -75.4            | H               | 3.0      | -13.9                  | 34.9   | 1.0        | -47.7 | -13.0 | -34.7 |       |
| 4.62                        | -68.1            | V               | 3.0      | -14.4                  | 37.9   | 1.0        | -52.3 | -13.0 | -39.3 |       |
| 6.93                        | -72.7            | V               | 3.0      | -13.2                  | 36.5   | 1.0        | -46.7 | -13.0 | -33.7 |       |
| 9.24                        | -76.2            | V               | 3.0      | -14.4                  | 34.9   | 1.0        | -48.3 | -13.0 | -35.3 |       |

LTE B30 10MHz 16QAM

## 9.1.11. LTE BAND 41

**High Frequency Substitution Measurement**  
UL Fremont Radiated Chamber

Company:  
Project #: 061618  
Date: 19429  
Test Engineer: EUT Only  
Configuration: LTE Band 41, 20MHz QPSK  
Mode:

**Test Equipment:**  
Substitution: Horn T59 Substitution, and 8T SMA Cable

Chamber  
3m Chamber E

Pre-amplifier  
3m Chamber E

Filter  
Filter

Limit  
LTE B41

| Frequency (GHz)              | SA reading (dBm) | Ant. Pol. (H/V) | Distance | ERP @ TX Ant End (dBm) | Preamp | Attenuator | ERP   | Limit | Delta | Notes |
|------------------------------|------------------|-----------------|----------|------------------------|--------|------------|-------|-------|-------|-------|
| <b>Low Channel (250MHz)</b>  |                  |                 |          |                        |        |            |       |       |       |       |
| 5.01                         | -61.9            | H               | 3.0      | -9.0                   | 38.7   | 1.0        | -46.7 | -25.0 | -21.7 |       |
| 7.52                         | -63.7            | H               | 3.0      | -5.9                   | 37.7   | 1.0        | -42.6 | -25.0 | -17.6 |       |
| 10.02                        | -65.6            | H               | 3.0      | -4.8                   | 36.1   | 1.0        | -39.9 | -25.0 | -14.9 |       |
| 5.01                         | -60.6            | V               | 3.0      | -8.0                   | 38.7   | 1.0        | -45.7 | -25.0 | -20.7 |       |
| 7.52                         | -64.5            | V               | 3.0      | -6.4                   | 37.7   | 1.0        | -43.1 | -25.0 | -18.1 |       |
| 10.02                        | -66.2            | V               | 3.0      | -4.4                   | 36.1   | 1.0        | -39.5 | -25.0 | -14.5 |       |
| <b>Mid Channel (250MHz)</b>  |                  |                 |          |                        |        |            |       |       |       |       |
| 5.19                         | -62.6            | H               | 3.0      | -8.7                   | 38.7   | 1.0        | -46.4 | -25.0 | -21.4 |       |
| 7.78                         | -63.5            | H               | 3.0      | -5.4                   | 37.6   | 1.0        | -42.0 | -25.0 | -17.0 |       |
| 10.37                        | -64.2            | H               | 3.0      | -3.1                   | 36.4   | 1.0        | -38.5 | -25.0 | -13.5 |       |
| 5.19                         | -62.7            | V               | 3.0      | -9.3                   | 38.7   | 1.0        | -46.8 | -25.0 | -21.8 |       |
| 7.78                         | -63.5            | V               | 3.0      | -5.6                   | 37.6   | 1.0        | -42.2 | -25.0 | -17.2 |       |
| 10.37                        | -64.7            | V               | 3.0      | -3.6                   | 36.4   | 1.0        | -38.9 | -25.0 | -13.9 |       |
| <b>High Channel (260MHz)</b> |                  |                 |          |                        |        |            |       |       |       |       |
| 5.36                         | -62.4            | H               | 3.0      | -8.8                   | 38.6   | 1.0        | -46.4 | -25.0 | -21.4 |       |
| 8.04                         | -63.4            | H               | 3.0      | -6.0                   | 37.4   | 1.0        | -41.4 | -25.0 | -16.4 |       |
| 10.72                        | -65.1            | H               | 3.0      | -3.7                   | 36.6   | 1.0        | -39.3 | -25.0 | -14.3 |       |
| 5.36                         | -62.7            | V               | 3.0      | -8.4                   | 38.6   | 1.0        | -47.0 | -25.0 | -22.0 |       |
| 8.04                         | -63.5            | V               | 3.0      | -6.2                   | 37.4   | 1.0        | -41.6 | -25.0 | -16.6 |       |
| 10.72                        | -65.2            | V               | 3.0      | -3.6                   | 36.6   | 1.0        | -39.2 | -25.0 | -14.2 |       |

LTE B41 20MHz QPSK

**High Frequency Substitution Measurement**  
UL Fremont Radiated Chamber

Company:  
Project #: 061618  
Date: 19429  
Test Engineer: EUT Only  
Configuration: LTE Band 41, 20MHz 16QAM  
Mode:

**Test Equipment:**  
Substitution: Horn T59 Substitution, and 8T SMA Cable

Chamber  
3m Chamber E

Pre-amplifier  
3m Chamber E

Filter  
Filter

Limit  
LTE B41

| Frequency (GHz)              | SA reading (dBm) | Ant. Pol. (H/V) | Distance | ERP @ TX Ant End (dBm) | Preamp | Attenuator | ERP   | Limit | Delta | Notes |
|------------------------------|------------------|-----------------|----------|------------------------|--------|------------|-------|-------|-------|-------|
| <b>Low Channel (250MHz)</b>  |                  |                 |          |                        |        |            |       |       |       |       |
| 5.01                         | -61.9            | H               | 3.0      | -9.0                   | 38.7   | 1.0        | -46.7 | -25.0 | -21.7 |       |
| 7.52                         | -64.1            | H               | 3.0      | -6.3                   | 37.7   | 1.0        | -43.0 | -25.0 | -18.0 |       |
| 10.02                        | -64.5            | H               | 3.0      | -3.7                   | 36.1   | 1.0        | -38.0 | -25.0 | -13.0 |       |
| 5.01                         | -63.2            | V               | 3.0      | -8.5                   | 38.7   | 1.0        | -46.2 | -25.0 | -21.2 |       |
| 7.52                         | -63.5            | V               | 3.0      | -5.9                   | 37.7   | 1.0        | -42.7 | -25.0 | -17.7 |       |
| 10.02                        | -66.6            | V               | 3.0      | -4.8                   | 36.1   | 1.0        | -39.9 | -25.0 | -14.9 |       |
| <b>Mid Channel (250MHz)</b>  |                  |                 |          |                        |        |            |       |       |       |       |
| 5.19                         | -62.2            | H               | 3.0      | -8.9                   | 38.7   | 1.0        | -46.6 | -25.0 | -21.6 |       |
| 7.78                         | -62.9            | H               | 3.0      | -4.8                   | 37.6   | 1.0        | -41.4 | -25.0 | -16.4 |       |
| 10.37                        | -64.7            | H               | 3.0      | -3.6                   | 36.4   | 1.0        | -38.0 | -25.0 | -13.0 |       |
| 5.19                         | -61.7            | V               | 3.0      | -8.8                   | 38.7   | 1.0        | -46.5 | -25.0 | -21.5 |       |
| 7.78                         | -63.4            | V               | 3.0      | -6.4                   | 37.6   | 1.0        | -42.0 | -25.0 | -17.0 |       |
| 10.37                        | -64.7            | V               | 3.0      | -3.5                   | 36.4   | 1.0        | -38.9 | -25.0 | -13.9 |       |
| <b>High Channel (260MHz)</b> |                  |                 |          |                        |        |            |       |       |       |       |
| 5.36                         | -63.3            | H               | 3.0      | -9.7                   | 38.6   | 1.0        | -47.3 | -25.0 | -22.3 |       |
| 8.04                         | -62.6            | H               | 3.0      | -4.1                   | 37.4   | 1.0        | -40.9 | -25.0 | -15.9 |       |
| 10.72                        | -65.0            | H               | 3.0      | -3.6                   | 36.6   | 1.0        | -39.2 | -25.0 | -14.2 |       |
| 5.36                         | -63.0            | V               | 3.0      | -9.7                   | 38.6   | 1.0        | -47.4 | -25.0 | -22.4 |       |
| 8.04                         | -63.2            | V               | 3.0      | -4.9                   | 37.4   | 1.0        | -41.4 | -25.0 | -16.4 |       |
| 10.72                        | -64.5            | V               | 3.0      | -2.9                   | 36.6   | 1.0        | -38.5 | -25.0 | -13.5 |       |

LTE B41 20MHz 16QAM



## 9.2. FIELD STRENGTH OF SPURIOUS RADIATION, ANT 2

### 9.2.1. LTE BAND 2

High Frequency Substitution Measurement

UL Fremont Radiated Chamber

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

06/25/18

19429

EUT Only

LTE Band 2, 20MHz QPSK

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber

3m Chamber C

Pre-amplifier

3m Chamber C

Filter

Filter

Limit

EIRP

| Frequency (GHz)       | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
|-----------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Low Channel (180MHz)  |                  |                 |          |                         |        |            |       |       |       |       |
| 3.72                  | -63.4            | H               | 3.0      | -13.4                   | 34.1   | 1.0        | -46.5 | -13.0 | -33.5 |       |
| 5.98                  | -65.5            | H               | 3.0      | -11.5                   | 33.3   | 1.0        | -43.8 | -13.0 | -30.8 |       |
| 7.44                  | -65.5            | H               | 3.0      | -8.2                    | 33.1   | 1.0        | -40.2 | -13.0 | -27.2 |       |
| 3.72                  | -65.4            | V               | 3.0      | -15.1                   | 34.1   | 1.0        | -48.2 | -13.0 | -35.2 |       |
| 5.98                  | -65.9            | V               | 3.0      | -12.0                   | 33.3   | 1.0        | -44.3 | -13.0 | -31.3 |       |
| 7.44                  | -65.5            | V               | 3.0      | -8.1                    | 33.1   | 1.0        | -40.2 | -13.0 | -27.2 |       |
| Mid Channel (180MHz)  |                  |                 |          |                         |        |            |       |       |       |       |
| 3.76                  | -63.8            | H               | 3.0      | -13.7                   | 34.1   | 1.0        | -46.8 | -13.0 | -33.8 |       |
| 5.64                  | -65.2            | H               | 3.0      | -11.0                   | 33.3   | 1.0        | -43.3 | -13.0 | -30.3 |       |
| 7.52                  | -64.7            | H               | 3.0      | -7.1                    | 33.9   | 1.0        | -39.1 | -13.0 | -26.1 |       |
| 3.76                  | -63.5            | V               | 3.0      | -13.0                   | 34.1   | 1.0        | -46.1 | -13.0 | -33.1 |       |
| 5.64                  | -65.6            | V               | 3.0      | -11.5                   | 33.3   | 1.0        | -43.8 | -13.0 | -30.8 |       |
| 7.52                  | -67.8            | V               | 3.0      | -10.2                   | 33.0   | 1.0        | -42.2 | -13.0 | -29.2 |       |
| High Channel (180MHz) |                  |                 |          |                         |        |            |       |       |       |       |
| 3.80                  | -63.4            | H               | 3.0      | -13.2                   | 34.0   | 1.0        | -46.2 | -13.0 | -33.2 |       |
| 5.70                  | -65.1            | H               | 3.0      | -10.8                   | 33.3   | 1.0        | -43.1 | -13.0 | -30.1 |       |
| 7.60                  | -65.9            | H               | 3.0      | -8.7                    | 33.0   | 1.0        | -40.2 | -13.0 | -27.2 |       |
| 3.80                  | -63.1            | V               | 3.0      | -12.5                   | 34.0   | 1.0        | -45.6 | -13.0 | -32.6 |       |
| 5.70                  | -65.1            | V               | 3.0      | -10.8                   | 33.3   | 1.0        | -43.1 | -13.0 | -30.1 |       |
| 7.60                  | -66.5            | V               | 3.0      | -8.8                    | 33.0   | 1.0        | -40.5 | -13.0 | -27.5 |       |

Rev. 05.21.15

High Frequency Substitution Measurement

UL Fremont Radiated Chamber

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

06/25/18

19429

EUT Only

LTE Band 2, 20MHz 16QAM

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber

3m Chamber C

Pre-amplifier

3m Chamber C

Filter

Filter

Limit

EIRP

| Frequency (GHz)       | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
|-----------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Low Channel (180MHz)  |                  |                 |          |                         |        |            |       |       |       |       |
| 3.72                  | -63.7            | H               | 3.0      | -13.7                   | 34.1   | 1.0        | -46.8 | -13.0 | -33.8 |       |
| 5.98                  | -66.0            | H               | 3.0      | -12.0                   | 33.3   | 1.0        | -44.3 | -13.0 | -31.3 |       |
| 7.44                  | -65.7            | H               | 3.0      | -8.8                    | 33.1   | 1.0        | -40.8 | -13.0 | -27.8 |       |
| 3.72                  | -64.1            | V               | 3.0      | -13.7                   | 34.1   | 1.0        | -46.9 | -13.0 | -33.9 |       |
| 5.98                  | -65.2            | V               | 3.0      | -11.2                   | 33.3   | 1.0        | -43.5 | -13.0 | -30.5 |       |
| 7.44                  | -65.9            | V               | 3.0      | -8.4                    | 33.1   | 1.0        | -40.4 | -13.0 | -27.4 |       |
| Mid Channel (180MHz)  |                  |                 |          |                         |        |            |       |       |       |       |
| 3.76                  | -63.1            | H               | 3.0      | -13.0                   | 34.1   | 1.0        | -46.1 | -13.0 | -33.1 |       |
| 5.64                  | -66.1            | H               | 3.0      | -11.9                   | 33.3   | 1.0        | -44.2 | -13.0 | -31.2 |       |
| 7.52                  | -66.0            | H               | 3.0      | -7.4                    | 33.9   | 1.0        | -40.5 | -13.0 | -27.5 |       |
| 3.76                  | -63.5            | V               | 3.0      | -12.8                   | 34.1   | 1.0        | -45.9 | -13.0 | -32.9 |       |
| 5.64                  | -66.4            | V               | 3.0      | -10.1                   | 33.3   | 1.0        | -43.4 | -13.0 | -30.4 |       |
| 7.52                  | -67.2            | V               | 3.0      | -7.8                    | 33.0   | 1.0        | -40.0 | -13.0 | -27.0 |       |
| High Channel (180MHz) |                  |                 |          |                         |        |            |       |       |       |       |
| 3.80                  | -63.5            | H               | 3.0      | -13.4                   | 34.0   | 1.0        | -46.4 | -13.0 | -33.4 |       |
| 5.70                  | -65.5            | H               | 3.0      | -11.2                   | 33.3   | 1.0        | -43.5 | -13.0 | -30.5 |       |
| 7.60                  | -66.1            | H               | 3.0      | -8.5                    | 33.0   | 1.0        | -40.5 | -13.0 | -27.5 |       |
| 3.80                  | -63.9            | V               | 3.0      | -13.4                   | 34.0   | 1.0        | -46.4 | -13.0 | -33.4 |       |
| 5.70                  | -66.2            | V               | 3.0      | -11.0                   | 33.3   | 1.0        | -44.3 | -13.0 | -31.3 |       |
| 7.60                  | -66.9            | V               | 3.0      | -8.2                    | 33.0   | 1.0        | -41.2 | -13.0 | -28.2 |       |

Rev. 05.21.15

LTE B2 20MHz QPSK

LTE B2 20MHz 16QAM

High Frequency Substitution Measurement

UL Fremont Radiated Chamber

Company:

Project #:

Date: 06/25/18

Test Engineer: 19429

Configuration: EUT Only

Mode: LTE Band 2, 20MHz 16QAM

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber

Pre-amplifier

Filter

Limit

3m Chamber C

3m Chamber C

Filter

EIRP

| Frequency (GHz)       | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
|-----------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Low Channel (180MHz)  |                  |                 |          |                         |        |            |       |       |       |       |
| 3.72                  | -63.7            | H               | 3.0      | -13.7                   | 34.1   | 1.0        | -46.8 | -13.0 | -33.8 |       |
| 5.98                  | -66.0            | H               | 3.0      | -12.0                   | 33.3   | 1.0        | -44.3 | -13.0 | -31.3 |       |
| 7.44                  | -65.3            | H               | 3.0      | -8.4                    | 33.0   | 1.0        | -40.5 | -13.0 | -27.5 |       |
| 3.72                  | -64.1            | V               | 3.0      | -13.7                   | 34.1   | 1.0        | -46.9 | -13.0 | -33.9 |       |
| 5.98                  | -65.2            | V               | 3.0      | -11.2                   | 33.3   | 1.0        | -43.5 | -13.0 | -30.5 |       |
| 7.44                  | -65.8            | V               | 3.0      | -8.4                    | 33.1   | 1.0        | -40.4 | -13.0 | -27.4 |       |
| Mid Channel (180MHz)  |                  |                 |          |                         |        |            |       |       |       |       |
| 3.76                  | -63.1            | H               | 3.0      | -13.0                   | 34.1   | 1.0        | -46.1 | -13.0 | -33.1 |       |
| 5.64                  | -66.1            | H               | 3.0      | -11.9                   | 33.3   | 1.0        | -44.2 | -13.0 | -31.2 |       |
| 7.52                  | -66.0            | H               | 3.0      | -8.4                    | 33.0   | 1.0        | -40.5 | -13.0 | -27.5 |       |
| 3.76                  | -63.3            | V               | 3.0      | -12.8                   | 34.1   | 1.0        | -45.9 | -13.0 | -32.9 |       |
| 5.64                  | -64.2            | V               | 3.0      | -10.1                   | 33.3   | 1.0        | -42.4 | -13.0 | -29.4 |       |
| 7.52                  | -65.5            | V               | 3.0      | -7.9                    | 33.0   | 1.0        | -40.0 | -13.0 | -27.0 |       |
| High Channel (180MHz) |                  |                 |          |                         |        |            |       |       |       |       |
| 3.80                  | -63.6            | H               | 3.0      | -13.4                   | 34.0   | 1.0        | -46.4 | -13.0 | -33.4 |       |
| 5.70                  | -65.5            | H               | 3.0      | -11.2                   | 33.3   | 1.0        | -43.5 | -13.0 | -30.5 |       |
| 7.60                  | -66.1            | H               | 3.0      | -8.5                    | 33.0   | 1.0        | -40.5 | -13.0 | -27.5 |       |
| 3.80                  | -63.9            | V               | 3.0      | -13.4                   | 34.0   | 1.0        | -46.4 | -13.0 | -33.4 |       |
| 5.70                  | -66.2            | V               | 3.0      | -12.0                   | 33.3   | 1.0        | -44.3 | -13.0 | -31.3 |       |
| 7.60                  | -66.9            | V               | 3.0      | -9.2                    | 33.0   | 1.0        | -41.2 | -13.0 | -28.2 |       |

Rev. 05.21.15

LTE B2 20MHz 16QAM

### 9.2.2. LTE BAND 5

High Frequency Substitution Measurement

UL Fremont Radiated Chamber

Company:

Project #:

Date: 06/25/18

Test Engineer: 19429

Configuration: EUT Only

Mode: LTE Band 5, 10MHz QPSK

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber

3m Chamber C

Pre-amplifier

3m Chamber C

Filter

Filter

Limit

EIRP

| Frequency (GHz)      | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
|----------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Low Channel (10MHz)  |                  |                 |          |                         |        |            |       |       |       |       |
| 1.66                 | -68.7            | H               | 3.0      | -24.9                   | 36.5   | 1.0        | -60.4 | -13.0 | -47.4 |       |
| 2.49                 | -66.2            | H               | 3.0      | -20.3                   | 35.2   | 1.0        | -54.5 | -13.0 | -41.5 |       |
| 3.32                 | -65.9            | H               | 3.0      | -18.0                   | 34.6   | 1.0        | -51.6 | -13.0 | -38.6 |       |
| 1.66                 | -67.3            | V               | 3.0      | -24.6                   | 36.5   | 1.0        | -60.1 | -13.0 | -47.1 |       |
| 2.49                 | -68.7            | V               | 3.0      | -20.9                   | 35.2   | 1.0        | -55.0 | -13.0 | -42.0 |       |
| 3.32                 | -67.5            | V               | 3.0      | -18.0                   | 34.6   | 1.0        | -51.6 | -13.0 | -38.6 |       |
| Mid Channel (10MHz)  |                  |                 |          |                         |        |            |       |       |       |       |
| 1.67                 | -68.5            | H               | 3.0      | -24.6                   | 36.5   | 1.0        | -60.0 | -13.0 | -47.0 |       |
| 2.51                 | -65.9            | H               | 3.0      | -20.0                   | 35.1   | 1.0        | -54.2 | -13.0 | -41.2 |       |
| 3.35                 | -66.6            | H               | 3.0      | -17.4                   | 34.6   | 1.0        | -51.2 | -13.0 | -38.2 |       |
| 1.67                 | -66.1            | V               | 3.0      | -21.3                   | 36.5   | 1.0        | -58.8 | -13.0 | -45.8 |       |
| 2.51                 | -66.2            | V               | 3.0      | -20.2                   | 35.1   | 1.0        | -54.4 | -13.0 | -41.4 |       |
| 3.35                 | -66.5            | V               | 3.0      | -16.0                   | 34.6   | 1.0        | -50.4 | -13.0 | -37.4 |       |
| High Channel (10MHz) |                  |                 |          |                         |        |            |       |       |       |       |
| 1.69                 | -67.8            | H               | 3.0      | -24.9                   | 36.4   | 1.0        | -60.3 | -13.0 | -47.3 |       |
| 2.53                 | -65.1            | H               | 3.0      | -19.1                   | 35.1   | 1.0        | -53.3 | -13.0 | -40.3 |       |
| 3.38                 | -66.7            | H               | 3.0      | -17.7                   | 34.5   | 1.0        | -51.2 | -13.0 | -38.2 |       |
| 1.69                 | -67.1            | V               | 3.0      | -24.1                   | 36.4   | 1.0        | -59.6 | -13.0 | -46.6 |       |
| 2.53                 | -64.5            | V               | 3.0      | -18.4                   | 35.1   | 1.0        | -54.5 | -13.0 | -41.5 |       |
| 3.38                 | -67.8            | V               | 3.0      | -17.4                   | 34.5   | 1.0        | -50.9 | -13.0 | -37.9 |       |

Rev. 05.21.15

High Frequency Substitution Measurement

UL Fremont Radiated Chamber

Company:

Project #:

Date: 06/25/18

Test Engineer: 19429

Configuration: EUT Only

Mode: LTE Band 5, 10MHz 16QAM

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber

3m Chamber C

Pre-amplifier

3m Chamber C

Filter

Filter

Limit

EIRP

| Frequency (GHz)      | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
|----------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Low Channel (10MHz)  |                  |                 |          |                         |        |            |       |       |       |       |
| 1.66                 | -66.1            | H               | 3.0      | -24.3                   | 36.5   | 1.0        | -59.7 | -13.0 | -46.7 |       |
| 2.49                 | -65.5            | H               | 3.0      | -19.7                   | 35.2   | 1.0        | -53.9 | -13.0 | -40.9 |       |
| 3.32                 | -65.6            | H               | 3.0      | -18.7                   | 34.6   | 1.0        | -50.3 | -13.0 | -37.3 |       |
| 1.66                 | -66.1            | V               | 3.0      | -22.4                   | 36.5   | 1.0        | -58.9 | -13.0 | -45.9 |       |
| 2.49                 | -66.6            | V               | 3.0      | -20.8                   | 35.2   | 1.0        | -54.9 | -13.0 | -41.9 |       |
| 3.32                 | -66.5            | V               | 3.0      | -17.9                   | 34.6   | 1.0        | -50.6 | -13.0 | -37.6 |       |
| Mid Channel (10MHz)  |                  |                 |          |                         |        |            |       |       |       |       |
| 1.67                 | -67.5            | H               | 3.0      | -25.5                   | 36.5   | 1.0        | -61.0 | -13.0 | -48.0 |       |
| 2.51                 | -67.3            | H               | 3.0      | -21.4                   | 35.1   | 1.0        | -55.6 | -13.0 | -42.6 |       |
| 3.35                 | -66.2            | H               | 3.0      | -17.3                   | 34.6   | 1.0        | -50.8 | -13.0 | -37.8 |       |
| 1.67                 | -65.8            | V               | 3.0      | -21.0                   | 36.5   | 1.0        | -58.5 | -13.0 | -45.5 |       |
| 2.51                 | -65.6            | V               | 3.0      | -19.7                   | 35.1   | 1.0        | -53.8 | -13.0 | -40.8 |       |
| 3.35                 | -66.4            | V               | 3.0      | -16.8                   | 34.6   | 1.0        | -50.3 | -13.0 | -37.2 |       |
| High Channel (10MHz) |                  |                 |          |                         |        |            |       |       |       |       |
| 1.69                 | -66.1            | H               | 3.0      | -24.8                   | 36.4   | 1.0        | -59.5 | -13.0 | -46.5 |       |
| 2.53                 | -66.0            | H               | 3.0      | -20.0                   | 35.1   | 1.0        | -54.2 | -13.0 | -41.2 |       |
| 3.38                 | -65.4            | H               | 3.0      | -16.4                   | 34.5   | 1.0        | -49.5 | -13.0 | -36.5 |       |
| 1.69                 | -67.2            | V               | 3.0      | -24.2                   | 36.4   | 1.0        | -59.7 | -13.0 | -46.7 |       |
| 2.53                 | -66.9            | V               | 3.0      | -20.8                   | 35.1   | 1.0        | -55.0 | -13.0 | -42.0 |       |
| 3.38                 | -66.0            | V               | 3.0      | -16.3                   | 34.5   | 1.0        | -49.8 | -13.0 | -36.8 |       |

Rev. 05.21.15

LTE B5 10MHz QPSK

LTE B5 10MHz 16QAM

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

06/25/18

19429

EUT Only

LTE Band 5, 10MHz 16QAM

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber

3m Chamber C

Pre-amplifier

3m Chamber C

Filter

Filter

Limit

EIRP

| Frequency (GHz)      | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
|----------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Low Channel (10MHz)  |                  |                 |          |                         |        |            |       |       |       |       |
| 1.66                 | -66.1            | H               | 3.0      | -24.3                   | 36.5   | 1.0        | -59.7 | -13.0 | -46.7 |       |
| 2.49                 | -65.5            | H               | 3.0      | -19.7                   | 35.2   | 1.0        | -53.9 | -13.0 | -40.9 |       |
| 3.32                 | -65.6            | H               | 3.0      | -16.7                   | 34.6   | 1.0        | -50.3 | -13.0 | -37.3 |       |
| 1.66                 | -66.1            | V               | 3.0      | -23.4                   | 36.5   | 1.0        | -58.9 | -13.0 | -45.9 |       |
| 2.49                 | -66.6            | V               | 3.0      | -20.8                   | 35.2   | 1.0        | -54.9 | -13.0 | -41.9 |       |
| 3.32                 | -66.5            | V               | 3.0      | -17.0                   | 34.6   | 1.0        | -50.6 | -13.0 | -37.6 |       |
| Mid Channel (10MHz)  |                  |                 |          |                         |        |            |       |       |       |       |
| 1.67                 | -67.5            | H               | 3.0      | -25.5                   | 36.5   | 1.0        | -61.0 | -13.0 | -48.0 |       |
| 2.51                 | -67.3            | H               | 3.0      | -21.4                   | 35.1   | 1.0        | -56.6 | -13.0 | -43.6 |       |
| 3.35                 | -66.2            | H               | 3.0      | -17.3                   | 34.6   | 1.0        | -50.8 | -13.0 | -37.8 |       |
| 1.67                 | -65.8            | V               | 3.0      | -23.0                   | 36.5   | 1.0        | -58.5 | -13.0 | -45.5 |       |
| 2.51                 | -65.6            | V               | 3.0      | -19.7                   | 35.1   | 1.0        | -53.8 | -13.0 | -40.8 |       |
| 3.35                 | -66.4            | V               | 3.0      | -16.8                   | 34.6   | 1.0        | -50.1 | -13.0 | -37.1 |       |
| High Channel (10MHz) |                  |                 |          |                         |        |            |       |       |       |       |
| 1.69                 | -68.1            | H               | 3.0      | -24.8                   | 36.4   | 1.0        | -59.5 | -13.0 | -46.5 |       |
| 2.53                 | -66.8            | H               | 3.0      | -20.8                   | 35.1   | 1.0        | -54.2 | -13.0 | -41.2 |       |
| 3.38                 | -65.4            | H               | 3.0      | -16.4                   | 34.5   | 1.0        | -49.9 | -13.0 | -36.9 |       |
| 1.69                 | -67.2            | V               | 3.0      | -24.2                   | 36.4   | 1.0        | -59.7 | -13.0 | -46.7 |       |
| 2.53                 | -66.9            | V               | 3.0      | -20.8                   | 35.1   | 1.0        | -55.0 | -13.0 | -42.0 |       |
| 3.38                 | -66.8            | V               | 3.0      | -16.3                   | 34.5   | 1.0        | -49.8 | -13.0 | -36.8 |       |

Rev. 05.21.15

LTE B5 10MHz 16QAM

### 9.2.3. LTE BAND 7

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                      |                     |                               |          |                               |        |                 |       |       |       |       |
|-----------------------------------------------------------------------------------------------------------------------------|---------------------|-------------------------------|----------|-------------------------------|--------|-----------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/25/18<br>Test Engineer: USA25<br>Configuration: EUT Only<br>Mode: LTE Band 7, 20MHz QPSK |                     |                               |          |                               |        |                 |       |       |       |       |
| Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable                                                   |                     |                               |          |                               |        |                 |       |       |       |       |
| Chamber<br>3m Chamber C                                                                                                     |                     | Pre-amplifier<br>3m Chamber C |          | Filter<br>Filter              |        | Limit<br>LTE B7 |       |       |       |       |
| Frequency<br>(GHz)                                                                                                          | SA reading<br>(dBm) | Ant. Pol.<br>(H/V)            | Distance | EIRP @ TX<br>Ant End<br>(dBm) | Preamp | Attenuator      | EIRP  | Limit | Delta | Notes |
| Low Channel (2510MHz)                                                                                                       |                     |                               |          |                               |        |                 |       |       |       |       |
| 5.92                                                                                                                        | -65.3               | H                             | 3.0      | -32.4                         | 33.4   | 1.0             | -44.8 | -25.0 | -19.8 |       |
| 7.53                                                                                                                        | -66.0               | H                             | 3.0      | -8.4                          | 33.0   | 1.0             | -40.4 | -25.0 | -15.4 |       |
| 10.04                                                                                                                       | -65.3               | H                             | 3.0      | -4.5                          | 32.6   | 1.0             | -36.2 | -25.0 | -11.2 |       |
| 5.92                                                                                                                        | -65.3               | V                             | 3.0      | -32.4                         | 33.4   | 1.0             | -44.8 | -25.0 | -19.8 |       |
| 7.53                                                                                                                        | -64.9               | V                             | 3.0      | -7.3                          | 33.0   | 1.0             | -39.4 | -25.0 | -14.4 |       |
| 10.04                                                                                                                       | -65.2               | V                             | 3.0      | -4.3                          | 32.6   | 1.0             | -35.7 | -25.0 | -10.7 |       |
| Mid Channel (2530MHz)                                                                                                       |                     |                               |          |                               |        |                 |       |       |       |       |
| 5.97                                                                                                                        | -65.1               | H                             | 3.0      | -32.3                         | 33.4   | 1.0             | -44.5 | -25.0 | -19.5 |       |
| 7.61                                                                                                                        | -65.1               | H                             | 3.0      | -7.4                          | 33.0   | 1.0             | -39.4 | -25.0 | -14.4 |       |
| 10.14                                                                                                                       | -65.2               | H                             | 3.0      | -4.3                          | 32.6   | 1.0             | -35.9 | -25.0 | -10.9 |       |
| 5.97                                                                                                                        | -65.6               | V                             | 3.0      | -32.0                         | 33.4   | 1.0             | -44.4 | -25.0 | -19.4 |       |
| 7.61                                                                                                                        | -65.6               | V                             | 3.0      | -7.9                          | 33.0   | 1.0             | -39.0 | -25.0 | -14.9 |       |
| 10.14                                                                                                                       | -65.4               | V                             | 3.0      | -4.2                          | 32.6   | 1.0             | -35.9 | -25.0 | -10.9 |       |
| High Channel (2560MHz)                                                                                                      |                     |                               |          |                               |        |                 |       |       |       |       |
| 5.12                                                                                                                        | -64.9               | H                             | 3.0      | -31.6                         | 33.4   | 1.0             | -44.2 | -25.0 | -19.2 |       |
| 7.68                                                                                                                        | -66.4               | H                             | 3.0      | -8.7                          | 33.0   | 1.0             | -40.7 | -25.0 | -15.7 |       |
| 10.24                                                                                                                       | -66.7               | H                             | 3.0      | -5.7                          | 32.5   | 1.0             | -37.2 | -25.0 | -12.2 |       |
| 5.12                                                                                                                        | -65.9               | V                             | 3.0      | -32.9                         | 33.4   | 1.0             | -45.2 | -25.0 | -20.2 |       |
| 7.68                                                                                                                        | -66.6               | V                             | 3.0      | -8.7                          | 33.0   | 1.0             | -40.8 | -25.0 | -15.8 |       |
| 10.24                                                                                                                       | -66.7               | V                             | 3.0      | -5.5                          | 32.5   | 1.0             | -37.0 | -25.0 | -12.0 |       |
| Rev 05.21.15                                                                                                                |                     |                               |          |                               |        |                 |       |       |       |       |
| LTE B7 20MHz QPSK                                                                                                           |                     |                               |          |                               |        |                 |       |       |       |       |

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                       |                     |                               |          |                               |        |                 |       |       |       |       |
|------------------------------------------------------------------------------------------------------------------------------|---------------------|-------------------------------|----------|-------------------------------|--------|-----------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/25/18<br>Test Engineer: USA25<br>Configuration: EUT Only<br>Mode: LTE Band 7, 20MHz 16QAM |                     |                               |          |                               |        |                 |       |       |       |       |
| Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable                                                    |                     |                               |          |                               |        |                 |       |       |       |       |
| Chamber<br>3m Chamber C                                                                                                      |                     | Pre-amplifier<br>3m Chamber C |          | Filter<br>Filter              |        | Limit<br>LTE B7 |       |       |       |       |
| Frequency<br>(GHz)                                                                                                           | SA reading<br>(dBm) | Ant. Pol.<br>(H/V)            | Distance | EIRP @ TX<br>Ant End<br>(dBm) | Preamp | Attenuator      | EIRP  | Limit | Delta | Notes |
| Low Channel (2510MHz)                                                                                                        |                     |                               |          |                               |        |                 |       |       |       |       |
| 5.92                                                                                                                         | -65.4               | H                             | 3.0      | -31.5                         | 33.4   | 1.0             | -44.0 | -25.0 | -19.0 |       |
| 7.53                                                                                                                         | -65.6               | H                             | 3.0      | -8.0                          | 33.0   | 1.0             | -40.0 | -25.0 | -15.0 |       |
| 10.04                                                                                                                        | -66.3               | H                             | 3.0      | -5.5                          | 32.6   | 1.0             | -37.1 | -25.0 | -12.1 |       |
| 5.92                                                                                                                         | -64.8               | V                             | 3.0      | -31.9                         | 33.4   | 1.0             | -44.3 | -25.0 | -19.3 |       |
| 7.53                                                                                                                         | -65.7               | V                             | 3.0      | -8.1                          | 33.0   | 1.0             | -40.1 | -25.0 | -15.1 |       |
| 10.04                                                                                                                        | -66.1               | V                             | 3.0      | -5.0                          | 32.6   | 1.0             | -36.7 | -25.0 | -11.7 |       |
| Mid Channel (2530MHz)                                                                                                        |                     |                               |          |                               |        |                 |       |       |       |       |
| 5.97                                                                                                                         | -65.0               | H                             | 3.0      | -33.0                         | 33.4   | 1.0             | -46.4 | -25.0 | -20.4 |       |
| 7.61                                                                                                                         | -65.9               | H                             | 3.0      | -8.2                          | 33.0   | 1.0             | -40.3 | -25.0 | -15.3 |       |
| 10.14                                                                                                                        | -66.4               | H                             | 3.0      | -5.3                          | 32.6   | 1.0             | -37.0 | -25.0 | -12.0 |       |
| 5.97                                                                                                                         | -65.3               | V                             | 3.0      | -32.4                         | 33.4   | 1.0             | -44.0 | -25.0 | -19.0 |       |
| 7.61                                                                                                                         | -64.8               | V                             | 3.0      | -7.1                          | 33.0   | 1.0             | -39.1 | -25.0 | -14.1 |       |
| 10.14                                                                                                                        | -65.7               | V                             | 3.0      | -4.6                          | 32.6   | 1.0             | -36.1 | -25.0 | -11.1 |       |
| High Channel (2560MHz)                                                                                                       |                     |                               |          |                               |        |                 |       |       |       |       |
| 5.12                                                                                                                         | -64.8               | H                             | 3.0      | -31.7                         | 33.4   | 1.0             | -44.1 | -25.0 | -19.1 |       |
| 7.68                                                                                                                         | -65.5               | H                             | 3.0      | -7.7                          | 33.0   | 1.0             | -39.7 | -25.0 | -14.7 |       |
| 10.24                                                                                                                        | -66.7               | H                             | 3.0      | -5.7                          | 32.5   | 1.0             | -37.2 | -25.0 | -12.2 |       |
| 5.12                                                                                                                         | -65.0               | V                             | 3.0      | -33.0                         | 33.4   | 1.0             | -45.4 | -25.0 | -20.4 |       |
| 7.68                                                                                                                         | -66.4               | V                             | 3.0      | -8.6                          | 33.0   | 1.0             | -40.6 | -25.0 | -15.6 |       |
| 10.24                                                                                                                        | -66.2               | V                             | 3.0      | -4.0                          | 32.5   | 1.0             | -35.5 | -25.0 | -10.5 |       |
| Rev 05.21.15                                                                                                                 |                     |                               |          |                               |        |                 |       |       |       |       |
| LTE B7 20MHz 16QAM                                                                                                           |                     |                               |          |                               |        |                 |       |       |       |       |



## 9.2.6. LTE BAND 14

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                       |                  |                 |          |                         |        |            |       |       |       |       |
|------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/26/18<br>Test Engineer: 19431<br>Configuration: EUT Only<br>Mode: LTE Band 14, 10MHz QPSK |                  |                 |          |                         |        |            |       |       |       |       |
| Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable                                                    |                  |                 |          |                         |        |            |       |       |       |       |
| Chamber                                                                                                                      |                  | Pre-amplifier   |          | Filter                  |        | Limit      |       |       |       |       |
| 3m Chamber C                                                                                                                 |                  | 3m Chamber C    |          | Filter                  |        | LTE B14    |       |       |       |       |
| Frequency (GHz)                                                                                                              | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
| Mid Channel (750MHz)                                                                                                         |                  |                 |          |                         |        |            |       |       |       |       |
| 1.99                                                                                                                         | -68.3            | H               | 3.0      | -27.0                   | 36.5   | 1.0        | -62.6 | -40.0 | -22.6 |       |
| 2.38                                                                                                                         | -69.5            | H               | 3.0      | -24.6                   | 35.7   | 1.0        | -58.9 | -13.0 | -45.6 |       |
| 3.17                                                                                                                         | -68.7            | H               | 3.0      | -20.2                   | 34.8   | 1.0        | -54.0 | -13.0 | -41.0 |       |
| 1.99                                                                                                                         | -68.1            | V               | 3.0      | -26.1                   | 36.5   | 1.0        | -61.7 | -40.0 | -21.7 |       |
| 2.38                                                                                                                         | -69.4            | V               | 3.0      | -23.9                   | 36.2   | 1.0        | -58.1 | -13.0 | -45.1 |       |
| 3.17                                                                                                                         | -69.7            | V               | 3.0      | -20.5                   | 34.8   | 1.0        | -54.3 | -13.0 | -41.3 |       |

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                        |                  |                 |          |                         |        |            |       |       |       |       |
|-------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/26/18<br>Test Engineer: 19431<br>Configuration: EUT Only<br>Mode: LTE Band 14, 10MHz 16QAM |                  |                 |          |                         |        |            |       |       |       |       |
| Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable                                                     |                  |                 |          |                         |        |            |       |       |       |       |
| Chamber                                                                                                                       |                  | Pre-amplifier   |          | Filter                  |        | Limit      |       |       |       |       |
| 3m Chamber C                                                                                                                  |                  | 3m Chamber C    |          | Filter                  |        | LTE B14    |       |       |       |       |
| Frequency (GHz)                                                                                                               | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
| Mid Channel (750MHz)                                                                                                          |                  |                 |          |                         |        |            |       |       |       |       |
| 1.99                                                                                                                          | -68.4            | H               | 3.0      | -27.1                   | 36.6   | 1.0        | -62.7 | -40.0 | -22.7 |       |
| 2.38                                                                                                                          | -69.6            | H               | 3.0      | -24.2                   | 35.2   | 1.0        | -58.4 | -13.0 | -45.4 |       |
| 3.17                                                                                                                          | -68.8            | H               | 3.0      | -20.3                   | 34.8   | 1.0        | -54.1 | -13.0 | -41.1 |       |
| 1.99                                                                                                                          | -68.2            | V               | 3.0      | -26.2                   | 36.6   | 1.0        | -61.8 | -40.0 | -21.8 |       |
| 2.38                                                                                                                          | -69.8            | V               | 3.0      | -25.3                   | 35.2   | 1.0        | -59.5 | -13.0 | -46.5 |       |
| 3.17                                                                                                                          | -69.3            | V               | 3.0      | -20.1                   | 34.8   | 1.0        | -53.9 | -13.0 | -40.9 |       |

## 9.2.7. LTE BAND 17

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                       |                  |                 |          |                         |        |            |       |       |       |       |
|------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/26/18<br>Test Engineer: 19431<br>Configuration: EUT Only<br>Mode: LTE Band 17, 10MHz QPSK |                  |                 |          |                         |        |            |       |       |       |       |
| Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable                                                    |                  |                 |          |                         |        |            |       |       |       |       |
| Chamber                                                                                                                      |                  | Pre-amplifier   |          | Filter                  |        | Limit      |       |       |       |       |
| 3m Chamber C                                                                                                                 |                  | 3m Chamber C    |          | Filter                  |        | EIRP       |       |       |       |       |
| Frequency (GHz)                                                                                                              | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
| Mid Channel (710MHz)                                                                                                         |                  |                 |          |                         |        |            |       |       |       |       |
| 1.42                                                                                                                         | -67.2            | H               | 3.0      | -26.8                   | 35.7   | 1.0        | -62.6 | -13.0 | -49.6 |       |
| 2.13                                                                                                                         | -66.9            | H               | 3.0      | -22.0                   | 35.7   | 1.0        | -56.7 | -13.0 | -43.7 |       |
| 2.84                                                                                                                         | -65.3            | H               | 3.0      | -18.0                   | 35.0   | 1.0        | -52.0 | -13.0 | -39.0 |       |
| 1.42                                                                                                                         | -66.7            | V               | 3.0      | -25.9                   | 36.7   | 1.0        | -61.6 | -13.0 | -48.6 |       |
| 2.13                                                                                                                         | -67.3            | V               | 3.0      | -21.6                   | 35.7   | 1.0        | -56.3 | -13.0 | -43.3 |       |
| 2.84                                                                                                                         | -65.9            | V               | 3.0      | -18.0                   | 35.0   | 1.0        | -52.0 | -13.0 | -39.0 |       |

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                        |                  |                 |          |                         |        |            |       |       |       |       |
|-------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/26/18<br>Test Engineer: 19431<br>Configuration: EUT Only<br>Mode: LTE Band 17, 10MHz 16QAM |                  |                 |          |                         |        |            |       |       |       |       |
| Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable                                                     |                  |                 |          |                         |        |            |       |       |       |       |
| Chamber                                                                                                                       |                  | Pre-amplifier   |          | Filter                  |        | Limit      |       |       |       |       |
| 3m Chamber C                                                                                                                  |                  | 3m Chamber C    |          | Filter                  |        | EIRP       |       |       |       |       |
| Frequency (GHz)                                                                                                               | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
| Mid Channel (710MHz)                                                                                                          |                  |                 |          |                         |        |            |       |       |       |       |
| 1.42                                                                                                                          | -65.3            | H               | 3.0      | -25.1                   | 35.7   | 1.0        | -60.7 | -13.0 | -47.7 |       |
| 2.13                                                                                                                          | -66.8            | H               | 3.0      | -21.9                   | 35.7   | 1.0        | -56.6 | -13.0 | -43.6 |       |
| 2.84                                                                                                                          | -64.9            | H               | 3.0      | -18.5                   | 35.0   | 1.0        | -53.5 | -13.0 | -40.5 |       |
| 1.42                                                                                                                          | -67.0            | V               | 3.0      | -26.3                   | 35.7   | 1.0        | -62.0 | -13.0 | -49.0 |       |
| 2.13                                                                                                                          | -68.8            | V               | 3.0      | -23.1                   | 35.7   | 1.0        | -58.8 | -13.0 | -45.8 |       |
| 2.84                                                                                                                          | -67.1            | V               | 3.0      | -19.2                   | 35.0   | 1.0        | -53.2 | -13.0 | -40.2 |       |



## 9.2.8. LTE BAND 25

High Frequency Substitution Measurement

UL Fremont Radiated Chamber

Company:

Project #:

Date: 06/25/18

Test Engineer: 19429

Configuration: EUT Only

Mode: LTE Band 25, 20MHz QPSK

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber

3m Chamber F

Pre-amplifier

3m Chamber F

Filter

Filter

Limit

EIRP

| Frequency (GHz)         | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
|-------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Low Channel (1860MHz)   |                  |                 |          |                         |        |            |       |       |       |       |
| 3.72                    | -69.2            | H               | 3.0      | -19.4                   | 34.4   | 1.0        | -52.8 | -13.0 | -39.8 |       |
| 5.98                    | -70.9            | H               | 3.0      | -17.4                   | 34.1   | 1.0        | -50.5 | -13.0 | -37.5 |       |
| 7.44                    | -73.0            | H               | 3.0      | -16.6                   | 33.6   | 1.0        | -49.2 | -13.0 | -36.2 |       |
| 3.72                    | -70.6            | V               | 3.0      | -20.1                   | 34.4   | 1.0        | -53.5 | -13.0 | -40.5 |       |
| 5.98                    | -70.0            | V               | 3.0      | -18.3                   | 34.1   | 1.0        | -49.5 | -13.0 | -36.5 |       |
| 7.44                    | -72.2            | V               | 3.0      | -16.1                   | 33.6   | 1.0        | -48.7 | -13.0 | -35.7 |       |
| Mid Channel (1882.5MHz) |                  |                 |          |                         |        |            |       |       |       |       |
| 3.77                    | -70.7            | H               | 3.0      | -20.7                   | 34.4   | 1.0        | -54.1 | -13.0 | -41.1 |       |
| 5.96                    | -70.2            | H               | 3.0      | -18.5                   | 34.1   | 1.0        | -49.7 | -13.0 | -36.7 |       |
| 7.53                    | -72.7            | H               | 3.0      | -18.2                   | 33.5   | 1.0        | -48.7 | -13.0 | -35.7 |       |
| 3.77                    | -70.5            | V               | 3.0      | -20.4                   | 34.4   | 1.0        | -53.8 | -13.0 | -40.8 |       |
| 5.96                    | -70.1            | V               | 3.0      | -18.5                   | 34.1   | 1.0        | -49.7 | -13.0 | -36.7 |       |
| 7.53                    | -72.4            | V               | 3.0      | -18.1                   | 33.5   | 1.0        | -48.6 | -13.0 | -35.6 |       |
| High Channel (1905MHz)  |                  |                 |          |                         |        |            |       |       |       |       |
| 3.81                    | -70.3            | H               | 3.0      | -20.1                   | 34.4   | 1.0        | -53.5 | -13.0 | -40.5 |       |
| 5.72                    | -71.0            | H               | 3.0      | -17.2                   | 34.1   | 1.0        | -50.4 | -13.0 | -37.4 |       |
| 7.62                    | -72.7            | H               | 3.0      | -16.1                   | 33.4   | 1.0        | -48.5 | -13.0 | -35.5 |       |
| 3.81                    | -70.2            | V               | 3.0      | -20.0                   | 34.4   | 1.0        | -53.3 | -13.0 | -40.3 |       |
| 5.72                    | -71.4            | V               | 3.0      | -17.6                   | 34.1   | 1.0        | -50.7 | -13.0 | -37.7 |       |
| 7.62                    | -72.5            | V               | 3.0      | -16.1                   | 33.4   | 1.0        | -48.5 | -13.0 | -35.5 |       |

Rev 05.21.15

High Frequency Substitution Measurement

UL Fremont Radiated Chamber

Company:

Project #:

Date: 06/25/18

Test Engineer: 19429

Configuration: EUT Only

Mode: LTE Band 25, 20MHz 16QAM

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber

3m Chamber F

Pre-amplifier

3m Chamber F

Filter

Filter

Limit

EIRP

| Frequency (GHz)         | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
|-------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Low Channel (1860MHz)   |                  |                 |          |                         |        |            |       |       |       |       |
| 3.72                    | -67.7            | H               | 3.0      | -17.9                   | 34.4   | 1.0        | -51.3 | -13.0 | -38.3 |       |
| 5.98                    | -70.9            | H               | 3.0      | -17.3                   | 34.1   | 1.0        | -50.4 | -13.0 | -37.4 |       |
| 7.44                    | -71.3            | H               | 3.0      | -14.9                   | 33.6   | 1.0        | -47.5 | -13.0 | -34.5 |       |
| 3.72                    | -69.8            | V               | 3.0      | -19.9                   | 34.4   | 1.0        | -53.3 | -13.0 | -40.3 |       |
| 5.98                    | -69.4            | V               | 3.0      | -15.7                   | 34.1   | 1.0        | -48.9 | -13.0 | -35.9 |       |
| 7.44                    | -71.0            | V               | 3.0      | -16.8                   | 33.6   | 1.0        | -49.4 | -13.0 | -36.4 |       |
| Mid Channel (1882.5MHz) |                  |                 |          |                         |        |            |       |       |       |       |
| 3.77                    | -69.2            | H               | 3.0      | -19.2                   | 34.4   | 1.0        | -52.6 | -13.0 | -39.6 |       |
| 5.98                    | -71.1            | H               | 3.0      | -17.5                   | 34.1   | 1.0        | -50.6 | -13.0 | -37.6 |       |
| 7.53                    | -72.2            | H               | 3.0      | -15.7                   | 33.9   | 1.0        | -48.2 | -13.0 | -35.2 |       |
| 3.77                    | -70.1            | V               | 3.0      | -20.0                   | 34.4   | 1.0        | -53.4 | -13.0 | -40.4 |       |
| 5.96                    | -70.8            | V               | 3.0      | -17.0                   | 34.1   | 1.0        | -50.1 | -13.0 | -37.1 |       |
| 7.53                    | -72.4            | V               | 3.0      | -16.1                   | 33.5   | 1.0        | -48.6 | -13.0 | -35.6 |       |
| High Channel (1905MHz)  |                  |                 |          |                         |        |            |       |       |       |       |
| 3.81                    | -70.0            | H               | 3.0      | -19.8                   | 34.4   | 1.0        | -52.2 | -13.0 | -39.2 |       |
| 5.72                    | -71.0            | H               | 3.0      | -17.3                   | 34.1   | 1.0        | -50.4 | -13.0 | -37.4 |       |
| 7.62                    | -72.9            | H               | 3.0      | -15.3                   | 33.4   | 1.0        | -48.7 | -13.0 | -35.7 |       |
| 3.81                    | -70.2            | V               | 3.0      | -20.0                   | 34.4   | 1.0        | -53.4 | -13.0 | -40.4 |       |
| 5.72                    | -72.2            | V               | 3.0      | -18.4                   | 34.1   | 1.0        | -51.5 | -13.0 | -38.5 |       |
| 7.62                    | -70.9            | V               | 3.0      | -16.6                   | 33.4   | 1.0        | -49.0 | -13.0 | -36.0 |       |

Rev 05.21.15

LTE B25 20MHz QPSK

LTE B25 20MHz 16QAM

## 9.2.9. LTE BAND 26 (PART 90S)

High Frequency Substitution Measurement

UL Fremont Radiated Chamber

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

06/25/18

19429

EUT Only

LTE Band 26 (90S), 10MHz QPSK

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber

3m Chamber C

Pre-amplifier

3m Chamber C

Filter

Filter

Limit

EIRP

| Frequency (GHz)      | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
|----------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Mid Channel (819MHz) |                  |                 |          |                         |        |            |       |       |       |       |
| 1.64                 | -66.0            | H               | 3.0      | -24.3                   | 36.5   | 1.0        | -58.8 | -13.0 | -46.8 |       |
| 2.46                 | -66.2            | H               | 3.0      | -20.5                   | 35.2   | 1.0        | -54.7 | -13.0 | -41.7 |       |
| 3.28                 | -65.3            | H               | 3.0      | -16.5                   | 34.7   | 1.0        | -50.2 | -13.0 | -37.2 |       |
| 1.64                 | -67.1            | V               | 3.0      | -24.6                   | 36.5   | 1.0        | -60.1 | -13.0 | -47.1 |       |
| 2.46                 | -66.7            | V               | 3.0      | -21.0                   | 35.2   | 1.0        | -55.2 | -13.0 | -42.2 |       |
| 3.28                 | -65.7            | V               | 3.0      | -16.2                   | 34.7   | 1.0        | -49.9 | -13.0 | -36.9 |       |

Rev 05.21.15

LTE B26 10MHz QPSK

High Frequency Substitution Measurement

UL Fremont Radiated Chamber

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

06/25/18

19429

EUT Only

LTE Band 26 (90S), 10MHz 16QAM

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber

3m Chamber C

Pre-amplifier

3m Chamber C

Filter

Filter

Limit

EIRP

| Frequency (GHz)      | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
|----------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Mid Channel (819MHz) |                  |                 |          |                         |        |            |       |       |       |       |
| 1.64                 | -67.2            | H               | 3.0      | -25.5                   | 36.5   | 1.0        | -61.0 | -13.0 | -48.0 |       |
| 2.46                 | -66.2            | H               | 3.0      | -20.6                   | 35.2   | 1.0        | -54.7 | -13.0 | -41.7 |       |
| 3.28                 | -65.2            | H               | 3.0      | -16.5                   | 34.7   | 1.0        | -50.1 | -13.0 | -37.1 |       |
| 1.64                 | -67.7            | V               | 3.0      | -24.2                   | 36.5   | 1.0        | -59.8 | -13.0 | -46.8 |       |
| 2.46                 | -66.6            | V               | 3.0      | -20.9                   | 35.2   | 1.0        | -55.1 | -13.0 | -42.1 |       |
| 3.28                 | -66.1            | V               | 3.0      | -16.6                   | 34.7   | 1.0        | -50.3 | -13.0 | -37.3 |       |

Rev 05.21.15

LTE B26 10MHz 16QAM

## 9.2.10. LTE BAND 30

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                       |                  |                               |          |                         |        |                  |       |       |       |       |  |
|------------------------------------------------------------------------------------------------------------------------------|------------------|-------------------------------|----------|-------------------------|--------|------------------|-------|-------|-------|-------|--|
| Company:<br>Project #:<br>Date: 06/26/18<br>Test Engineer: 19431<br>Configuration: EUT only<br>Mode: LTE Band 30, 10MHz QPSK |                  |                               |          |                         |        |                  |       |       |       |       |  |
| Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable                                                    |                  |                               |          |                         |        |                  |       |       |       |       |  |
| Chamber<br>3m Chamber C                                                                                                      |                  | Pre-amplifier<br>3m Chamber C |          | Filter<br>Filter        |        | Limit<br>LTE B30 |       |       |       |       |  |
| Frequency (GHz)                                                                                                              | SA reading (dBm) | Ant. Pol. (H/V)               | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator       | EIRP  | Limit | Delta | Notes |  |
| Mid Channel (250MHz)                                                                                                         |                  |                               |          |                         |        |                  |       |       |       |       |  |
| 4.62                                                                                                                         | -69.2            | H                             | 3.0      | -35.4                   | 37.9   | 1.0              | -52.3 | -40.0 | -12.3 |       |  |
| 6.93                                                                                                                         | -68.8            | H                             | 3.0      | -30.2                   | 36.5   | 1.0              | -45.6 | -40.0 | -5.6  |       |  |
| 9.24                                                                                                                         | -69.5            | H                             | 3.0      | -8.3                    | 34.9   | 1.0              | -42.3 | -40.0 | -2.3  |       |  |
| 4.62                                                                                                                         | -68.7            | V                             | 3.0      | -35.0                   | 37.9   | 1.0              | -51.9 | -40.0 | -11.9 |       |  |
| 6.93                                                                                                                         | -68.6            | V                             | 3.0      | -9.1                    | 36.5   | 1.0              | -44.6 | -40.0 | -4.6  |       |  |
| 9.24                                                                                                                         | -70.3            | V                             | 3.0      | -8.3                    | 34.9   | 1.0              | -42.2 | -40.0 | -2.2  |       |  |
| Rev 05.21.15                                                                                                                 |                  |                               |          |                         |        |                  |       |       |       |       |  |
| LTE B30 10MHz QPSK                                                                                                           |                  |                               |          |                         |        |                  |       |       |       |       |  |

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                        |                  |                               |          |                         |        |                  |       |       |       |       |  |
|-------------------------------------------------------------------------------------------------------------------------------|------------------|-------------------------------|----------|-------------------------|--------|------------------|-------|-------|-------|-------|--|
| Company:<br>Project #:<br>Date: 06/26/18<br>Test Engineer: 19431<br>Configuration: EUT only<br>Mode: LTE Band 30, 10MHz 16QAM |                  |                               |          |                         |        |                  |       |       |       |       |  |
| Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable                                                     |                  |                               |          |                         |        |                  |       |       |       |       |  |
| Chamber<br>3m Chamber C                                                                                                       |                  | Pre-amplifier<br>3m Chamber C |          | Filter<br>Filter        |        | Limit<br>LTE B30 |       |       |       |       |  |
| Frequency (GHz)                                                                                                               | SA reading (dBm) | Ant. Pol. (H/V)               | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator       | EIRP  | Limit | Delta | Notes |  |
| Mid Channel (250MHz)                                                                                                          |                  |                               |          |                         |        |                  |       |       |       |       |  |
| 4.62                                                                                                                          | -69.1            | H                             | 3.0      | -35.3                   | 37.9   | 1.0              | -52.2 | -40.0 | -12.2 |       |  |
| 6.93                                                                                                                          | -67.5            | H                             | 3.0      | -8.9                    | 36.5   | 1.0              | -44.3 | -40.0 | -4.3  |       |  |
| 9.24                                                                                                                          | -69.7            | H                             | 3.0      | -8.2                    | 34.9   | 1.0              | -42.0 | -40.0 | -2.0  |       |  |
| 4.62                                                                                                                          | -68.1            | V                             | 3.0      | -35.4                   | 37.9   | 1.0              | -52.3 | -40.0 | -12.3 |       |  |
| 6.93                                                                                                                          | -68.4            | V                             | 3.0      | -8.9                    | 36.5   | 1.0              | -44.4 | -40.0 | -4.4  |       |  |
| 9.24                                                                                                                          | -69.5            | V                             | 3.0      | -7.7                    | 34.9   | 1.0              | -41.6 | -40.0 | -1.6  |       |  |
| Rev 05.21.15                                                                                                                  |                  |                               |          |                         |        |                  |       |       |       |       |  |
| LTE B30 10MHz 16QAM                                                                                                           |                  |                               |          |                         |        |                  |       |       |       |       |  |

## 9.2.11. LTE BAND 41

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                       |                  |                               |          |                         |        |                  |       |       |       |       |  |
|------------------------------------------------------------------------------------------------------------------------------|------------------|-------------------------------|----------|-------------------------|--------|------------------|-------|-------|-------|-------|--|
| Company:<br>Project #:<br>Date: 06/26/18<br>Test Engineer: 19431<br>Configuration: EUT Only<br>Mode: LTE Band 41, 20MHz QPSK |                  |                               |          |                         |        |                  |       |       |       |       |  |
| Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable                                                    |                  |                               |          |                         |        |                  |       |       |       |       |  |
| Chamber<br>3m Chamber C                                                                                                      |                  | Pre-amplifier<br>3m Chamber C |          | Filter<br>Filter        |        | Limit<br>LTE B41 |       |       |       |       |  |
| Frequency (GHz)                                                                                                              | SA reading (dBm) | Ant. Pol. (H/V)               | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator       | EIRP  | Limit | Delta | Notes |  |
| Low Channel (250MHz)                                                                                                         |                  |                               |          |                         |        |                  |       |       |       |       |  |
| 5.01                                                                                                                         | -68.1            | H                             | 3.0      | -35.2                   | 33.4   | 1.0              | -47.6 | -25.0 | -22.6 |       |  |
| 7.52                                                                                                                         | -69.0            | H                             | 3.0      | -10.4                   | 33.0   | 1.0              | -42.5 | -25.0 | -17.5 |       |  |
| 10.02                                                                                                                        | -69.0            | H                             | 3.0      | -8.2                    | 32.7   | 1.0              | -39.9 | -25.0 | -14.9 |       |  |
| 5.01                                                                                                                         | -68.7            | V                             | 3.0      | -35.9                   | 33.4   | 1.0              | -48.3 | -25.0 | -23.3 |       |  |
| 7.52                                                                                                                         | -69.5            | V                             | 3.0      | -11.9                   | 33.0   | 1.0              | -43.9 | -25.0 | -18.9 |       |  |
| 10.02                                                                                                                        | -68.5            | V                             | 3.0      | -7.8                    | 32.7   | 1.0              | -39.5 | -25.0 | -14.5 |       |  |
| Mid Channel (250MHz)                                                                                                         |                  |                               |          |                         |        |                  |       |       |       |       |  |
| 5.19                                                                                                                         | -68.0            | H                             | 3.0      | -14.8                   | 32.4   | 1.0              | -47.1 | -25.0 | -22.1 |       |  |
| 7.78                                                                                                                         | -68.2            | H                             | 3.0      | -10.3                   | 33.0   | 1.0              | -42.3 | -25.0 | -17.3 |       |  |
| 10.37                                                                                                                        | -69.1            | H                             | 3.0      | -7.0                    | 32.4   | 1.0              | -38.4 | -25.0 | -13.4 |       |  |
| 5.19                                                                                                                         | -67.5            | V                             | 3.0      | -14.3                   | 33.4   | 1.0              | -46.7 | -25.0 | -21.7 |       |  |
| 7.78                                                                                                                         | -67.8            | V                             | 3.0      | -9.8                    | 33.0   | 1.0              | -41.8 | -25.0 | -16.8 |       |  |
| 10.37                                                                                                                        | -66.5            | V                             | 3.0      | -7.2                    | 32.4   | 1.0              | -38.6 | -25.0 | -13.6 |       |  |
| High Channel (250MHz)                                                                                                        |                  |                               |          |                         |        |                  |       |       |       |       |  |
| 5.36                                                                                                                         | -69.5            | H                             | 3.0      | -15.9                   | 33.3   | 1.0              | -48.2 | -25.0 | -23.2 |       |  |
| 8.04                                                                                                                         | -69.5            | H                             | 3.0      | -6.5                    | 33.0   | 1.0              | -40.6 | -25.0 | -15.6 |       |  |
| 10.72                                                                                                                        | -68.8            | H                             | 3.0      | -7.3                    | 32.2   | 1.0              | -38.5 | -25.0 | -13.5 |       |  |
| 5.36                                                                                                                         | -67.9            | V                             | 3.0      | -14.4                   | 33.3   | 1.0              | -46.7 | -25.0 | -21.7 |       |  |
| 8.04                                                                                                                         | -67.3            | V                             | 3.0      | -9.9                    | 33.0   | 1.0              | -40.9 | -25.0 | -15.9 |       |  |
| 10.72                                                                                                                        | -68.7            | V                             | 3.0      | -7.2                    | 32.2   | 1.0              | -38.4 | -25.0 | -13.4 |       |  |
| Rev 05.21.15                                                                                                                 |                  |                               |          |                         |        |                  |       |       |       |       |  |
| LTE B41 20MHz QPSK                                                                                                           |                  |                               |          |                         |        |                  |       |       |       |       |  |

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                        |                  |                               |          |                         |        |                  |       |       |       |       |  |
|-------------------------------------------------------------------------------------------------------------------------------|------------------|-------------------------------|----------|-------------------------|--------|------------------|-------|-------|-------|-------|--|
| Company:<br>Project #:<br>Date: 06/26/18<br>Test Engineer: 19431<br>Configuration: EUT Only<br>Mode: LTE Band 41, 20MHz 16QAM |                  |                               |          |                         |        |                  |       |       |       |       |  |
| Test Equipment:<br>Substitution: Horn T59 Substitution, and 8ft SMA Cable                                                     |                  |                               |          |                         |        |                  |       |       |       |       |  |
| Chamber<br>3m Chamber C                                                                                                       |                  | Pre-amplifier<br>3m Chamber C |          | Filter<br>Filter        |        | Limit<br>LTE B41 |       |       |       |       |  |
| Frequency (GHz)                                                                                                               | SA reading (dBm) | Ant. Pol. (H/V)               | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator       | EIRP  | Limit | Delta | Notes |  |
| Low Channel (250MHz)                                                                                                          |                  |                               |          |                         |        |                  |       |       |       |       |  |
| 5.01                                                                                                                          | -68.2            | H                             | 3.0      | -35.3                   | 33.4   | 1.0              | -47.7 | -25.0 | -22.7 |       |  |
| 7.52                                                                                                                          | -69.0            | H                             | 3.0      | -11.4                   | 33.0   | 1.0              | -43.5 | -25.0 | -18.5 |       |  |
| 10.02                                                                                                                         | -69.4            | H                             | 3.0      | -8.6                    | 32.7   | 1.0              | -40.3 | -25.0 | -15.3 |       |  |
| 5.01                                                                                                                          | -68.4            | V                             | 3.0      | -35.6                   | 33.4   | 1.0              | -48.0 | -25.0 | -23.0 |       |  |
| 7.52                                                                                                                          | -69.1            | V                             | 3.0      | -11.5                   | 33.0   | 1.0              | -43.5 | -25.0 | -18.5 |       |  |
| 10.02                                                                                                                         | -69.3            | V                             | 3.0      | -8.2                    | 32.7   | 1.0              | -39.9 | -25.0 | -14.9 |       |  |
| Mid Channel (250MHz)                                                                                                          |                  |                               |          |                         |        |                  |       |       |       |       |  |
| 5.19                                                                                                                          | -67.1            | H                             | 3.0      | -13.9                   | 33.4   | 1.0              | -46.2 | -25.0 | -21.2 |       |  |
| 7.78                                                                                                                          | -69.4            | H                             | 3.0      | -11.5                   | 33.0   | 1.0              | -43.5 | -25.0 | -18.5 |       |  |
| 10.37                                                                                                                         | -67.1            | H                             | 3.0      | -6.0                    | 32.4   | 1.0              | -37.4 | -25.0 | -12.4 |       |  |
| 5.19                                                                                                                          | -69.1            | V                             | 3.0      | -15.9                   | 33.4   | 1.0              | -48.3 | -25.0 | -23.3 |       |  |
| 7.78                                                                                                                          | -68.8            | V                             | 3.0      | -10.8                   | 33.0   | 1.0              | -42.8 | -25.0 | -17.8 |       |  |
| 10.37                                                                                                                         | -68.0            | V                             | 3.0      | -6.7                    | 32.4   | 1.0              | -38.1 | -25.0 | -13.1 |       |  |
| High Channel (250MHz)                                                                                                         |                  |                               |          |                         |        |                  |       |       |       |       |  |
| 5.36                                                                                                                          | -69.1            | H                             | 3.0      | -14.5                   | 33.3   | 1.0              | -46.8 | -25.0 | -21.8 |       |  |
| 8.04                                                                                                                          | -69.0            | H                             | 3.0      | -8.7                    | 33.0   | 1.0              | -41.7 | -25.0 | -16.7 |       |  |
| 10.72                                                                                                                         | -69.9            | H                             | 3.0      | -4.4                    | 32.2   | 1.0              | -36.5 | -25.0 | -10.5 |       |  |
| 5.36                                                                                                                          | -69.4            | V                             | 3.0      | -15.9                   | 33.3   | 1.0              | -48.2 | -25.0 | -23.2 |       |  |
| 8.04                                                                                                                          | -69.5            | V                             | 3.0      | -11.2                   | 33.0   | 1.0              | -43.1 | -25.0 | -18.1 |       |  |
| 10.72                                                                                                                         | -68.1            | V                             | 3.0      | -6.6                    | 32.2   | 1.0              | -37.8 | -25.0 | -12.8 |       |  |
| Rev 05.21.15                                                                                                                  |                  |                               |          |                         |        |                  |       |       |       |       |  |
| LTE B41 20MHz 16QAM                                                                                                           |                  |                               |          |                         |        |                  |       |       |       |       |  |

## 9.2.12. LTE BAND 66

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                                                                                                   |                  |                 |          |                         |        |            |       |       |       |       |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/20/18<br>Test Engineer: 10643<br>Configuration: EUT Only<br>Mode: LTE Band 66, 20MHz QPSK<br>Test Equipment:<br>Substitution: Horn T59 Substitution, and 8T SMA Cable |                  |                 |          |                         |        |            |       |       |       |       |
| Chamber                                                                                                                                                                                                  | Pre-amplifier    | Filter          | Limit    |                         |        |            |       |       |       |       |
| 3m Chamber C                                                                                                                                                                                             | 3m Chamber C     | Filter          | EIRP     |                         |        |            |       |       |       |       |
| Frequency (GHz)                                                                                                                                                                                          | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
| <b>Low Channel (1720.0MHz)</b>                                                                                                                                                                           |                  |                 |          |                         |        |            |       |       |       |       |
| 3.44                                                                                                                                                                                                     | -70.9            | H               | 3.0      | -21.7                   | 34.5   | 1.0        | -55.1 | -13.0 | -42.1 |       |
| 5.16                                                                                                                                                                                                     | -69.1            | H               | 3.0      | -15.9                   | 33.4   | 1.0        | -48.3 | -13.0 | -35.3 |       |
| 6.88                                                                                                                                                                                                     | -67.5            | H               | 3.0      | -10.8                   | 33.1   | 1.0        | -43.0 | -13.0 | -30.0 |       |
| 3.44                                                                                                                                                                                                     | -69.6            | V               | 3.0      | -21.6                   | 34.5   | 1.0        | -55.1 | -13.0 | -42.1 |       |
| 5.16                                                                                                                                                                                                     | -68.6            | V               | 3.0      | -15.5                   | 33.4   | 1.0        | -47.2 | -13.0 | -34.2 |       |
| 6.88                                                                                                                                                                                                     | -67.4            | V               | 3.0      | -10.5                   | 33.1   | 1.0        | -42.6 | -13.0 | -29.6 |       |
| <b>Mid Channel (1745.0MHz)</b>                                                                                                                                                                           |                  |                 |          |                         |        |            |       |       |       |       |
| 3.49                                                                                                                                                                                                     | -71.6            | H               | 3.0      | -22.2                   | 34.4   | 1.0        | -56.6 | -13.0 | -43.6 |       |
| 5.24                                                                                                                                                                                                     | -66.5            | H               | 3.0      | -13.1                   | 33.3   | 1.0        | -45.5 | -13.0 | -32.5 |       |
| 6.98                                                                                                                                                                                                     | -69.2            | H               | 3.0      | -11.3                   | 33.1   | 1.0        | -43.4 | -13.0 | -30.4 |       |
| 3.49                                                                                                                                                                                                     | -71.7            | V               | 3.0      | -21.6                   | 34.4   | 1.0        | -56.2 | -13.0 | -43.2 |       |
| 5.24                                                                                                                                                                                                     | -68.1            | V               | 3.0      | -14.8                   | 33.3   | 1.0        | -47.2 | -13.0 | -34.2 |       |
| 6.98                                                                                                                                                                                                     | -68.3            | V               | 3.0      | -11.5                   | 33.1   | 1.0        | -43.6 | -13.0 | -30.6 |       |
| <b>High Channel (1770.0MHz)</b>                                                                                                                                                                          |                  |                 |          |                         |        |            |       |       |       |       |
| 3.54                                                                                                                                                                                                     | -70.8            | H               | 3.0      | -21.3                   | 34.3   | 1.0        | -54.6 | -13.0 | -41.6 |       |
| 5.31                                                                                                                                                                                                     | -67.7            | H               | 3.0      | -14.2                   | 33.3   | 1.0        | -46.5 | -13.0 | -33.5 |       |
| 7.08                                                                                                                                                                                                     | -69.7            | H               | 3.0      | -12.7                   | 33.1   | 1.0        | -44.3 | -13.0 | -31.3 |       |
| 3.54                                                                                                                                                                                                     | -71.3            | V               | 3.0      | -21.3                   | 34.3   | 1.0        | -54.6 | -13.0 | -41.6 |       |
| 5.31                                                                                                                                                                                                     | -68.1            | V               | 3.0      | -14.7                   | 33.3   | 1.0        | -47.0 | -13.0 | -34.0 |       |
| 7.08                                                                                                                                                                                                     | -70.1            | V               | 3.0      | -13.1                   | 33.1   | 1.0        | -45.2 | -13.0 | -32.2 |       |
| Rev. 02.24.17                                                                                                                                                                                            |                  |                 |          |                         |        |            |       |       |       |       |

LTE B66 20MHz QPSK

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                                                                                                    |                  |                 |          |                         |        |            |       |       |       |       |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/20/18<br>Test Engineer: 10643<br>Configuration: EUT Only<br>Mode: LTE Band 66, 20MHz 16QAM<br>Test Equipment:<br>Substitution: Horn T59 Substitution, and 8T SMA Cable |                  |                 |          |                         |        |            |       |       |       |       |
| Chamber                                                                                                                                                                                                   | Pre-amplifier    | Filter          | Limit    |                         |        |            |       |       |       |       |
| 3m Chamber C                                                                                                                                                                                              | 3m Chamber C     | Filter          | EIRP     |                         |        |            |       |       |       |       |
| Frequency (GHz)                                                                                                                                                                                           | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
| <b>Low Channel (1720.0MHz)</b>                                                                                                                                                                            |                  |                 |          |                         |        |            |       |       |       |       |
| 3.44                                                                                                                                                                                                      | -70.9            | H               | 3.0      | -21.6                   | 34.5   | 1.0        | -55.0 | -13.0 | -42.0 |       |
| 5.16                                                                                                                                                                                                      | -69.2            | H               | 3.0      | -16.0                   | 33.4   | 1.0        | -48.4 | -13.0 | -35.4 |       |
| 6.88                                                                                                                                                                                                      | -69.2            | H               | 3.0      | -12.5                   | 33.1   | 1.0        | -44.7 | -13.0 | -31.7 |       |
| 3.44                                                                                                                                                                                                      | -69.1            | V               | 3.0      | -19.3                   | 34.5   | 1.0        | -52.8 | -13.0 | -39.8 |       |
| 5.16                                                                                                                                                                                                      | -68.6            | V               | 3.0      | -15.5                   | 33.4   | 1.0        | -47.8 | -13.0 | -34.8 |       |
| 6.88                                                                                                                                                                                                      | -68.9            | V               | 3.0      | -10.2                   | 33.1   | 1.0        | -42.3 | -13.0 | -29.3 |       |
| <b>Mid Channel (1745.0MHz)</b>                                                                                                                                                                            |                  |                 |          |                         |        |            |       |       |       |       |
| 3.49                                                                                                                                                                                                      | -69.6            | H               | 3.0      | -20.2                   | 34.4   | 1.0        | -53.6 | -13.0 | -40.6 |       |
| 5.24                                                                                                                                                                                                      | -67.4            | H               | 3.0      | -14.0                   | 33.3   | 1.0        | -46.4 | -13.0 | -33.4 |       |
| 6.98                                                                                                                                                                                                      | -69.2            | H               | 3.0      | -12.3                   | 33.1   | 1.0        | -44.4 | -13.0 | -31.4 |       |
| 3.49                                                                                                                                                                                                      | -71.0            | V               | 3.0      | -21.1                   | 34.4   | 1.0        | -54.5 | -13.0 | -41.5 |       |
| 5.24                                                                                                                                                                                                      | -66.5            | V               | 3.0      | -13.2                   | 33.3   | 1.0        | -45.6 | -13.0 | -32.6 |       |
| 6.98                                                                                                                                                                                                      | -68.6            | V               | 3.0      | -12.8                   | 33.1   | 1.0        | -44.9 | -13.0 | -31.9 |       |
| <b>High Channel (1770.0MHz)</b>                                                                                                                                                                           |                  |                 |          |                         |        |            |       |       |       |       |
| 3.54                                                                                                                                                                                                      | -71.1            | H               | 3.0      | -21.6                   | 34.3   | 1.0        | -54.9 | -13.0 | -41.9 |       |
| 5.31                                                                                                                                                                                                      | -66.6            | H               | 3.0      | -13.1                   | 33.3   | 1.0        | -46.4 | -13.0 | -33.4 |       |
| 7.08                                                                                                                                                                                                      | -70.1            | H               | 3.0      | -13.1                   | 33.1   | 1.0        | -45.2 | -13.0 | -32.2 |       |
| 3.54                                                                                                                                                                                                      | -71.0            | V               | 3.0      | -21.0                   | 34.3   | 1.0        | -54.3 | -13.0 | -41.3 |       |
| 5.31                                                                                                                                                                                                      | -68.1            | V               | 3.0      | -14.7                   | 33.3   | 1.0        | -47.0 | -13.0 | -34.0 |       |
| 7.08                                                                                                                                                                                                      | -69.8            | V               | 3.0      | -12.8                   | 33.1   | 1.0        | -44.9 | -13.0 | -31.9 |       |
| Rev. 02.24.17                                                                                                                                                                                             |                  |                 |          |                         |        |            |       |       |       |       |

LTE B66 20MHz 16QAM

## 9.2.13. LTE BAND 71

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                                                                                                   |                  |                 |          |                         |        |            |       |       |       |       |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/12/18<br>Test Engineer: 10643<br>Configuration: EUT Only<br>Mode: LTE Band 71, 20MHz QPSK<br>Test Equipment:<br>Substitution: Horn T59 Substitution, and 8T SMA Cable |                  |                 |          |                         |        |            |       |       |       |       |
| Chamber                                                                                                                                                                                                  | Pre-amplifier    | Filter          | Limit    |                         |        |            |       |       |       |       |
| 3m Chamber E                                                                                                                                                                                             | 3m Chamber E     | Filter          | EIRP     |                         |        |            |       |       |       |       |
| Frequency (GHz)                                                                                                                                                                                          | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
| <b>Low Channel (670MHz)</b>                                                                                                                                                                              |                  |                 |          |                         |        |            |       |       |       |       |
| 1.35                                                                                                                                                                                                     | -68.7            | H               | 3.0      | -27.4                   | 38.2   | 1.0        | -64.6 | -13.0 | -51.6 |       |
| 2.02                                                                                                                                                                                                     | -69.5            | H               | 3.0      | -25.3                   | 37.9   | 1.0        | -62.2 | -13.0 | -49.2 |       |
| 2.69                                                                                                                                                                                                     | -71.0            | H               | 3.0      | -24.7                   | 38.5   | 1.0        | -62.2 | -13.0 | -49.2 |       |
| 1.35                                                                                                                                                                                                     | -69.7            | V               | 3.0      | -29.1                   | 38.2   | 1.0        | -66.3 | -13.0 | -53.3 |       |
| 2.02                                                                                                                                                                                                     | -68.6            | V               | 3.0      | -24.7                   | 37.9   | 1.0        | -61.6 | -13.0 | -48.6 |       |
| 2.69                                                                                                                                                                                                     | -70.5            | V               | 3.0      | -24.2                   | 38.5   | 1.0        | -61.7 | -13.0 | -48.7 |       |
| <b>Mid Channel (680.5MHz)</b>                                                                                                                                                                            |                  |                 |          |                         |        |            |       |       |       |       |
| 1.35                                                                                                                                                                                                     | -69.3            | H               | 3.0      | -27.8                   | 38.2   | 1.0        | -65.1 | -13.0 | -52.1 |       |
| 2.04                                                                                                                                                                                                     | -69.0            | H               | 3.0      | -25.7                   | 37.9   | 1.0        | -62.6 | -13.0 | -49.6 |       |
| 2.72                                                                                                                                                                                                     | -70.9            | H               | 3.0      | -24.4                   | 38.5   | 1.0        | -61.9 | -13.0 | -48.9 |       |
| 1.35                                                                                                                                                                                                     | -69.6            | V               | 3.0      | -28.9                   | 38.2   | 1.0        | -66.1 | -13.0 | -53.1 |       |
| 2.04                                                                                                                                                                                                     | -69.0            | V               | 3.0      | -25.0                   | 37.9   | 1.0        | -62.0 | -13.0 | -49.0 |       |
| 2.72                                                                                                                                                                                                     | -70.3            | V               | 3.0      | -23.9                   | 38.5   | 1.0        | -61.4 | -13.0 | -48.4 |       |
| <b>High Channel (688MHz)</b>                                                                                                                                                                             |                  |                 |          |                         |        |            |       |       |       |       |
| 1.38                                                                                                                                                                                                     | -69.4            | H               | 3.0      | -27.9                   | 38.2   | 1.0        | -65.1 | -13.0 | -52.1 |       |
| 2.06                                                                                                                                                                                                     | -69.4            | H               | 3.0      | -26.0                   | 38.0   | 1.0        | -63.0 | -13.0 | -50.0 |       |
| 2.75                                                                                                                                                                                                     | -70.7            | H               | 3.0      | -24.0                   | 38.5   | 1.0        | -61.4 | -13.0 | -48.4 |       |
| 1.38                                                                                                                                                                                                     | -69.4            | V               | 3.0      | -28.6                   | 38.2   | 1.0        | -65.8 | -13.0 | -52.8 |       |
| 2.06                                                                                                                                                                                                     | -68.9            | V               | 3.0      | -24.9                   | 38.0   | 1.0        | -61.9 | -13.0 | -48.9 |       |
| 2.75                                                                                                                                                                                                     | -70.4            | V               | 3.0      | -23.8                   | 38.5   | 1.0        | -61.3 | -13.0 | -48.3 |       |
| Rev. 12.18.15                                                                                                                                                                                            |                  |                 |          |                         |        |            |       |       |       |       |

LTE B71 20MHz QPSK

| High Frequency Substitution Measurement<br>UL Fremont Radiated Chamber                                                                                                                                    |                  |                 |          |                         |        |            |       |       |       |       |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------|----------|-------------------------|--------|------------|-------|-------|-------|-------|
| Company:<br>Project #:<br>Date: 06/12/18<br>Test Engineer: 10643<br>Configuration: EUT Only<br>Mode: LTE Band 71, 20MHz 16QAM<br>Test Equipment:<br>Substitution: Horn T59 Substitution, and 8T SMA Cable |                  |                 |          |                         |        |            |       |       |       |       |
| Chamber                                                                                                                                                                                                   | Pre-amplifier    | Filter          | Limit    |                         |        |            |       |       |       |       |
| 3m Chamber E                                                                                                                                                                                              | 3m Chamber E     | Filter          | EIRP     |                         |        |            |       |       |       |       |
| Frequency (GHz)                                                                                                                                                                                           | SA reading (dBm) | Ant. Pol. (H/V) | Distance | EIRP @ TX Ant End (dBm) | Preamp | Attenuator | EIRP  | Limit | Delta | Notes |
| <b>Low Channel (670MHz)</b>                                                                                                                                                                               |                  |                 |          |                         |        |            |       |       |       |       |
| 1.35                                                                                                                                                                                                      | -69.2            | H               | 3.0      | -27.9                   | 38.2   | 1.0        | -65.1 | -13.0 | -52.1 |       |
| 2.02                                                                                                                                                                                                      | -69.3            | H               | 3.0      | -25.0                   | 37.9   | 1.0        | -61.9 | -13.0 | -48.9 |       |
| 2.69                                                                                                                                                                                                      | -71.4            | H               | 3.0      | -25.1                   | 38.5   | 1.0        | -62.6 | -13.0 | -49.6 |       |
| 1.35                                                                                                                                                                                                      | -70.2            | V               | 3.0      | -29.6                   | 38.2   | 1.0        | -66.8 | -13.0 | -53.8 |       |
| 2.02                                                                                                                                                                                                      | -68.4            | V               | 3.0      | -24.5                   | 37.9   | 1.0        | -61.4 | -13.0 | -48.4 |       |
| 2.69                                                                                                                                                                                                      | -70.6            | V               | 3.0      | -24.3                   | 38.5   | 1.0        | -61.8 | -13.0 | -48.8 |       |
| <b>Mid Channel (680.5MHz)</b>                                                                                                                                                                             |                  |                 |          |                         |        |            |       |       |       |       |
| 1.35                                                                                                                                                                                                      | -69.6            | H               | 3.0      | -28.2                   | 38.2   | 1.0        | -65.4 | -13.0 | -52.4 |       |
| 2.04                                                                                                                                                                                                      | -68.4            | H               | 3.0      | -25.0                   | 37.9   | 1.0        | -62.0 | -13.0 | -49.0 |       |
| 2.72                                                                                                                                                                                                      | -71.1            | H               | 3.0      | -24.6                   | 38.5   | 1.0        | -62.1 | -13.0 | -49.1 |       |
| 1.35                                                                                                                                                                                                      | -69.2            | V               | 3.0      | -28.5                   | 38.2   | 1.0        | -66.7 | -13.0 | -53.7 |       |
| 2.04                                                                                                                                                                                                      | -68.1            | V               | 3.0      | -24.1                   | 37.9   | 1.0        | -61.0 | -13.0 | -48.0 |       |
| 2.72                                                                                                                                                                                                      | -71.4            | V               | 3.0      | -25.0                   | 38.5   | 1.0        | -62.5 | -13.0 | -49.5 |       |
| <b>High Channel (688MHz)</b>                                                                                                                                                                              |                  |                 |          |                         |        |            |       |       |       |       |
| 1.38                                                                                                                                                                                                      | -69.3            | H               | 3.0      | -26.8                   | 38.2   | 1.0        | -63.9 | -13.0 | -50.9 |       |
| 2.06                                                                                                                                                                                                      | -69.5            | H               | 3.0      | -26.1                   | 38.0   | 1.0        | -63.1 | -13.0 | -50.1 |       |
| 2.75                                                                                                                                                                                                      | -71.3            | H               | 3.0      | -24.6                   | 38.5   | 1.0        | -62.1 | -13.0 | -49.1 |       |
| 1.38                                                                                                                                                                                                      | -69.4            | V               | 3.0      | -28.4                   | 38.2   | 1.0        | -65.6 | -13.0 | -52.6 |       |
| 2.06                                                                                                                                                                                                      | -68.9            | V               | 3.0      | -24.9                   | 38.0   | 1.0        | -61.9 | -13.0 | -48.9 |       |
| 2.75                                                                                                                                                                                                      | -71.1            | V               | 3.0      | -24.5                   | 38.5   | 1.0        | -62.0 | -13.0 | -49.0 |       |
| Rev. 12.18.15                                                                                                                                                                                             |                  |                 |          |                         |        |            |       |       |       |       |

LTE B71 20MHz 16QAM

END OF REPORT

## 10. SETUP PHOTOS

Please refers to 12162294-EP1V1

