



Nemko Test Report: 1028473RUS1

Applicant: Andrew Corporation
620 N. Greenfield Parkway
Garner, NC 27529
USA

Equipment Under Test: TFAH-US7/17
(E.U.T.)

FCC Identifier: BCR-TFAHUS717

In Accordance With: **CFR 47, Part 27, Subpart C**
Miscellaneous Wireless Communication Services

Tested By: Nemko USA, Inc.
802 N. Kealy
Lewisville, TX 75057-3136

TESTED BY:

A handwritten signature in black ink, appearing to read 'David Light', written over a horizontal line.

David Light, Senior Wireless Engineer

DATE: 01 June 2011

APPROVED BY:

A handwritten signature in black ink, appearing to read 'Tom Tidwell', written over a horizontal line.

Tom Tidwell, Reviewer

DATE: 17 June 2011

Number of Pages: 50

Table of Contents

SECTION 1.	SUMMARY OF TEST RESULTS	3
SECTION 2.	GENERAL EQUIPMENT SPECIFICATION	5
SECTION 3.	RF POWER OUTPUT	7
SECTION 4.	OCCUPIED BANDWIDTH	8
SECTION 5.	SPURIOUS EMISSIONS AT ANTENNA TERMINALS	19
SECTION 6.	FIELD STRENGTH OF SPURIOUS	40
SECTION 7.	TEST EQUIPMENT LIST	41
ANNEX A - TEST DETAILS		42
ANNEX B - TEST DIAGRAMS		47

Section 1. Summary of Test Results

Manufacturer: Andrew Corporation

Model No.: TFAH-US7/17

Serial No.: 10

General: **All measurements are traceable to national standards.**

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with CFR 47, Part 27, Subpart C.



New Submission



Production Unit



Class II Permissive Change



Pre-Production Unit

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.

THE FOLLOWING DEVIATIONS FROM, ADDITIONS TO, OR EXCLUSIONS FROM THE
TEST SPECIFICATIONS HAVE BEEN MADE.

See " Summary of Test Data".



NVLAP Lab Code 100426-0

Nemko USA, Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety, for use by the company's employees only.

This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government. Nemko USA, Inc. is a NVLAP accredited laboratory.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko USA, Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.

Summary Of Test Data


NAME OF TEST	PARA. NO.	RESULT
RF Power Output	27.50(d)	Complies
Occupied Bandwidth	2.1049	Complies
Spurious Emissions at Antenna Terminals	27.53(g)	Complies
Field Strength of Spurious Emissions	27.53(g)	Complies
Frequency Stability	27.54	NA

Section 2. General Equipment Specification

Supply Voltage Input:	120 Vac		
Frequency Bands: Downlink:	728 to 757 MHz 2110 to 2155 MHz		
Frequency Bands: Uplink:	NA		
Emission Designator(s):	F9W		
Output Impedance:	50 ohms		
RF Output (Rated): Downlink	$\frac{1.25}{31.0} \text{ W (2100 MHz band)}$ dBm		
RF Output (Rated): Uplink	$\frac{\text{NA}}{\text{NA}} \text{ W}$ dBm		
Frequency Translation:	F1-F1 ☒	F1-F2 ☐	N/A ☐
Band Selection:	Software ☐	Duplexer ☐	Fullband ☒

Description of EUT

The TFAH-US4B is a four band high power remote unit designed to distribute Cell700, Cell850, AWS, and Extended PCS1900 band signals along the same fiber.

System Diagram

Section 3. RF Power Output

NAME OF TEST: RF Power Output	PARA. NO.: 27.50
TESTED BY: David Light	DATE: 23 May 2011

Test Results: Complies.

Measurement Data:

Band	Modulation	Output per Channel (dBm)	Composite Power (dBm)	Composite Power (W)
700	Analog	28.0	31.0	1.25
700	LTE	28.0	31.0	1.25
700	GSM	28.0	31.0	1.25
2100	CDMA	28.0	31.0	1.25
2100	WCDMA	28.0	31.0	1.25
2100	LTE	28.0	31.0	1.25

Equipment Used: 1767-1082-1472-1469

Measurement Uncertainty: +/- 1.7 dB

Temperature: 22 °C

Relative Humidity: 45 %

Section 4. Occupied Bandwidth

NAME OF TEST: Occupied Bandwidth	PARA. NO.: 2.1049
TESTED BY: David Light	DATE: 23 May 2011

Test Results: Complies.

Test Data: See attached plot(s).

Equipment Used: 1767-1082-1472-1469

Measurement Uncertainty: 1X10⁻⁷ ppm

Temperature: 22 °C

Relative Humidity: 45 %


Test Data – Occupied Bandwidth

Analog

2 kHz tone / 2.5 kHz deviation

Output



 Marker 1 [T1] RBW 300 Hz RF Att 30 dB
 25.79 dBm VBW 300 Hz
 740.00015030 MHz SWT 2.8 s Unit dBm
 Ref Lvl 40 dBm



Test Data – Occupied Bandwidth

Analog


Input



Test Data – Occupied Bandwidth


GSM

Output




Test Data – Occupied Bandwidth

Input
GSM




Test Data – Occupied Bandwidth LTE
Output



Test Data – Occupied Bandwidth


LTE
Input



Test Data – Occupied Bandwidth

WCDMA


Output



Test Data – Occupied Bandwidth

WCDMA


Input



Test Data – Occupied Bandwidth


LTE

Output



Test Data – Occupied Bandwidth


Input
LTE



Test Data – Occupied Bandwidth

CDMA


Output



Test Data – Occupied Bandwidth

CDMA

Input



Section 5. Conducted Spurious Emissions

NAME OF TEST: Conducted Spurious Emissions

PARA. NO.: 27.53

TESTED BY: David Light


DATE: 23 May 2011

Test Results: Complies.**Test Data:** See attached plot(s).**Equipment Used:** 1767-1082-1472-1469**Measurement Uncertainty:** +/- 1.7 dB**Temperature:** 22 °C**Relative Humidity:** 48 %

Test Data – Spurious Emissions at Antenna Terminals

Low Edge


Analog



Test Data – Spurious Emissions at Antenna Terminals

High Edge


Analog



Test Data – Spurious Emissions at Antenna Terminals

Spurs

Analog



Test Data – Spurious Emissions at Antenna Terminals


GSM

Lower Edge



Ref Lvl
40 dBm

RBW 3 kHz RF Att 30 dB
VBW 3 kHz
SWT 560 ms Unit dBm



Test Data – Spurious Emissions at Antenna Terminals


GSM

Upper Edge



Ref Lvl
40 dBm


RBW 3 kHz RF Att 30 dB
VBW 3 kHz
SWT 560 ms Unit dBm



Test Data – Spurious Emissions at Antenna Terminals

Spurs


GSM



Test Data – Spurious Emissions at Antenna Terminals

Lower Edge

LTE



Test Data – Spurious Emissions at Antenna Terminals


Upper Edge

LTE



Ref Lvl
40 dBm


RBW	30 kHz	RF Att	30 dB
VBW	30 kHz		
SWT	28 ms	Unit	dBm



Test Data – Spurious Emissions at Antenna Terminals

LTE

Spurs




Test Data – Spurious Emissions at Antenna Terminals

Low Edge

WCDMA

Ref Lvl
40 dBm

RBW	30 kHz	RF Att	30 dB
VBW	30 kHz		
SWT	34 ms	Unit	dBm



Test Data – Spurious Emissions at Antenna Terminals


High Edge

WCDMA



Ref Lvl
40 dBm


RBW	30 kHz	RF Att	30 dB
VBW	30 kHz		
SWT	34 ms	Unit	dBm



Test Data – Spurious Emissions at Antenna Terminals

Spurs

WCDMA



Test Data – Spurious Emissions at Antenna Terminals


LTE

Lower Edge



Ref Lvl
40 dBm

RBW 30 kHz RF Att 30 dB
VBW 30 kHz
SWT 28 ms Unit dBm



Test Data – Spurious Emissions at Antenna Terminals


LTE

Upper Edge



Ref Lvl
40 dBm


RBW 30 kHz RF Att 30 dB
VBW 30 kHz
SWT 28 ms Unit dBm



Test Data – Spurious Emissions at Antenna Terminals

Spurs


LTE



Test Data – Spurious Emissions at Antenna Terminals

Lower Edge

CDMA



Test Data – Spurious Emissions at Antenna Terminals


Upper Edge

CDMA



Ref Lvl
40 dBm


RBW	30 kHz	RF Att	30 dB
VBW	30 kHz		
SWT	14 ms	Unit	dBm



Test Data – Spurious Emissions at Antenna Terminals

CDMA

Spurs



Section 6. Field Strength of Spurious

NAME OF TEST: Field Strength of Spurious Emissions	PARA. NO.: 27.53
TESTED BY: David Light	DATE: 24 May 2011

Test Results: Complies.**Test Data:** The spectrum was searched from 30 MHz to the tenth harmonic of the carrier. There were no emissions detected above the noise floor which was at least 20 dB below the specification limit.

RBW=VBW=100 kHz below 1000 MHz

RBW=VBW=1 MHz above 1000 MHz

Peak detector

Equipment Used: 1767-1484-1485-1016-993-791-1763**Measurement Uncertainty:** +/-1.7 dB**Temperature:** 24 °C**Relative Humidity:** 49 %

Section 7. Test Equipment List

Asset Tag	Description	Manufacturer	Model	Serial #	Last Cal	Next Cal
993	Antenna, Horn	A.H. Systems	SAS-200/571	162	09-Sep-2009	09-Sep-2011
1016	Preamplifier	Hewlett Packard	8449A	2749A00159	19-Jun-2010	19-Jun-2011
1082	Cable	Astrolab	32027-2- 29094-72TC		N/R	
1469	Attenuator,	MCL Inc.	BW-S10W2 10db-2WDC		N/R	
1472	Attenuator,	Omni Spectra	20600-20db		N/R	
1484	Cable	Storm	PR90-010- 072		19-Jun-2010	19-Jun-2011
1485	Cable	Storm	PR90-010- 216		19-Jun-2010	19-Jun-2011
1763	Antenna, Bilog	Schaffner	CBL 6111D	22926	11-Feb-2011	11-Feb-2012
1767	Receiver	Rohde & Schwartz	ESIB26	837491/0002	01-Dec-2010	01-Dec-2011
791	Pre Amplifier	Nemko, USA	CRA69 321003 9605	119	19-May-2011	19-May-2012

ANNEX A - TEST DETAILS

NAME OF TEST: RF Power Output**PARA. NO.: 2.1046**

Minimum Standard: Para. No.27.53(d)(1). The power of each fixed or base station transmitting in the 2110-2155 MHz band and located in any county with population density of 100 or fewer persons per square mile, based upon the most recently available population statistics from the Bureau of the Census, is limited to a peak equivalent isotropically radiated power (EIRP) of 3280 watts. The power of each fixed or base station transmitting in the 2110-2155 MHz band from any other location is limited to a peak EIRP of 1640 watts. A licensee operating a base or fixed station utilizing a power of more than 1640 watts EIRP must coordinate such operations in advance with all Government and non-Government satellite entities in the 2025-2110 MHz band. Operations above 1640 watts EIRP must also be coordinated in advance with the following licensees within 120 kilometers (75 miles) of the base or fixed station: all Broadband Radio Service (BRS) licensees authorized under Part 27 in the 2155-2160 MHz band and all AWS licensees in the 2110-2155 MHz band.

Method Of Measurement:Detachable Antenna:

The channel power integrated across the carrier's bandwidth at antenna terminals is measured using a spectrum analyzer. Power output is measured with the maximum rated input level.

Integral Antenna:

The antenna substitution method is used to determine the equivalent radiated power at spurious frequencies. The spurious emissions are measured at a distance of 3 meters. The EUT is then replaced with a reference substitution antenna with a known gain referenced to an isotropic radiator. This antenna is fed with a signal at the spurious frequency. The level of the signal is adjusted to repeat the previously measured level. The resulting eirp is the signal level fed to the reference antenna corrected for gain referenced to an isotropic radiator.

NAME OF TEST: Occupied Bandwidth

PARA. NO.: 2.1049

Minimum Standard: Input/Output

Method Of Measurement:

CDMA

Spectrum analyzer settings:

RBW=VBW=30 kHz

Span: 5 MHz

Sweep: Auto

GSM / EDGE

RBW=VBW= 3 kHz

Span: 1 MHz

Sweep: Auto

TDMA

RBW=VBW= 1 kHz

Span: 1 MHz

Sweep: Auto

W-CDMA

RBW=VBW= 50 kHz

Span: 10 MHz

Sweep: Auto

NAME OF TEST: Spurious Emission at Antenna Terminals PARA. NO.: 27.53

Minimum Standard: Para. No.27.53(g) For operations in the 1710-1755 MHz and 2110-2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.

Method Of Measurement:

Spectrum analyzer settings:

CDMA

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 30 kHz (< 1MHz from Band Edge)
VBW: $\geq$ RBW
Sweep: Auto
Video Avg: 6 Sweeps

GSM / EDGE

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 3 kHz (< 1 MHz from Band Edge)
VBW: $\geq$ RBW
Sweep: Auto
Video Avg: Disabled

TDMA

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 3 kHz (< 1 MHz from Band Edge)
VBW: $\geq$ RBW
Sweep: Auto
Video Avg: Disabled

W-CDMA

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 50 kHz (< 1MHz from Band Edge)
VBW: $\geq$ RBW
Sweep: Auto
Video Avg: 6 Sweeps

To demonstrate compliance at band edges the frequency of the input signal is set to the lowest and highest assigned channel and the center frequency of the spectrum analyzer is set to the upper and lower edges of the appropriate frequency block.

NAME OF TEST: Field Strength of Spurious Radiation	PARA. NO.: 27.53
---	-------------------------

Minimum Standard:

Para. No.27.53(g) For operations in the 1710-1755 MHz and 2110-2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB.


Method of Measurement

ANSI/TIA -603-C-2004


The antenna substitution method is used to determine the equivalent radiated power at spurious frequencies. The spurious emissions are measured at a distance of 3 meters. The EUT is then replaced with a reference substitution antenna with a known gain referenced to an isotropic radiator. This antenna is fed with a signal at the spurious frequency. The level of the signal is adjusted to repeat the previously measured level. The resulting eirp is the signal level fed to the reference antenna corrected for gain referenced to an isotropic radiator.

ANNEX B - TEST DIAGRAMS



Para. No. 2.985 - R.F. Power Output



Para. No. 2.989 - Occupied Bandwidth



Para. No. 2.991 Spurious Emissions at Antenna Terminals



Para. No. 2.993 - Field Strength of Spurious Radiation

