

FCC MPE REPORT

FCC Certification

Applicant Name:
LG Electronics USA**Address:**
1000 Sylvan Avenue Englewood Cliffs New Jersey United
States 07632**Date of Issue:**

June 20, 2016

Test Site/Location:

HCT CO., LTD., 74,Seoicheon-ro 578beon-gil, Majang-

myeo,Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Report No.: HCT-R-1606-F005-1**HCT FRN:** 0005866421**IC Recognition No.:** 5944A-5**FCC ID:** BEJ-LCW004**APPLICANT:** LG Electronics USA**Model(s):** LCW-004**EUT Type:** WLAN Module**Frequency Range:** 2412 MHz - 2462 MHz (2.4 GHz Band)

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)



Report prepared by
: Kyung Soo Kang
Test engineer of RF Team

Approved by
: Jong Seok Lee
Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1606-F005	June 10, 2016	- First Approval Report
HCT-R-1606-F005-1	June 20, 2016	- Revise the antenna peak gain

RF Exposure Statement

1. LIMITS

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	f/1500	30
1500 - 100.000.....	1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

3. RESULTS

*. 802.11b Mode

Max Peak output Power at antenna input terminal	22.4400	dBm
Max Peak output Power at antenna input terminal	175.388	mW
Prediction distance	20.00000	cm
Prediction frequency	2437.00000	MHz
Antenna Gain(Peak)	1.81000	dBi
Antenna Gain(numeric)	1.51705	-
Power density at prediction frequency (S)	0.052933	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.00000	mW/cm ²

*. 802.11g Mode

Max Peak output Power at antenna input terminal	24.6800	dBm
Max Peak output Power at antenna input terminal	293.765	mW
Prediction distance	20.00000	cm
Prediction frequency	2412.00000	MHz
Antenna Gain(Peak)	1.81000	dBi
Antenna Gain(numeric)	1.51705	-
Power density at prediction frequency (S)	0.088660	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.00000	mW/cm ²

*. 802.11n_HT20 Mode

Max Peak output Power at antenna input terminal	24.1100	dBm
Max Peak output Power at antenna input terminal	257.632	mW
Prediction distance	20.00000	cm
Prediction frequency	2412.00000	MHz
Antenna Gain(Peak)	1.81000	dBi
Antenna Gain(numeric)	1.51705	-
Power density at prediction frequency (S)	0.077755	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.00000	mW/cm ²