

Report Number: F690501/RF-RTL012953-1

TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: BEJ-LCW007

Equipment Under Test	:	WLAN Module	
Model Name	:	LCW-007	
Applicant	:	LG Electronics USA	
Manufacturer	:	LG Electronics Inc.	
Date of Receipt	:	2018.07.23	
Date of Test(s)	:	2018.07.26 ~ 2018.08.03	
Date of Issue	:	2018.08.10	

In the configuration tested, the EUT complied with the standards specified above.

Tested By:	2	Date:	2018.08.10	
	Nancy Park			
Technical Manager:	nec-	Date:	2018.08.10	
J	ungmin Yang			

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL012953-1

INDEX

Table of Contents	Page
1. General Information	3
2. RF Exposure Evaluation	5

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL012953-1

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

- Phone No. : +82 31 688 0901
- Fax No. : +82 31 688 0921

1.2. Details of Applicant

Applicant:LG Electronics USAAddress:1000 Sylvan Avenue, Englewood Cliffs, New Jersey, United States, 07632Contact Person:Han, Kyung-suPhone No.:+1 201 472 2623

1.3. Details of Manufacturer

Company : LG Electronics Inc. Address : 170, Seongsanpaechong-ro, Seongsan-gu, Changwon-si, Gyeongsangnam-do 51533, Korea

1.4. Description of EUT

Kind of Product	WLAN Module
Model Name	LCW-007
Power Supply	DC 5 V, DC 12 V (Dual)
Frequency Range 2 412 Mb ~ 2 462 Mb (11b/g/n_HT20), 2 422 Mb ~ 2 452 Mb (11n_HT40)	
Modulation Technique	DSSS, OFDM
Number of Channels	11 channels (11b/g/n_HT20), 7 channels (11n_HT40)
Antenna Type	PCB pattern antenna
Antenna Gain	1.81 dB i

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



1.5. Test report revision

Revision	Report number	Date of Issue	Description
0	F690501/RF-RTL012953	2018.08.06	Initial
1	F690501/RF-RTL012953-1	2018.08.10	Deleted the ISED standard

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

Frequency Range (쌘)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (ɪ⊮/cɪr)	Average Time	
	(A) Limits for	Occupational/Control	led Exposure		
0.3-3.0	614	1.63	*100	6	
3.0-30	1842/f	4.89/f	*900/f ²	6	
30-300	61.4	0.163	1.0	6	
300-1 500	-	-	f/300	6	
1 500-100 000	-	-	5	6	
(B) Limits for General Population/Uncontrolled Exposure					
0.3-1.34	614	1.63	*100	30	
1.34-30	824/f	2.19/f	*180/f ²	30	
30-300	27.5	0.073	0.2	30	
300-1 500	-	-	f/1500	30	
<u>1 500-100 000</u>	-	-	<u>1.0</u>	<u>30</u>	

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

2.1.1. Friis transmission formula: Pd = (Pout*G)/(4*pi*R²)

Where Pd = power density in mW/cm²

Pout = output power to antenna in mW

- G = gain of antenna in linear scale
- Pi = 3.1416

R = distance between observation point and center of the radiator in \mbox{cm}

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

WLAN (2.4G)	
- Maximum tune	up tolerance

Operating Frequency (쌘)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (n\/cm)	Limits (nW/cn²)
2 412 ~ 2 462	19	1.81	0.023 973	1

Remark;

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².

- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20 $\,\mathrm{cm}\,$ between the radiator and your body.
- The antenna gain of this transmitter is less than 6 dB i and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.

- End of the Test Report -

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.