

Report Number: F690501/RF-RTL014064 Page: of 168

# TEST REPORT

of

FCC Part 15 Subpart C §15.247 RSS-247 Issue 2, RSS-Gen Issue 5

FCC ID: BEJ-LCW007 IC Certification: 2703N-LCW007

Equipment Under Test : WLAN Module

Model Name : LCW-007

**FCC Applicant** : LG Electronics USA

**IC** Applicant : LG Electronics Inc.

Manufacturer : LG Electronics Inc.

Date of Receipt : 2019.06.19

Date of Test(s) : 2019.07.02 ~ 2019.07.10

Date of Issue : 2019.07.18

In the configuration tested, the EUT complied with the standards specified above

Tested By:

Date:

2017.07.18

**Jinhyoung Cho** 

**Technical** Manager:

Jungmin Yang

Date:

2017.07.18



of Report Number: F690501/RF-RTL014064 Page: 2 168

# **INDEX**

# **Table of Contents**

1. General Information	3
2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission	10
3. 6 dB Bandwidth 99% Bandwidth	116
4. Maximum Peak Conducted Output Power	143
5. Power Spectral Density	147
6. AC Power Line Conducted Emissions	161
7. Antenna Requirement	168



Report Number: F690501/RF-RTL014064 Page: 3 of 168

# 1. General Information

# 1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
  4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a>.

Phone No. : +82 31 688 0901 Fax No. : +82 31 688 0921

# 1.2. Details of Applicant

FCC Applicant : LG Electronics USA

FCC Address : 1000 Sylvan Avenue, Englewood Cliffs, New Jersey, United States, 07632

IC Applicant : LG Electronics Inc.

IC Address 170, Seongsanpaechong-ro, Seongsan-gu, Changwon-si, Gyeongsangnam-do

51533, Korea (Republic of)

Contact Person : Han, Kyung-su Phone No. : +2 201 472 2623

#### 1.3. Details of Manufacturer

Company : LG Electronics Inc.

Address : 170, Seongsanpaechong-ro, Seongsan-gu, Changwon-si, Gyeongsangnam-do 51533,

Korea

Factory Location: Korea, Indonesia

# 1.4. Description of EUT

Kind of Product	WLAN Module
Model Name	LCW-007
Power Supply	DC 5 V, DC 12 V (Dual Voltage)
Frequency Range	2 412 Mb ~ 2 462 Mb (11b/g/n_HT20) 2 422 Mb ~ 2 452 Mb (11n_HT40)
Modulation Technique	DSSS, OFDM
Number of Channels	11 channels (11b/g/n_HT20) 7 channels (11n_HT40)
Antenna Type	PCB pattern antenna
Antenna Gain	1.50 dB i



Report Number: F690501/RF-RTL014064 Page: 4 of 168

# 1.5. Test Equipment List

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Interval	Cal. Due
Signal Generator	R&S	SMR40	100272	Jun. 07, 2019	Annual	Jun. 07, 2020
Signal Generator	R&S	SMBV100A	255834	Jun. 10, 2019	Annual	Jun. 10, 2020
Spectrum Analyzer	R&S	FSV30	103210	Dec. 05, 2018	Annual	Dec. 05, 2019
Spectrum Analyzer	Agilent	N9020A	MY53421758	Sep. 21, 2018	Annual	Sep. 21, 2019
Attenuator	AEROFLEX / INMET	40AH2W-10	40G-2	Jun. 20, 2019	Annual	Jun. 20, 2020
High Pass Filter	Wainwright Instrument GmbH	WHK3.0/18G-10SS	344	May 21, 2019	Annual	May 21, 2020
High Pass Filter	Wainwright Instrument GmbH	WHNX7.5/26.5G-6SS	15	Jun. 05, 2019	Annual	Jun. 05, 2020
Low Pass Filter	Mini-Circuits	NLP-1200+	V 8979400903-2	Feb. 19, 2019	Annual	Feb. 19, 2020
Power Sensor	R&S	NRP-Z81	100748	Jun. 05, 2019	Annual	Jun. 05, 2020
DC Power Supply	R&S	HMP2020	019258024	Nov. 06, 2018	Annual	Nov. 06, 2019
Preamplifier	H.P.	8447F	2944A03909	Aug. 07, 2018	Annual	Aug. 07, 2019
Preamplifier	Agilent	8449B	3008A01932	Feb. 22, 2019	Annual	Feb. 22, 2020
Loop Antenna	Schwarzbeck Mess-Elektronik	FMZB 1519	1519-039	Aug. 23, 2017	Biennial	Aug. 23, 2019
Bilog Antenna	Schwarzbeck Mess-Elektronik	VULB 9163	01126	Mar. 26, 2018	Biennial	Mar. 26, 2020
Horn Antenna	R&S	HF906	100326	Feb. 14, 2018	Biennial	Feb. 14, 2020
Horn Antenna	Schwarzbeck Mess-Elektronik	BBHA 9170	BBHA9170431	Sep. 10, 2018	Biennial	Sep. 10, 2020
Test Receiver	R&S	ESU26	100109	Jan. 31, 2019	Annual	Jan. 31, 2020
Turn Table	Innco systems GmbH	DS 1200 S	N/A	N.C.R.	N/A	N.C.R.
Controller	Innco systems GmbH	CONTROLLER CO3000-4P	CO3000/963/383 30516/L	N.C.R.	N/A	N.C.R.
Antenna Mast	Innco systems GmbH	MA4640-XP-ET	MA4640/536/383 30516/L	N.C.R.	N/A	N.C.R.
Anechoic Chamber	SY Corporation	$L \times W \times H$ (9.6 m × 6.4 m × 6.6 m)	N/A	N.C.R.	N/A	N.C.R.
Test Receiver	R&S	ESU26	100109	Jan. 31, 2019	Annual	Jan. 31, 2020
Test Receiver	R&S	ESCI 7	100911	Feb. 20, 2019	Annual	Feb. 20, 2020
Two-Line V-Network	R&S	ENV216	100190	May 14, 2019	Annual	May 14, 2020
Shield Room	SY Corporation	$L \times W \times H$ (6.5 m × 3.5 m × 3.5 m)	N/A	N.C.R.	N/A	N.C.R.
Coaxial Cable	SUCOFLEX	104 (3 m)	MY3258414	Jul. 04, 2019	Semi- annual	Jan. 04, 2020
Coaxial Cable	SUCOFLEX	104 (10 m)	MY3145814	Jul. 04, 2019	Semi- annual	Jan. 04, 2020
Coaxial Cable	Rosenberger	LA1-C006-1500	131014 01/20	Feb. 28, 2019	Semi- annual	Aug. 28, 2019



Report Number: F690501/RF-RTL014064 Page: 5 of 168

# 1.6. Summary of Test Results

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part15 Subpart C, RSS-247 Issue 2, RSS-Gen Issue 5				
Section in FCC	Section in IC	Test Item(s)	Result	
15.205(a) 15.209 15.247(d)	RSS-247 Issue 2 5.5 RSS-Gen Issue 5 8.9	Transmitter Radiated Spurious Emissions and Conducted Spurious Emission	Complied	
15.247(a)(2)	RSS-247 Issue 2 5.2(a) RSS-Gen Issue 5 6.7	6 dB Bandwidth & 99 % Bandwidth	Complied	
15.247(b)(3)	RSS-247 Issue 2 5.4(d)	Maximum Peak Conducted Output Power	Complied	
15.247(e)	RSS-247 Issue 2 5.2(b)	Power Spectral Density	Complied	
15.207	RSS-Gen Issue 5 8.8	AC Power Line Conducted Emissions	Complied	

# 1.7. Test Procedure(s)

The measurement procedures described in the American National Standard of Procedure for Compliance Testing of unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 15.247 Meas Guidance v05r02 were used in the measurement of the DUT.

#### 1.8. Sample Calculation

Where relevant, the following sample calculation is provided:

# 1.8.1. Conducted Test

Offset value (dB) = Attenuator (dB) + Cable loss (dB)

#### 1.8.2. Radiation Test

Field strength level ( $dB\mu V/m$ ) = Measured level ( $dB\mu V$ ) + Antenna factor (dB) + Cable loss (dB) - Amplifier gain (dB)



Report Number: F690501/RF-RTL014064 Page: 6 of 168

# 1.9. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
RF Output Power	<b>± 0.52</b> dB
Occupied Bandwidth	± 9.66 kHz
Power Spectral Density	<b>± 0.41</b> dB
Conducted Spurious Emission	<b>± 0.76</b> dB
AC Conducted Emission	± <b>3.30</b> dB
Radiated Emission, 9 kHz to 30 MHz	<b>± 3.59</b> dB
Radiated Emission, below 1 @z	± 5.88 dB
Radiated Emission, above 1 @z	<b>± 5.94</b> dB

Uncertainty figures are valid to a confidence level of 95 %.

# 1.10. Test Report Revision

Revision	Report Number Date of Issue		Description	
0	F690501/RF-RTL014064	2019.07.18	Initial	



Report Number: F690501/RF-RTL014064 Page: 7 of 168

# 1.11. Duty Cycle of EUT

Regarding to KDB 558074 D01 15.247 Meas Guidance v05r02, 6, the maximum duty cycles of all modes were investigated and set the spectrum analyzer as below;

Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100.


Mode	Data Rate (Mbps)	Duty Cycle (%)	Correction Factor (dB)
11b	1	98.96	0.05
11g	6	94.08	0.27
11n_HT20	MCS0	93.61	0.29
11n_HT40	MCS0	87.84	0.56

#### Remark:

- 1. As measured duty cycles of EUT, all of mode and data rate keep constant period and are converted to log scale (power averaging) to compensate correction factor to result of average test items.
- 2. Duty Cycle (%) =  $(Tx \text{ on time } / Tx \text{ on + off time}) \times 100$
- 3. Correction factor (dB) = 10 log (1 / Duty Cycle)

#### - Test plots


802.11b






Report Number: F690501/RF-RTL014064 Page: 8 of 168

#### 802.11g




#### 802.11n\_HT20





Report Number: F690501/RF-RTL014064 Page: 9 of 168

#### 802.11n\_HT40






Report Number: F690501/RF-RTL014064 Page: 10 of 168

# 2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission


# 2.1. Test Setup

# 2.1.1. Transmitter Radiated Spurious Emissions

The diagram below shows the test setup that is utilized to make the measurements for emission from 9  $\,\mathrm{kll}$  to 30  $\,\mathrm{ml}$  emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 \( \mathref{M} \) to 1 \( \mathref{M} \) emissions.



The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.


 SGS Korea Co., Ltd. (Gunpo Laboratory)
 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
 <a href="http://www.sgsgroup.kr">http://www.sgsgroup.kr</a>

 RTT5041-19(2019.04.24)(1)
 Tel. +82 31 428 5700 / Fax. +82 31 427 2370
 A4(210 mm x 297 mm)



F690501/RF-RTL014064 Report Number: Page: 11 of 168

The diagram below shows the test setup that is utilized to make the measurements for emission .The or 40 GHz, whichever is lower.





Report Number: F690501/RF-RTL014064 Page: 12 of 168

# 2.1.2. Conducted Spurious Emission



#### 2.2. Limit

#### 2.2.1. FCC

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section §15.209(a) is not required. In addition, radiated emission which fall in the restricted bands, as defined in section §15.205(a), must also comply with the radiated emission limits specified in section §15.205(c)).

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (쌘)	Field Strength (	Measurement Distance (Meters)
0.009-0.490	2 400/F(kHz)	300
0.490-1.705	24 000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

<sup>\*\*</sup> Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 Mb, 76-88 Mb, 174-216 Mb or 470-806 Mb. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.



Report Number: F690501/RF-RTL014064 Page: 13 of 168

#### 2.2.2. IC

According to RSS-247 Issue 2, 5.5, in any 100 \( \text{klz} \) bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 \( \text{dB} \) below that in the 100 \( \text{klz} \) bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 \( \text{dB} \) instead of 20 \( \text{dB} \). Attenuation below the general field strength limits specified in RSS-Gen is not required.

According to RSS-Gen Issue 5, 8.9, except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

Frequency (账)	Field Strength (μV/m at 3 m)
30-88	100
88-216	150
216-960	200
Above 960	500

Table 6 – General Field Strength Limits at frequencies below 30 №

Frequency	Magnetic Field Strength (H-Field) (⊯/m)	Measurement Distance (meters)
9-490 kHz <sup>1</sup>	6.37/F (F in 세z)	300
490-1 705 kHz	63.7/F (F in klb)	30
1.705-30 Mb	0.08	30

Note<sup>1</sup>: The emission limits for the ranges 9-90 klb and 110-490 klb are based on measurements employing a linear average detector.



Report Number: F690501/RF-RTL014064 Page: 14 of 168

#### 2.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2013.

#### 2.3.1. Test Procedures for emission below 30 Mb

- 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
- 3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.

#### 2.3.2. Test Procedures for emission from above 30 Mb

- 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site below 1 ¾ and 1.5 meters above the ground at a 3 meter anechoic chamber test site above 1 ¾. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2. During performing radiated emission below 1 Gb, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 Gb, the EUT was set 3 meter away from the interference-receiving antenna.
- 3. The antenna is a bi-log antenna, a horn antenna and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



Report Number: F690501/RF-RTL014064 Page: 15 of 168

#### Note;

All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

- 1. Unwanted Emissions into Non-Restricted Frequency Bands
- The Reference Level Measurement refer to section 11.11.2 Set analyzer center frequency to DTS channel center frequency, SPAN  $\geq$  1.5 times the DTS bandwidth, the RBW = 100 kHz and VBW  $\geq$  3  $\times$  RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold.
- Unwanted Emissions Level Measurement refer to section 11.11.3 Set the center frequency and span to encompass frequency range to be measured, the RBW = 100  $\,\mathrm{kl}$  and  $\,\mathrm{VBW} \ge 3 \times \mathrm{RBW}$ , Detector = Peak, Sweep time = Auto couple, Trace = Max hold.
- 2. Unwanted Emissions into Restricted Frequency Bands
- Peak Power measurement procedure refer to section 11.12.2.4 Set RBW = as specified in Table 9, VBW ≥ 3 x RBW, Detector = Peak, Sweep time = auto, Trace = Max hold.

Table 9– RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1 000 MHz	100 kHz to 120 kHz
> 1 000 MHz	1 MHz

If the peak – detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

- Average Power measurements procedure refer to section 11.12.2.5.2 The EUT shall be configured to operate at the maximum achievable duty cycle. Measure the duty cycle D of the transmitter output signal as described in section 11.6. Set RBW = 1 Mb, VBW  $\geq$  3 x RBW, Detector = RMS, if span / (# of points in sweep)  $\leq$  (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied then the detector mode shall be set to peak.

Averaging type = power (i.e., RMS).

As an alternative the detector and averaging type may be set for linear voltage averaging.

Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used. Sweep time = auto, Perform a trace average of at least 100 traces.

A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:

- 1) If power averaging (rms) mode was used in step f), then the applicable correction factor is [10 log(1 / D)], where D is the duty cycle.
- 3) If a specific emission is demonstrated to be continuous (D ≥ 98 %) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.
- 3. Definition of DUT Axis.

Definition of the test orthogonal plan for EUT was described in the test setup photo. The test orthogonal plan of EUT is **X** – **axis** during radiation test.



Report Number: F690501/RF-RTL014064 Page: 16 of 168

# 2.3.3. Test Procedures for Conducted Spurious Emissions

All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

Per the guidance of ANSI C63.10-2013, section 11.11.1 & 11.11.2 & 11.11.3, the reference level for out of band emissions is established from the plots of this section since the band edge emissions are measured with a RBW of 100 kHz. This reference level is then used as the limit in subsequent plots for out of band spurious emissions shown in section 2.4.3. The limit for out of band spurious emission at the band edge is 20 dB below the fundamental emission level measured in a 100 kHz bandwidth.

#### 1. Conducted Emissions at Band Edge

- The Measurement refer to section 11.11.2

Set the center frequency and span to encompass frequency range to be measured, the RBW = 100 klb and VBW ≥ 3 x RBW, Detector = Peak, Sweep time = Auto couple, Trace mode = Max hold, The trace was allowed to stabilize.

#### 2. Conducted Spurious Emissions

- The Measurement refer to section 11.11.3

Start frequency was set to 9 № and stop frequency was set to 25 № (separated into two plots per channel), RBW = 1 №, VBW ≥ 3 x RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold, The trace was allowed to stabilize.

#### 3. TDF function

- For plots showing conducted spurious emissions from 9  $\,\mathrm{kl\!k}$  to 25  $\,\mathrm{Gl\!k}$ , all path loss of wide frequency range was investigated and compensated to spectrum analyzer as TDF function. So, the reading values shown in plots were final result.



Report Number: F690501/RF-RTL014064 Page: 17 of 168

#### 2.4. Test Results

Ambient temperature : (23  $\pm$  1)  $^{\circ}$ C Relative humidity : 47  $^{\circ}$  R.H.

# 2.4.1. Radiated Spurious Emission below 1 000 Mb

The frequency spectrum from 9 klb to 1 000 klb was investigated. All reading values are peak values.

**Test Condition: DC 5 V** 

Radiated Emissions		Ant	Correctio	n Factors	Total	Limi	it	
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
32.75	46.40	Peak	V	16.10	-26.90	35.60	40.00	4.40
49.93	38.30	Peak	V	20.30	-26.43	32.17	40.00	7.83
87.68	46.20	Peak	Н	14.20	-25.34	35.06	40.00	4.94
145.71	47.40	Peak	V	13.83	-24.93	36.30	43.50	7.20
305.93	45.60	Peak	Н	19.22	-24.07	40.75	46.00	5.25
506.76	40.30	Peak	Н	23.14	-22.63	40.81	46.00	5.19
Above 600.00	Not detected	-	-	-	-	-	-	-

Test Condition: DC 12 V

Test Conditi	on: DC 12 V							
Radia	ated Emissio	ns	Ant	Correctio	n Factors	Total	Limit	
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
32.75	47.10	Peak	V	16.10	-26.90	36.30	40.00	3.70
87.47	45.90	Peak	Н	14.14	-25.36	34.68	40.00	5.32
145.35	45.40	Peak	V	13.87	-24.94	34.33	43.50	9.17
302.85	43.60	Peak	Н	19.20	-24.00	38.80	46.00	7.20
504.54	38.80	Quasi Peak	Н	23.09	-22.60	39.29	46.00	6.71
793.43	33.90	Peak	Н	26.67	-22.30	38.27	46.00	7.73
Above 800.00	Not detected	-	-	-	-	-	-	-




Report Number: F690501/RF-RTL014064 Page: 18 of 168

#### Remark;


- 1. Spurious emissions for all channels were investigated and almost the same below 1 @lb.
- Reported spurious emissions are in 11g / 6Mbps / Low channel as worst case among 2.
- other modes.
- 3. Radiated spurious emission measurement as below. (Actual = Reading + AF + AMP + CL)
- 4. According to §15.31(o), emission levels are not report much lower than the limits by over 20 dB.

# - Test plots

#### **Test Condition: DC 5 V**




# **Test Condition: DC 12 V**





Report Number: F690501/RF-RTL014064 Page: 19 of 168





Report Number: F690501/RF-RTL014064 Page: 20 of 168

# 2.4.2. Radiated Spurious Emission above 1 000 Mb

The frequency spectrum above 1 000 Mb was investigated. All reading values are peak and average values.

**Test Condition: DC 5 V** 

DSSS: 802.11b (1 Mbps)

Low Channel (2 412 Mb)

Radia	ated Emissic	ons	Ant.	Corre	ection Fact	ors	Total	Lim	it
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 310.00	48.01	Peak	Н	27.82	-24.94	-	50.89	74.00	23.11
*2 310.00	37.63	Average	Н	27.82	-24.94	-	40.51	54.00	13.49
*2 387.75	53.96	Peak	Н	27.98	-24.81	ı	57.13	74.00	16.87
*2 387.75	43.82	Average	Н	27.98	-24.81	ı	46.99	54.00	7.01
*2 390.00	53.38	Peak	Н	27.98	-24.80	-	56.56	74.00	17.44
*2 390.00	43.03	Average	Н	27.98	-24.80	-	46.21	54.00	7.79

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (畑)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBµV/m)	Margin (dB)
*4 824.04	45.41	Peak	Н	32.54	-22.99	-	54.96	74.00	19.04
*4 823.90	42.79	Average	Н	32.54	-22.99	-	52.34	54.00	1.66
Above 4 900.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL014064 Page: 21 of 168

#### Middle Channel (2 437 Mb)

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*7 310.75	41.58	Peak	V	35.84	-20.21	-	57.21	74.00	16.79
*7 310.15	36.47	Average	V	35.84	-20.21	-	52.10	54.00	1.90
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-

# High Channel (2 462 Mb)

Radia	ated Emissic	ons	Ant.	Correction Factors			Total	Lim	it
Frequency (脈)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 483.50	53.61	Peak	Н	28.00	-24.67	-	56.94	74.00	17.06
*2 483.50	42.70	Average	Н	28.00	-24.67	-	46.03	54.00	7.97
*2 484.14	54.58	Peak	Н	28.00	-24.67	-	57.91	74.00	16.09
*2 483.90	42.19	Average	Н	28.00	-24.67	-	45.52	54.00	8.48
*2 500.00	50.87	Peak	Н	28.00	-24.66	-	54.21	74.00	19.79
*2 500.00	39.08	Average	Н	28.00	-24.66	-	42.42	54.00	11.58

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (畑)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*7 386.00	42.91	Peak	V	36.07	-20.05	-	58.93	74.00	15.07
*7 385.05	36.42	Average	V	36.07	-20.05	-	52.44	54.00	1.56
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL014064 Page: 22 of 168

# OFDM: 802.11g (6 Mbps)

Low Channel (2 412 Mb)

Radia	ated Emissic	ons	Ant.	Corre	ection Fact	ors	Total	Lim	it
Frequency (쌢)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 310.00	48.60	Peak	Н	27.82	-24.94	-	51.48	74.00	22.52
*2 310.00	38.94	Average	Н	27.82	-24.94	0.27	42.09	54.00	11.91
*2 388.14	63.93	Peak	Н	27.98	-24.81	-	67.10	74.00	6.90
*2 387.49	46.39	Average	Н	27.97	-24.81	0.27	49.82	54.00	4.18
*2 390.00	63.89	Peak	Н	27.98	-24.80	-	67.07	74.00	6.93
*2 390.00	47.24	Average	Н	27.98	-24.80	0.27	50.69	54.00	3.31

Radia	ated Emissio	ns	Ant.	Corr	Correction Factors			Limit	
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

# Middle Channel (2 437 Mb)

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (脈)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*7 304.84	45.65	Peak	V	35.82	-20.22	-	61.25	74.00	12.75
*7 306.66	32.85	Average	V	35.83	-20.22	0.27	48.73	54.00	5.27
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL014064 Page: 23 of 168

# High Channel (2 462 账)

Radia	ated Emissic	ons	Ant.	Corre	ection Fact	tors	Total	Lim	it
Frequency (脈)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 483.50	54.52	Peak	Н	28.00	-24.67	-	57.85	74.00	16.15
*2 483.50	44.56	Average	Н	28.00	-24.67	0.27	48.16	54.00	5.84
*2 484.44	55.10	Peak	Н	28.00	-24.67	-	58.43	74.00	15.57
*2 483.78	44.57	Average	Н	28.00	-24.67	0.27	48.17	54.00	5.83
*2 500.00	50.26	Peak	Н	28.00	-24.66	-	53.60	74.00	20.40
*2 500.00	40.55	Average	Н	28.00	-24.66	0.27	44.16	54.00	9.84

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*7 380.54	44.53	Peak	٧	36.06	-20.05	-	60.54	74.00	13.46
*7 384.74	31.92	Average	V	36.07	-20.05	0.27	48.21	54.00	5.79
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL014064 Page: 24 of 168

# OFDM: 802.11n\_HT20 (MCS0)

Low Channel (2 412 Mb)

LOW GHAINIO	SW Charmer (2 412 mg)											
Radia	ated Emissio	ons	Ant.	Corre	ection Fact	ors	Total	Lim	it			
Frequency (쌢)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)			
*2 310.00	48.01	Peak	Н	27.82	-24.94	-	50.89	74.00	23.11			
*2 310.00	37.62	Average	Н	27.82	-24.94	0.29	40.79	54.00	13.21			
*2 382.03	63.09	Peak	Н	27.96	-24.81	-	66.24	74.00	7.76			
*2 382.68	43.90	Average	Н	27.97	-24.81	0.29	47.35	54.00	6.65			
*2 390.00	66.24	Peak	Н	27.98	-24.80	-	69.42	74.00	4.58			
*2 390.00	47.04	Average	Н	27.98	-24.80	0.29	50.51	54.00	3.49			

Radia	ated Emissio	ns	Ant.	Corr	Correction Factors			Lir	nit
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

# Middle Channel (2 437 Mb)

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*7 318.14	39.47	Peak	٧	35.87	-20.18	-	55.16	74.00	18.84
*7 313.94	25.02	Average	V	35.86	-20.20	0.29	40.97	54.00	13.03
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL014064 Page: 25 of 168

# High Channel (2 462 账)

Radia	ated Emissic	ons	Ant.	Corre	ection Fact	ors	Total	Lim	it
Frequency (脈)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	<b>DF</b> (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 483.50	63.82	Peak	Н	28.00	-24.67	-	67.15	74.00	6.85
*2 483.50	43.14	Average	Н	28.00	-24.67	0.29	46.76	54.00	7.24
*2 484.08	62.21	Peak	Н	28.00	-24.67	-	65.54	74.00	8.46
*2 484.08	44.55	Average	Н	28.00	-24.67	0.29	48.17	54.00	5.83
*2 500.00	52.47	Peak	Н	28.00	-24.66	-	55.81	74.00	18.19
*2 500.00	39.28	Average	Н	28.00	-24.66	0.29	42.91	54.00	11.09

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*7 392.93	43.74	Peak	٧	36.09	-20.04	-	59.79	74.00	14.21
*7 380.61	28.65	Average	V	36.06	-20.05	0.29	44.95	54.00	9.05
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL014064 Page: 26 of 168

# OFDM: 802.11n\_HT40 (MCS0)

Low Channel (2 422 Mb)

Zow Onamio	(								
Radia	ated Emissic	ons	Ant.	Corre	ection Fact	ors	Total	Lim	it
Frequency (쌢)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 310.00	47.71	Peak	Н	27.82	-24.94	-	50.59	74.00	23.41
*2 310.00	37.53	Average	Н	27.82	-24.94	0.56	40.97	54.00	13.03
*2 388.20	61.16	Peak	Н	27.98	-24.81	-	64.33	74.00	9.67
*2 388.48	47.32	Average	Н	27.98	-24.81	0.56	51.05	54.00	2.95
*2 390.00	58.79	Peak	Н	27.98	-24.80	-	61.97	74.00	12.03
*2 390.00	47.41	Average	Н	27.98	-24.80	0.56	51.15	54.00	2.85

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (雕)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*7 282.60	49.62	Peak	V	35.77	-20.16	-	65.23	74.00	8.77
*7 267.00	36.00	Average	V	35.73	-20.09	0.56	52.20	54.00	1.80
Above 7 300.00	Not detected	-	-	-	-	-	-	-	-

# Middle Channel (2 437 Mb)

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL014064 Page: 27 of 168

# High Channel (2 452 账)

Radia	ated Emissic	ons	Ant.	Corre	ection Fact	ors	Total	Lim	it
Frequency (脈)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	<b>DF</b> (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 483.50	57.03	Peak	Н	28.00	-24.67	ı	60.36	74.00	13.64
*2 483.50	42.81	Average	Н	28.00	-24.67	0.56	46.70	54.00	7.30
*2 485.36	56.67	Peak	Н	28.00	-24.67	-	60.00	74.00	14.00
*2 484.03	42.79	Average	Н	28.00	-24.67	0.56	46.68	54.00	7.32
*2 500.00	48.90	Peak	Н	28.00	-24.66	-	52.24	74.00	21.76
*2 500.00	39.22	Average	Н	28.00	-24.66	0.56	43.12	54.00	10.88

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL014064 Page: 28 of 168

Test Condition: DC 12 V DSSS: 802.11b (1 Mbps)

Low Channel (2 412 Mb)

Radia	ated Emissic	ons	Ant.	Corre	ection Fact	ors	Total	Lim	it
Frequency (쌢)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 310.00	47.65	Peak	Н	27.82	-24.94	-	50.53	74.00	23.47
*2 310.00	37.64	Average	Н	27.82	-24.94	-	40.52	54.00	13.48
*2 386.06	54.10	Peak	Н	27.97	-24.81	-	57.26	74.00	16.74
*2 387.10	44.10	Average	Н	27.97	-24.81	-	47.26	54.00	6.74
*2 390.00	53.25	Peak	Н	27.98	-24.80	-	56.43	74.00	17.57
*2 390.00	43.60	Average	Н	27.98	-24.80	-	46.78	54.00	7.22

Radia	ated Emissio	ns	Ant.	Corr	Correction Factors			Lir	nit
Frequency (畑)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*4 823.88	45.44	Peak	V	32.54	-22.99	-	54.99	74.00	19.01
*4 823.96	42.84	Average	V	32.54	-22.99	-	52.39	54.00	1.61
Above 4 900.00	Not detected	-	-	-	-	-	-	-	-

# Middle Channel (2 437 Mb)

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*7 310.90	41.86	Peak	٧	35.84	-20.21	-	57.49	74.00	16.51
*7 309.80	36.53	Average	V	35.84	-20.21	-	52.16	54.00	1.84
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL014064 Page: 29 of 168

# High Channel (2 462 账)

Radia	ated Emissic	ons	Ant.	Corre	Correction Factors			Lim	it
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 483.50	54.06	Peak	Н	28.00	-24.67	-	57.39	74.00	16.61
*2 483.50	42.04	Average	Н	28.00	-24.67	-	45.37	54.00	8.63
*2 484.08	54.14	Peak	Н	28.00	-24.67	-	57.47	74.00	16.53
*2 484.02	42.41	Average	Н	28.00	-24.67	-	45.74	54.00	8.26
*2 500.00	50.07	Peak	Н	28.00	-24.66	-	53.41	74.00	20.59
*2 500.00	39.08	Average	Н	28.00	-24.66	-	42.42	54.00	11.58

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*7 385.85	41.90	Peak	٧	36.07	-20.05	-	57.92	74.00	16.08
*7 384.85	36.63	Average	V	36.07	-20.05	-	52.65	54.00	1.35
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL014064 Page: 30 of 168

# OFDM: 802.11g (6 Mbps)

Low Channel (2 412 Mb)

Radia	ated Emissic	ons	Ant.	Corre	ection Fact	ors	Total	Lim	it
Frequency (쌢)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 310.00	49.99	Peak	Н	27.82	-24.94	-	52.87	74.00	21.13
*2 310.00	38.23	Average	Н	27.82	-24.94	0.27	41.38	54.00	12.62
*2 388.01	64.14	Peak	Н	27.98	-24.81	-	67.31	74.00	6.69
*2 388.40	47.16	Average	Н	27.98	-24.81	0.27	50.60	54.00	3.40
*2 390.00	62.87	Peak	Н	27.98	-24.80	-	66.05	74.00	7.95
*2 390.00	47.18	Average	Н	27.98	-24.80	0.27	50.63	54.00	3.37

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

# Middle Channel (2 437 Mb)

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (脈)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*7 304.49	45.23	Peak	٧	35.82	-20.23	-	60.82	74.00	13.18
*7 311.35	32.85	Average	V	35.85	-20.20	0.27	48.77	54.00	5.23
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL014064 Page: 31 of 168

# High Channel (2 462 账)

Radia	ated Emissic	ons	Ant.	Corre	ection Fact	tors	Total	Lim	it
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	<b>DF</b> (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 483.50	55.51	Peak	Н	28.00	-24.67	-	58.84	74.00	15.16
*2 483.50	42.52	Average	Н	28.00	-24.67	0.27	46.12	54.00	7.88
*2 484.26	55.23	Peak	Н	28.00	-24.67	-	58.56	74.00	15.44
*2 484.26	43.18	Average	Н	28.00	-24.67	0.27	46.78	54.00	7.22
*2 500.00	50.63	Peak	Н	28.00	-24.66	-	53.97	74.00	20.03
*2 500.00	40.75	Average	Н	28.00	-24.66	0.27	44.36	54.00	9.64

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*7 380.12	45.37	Peak	٧	36.06	-20.05	-	61.38	74.00	12.62
*7 382.50	32.55	Average	V	36.07	-20.05	0.27	48.84	54.00	5.16
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL014064 Page: 32 of 168

# OFDM: 802.11n\_HT20 (MCS0)

Low Channel (2 412 Mb)

Zow Onamio									
Radia	ated Emissic	ons	Ant.	Corre	ection Fact	ors	Total	Lim	it
Frequency (쌢)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 310.00	47.60	Peak	Н	27.82	-24.94	-	50.48	74.00	23.52
*2 310.00	36.96	Average	Н	27.82	-24.94	0.29	40.13	54.00	13.87
*2 383.07	62.82	Peak	Н	27.97	-24.81	-	65.98	74.00	8.02
*2 389.31	46.97	Average	Н	27.98	-24.81	0.29	50.43	54.00	3.57
*2 390.00	67.07	Peak	Н	27.98	-24.80	-	70.25	74.00	3.75
*2 390.00	47.25	Average	Н	27.98	-24.80	0.29	50.72	54.00	3.28

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

# Middle Channel (2 437 Mb)

Radia	ated Emissio	ns	Ant.	Corr	Correction Factors			Lir	nit
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Above 1 000.00	Not detected	ı	-	-	-	ı	-	-	-



Report Number: F690501/RF-RTL014064 Page: 33 of 168

# High Channel (2 462 账)

Radia	ated Emissic	ons	Ant.	Corre	ection Fact	ors	Total	Lim	it
Frequency (脈)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	<b>DF</b> (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 483.50	62.68	Peak	Н	28.00	-24.67	-	66.01	74.00	7.99
*2 483.50	43.98	Average	Н	28.00	-24.67	0.29	47.60	54.00	6.40
*2 483.78	62.92	Peak	Н	28.00	-24.67	-	66.25	74.00	7.75
*2 483.96	45.55	Average	Н	28.00	-24.67	0.29	49.17	54.00	4.83
*2 500.00	51.83	Peak	Н	28.00	-24.66	-	55.17	74.00	18.83
*2 500.00	38.98	Average	Н	28.00	-24.66	0.29	42.61	54.00	11.39

Radia	ated Emissio	ns	Ant.	Corr	ection Fac	tors	Total	Lir	nit
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*7 392.65	43.07	Peak	٧	36.09	-20.04	-	59.12	74.00	14.88
*7 379.84	28.16	Average	V	36.06	-20.05	0.29	44.46	54.00	9.54
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL014064 Page: 34 of 168

# OFDM: 802.11n\_HT40 (MCS0)

Low Channel (2 422 Mb)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (쌢)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 310.00	47.95	Peak	Н	27.82	-24.94	-	50.83	74.00	23.17
*2 310.00	37.54	Average	Н	27.82	-24.94	0.56	40.98	54.00	13.02
*2 388.20	60.77	Peak	Н	27.98	-24.81	-	63.94	74.00	10.06
*2 388.34	46.45	Average	Н	27.98	-24.81	0.56	50.18	54.00	3.82
*2 390.00	58.66	Peak	Н	27.98	-24.80	-	61.84	74.00	12.16
*2 390.00	47.63	Average	Н	27.98	-24.80	0.56	51.37	54.00	2.63

Radiated Emissions			Ant.	Corr	ection Fac	tors	Total	Limit	
Frequency (雕)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*7 282.60	49.60	Peak	V	35.77	-20.16	-	65.21	74.00	8.79
*7 268.20	35.93	Average	V	35.73	-20.09	0.56	52.13	54.00	1.87
Above 7 300.00	Not detected	-	-	-	-	-	-	-	-

# Middle Channel (2 437 Mb)

Radiated Emissions			Ant.	Corr	ection Fac	tors	Total	Limit	
Frequency (雕)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBµV/m)	Margin (dB)
*7 313.20	38.53	Peak	V	35.85	-20.20	-	54.18	74.00	19.82
*7 314.00	26.26	Average	V	35.86	-20.20	0.56	42.48	54.00	11.52
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL014064 Page: 35 of 168

# High Channel (2 452 账)

Tigh Onamic (2 402 mb)									
Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (쌢)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 483.50	55.61	Peak	Н	28.00	-24.67	ı	58.94	74.00	15.06
*2 483.50	42.63	Average	Н	28.00	-24.67	0.56	46.52	54.00	7.48
*2 487.11	56.95	Peak	Н	28.00	-24.67	-	60.28	74.00	13.72
*2 485.15	43.21	Average	Н	28.00	-24.67	0.56	47.10	54.00	6.90
*2 500.00	49.25	Peak	Н	28.00	-24.66	-	52.59	74.00	21.41
*2 500.00	38.67	Average	Н	28.00	-24.66	0.56	42.57	54.00	11.43

Radiated Emissions			Ant.	Corr	ection Fac	tors	Total	Limit	
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

#### Remarks;

- 1. "\*" means the restricted band.
- 3. Radiated emissions measured in frequency above 1 000 Mb were made with an instrument using peak/average detector mode.
- 4. Actual = Reading + AF + AMP + CL + (DF).
- 5. According to § 15.31(o), emission levels are not reported much lower than the limits by over 20 dB.
- 6. The maximized peak measured value complies with the average limit, to perform an average measurement is unnecessary.



Report Number: F690501/RF-RTL014064 Page: 36 of 168

#### - Test plots


**Test Condition: DC 5 V** 

**DSSS: 802.11b (1 Mbps)** 

Low channel Band edge (Peak)



#### Low channel Band edge (Average)





Report Number: F690501/RF-RTL014064 Page: 37 of 168

#### High channel Band edge (Peak)



### High channel Band edge (Average)



The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

A4(210 mm × 297 mm)



Report Number: F690501/RF-RTL014064 Page: 38 of 168

#### OFDM: 802.11g (6 Mbps)

Low channel Band edge (Peak)



### Low channel Band edge (Average)





Report Number: F690501/RF-RTL014064 Page: 39 of 168

#### High channel Band edge (Peak)



### High channel Band edge (Average)





Report Number: F690501/RF-RTL014064 Page: 40 of 168

### OFDM: 802.11n\_HT20 (MCS0)

Low channel Band edge (Peak)



### Low channel Band edge (Average)





Report Number: F690501/RF-RTL014064 Page: 41 of 168

#### High channel Band edge (Peak)



### High channel Band edge (Average)





Report Number: F690501/RF-RTL014064 Page: 42 of 168

### OFDM: 802.11n\_HT40 (MCS0)

Low channel Band edge (Peak)



### Low channel Band edge (Average)





Report Number: F690501/RF-RTL014064 Page: 43 of 168

#### High channel Band edge (Peak)



### High channel Band edge (Average)





Report Number: F690501/RF-RTL014064 Page: 44 of 168

### **DSSS: 802.11b (1 Mbps)**

Low channel 2<sup>nd</sup> harmonic (Peak)




## Low channel 2<sup>nd</sup> harmonic (Average)






Report Number: F690501/RF-RTL014064 Page: 45 of 168

### Middle channel 3<sup>rd</sup> harmonic (Peak)



# Middle channel 3<sup>rd</sup> harmonic (Average)






Report Number: F690501/RF-RTL014064 Page: 46 of 168

## High channel 3<sup>rd</sup> harmonic (Peak)



## High channel 3<sup>rd</sup> harmonic (Average)





Report Number: F690501/RF-RTL014064 Page: 47 of 168

#### OFDM: 802.11g (6 Mbps)

Middle channel 3<sup>rd</sup> harmonic (Peak)



## Middle channel 3<sup>rd</sup> harmonic (Average)





Report Number: F690501/RF-RTL014064 Page: 48 of 168

## High channel 3<sup>rd</sup> harmonic (Peak)



## High channel 3<sup>rd</sup> harmonic (Average)






Report Number: F690501/RF-RTL014064 Page: 49 of 168

### OFDM: 802.11n\_HT20 (MCS0)

Middle channel 3<sup>rd</sup> harmonic (Peak)



## Middle channel 3<sup>rd</sup> harmonic (Average)





Report Number: F690501/RF-RTL014064 Page: 50 of 168

## High channel 3<sup>rd</sup> harmonic (Peak)



## High channel 3<sup>rd</sup> harmonic (Average)





Report Number: F690501/RF-RTL014064 Page: 51 of 168

### OFDM: 802.11n\_HT40 (MCS0)

Low channel 3<sup>rd</sup> harmonic (Peak)



Low channel 3<sup>rd</sup> harmonic (Average)





Report Number: F690501/RF-RTL014064 Page: 52 of 168

Test Condition: DC 12 V

**DSSS: 802.11b (1 Mbps)** 

Low channel Band edge (Peak)



## Low channel Band edge (Average)





Report Number: F690501/RF-RTL014064 Page: 53 of 168

#### High channel Band edge (Peak)



### High channel Band edge (Average)





Report Number: F690501/RF-RTL014064 Page: 54 of 168

#### OFDM: 802.11g (6 Mbps)

Low channel Band edge (Peak)



### Low channel Band edge (Average)





Report Number: F690501/RF-RTL014064 Page: 55 of 168

#### High channel Band edge (Peak)



### High channel Band edge (Average)



The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

A4(210 mm × 297 mm)



Report Number: F690501/RF-RTL014064 Page: 56 of 168

### OFDM: 802.11n\_HT20 (MCS0)

Low channel Band edge (Peak)



### Low channel Band edge (Average)





Report Number: F690501/RF-RTL014064 Page: 57 of 168

#### High channel Band edge (Peak)



### High channel Band edge (Average)





Report Number: F690501/RF-RTL014064 Page: 58 of 168

### OFDM: 802.11n\_HT40 (MCS0)

Low channel Band edge (Peak)



### Low channel Band edge (Average)





Report Number: F690501/RF-RTL014064 Page: 59 of 168

## High channel Band edge (Peak)



### High channel Band edge (Average)





Report Number: F690501/RF-RTL014064 Page: 60 of 168

### **DSSS: 802.11b (1 Mbps)**

Low channel 2<sup>nd</sup> harmonic (Peak)



# Low channel 2<sup>nd</sup> harmonic (Average)






Page: 61 of Report Number: F690501/RF-RTL014064 168

### Middle channel 3<sup>rd</sup> harmonic (Peak)



# Middle channel 3<sup>rd</sup> harmonic (Average)






Page: 62 of Report Number: F690501/RF-RTL014064 168

## High channel 3<sup>rd</sup> harmonic (Peak)



## High channel 3<sup>rd</sup> harmonic (Average)






Report Number: F690501/RF-RTL014064 Page: 63 of 168

#### OFDM: 802.11g (6 Mbps)

Middle channel 3<sup>rd</sup> harmonic (Peak)



## Middle channel 3<sup>rd</sup> harmonic (Average)





Report Number: F690501/RF-RTL014064 Page: 64 of 168

## High channel 3<sup>rd</sup> harmonic (Peak)



## High channel 3<sup>rd</sup> harmonic (Average)





Report Number: F690501/RF-RTL014064 Page: 65 of 168

### OFDM: 802.11n\_HT20 (MCS0)

High channel 3<sup>rd</sup> harmonic (Peak)



High channel 3<sup>rd</sup> harmonic (Average)



The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 http://www.sgsgroup.kr RTT5041-19(2019.04.24)(1) Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm × 297 mm)



Report Number: F690501/RF-RTL014064 Page: 66 of 168

### OFDM: 802.11n\_HT40 (MCS0)

Low channel 3<sup>rd</sup> harmonic (Peak)



Low channel 3<sup>rd</sup> harmonic (Average)






Report Number: F690501/RF-RTL014064 Page: 67 of 168

### Middle channel 3<sup>rd</sup> harmonic (Peak)



# Middle channel 3<sup>rd</sup> harmonic (Average)






Report Number: F690501/RF-RTL014064 Page: 68 of 168

#### 2.4.3. Plot of Conducted Spurious Emissions

**Test Condition: DC 5 V** 

DSSS: 802.11b (1 Mbps)

Low Channel




The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

 SGS Korea Co., Ltd. (Gunpo Laboratory)
 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
 <a href="http://www.sgsgroup.kr">http://www.sgsgroup.kr</a>

 RTT5041-19(2019.04.24)(1)
 Tel. +82 31 428 5700 / Fax. +82 31 427 2370
 A4(210 mm x 297 mm)




Report Number: F690501/RF-RTL014064 Page: 69 of 168






Report Number: F690501/RF-RTL014064 Page: 70 of 168

#### Middle Channel






of Report Number: F690501/RF-RTL014064 Page: 71 168






Report Number: F690501/RF-RTL014064 Page: 72 of 168

#### High Channel





of Report Number: F690501/RF-RTL014064 Page: 73 168






Report Number: F690501/RF-RTL014064 Page: 74 of 168


#### OFDM: 802.11g (6 Mbps)

#### Low Channel





of Report Number: F690501/RF-RTL014064 Page: 75 168





Report Number: F690501/RF-RTL014064 Page: 76 of 168

#### Middle Channel

