

Maximum Permissible Exposure (MPE)

Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1093 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-15000	/	/	1.0	30

F = frequency in MHz

* = Plane-wave equipment power density

Maximum Permissible Exposure (MPE) Evaluation

802.11b Power Table

Frequency (MHz)	Reading Power (dBm)	Cable Loss	Output Power (dBm)	Output Power (W)	Limit (W)
2412.00	16.70	0.00	16.70	0.04699	1
2437.00	16.66	0.00	16.66	0.04634	1
2462.00	16.62	0.00	16.62	0.04592	1

MPE Prediction (802.11b)

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	16.7	(dBm)
Maximum peak output power at antenna input terminal:	46.77351413	(mW)
Duty cycle:	100	(%)
Maximum Pav :	46.77351413	(mW)
Antenna gain (typical):	-0.22	(dBi)
Maximum antenna gain:	0.950604794	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	2412	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.0088501	(mW/cm ²)

Measurement Result

The predicted power density level at 20 cm is 0.00885 mW/cm². This is below the uncontrolled exposure limit of 1 mW/cm² at 2412MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。
This Test Report is issued by the Company under its General Conditions of Service which is available on request or accessible at http://www.sgs.com/terms_and_conditions.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this Test Report is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

802.11g Power Table

Frequency (MHz)	Reading Power (dBm)	Cable Loss	Output Power (dBm)	Output Power (W)	Limit (W)
2412.00	14.17	0.00	14.17	0.02612	1
2437.00	14.16	0.00	14.16	0.02606	1
2462.00	14.28	0.00	14.28	0.02679	1

MPE Prediction (802.11g)

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	14.28	(dBm)
Maximum peak output power at antenna input terminal:	26.79168325	(mW)
Duty cycle:	100	(%)
Maximum Pav :	26.79168325	(mW)
Antenna gain (typical):	-0.22	(dBi)
Maximum antenna gain:	0.950604794	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	2462	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.0050693	(mW/cm ²)

Measurement Result

The predicted power density level at 20 cm is 0.00507 mW/cm². This is below the uncontrolled exposure limit of 1 mW/cm² at 2462.

802.11n_20M Power Table (Worse case)

Frequency (MHz)	Reading Power (dBm)	Cable Loss	Output Power (dBm)	Output Power (W)	Limit (W)
2412.00	13.56	0.00	13.56	0.02270	1
2437.00	13.57	0.00	13.57	0.02275	1
2462.00	13.65	0.00	13.65	0.02317	1

MPE Prediction (802.11n_20M)

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	13.65	(dBm)
Maximum peak output power at antenna input terminal:	23.1739465	(mW)
Duty cycle:	100	(%)
Maximum Pav :	23.1739465	(mW)
Antenna gain (typical):	-0.22	(dBi)
Maximum antenna gain:	0.950604794	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	2462	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.0043848	(mW/cm ²)

Measurement Result

The predicted power density level at 20 cm is 0.00439 mW/cm². This is below the uncontrolled exposure limit of 1 mW/cm² at 2462.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。
This Test Report is issued by the Company under its General Conditions of Service which is available on request or accessible at http://www.sgs.com/terms_and_conditions.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this Test Report is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

802.11a Power Table

Frequency (MHz)	Reading Power (dBm)	Cable Loss	Output Power (dBm)	Output Power (W)	Limit (W)
5745.00	14.09	0.00	14.09	0.02564	1
5785.00	14.29	0.00	14.29	0.02685	1
5825.00	14.19	0.00	14.19	0.02624	1

MPE Prediction (802.11a)

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	14.29	(dBm)
Maximum peak output power at antenna input terminal:	26.85344446	(mW)
Duty cycle:	100	(%)
Maximum Pav :	26.85344446	(mW)
Antenna gain (typical):	5.53	(dBi)
Maximum antenna gain:	3.572728382	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5785	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.0190964	(mW/cm ²)

Measurement Result

The predicted power density level at 20 cm is 0.01910 mW/cm². This is below the uncontrolled exposure limit of 1 mW/cm² at 5785.

**802.11a/n_40M Power Table
(Worse case)**

Frequency (MHz)	Reading Power (dBm)	Cable Loss	Output Power (dBm)	Output Power (W)	Limit (W)
5755.00	13.54	0.00	13.54	0.02259	1
5795.00	13.62	0.00	13.62	0.02201	1

MPE Prediction (802.11n_40M)

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	13.62	(dBm)
Maximum peak output power at antenna input terminal:	23.01441817	(mW)
Duty cycle:	100	(%)
Maximum Pav :	23.01441817	(mW)
Antenna gain (typical):	5.53	(dBi)
Maximum antenna gain:	3.572728382	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5795	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.0163663	(mW/cm ²)

Measurement Result

The predicted power density level at 20 cm is 0.01637 mW/cm². This is below the uncontrolled exposure limit of 1 mW/cm² at 5795.