

EMC TEST REPORT

Test item : LCD TV Monitor
Model No. : 32CS460-UC
Order No. : 1201-00094
Date of receipt : 2012-01-20
Test duration : 2012-02-01 ~ 2012-02-04
Use of report : FCC CoC Marking
Date of Issue : 2012-02-07

Applicant : LG Electronics Inc.

9-1, Cheongho-ri, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 451-713, Korea

Test laboratory : Digital EMC Co., Ltd.

683-3, Yubang-Dong, Cheoin-Gu, Yongin-Si, Gyeonggi-Do, 449-080, Korea

Test specification : ANSI C 63.4:2003
FCC Part 15 Subpart B
(Type of Device : Class B Personal Computers
and Peripherals (JBP))

Test environment : Temperature : (18 ~ 20) °C,
Humidity : (28 ~ 34) % R.H.

Test result : Comply Not Comply

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose.


This test report shall not be reproduced except in full, without the written approval of DIGITAL EMC CO., LTD.

Tested by:



Assistant Manager
D.H.EUN

Reviewed by:



General Manager
C.H.LEE

The above test report is the accredited test results by Korea Laboratory Accreditation Scheme, which signed the ILAC-MRA.

PRESIDENT OF DIGITAL EMC CO., LTD.

CONTENTS

1. General Remarks	3
2. Test Laboratory	3
3. General Information of EUT	4
4. Test Summary	5
4.1 Applied standards and test results	5
4.2 Test environment and conditions	5
4.3 Test result Summary	5
5. Test Set-up and operation mode	6
5.1 Principle of Configuration Selection	6
5.2 Test Operation Mode	6
5.3 Support Equipment Used	6
6. Test Results : Emission	7
6.1 Conducted Disturbance	7
6.2 Radiated Disturbance	12
Appendix 1	26
List of Test and Measurement Instruments	26

1. General Remarks

This report contains the result of tests performed by:

DIGITAL EMC CO., LTD.

Address : 683-3, Yubang-Dong, Cheoin-Gu, Yongin-Si, Gyeonggi-Do, 449-080, Korea

<http://www.digitalemc.com>

Tel: +82-31-321-2664 Fax: +82-31-321-1664

2. Test Laboratory

Digital EMC Co., Ltd. Has been accredited / filed / authorized by the agencies listed in the following table;

Certificate	Nation	Agency	Code	Mark
Accreditation	Korea	KOLAS	393	ISO/IEC 17025
Site Filing	USA	FCC	101842 678747	Test Facility list & NSA Data
	Canada	IC	5740A-1 5740A-2	Test Facility list & NSA Data
	Japan	VCCI	C-1427 R-1364, R-3385 T-1442, G-338	Test Facility list & NSA Data
Certification	Korea	KC	KR0034	Test Facility list & NSA Data
	Germany	TUV	ROK1028C	ISO/IEC 17025

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the "General requirements for the competent of calibration and testing laboratory".

3. General Information of EUT

Model No.	32CS460-UC
EUT Type	LCD TV Monitor
Serial No	NONE
FCC ID	BEJ32CS460UC
Type of Sample Tested	Pre-Production
High Frequency	800 MHz
Rating	AC100-240 V~, 50/60 Hz, 1.1 A
Supplied Power for Test	AC120 V, 60 Hz
Applicant	LG Electronics Inc. 19-1, Cheongho-ri, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 451-713, Korea
Manufacturer	LG Electronics Inc. 19-1, Cheongho-ri, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 451-713, Korea

Resolution	Horizontal Frequency (KHz)	Vertical Frequency (Hz)
720x400	31.469	70.08
640x480	31.469	59.94
800x600	37.879	60.31
1024x768	48.363	60.00
1360x768	47.712	60.015
1280x1024	63.981	60.02
1920x1080	67.5	60.00

4. Test Summary

4.1 Applied standards and test results

Test Items	Applied Standards	Results
Conducted Disturbance	ANSI C63.4:2003	C
Radiated Disturbance	ANSI C63.4:2003	C
C=Comply N/C=Not Comply N/T=Not Tested N/A=Not Applicable		

The data in this test report are traceable to the national or international standards.

4.2 Test environment and conditions

Test Items	Test date (MM-DD)	Temp ()	Humidity (% R.H.)	Pressure (hPa)
Conducted Disturbance	02-01	18	34	-
Radiated Disturbance	02-03	20	31	
	02-04	19	28	

4.3 Test result Summary

(1) Conducted Emission(HDMI MODE)

Frequency [MHz]	Phase	Result [dB μ V]	Detector	Limit [dB μ V]	Margin [dB]
24.60300	N	40.6	Average	50.0	9.4

(2) Radiated Emission(USB MODE)

Frequency [MHz]	Pol.	Result [dB(μ V/m)]	Detector	Limit [dB(μ V/m)]	Margin [dB]
47.116	V	33.8	Quasi-Peak	40.0	6.2

5. Test Set-up and operation mode

5.1 Principle of Configuration Selection

Emission : The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

5.2 Test Operation Mode

- HDMI MODE – Resolution : 1920 x 1080 Resolution (Worst Case)
- USB MODE

5.3 Support Equipment Used

Unit	Model No.	Serial No.	Manufacturer	CABLE			Backshell	FCC ID
				Connect type	Length (m)	shield		
PC	VOSTRO430	9K77SBX	DELL	POWER	1.8	Non-shield	Plastic	DOC
				HDMI	1.8	Shield		
				AV	1.6	Non-shield		
				PS/2	1.6	Non-shield		
				PS/2	1.8	Non-shield		
KEYBOARD	SKG-210PB	TAKSB24503Y	MONITEREY INTERNATIONAL CORP	PS/2	1.6	Non-shield	Plastic	DOC
MOUSE	SML-510PB	TAKS903519Z	MONITEREY INTERNATIONAL CORP	PS/2	1.8	Non-shield	Plastic	DOC
CD/DVD PLAYER	DVP-NS92V	2000407	SONY EMCS	POWER	1.8	Non-shield	Plastic	DOC
				AV	1.6			
USB MEMORY	JEWERLY	N/A	AXXEN	USB	-	-	-	DOC

6. Test Results : Emission

6.1 Conducted Disturbance

6.1.1 Measurement Procedure

In the range of 0.15MHz to 30MHz, the conducted disturbance was measured and set-up was made accordance with **ANSI C63.4**.

If the EUT is table top equipment, it was placed on a wooden table with a height of 0.8m above the reference ground plane and 0.4m from the conducting wall of the shielded room.

Also if the EUT is floor-standing equipment, it was placed on a non-conducted support with a height up to 0.15m above the reference ground plane.

Connect the EUT's power source lines to the appropriate power mains / peripherals through the LISN. All the other peripherals are connected to the 2nd LISN, if any.

Unused measuring port of the LISN was resistively terminated by 50 ohm terminator.

The measuring port of the LISN for EUT was connected to spectrum analyzer.

Using conducted emission test software, the emissions were scanned with peak detector mode.

After scanning over the frequency range, suspected emissions were selected to perform final measurement. When performing final measurement, the receiver was used which has Quasi-Peak detector and Average detector.

By varying the configuration of the test sample and the cable routing it was attempted to maximize the emission.

For further description of the configuration refer to the picture of the test set-up.

6.1.2 Limit for Conducted Disturbance

(1) Conducted disturbance at mains ports.

Frequency range (MHz)	Limits dB(μ V)			
	Quasi-peak		Average	
	Class A	Class B	Class A	Class B
0.15 to 0.50	79	66 to 56	66	56 to 46
0.50 to 5	73	56	60	46
5 to 30		60		50

Note 1 The lower limit shall apply at the transition frequencies.
 Note 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

Test Result

< HDMI MODE >





Results of Conducted Emission

Digital EMC
 Date : 2012-02-01

Model No. : 32CS460-UC
 Type :
 Serial No. :
 Test Condition : HDMI

Reference No. :
 Power Supply : 120V 60Hz
 Temp/Humi. : 18 °C 34 % R.H.
 Operator :

Memo :
 LIMIT : CISPR22_B OP
 CISPR22_B AV



Results of Conducted Emission

Digital EMC
Date : 2012-02-01

Model No. :	32CS460-UC	Reference No. :	:
Type :	:	Power Supply :	120V 60Hz
Serial No. :	:	Temp/Humi. :	18 °C 34 % R.H.
Test Condition :	HDMI	Operator :	:
Memo :	:		

LIMIT : CISPR22_B QP
CISPR22_B AV

NO	FREQ [MHz]	READING		C. FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.15018	45.1	28.0	0.3	45.4	28.3	66.0	56.0	20.6	27.7	N
2	0.18429	37.0	33.0	0.2	37.2	33.2	64.3	54.3	27.1	21.1	N
3	0.20850	37.2	23.8	0.2	37.4	24.0	63.3	53.3	25.9	29.3	N
4	0.62918	33.9	27.0	0.2	34.1	27.2	56.0	46.0	21.9	18.8	N
5	0.94304	33.2	29.4	0.3	33.5	29.7	56.0	46.0	22.5	16.3	N
6	3.92200	36.0	29.7	0.4	36.4	30.1	56.0	46.0	19.6	15.9	N
7	6.53150	40.9	35.2	0.4	41.3	35.6	60.0	50.0	18.7	14.4	N
8	6.63550	40.4	34.4	0.4	40.8	34.8	60.0	50.0	19.2	15.2	N
9	24.60300	42.0	39.4	1.2	43.2	40.6	60.0	50.0	16.8	9.4	N
10	0.15012	47.8	32.5	0.3	48.1	32.8	66.0	56.0	17.9	23.2	L1
11	0.18410	37.0	32.9	0.2	37.2	33.1	64.3	54.3	27.1	21.2	L1
12	0.58750	29.8	12.4	0.2	30.0	12.6	56.0	46.0	26.0	33.4	L1
13	3.86600	35.1	29.8	0.4	35.5	30.2	56.0	46.0	20.5	15.8	L1
14	6.52950	40.9	36.9	0.4	41.3	37.3	60.0	50.0	18.7	12.7	L1
15	6.63350	40.4	36.1	0.4	40.8	36.5	60.0	50.0	19.2	13.5	L1

< USB MODE >





Results of Conducted Emission

Digital EMC
 Date : 2012-02-01

Model No.	: 32CS460-UC	Reference No.	:
Type	:	Power Supply	: 120V 60Hz
Serial No.	:	Temp/Humi.	: 18 °C 34 % R.H.
Test Condition	: USB	Operator	:

Memo :
 LIMIT : CISPR22_B OP
 CISPR22_B AV



Results of Conducted Emission

Digital EMC
Date : 2012-02-01

Model No. : 32CS460-UC
 Type :
 Serial No. :
 Test Condition : USB

Reference No. :
 Power Supply : 120V 60Hz
 Temp/Humi. : 18 'C 34 % R.H.
 Operator :

Memo :

LIMIT : CISPR22_B QP
 CISPR22_B AV

NO	FREQ [MHz]	READING		C. FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.15006	52.0	34.2	0.3	52.3	34.5	66.0	56.0	13.7	21.5	N
2	0.31401	37.3	25.4	0.2	37.5	25.6	59.9	49.9	22.4	24.3	N
3	0.51656	37.2	25.3	0.2	37.4	25.5	56.0	46.0	18.6	20.5	N
4	0.94301	35.4	29.9	0.3	35.7	30.2	56.0	46.0	20.3	15.8	N
5	3.38700	33.2	24.9	0.4	33.6	25.3	56.0	46.0	22.4	20.7	N
6	3.88150	34.1	26.7	0.4	34.5	27.1	56.0	46.0	21.5	18.9	N
7	6.42250	38.9	32.5	0.4	39.3	32.9	60.0	50.0	20.7	17.1	N
8	6.42100	38.1	31.1	0.4	38.5	31.5	60.0	50.0	21.5	18.5	N
9	25.75200	41.0	35.7	1.3	42.3	37.0	60.0	50.0	17.7	13.0	N
10	0.15012	52.3	34.6	0.3	52.6	34.9	66.0	56.0	13.4	21.1	L1
11	0.34150	35.5	24.4	0.3	35.8	24.7	59.2	49.2	23.4	24.5	L1
12	0.51650	36.7	23.7	0.2	36.9	23.9	56.0	46.0	19.1	22.1	L1
13	0.94324	32.5	28.3	0.3	32.8	28.6	56.0	46.0	23.2	17.4	L1
14	3.92150	34.9	26.6	0.4	35.3	27.0	56.0	46.0	20.7	19.0	L1
15	6.31650	38.0	33.2	0.4	38.4	33.6	60.0	50.0	21.6	16.4	L1
16	6.42300	38.9	34.7	0.4	39.3	35.1	60.0	50.0	20.7	14.9	L1

6.2 Radiated Disturbance

6.2.1 Measurement Procedure

The radiated disturbance was measured and set-up was made accordance with **ANSI C63.4**.

If the EUT is tabletop equipment, it was placed on a wooden table with a height of 0.8m above the reference ground plane and 3m away from the interference receiving antenna in the **10m semi-anechoic chamber**.

Also if the EUT is floor-standing equipment, it was placed on a non-conducted support with a height up to 0.15m above the reference ground plane.

Rotate the EUT from 0° to 360° and position the receiving antenna at heights from 1 to 4m above the reference ground plane continuously to determine associated with higher emission levels and record them.

The measurement was made in both the vertical and horizontal polarization, and the maximum value is presented in the report.

For below 1GHz frequency range, Quasi-Peak detector with 120kHz RBW was used.

Also Peak and Average detector with 1MHz RBW were used for above 1GHz frequency range.

For further description of the configuration refer to the picture of the test set-up.

6.2.2 Limit for Radiated Disturbance

- The test frequency range of Radiated Disturbance measurements are listed below.

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

(1) Limit for Radiated Emission below 1000MHz

Frequency range (MHz)	Class A Equipment (10m distance)	Class B Equipment (3m distance)
	Quasi-peak (dB μ V/m)	Quasi-peak (dB μ V/m)
30 to 88	39.1	40
88 to 216	43.5	43.5
216 to 960	46.4	46
960 to 1000	49.5	54

Note 1 The lower limit shall apply at the transition frequency.

Note 2 Additional provisions may be required for cases where interference occurs.

Note 3 According to 15.109(g), as an alternative to the radiated emission limit shown above, digital devices may be shown to comply with the standards(CISPR), Pub. 22 shown as below.

Frequency range (MHz)	Class A Equipment (10m distance)	Class B Equipment (10m distance)
	Quasi-peak (dB μ V/m)	Quasi-peak (dB μ V/m)
30 to 230	40	30
230 to 1000	47	37

(2) Limits for Radiated Emission above 1000MHz at a measuring distance of 3m

Frequency (GHz)	Class A Equipment		Class B Equipment	
	Peak (dB μ V/m)	Average (dB μ V/m)	Peak (dB μ V/m)	Average (dB μ V/m)
1 to 40	80	60	74	54

Test Result



< HDMI MODE_30 MHz ~ 1 GHz >

RADIATED EMISSION

Date : 2012-02-03

Model Name	: 32CS460-UC	Reference No.	:
Model No.	:	Power Supply	: 120V 60Hz
Serial No.	:	Temp/Humi	: 20 °C 31 % R.H.
Test Condition	: HDMI	Operator	:

Memo :
 LIMIT : FCC Part15 Subpart B Class B (3m)
 MARGIN: 3 dB



RADIATED EMISSION

Date : 2012-02-03

Model Name	: 32CS460-UC	Reference No.	:
Model No.	:	Power Supply	: 120V 60Hz
Serial No.	:	Temp/Humi	: 20°C 31 % R.H.
Test Condition	: HDMI	Operator	:

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m)
 MARGIN: 3 dB

No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	37.275	29.0	15.4	0.9	23.1	22.2	40.0	17.8	100	1
2	146.400	39.0	10.6	1.7	23.1	28.2	43.5	15.3	160	351
3	275.933	45.2	13.5	2.5	23.8	37.4	46.0	8.6	100	223
4	286.700	45.4	13.6	2.5	23.8	37.7	46.0	8.3	100	224
5	716.510	36.2	19.1	4.3	24.1	35.5	46.0	10.5	200	34
----- Vertical -----										
6	35.478	36.5	16.4	0.9	23.1	30.7	40.0	9.3	100	333
7	47.050	43.2	12.2	1.0	22.8	33.6	40.0	6.4	100	358
8	90.450	41.0	9.1	1.4	22.8	28.7	43.5	14.8	100	358
9	144.603	37.5	10.7	1.6	23.0	26.8	43.5	16.7	100	1
10	219.178	40.1	11.0	2.2	23.4	29.9	46.0	16.1	100	190
11	247.300	40.4	12.9	2.3	23.6	32.0	46.0	14.0	127	204
12	292.273	43.0	13.7	2.6	23.8	35.5	46.0	10.5	130	176

< HDMI MODE_1 GHz ~ 6 GHz_Peak >



RADIATED EMISSION

Date : 2012-02-04

Model Name	: 32CS460-UC	Reference No.	:
Model No.	:	Power Supply	: 120V 60Hz
Serial No.	:	Temp/Humi	: 19 °C 28 % R.H.
Test Condition	: HDMI	Operator	:

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Peak)
 FCC Part15 Subpart.B Class B (3m) - 18G(Avg)



RADIATED EMISSION

Date : 2012-02-04

Model Name	: 32CS460-UC	Reference No.	:
Model No.	:	Power Supply	: 120V 60Hz
Serial No.	:	Temp/Humi	: 19 °C 28 % R.H.
Test Condition	: HDMI	Operator	:

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Peak)
 FCC Part15 Subpart B Class B (3m) - 18G(Avg)

No.	FREQ [MHz]	READING PEAK [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	1937.500	67.5	25.2	6.9	41.7	57.9	74.0	16.1	100	1
2	2037.500	60.0	25.4	7.1	41.7	50.8	74.0	23.2	100	182
3	4550.000	53.5	30.9	10.7	42.0	53.1	74.0	20.9	100	1
----- Vertical -----										
4	1950.000	63.5	25.2	6.9	41.7	53.9	74.0	20.1	100	358
5	2637.500	54.9	27.7	8.0	41.8	48.8	74.0	25.2	100	162
6	3300.000	53.5	29.0	9.2	41.9	49.8	74.0	24.2	100	197
7	4512.500	55.4	30.8	10.7	42.0	54.9	74.0	19.1	100	213

< HDMI MODE_1 GHz ~ 6 GHz_Average >

RADIATED EMISSION



Date : 2012-02-04

Model Name : 32CS460-UC
 Model No. :
 Serial No. :
 Test Condition : HDMI

Reference No. :
 Power Supply : 120V 60Hz
 Temp/Humi : 19 °C 28 % R.H.
 Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Avg)
 FCC Part15 Subpart.B Class B (3m) - 18G(Peak)



RADIATED EMISSION

Date : 2012-02-04

Model Name	: 32CS460-UC	Reference No.	:
Model No.	:	Power Supply	: 120V 60Hz
Serial No.	:	Temp/Humi	: 19 °C 28 % R.H.
Test Condition	: HDMI	Operator	:

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Avg)
 FCC Part15 Subpart.B Class B (3m) - 18G(Peak)

No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
	[MHz]	[dBuV]	FACTOR	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
----- Horizontal -----										
1	1937.500	48.7	25.2	6.9	41.7	39.1	54.0	14.9	100	1
2	4551.000	37.0	30.9	10.7	42.0	36.6	54.0	17.4	100	1
----- Vertical -----										
3	1950.000	47.8	25.2	6.9	41.7	38.2	54.0	15.8	100	358
4	2640.010	48.4	27.7	8.0	41.8	42.3	54.0	11.7	100	162
5	3300.010	47.7	29.0	9.2	41.9	44.0	54.0	10.0	100	197
6	4550.000	40.1	30.9	10.7	42.0	39.7	54.0	14.3	100	213

< USB MODE_30 MHz ~ 1 GHz >



RADIATED EMISSION

Date : 2012-02-03

Model Name : 32CS460-UC	Reference No. :
Model No. :	Power Supply : 120V 60Hz
Serial No. :	Temp/Humi : 20 °C 31 % R.H.
Test Condition : USB	Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m)
 MARGIN: 3 dB



RADIATED EMISSION

Date : 2012-02-03

Model Name : 32CS460-UC	Reference No. :
Model No. :	Power Supply : 120V 60Hz
Serial No. :	Temp/Humi : 20°C 31 % R.H.
Test Condition : USB	Operator :

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m)
 MARGIN: 3 dB

No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	37.275	31.2	15.4	0.9	23.1	24.4	40.0	15.6	100	358
2	215.039	43.8	10.7	2.1	23.4	33.2	43.5	10.3	100	188
3	254.443	39.0	13.1	2.4	23.6	30.9	46.0	15.1	100	168
4	275.925	39.8	13.5	2.5	23.8	32.0	46.0	14.0	100	144
5	716.503	33.3	19.1	4.3	24.1	32.6	46.0	13.4	300	0
----- Vertical -----										
6	35.588	36.8	16.4	0.9	23.1	31.0	40.0	9.0	100	8
7	47.116	43.4	12.2	1.0	22.8	33.8	40.0	6.2	100	237
8	90.575	40.4	9.1	1.4	22.8	28.1	43.5	15.4	100	2
9	215.044	41.4	10.7	2.1	23.4	30.8	43.5	12.7	167	159
10	286.690	43.8	13.6	2.5	23.8	36.1	46.0	9.9	167	166

< USB MODE_1 GHz ~ 6 GHz_Peak >

RADIATED EMISSION



Date : 2012-02-04

Model Name : 32CS460-UC
 Model No. :
 Serial No. :
 Test Condition : USB

Reference No. :
 Power Supply : 120V 60Hz
 Temp/Humi : 19 °C 28 % R.H.
 Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Peak)
 FCC Part15 Subpart.B Class B (3m) - 18G(Avg)



RADIATED EMISSION

Date : 2012-02-04

Model Name : 32CS460-UC	Reference No. :
Model No. :	Power Supply : 120V 60Hz
Serial No. :	Temp/Humi : 19 °C 28 % R.H.
Test Condition : USB	Operator :

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Peak)
 FCC Part15 Subpart B Class B (3m) - 18G(Avg)

No.	FREQ [MHz]	READING PEAK [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	1200.000	62.1	24.2	5.3	41.9	49.7	74.0	24.3	100	178
2	1437.500	75.3	25.0	5.8	41.6	64.5	74.0	9.5	100	358
3	1950.000	65.4	25.2	6.9	41.7	55.8	74.0	18.2	100	187
4	4550.000	51.5	30.9	10.7	42.0	51.1	74.0	22.9	100	358
----- Vertical -----										
5	1312.500	59.6	24.6	5.5	41.8	47.9	74.0	26.1	100	184
6	1437.500	64.0	25.0	5.8	41.6	53.2	74.0	20.8	100	1
7	1937.500	63.0	25.2	6.9	41.7	53.4	74.0	20.6	100	199
8	3300.000	54.0	29.0	9.2	41.9	50.3	74.0	23.7	100	187
9	4562.500	55.4	31.0	10.7	42.0	55.1	74.0	18.9	100	1

< USB MODE_1 GHz ~ 6 GHz_Average >

RADIATED EMISSION



Date : 2012-02-04

Model Name : 32CS460-UC
 Model No. :
 Serial No. :
 Test Condition : USB

Reference No. :
 Power Supply : 120V 60Hz
 Temp/Humi : 19 °C 28 % R.H.
 Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Avg)
 FCC Part15 Subpart.B Class B (3m) - 18G(Peak)



RADIATED EMISSION

Date : 2012-02-04

Model Name	: 32CS460-UC	Reference No.	:
Model No.	:	Power Supply	: 120V 60Hz
Serial No.	:	Temp/Humi	: 19 °C 28 % R.H.
Test Condition	: USB	Operator	:

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Avg)
 FCC Part15 Subpart.B Class B (3m) - 18G(Peak)

No.	FREQ [MHz]	READING AV [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	1200.000	42.6	24.2	5.3	41.9	30.2	54.0	23.8	100	178
2	1440.018	43.8	25.0	5.8	41.6	33.0	54.0	21.0	100	358
3	1947.958	45.8	25.2	6.9	41.7	36.2	54.0	17.8	100	187
4	4555.000	35.4	30.9	10.7	42.0	35.0	54.0	19.0	100	358
----- Vertical -----										
5	1319.950	51.3	24.6	5.5	41.8	39.6	54.0	14.4	100	184
6	1440.018	40.6	25.0	5.8	41.6	29.8	54.0	24.2	100	1
7	1947.958	45.4	25.2	6.9	41.7	35.8	54.0	18.2	100	199
8	3300.000	49.4	29.0	9.2	41.9	45.7	54.0	8.3	100	187
9	4555.000	37.4	30.9	10.7	42.0	37.0	54.0	17.0	100	1

Appendix 1

List of Test and Measurement Instruments

1. Conducted Disturbance

Name of Instrument	Model No.	Manufacturer	Serial No.	Cal. Date	Next Cal. Date
<input type="checkbox"/> SPECTRUM ANALYZER	8591E	H/P	3649A05889	2011.03.07	2012.03.07
<input type="checkbox"/> RFI/FIELD INTENSITY METER	KNM-2402	KYORITSU	4N-170-3	2011.07.02	2012.07.02
<input type="checkbox"/> LISN	KNW-407	KYORITSU	8-317-8	2012.01.09	2013.01.09
<input type="checkbox"/> LISN	KNW-242	KYORITSU	8-654-15	2011.07.01	2012.07.01
<input type="checkbox"/> 50 OHM TERMINATOR	CT-01	TME	N/A	2012.01.09	2013.01.09
<input checked="" type="checkbox"/> EMI TEST RECEIVER	ESCI	ROHDE & SCHWARZ	100364	2011.03.08	2012.03.08
<input checked="" type="checkbox"/> LISN	ESH2-Z5	ROHDE & SCHWARZ	828739/006	2011.09.30	2012.09.30
<input checked="" type="checkbox"/> LISN	LISN1600	TTI	197204	2011.07.02	2012.07.02
<input checked="" type="checkbox"/> 50 OHM TERMINATOR	CT-01	TME	N/A	2012.01.09	2013.01.09

2. Radiated Disturbance

Name of Instrument	Model No.	Manufacturer	Serial No.	Cal. Date	Next Cal. Date
<input checked="" type="checkbox"/> EMI TEST RECEIVER	ESU	ROHDE & SCHWARZ	100014	2012.01.09	2013.01.09
<input checked="" type="checkbox"/> BILOG ANTENNA	CBL6112B	SCHAFFNER	2737	2010.07.14	2012.07.14
<input checked="" type="checkbox"/> HORN ANTENNA	BBHA9120A	SCHWARZBECK	322	2010.04.13	2012.04.13
<input checked="" type="checkbox"/> AMPLIFIER	8447E	H/P	2945A02865	2012.01.09	2013.01.09
<input checked="" type="checkbox"/> AMPLIFIER	MLA-00108-B02-36	TSJ	1518831	2012.01.09	2013.01.09
<input type="checkbox"/> SPECTRUM ANALYZER	E4411B	AGILENT	US41062735	2011.07.01	2012.07.01
<input type="checkbox"/> AMPLIFIER	8447D	AGILENT	2443A03690	2011.07.01	2012.07.01
<input type="checkbox"/> BILOG ANTENNA	VULB9160	SCHAFFNER	3151	2010.08.25	2012.08.25
<input type="checkbox"/> EMI TEST RECEIVER	ESCI	ROHDE & SCHWARZ	100364	2011.03.08	2012.03.08
<input type="checkbox"/> BICONICAL ANT.	VHA 9103	SCHWARZBECK	91032789	2010.11.29	2012.11.29
<input type="checkbox"/> LOG-PERIODIC ANT.	UHALP 9108A	SCHWARZBECK	590	2010.07.07	2012.07.07
<input type="checkbox"/> BICONICAL ANT.	VHA 9103	SCHWARZBECK	91031946	2010.12.21	2012.12.21
<input type="checkbox"/> LOG-PERIODIC ANT.	UHALP 9108-A1	SCHWARZBECK	1098	2010.11.29	2012.11.29
<input type="checkbox"/> AMPLIFIER	MLA-100K01-B01-26	TSJ	1252741	2011.03.07	2012.03.07