



**ESTECH Co., Ltd.**

Rm. 1015, World Venture Center II,  
426-5 Gasan-dong, Guncheon-gu,  
Seoul, 158-803, Korea



**Electromagnetic  
Interference  
Test Report**

## Compliance Test Report for FCC

Report Number		ESTF150501-003			
Applicant	Company name	LG Electronics USA			
	Address	2000 Millbrook Dr Lincolnshire, IL 60069 United states			
	Telephone	847-841-8373			
Product	Product name	PLASMA MONITOR			
	Model No.	50PX4D-UB,DU-50PX41, DU-50PX41S, 50PX4D	Manufacturer	LG Electronics Inc.	
	Serial No.	NONE	Country of origin	KOREA	
Test date	2005-01-10 ~2005-01-19		Date of issue	2005-01-19	
Testing location	ESTECH. Co., Ltd. 97-1 Hoiuk-Ri Majang-Myon, Icheon-city, KyungKi-Do, Korea				
Standard	FCC PART 15 2002 , ANSI C 63.4 2001				
Test item	<input checked="" type="checkbox"/> Conducted Emission	<input type="checkbox"/> Class A	<input checked="" type="checkbox"/> Class B	Test result	OK
	<input checked="" type="checkbox"/> Radiated Emission	<input type="checkbox"/> Class A	<input checked="" type="checkbox"/> Class B	Test result	OK
Measurement facility registration number	94696				
Tested by	Senior Engineer J.M. Yang		(Signature)		
Reviewed by	Director T.K. Lee		(Signature)		
Abbreviation	OK, Pass = Passed, Fail = Failed, N/A = not applicable				
<p>* Note</p> <ul style="list-style-type: none"> <li>- This test report is not permitted to copy partly without our permission</li> <li>- This test result is dependent on only equipment to be used</li> <li>- This test result based on a single evaluation of one sample of the above mentioned</li> <li>- 50PX4D-UB,DU-50PX41, DU-50PX41S, 50PX4D are same product. ONLY Model name is different</li> </ul>					

## Contents

1. Laboratory Information .....	3
2. Description of EUT .....	4
3. Test Standards .....	5
4. Measurement condition .....	6
5. Measurement of radiated emission .....	8
5.1 Measurement equipment .....	8
5.2 Environmental conditions .....	8
5.3 Test data .....	9
6. Measurement of conducted emission .....	10
6.1 Measurement equipment .....	10
6.2 Environmental conditions .....	10
6.3 Test data .....	11
7. Photographs of test setup .....	12
8. Photographs of EUT .....	14
Appendix 1. Spectral diagram	
Appendix 2. Photographs of EUT in side PCB	
Appendix 3. Block diagram of EUT	
Appendix 4. Circuit Diagram	



## 1. Laboratory Information

### 1.1 General

This EUT (Equipment Under Test) has been shown to be capable of compliance with the applicable technical standards and is tested in accordance with the measurement procedures as indicated in this report.

ESTECH Lab attests to accuracy of test data. All measurement reported herein were performed by ESTECH Co., Ltd.

ESTECH Lab assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

### 1.2 Test Lab.

Corporation Name : ESTECH Co. Ltd

Head Office : Rm 1015, World Venture Center II, 426-5, Gasan-dong, Geumcheon-gu, Seoul, Korea  
(Safety & Telecom. Test Lab)

EMC Test Lab : 58-1 Osan-Ri, GaNam-Myon, YeoJoo-Gun, KyungKi-Do, Korea  
97-1 Hoiuk-Ri Majang-Myon, Icheon-city, KyungKi-Do, Korea

### 1.3 Official Qualification(s)

MIC : Granted Accreditation from Ministry of Information & Communication for EMC, Safety and Telecommunication

KOLAS : Accredited Lab By Korea Laboratory Accreditation Schema base on CENELEC requirements

FCC : Filed Laboratory at Federal Communications Commission

VCCI : Granted Accreditation from Voluntary Control Council for Interference from ITE



**ESTECH Co., Ltd.**

Rm 1015, World Venture Center 11,  
426-5 Gasan-dong, Guncheon-gu,  
Seoul, 158-803, Korea



**Electromagnetic  
Interference  
Test Report**

## 2. Description of EUT

### 2.1 Summary of Equipment Under Test

NONE : PLASMA MONITOR  
 Model Number : 50PX4D-UB,DU-50PX41, DU-50PX41S, 50PX4D  
 Serial Number : NONE  
 Manufacturer : LG Electronics Inc.  
 Country of origin : KOREA  
 Rating : INPUT:AC120V / 60Hz  
 Receipt Date : 2005-01-10

### 2.2 General descriptions of EUT

MODELS	DU-42PX41X	DU-50PX41
Width (inches / mm)	47.8 / 1216	55.2 / 1402
Height (inches / mm)	27.2 / 691	31.4 / 798.5
Depth (inches / mm)	10.7 / 271.4	11.9 / 302.5
Weight (pounds / kg)	88.54 / 40.16	122 / 55.3
Resolution	1024x768(Dot)	1366 x 768 (Dot)
Power requirement	AC100-240V ~ 60Hz	
Television System	NTSC-M, ATSC	
Program Coverage	VHF 2 ~ 13, UHF 14 ~ 69, CATV 1 ~ 135, CADTV 1 ~ 135. DTV 2 ~ 69	
External Antenna Impedance	75 Ω	
Color	16,770,000 (256 steps of each R, G and B)	
Operating Temperature Range	32 ~ 104°F (0 ~ 40°C)	
Operating Humidity Range	Less than 80%	
Maximum Elevation	6561 feet (2000m)	

Monitor Display Specifications (RGB-PC)

Resolution	Horizontal Frequency(KHz)	Vertical Frequency(Hz)	Resolution	Horizontal Frequency(KHz)	Vertical Frequency(Hz)
640x350	31.468	70.09	800x600	35.156	56.25
	37.861	85.08		37.879	60.31
720x400	31.469	70.08		48.077	72.18
	37.927	85.03		46.875	75.00
640x480	31.469	59.94		53.674	85.06
	37.861	72.80		48.363	60.00
	37.500	75.00	56.476	70.06	
	43.269	85.00	1024x768	60.023	75.02

Monitor Display Specifications (HDMI/DVI Mode)

Resolution	Horizontal Frequency(KHz)	Vertical Frequency(Hz)	Resolution	Horizontal Frequency(KHz)	Vertical Frequency(Hz)	
640x480	31.469	59.94	1024x768	48.363	60.00	
	37.861	72.80		56.476	70.06	
	37.500	75.00		60.023	75.02	
800x600	35.156	56.25				
	37.879	60.31				
	48.077	72.18				
	46.875	75.00				

Using Freq. :24.57Mhz(2ea)/18.43Mhz/8Mhz/4MHz(4ea)/25MHz(2ea)/12MHz



### 3. Test Standards

#### Test Standard : FCC PART 15 (2002)

This Standard sets out the regulations under which an intentional, unintentional, or incidental radiator may be operated without an individual license. It also contains the technical specifications, administrative requirements and other conditions relating to the marketing of Part 15 devices.

#### Test Method : ANSI C 63.4 (2001)

This standard sets forth uniform methods of measurement of radio-frequency (RF) signals and noise emitted from both unintentional and intentional emitters of RF energy in the frequency range 9 kHz to 40 GHz. Methods for the measurement of radiated and AC power-line conducted radio noise are covered and may be applied to any such equipment unless otherwise specified by individual equipment requirements. These methods cover measurement of certain devices that deliberately radiate energy, such as intentional emitters, but does not cover licensed transmitters. This standard is not intended for certification/approval of avionic equipment or for industrial, scientific, and medical (ISM) equipment. These methods apply to the measurement of individual units or systems comprised of multiple units.



**ESTECH Co., Ltd.**

Rm. 1015, World Venture Center II,  
426-5 Gasan-dong, Guncheon-gu,  
Seoul, 158-803, Korea




**Electromagnetic  
Interference  
Test Report**

## 4. Measurement Condition

### 4.1 EUT Operation.

- \* The EUT was in the following operation mode during all testing
- \* The operational conditions of the EUT was determined by the manufacturer according to the typical use of the EUT with respect to the expected highest level of emission
- \* After setting as test arrangement diagram, we tested the EUT under continuous displaying "H" character and playing Audio out /Video

### 4.2 Configuration and Peripherals



**ESTECH Co., Ltd.**Rm 1015, World Venture Center II,  
426-5 Gasan-dong, Guncheon-gu,  
Seoul, 158-803, Korea**Electromagnetic  
Interference  
Test Report**

### 4.3 EUT and Support equipment

Equipment Name	Model Name	S/N	Manufacturer	Remark (FCC ID)
PLASMA MONITOR	50PX4D-UB, DU-50PX41, DU-50PX41S, 50PX4D	NONE	LG Electronics USA	EUT
PERSONAL COMPUTER	HP Pavilion m000	KRF35200YM	HP	-
PRINTER	LQ-570H+	B1021095782	Trigem Computer Inc.,	-
KEYBOARD	SEM-DT35	32006557	Samsung Electro- mechanics Co., Ltd.,	-
MOUSE	M-BB48	LZE01550574	Logitech	-
				-

### 4.4 Cable Connecting

Start Equipment		End Equipment		Cable Standard		Remark
Name	I/O port	Name	I/O port	Length	Shielded	
PLASMA MONITOR	VIDEO	PERSONAL COMPUTER	VIDEO	2	Y	-
PLASMA MONITOR	S-VIDEO	PERSONAL COMPUTER	S-VIDEO	2	Y	-
PLASMA MONITOR	DVI	PERSONAL COMPUTER	DVI	2	Y	-
PLASMA MONITOR	LINE-IN	PERSONAL COMPUTER	LINE-IN	2	N	-
PLASMA MONITOR	COMPONENT 1	-	-	2	N	-
PLASMA MONITOR	COMPONENT 2	-	-	2	N	-
PLASMA MONITOR	COMPONENT 3	-	-	2	N	-
PLASMA MONITOR	AV INPUT	-	-	2	N	-
PLASMA MONITOR	MONITOR OUTPUT	-	-	2	N	-
PLASMA MONITOR	IEEE 1394	-	-	2	N	-
PLASMA MONITOR	ANT1	-	-	2	N	-
PLASMA MONITOR	ANT2	-	-	2	N	-
PLASMA MONITOR	S-VIDEO	-	-	2	N	-
PERSONAL COMPUTER	PARALLEL	PRINTER	PARALLEL	2	Y	-
PERSONAL COMPUTER	PS/2 KEYBOARD	KEYBOARD	PS/2 KEYBOARD	2	N	-
PERSONAL COMPUTER	PS/2 MOUSE	MOUSE	PS/2 MOUSE	2	N	-
						-
						-

## 5. Measurement of radiated disturbance

Above 30 MHz Electric Field strength was measured in accordance with FCC Part 15 (2002) & ANSI C 63.4 (2001). The test setup was made according to FCC Part 15 (2002) & ANSI C 63.4 (2001) on an open test site, which allows a 3m distance measurement. The EUT was placed in the center of wooden turntable. The height of this table was 0.8m. The measurement was conducted with both horizontal and vertical antenna polarization. The turntable has fully rotated. For further description of the configuration refer to the picture of the test set-up.

### 5.1 Measurement equipments

Equipment Name	Type	Manufacturer	Serial No.	Next Calibration date
TEST Receive	ESPI7	Rohde & Schwarz	100185	2005. 8. 20
Spectrum Analyzer	R3261B	ADVANTEST	1720302	2005.2.12
LogBicon Antenna	VULB 9160	S/B	3142	2005.7.06
Horn Antenna	BBHA 9120 D	SCHWARZBECK	352	2006.4.06
Turn Table	2087	EMCO	2129	-
Antenna Mast	2070-01	EMCO	9702-203	-
ANT Mast Controller	2090	EMCO	1535	-
Turn Table Controller	2090	EMCO	1535	-

### 5.2 Environmental Condition

Test Place : Open site(3m)  
 Temperature (°C) : 7 °C  
 Humidity (%) : 55 %





## 6. Measurement of conducted disturbance

The continuous disturbance voltage of AC Mains in the frequency from 0.15 to 30 MHz was measured in accordance to FCC Part 15 (2002) & ANSI C 63.4 (2001) The test setup was made according to FCC Part 15 (2002) & ANSI C 63.4 (2001) in a shielded. The EUT was placed on a non-conductive table at least 80 above the ground plan. A grounded vertical reference plane was positioned in a distance of 40cm from the EUT. The distance from the EUT to other metal surfaces was at least 0.8m. The EUT was only earthen by its power cord through the line impedance stabilizing network. The power cord has been bundled to a length of 1.0m.. The test receiver with Quasi Peak detector complies with CISPR 16.

### 6.1 Measurement equipments

Equipment Name	Type	Manufacturer	Serial No.	Next Calibration date
LISN	ESH3-Z5	Rohde & Schwarz	838979/010	2005. 2. 12
LISN	NNLA8120A	Schwarzbeck	NONE	2005. 2. 12
TEST Receive	ESPI7	Rohde & Schwarz	100185	2005. 8. 20
Pulse Limiter	ESH3Z2	Rohde & Schwarz	NONE	2005. 6. 15

### 6.2 Environmental Condition

Test Place : Shield Room  
 Temperature (°C) : 22 °C  
 Humidity (%) : 25 %



**ESTECH Co., Ltd.**

Rm 1015, World Venture Center II,  
426-5 Gasan-dong, Guncheon-gu,  
Seoul, 158-803, Korea



**Electromagnetic  
Interference  
Test Report**

### 6.3 Test data

Frequency (MHz)	Correction Factor		Line (H/N)	Quasi-peak Value			Average Value		
	Lisn (dB)	Cable (dB)		Limit (dB $\mu$ V)	Reading (dB $\mu$ V)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Reading (dB $\mu$ V)	Result (dB $\mu$ V)
0.220	0.07	0.0	N	62.82	48.94	49.06	52.82	45.52	45.64
0.277	0.07	0.1	H	60.92	45.94	46.09	50.92	37.40	37.55
0.330	0.07	0.1	N	59.45	43.46	43.65	49.45	38.73	38.92
0.390	0.07	0.1	H	58.06	37.40	37.62	48.06		
0.398	0.07	0.1	N	57.89	37.95	38.17	47.89		
0.440	0.07	0.2	N	57.07	36.75	36.99	47.07	33.45	33.69
0.548	0.07	0.2	H	56.00	31.41	31.68	46.00		
0.625	0.08	0.2	N	56.00	34.89	35.17	46.00		
0.833	0.09	0.2	H	56.00	32.98	33.27	46.00		
1.042	0.09	0.2	N	56.00	42.20	42.50	46.00		
1.462	0.10	0.2	N	56.00	36.12	36.47	46.00		
1.879	0.11	0.3	N	56.00	32.48	32.88	46.00		
3.543	0.16	0.3	N	56.00	35.41	35.87	46.00		
3.748	0.16	0.3	H	56.00	35.66	36.12	46.00	21.92	22.38
3.958	0.17	0.3	N	56.00	40.43	40.90	46.00	26.28	26.75
10.075	0.36	0.6	H	60.00	34.92	35.89	50.00	20.21	21.18
10.078	0.36	0.6	N	60.00	35.69	36.66	50.00	23.04	24.01
10.497	0.38	0.6	H	60.00	38.06	39.06	50.00	21.85	22.85
10.701	0.40	0.6	N	60.00	33.62	34.64	50.00		
14.715	0.60	0.8	H	60.00	41.30	42.68	50.00		
15.754	0.62	0.8	N	60.00	38.48	39.90	50.00	26.73	28.15
16.197	0.63	0.8	H	60.00	43.16	44.59	50.00	25.94	27.37
16.611	0.64	0.8	N	60.00	38.13	39.57	50.00	26.14	27.58
19.688	0.69	0.8	N	60.00	32.91	34.40	50.00	26.47	27.96
Remark	H : Hot Line, N : Neutral Line								



**ESTECH Co., Ltd.**

Rm 1015, World Venture Center 11,  
426-5 Gasan-dong, Guncheon-gu,  
Seoul, 158-803, Korea



**Electromagnetic  
Interference  
Test Report**

## 7. Photographs of test setup

### 7.1 Setup for Radiated Test : 30 ~ 1000 MHz

[ Front ]



[ Rear ]





**ESTECH Co., Ltd.**


Rm. 1015, World Venture Center II,  
426-5 Gasan-dong, Guncheon-gu,  
Seoul, 158-803, Korea



**Electromagnetic  
Interference  
Test Report**

## 7.2 Setup for Conducted Test : 0.15 ~ 30 MHz

[ Front ]



[ Rear ]



8. Photographs of EUT

[ Front ]



[ Rear ]



# Appendix 1. Spectral diagram

\*HOT


ESTECH\_HOT\_0024

RBW 9 kHz

MT 1 s

Att 10 dB

PREAMP OFF



Comment: LG Electronics USA\_PLASAMA MONITOR\_50PX4D-UB\_H

Date: 17.JAN.2005 17:01:05

\*NETRUL


ESTECH\_NEUTRAL\_0024

RBW 9 kHz

MT 1 s

Att 10 dB

PREAMP OFF



Comment: LG Electronics USA\_PLASAMA MONITOR\_50PX4D-UB\_N

Date: 17.JAN.2005 17:06:13

Appendix 2. Photographs of EUT in side PCB

