RF TEST REPORT

Test item	:	Bluetooth Adapter Card
Model No.	:	MB0502LX
Order No.	:	DEMC1211-02413
Date of receipt	:	2012-11-06
Test duration	:	2012-11-09 ~ 2012-11-24
Date of issue	:	2012-11-29
Use of report	:	FCC Original Grant

Applicant : LG Electronics USA.
1000 Sylvan Avenue Englewood Cliffs, New Jersey, United States

Test laboratory : Digital EMC Co., Ltd.
683-3, Yubang-Dong, Cheoin-Gu, Yongin-Si, Kyunggi-Do, 449-080, Korea

Test specification	:	FCC Part 15 Subpart C 247
Test environment	:	See appended test report
Test result	:	☒ Pass ☐ Fail

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose. This test report shall not be reproduced except in full, without the written approval of DIGITAL EMC CO., LTD.

Tested by:	Witnessed by:	Reviewed by:
Engineer HongHee, Lee	N/A	Technical Director Harvey Sung

Table of Contents

1. General Information 4
1.1 Testing Laboratory 4
1.2 Details of Applicant 4
1.3 Description of EUT 4
1.4. Declaration by the manufacturer 4
1.5. Information about the FHSS characteristics: 5
1.5.1. Pseudorandom Frequency Hopping Sequence 5
1.5.2. Equal Hopping Frequency Use 5
1.5.3. System Receiver Input Bandwidth 5
1.6. Test Equipment List 6
1.7. Summary of Test Results 7
1.8 Conclusion of worst-case and operation mode 8
1.9 Test report revision 8
2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission 9
2.1. Test Setup 9
2.2. Limit 9
2.3. Test Procedures 10
2.3.1. Test Procedures for Radiated Spurious Emissions 10
2.3.2. Test Procedures for Conducted Spurious Emissions 10
2.4. Test Results 11
2.4.1. Radiated Emission 11
2.4.2. Conducted Spurious Emissions 14
3. Carrier Frequency Separation 29
3.1. Test Setup 29
3.2. Limit 29
4. Number of Hopping Frequencies 34
4.1. Test Setup 34
4.2. Limit 34
5. 20dBc BW 43
5.1. Test Setup 43
5.2. Limit 43
5.3. Test Procedure 43
5.4. Test Results 43
6. Time of Occupancy (Dwell Time) 49
6.1. Test Setup 49
6.2. Limit 49
6.3. Test Procedure 49
6.4. Test Results 49
7. Maximum Peak Output Power Measurement 54
7.1. Test Setup 54

Copyright © 2012, Digital EMC Co., Ltd.

7.2. Limit 54
7.3. Test Procedure 54
7.4. Test Results 55
8. Transmitter AC Power Line Conducted Emission 61
8.1. Test Setup 61
8.2. Limit 61
8.3. Test Procedures 61
8.4. Test Results 62
9. Antenna Requirement 64

Copyright © 2012, Digital EMC Co., Ltd.

1. General Information

1.1 Testing Laboratory

Digital EMC Co., Ltd.
683-3, Yubang-Dong, Cheoin-Gu, Yongin-Si, Kyunggi-Do, 449-080, Korea
www.digitalemc.com
Telephone : + 82-31-321-2664
FAX : + 82-31-321-1664

1.2 Details of Applicant

Applicant : LG Electronics USA.
Address : 1000 Sylvan Avenue Englewood Cliffs, New Jersey, United States
Contact person : Jacob Cho
Phone No. : +201-816-2003

1.3 Description of EUT

Product	Bluetooth module
Model Name	MB0502LX
Serial Number	Identical prototype
Power Supply	DC 3.3V
Frequency Range	2402 ~ 2480MHz
Modulation Technique	GFSK, π/4-DQPSK, 8DPSK
Number of Channels	79
Antenna Type	Internal Antenna
Antenna Gain	PK : 1.829 dBi

1.4. Declaration by the manufacturer

- N/A

Copyright © 2012, Digital EMC Co., Ltd.

1.5. Information about the FHSS characteristics:

1.5.1. Pseudorandom Frequency Hopping Sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The nominal hop rate is 1600 hops/s.

1.5.2. Equal Hopping Frequency Use

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

1.5.3. System Receiver Input Bandwidth

Each channel bandwidth is 1㎒

Copyright ⓒ 2012, Digital EMC Co., Ltd.

1.6. Test Equipment List

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent	E4440A	12/10/22	13/10/22	US45303022
MXA Signal Analyzer	Agilent	N9020A	12/01/09	13/01/09	MY49100833
Spectrum Analyzer	Rohde Schwarz	FSQ26	12/01/09	13/01/09	200445
Digital Multimeter	H.P	34401A	12/03/05	13/03/05	3146A13475
Signal Generator	Rohde Schwarz	SMR20	12/03/05	13/03/05	101251
Vector Signal Generator	Rohde Schwarz	SMJ100A	12/01/09	13/01/09	100148
Thermo hygrometer	BODYCOM	BJ5478	12/01/13	13/01/13	090205-2
DC Power Supply	HP	6622A	12/03/05	13/03/05	3448A03760
High-pass filter	Wainwright	WHNX3.0	12/09/17	13/09/17	9
BILOG ANTENNA	SCHAFFNER	CBL6112D	10/12/21	12/12/21	22609
HORN ANT	ETS	3115	12/02/20	14/02/20	6419
HORN ANT	A.H.Systems	SAS-574	11/03/25	13/03/25	154
Amplifier (22dB)	H.P	8447E	12/01/09	13/01/09	2945A02865
Amplifier (30dB)	Agilent	8449B	12/03/05	13/03/05	3008A00370
EMI TEST RECEIVER	R&S	ESU	12/01/09	13/01/09	100014
EMI TEST RECEIVER	R&S	ESCI	12/03/06	13/03/06	100364
CVCF	NF Electronic	4420	12/03/05	13/03/05	304935/337980
ARTIFICIAL MAINS NETWORK	R&S	ESH2-Z5	12/09/18	13/09/18	828739/006
RFI/Field intensity Meter	KYORITSU	KNM-2402	12/07/02	13/07/02	4N-170-3

Copyright © 2012, Digital EMC Co., Ltd.

1.7. Summary of Test Results

FCC Part RSS-210 & GEN	Parameter	Limit (Using in 2400 ~ 2483.5MHz)	Test Condition	Status Note 1
I. Transmit mode (TX)				
15.247(a) RSS-210(A8.1)	Carrier Frequency Separation	>= 20dB BW or >= Two-Thirds of the 20dB BW	Conducted	C
	Number of Hopping Frequencies	>= 15 hops		C
	20 dB Bandwidth	None		C
	Dwell Time	=< 0.4 seconds		C
15.247(b) RSS-210(A8.4)	Transmitter Output Power	=< 1Watt , if CHs >= 75 Others =<0.125W		C
15.247(d) RSS-210(A8.5)	Band-edge /Conducted	The radiated emission to any 100 kHz of out-band shall be at least 20dB below the highest in-band spectral density.		C
	Conducted Spurious Emissions			C
15.205, 15.209 RSS-210(A8.5)	Radiated Spurious Emissions	FCC 15.209 Limits	Radiated	C Note.2
15.207 RSS-Gen(7.2.4)	AC Conducted Emissions	EN 55022	AC Line Conducted	C
15.203 RSS-Gen(7.1.2)	Antenna Requirements	FCC 15.203	-	C

Note 1: **C**=Comply **NC**=Not Comply **NT**=Not Tested **NA**=Not Applicable

Note 2: This test item was performed in each axis. And the worst case data were reported.

Copyright © 2012, Digital EMC Co., Ltd.

1.8 Conclusion of worst-case and operation mode

The EUT has three type of modulation (GFSK, π/4DQPSK and 8DPSK).

Therefore all applicable requirements were tested with all the modulations.

The field strength of spurious emission was measured in three orthogonal EUT positions(X-axis, Y-axis and Z-axis).

Tested frequency information,

- Hopping Function: Enable

	TX Frequency (MHz)	RX Frequency (MHz)
Hopping Band	2402 ~ 2480	2402 ~ 2480

- Hopping Function: Disable

	TX Frequency (MHz)	RX Frequency (MHz)
Lowest Channel	2402	2402
Middle Channel	2441	2441
Highest Channel	2480	2480

1.9 Test report revision

Test Report No.	Date	Description
DRTFCC1211-0825	Nov. 29, 2012	Request of customer

Copyright © 2012, Digital EMC Co., Ltd.

2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission

2.1. Test Setup

Refer to the APPENDIX I.

2.2. Limit

According to §15.247(d), in any 100 ㎑ bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 ㏈ below that in the 100 ㎑ bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement , provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval , as permitted under paragraph(b)(3) of this section , the attenuation required under this paragraph shall be 30 ㏈ instead of 20 ㏈. Attenuation below the general limits specified in section §15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section §15.205(a), must also comply the radiated emission limits specified in section §15.209(a) (see section §15.205(c))

According to § 15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

According to § 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	3600 ~ 4400	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	4.5 ~ 5.15	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~ 12.52025	149.9 ~ 150.05	1645.5 ~ 1646.5	5.35 ~ 5.46	17.7 ~ 21.4
4.125 ~ 4.128	12.57675 ~ 12.57725	156.52475 ~	1660 ~ 1710	7.25 ~ 7.75	22.01 ~ 23.12
4.17725 ~ 4.17775	13.36 ~ 13.41	156.52525	1718.8 ~ 1722.2	8.025 ~ 8.5	23.6 ~ 24.0
4.20725 ~ 4.20775	16.42 ~ 16.423	156.7 ~ 156.9	2200 ~ 2300	9.0 ~ 9.2	31.2 ~ 31.8
6.215 ~ 6.218	16.69475 ~ 16.69525	162.0125 ~ 167.17	2310 ~ 2390	9.3 ~ 9.5	36.43 ~ 36.5
6.26775 ~ 6.26825	16.80425 ~ 16.80475	167.72 ~ 173.2	2483.5 ~ 2500	10.6 ~ 12.7	Above 38.6
6.31175 ~ 6.31225	25.5 ~ 25.67	240 ~ 285	2655 ~ 2900	13.25 ~ 13.4	
8.291 ~ 8.294	37.5 ~ 38.25	322 ~ 335.4	3260 ~ 3267		
8.362 ~ 8.366	73 ~ 74.6	399.90 ~ 410	3332 ~ 3339		
8.37625 ~ 8.38675	74.8 ~ 75.2	608 ~ 614	3345.8 ~ 3358		
		960 ~ 1240			

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

Copyright © 2012, Digital EMC Co., Ltd.

2.3. Test Procedures

Radiated emissions from the EUT were measured according to the DA 00-705 and ANSI C63.4:2003

2.3.1. Test Procedures for Radiated Spurious Emissions

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 ㎓, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 ㎓, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10 ㏈ lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 ㏈ margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE ;
1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 ㎑ for Quasi-peak detection (QP) at frequency below 1 ㎓.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1㎒ for Peak detection and frequency above 1 ㎓.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 ㎒ and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1 ㎓.

2.3.2. Test Procedures for Conducted Spurious Emissions

1. The transmitter output was connected to the spectrum analyzer.
2. The reference level of the fundamental frequency was measured with the spectrum analyzer using RBW=100 ㎑, VBW=300 ㎑.
3. The conducted spurious emission was performed using the spectrum analyzer's spurious measurement function from 30 MHz to 25 GHz with the 11 sub measurement ranges.(Detail ranges are listed on the measurement plots) The following spectrum settings was used for each measurement rages.
   RBW=100 ㎑, VBW=300 ㎑, SWEEP TIME = AUTO, DETECTOR = PEAK, TRACE = MAX HOLD.

Copyright © 2012, Digital EMC Co., Ltd.

2.4. Test Results

Ambient temperature : 22 °C
Relative humidity : 48 %

2.4.1. Radiated Emission

30MHz ~ 25GHz Data(Modulation: ***GFSK***)

▪ Lowest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2387.240	H	Z	PK	61.68	-4.73	N/A	56.95	74.00	17.05
2386.240	H	Z	AV	50.48	-4.73	N/A	45.75	54.00	8.25
4804.063	V	Y	PK	71.06	2.15	-30.81	42.40	74.00	31.60
4804.045	V	Y	AV	68.19	2.15	-30.81	39.53	54.00	14.47
-	-	-	-	-	-	-	-	-	-

▪ Middle Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4882.072	V	Y	PK	68.66	2.94	-30.81	40.79	74.00	33.21
4882.060	V	Y	AV	65.72	2.94	-30.81	37.85	54.00	16.15
-	-	-	-	-	-	-	-	-	-

▪ Highest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.517	H	Z	PK	67.88	-4.59	N/A	63.29	74.00	10.71
2483.500	H	Z	AV	54.73	-4.59	N/A	50.14	54.00	3.86
4960.072	V	Y	PK	70.11	2.74	-30.81	42.04	74.00	31.96
4960.051	V	Y	AV	59.92	2.74	-30.81	31.85	54.00	22.15
-	-	-	-	-	-	-	-	-	-

Note.

1. No other spurious and harmonic emissions were reported greater than listed emissions above table.
2. Above listed point data is the worst case data.
3. Sample Calculation.
   Margin = Limit – Result / Result = Reading + T.F+ DCF / T.F = AF + CL – AG
   Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,
   DCF = Duty Cycle Correction Factor
   - Time to cycle through all channels= $\Delta t = \tau_{[ms]}$ X 79 channels = 227.52ms, where τ = pulse width
   - 100ms / $\Delta t_{[ms]} = H$ -> Round up to next highest integer, to account for worst case, $H' = 1$
   - Worst Case Dwell Time = $\tau_{[ms]}$ X H' = 2.88ms
   - Duty Cycle Correction = 20log(Worst Case Dwell Time / 100ms) $_{[dB]}$ = -30.81 dB

Copyright © 2012, Digital EMC Co., Ltd.

30MHz ~ 25GHz Data(Modulation: *π/4 DQPSK*)

▪ Lowest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2383.760	H	Z	PK	61.45	-4.73	N/A	56.72	74.00	17.28
2385.680	H	Z	AV	49.18	-4.73	N/A	44.45	54.00	9.55
4804.096	V	Y	PK	70.97	2.15	-30.81	42.31	74.00	31.69
4804.027	V	Y	AV	65.89	2.15	-30.81	37.23	54.00	16.77
-	-	-	-	-	-	-	-	-	-

▪ Middle Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4882.024	V	Y	PK	68.75	2.94	-30.81	40.88	74.00	33.12
4882.063	V	Y	AV	63.87	2.94	-30.81	36.00	54.00	18.00
-	-	-	-	-	-	-	-	-	-

▪ Highest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.517	H	Z	PK	67.54	-4.59	N/A	62.95	74.00	11.05
2483.512	H	Z	AV	53.98	-4.59	N/A	49.39	54.00	4.61
4959.937	V	Y	PK	69.84	2.74	-30.81	41.77	74.00	32.23
4959.946	V	Y	AV	57.24	2.74	-30.81	29.17	54.00	24.83
-	-	-	-	-	-	-	-	-	-

Note.

1. No other spurious and harmonic emissions were reported greater than listed emissions above table.
2. Above listed point data is the worst case data.
3. Sample Calculation.
   Margin = Limit – Result / Result = Reading + T.F+ DCF / T.F = AF + CL – AG
   Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,
   DCF = Duty Cycle Correction Factor
   - Time to cycle through all channels= $\Delta t = \tau_{[ms]}$ X 79 channels = 227.52ms, where τ = pulse width
   - 100ms / $\Delta t_{[ms]}$ = H -> Round up to next highest integer, to account for worst case, $H' = 1$
   - Worst Case Dwell Time = $\tau_{[ms]}$ X H' = 2.88ms
   - Duty Cycle Correction = 20log(Worst Case Dwell Time / 100ms) $_{[dB]}$ = -30.81 dB

Copyright © 2012, Digital EMC Co., Ltd.

30MHz ~ 25GHz Data(Modulation: ***8DPSK***)

▪ Lowest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2386.490	H	Z	PK	61.39	-4.73	N/A	56.66	74.00	17.34
2387.040	H	Z	AV	49.29	-4.73	N/A	44.56	54.00	9.44
4804.087	V	Y	PK	70.89	2.15	-30.81	42.23	74.00	31.77
4804.033	V	Y	AV	66.04	2.15	-30.81	37.38	54.00	16.62
-	-	-	-	-	-	-	-	-	-

▪ Middle Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4881.985	V	Y	PK	68.57	2.94	-30.81	40.70	74.00	33.30
4882.069	V	Y	AV	63.91	2.94	-30.81	36.04	54.00	17.96
-	-	-	-	-	-	-	-	-	-

▪ Highest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F. (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.514	H	Z	PK	67.66	-4.59	N/A	63.07	74.00	10.93
2483.520	H	Z	AV	53.88	-4.59	N/A	49.29	54.00	4.71
4960.050	V	Y	PK	69.94	2.74	-30.81	41.87	74.00	32.13
4960.042	V	Y	AV	57.33	2.74	-30.81	29.26	54.00	24.74
-	-	-	-	-	-	-	-	-	-

Note.

1. No other spurious and harmonic emissions were reported greater than listed emissions above table.
2. Above listed point data is the worst case data.
3. Sample Calculation.
   Margin = Limit – Result / Result = Reading + T.F+ DCF / T.F = AF + CL – AG
   Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,
   DCF = Duty Cycle Correction Factor
   - Time to cycle through all channels= $\Delta t = \tau_{[ms]}$ X 79 channels = 227.52ms, where τ = pulse width
   - 100ms / $\Delta t_{[ms]} = H$ -> Round up to next highest integer, to account for worst case, $H' = 1$
   - Worst Case Dwell Time = $\tau_{[ms]}$ X H' = 2.88ms
   - Duty Cycle Correction = 20log(Worst Case Dwell Time / 100ms) $_{[dB]}$ = -30.81 dB

Copyright © 2012, Digital EMC Co., Ltd.

2.4.2. Conducted Spurious Emissions

Low Band-edge ***Lowest Channel*** & Modulation: ***GFSK***



Low Band-edge ***Hopping mode*** & Modulation: ***GFSK***

Copyright © 2012, Digital EMC Co., Ltd.

Conducted Spurious Emissions

Lowest Channel & Modulation: ***GFSK***



Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]	Δ Limit [dB]
30.000 M	1.000 G	100.00 k	385.990000 M	-47.07	-200.00
1.000 G	2.000 G	100.00 k	1.490000 G	-45.88	-200.00
2.000 G	2.400 G	100.00 k	2.399800 G	-44.31	-200.00
2.400 G	2.483 G	100.00 k	2.402150 G	5.43	-200.00
2.483 G	3.000 G	100.00 k	2.592378 G	-44.28	-200.00
3.000 G	6.000 G	100.00 k	5.629000 G	-43.52	-200.00
6.000 G	9.000 G	100.00 k	7.882333 G	-42.52	-200.00
9.000 G	12.000 G	100.00 k	11.008333 G	-41.69	-200.00
12.000 G	15.000 G	100.00 k	14.085333 G	-41.50	-200.00
15.000 G	20.000 G	100.00 k	17.480000 G	-39.14	-200.00
20.000 G	25.000 G	100.00 k	24.873333 G	-35.32	-200.00

Copyright © 2012, Digital EMC Co., Ltd.

Reference for limit

Middle Channel & Modulation: ***GFSK***

Conducted Spurious Emissions

Middle Channel & Modulation: ***GFSK***



Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]	ΔLimit [dB]
30.000 M	1.000 G	100.00 k	469.410000 M	-47.83	-200.00
1.000 G	2.000 G	100.00 k	1.108000 G	-46.13	-200.00
2.000 G	2.400 G	100.00 k	2.366880 G	-45.87	-200.00
2.400 G	2.483 G	100.00 k	2.440017 G	5.90	-200.00
2.483 G	3.000 G	100.00 k	2.699190 G	-45.06	-200.00
3.000 G	6.000 G	100.00 k	3.579000 G	-43.49	-200.00
6.000 G	9.000 G	100.00 k	8.747667 G	-42.87	-200.00
9.000 G	12.000 G	100.00 k	11.696333 G	-41.69	-200.00
12.000 G	15.000 G	100.00 k	14.010000 G	-41.54	-200.00
15.000 G	20.000 G	100.00 k	19.237778 G	-39.99	-200.00
20.000 G	25.000 G	100.00 k	24.852778 G	-35.34	-200.00

Copyright © 2012, Digital EMC Co., Ltd.

High Band-edge ***Highest Channel*** & Modulation: ***GFSK***

High Band-edge ***Hopping mode*** & Modulation: ***GFSK***

Copyright © 2012, Digital EMC Co., Ltd.

Conducted Spurious Emissions

Highest Channel & Modulation: ***GFSK***



Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]	Δ Limit [dB]
30.000 M	1.000 G	100.00 k	572.230000 M	-46.14	-200.00
1.000 G	2.000 G	100.00 k	1.812000 G	-45.65	-200.00
2.000 G	2.400 G	100.00 k	2.202880 G	-45.42	-200.00
2.400 G	2.483 G	100.00 k	2.479980 G	5.61	-200.00
2.483 G	3.000 G	100.00 k	2.675793 G	-44.66	-200.00
3.000 G	6.000 G	100.00 k	3.526333 G	-42.85	-200.00
6.000 G	9.000 G	100.00 k	8.854667 G	-42.88	-200.00
9.000 G	12.000 G	100.00 k	10.551000 G	-41.48	-200.00
12.000 G	15.000 G	100.00 k	13.436333 G	-41.77	-200.00
15.000 G	20.000 G	100.00 k	17.468333 G	-39.70	-200.00
20.000 G	25.000 G	100.00 k	24.821667 G	-35.50	-200.00

Copyright © 2012, Digital EMC Co., Ltd.

Low Band-edge ***Lowest Channel*** & Modulation: ***π/4 DQPSK***

Low Band-edge ***Hopping mode*** & Modulation: ***π/4 DQPSK***

Copyright © 2012, Digital EMC Co., Ltd.

Conducted Spurious Emissions

Lowest Channel & Modulation: ***π/4 DQPSK***



Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]	Δ Limit [dB]
30.000 M	1.000 G	100.00 k	336.520000 M	-46.73	-200.00
1.000 G	2.000 G	100.00 k	1.708000 G	-45.55	-200.00
2.000 G	2.400 G	100.00 k	2.399640 G	-43.63	-200.00
2.400 G	2.483 G	100.00 k	2.401987 G	1.98	-200.00
2.483 G	3.000 G	100.00 k	2.651931 G	-44.60	-200.00
3.000 G	6.000 G	100.00 k	4.964333 G	-44.03	-200.00
6.000 G	9.000 G	100.00 k	8.859000 G	-43.28	-200.00
9.000 G	12.000 G	100.00 k	10.551667 G	-41.60	-200.00
12.000 G	15.000 G	100.00 k	14.699333 G	-42.36	-200.00
15.000 G	20.000 G	100.00 k	18.093333 G	-39.58	-200.00
20.000 G	25.000 G	100.00 k	24.778333 G	-34.86	-200.00

Copyright © 2012, Digital EMC Co., Ltd.

Reference for limit

Middle Channel & Modulation: ***π/4 DQPSK***

Conducted Spurious Emissions

Middle Channel & Modulation: ***π/4 DQPSK***



Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]	Δ Limit [dB]
30.000 M	1.000 G	100.00 k	771.080000 M	-46.95	-200.00
1.000 G	2.000 G	100.00 k	1.034000 G	-46.01	-200.00
2.000 G	2.400 G	100.00 k	2.019000 G	-44.92	-200.00
2.400 G	2.483 G	100.00 k	2.440986 G	2.99	-200.00
2.483 G	3.000 G	100.00 k	2.787564 G	-44.83	-200.00
3.000 G	6.000 G	100.00 k	3.068000 G	-43.32	-200.00
6.000 G	9.000 G	100.00 k	8.630667 G	-43.01	-200.00
9.000 G	12.000 G	100.00 k	10.634667 G	-41.10	-200.00
12.000 G	15.000 G	100.00 k	14.591667 G	-42.23	-200.00
15.000 G	20.000 G	100.00 k	19.904444 G	-38.71	-200.00
20.000 G	25.000 G	100.00 k	24.770000 G	-34.88	-200.00

.

Copyright © 2012, Digital EMC Co., Ltd.

High Band-edge ***Highest Channel*** & Modulation: ***π/4 DQPSK***

High Band-edge ***Hopping mode*** & Modulation: ***π/4 DQPSK***

Copyright © 2012, Digital EMC Co., Ltd.

Conducted Spurious Emissions

Highest Channel & Modulation: ***π/4 DQPSK***



Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]	Δ Limit [dB]
30.000 M	1.000 G	100.00 k	386.960000 M	-46.76	-200.00
1.000 G	2.000 G	100.00 k	1.789000 G	-46.27	-200.00
2.000 G	2.400 G	100.00 k	2.104000 G	-45.62	-200.00
2.400 G	2.483 G	100.00 k	2.479972 G	2.65	-200.00
2.483 G	3.000 G	100.00 k	2.645010 G	-45.03	-200.00
3.000 G	6.000 G	100.00 k	5.285000 G	-43.63	-200.00
6.000 G	9.000 G	100.00 k	8.947000 G	-43.03	-200.00
9.000 G	12.000 G	100.00 k	11.143667 G	-41.61	-200.00
12.000 G	15.000 G	100.00 k	12.399000 G	-42.02	-200.00
15.000 G	20.000 G	100.00 k	18.079444 G	-39.26	-200.00
20.000 G	25.000 G	100.00 k	24.867778 G	-34.50	-200.00

Copyright © 2012, Digital EMC Co., Ltd.

Low Band-edge ***Lowest Channel*** & Modulation: ***8DPSK***



Low Band-edge ***Hopping mode*** & Modulation: ***8DPSK***

Copyright © 2012, Digital EMC Co., Ltd.

Conducted Spurious Emissions

Lowest Channel & Modulation: ***8DPSK***



Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]	Δ Limit [dB]
30.000 M	1.000 G	100.00 k	606.180000 M	-47.37	-200.00
1.000 G	2.000 G	100.00 k	1.931000 G	-45.82	-200.00
2.000 G	2.400 G	100.00 k	2.399640 G	-42.39	-200.00
2.400 G	2.483 G	100.00 k	2.402935 G	3.24	-200.00
2.483 G	3.000 G	100.00 k	2.942668 G	-43.99	-200.00
3.000 G	6.000 G	100.00 k	5.285333 G	-43.61	-200.00
6.000 G	9.000 G	100.00 k	8.991333 G	-41.94	-200.00
9.000 G	12.000 G	100.00 k	9.470000 G	-41.52	-200.00
12.000 G	15.000 G	100.00 k	14.164667 G	-42.04	-200.00
15.000 G	20.000 G	100.00 k	18.861111 G	-39.90	-200.00
20.000 G	25.000 G	100.00 k	24.813333 G	-35.28	-200.00

Copyright © 2012, Digital EMC Co., Ltd.

Reference for limit

Middle Channel & Modulation: ***8DPSK***

Conducted Spurious Emissions

Middle Channel & Modulation: ***8DPSK***



Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]	Δ Limit [dB]
30.000 M	1.000 G	100.00 k	374.350000 M	-47.29	-200.00
1.000 G	2.000 G	100.00 k	1.361000 G	-46.03	-200.00
2.000 G	2.400 G	100.00 k	2.314520 G	-45.51	-200.00
2.400 G	2.483 G	100.00 k	2.440832 G	2.45	-200.00
2.483 G	3.000 G	100.00 k	2.625538 G	-44.41	-200.00
3.000 G	6.000 G	100.00 k	3.354667 G	-43.93	-200.00
6.000 G	9.000 G	100.00 k	8.723333 G	-42.63	-200.00
9.000 G	12.000 G	100.00 k	10.548667 G	-41.10	-200.00
12.000 G	15.000 G	100.00 k	14.940333 G	-41.98	-200.00
15.000 G	20.000 G	100.00 k	18.323333 G	-39.05	-200.00
20.000 G	25.000 G	100.00 k	24.793333 G	-35.64	-200.00

Copyright © 2012, Digital EMC Co., Ltd.

High Band-edge ***Highest Channel*** & Modulation: ***8DPSK***



High Band-edge ***Hopping mode*** & Modulation: ***8DPSK***

Copyright © 2012, Digital EMC Co., Ltd.

Conducted Spurious Emissions

Highest Channel & Modulation: ***8DPSK***



Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	PwrAbs [dBm]	Δ Limit [dB]
30.000 M	1.000 G	100.00 k	163.860000 M	-46.85	-200.00
1.000 G	2.000 G	100.00 k	1.520000 G	-45.99	-200.00
2.000 G	2.400 G	100.00 k	2.287480 G	-45.08	-200.00
2.400 G	2.483 G	100.00 k	2.479826 G	2.70	-200.00
2.483 G	3.000 G	100.00 k	2.654565 G	-44.77	-200.00
3.000 G	6.000 G	100.00 k	4.848667 G	-43.24	-200.00
6.000 G	9.000 G	100.00 k	8.581000 G	-42.83	-200.00
9.000 G	12.000 G	100.00 k	9.992333 G	-41.59	-200.00
12.000 G	15.000 G	100.00 k	13.455333 G	-41.88	-200.00
15.000 G	20.000 G	100.00 k	17.442222 G	-38.90	-200.00
20.000 G	25.000 G	100.00 k	24.501667 G	-34.80	-200.00

Copyright © 2012, Digital EMC Co., Ltd.

3. Carrier Frequency Separation

3.1. Test Setup

Refer to the APPENDIX I.

3.2. Limit

Limit: >= 20dB BW or >= Two-Thirds of the 20dB BW

- Procedure:

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.
After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = wide enough to capture the peaks of two adjacent channels
RBW = 1% of the span
Sweep = auto
VBW = ≥ RBW
Detector function = peak
Trace = max hold

- Measurement Data: Comply

- FH mode

Hopping Mode	Test Mode	Peak of center channel (MHz)	Peak of adjacent Channel (MHz)	Test Result (MHz)
Enable	Test Case 1	2440.997	2441.999	1.002
	Test Case 2	2441.015	2442.017	1.002
	Test Case 3	2439.998	2441.000	1.002

- AFH mode

Hopping Mode	Test Mode	Peak of center channel (MHz)	Peak of adjacent Channel (MHz)	Test Result (MHz)
Enable	Test Case 1	2409.989	2410.991	1.002
	Test Case 2	2409.992	2410.994	1.002
	Test Case 3	2409.983	2410.985	1.002

Note 1: See next pages for actual measured spectrum plots.

- Minimum Standard:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

Copyright © 2012, Digital EMC Co., Ltd.

Carrier Frequency Separation (FH) Hopping mode: Enable & Test Case 1



Carrier Frequency Separation (FH) Hopping mode: Enable & Test Case 2



Copyright © 2012, Digital EMC Co., Ltd.

Carrier Frequency Separation (FH) Hopping mode: Enable & Test Case 3



Copyright © 2012, Digital EMC Co., Ltd.

Carrier Frequency Separation (AFH) Hopping mode: Enable & Test Case 1



Carrier Frequency Separation (AFH) Hopping mode: Enable & Test Case 2



Copyright © 2012, Digital EMC Co., Ltd.

Carrier Frequency Separation (AFH) Hopping mode: Enable & Test Case 3



Copyright © 2012, Digital EMC Co., Ltd.

4. Number of Hopping Frequencies

4.1. Test Setup

Refer to the APPENDIX I.

4.2. Limit

Limit: >= 15 hops

- Procedure:

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.
To get higher resolution, four frequency ranges within the 2400 ~ 2483.5 MHz FH band were examined.

The spectrum analyzer is set to:

Span = 25MHz
Plot 1: Start Frequency = 2389.5MHz, Stop Frequency = 2414.5 MHz
Plot 2: Start Frequency = 2414.5MHz, Stop Frequency = 2439.5 MHz
Plot 3: Start Frequency = 2439.5MHz, Stop Frequency = 2464.5 MHz
Plot 4: Start Frequency = 2464.5MHz, Stop Frequency = 2489.5 MHz
RBW = 1% of the span or more
Sweep = auto
VBW = ≥ RBW
Detector function = peak
Trace = max hold

- **Measurement Data: Comply**
- **FH mode**

Hopping mode	Test mode	Test Result (Total Hops)
Enable	Test Case 1	79
	Test Case 2	79
	Test Case 3	79

- AFH mode

Hopping mode	Test mode	Test Result (Total Hops)
Enable	Test Case 1	20
	Test Case 2	20
	Test Case 3	20

Note 1: See next pages for actual measured spectrum plots.

- Minimum Standard:

At least 15 hopes

Copyright © 2012, Digital EMC Co., Ltd.

Number of Hopping Frequencies 1(FH) Hopping mode: Enable & Test Case 1



Number of Hopping Frequencies 2(FH) Hopping mode: Enable & Test Case 1



Copyright © 2012, Digital EMC Co., Ltd.

Number of Hopping Frequencies 3(FH) Hopping mode: Enable & Test Case 1



Number of Hopping Frequencies 4(FH) Hopping mode: Enable & Test Case 1



Copyright © 2012, Digital EMC Co., Ltd.

Number of Hopping Frequencies 1(FH) Hopping mode: Enable & Test Case 2



Number of Hopping Frequencies 2(FH) Hopping mode: Enable & Test Case 2



Copyright © 2012, Digital EMC Co., Ltd.

Number of Hopping Frequencies 3(FH) Hopping mode: Enable & Test Case 2



Number of Hopping Frequencies 4(FH) Hopping mode: Enable & Test Case 2



Copyright © 2012, Digital EMC Co., Ltd.

Number of Hopping Frequencies 1(FH) Hopping mode: Enable & Test Case 3



Number of Hopping Frequencies 2(FH) Hopping mode: Enable & Test Case 3



Copyright © 2012, Digital EMC Co., Ltd.

Number of Hopping Frequencies 3(FH) Hopping mode: Enable & Test Case 3



Number of Hopping Frequencies 4(FH) Hopping mode: Enable & Test Case 3



Copyright © 2012, Digital EMC Co., Ltd.

Number of Hopping Frequencies 1(AFH) Hopping mode: Enable & Test Case 1



Number of Hopping Frequencies 1(AFH) Hopping mode: Enable & Test Case 2



Copyright © 2012, Digital EMC Co., Ltd.

Number of Hopping Frequencies 1(AFH) Hopping mode: Enable & Test Case 3



Copyright © 2012, Digital EMC Co., Ltd.

5. 20dBc BW

5.1. Test Setup

Refer to the APPENDIX I.

5.2. Limit

Limit: Not Applicable

5.3. Test Procedure

1. The 20dBc bandwidth were measured with a spectrum analyzer connected to RF antenna connector(conducted measurement) while EUT was operating in transmit mode. The analyzer center frequency was set to the EUT carrier frequency, using the analyzer.

2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ RBW, Span = 3 ㎒.

5.4. Test Results

Ambient temperature : 23 °C
Relative humidity : 51 %

Modulation	Tested Channel	20dBc BW (MHz)
GFSK	**Lowest**	**0.923**
	Middle	**0.933**
	Highest	**0.941**
π/4 DQPSK	**Lowest**	**1.250**
	Middle	**1.314**
	Highest	**1.315**
8DPSK	**Lowest**	**1.258**
	Middle	**1.329**
	Highest	**1.299**

Note 1: See next pages for actual measured spectrum plots.

Copyright © 2012, Digital EMC Co., Ltd.

20dBc Bandwidth ***Lowest Channel*** & Modulation: ***GFSK***



20dBc Bandwidth ***Middle Channel*** & Modulation: ***GFSK***

Copyright © 2012, Digital EMC Co., Ltd.

20dBc Bandwidth ***Highest Channel*** & Modulation: ***GFSK***



20dBc Bandwidth ***Lowest Channel*** & Modulation: ***π/4 DQPSK***

Copyright © 2012, Digital EMC Co., Ltd.

20dBc Bandwidth ***Middle Channel*** & Modulation: ***π/4 DQPSK***

20dBc Bandwidth ***Highest Channel*** & Modulation: ***π/4 DQPSK***

Copyright © 2012, Digital EMC Co., Ltd.

20dBc Bandwidth ***Lowest Channel*** & Modulation: ***8DPSK***



20dBc Bandwidth ***Middle Channel*** & Modulation: ***8DPSK***



Copyright © 2012, Digital EMC Co., Ltd.

20dBc Bandwidth ***Highest Channel*** & Modulation: ***8DPSK***

Copyright © 2012, Digital EMC Co., Ltd.

6. Time of Occupancy (Dwell Time)

6.1. Test Setup

Refer to the APPENDIX I.

6.2. Limit

Limit: Not Applicable

6.3. Test Procedure

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = 2441 MHz
RBW = 1 MHz
Trace = max hold
Span = zero
VBW = ≥ RBW
Detector function = peak

6.4. Test Results

Ambient temperature : 23 °C
Relative humidity : 51 %

- FH mode

Hopping mode	Packet Type	Number of hopping Channels	Burst On Time (ms)	Period (ms)	Test Result (s)
Enable	DH 5	79	2.88	3.75	0.3072
	2 DH 5	79	2.88	3.75	0.3072
	3 DH 5	79	2.88	3.75	0.3072

- AFH mode

Hopping mode	Packet Type	Number of hopping Channels	Burst On Time (ms)	Period (ms)	Test Result (s)
Enable	DH 5	20	2.88	3.75	0.3072
	2 DH 5	20	2.88	3.75	0.3072
	3 DH 5	20	2.88	3.75	0.3072

Note 1: Each new transmission event begins on the next channel in the hopping sequence after the final channel used in the previous transmission event.
DWELL TIME = (0.4 x Number of hopping Channels) x Burst On time / (period x Number of hopping Channels)
Note 2: See next pages for actual measured spectrum plots.

Copyright © 2012, Digital EMC Co., Ltd.

Time of Occupancy (FH) Hopping mode: Enable & Test Case 1



Time of Occupancy (FH) Hopping mode: Enable & Test Case 2



Copyright © 2012, Digital EMC Co., Ltd.

Time of Occupancy (FH) Hopping mode: Enable & Test Case 3



Copyright © 2012, Digital EMC Co., Ltd.

Time of Occupancy (AFH) Hopping mode: Enable & Test Case 1



Time of Occupancy (AFH) Hopping mode: Enable & Test Case 2



Copyright © 2012, Digital EMC Co., Ltd.

Time of Occupancy (AFH) Hopping mode: Enable & Test Case 3



Copyright © 2012, Digital EMC Co., Ltd.

7. Maximum Peak Output Power Measurement

7.1. Test Setup

Refer to the APPENDIX I.

7.2. Limit

The maximum peak output power of the intentional radiator shall not exceed the following :

1. §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 ㎑ or the 20 ㏈ bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 ㎽.

2. §15.247(b)(1), For frequency hopping systems operating in the 2 400 – 2 483.5 ㎒ employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5 725 – 5 805 ㎒ band: 1 Watt.

7.3. Test Procedure

1. The RF power output was measured with a Spectrum analyzer connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency, A spectrum analyzer was used to record the shape of the transmit signal.

2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using ;
   Span = approximately 10 times the 20 ㏈ bandwidth, centered on a hopping channel
   RBW ≥ 20㏈ BW
   VBW ≥ RBW
   Sweep = auto
   Detector function = peak
   Trace = max hold

Copyright ⓒ 2012, Digital EMC Co., Ltd.

7.4. Test Results

Ambient temperature : 23 °C
Relative humidity : 51 %

Modulation	Tested Channel	Peak Output Power	
		dBm	mW
GFSK	**Lowest**	5.36	3.439
	Middle	**6.32**	**4.285**
	Highest	5.74	3.750
π/4 DQPSK	**Lowest**	3.49	2.234
	Middle	**4.45**	**2.786**
	Highest	3.88	2.443
8DPSK	**Lowest**	3.82	2.410
	Middle	**4.83**	**3.041**
	Highest	4.04	2.535

Note 1: See next pages for actual measured spectrum plots.

Copyright © 2012, Digital EMC Co., Ltd.

Peak Output Power ***Lowest Channel*** & Modulation: ***GFSK***



Peak Output Power ***Middle Channel*** & Modulation: ***GFSK***



Copyright © 2012, Digital EMC Co., Ltd.

Peak Output Power ***Highest Channel*** & Modulation: ***GFSK***



Peak Output Power ***Lowest Channel*** & Modulation: ***π/4 DQPSK***



Copyright © 2012, Digital EMC Co., Ltd.

Peak Output Power ***Middle Channel*** & Modulation: ***π/4 DQPSK***



Peak Output Power ***Highest Channel*** & Modulation: ***π/4 DQPSK***



Copyright © 2012, Digital EMC Co., Ltd.

Peak Output Power ***Lowest Channel*** & Modulation: ***8DPSK***



Peak Output Power ***Middle Channel*** & Modulation: ***8DPSK***



Copyright © 2012, Digital EMC Co., Ltd.

Peak Output Power ***Highest Channel*** & Modulation: ***8DPSK***



Copyright © 2012, Digital EMC Co., Ltd.

8. Transmitter AC Power Line Conducted Emission

8.1. Test Setup

Refer to test setup photo.

8.2. Limit

According to §15.207(a) for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 ㎑ to 30 ㎒, shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network(LISN).
Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

8.3. Test Procedures

Conducted emissions from the EUT were measured according to the dictates of ANSI C63.4:2003

1. The test procedure is performed in a 6.5 m × 3.5 m × 3.5 m (L × W × H) shielded room. The EUT along with its peripherals were placed on a 1.0 m (W) × 1.5 m (L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

Copyright © 2012, Digital EMC Co., Ltd.

8.4. Test Results

AC Line Conducted Emissions (Graph) & Modulation: ***GFSK***

Digital EMC

Results of Conducted Emission

Digital EMC
Date : 2012-11-22

Model No.	:	MB0502LX	Referrence No.	:	
Type	:		Power Supply	:	120 V, 60 Hz
Serial No.	:	NONE	Temp/Humi.	:	23 'C, 45 % R.H.
Test Condition	:	BLUETOOTH	Operator	:	Hong-Hee, Lee

Memo :

LIMIT : CISPR22_B QP
CISPR22_B AV





Copyright © 2012, Digital EMC Co., Ltd.

AC Line Conducted Emissions (List) & Modulation: ***GFSK***

Results of Conducted Emission

Digital EMC
Date : 2012-11-22

Model No.	:	MB0502LX	Referrence No.	:	
Type	:		Power Supply	:	120 V, 60 Hz
Serial No.	:	NONE	Temp/Humi.	:	23 'C, 45 % R.H.
Test Condition	:	BLUETOOTH	Operator	:	Hong-Hee, Lee

Memo :

LIMIT : CISPR22_B QP
CISPR22_B AV

NO	FREQ	READING QP	READING AV	C.FACTOR	RESULT QP	RESULT AV	LIMIT QP	LIMIT AV	MARGIN QP	MARGIN AV	PHASE
	[MHz]	[dBuV]	[dBuV]	[dB]	[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dBuV]	
1	0.15961	52.4	34.9	0.2	52.6	35.1	65.5	55.5	12.9	20.4	N
2	0.17995	49.6	28.5	0.2	49.8	28.7	64.5	54.5	14.7	25.8	N
3	0.24450	39.6	20.5	0.2	39.8	20.7	61.9	51.9	22.1	31.2	N
4	0.58413	40.5	32.5	0.2	40.7	32.7	56.0	46.0	15.3	13.3	N
5	4.58800	24.4	15.8	0.4	24.8	16.2	56.0	46.0	31.2	29.8	N
6	13.97150	24.7	15.5	0.7	25.4	16.2	60.0	50.0	34.6	33.8	N
7	0.16395	51.6	32.4	0.2	51.8	32.6	65.3	55.3	13.5	22.7	L1
8	0.18319	48.2	27.3	0.2	48.4	27.5	64.3	54.3	15.9	26.8	L1
9	0.24461	39.0	19.9	0.2	39.2	20.1	61.9	51.9	22.7	31.8	L1
10	0.59215	38.0	30.5	0.2	38.2	30.7	56.0	46.0	17.8	15.3	L1
11	3.85350	23.6	17.1	0.3	23.9	17.4	56.0	46.0	32.1	28.6	L1
12	13.55350	26.0	16.2	0.7	26.7	16.9	60.0	50.0	33.3	33.1	L1

Copyright © 2012, Digital EMC Co., Ltd.

9. Antenna Requirement

▣ **Procedure:**

Describe how the EUT complies with the requirement that either its antenna is permanently attached, or that it employs a unique antenna connector, for every antenna proposed for use with the EUT.

▣ **Conclusion: Comply**

The internal antenna is attached on the main PCB using the special spring tension. (Refer to Internal Photo file.)

▣ **Minimum Standard:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions.

Copyright © 2012, Digital EMC Co., Ltd.