

EMF TEST REPORT

Test Report No. : OT-212-RWD-055

Reception No. : 2012005262

Applicant : LG Electronics USA

Address : 111 Sylvan Avenue North Building, Englewood Cliffs, New Jersey, United States

Manufacturer : LG Electronics Inc.

Address : 10, Magokjungang 10-ro, Gangseo-gu, Seoul, Republic of Korea

Type of Equipment : CAR NAVIGATION SYSTEM

FCC ID. : BEJCCICUS

Model Name : CCIC US

Serial number : N/A

Total page of Report : 14 pages (including this page)

Date of Incoming : January 08, 2021

Date of issue : February 16, 2021

SUMMARY

The equipment complies with the regulation; *FCC PART 15 SUBPART C Section 15.247 and FCC PART 15 SUBPART E Section 15.407*

This test report only contains the result of a single test of the sample supplied for the examination.


It is not a generally valid assessment of the features of the respective products of the mass-production.



Tested by
Ju Yun Park / Manager
ONETECH Corp.



Reviewed by
Ha-Ram Lee / Manager
ONETECH Corp.



Approved by
Ki-Hong, Nam / General Manager
ONETECH Corp.

CONTENTS

	PAGE
1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	7
3. EUT MODIFICATIONS.....	7
4. MAXIMUM PERMISSIBLE EXPOSURE.....	8
4.1 RF EXPOSURE CALCULATION	8
4.2 EUT DESCRIPTION.....	8
4.3 CALCULATED MPE SAFE DISTANCE FOR WLAN.....	9
4.3.1 DATA for WLAN 2.4 GHz.....	9
4.3.2 DATA for WLAN 5 GHz (Antenna 0).....	10
4.3.3 DATA for WLAN 5 GHz (Antenna 1).....	11
4.3.4 DATA for Multiple Transmit (WLAN 5 GHz).....	12
4.4 CALCULATED MPE SAFE DISTANCE FOR BLUETOOTH	13
4.6 DATA FOR INTERMODULATION TRANSMIT	14

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-212-RWD-055	February 16, 2021	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : LG Electronics USA
 Address : 111 Sylvan Avenue North Building, Englewood Cliffs, New Jersey, United States
 Contact Person : Dae Woong Kim / Director, Regulatory and Environmental Affairs
 Telephone No. : 201-266-2215
 FCC ID : BEJCCICUS
 Model Name : CCIC US
 Brand Name : LG
 Serial Number : N/A
 Date : February 16, 2021

EQUIPMENT CLASS	DSS – PART 15 SPREAD SPECTRUM TRANSMITTER DTS – DIGITAL TRNSMISSION SYSTEM Unlicensed National Information infrastructure(UNII)
E.U.T. DESCRIPTION	CAR NAVIGATION SYSTEM
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02 FCC PART 15 SUBPART E Section 15.407 789033 D02 General UNII Test Procedures New Rules v02r01
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The LG Electronics USA, Model CCIC US (referred to as the EUT in this report) is a CAR NAVIGATION SYSTEM. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	CAR NAVIGATION SYSTEM		
Temperature Range	-30 °C ~ 85 °C		
OPERATING FREQUENCY	Bluetooth	2 402 MHz ~ 2 480 MHz	
	WLAN 2.4 GHz	2 412 MHz ~ 2 462 MHz (802.11b/g/n(HT20))	
	5 150 MHz ~ 5 250 MHz Band	5 180 MHz ~ 5 240 MHz (802.11a/n(HT20)/ac(VHT20))	
		5 190 MHz ~ 5 230 MHz (802.11n(HT40)/ac(VHT40))	
		5 210 MHz (802.11ac(VHT80))	
	5 725 MHz ~ 5 850 MHz Band	5 745 MHz ~ 5 825 MHz (802.11a/n(HT20)/ac(VHT20))	
		5 755 MHz ~ 5 795 MHz (802.11n(HT40)/ac(VHT40))	
5 775 MHz (802.11ac(VHT80))			
MODULATION TYPE	Bluetooth	GFSK for 1Mbps, $\pi/4$ -DQPSK for 2Mbps, 8-DPSK for 3Mbps	
	WLAN 2.4 GHz	802.11b: DSSS Modulation(DBPSK/DQPSK/CCK) 802.11g/n(HT20): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)	
	WLAN 5 GHz	802.11a/n(HT20)/n(HT40)/ac(VHT80): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)	
RF OUTPUT POWER	Bluetooth	1 Mbps	-0.05 dBm
		2 Mbps	-2.30 dBm
		3 Mbps	-1.87 dBm
	WLAN 2.4 GHz	15.15 dBm(802.11b) 11.58 dBm(802.11g) 11.54 dBm(802.11n_HT20)	

RF OUTPUT POWER	5 150 MHz ~ 5 250 MHz Band	Antenna 0	10.60 dBm(802.11a) 10.05 dBm(802.11n_HT20) 5.63 dBm(802.11ac_VHT20) 7.16 dBm(802.11n_HT40) 5.11 dBm(802.11ac_VHT40) 5.24 dBm(802.11ac_VHT80)
		Antenna 1	12.28 dBm(802.11a) 12.03 dBm(802.11n_HT20) 7.77 dBm(802.11ac_VHT20) 9.25 dBm(802.11n_HT40) 6.78 dBm(802.11ac_VHT40) 6.72 dBm(802.11ac_VHT80)
		Multiple Antenna	14.47 dBm(802.11a) 14.16 dBm(802.11n_HT20) 9.84 dBm(802.11ac_VHT20) 11.34 dBm(802.11n_HT40) 9.03 dBm(802.11ac_VHT40) 9.05 dBm(802.11ac_VHT80)
	5 725 MHz ~ 5 850 MHz Band	Antenna 0	10.44 dBm(802.11a) 10.23 dBm(802.11n_HT20) 5.98 dBm(802.11ac_VHT20) 10.05 dBm(802.11n_HT40) 5.70 dBm(802.11ac_VHT40) 5.62 dBm(802.11ac_VHT80)
		Antenna 1	11.88 dBm(802.11a) 12.14 dBm(802.11n_HT20) 8.91 dBm(802.11ac_VHT20) 11.91 dBm(802.11n_HT40) 8.52 dBm(802.11ac_VHT40) 8.15 dBm(802.11ac_VHT80)
		Multiple Antenna	14.13 dBm(802.11a) 14.26 dBm(802.11n_HT20) 10.57 dBm(802.11ac_VHT20) 14.06 dBm(802.11n_HT40) 10.35 dBm(802.11ac_VHT40) 10.08 dBm(802.11ac_VHT80)

ANTENNA TYPE	PCB Antenna		
ANTENNA GAIN	Bluetooth	-1.59 dBi	
	WLAN 2.4 GHz	-1.45 dBi	
	5 150 MHz ~ 5 250 MHz Band	Antenna 0	-1.15 dBi
		Antenna 1	-0.89 dBi
		Multiple Antenna	1.99 dBi
	5 725 MHz ~ 5 850 MHz Band	Antenna 0	-1.08 dBi
		Antenna 1	-1.07 dBi
		Multiple Antenna	1.94 dBi
	List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	8 MHz, 24 MHz, 24.576 MHz, 25 MHz, 26 MHz, 32 MHz, 37.4 MHz, 38.4 MHz, 55.46667 MHz	
Rated Supply Voltage	DC 12.0 V		

Note. : - Bluetooth transmit simultaneously with 2.4 GHz or 5 GHz WiFi.

- Directional Gain Calculations

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{\text{ANT}}] \text{ dBi}$$

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. EUT MODIFICATIONS

-. None

4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are $f/1500$ mW/cm² for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm² for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm² exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm², Z = Impedance of free space, 377 Ω

E = Electric field strength in V/m, G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm, using P (mW) = P (W) / 1 000, d (cm) = 0.01 * d (m)

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm, P = Power in mW, G = Numeric antenna gain, and S = Power density in mW/cm²

4.2 EUT Description

Kind of EUT	CAR NAVIGATION SYSTEM
Device Category	<input type="checkbox"/> Portable (< 20 cm separation) <input type="checkbox"/> Mobile (> 20 cm separation) <input checked="" type="checkbox"/> Others
Exposure Evaluation Applied	<input checked="" type="checkbox"/> MPE <input type="checkbox"/> SAR <input type="checkbox"/> N/A

4.3 Calculated MPE Safe Distance for WLAN

4.3.1 DATA for WLAN 2.4 GHz

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)	Log	Linear			
2 400 ~ 2 483.5	802.11b	15.15 ± 1.0	16.15	41.21	-1.45	0.716	1.53	0.005 9	1
	802.11g	11.58 ± 1.0	12.58	18.11			1.02	0.002 6	1
	802.11n_HT20	11.54 ± 1.0	12.54	17.95			1.01	0.002 6	1

According to above table, for 2 400 ~ 2483.5 MHz Band(802.11 b), safe distance,

$$D = 0.282 * \sqrt{(41.21 * 0.716)/1.00} = 1.53 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 41.21 * 0.716 / (4 * \pi * 20^2) = 0.005 9$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

4.3.2 DATA for WLAN 5 GHz (Antenna 0)

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)	Log	Linear			
5 150 ~ 5 250	802.11a	10.60 ± 1.0	11.60	14.45	-1.15	0.767	0.94	0.002 2	1
	802.11n_HT20	10.05 ± 1.0	11.05	12.74			0.88	0.001 9	1
	802.11ac_VHT20	5.63 ± 1.0	6.63	4.60			0.53	0.000 7	1
	802.11n_HT40	7.16 ± 1.0	8.16	6.55			0.63	0.001 0	1
	802.11ac_VHT40	5.11 ± 1.0	6.11	4.08			0.50	0.000 6	1
	802.11ac_VHT80	5.24 ± 1.0	6.24	4.21			0.51	0.000 6	1
5 725 ~ 5 850	802.11a	10.44 ± 1.0	11.44	13.93	-1.80	0.661	0.86	0.001 8	1
	802.11n_HT20	10.23 ± 1.0	11.23	13.27			0.84	0.001 7	1
	802.11ac_VHT20	5.98 ± 1.0	6.96	4.99			0.51	0.000 7	1
	802.11n_HT40	10.05 ± 1.0	11.05	12.74			0.82	0.001 7	1
	802.11ac_VHT40	5.70 ± 1.0	6.70	4.68			0.50	0.000 6	1
	802.11ac_VHT80	5.62 ± 1.0	6.62	4.59			0.49	0.000 6	1

According to above table, for 5 150 ~ 5 250 MHz Band(802.11 a), safe distance,

$$D = 0.282 * \sqrt{(14.45 * 0.767)/1.00} = 0.94 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 14.45 * 0.767 / (4 * \pi * 20^2) = 0.002 2$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

4.3.3 DATA for WLAN 5 GHz (Antenna 1)

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)	Log	Linear			
5 150 ~ 5 250	802.11a	12.28 ± 1.0	13.28	21.28	-0.89	0.815	1.17	0.003 4	1
	802.11n_HT20	12.03 ± 1.0	12.03	20.09			1.14	0.003 3	1
	802.11ac_VHT20	7.77 ± 1.0	8.77	7.53			0.70	0.001 2	1
	802.11n_HT40	9.25 ± 1.0	10.25	10.59			0.83	0.001 7	1
	802.11ac_VHT40	6.78 ± 1.0	7.78	6.00			0.62	0.001 0	1
	802.11ac_VHT80	6.72 ± 1.0	7.72	5.92			0.62	0.001 0	1
5 725 ~ 5 850	802.11a	11.88 ± 1.0	12.88	19.41	-1.07	0.782	1.10	0.003 0	1
	802.11n_HT20	12.14 ± 1.0	13.14	20.61			1.13	0.003 2	1
	802.11ac_VHT20	8.91 ± 1.0	9.91	9.79			0.78	0.001 5	1
	802.11n_HT40	11.91 ± 1.0	12.91	19.54			1.10	0.003 0	1
	802.11ac_VHT40	8.52 ± 1.0	9.52	8.95			0.75	0.001 4	1
	802.11ac_VHT80	8.15 ± 1.0	9.15	8.22			0.71	0.001 3	1

According to above table, for 5 150 ~ 5 250 MHz Band(802.11 a), safe distance,

$$D = 0.282 * \sqrt{(21.28 * 0.815)/1.00} = 1.17 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 21.28 * 0.815 / (4 * \pi * 20^2) = 0.003 4$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

4.3.4 DATA for Multiple Transmit (WLAN 5 GHz)

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Power Density (mW/cm ²) @ 20 cm Separation	Sum Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)			
5 150 ~ 5 250	802.11a	10.60 ± 1.0	11.60	14.45	0.002 2	0.005 6	1.00
		12.28 ± 1.0	13.28	21.28	0.003 4		
	802.11n_HT20	10.05 ± 1.0	11.05	12.74	0.001 9	0.005 2	1.00
		12.03 ± 1.0	13.03	20.09	0.003 3		
	802.11ac_VHT20	5.63 ± 1.0	6.63	4.60	0.000 7	0.001 9	1.00
		7.77 ± 1.0	8.77	7.53	0.001 2		
	802.11n_HT40	7.16 ± 1.0	8.16	6.55	0.001 0	0.002 7	1.00
		9.25 ± 1.0	10.25	10.59	0.001 7		
	802.11ac_VHT40	5.11 ± 1.0	6.11	4.08	0.000 6	0.001 6	1.00
		6.78 ± 1.0	7.78	6.00	0.001 0		
	802.11ac_VHT80	5.24 ± 1.0	6.24	4.21	0.000 6	0.001 6	1.00
		6.72 ± 1.0	7.72	5.92	0.001 0		
5 725 ~ 5 850	802.11a	10.44 ± 1.0	11.44	13.93	0.001 8	0.004 8	1.00
		11.88 ± 1.0	12.88	19.41	0.003 0		
	802.11n_HT20	10.23 ± 1.0	11.23	13.27	0.001 7	0.004 9	1.00
		12.14 ± 1.0	13.14	20.61	0.003 2		
	802.11ac_VHT20	5.98 ± 1.0	6.98	4.99	0.000 7	0.002 2	1.00
		8.91 ± 1.0	9.91	9.79	0.001 5		
	802.11n_HT40	10.05 ± 1.0	11.05	12.74	0.001 7	0.004 7	1.00
		11.91 ± 1.0	12.91	19.54	0.003 0		
	802.11ac_VHT40	5.70 ± 1.0	6.70	4.68	0.000 6	0.002 0	1.00
		8.52 ± 1.0	9.52	8.95	0.001 4		
	802.11ac_VHT80	5.62 ± 1.0	6.62	4.59	0.000 6	0.001 9	1.00
		8.15 ± 1.0	9.51	8.22	0.001 3		

$$\text{WLAN 5 GHz}(802.11 \text{ a}) = (0.002 \text{ 2}/1) + (0.003 \text{ 4}/1) = 0.005 \text{ 6}$$

4.4 Calculated MPE Safe Distance for Bluetooth

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)	Log	Linear			
2 402 ~ 2 480	1 Mbps	-0.05 ± 1.0	0.95	1.24	-1.59	0.693	0.26	0.000 17	1.00
	2 Mbps	-2.30 ± 1.0	-1.30	0.74			0.20	0.000 10	1.00
	3 Mbps	-1.87 ± 1.0	-0.87	0.82			0.21	0.000 11	1.00

According to above table, for 2 402 ~ 2480 MHz Band(1 Mbps), safe distance,

$$D = 0.282 * \sqrt{(1.24 * 0.693)/1.00} = 0.26 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 1.24 * 0.693 / (4 * \pi * 20^2) = 0.000 17$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

4.6 DATA for Intermodulation Transmit

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Power Density (mW/cm ²) @ 20 cm Separation	Sum Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)			
Bluetooth + WLAN 2 G	Bluetooth (1 Mbps)	-0.05 ± 1.0	0.95	1.24	0.000 17	0.006 07	1.00
	WLAN 2 G (802.11 b)	15.15 ± 1.0	16.15	41.21	0.005 9		

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Power Density (mW/cm ²) @ 20 cm Separation	Sum Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)			
Bluetooth + WLAN 5 G	Bluetooth (1 Mbps)	-0.05 ± 1.0	0.95	1.24	0.000 17	0.003 57	1.00
	WLAN 5 G (UNII 1 802.11 a Ant 1)	12.28 ± 1.0	13.28	21.28	0.003 4		