



PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA

Tel. 410.290.6652 / Fax 410.290.6554

http://www.pctestlab.com



CERTIFICATE OF COMPLIANCE (SAR EVALUATION)

Applicant Name:
LG Electronics USA
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States

Date of Testing:
10/12/06 - 10/16/06
Test Site/Location:
PCTEST Lab, Columbia, MD, USA
Test Report Serial No.:
0610110884

FCC ID: BEJCU400

APPLICANT: LG ELECTRONICS USA

EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth
Application Type: Class II Permissive Change
FCC Rule Part(s): §2.1093; FCC/OET Bulletin 65 Supplement C [July 2001]
FCC Classification: Licensed Transmitter Held to Ear (PCE)
Model(s): CU400
Tx Frequency: 824.20 - 848.80 MHz (Cellular GSM) / 1850.20 - 1909.80 MHz (GSM PCS)
826.40 - 846.60 MHz (Cellular WCDMA)/1852.4 - 1907.6 MHz (PCS WCDMA)
Conducted Power: 32.5 dBm : GSM850MHz / 29.2 dBm : GSM1900MHz
23.1 dBm : WCDMA 850MHz / 22.56 dBm : WCDMA 1900MHz
Max. SAR Measurement: 0.706 W/kg UMTS Head SAR / 0.498 W/kg UMTS Body SAR
0.474 W/kg PCS Head SAR 0.25 W/kg PCS Body SAR
0.773W/kg GSM850MHz Head SAR / 1.14W/kg GSM850MHz Body SAR
0.355W/kg GSM1900MHz Head SAR / 0.34W/kg GSM1900MHz Body SAR
Test Device Serial No. Pre-Production [S/N: SAR#1]
Date of original Grant Aug 10, 2006
Class II Permissive Change(s): See Attachment

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE Std. C95.1-2005 and had been tested in accordance with the measurement procedures specified in FCC/OET Bulletin 65 Supplement C (2001) and IEEE Std. 1528-2003.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant Conditions: Power output listed is ERP for Part 22 and EIRP for Part 24. SAR compliance for body-worn operating configuration is based on a separation distance of 1.5 cm between the back of the unit and the body of the user. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance. Belt clips or holsters may not contain metallic components.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.



Randy Ortanez
President



| | | | | |
|------------------------------------|---|--|--------------|--|
| FCC ID: BEJCU400 | | CERTIFICATION REPORT | | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | Page 1 of 26 | |

TABLE OF CONTENTS

| | | |
|----|--|----|
| 1 | INTRODUCTION | 3 |
| 2 | TEST SITE LOCATION | 4 |
| 3 | SAR MEASUREMENT SETUP | 5 |
| 4 | DASY E-FIELD PROBE SYSTEM..... | 7 |
| 5 | PROBE CALIBRATION PROCESS..... | 8 |
| 6 | PHANTOM AND EQUIVALENT TISSUES..... | 9 |
| 7 | DOSIMETRIC ASSESSMENT & PHANTOM SPECS | 10 |
| 8 | DEFINITION OF REFERENCE POINTS | 11 |
| 9 | TEST CONFIGURATION POSITIONS | 12 |
| 10 | ANSI/IEEE C95.1 - 1992 RF EXPOSURE LIMITS..... | 14 |
| 11 | MEASUREMENT UNCERTANTIES | 15 |
| 12 | SYSTEM VERIFICATION..... | 16 |
| 13 | DEVICE TEST CONDITIONS | 17 |
| 14 | SAR DATA SUMMARY | 18 |
| 15 | EQUIPMENT LIST..... | 23 |
| 16 | CONCLUSION | 24 |
| 17 | REFERENCES | 25 |

| | | | | |
|------------------------------------|---|--|---|--|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 2 of 26 |

1

INTRODUCTION

The FCC has adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices.[1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz. (c) 1992 by the Institute of Electrical and Electronics Engineers, Inc., New York, New York 10017.[2] The measurement procedure described in IEEE/ANSI C95.3-1992 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave[3] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," NCRP Report No. 86 (c) NCRP, 1986, Bethesda, MD 20814.[6] SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

1.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Fig. 1-1).

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dV} \right)$$

Figure 1-1
SAR Mathematical Equation



SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \sigma E^2 / \rho$$

where:

- σ = conductivity of the tissue-simulant material (S/m)
- ρ = mass density of the tissue-simulant material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 3 of 26 |

2 TEST SITE LOCATION

2.1 INTRODUCTION

The map at the right shows the location of the PCTEST LABORATORY in Columbia, Maryland. It is in proximity to the FCC Laboratory, the Baltimore-Washington International (BWI) airport, the city of Baltimore and Washington, DC (See Figure 2).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49' 38" W longitude. The facility is 1.5 miles north of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 2002.





Fig 2-1
Map of the Greater Baltimore and Metropolitan Washington, D.C. area

2.2 Test Facility / A2LA Accreditation:

Measurements were performed at an independent accredited PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC 2451).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) for Specific Absorption Rate (SAR) testing, CTIA Test Plans, FCC, HAC, CTIA OTA and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the US-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules.
- PCTEST facility is an IC registered (IC-2451) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) in AMPS and CDMA mobile phones.

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 4 of 26 |

3 SAR MEASUREMENT SETUP

3.1 Robotic System

Measurements are performed using the DASY4 automated dosimetric assessment system. The DASY4 is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland and consists of high precision robotics system (Staubli), robot controller, Pentium III computer, near-field probe, probe alignment sensor, and the generic twin phantom containing the brain equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Fig. 3.1).

3.2 System Hardware

A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and a remote control used to drive the robot motors. The PC consists of the Gateway Pentium 4 2.53 GHz computer with Windows XP system and SAR Measurement Software DASY4, A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit that performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.

3.3 System Electronics






Fig 3-1
SAR Measurement System Setup

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer. The system is described in detail in [7].

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 5 of 26 |

3.4 Automated Test System Specifications

Positioner

Robot: Stäubli Unimation Corp. Robot RX60L
 Repeatability: 0.02 mm
 No. of Axes: 6

Data Acquisition Electronic System (DAE)

Cell Controller

Processor: Pentium 4
 Clock Speed: 2.53 GHz
 Operating System: Windows XP Professional

Data Converter

Features: Signal Amplifier, multiplexer, A/D converter & control logic
 Software: DASY4, SEMCAD software
 Connecting Lines: Optical Downlink for data and status info
 Optical upload for commands and clock

PC Interface Card



Function: 24-bit (64 MHz) DSP for real-time processing
 Link to DAE
 16-bit A/D converter for surface detection system
 Serial link to robotics
 Direct emergency stop output for robot

Phantom

Type: SAM Twin Phantom (V4.0)
 Shell Material: Composite
 Thickness: 2.0 ± 0.2 mm



**Fig 3-2
 DASY4 SAR Measurement System**

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | Page 6 of 26 | |

4.1 Probe Measurement System

The SAR measurements were conducted with the dosimetric probe ET3DV6, designed in the classical triangular configuration [7] (see Fig. 3.2) and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi-fiber line ending at the front of the probe tip (see Fig. 3.3). It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 software reads the reflection during a software approach and looks for the maximum using a 2nd order fitting (see Fig 5-1). The approach is stopped at reaching the maximum.




Fig 4-1
SAR System

4.2 Probe Specifications



| | |
|--------------------------|---|
| Model: | EX3DV4 |
| Frequency Range: | 10 MHz – 6.0 GHz |
| Calibration: | In brain and muscle simulating tissue at Frequencies from 835 up to 5800MHz |
| Linearity: | ± 0.2 dB (30 MHz to 6 GHz) |
| Dynamic Range: | 0.05 W/kg – 100 W/kg |
| Probe Length: | 330 mm |
| Probe Tip Length: | 16 mm |
| Body Diameter: | 12 mm |
| Tip Diameter: | 3 mm |
| Tip-Center: | 2 mm |
| Application: | SAR Dosimetry Testing Compliance tests of mobile phones |



Fig 4-2
Probe Thick Film Technique



Δ - BEAM
Fig 4-3
Triangular Probe Configuration

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 7 of 26 |

5 PROBE CALIBRATION PROCESS

5.1 Dosimetric Assessment Procedure

Each E-Probe/Probe amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm²) using an RF Signal generator, TEM cell, and RF Power Meter.

5.2 Free Space Assessment

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm².

5.3 Temperature Assessment

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

where:

- Δt = exposure time (30 seconds),
- C = heat capacity of tissue (brain or muscle),
- ΔT = temperature increase due to RF exposure.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

where:

- σ = simulated tissue conductivity,
- ρ = Tissue density (1.25 g/cm³ for brain tissue)

SAR is proportional to $\Delta T/\Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. Now it's possible to quantify the electric field in the simulated tissue by equating the thermally derived SAR to the E- field;




Fig 5-1 E-Field and Temperature measurements at 900MHz [7]




Fig 5-2 E-Field and temperature measurements at 1.9GHz [7]

| | | | | |
|-----------------------------|------------------------------------|---|--|---------------------------------|
| FCC ID: BEJCU400 | | CERTIFICATION REPORT | | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 8 of 26 |

6.1 SAM Phantoms



Figure 6-1
SAM Phantoms

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users [11][12]. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. (see Fig. 5.1)

6.2 Brain & Muscle Simulating Mixture Characterization




Figure 6-2
Head Simulated



The brain and muscle mixtures consist of a viscous gel using hydroxyethylcellulose (HEC) gelling agent and saline solution (see Table 6.1). Preservation with a bactericide is added and visual inspection is made to make sure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table. Other head and body tissue parameters that have not been specified in IEEE-1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations. The mixture characterizations used for the brain and muscle tissue simulating liquids are according to the data by C. Gabriel and G. Hartsgrrove [13]. (See Table 6-1)

Table 6-1

Composition of the Brain & Muscle Tissue Equivalent Matter

| Ingredients (% by weight) | Frequency (MHz) | | | | | | | | | |
|------------------------------|-----------------|-------|-------|------|-------|-------|-------|------|------|------|
| | 450 | | 835 | | 915 | | 1900 | | 2450 | |
| Tissue Type | Head | Body | Head | Body | Head | Body | Head | Body | Head | Body |
| Water | 38.56 | 51.16 | 41.45 | 52.4 | 41.05 | 56.0 | 54.9 | 40.4 | 62.7 | 73.2 |
| Salt (NaCl) | 3.95 | 1.49 | 1.45 | 1.4 | 1.35 | 0.76 | 0.18 | 0.5 | 0.5 | 0.04 |
| Sugar | 56.32 | 46.78 | 56.0 | 45.0 | 56.5 | 41.76 | 0.0 | 58.0 | 0.0 | 0.0 |
| HEC | 0.98 | 0.52 | 1.0 | 1.0 | 1.0 | 1.21 | 0.0 | 1.0 | 0.0 | 0.0 |
| Bactericide | 0.19 | 0.05 | 0.1 | 0.1 | 0.1 | 0.27 | 0.0 | 0.1 | 0.0 | 0.0 |
| Triton X-100 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 36.8 | 0.0 |
| DGBE | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 44.92 | 0.0 | 0.0 | 26.7 |

Salt: 99% Pure Sodium Chloride Sugar: 98% Pure Sucrose
 Water: De-ionized, 16 MΩ resistivity HEC: Hydroxyethyl Cellulose
 DGBE: 99% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]
 Triton X-100 (ultra pure): Polyethylene glycol mono [4-(1,1,3,3-tetramethylbutyl)phenyl] ether

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 9 of 26 |

7.1 Measurement Procedure

The evaluation was performed using the following procedure:

1. The SAR measurement was taken at a selected spatial reference point to monitor power variations during testing. This fixed point was measured and used as a reference value.
2. The SAR distribution at the exposed side of the head was measured at a distance of 3.9mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm x 15mm.
3. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation. Around this point, a volume of 32mm x 32mm x 30mm (fine resolution volume scan, zoom scan) was assessed by measuring 5 x 5 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see Fig. 7.1):
 - a. The data at the surface was extrapolated, since the center of the dipoles is 2.7mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. The extrapolation was based on a least square algorithm [15]. A polynomial of the fourth order was calculated through the points in z-axis. This polynomial was then used to evaluate the points between the surface and the probe tip.
 - b. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions) [15][16]. The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 1, was re-measured. If the value changed by more than 5%, the evaluation is repeated.




Fig 7-1
Sample SAR Area Scan

7.2 Specific Anthropomorphic Mannequin (SAM) Specifications

The phantom for handset SAR assessment testing is a low-loss dielectric shell, with shape and dimensions derived from the anthropometric data of the 90th percentile adult male head dimensions as tabulated by the US Army. The SAM Twin Phantom shell is bisected along the mid-sagittal plane into right and left halves (see Fig. 7.2). The perimeter sidewalls of each phantom halves are extended to allow filling with liquid to a depth that is sufficient to minimized reflections from the upper surface. The liquid depth is maintained at a minimum depth of 15cm to minimize reflections from the upper surface.






Fig 7-2
SAM Twin Phantom Shell

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 10 of 26 |

8.1 EAR REFERENCE POINT

Fig 8-1 shows the front, back and side views of the SAM Twin Phantom. The point "M" is the reference point for the center of the mouth, "LE" is the left ear reference point (ERP), and "RE" is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Fig 9-2. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front) is perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Fig 8-2). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Fig 8-1
Close-Up Side view
of ERP

8.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the "test device reference point" located along the "vertical centerline" on the front of the device aligned to the "ear reference point" (See Fig 8-3). The "test device reference point" was then located at the same level as the center of the ear reference point. The test device was positioned so that the "vertical centerline" was bisecting the front surface of the handset at it's top and bottom edges, positioning the "ear reference point" on the outer surface of the both the left and right head phantoms on the ear reference point.



Fig 8-2
Front, back and side view of SAM Twin Phantom






Fig 8-3
Handset Vertical Center & Horizontal Line Reference Points

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 11 of 26 |

9.1 Positioning for Cheek/Touch

1. The test device was positioned with the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Fig 9-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Fig 9-1 Front, Side and Top View of Cheek/Touch Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the ear.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the plane normal to MB-NF including the line MB (reference plane).
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the phone contact with the ear, the handset was rotated about the line NF until any point on the handset made contact with a phantom point below the ear (cheek). See Fig 9-2)






Fig 9-2 Side view w/ relevant markings

9.2 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek/Touch Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degree.
2. The phone was then rotated around the horizontal line by 15 degree.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the phone touches the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. The tilted

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 12 of 26 |

position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Fig 9-3).




Fig 9-3 Front, Side and Top View of Ear/15° Tilt Position




Fig 9-4 Side view w/ relevant markings



Fig 9-5 Body SAR Sample Photo (Not Actual EUT)



9.3 Body Holster /Belt Clip Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Fig 9-5). A device with a headset output is tested with a headset connected to the device.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in brain fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

In all cases SAR measurements are performed to investigate the worst-case positioning. Worst-case positioning is then documented and used to perform Body SAR testing.

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 13 of 26 |

10 ANSI/IEEE C95.1 - 1992 RF EXPOSURE LIMITS

10.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

10.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.



| HUMAN EXPOSURE LIMITS | | |
|--|--|--|
| | UNCONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g) | CONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g) |
| SPATIAL PEAK SAR ¹ Brain | 1.60 | 8.00 |
| SPATIAL AVERAGE SAR ² Whole Body | 0.08 | 0.40 |
| SPATIAL PEAK SAR ³ Hands, Feet, Ankles, Wrists | 4.00 | 20.00 |

Table 10.1. Human Exposure limit was specified in ANSI / IEEE C95.1-2005

1 The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

2 The Spatial Average value of the SAR averaged over the whole body.



3 The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | Page 14 of 26 | |

11 MEASUREMENT UNCERTAINTIES

| a | b | c | d | e= f(d,k) | f | g | h = cx/f/e | i = cxg/e | k |
|---|--------|---------------|----------------|--------------|------------------|-------------------|-------------------------|--------------------------|----------|
| Uncertainty Component | Sec. | Tol. (± %) | Prob. Dist. | Div. | c_i (1 - g) | c_i (10 - g) | 1 - g u_i (± %) | 10 - g u_i (± %) | v_i |
| Measurement System | | | | | | | | | |
| Probe Calibration | E1.1 | 4.8 | N | 1 | 1 | 1 | 4.8 | 4.8 | 8 |
| Axial Isotropy | E1.2 | 4.7 | R | $\sqrt{3}$ | 0.7 | 0.7 | 1.9 | 1.9 | 8 |
| Hemishperical Isotropy | E1.2 | 9.6 | R | $\sqrt{3}$ | 0.7 | 0.7 | 3.9 | 3.9 | 8 |
| Boundary Effect | E1.3 | 1.0 | R | $\sqrt{3}$ | 1 | 1 | 0.6 | 0.6 | 8 |
| Linearity | E1.4 | 4.7 | R | $\sqrt{3}$ | 1 | 1 | 2.7 | 2.7 | 8 |
| System Detection Limits | E1.5 | 1.0 | R | $\sqrt{3}$ | 1 | 1 | 0.6 | 0.6 | 8 |
| Readout Electronics | E1.6 | 1.0 | N | 1 | 1 | 1 | 1.0 | 1.0 | 8 |
| Response Time | E1.7 | 0.8 | R | $\sqrt{3}$ | 1 | 1 | 0.5 | 0.5 | 8 |
| Integration Time | E1.8 | 2.6 | R | $\sqrt{3}$ | 1 | 1 | 1.5 | 1.5 | 8 |
| RF Ambient Conditions | E5.1 | 3.0 | R | $\sqrt{3}$ | 1 | 1 | 1.7 | 1.7 | 8 |
| Probe Positioner Mechanical Tolerance | E5.2 | 0.4 | R | $\sqrt{3}$ | 1 | 1 | 0.2 | 0.2 | 8 |
| Probe Positioning w/ respect to Phantom | E5.3 | 2.9 | R | $\sqrt{3}$ | 1 | 1 | 1.7 | 1.7 | 8 |
| Extrapolation, Interpolation & Integration Algorithms for Max. SAR Evaluation | E4.2 | 1.0 | R | $\sqrt{3}$ | 1 | 1 | 0.6 | 0.6 | 8 |
| Test Sample Related | | | | | | | | | |
| Test Sample Positioning | E3.2.1 | 2.9 | N | 1 | 1 | 1 | 2.9 | 2.9 | 145 |
| Device Holder Uncertainty | E3.1.1 | 3.6 | N | 1 | 1 | 1 | 3.6 | 3.6 | 5 |
| Output Power Variation - SAR drift measurement | 5.6.2 | 5.0 | R | $\sqrt{3}$ | 1 | 1 | 2.9 | 2.9 | 8 |
| Phantom & Tissue Parameters | | | | | | | | | |
| Phantom Uncertainty (Shape & Thickness tolerances) | E2.1 | 4.0 | R | $\sqrt{3}$ | 1 | 1 | 2.3 | 2.3 | 8 |
| Liquid Conductivity - deviation from target values | E2.2 | 5.0 | R | $\sqrt{3}$ | 0.64 | 0.43 | 1.8 | 1.2 | 8 |
| Liquid Conductivity - measurement uncertainty | E2.2 | 2.5 | N | 1 | 0.64 | 0.43 | 1.6 | 1.1 | 8 |
| Liquid Permittivity - deviation from target values | E2.2 | 5.0 | R | $\sqrt{3}$ | 0.6 | 0.5 | 1.7 | 1.4 | 8 |
| Liquid Permittivity - measurement uncertainty | E2.2 | 2.5 | N | 1 | 0.6 | 0.5 | 1.5 | 1.2 | 8 |
| Combined Standard Uncertainty (k=1) | | | RSS | | | | 10.3 | 10.0 | |
| Expanded Uncertainty (k=2) (95% CONFIDENCE LEVEL) | | | | | | | 20.6 | 20.1 | |

Table 11.1 The above measurement uncertainties are according to IEEE Std. 1528 - 2003.

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 15 of 26 |

12 SYSTEM VERIFICATION

12.1 Tissue Verification

**Table 12-1
Measured Tissue Properties**


| | | | | | | | | |
|---------------------|----------|----------|----------|----------|----------|----------|----------|----------|
| Calibrated Date: | 10/12/06 | | 10/12/06 | | 10/13/06 | | 10/13/06 | |
| | 835H | | 835M | | 1900H | | 1900M | |
| | Target | Measured | Target | Measured | Target | Measured | Target | Measured |
| Dielectric Constant | 41.5 | 39.5 | 55.2 | 52.8 | 40.0 | 39.4 | 53.3 | 53.5 |
| Conductivity | 0.90 | 0.87 | 0.97 | 0.93 | 1.40 | 1.38 | 1.52 | 1.57 |

12.2 Test System Verification

Prior to assessment, the system is verified to $\pm 10\%$ of the specifications at 835 MHz and 1900 MHz by using the system validation kit(s). (Graphic Plots Attached)

**Table 12-2
System Verification Results
TARGET & MEASURED**

| Date: | Amb. Temp (°C) | Liquid Temp(°C) | Input Power (W) | Tissue Frequency (Mhz) | Targeted SAR _{1g} (mW) | Measured SAR _{1g} (mW) | Deviation (%) |
|----------|----------------|-----------------|-----------------|------------------------|---------------------------------|---------------------------------|---------------|
| 10/12/06 | 23.2 | 21.5 | 0.25 | 835 | 2.38 | 2.42 | 1.9% |
| 10/13/06 | 22.4 | 21.8 | 0.25 | 835 | 2.38 | 2.53 | 6.5% |
| 10/13/06 | 23.8 | 21.7 | 0.1 | 1900 | 3.97 | 3.74 | -5.8% |
| 10/16/06 | 23.8 | 21.7 | 0.1 | 1900 | 3.97 | 3.76 | -5.3% |



**Fig 12-3
System Verification Setup Diagram**



**Fig 12-4
System Verification Setup Photo**

| | | | | |
|-----------------------------|------------------------------------|---|--|---------------------------------|
| FCC ID: BEJCU400 | | CERTIFICATION REPORT | | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 16 of 26 |

13 FCC 3G MEASUREMENT PROCEDURES – JUNE 2006

Power measurements were performed using a base station simulator under digital average power[21].

13.1 Procedures Used to Establish RF Signal for SAR

The handset was placed into a simulated call using a base station simulator in a shielded chamber. Such test signals offer a consistent means for testing SAR and are recommended for evaluating SAR[4]. SAR measurements were taken with a fully charged battery. In order to verify that the device was tested and maintained at full power, this was configured with the base station simulator. The SAR measurement software calculates a reference point at the start and end of the test to check for power drifts. If conducted power deviations of more than 5% occurred, the tests were repeated.

13.2 SAR Measurement Conditions for UMTS

13.2.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all "1s". Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes) should be tabulated in the test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations should be clearly identified.

13.2.2 Head SAR Measurements

SAR for head exposure configurations is measured using the 12.2 kbps RMC with TPC bits configured to all "1s". SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than ¼ dB higher than that measured in 12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2 AMR with a 3.4 kbps SRB (signaling radio bearer) using the exposure configuration that results in the highest SAR for that RF channel in 12.2 RMC.

13.2.3 Body SAR Measurements



SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits configured to all "1s".

13.2.4 Handsets with HSDPA

Body SAR is not required for handsets with HSDPA capabilities, when the maximum average output of each RF channel with HSDPA active is less than ¼ dB higher than that measured in 12.2 kbps RMC without HSDPA. Otherwise, SAR for HSDPA is measured using FRC (fixed reference channel) in the body exposure configuration that results in the highest SAR for that RF channel in 12.2 RMC.

Table 13-1 Conducted Power for CU400

| | Channel | RMC [dBm] | AMR [dBm] | | Channel | Max [dBm] |
|------------------|---------|-----------|-----------|----------------|---------|-----------|
| WCDMA850 | 4132 | 22.82 | 22.88 | GSM850 | 128 | 32.5 |
| | 4175 | 22.91 | 23.04 | | 190 | 32.4 |
| | 4233 | 23.1 | 23.02 | | 251 | 32 |
| WCDMA1900 | 9262 | 22.28 | 22.27 | GSM1900 | 512 | 29.2 |
| | 9400 | 22.56 | 22.35 | | 661 | 28.9 |
| | 9538 | 22.28 | 22.53 | | 810 | 28.8 |

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 17 of 26 |

14 SAR DATA SUMMARY



14.1 GSM850 Head SAR Results

| MEASUREMENT RESULTS | | | | | | | | | | | |
|---|-----|------|--------------|-------|-------|--|--------------|----------|-----------|--------|--------|
| FREQUENCY | | Mode | C_Power[dBm] | | Side | Test Position | Antenna Type | Battery | Bluetooth | Memory | SAR |
| MHz | Ch. | | Start | End | | | | | | | (W/kg) |
| 836.60 | 190 | GSM | 32.50 | 32.55 | Right | Touch | Fixed | Standard | off | no | 0.755 |
| 836.60 | 190 | GSM | 32.50 | 32.51 | Right | Touch | Fixed | Extended | off | no | 0.752 |
| 836.60 | 190 | GSM | 32.50 | 32.52 | Right | Touch | Fixed | Standard | on | no | 0.740 |
| 836.60 | 190 | GSM | 32.50 | 32.60 | Right | Tilt | Fixed | Standard | off | no | 0.259 |
| 836.60 | 190 | GSM | 32.50 | 32.69 | Right | Tilt | Fixed | Extended | off | no | 0.260 |
| 836.60 | 190 | GSM | 32.50 | 32.60 | Left | Touch | Fixed | Standard | off | no | 0.773 |
| 836.60 | 190 | GSM | 32.50 | 32.64 | Left | Touch | Fixed | Extended | off | no | 0.764 |
| 836.60 | 190 | GSM | 32.50 | 32.59 | Left | Touch | Fixed | Standard | on | no | 0.750 |
| 836.60 | 190 | GSM | 32.50 | 32.51 | Left | Tilt | Fixed | Standard | off | no | 0.289 |
| 836.60 | 190 | GSM | 32.50 | 32.61 | Left | Tilt | Fixed | Extended | off | no | 0.292 |
| ANSI / IEEE C95.1 2005 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population | | | | | | Brain 1.6 W/kg (mW/g) averaged over 1 gram | | | | | |

Table 14.1

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard and Extended batteries were investigated..
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is 15.1 cm. ± 0.1.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
7. Justification for reduced test configurations: This model supports GPRS CLASS "10" (2Tx) and EDGE. The burst power and timing period is more than 2dB higher in GPRS mode than in GSM1900 mode. Hence, the GSM1900 mode was not measured. EDGE mode was also measured.

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 18 of 26 |



14.2 GSM PCS Head SAR Results

| MEASUREMENT RESULTS | | | | | | | | | | | |
|--|-----|------|--------------|-------|-------|----------------------|--------------|----------|-----------|--------|------------|
| FREQUENCY | | Mode | C_Power[dBm] | | Side | Test Position | Antenna Type | Battery | Bluetooth | Memory | SAR (W/kg) |
| MHz | Ch. | | Start | End | | | | | | | |
| 1880.00 | 661 | PCS | 28.90 | 29.08 | Right | Touch | Fixed | Standard | off | no | 0.355 |
| 1880.00 | 661 | PCS | 28.90 | 29.03 | Right | Touch | Fixed | Extended | off | no | 0.337 |
| 1880.00 | 661 | PCS | 28.90 | 29.02 | Right | Touch | Fixed | Standard | on | no | 0.337 |
| 1880.00 | 661 | PCS | 28.90 | 29.03 | Right | Tilt | Fixed | Standard | off | no | 0.045 |
| 1880.00 | 661 | PCS | 28.90 | 28.98 | Right | Tilt | Fixed | Extended | off | no | 0.038 |
| 1880.00 | 661 | PCS | 28.90 | 29.04 | Left | Touch | Fixed | Standard | off | no | 0.258 |
| 1880.00 | 661 | PCS | 28.90 | 29.05 | Left | Touch | Fixed | Extended | off | no | 0.239 |
| 1880.00 | 661 | PCS | 28.90 | 29.02 | Left | Touch | Fixed | Standard | on | no | 0.231 |
| 1880.00 | 661 | PCS | 28.90 | 28.95 | Left | Tilt | Fixed | Standard | off | no | 0.065 |
| 1880.00 | 661 | PCS | 28.90 | 29.02 | Left | Tilt | Fixed | Extended | off | no | 0.064 |
| ANSI / IEEE C95.1 2005 - SAFETY LIMIT | | | | | | Brain | | | | | |
| Spatial Peak | | | | | | 1.6 W/kg (mW/g) | | | | | |
| Uncontrolled Exposure/General Population | | | | | | averaged over 1 gram | | | | | |

Table 14.2

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard and Extended batteries were investigated..
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is 15.1 cm. \pm 0.1.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
7. Justification for reduced test configurations: This model supports GPRS CLASS "10" (2Tx) and EDGE. The burst power and timing period is more than 2dB higher in GPRS mode than in GSM1900 mode. Hence, the GSM1900 mode was not measured. EDGE mode was also measured.

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | Page 19 of 26 | |



14.3 WCDMA Band V (Cellular) Head SAR Results

| MEASUREMENT RESULTS | | | | | | | | | | | | |
|---|------|------|--------------|-------|-------|--|--------------|----------|-----------|--------|--------|--|
| FREQUENCY | | Mode | C_Power[dBm] | | Side | Test Position | Antenna Type | Battery | Bluetooth | Memory | SAR | |
| MHz | Ch. | | Start | End | | | | | | | (W/kg) | |
| 835.00 | 4175 | UMTS | 22.82 | 22.92 | Right | Touch | Fixed | Standard | off | no | 0.691 | |
| 835.00 | 4175 | UMTS | 22.82 | 22.96 | Right | Touch | Fixed | Extended | off | no | 0.689 | |
| 835.00 | 4175 | UMTS | 22.82 | 22.91 | Right | Touch | Fixed | Standard | on | no | 0.680 | |
| 835.00 | 4175 | UMTS | 22.82 | 22.86 | Right | Tilt | Fixed | Standard | off | no | 0.259 | |
| 835.00 | 4175 | UMTS | 22.82 | 22.91 | Right | Tilt | Fixed | Extended | off | no | 0.258 | |
| 835.00 | 4175 | UMTS | 22.82 | 22.94 | Left | Touch | Fixed | Standard | off | no | 0.706 | |
| 835.00 | 4175 | UMTS | 22.82 | 22.96 | Left | Touch | Fixed | Extended | off | no | 0.703 | |
| 835.00 | 4175 | UMTS | 22.82 | 22.90 | Left | Touch | Fixed | Standard | on | no | 0.700 | |
| 835.00 | 4175 | UMTS | 22.82 | 22.98 | Left | Tilt | Fixed | Standard | off | no | 0.273 | |
| 835.00 | 4175 | UMTS | 22.82 | 22.84 | Left | Tilt | Fixed | Extended | off | no | 0.271 | |
| ANSI / IEEE C95.1 2005 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population | | | | | | Brain 1.6 W/kg (mW/g) averaged over 1 gram | | | | | | |

Table 14.3

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard and Extended batteries were investigated..
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is 15.1 cm. ± 0.1.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | Page 20 of 26 | |



14.4 WCDMA Band II (PCS) Head SAR Results

| MEASUREMENT RESULTS | | | | | | | | | | | |
|---|------|------|--------------|-------|-------|--|--------------|----------|-----------|--------|--------|
| FREQUENCY | | Mode | C_Power[dBm] | | Side | Test Position | Antenna Type | Battery | Bluetooth | Memory | SAR |
| MHz | Ch. | | Start | End | | | | | | | (W/kg) |
| 1880.00 | 9400 | PCS | 22.56 | 22.73 | Right | Touch | Fixed | Standard | off | no | 0.474 |
| 1880.00 | 9400 | PCS | 22.56 | 22.66 | Right | Touch | Fixed | Extended | off | no | 0.458 |
| 1880.00 | 9400 | PCS | 22.56 | 22.68 | Right | Touch | Fixed | Standard | on | no | 0.461 |
| 1880.00 | 9400 | PCS | 22.56 | 22.66 | Right | Tilt | Fixed | Standard | off | no | 0.066 |
| 1880.00 | 9400 | PCS | 22.56 | 22.56 | Right | Tilt | Fixed | Extended | off | no | 0.063 |
| 1880.00 | 9400 | PCS | 22.56 | 22.68 | Left | Touch | Fixed | Standard | off | no | 0.374 |
| 1880.00 | 9400 | PCS | 22.56 | 22.57 | Left | Touch | Fixed | Extended | off | no | 0.367 |
| 1880.00 | 9400 | PCS | 22.56 | 22.57 | Left | Touch | Fixed | Standard | on | no | 0.371 |
| 1880.00 | 9400 | PCS | 22.56 | 22.68 | Left | Tilt | Fixed | Standard | off | no | 0.117 |
| 1880.00 | 9400 | PCS | 22.56 | 22.70 | Left | Tilt | Fixed | Extended | off | no | 0.110 |
| ANSI / IEEE C95.1 2005 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population | | | | | | Brain 1.6 W/kg (mW/g) averaged over 1 gram | | | | | |

Table 14.4

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard and Extended batteries were investigated..
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is 15.1 cm. ± 0.1.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | Page 21 of 26 | |



14.5 Body SAR Results

| MEASUREMENT RESULTS | | | | | | | | | | | | |
|---|------|------|--------------|-------|----------|---|--------------|----------|-----------|--------|------|---------------|
| FREQUENCY | | Mode | C_Power[dBm] | | Position | Spacing | Antenna Type | Battery | Bluetooth | Memory | Side | SAR (W/kg) |
| MHz | Ch. | | Start | End | | | | | | | | |
| 824.20 | 128 | GSM | 32.50 | 32.60 | Body | 1.5 cm | Fixed | Standard | off | no | back | 1.040 |
| 836.60 | 190 | GSM | 32.50 | 32.67 | Body | 1.5 cm | Fixed | Standard | off | no | back | 1.140 |
| 848.80 | 251 | GSM | 32.50 | 32.62 | Body | 1.5 cm | Fixed | Standard | off | no | back | 0.867 |
| 836.60 | 190 | GSM | 32.50 | 32.68 | Body | 1.5 cm | Fixed | Extended | off | no | back | 0.978 |
| 836.60 | 190 | GSM | 32.50 | 32.57 | Body | 1.5 cm | Fixed | Standard | on | no | back | 1.110 |
| 1880.00 | 661 | PCS | 28.90 | 29.02 | Body | 1.5 cm | Fixed | Standard | off | no | back | 0.340 |
| 1880.00 | 661 | PCS | 28.90 | 28.96 | Body | 1.5 cm | Fixed | Extended | off | no | back | 0.321 |
| 1880.00 | 661 | PCS | 28.90 | 29.04 | Body | 1.5 cm | Fixed | Standard | on | no | back | 0.322 |
| ANSI / IEEE C95.1 2005 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population | | | | | | Muscle 1.6 W/kg (mW/g) averaged over 1 gram | | | | | | |
| MEASUREMENT RESULTS | | | | | | | | | | | | |
| FREQUENCY | | Mode | C_Power[dBm] | | Position | Spacing | Antenna Type | Battery | Bluetooth | Memory | Side | SAR (W/kg) |
| MHz | Ch. | | Start | End | | | | | | | | |
| 835.00 | 4175 | UMTS | 22.82 | 22.94 | Body | 1.5 cm | Fixed | Standard | off | no | back | 0.498 |
| 835.00 | 4175 | UMTS | 22.82 | 22.87 | Body | 1.5 cm | Fixed | Extended | off | no | back | 0.493 |
| 835.00 | 4175 | UMTS | 22.82 | 22.88 | Body | 1.5 cm | Fixed | Standard | on | no | back | 0.491 |
| 1880.00 | 9400 | PCS | 22.56 | 22.56 | Body | 1.5 cm | Fixed | Standard | off | no | back | 0.250 |
| 1880.00 | 9400 | PCS | 22.56 | 22.68 | Body | 1.5 cm | Fixed | Extended | off | no | back | 0.242 |
| 1880.00 | 9400 | PCS | 22.56 | 22.67 | Body | 1.5 cm | Fixed | Standard | on | no | back | 0.250 |
| ANSI / IEEE C95.1 2005 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population | | | | | | Muscle 1.6 W/kg (mW/g) averaged over 1 gram | | | | | | |

Table 14.5

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard and Extended batteries were investigated.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Both sides of the phone were tested, and the worst-case is reported.
6. Liquid tissue depth is 15.1 cm. ± 0.1.
7. Device was tested using a fixed spacing.
8. Justification for reduced test configurations: This model supports GPRS CLASS "10" (2Tx) and EDGE. The burst power and timing period is more than 2dB higher in GPRS mode than in GSM1900 mode. Hence, the GSM1900 mode was not measured. EDGE mode was also measured.

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | Page 22 of 26 | |



15 EQUIPMENT LIST

| EQUIPMENT SPECIFICATIONS | | |
|---|--------------|---------------------|
| Type | Cal Due | Serial Number |
| Staubli Robot RX60L | Oct 2007 | 599131-01 |
| Staubli Robot Controller | Oct 2007 | PCT592 |
| Staubli Teach Pendant (Joystick) | Oct 2007 | 3323-00161 |
| Gateway Computer, 2.52GHz/768MB,Windows-XP | N/A | PCT678 |
| SPEAG EDC3 | Oct 2007 | 321 |
| SPEAG DAE4 | June 1 2007 | 704 |
| SPEAG E-Field Probe EX3DV4 | July 14 2007 | 3589 |
| SPEAG Validation Dipole D835V2 | Feb 2007 | PCT512 |
| SPEAG Validation Dipole D1900V2 | Feb 2007 | PCT613 |
| Rohde & Schwarz CMU200 Base Station Simulator | Apr 2007 | 836371 |
| Agilent 8960 Test Communications Set | Jan 2007 | GB43193972 |
| SPEAG Freespace 1900MHz Dipole | Feb 2007 | 1002 |
| SPEAG Freespace 2450 MHz Dipole | Feb 2007 | 1004 |
| ETS Freespace 835 MHz Dipole | Feb 2007 | A005 |
| SPEAG Freespace 835 MHz Dipole | Feb 2007 | 1003 |
| MW Amp. Model: 5S1G4, (800MHz - 4.2GHz) | Jan 2007 | 22332 |
| Gigatronics 8651A Power Meter | Jan 2007 | 1835299 |
| Gigatronics 80701A Sensor(50MHz-18GHz) | Jan 2007 | PCT606 |
| HP-8648D (9kHz ~ 4GHz) Signal Generator | Jan 2007 | PCT530 |
| HP-8241A (-18GHz) Signal Generator | Jan 2007 | |
| Amplifier Research 5S1G4 AMP | Jan 2007 | PCT540 |
| HP-8753E (30kHz ~ 6GHz) Network Analyzer | May 2007 | PCT552 |
| HP85070B Dielectric Probe Kit | Jun 2007 | PCT501 |
| Ambient Noise/Reflection, etc. (<12mW/kg/<3%of SAR) | N/A | Anechoic Room PCT01 |

Table 15.1 Test Equipment List

Notes:

The E-field probe was calibrated by SPEAG, by the waveguide technique procedure. Dipole Validation measurement is performed by PCTEST prior to SAR evaluation. The brain and muscle simulating material are calibrated by PCTEST using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the brain or muscle- equivalent material.



| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 23 of 26 |

16 CONCLUSION

16.1 Measurement Conclusion



The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

| | | | | |
|------------------------------------|---|--|---|--|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 24 of 26 |

17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1 - 1991, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz, New York: IEEE, Aug. 1992.
- [3] ANSI/IEEE C95.3 - 1991, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, 1992.
- [4] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, July 2001.
- [5] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528 – 2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 120-124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.

| | | | | |
|-----------------------------|---|---|---|---------------------------------|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 25 of 26 |



[17] Federal Communications Commission, OET Bulletin 65, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields. Supplement C, Dec. 1997.

[18] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

[19] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.

[20] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zurich, Dosimetric Evaluation of the Cellular Phone.

[21] FCC 3G Measurement Policy, June 2006

| | | | | |
|------------------------------------|---|--|---|--|
| FCC ID: BEJCU400 |  | CERTIFICATION REPORT |  | Reviewed by: Quality Manager |
| SAR Filename: 0610110884 | Test Dates: 10/12/06 - 10/16/06 | EUT Type: Dual-Band GSM/WCDMA Phone with Bluetooth | | Page 26 of 26 |

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: GSM850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Brain ($\sigma = 0.87$ mho/m, $\epsilon_r = 39.47$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

Test Date: 10-12-2006; Ambient Temp: 23.2°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3589; ConvF(8.36, 8.36, 8.36); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: GSM850, Left Head, Touch, Mid.ch


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.97 V/m

Peak SAR (extrapolated) = 1.08 W/kg

SAR(1 g) = 0.773 mW/g; SAR(10 g) = 0.547 mW/g



0 dB = 0.878mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: GSM850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Brain ($\sigma = 0.87$ mho/m, $\epsilon_r = 39.47$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

Test Date: 10-12-2006; Ambient Temp: 23.2°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3589; ConvF(8.36, 8.36, 8.36); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: GSM850, Left Head, Tilt, Mid.ch, Extended Battery


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.5 V/m

Peak SAR (extrapolated) = 0.372 W/kg

SAR(1 g) = 0.292 mW/g; SAR(10 g) = 0.220 mW/g



0 dB = 0.321mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: GSM850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Brain ($\sigma = 0.87$ mho/m, $\epsilon_r = 39.47$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

Test Date: 10-12-2006; Ambient Temp: 23.2°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3589; ConvF(8.36, 8.36, 8.36); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: GSM850, Right Head, Touch, Mid.ch


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.88 V/m

Peak SAR (extrapolated) = 1.09 W/kg

SAR(1 g) = 0.755 mW/g; SAR(10 g) = 0.518 mW/g



0 dB = 0.866mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: GSM850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Brain ($\sigma = 0.87$ mho/m, $\epsilon_r = 39.47$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

Test Date: 10-12-2006; Ambient Temp: 23.2°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3589; ConvF(8.36, 8.36, 8.36); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: GSM850, Right Head, Tilt, Mid.ch Extended Battery


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.7 V/m

Peak SAR (extrapolated) = 0.338 W/kg

SAR(1 g) = 0.260 mW/g; SAR(10 g) = 0.194 mW/g



0 dB = 0.287mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: GSM850 GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Muscle ($\sigma = 0.93$ mho/m, $\epsilon_r = 52.8$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-13-2006; Ambient Temp: 22.4°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3589; ConvF(8.15, 8.15, 8.15); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: GSM850, Body SAR, Mid.ch.


Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.6 V/m

Peak SAR (extrapolated) = 1.59 W/kg

SAR(1 g) = 1.14 mW/g; SAR(10 g) = 0.804 mW/g



0 dB = 1.30mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: GSM1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Brain ($\sigma = 1.38$ mho/m, $\epsilon_r = 39.39$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

Test Date: 03-16-2006; Ambient Temp: 23.8°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN3589; ConvF(7.11, 7.11, 7.11); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: GSM1900, Left Head, Touch, Mid.ch


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.62 V/m

Peak SAR (extrapolated) = 0.419 W/kg

SAR(1 g) = 0.258 mW/g; SAR(10 g) = 0.153 mW/g



0 dB = 0.304mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: GSM1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Brain ($\sigma = 1.38$ mho/m, $\epsilon_r = 39.39$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

Test Date: 03-16-2006; Ambient Temp: 23.8°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN3589; ConvF(7.11, 7.11, 7.11); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: GSM1900, Left Head, Tilt, Mid.ch


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.13 V/m

Peak SAR (extrapolated) = 0.108 W/kg

SAR(1 g) = 0.065 mW/g; SAR(10 g) = 0.036 mW/g



0 dB = 0.078mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: GSM1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Brain ($\sigma = 1.38$ mho/m, $\epsilon_r = 39.39$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

Test Date: 03-16-2006; Ambient Temp: 23.8°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN3589; ConvF(7.11, 7.11, 7.11); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: GSM1900, Right Head, Touch, Mid.ch


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.63 V/m

Peak SAR (extrapolated) = 0.612 W/kg

SAR(1 g) = 0.355 mW/g; SAR(10 g) = 0.199 mW/g



0 dB = 0.430mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: GSM1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Brain ($\sigma = 1.38$ mho/m, $\epsilon_r = 39.39$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

Test Date: 03-16-2006; Ambient Temp: 23.8°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN3589; ConvF(7.11, 7.11, 7.11); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: GSM1900, Right Head, Tilt, Mid.ch


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.57 V/m

Peak SAR (extrapolated) = 0.073 W/kg

SAR(1 g) = 0.045 mW/g; SAR(10 g) = 0.027 mW/g



0 dB = 0.051mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: GSM1900 GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Muscle ($\sigma = 1.57$ mho/m, $\epsilon_r = 53.49$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-13-2006; Ambient Temp: 22.4°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3589; ConvF(6.64, 6.64, 6.64); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: GSM1900, Body SAR, Mid.ch


Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.6 V/m

Peak SAR (extrapolated) = 0.648 W/kg

SAR(1 g) = 0.340 mW/g; SAR(10 g) = 0.184 mW/g



0 dB = 0.426mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: WCDMA850; Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium: 835 Brain ($\sigma = 0.87$ mho/m, $\epsilon_r = 39.47$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

Test Date: 10-12-2006; Ambient Temp: 23.2°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3589; ConvF(8.36, 8.36, 8.36); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: WCDMA850, Left Head, Touch, Mid.ch


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.29 V/m

Peak SAR (extrapolated) = 0.983 W/kg

SAR(1 g) = 0.706 mW/g; SAR(10 g) = 0.503 mW/g



0 dB = 0.796mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: WCDMA850; Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium: 835 Brain ($\sigma = 0.87$ mho/m, $\epsilon_r = 39.47$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

Test Date: 10-12-2006; Ambient Temp: 23.2°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3589; ConvF(8.36, 8.36, 8.36); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: WCDMA850, Left Head, Tilt, Mid.ch


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.8 V/m

Peak SAR (extrapolated) = 0.349 W/kg

SAR(1 g) = 0.273 mW/g; SAR(10 g) = 0.206 mW/g



0 dB = 0.299mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: WCDMA850; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Brain ($\sigma = 0.87$ mho/m, $\epsilon_r = 39.47$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

Test Date: 10-12-2006; Ambient Temp: 23.2°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3589; ConvF(8.36, 8.36, 8.36); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: WCDMA850, Right Head, Touch, Mid.ch,


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.6 V/m

Peak SAR (extrapolated) = 1.01 W/kg

SAR(1 g) = 0.691 mW/g; SAR(10 g) = 0.473 mW/g



0 dB = 0.793mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: WCDMA850; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Brain ($\sigma = 0.87$ mho/m, $\epsilon_r = 39.47$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

Test Date: 10-12-2006; Ambient Temp: 23.2°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3589; ConvF(8.36, 8.36, 8.36); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: WCDMA850, Right Head, Tilt, Mid.ch


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.1 V/m

Peak SAR (extrapolated) = 0.332 W/kg

SAR(1 g) = 0.259 mW/g; SAR(10 g) = 0.192 mW/g



0 dB = 0.286mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: WCDMA850; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Muscle ($\sigma = 0.93$ mho/m, $\epsilon_r = 52.8$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-12-2006; Ambient Temp: 23.2°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3589; ConvF(8.15, 8.15, 8.15); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: WCDMA850, Body SAR, Mid.ch,


Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.6 V/m

Peak SAR (extrapolated) = 0.703 W/kg

SAR(1 g) = 0.498 mW/g; SAR(10 g) = 0.342 mW/g



0 dB = 0.571mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Brain ($\sigma = 1.38$ mho/m, $\epsilon_r = 39.39$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

Test Date: 03-16-2006; Ambient Temp: 23.8°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN3589; ConvF(7.11, 7.11, 7.11); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: WCDMA1900, Left Head, Touch, Mid.ch


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.15 V/m

Peak SAR (extrapolated) = 0.621 W/kg

SAR(1 g) = 0.374 mW/g; SAR(10 g) = 0.224 mW/g



0 dB = 0.442mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Brain ($\sigma = 1.38$ mho/m, $\epsilon_r = 39.39$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

Test Date: 03-16-2006; Ambient Temp: 23.8°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN3589; ConvF(7.11, 7.11, 7.11); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: WCDMA1900, Left Head, Tilt, Mid.ch


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.44 V/m

Peak SAR (extrapolated) = 0.191 W/kg

SAR(1 g) = 0.117 mW/g; SAR(10 g) = 0.067 mW/g



0 dB = 0.140mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Brain ($\sigma = 1.38$ mho/m, $\epsilon_r = 39.39$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

Test Date: 03-16-2006; Ambient Temp: 23.8°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN3589; ConvF(7.11, 7.11, 7.11); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: WCDMA1900, Right Head, Touch, Mid.ch


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.56 V/m

Peak SAR (extrapolated) = 0.833 W/kg

SAR(1 g) = 0.474 mW/g; SAR(10 g) = 0.267 mW/g



0 dB = 0.573mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Brain ($\sigma = 1.38$ mho/m, $\epsilon_r = 39.39$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

Test Date: 03-16-2006; Ambient Temp: 23.8°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN3589; ConvF(7.11, 7.11, 7.11); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: WCDMA1900, Right Head, Tilt, Mid.ch


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.75 V/m

Peak SAR (extrapolated) = 0.107 W/kg

SAR(1 g) = 0.065 mW/g; SAR(10 g) = 0.039 mW/g



0 dB = 0.077mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: CU400; Type: Dual Band GSM/WCDMA with Bluetooth Phone ; Serial No: SAR#1

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Muscle ($\sigma = 1.57$ mho/m, $\epsilon_r = 53.49$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-13-2006; Ambient Temp: 22.4°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3589; ConvF(6.64, 6.64, 6.64); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Mode: WCDMA1900, Body SAR, Mid.ch


Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.3 V/m

Peak SAR (extrapolated) = 0.474 W/kg

SAR(1 g) = 0.250 mW/g; SAR(10 g) = 0.136 mW/g



0 dB = 0.307mW/g

APPENDIX B: DIPOLE VALIDATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 406

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Brain ($\sigma = 0.87$ mho/m, $\epsilon_r = 39.47$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-12-2006; Ambient Temp: 23.2°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3589; ConvF(8.36, 8.36, 8.36); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

835MHz Dipole Validation


Area Scan (7x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Input Power = 24.0 dBm (250 mW)

SAR(1 g) = 2.42 mW/g; SAR(10 g) = 1.57 mW/g

Target SAR(1g) = 2.375 mW/g; Deviation = 1.89 %



0 dB = 2.83mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 406

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Brain ($\sigma = 0.87$ mho/m, $\epsilon_r = 39.47$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 10-13-2006; Ambient Temp: 22.4°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3589; ConvF(8.36, 8.36, 8.36); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

835MHz Dipole Validation


Area Scan (7x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Input Power = 24.0 dBm (250 mW)

SAR(1 g) = 2.53 mW/g; SAR(10 g) = 1.61 mW/g

Target SAR(1g) = 2.375 mW/g; Deviation = 6.53 %



0 dB = 2.87mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 502

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Brain ($\sigma = 1.38$ mho/m, $\epsilon_r = 39.39$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 10-13-2006; Ambient Temp: 22.4°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3589; ConvF(7.11, 7.11, 7.11); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

1900MHz Dipole Validation


Area Scan (5x6x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Input Power = 20.0 dBm (100 mW)

SAR(1 g) = 3.74 mW/g; SAR(10 g) = 1.87 mW/g

Target SAR(1g) = 3.97 mW/g; Deviation = -5.79 %



0 dB = 4.86mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 502

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Brain ($\sigma = 1.38$ mho/m, $\epsilon_r = 39.39$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-16-2006; Ambient Temp: 23.8°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN3589; ConvF(7.11, 7.11, 7.11); Calibrated: 7/14/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 6/1/2006

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

1900MHz Dipole Validation


Area Scan (5x6x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Input Power = 20.0 dBm (100 mW)

SAR(1 g) = 3.76 mW/g; SAR(10 g) = 1.89 mW/g

Target SAR(1g) = 3.97 mW/g; Deviation = -5.29 %



0 dB = 4.86mW/g

APPENDIX C: PROBE CALIBRATION



Accredited by the Swiss Federal Office of Metrology and Accreditation
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **EX3-3589_Jul06**

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3589**

Calibration procedure(s) **QA CAL-01.v5 and QA CAL-14.v3
Calibration procedure for dosimetric E-field probes**

Calibration date: **July 14, 2006**

Condition of the calibrated item **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID # | Cal Date (Calibrated by, Certificate No.) | Scheduled Calibration |
|----------------------------|-----------------|---|-----------------------|
| Power meter E4419B | GB41293874 | 5-Apr-06 (METAS, No. 251-00557) | Apr-07 |
| Power sensor E4412A | MY41495277 | 5-Apr-06 (METAS, No. 251-00557) | Apr-07 |
| Power sensor E4412A | MY41498087 | 5-Apr-06 (METAS, No. 251-00557) | Apr-07 |
| Reference 3 dB Attenuator | SN: S5054 (3c) | 11-Aug-05 (METAS, No. 251-00499) | Aug-06 |
| Reference 20 dB Attenuator | SN: S5086 (20b) | 4-Apr-06 (METAS, No. 251-00558) | Apr-07 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 11-Aug-05 (METAS, No. 251-00500) | Aug-06 |
| Reference Probe ES3DV2 | SN: 3013 | 2-Jan-06 (SPEAG, No. ES3-3013_Jan06) | Jan-07 |
| DAE4 | SN: 654 | 21-Jun-06 (SPEAG, No. DAE4-654_Jun06) | Jun-07 |

| Secondary Standards | ID # | Check Date (in house) | Scheduled Check |
|---------------------------|--------------|--|------------------------|
| RF generator HP 8648C | US3642U01700 | 4-Aug-99 (SPEAG, in house check Nov-05) | In house check: Nov-07 |
| Network Analyzer HP 8753E | US37390585 | 18-Oct-01 (SPEAG, in house check Nov-05) | In house check: Nov 06 |

| | Name | Function | Signature |
|----------------|---------------|-------------------|-----------|
| Calibrated by: | Katja Pokovic | Technical Manager | |
| Approved by: | Niels Kuster | Quality Manager | |

Issued: July 17, 2006

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Federal Office of Metrology and Accreditation
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

| | |
|--------------------------|--|
| TSL | tissue simulating liquid |
| NORM _{x,y,z} | sensitivity in free space |
| ConF | sensitivity in TSL / NORM _{x,y,z} |
| DCP | diode compression point |
| Polarization φ | φ rotation around probe axis |
| Polarization ϑ | ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis |

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- CENELEC EN 50361, "Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones (300 MHz - 3 GHz), July 2001

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not effect the E^2 -field uncertainty inside TSL (see below *ConvF*).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * *frequency_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * *ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe EX3DV4

SN:3589

| | |
|---------------|----------------|
| Manufactured: | March 30, 2006 |
| Calibrated: | July 14, 2006 |

Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)

DASY - Parameters of Probe: EX3DV4 SN:3589

Sensitivity in Free Space^A

| | | | | |
|-------|----------------------|-------------------------------------|-------|--------------|
| NormX | 0.460 ± 10.1% | $\mu\text{V}/(\text{V}/\text{m})^2$ | DCP X | 90 mV |
| NormY | 0.400 ± 10.1% | $\mu\text{V}/(\text{V}/\text{m})^2$ | DCP Y | 90 mV |
| NormZ | 0.370 ± 10.1% | $\mu\text{V}/(\text{V}/\text{m})^2$ | DCP Z | 90 mV |

Diode Compression^B

Sensitivity in Tissue Simulating Liquid (Conversion Factors)

Please see Page 8.

Boundary Effect

TSL **835 MHz** **Typical SAR gradient: 5 % per mm**

| | | | |
|---|------------------------------|---------------|---------------|
| Sensor Center to Phantom Surface Distance | | 3.7 mm | 4.7 mm |
| SAR _{be} [%] | Without Correction Algorithm | 4.5 | 1.6 |
| SAR _{be} [%] | With Correction Algorithm | 0.3 | 0.5 |

TSL **1900 MHz** **Typical SAR gradient: 10 % per mm**

| | | | |
|---|------------------------------|---------------|---------------|
| Sensor Center to Phantom Surface Distance | | 3.7 mm | 4.7 mm |
| SAR _{be} [%] | Without Correction Algorithm | 2.5 | 1.0 |
| SAR _{be} [%] | With Correction Algorithm | 0.2 | 0.4 |

Sensor Offset

Probe Tip to Sensor Center **1.0 mm**


The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E²-field uncertainty inside TSL (see Page 8).

^B Numerical linearization parameter: uncertainty not required.




Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)




Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ (k=2)

Receiving Pattern (ϕ), $\vartheta = 0^\circ$





Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range f(SAR_{head}) (Waveguide R22, f = 1800 MHz)



Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Conversion Factor Assessment




| f [MHz] | Validity [MHz] ^c | TSL | Permittivity | Conductivity | Alpha | Depth | ConvF | Uncertainty |
|---------|-----------------------------|------|--------------|--------------|-------|-------|-------|---------------|
| 835 | ± 50 / ± 100 | Head | 41.5 ± 5% | 0.90 ± 5% | 0.84 | 0.69 | 8.36 | ± 11.0% (k=2) |
| 1900 | ± 50 / ± 100 | Head | 40.0 ± 5% | 1.40 ± 5% | 0.45 | 0.74 | 7.11 | ± 11.0% (k=2) |
| 2450 | ± 50 / ± 100 | Head | 39.2 ± 5% | 1.80 ± 5% | 0.60 | 0.75 | 6.27 | ± 11.8% (k=2) |
| 5200 | ± 50 / ± 100 | Head | 36.0 ± 5% | 4.66 ± 5% | 0.45 | 1.80 | 4.45 | ± 13.1% (k=2) |
| 5800 | ± 50 / ± 100 | Head | 35.3 ± 5% | 5.27 ± 5% | 0.45 | 1.80 | 4.05 | ± 13.1% (k=2) |
| | | | | | | | | |
| 835 | ± 50 / ± 100 | Body | 55.2 ± 5% | 0.97 ± 5% | 0.92 | 0.62 | 8.15 | ± 11.0% (k=2) |
| 1900 | ± 50 / ± 100 | Body | 53.3 ± 5% | 1.52 ± 5% | 0.20 | 1.13 | 6.64 | ± 11.0% (k=2) |
| 2450 | ± 50 / ± 100 | Body | 52.7 ± 5% | 1.95 ± 5% | 0.65 | 0.75 | 6.37 | ± 11.8% (k=2) |
| 5200 | ± 50 / ± 100 | Body | 49.0 ± 5% | 5.30 ± 5% | 0.47 | 1.70 | 4.08 | ± 13.1% (k=2) |
| 5800 | ± 50 / ± 100 | Body | 48.2 ± 5% | 6.00 ± 5% | 0.45 | 1.70 | 3.86 | ± 13.1% (k=2) |

^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

Deviation from Isotropy in HSL

Error (ϕ , ϑ), $f = 900$ MHz



Uncertainty of Spherical Isotropy Assessment: $\pm 2.6\%$ ($k=2$)