



FCC TEST REPORT

According to

47 CFR, Part 2, Part 15 and CISPR PUB. 22

Applicant	: LG Electronics USA
Address	: 1000 Sylvan Avenue Englewood Cliffs New Jersey United States
Manufacturer	: LG Electronics Nanjing Display Co., Ltd.
Address	: No.346,Yaoxin Road Economic & Technical Development Zone Nanjing China
Equipment	: LCD Monitor
Model No.	: E2240TV
FCC ID	: BEJE2240TV
Trade Name	: LG

This is a series report, the original report No.SEFD1002023

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of **CerpPASS Technology Corp.** the test report shall not be reproduced except in full.
- The test report must not be used by the clients to claim product certification approval by **NVLAP** or any agency of the Government.



Table of Contents

1. Summary of Test Procedure and Test Result	5
2. Test Configuration of Equipment under Test.....	6
2.1. Feature of Equipment under Test	6
2.2. Test Manner.....	6
2.3. Description of Test System	7
2.4. Connection Diagram of Test System	7
2.5. General Information of Test	8
2.6. Measurement Uncertainty	8
3. Test of Conducted Emission	9
3.1. Test Limit	9
3.2. Test Procedures.....	9
3.3. Typical test Setup	10
3.4. Measurement equipment.....	10
3.5. Test Result and Data	11
4. Test of Radiated Emission	12
4.1. Test Limit	12
4.2. Test Procedures.....	13
4.3. Typical test Setup	13
4.4. Measurement equipment.....	14
4.5. Test Result and Data	15

[illegible]



FCC TEST REPORT

According to

47 CFR, Part 2, Part 15 and CISPR PUB. 22

Applicant	: LG Electronics USA
Address	: 1000 Sylvan Avenue Englewood Cliffs New Jersey United States
Manufacturer	: LG Electronics Nanjing Display Co., Ltd.
Address	: No.346,Yaoxin Road Economic & Technical Development Zone Nanjing China
Equipment	: LCD Monitor
Model No.	: E2240TV
FCC ID	: BEJE2240TV
Trade Name	: LG

I HEREBY CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4 – 2003** and the energy emitted by this equipment was **passed CISPR PUB. 22 and FCC Part 15** in both radiated and conducted emission class B limits. Testing was carried out on Mar 06, 2010 at **CerpPASS Technology Corp.**

Documented By:

Approved By:

Sophie Li/ Administration

John Wang/ Technical director



1. Summary of Test Procedure and Test Result

Test Item	Normative References	Test Result
Conducted Emission	ANSI C63.4-2003 FCC Part 15 Subpart B	PASS
Radiated Emission	ANSI C63.4-2003 FCC Part 15 Subpart B	PASS



2. Test Configuration of Equipment under Test

2.1. Feature of Equipment under Test

LCD Monitor	Model No:	E2240TV
ADAPTER	Manufacturer:	LG
	Model No:	FSP036-DGAA1
	Input:	100-240V~, 1.3A(1,3A), 50-60Hz
	Output:	12.0V(12,0V) 3.0A(3,0A) MAX
DC Cable	Non-Shielded, 1.5m, with one ferrite core bonded	
VGA Cable	Shielded, 1.8m, with two ferrite cores bonded	
VGA Cable	Shielded, 1.8m	
DVI Cable	Shielded, 1.8m, with two ferrite cores bonded	
DVI Cable	Shielded, 1.8m	
Power Supply cable	Non-Shielded, 1.8m	
Note: The VGA Cable and DVI Cable are alternative on selling.		

2.2. Test Manner


Test Software	
a	During testing, the interface cables and equipment positions were varied according to ANSI C63.4.
b	The complete test system included the Printer, PC, USB Mouse, USB Keyboard and EUT for EMI test.
c	During the test, setup up the EUT and all system, turn on the power of all Equipments, run the EMC test software "H", set the contrast control to maximum, set the brightness control to maximum, use white letters on a black background to represent all colors, make the EUT at the test mode and it is normal operation, and then test.
The pre-test modes	
	Test Mode 1: Full system (VGA mode 1920*1080@60Hz)
	Test Mode 2: Full system (VGA mode 1280*800@75Hz)
	Test Mode 3: Full system (VGA mode 800*600@70Hz)
	Test Mode 4: Full system (DVI mode 1920*1080@60Hz)
	Test Mode 5: Full system (DVI mode 1280*800@75H)
	Test Mode 6: Full system (DVI mode 800*600@70Hz)
Select the worst case of the pre-test modes as the final test mode	
	Test Mode 1: Full system (VGA mode 1920*1080@60Hz)



2.3. Description of Test System

No	Device	Manufacturer	Model No.	Description
1	Printer	Epson	EX3	N/A
2	PC	Dell	DCTA	N/A
3	USB Mouse	DELL	G0K02XYK	N/A
4	USB Keyboard	DELL	SK-8115	N/A

2.4. Connection Diagram of Test System



No	Cable	Quantity	Description
A	VGA Cable	1	Shielded, 1.8m
B	DVI Cable	1	Shielded, 1.8m
C	Parallel Cable	1	Shielded, 1.8m
D	USB Cable	1	Shielded, 1.5m
E	USB Cable	1	Shielded, 1.8m, with one ferrite core bonded



2.5. General Information of Test

Test Site :	CerpPASS Technology Corp.
Performed Location	No.66, Tangzhuang Road, Suzhou Industrial Park, Jiangsu, China
NVLAP LAB Code :	200814-0
FCC Registration Number :	916572
VCCI Registration Number :	T-343 for Telecommunication Test C-2919 for Conducted emission test R-2670 for Radiated emission test
Test in Compliance with:	ANSI C63.4-2003 FCC Part 15 Subpart B
Frequency Range Investigated :	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 1,000 MHz Radiation: from 1GHz to 18GHz
Test Distance :	The test distance of radiated emission below 1GHz from antenna to EUT is 3 M. The test distance of radiated emission above 1GHz from antenna to EUT is 3 M.

Laboratory accreditation



2.6. Measurement Uncertainty

Conducted Emission		
The measurement uncertainty is evaluated as ± 2.71 dB.		
Radiated Emission		
(30MHz -1000MHz)	Horizontal	The measurement uncertainty is evaluated as ± 3.89 dB.
	Vertical	The measurement uncertainty is evaluated as ± 3.59 dB
(1G-18GHz)	Horizontal	The measurement uncertainty is evaluated as ± 2.31 dB.
	Vertical	The measurement uncertainty is evaluated as ± 2.15 dB.



3. Test of Conducted Emission

3.1. Test Limit


Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2003 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

3.2. Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

3.3. Typical test Setup




3.4. Measurement equipment

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date
EMC Emission Tester	EMCPARTNER	Harmonics-1000	159	2009.09.08
Test Receiver	R&S	ESCI	100565	2009.06.30
AMN	R&S	ESH2-Z5	100182	2009.06.23
Two-Line V-Network	R&S	ENV216	100325	2009.06.23
ISN	FCC	FCC-TLISN-T2-02	20379	2009.06.23
ISN	FCC	FCC-TLISN-T4-02	20380	2009.06.23
ISN	FCC	FCC-TLISN-T8-02	20381	2009.06.23
Attenuator	R&S	ESH3-Z2	100529	2010.01.11
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-004	2009.10.19



3.5. Test Result and Data

Test Mode :	Mode 1: Full system (VGA mode 1920*1080@60Hz)		
AC Power :	AC 120V/60Hz	Phase :	L&N
EUT :	LCD Monitor	Model No.:	E2240TV
Temperature :	20°C	Humidity:	50%
Pressur(mbar) :	1002	Date:	2010/03/05



Frequency MHz	Line Phase	Reading dB(uV) QP	Reading dB(uV) AV	Factor dB	Level dB(uV) QP	Level dB(uV) AV	Limit dB(uV) QP	Limit dB(uV) AV	Margin dB QP	Margin dB AV	Pass/Fail
0.18676	L1	25.5	10.6	19.5	45.0	30.1	64.2	54.2	19.2	24.1	Pass
0.24137	L1	19.2	2.5	19.5	38.7	22.0	62.0	52.0	23.3	30.0	Pass
1.30605	L1	7.8	-4.0	19.5	27.3	15.5	56.0	46.0	28.7	30.5	Pass
0.47922	L1	11.8	-0.9	19.7	31.5	18.8	56.4	46.4	24.9	27.6	Pass
1.91065	L1	7.8	-2.1	19.6	27.4	17.5	56.0	46.0	28.6	28.5	Pass
0.89593	L1	10.5	-1.7	19.5	30.0	17.8	56.0	46.0	26.0	28.2	Pass
0.18085	N	26.1	10.3	19.6	45.7	29.9	64.4	54.4	18.7	24.5	Pass
0.25166	N	19.3	5.5	19.8	39.1	25.3	61.7	51.7	22.6	26.4	Pass
0.60522	N	16.8	4.5	19.6	36.4	24.1	56.0	46.0	19.6	21.9	Pass
1.25755	N	14.8	2.9	19.5	34.3	22.4	56.0	46.0	21.7	23.6	Pass
1.56251	N	13.1	2.4	19.5	32.6	21.9	56.0	46.0	23.4	24.1	Pass
0.38629	N	12.4	0.2	19.7	32.1	19.9	58.1	48.1	26.0	28.2	Pass

Note: Measurement Level = Reading Level + Correct Factor

Chat 6s

Test engineer: _____



4. Test of Radiated Emission

4.1. Test Limit

Radiated emissions from 30 MHz to 1,000 MHz were measured with a bandwidth of 120 kHz according to the methods defines in ANSI C63.4-2003. The EUT was placed on a nonmetallic stand in the open-field site, 0.8 meter above the ground plane, as shown in section 3.2. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (m)	Level (dBuV/m)	Level (dBuV/m)
30 - 88	3	40(QP)	N/A
88 - 216	3	43(QP)	N/A
216-960	3	46(QP)	N/A
960-1000	3	54(QP)	N/A
1000-18000	3	74(PK)	54(AV)

For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the below table.

Frequency (MHz)	Distance Meters	Radiated (dB μ V/ M)
30-230	10	30
230-1000	10	37





4.2. Test Procedures

- The EUT was placed on a Rota table top 0.8 meter above ground.
- The EUT and its simulators are placed on the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters or 1 meter.
- The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.
- Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated on radiated measurement.
- Radiated emissions were investigated over the frequency range from 30MHz to 1GHz using a receiver bandwidth of 120KHz and the frequency range from 1GHz to 18GHz using a receiver bandwidth of 1MHz.

4.3. Typical test Setup

Below 1GHz Test Setup



**Above 1GHz Test Setup****4.4. Measurement equipment**


Instrument	Model No.	Manufacturer	Serial No.	Calibration Date
EMI Test Receiver	R&S	ESCI	100564	2009.06.23
H64 Amplifier	HP	8447F	3113A05582	2009.12.01
Preamplifier	Agilent	8449B	ED-HE-EMI-077	2010.02.10
Ultra Broadband Antenna	R&S	HL562	100362	2009.11.03
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-619	2009.09.26
Spectrum Analyzer	R&S	FSP40	100324	2009.11.02
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-001	2009.10.19



4.5. Test Result and Data

Under 1G

Engineer : Fred	
Site : EMC Lab AC 102	Time : 2010/03/05 - 10:04
Limit : FCC_CLASS_B_03M_QP	Margin : 6
EUT : LCD Monitor	Probe : HL562(30-1000MHz) - HORIZONTAL
Power : AC 120V/60Hz	Note : Mode 1: Full system (VGA mode 1920*1080@60Hz)




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		132.300	-17.058	42.300	25.243	-18.257	43.500	QUASIPeAK	300.000	266.100
2		200.100	-17.687	43.300	25.613	-17.887	43.500	QUASIPeAK	400.000	12.300
3		244.700	-15.423	43.200	27.777	-18.223	46.000	QUASIPeAK	300.000	54.300
4	*	273.300	-13.875	52.300	38.425	-7.575	46.000	QUASIPeAK	300.000	264.100
5		402.300	-10.728	36.600	25.873	-20.127	46.000	QUASIPeAK	300.000	147.900
6		554.200	-8.073	37.400	29.327	-16.673	46.000	QUASIPeAK	400.000	112.500

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor



Engineer : Fred	
Site : EMC Lab AC 102	Time : 2010/03/05 - 10:04
Limit : FCC_CLASS_B_03M_QP	Margin : 6
EUT : LCD Monitor	Probe : HL562(30-1000MHz) - VERTICAL
Power : AC 120V/60Hz	Note : Mode 1: Full system (VGA mode 1920*1080@60Hz)



		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		31.200	-8.372	34.600	26.228	-13.772	40.000	QUASIPeAK	200.000	26.400
2		163.200	-17.845	47.800	29.956	-13.544	43.500	QUASIPeAK	200.000	168.600
3	*	174.300	-17.235	51.200	33.966	-9.534	43.500	QUASIPeAK	200.000	142.700
4		265.400	-14.250	47.500	33.249	-12.751	46.000	QUASIPeAK	200.000	168.400
5		325.500	-12.105	44.400	32.295	-13.705	46.000	QUASIPeAK	200.000	265.400
6		413.300	-10.386	40.500	30.114	-15.886	46.000	QUASIPeAK	100.000	321.400


Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor



Above 1G:

Engineer : Fred	
Site : EMC Lab AC 102	Time : 2010/03/05 - 16:32
Limit : FCC_15_03M_PK	Margin : 6
EUT : LCD Monitor	Probe : BBHA9120D(1-18GHz) - HORIZONTAL
Power : AC 120V/60Hz	Note : Mode 1: Full system (VGA mode 1920*1080@60Hz)




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1601.320	-4.156	45.170	41.013	-32.987	74.000	PEAK	256.300	100.700
2		2941.370	0.527	45.140	45.667	-28.333	74.000	PEAK	185.600	301.200
3	*	3927.480	4.227	48.310	52.537	-21.463	74.000	PEAK	124.200	225.600

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor



Engineer : Fred	
Site : EMC Lab AC 102	Time : 2010/03/05 - 16:32
Limit : FCC_15_03M_AV	Margin : 6
EUT : LCD Monitor	Probe : BBHA9120D(1-18GHz) - HORIZONTAL
Power : AC 120V/60Hz	Note : Mode 1: Full system (VGA mode 1920*1080@60Hz)




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1601.320	-4.156	28.150	23.993	-30.007	54.000	AVERAGE	256.300	100.700
2		2941.370	0.527	26.140	26.667	-27.333	54.000	AVERAGE	185.600	301.200
3	*	3927.480	4.227	34.890	39.117	-14.883	54.000	AVERAGE	124.200	225.600

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor



Engineer : Fred	
Site : EMC Lab AC 102	Time : 2010/03/05 - 16:35
Limit : FCC_15_03M_PK	Margin : 6
EUT : LCD Monitor	Probe : BBHA9120D(1-18GHz) - VERTICAL
Power : AC 120V/60Hz	Note : Mode 1: Full system (VGA mode 1920*1080@60Hz)




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1703.500	-4.248	47.160	42.913	-31.087	74.000	PEAK	124.200	225.600
2		2728.330	0.665	43.150	43.815	-30.185	74.000	PEAK	185.600	301.200
3	*	4025.600	4.647	51.180	55.827	-18.173	74.000	PEAK	145.600	348.200

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor



Engineer : Fred	
Site : EMC Lab AC 102	Time : 2010/03/05 - 16:35
Limit : FCC_15_03M_AV	Margin : 6
EUT : LCD Monitor	Probe : BBHA9120D(1-18GHz) - VERTICAL
Power : AC 120V/60Hz	Note : Mode 1: Full system (VGA mode 1920*1080@60Hz)



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1	1703.500	-4.248	35.140	30.893	-23.107	54.000	AVERAGE	124.200	225.600
2	2728.330	0.665	31.140	31.805	-22.195	54.000	AVERAGE	185.600	301.200
3	* 4025.600	4.647	30.170	34.817	-19.183	54.000	AVERAGE	145.600	348.200

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Test engineer: Fred Guo