

Report Number: F690501/RF-RTL014156 Page: 1 of 7

TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: BEJIGCJ1PMN

Equipment Under Test : Car AVN

Model Name : IGCJ1PMN

Variant Model Name : IGCJ1PME

Applicant : LG Electronics USA

Manufacturer : LG Electronics Inc.

Date of Receipt : 2019.07.09

Date of Test(s) : 2019.07.15 ~ 2019.07.23

Date of Issue : 2019.07.31

In the configuration tested, the EUT complied with the standards specified above.

Tested By: Date: 2019.07.31

Nancy Park

Technical Manager: Date: 2019.07.31

Jungmin Yang



Report Number: F690501/RF-RTL014156 Page: 2 of 7

INDEX

Table of Contents	Page
1. General Information	3
2. RF Exposure Evaluation	5



Report Number: F690501/RF-RTL014156 Page: 3 of 7

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on

request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Telephone : +82 31 688 0901 FAX : +82 31 688 0921

1.2. Details of Applicant

Applicant : LG Electronics USA

Address : 1000 Sylvan Avenue, Englewood Cliffs, New Jersey, United States, 07632

Contact Person : Han, Kyung-su Phone No. : +2 201 472 2623

1.3. Details of Manufacturer

Company : LG Electronics Inc.

Address : 10, Magokjungang 10-ro, Gangseo-gu, Seoul, Korea, 07796

1.4. Description of EUT

Kind of Product	Car AVN
Model Name	IGCJ1PMN
Variant Model Name	IGCJ1PME
Power Supply	DC 12 V
Frequency Range	Bluetooth: 2 402 № ~ 2 480 № WLAN 2.4G (11b/g/n_HT20): 2 412 № ~ 2 462 № WLAN 5G Band 1 (11a/n_HT20, 11ac_VHT20): 5 180 № ~ 5 240 № WLAN 5G Band 1 (11n_HT40, 11ac_VHT40): 5 190 № ~ 5 230 № WLAN 5G Band 1 (11ac_VHT80): 5 210 № WLAN 5G Band 3 (11a/n_HT20, 11ac_VHT20): 5 745 № ~ 5 825 № WLAN 5G Band 3 (11n_HT40, 11ac_VHT40): 5 755 № ~ 5 795 № WLAN 5G Band 3 (11ac_VHT80): 5 775 №



Report Number: F690501/RF-RTL014156 Page: 7 of

1.5. Information of Variant Model

Model Name		Description		
		DAB	SXM	
Basic Model	IGCJ1PMN	0	Х	
Variant Model	IGCJ1PME	Х	0	

Note;

- IGCJ1PME is only for FCC

1.6. Test Report Revision

Revision	Report Number	Date of Issue	Description
0	F690501/RF-RTL014156	2019.07.31	Initial



Report Number: F690501/RF-RTL014156 Page: 5 of 7

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (쌘)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm)	Average Time	
(A) Limits for Occupational/Controlled Exposure					
0.3-3.0	614	1.63	*100	6	
3.0-30	1842/f	4.89/f	*900/f ²	6	
30-300	61.4	0.163	1.0	6	
300-1 500	-	-	f/300	6	
1 500-100 000	-	-	5	6	
(B) Limits for General Population/Uncontrolled Exposure					
0.3-1.34	614	1.63	*100	30	
1.34-30	824/f	2.19/f	*180/f ²	30	
30-300	27.5	0.073	0.2	30	
300-1 500	-	-	f/1500	30	
1 500-100 000	-	-	1.0	<u>30</u>	

2.1.1. Friis transmission formula: $Pd = (Pout*G)/(4*pi*R^2)$

Where Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



Report Number: F690501/RF-RTL014156 Page: 6 of 7

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

2.1.3. Test Information of Cable Loss and Antenna Gain

Test Item	Frequency Range (Mtz)	Cable Loss (dB)	Antenna Gain of EUT (dB i)	Final Antenna Gain (dB i)
Bluetooth	2 402 ~ 2 480	-1.94	3.00	1.06
WLAN 2.4G	2 412 ~ 2 462	-1.94	3.00	1.06
WLAN 5G	5 180 ~ 5 240	-2.08	8.01	5.93
WLAN 5G	5 745 ~ 5 825	-2.08	8.01	5.93

Note;

RTT5041-19(2019.04.24)(1)

-Final Antenna Gain (dB i) = Cable Loss (dB) + Antenna Gain of EUT (dB i)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm × 297 mm)



Report Number: F690501/RF-RTL014156 Page: 7 of 7

2.1.4. Output Power into Antenna & RF Exposure Evaluation Distance

Bluetooth

- Maximum tune up tolerance

Frequency (雕)	Power to	Average Antenna Bm)	Final Antenna Gain (dB i)	Power Density at 20 cm (ˌmʔ/cɪr/)	Limits (ﷺ)
2 402 ~ 2 480	C).5	1.06	0.000 285	1

WLAN 2.4G

- Maximum tune up tolerance

Frequency (脏)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (₪/cπ')	Limits (nW/cn²)
2 412 ~ 2 462	13.5	1.06	0.005 685	1

WLAN 5G

- Maximum tune up tolerance

Frequency (地) Output Average Power to Antenna (dB m)		Final Antenna Gain (dB i)	Power Density at 20 cm (ਛਾ/cਵਾਂ)	Limits (mW/cm²)
5 180 ~ 5 240	6	5.93	0.003 103	1
5 745 ~ 5 825	6	5.93	0.003 103	1

Note;

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².
- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20 $\,$ cm $\,$ between the radiator and your body.
- The antenna gain of this transmitter is less than $6\,\mathrm{dB}\,\mathrm{i}$ and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.

Simultaneous transmission of MPE test exclusion for worst case configuration.

Bluetooth: the ratio is 0.000 285 / 1 WLAN: the ratio is 0.005 685 / 1

Confirm the sum result of individual MPEs ratio is ≤ 1.0 ;

BT + WLAN: (0.000 285 / 1) + (0.005 685 / 1)

 $= 0.005 970 \le 1.0$

So this device meets the KDB447498 D01 v06 section 7.2 requirement of "Simultaneous transmission MPE test exclusion"

- End of the Test Report -