

TEST REPORT

FCC MPE Test for IL7SB
Certification

APPLICANT
LG Electronics Inc.

REPORT NO.
HCT-RF-2307-FI006-R1

DATE OF ISSUE
July 31, 2023

Tested by
Woong Jin Kim

Technical Manager
Jong Seok Lee

HCT CO., LTD.
Bongjai Huh
BongJai Huh / CEO



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401

**TEST
REPORT**

FCC MPE Test for
IL7SB

REPORT NO.

HCT-RF-2307-FI006-R1

DATE OF ISSUE

July 31, 2023

Additional Model

-

Applicant

LG Electronics Inc.

222, LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do 17709, Republic of Korea

**Eut Type
Model Name**

Silverbox RADIO ASM-RECEIVER
IL7SB

FCC ID

BEJIL7SB3

Frequency range

2 412 MHz ~ 2 462 MHz (WLAN)

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test results were applied only to the test methods required by the standard.

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	July 27, 2023	Initial Release
1	July 31, 2023	Revised The Typo on page 5.

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance

If this report is required to confirmation of authenticity, please contact to www.hct.co.kr



RF Exposure Statement

1. Limit

According to § 1.1310, § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34	614	1.63	*(100)	30
1.34 - 30	824/f	2.19/f	*(180/ f ²)	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	f/1500	30
1500 - 100.000	1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

2. Maximum Permissible Exposure Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = Power input to antenna

G = Power gain to the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

3. RESULTS

3-1. WLAN DTS Band (802.11b,g,n)

Average output Power at antenna input terminal	20.000	dBm
Average output Power at antenna input terminal	100.000	mW
Prediction distance	20.000	cm
Prediction frequency	2 412 ~ 2 462	MHz
Antenna Gain(Peak)	0.280	dBi
Antenna Gain(numeric)	1.067	-
Power density at prediction frequency(S)	0.02122	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

2.1091

EIRP	20.28	(dBm)
ERP	18.13	(dBm)
ERP	0.065	(W)
ERP Limit	3.00	(W)
MARGIN	16.64	(dB)