

HCT CO., LTD.



PRODUCT COMPLIANCE DIVISION
SAN 136-1, AMI-RI, BUBAL-EUP, ICHEON-SI, KYOUNGKI-DO, 467-701, KOREA
TEL : +82 31 639 8518 FAX : +82 31 639 8525 www.hct.co.kr

EMI REPORT (Certification)

LG Electronics, Inc.

**LG Twin Towers, 20. Yeouido-dong,
Yeongdeungpo-go, Seoul Korea 150-721**

Date of Issue: July 15, 2008

Test Report No.: HCT-F08-0715

Test Site: HCT CO., LTD.

HCT FRN: 0005-8664-21

FCC ID:

BEJKP270

Classification/ Standard(s): FCC PART 15 Subpart B / CISPR 22 CLASS B

Equipment (EUT) Type: PCS GSM/EDGE Phone with Bluetooth

Trade Name/Model(s): LG Electronics, Inc. / KP270

Application Type: Certification

Port/ Connector(s): DC Input Port / Ear Phone Port

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse of 1988, 21 U.S.C.853 (a).

**Report prepared by
: Kyoung Hee Yoon
Test engineer of EMC Tech. Part**

**Approved by
: Sang Jun Lee
Manager of EMC Tech. Part**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	3
1.1 Product Description.....	3
1.2 Related submittal(s)/Grant(s).....	3
1.3 Tested System Details.....	4
1.4 Cable Description.....	4
1.5 Noise Suppression Parts on Cable. (I/O CABLE)	4
1.6 Test Methodology.....	5
1.7 Test Facility.....	5
1.8 Frequency range of radiated measurements	5
2. SYSTEM TEST CONFIGURATION.....	6
2.1 Configuration of Tested System.....	6
3. PRELIMINARY TEST.....	7
3.1 Conducted Emission Test.....	7
3.2 Radiated Emission Test.....	7
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY.....	8
4.1 Conducted Emission Test.....	9 – 12
4.2 Radiated Emission Test.....	13
5. FIELD STRENGTH CALCULATION.....	14
6. Test Equipment.....	15
7. Conclusion.....	16

ATTACHMENT : TEST SETUP PHOTOGRAPHS

1. GENERAL INFORMATION

1.1 Product Description

The **LG Electronics, Inc. KP270 PCS GSM/EDGE Phone with Bluetooth.**

Its basic purpose is used for communications. It transmits from GSM1900 (1850.20 MHz – 1909.80 MHz), Bluetooth (2402 MHz – 2480 MHz) and receives from GSM1900 (1930.20 MHz – 1989.80 MHz), Bluetooth (2402 MHz – 2480 MHz).

MODEL	KP270
FCC ID	BEJKP270
EUT Type	PCS GSM/EDGE Phone with Bluetooth
TX Frequency	1850.20 MHz – 1909.80 MHz (GSM1900) 2402 MHz – 2480 MHz (Bluetooth)
RX Frequency	1930.20 MHz – 1989.80 MHz (GSM1900) 2402 MHz – 2480 MHz (Bluetooth)

1.2 Related Submittal(s) / Grant(s)

ORIGINAL SUBMITTAL ONLY

1.3 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

DEVICE TYPE	MANUFACTURER	MODEL NUMBER /PART NUMBER	FCC ID / DoC	CONNECTED TO
PCS GSM/EDGE Phone with Bluetooth	LG Electronics, Inc.	KP270	BEJKP270	Notebook PC,TA
Travel Adaptor	Salcomp	STA-P52ES	-	EUT
Notebook PC	Toshiba	PSMA2K-010002	DoC	EUT,TA
Notebook PC Adaptor	Delta	SADP-65KB B	-	Notebook PC
Mouse	Microsoft	Intellimouse optical USB and PS/2 compatible	DoC	Notebook PC
Ear phone	-	-	-	EUT
USB Cable	-	-	-	EUT, Notebook PC

1.4 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (M)
PCS GSM/EDGE Phone with Bluetooth	DC In	N	N/A	(P)1.8
	Ear Jack	N/A	N	(D)1.5
	USB Data	Y	Y	(P, D)1.5
Notebook PC	USB (Mouse)	N/A	Y	(D)1.8

The marked "(D)" means the Data Cable and "(P)" means the Power Cable.

1.5 Noise Suppression Parts on Cable. (I/O CABLE)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
PCS GSM/EDGE Phone with Bluetooth	DC-In	N	N/A	Y	EUT End
	Ear-jack	N	N/A	Y	EUT End
	USB Data	N	N/A	Y	Both End
Notebook PC	USB (Mouse)	Y	Notebook PC End	Y	Notebook PC End

1.6 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4/2003. Radiated testing was performed at an antenna to EUT distance of 3 meters.

1.7 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1, Maekok-Ri, Hobup-Myun, Ichon-Si, Kyonggi-Do, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 6, 2006(Registration Number: 90661)

1.8 Frequency range of radiated measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a radiated emission limit is specified, up to the frequency shown in the following table


Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

2.SYSTEM TEST CONFIGURATION

2.1 Configuration of Test system

Line Conducted Test : EUT was connected to LISN, all other supporting equipment were connected to another LISN. Preliminary Power line Conducted Emission tests were performed by using the procedure in ANSI C63.4/2003 7.2.3 to determine the worst operating conditions.

Radiated Emission Test : Preliminary Radiated Emission tests were performed by using the procedure in ANSI C63.4/2003 8.3.1.1 to determine the worst operating condition. Final Radiated Emission tests were performed at 3 meter open area test site.



[Configuration of Tested System]

3. PRELIMINARY TEST

3.1 Conducted Emission Test

During Preliminary Tests, the following operating mode was investigated

Operation Mode	The worst operating condition
GSM Idle (1900) Mode	
Camera Mode	○
MP3 Mode	
Bluetooth Mode	
Data Communication Mode	

3. 2 Radiated Emission Test

During Preliminary Test, the Following operation mode was investigated

Operation Mode	The worst operating condition
GSM Idle (1900) Mode	
Camera Mode	
MP3 Mode	
Bluetooth Mode	
Data Communication Mode	○

4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission Test

The following table shows the highest levels of conducted emissions on both polarization of hot and neutral line.

Limit apply to	: CISPR 22 CLASS B
Result	: PASSED BY 10.2 dB
Operating Condition	: Camera Mode
Detector	: Quasi-Peak, Average (6 dB Bandwidth: 9 kHz)
Temperature	: 30.5 °C
Humidity Level	: 52.2 %
Test Date	: July 01, 2008

Power Line Conducted Emissions				CISPR 22 Class B	
Frequency (MHz)	Amplitude (dBuV)	Conductor	Result	Limit (dBuV)	Margin (dB)
0.9280	43.6	HOT	Quasi-Peak	56.0	12.4
0.9440	35.8	HOT	Average	46.0	10.2
0.9280	41.7	NEUTRAL	Quasi-Peak	56.0	14.3
0.9600	32.0	NEUTRAL	Average	46.0	14.0

Line Conducted Emissions Tabulated Data


HCT

EMC TEST LAB.

EUT: KP270
Manufacturer: LG
Operating Condition: CAMERA MODE
Test Site: SHIELD ROOM
Operator: YH, LEE
Test Specification: CISPR 22 CLASS B
Comment: H

SCAN TABLE: "CISPR 22 Voltage"

Short Description:			CISPR 22 Voltage				IF Bandw.	Transducer
Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time				
150.1 kHz	500.0 kHz	2.5 kHz	MaxPeak	10.0 ms	9 kHz	None		
			Average					
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None		
			Average					
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None		
			Average					



MEASUREMENT RESULT: "PHONE_fin_QP"

7/1/2008 2:01PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Line	PE
0.405100	43.70	10.0	58	14.0	---	---
0.427600	36.50	10.0	57	20.8	---	---
0.487600	37.00	10.1	56	19.3	---	---
0.908000	42.60	10.1	56	13.4	---	---
0.928000	43.60	10.1	56	12.4	---	---
0.944000	42.50	10.1	56	13.5	---	---
7.996000	39.50	11.0	60	20.5	---	---
8.684000	39.60	11.0	60	20.4	---	---
9.136000	39.10	11.1	60	20.9	---	---

MEASUREMENT RESULT: "PHONE_fin AV"

7/1/2008 2:01PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.372600	33.20	10.0	48	15.3	---	---
0.392600	32.90	10.0	48	15.1	---	---
0.407600	36.50	10.0	48	11.2	---	---
0.564000	33.30	10.1	46	12.7	---	---
0.928000	35.40	10.1	46	10.6	---	---
0.944000	35.80	10.1	46	10.2	---	---
8.380000	31.80	11.0	50	18.2	---	---
8.788000	31.60	11.0	50	18.4	---	---
8.892000	31.50	11.0	50	18.5	---	---


HCT

EMC TEST LAB.

EUT: KP270
Manufacturer: LG
Operating Condition: CAMERA MODE
Test Site: SHIELD ROOM
Operator: YH, LEE
Test Specification: CISPR 22 CLASS B
Comment: N

SCAN TABLE: "CISPR 22 Voltage"

Short Description:			CISPR 22 Voltage				Transducer
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	None	
Frequency	Frequency	Width					
150.1 kHz	500.0 kHz	2.5 kHz	MaxPeak	10.0 ms	9 kHz	None	
500.0 kHz	5.0 MHz	4.0 kHz	Average	10.0 ms	9 kHz	None	
			MaxPeak				
5.0 MHz	30.0 MHz	4.0 kHz	Average	10.0 ms	9 kHz	None	
			MaxPeak				
			Average				



MEASUREMENT RESULT: "PHONE_fin QP"

7/1/2008 2:10PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.405100	40.00	10.0	58	17.8	---	---
0.452600	29.80	10.1	57	27.0	---	---
0.497600	36.70	10.1	56	19.3	---	---
0.720000	40.80	10.1	56	15.2	---	---
0.856000	39.50	10.1	56	16.5	---	---
0.928000	41.70	10.1	56	14.3	---	---
5.856000	38.70	10.7	60	21.3	---	---
6.688000	38.00	10.8	60	22.0	---	---
8.616000	39.90	11.0	60	20.1	---	---

MEASUREMENT RESULT: "PHONE_fin AV"

7/1/2008 2:10PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.372600	30.20	10.0	48	18.3	---	---
0.407600	31.80	10.0	48	15.9	---	---
0.492600	29.00	10.1	46	17.1	---	---
0.712000	31.60	10.1	46	14.4	---	---
0.944000	33.30	10.1	46	12.7	---	---
0.960000	32.00	10.1	46	14.0	---	---
5.956000	30.80	10.7	50	19.2	---	---
8.904000	31.90	11.0	50	18.1	---	---
9.096000	31.80	11.1	50	18.2	---	---

4.2 Radiated Emission Test

The following table shows the highest levels of Radiated Emissions on both polarization of horizontal and vertical.

Limit apply to	: FCC PART 15 Subpart B
Result	: PASSED BY 6.0 dB
Operating Condition	: Data Communication Mode
Detector	: Quasi-Peak (6 dB Bandwidth: 120 kHz)
Temperature	: 31.5 °C
Humidity Level	: 54.2 %
Test Date	: July 10, 2008

Frequency	Reading	Ant. Factor	Cable Loss	ANT POL	Total	Limit	Margin
MHz	dBuV/m	dB/m	dB	(H/V)	dBuV/m	dBuV/m	dB
168.0	19.7	12.2	3.1	V	35.0	43.5	8.5
222.0	22.3	10.1	3.6	V	36.0	46.0	10.0
399.0	20.3	15.0	4.7	H	40.0	46.0	6.0
260.0	24.5	11.6	3.9	H	40.0	46.0	6.0
480.7	14.4	16.9	5.2	H	36.5	46.0	9.5

*** For measurement over 1 GHz, noise level was more than 10 dB below the limit.

5. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor.

The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

Assume a receiver reading of 21.5 dBuV/m is obtained. The Antenna Factor of 7.4 dB and a Cable Factor of 1.1 dB is added. The 30 dBuV/m value is mathematically converted to its corresponding level in uV/m.

$$FS = 21.5 + 7.4 + 1.1 = 30 \text{ dBuV/m}$$

Radiated emission limits

Frequency of emission	Field strength	
	V / m	dB V / m
30 ~ 88	100	40.0
88 ~ 216	150	43.5
216 ~ 960	200	46.0
Above 960	500	54.0

6. Test Equipment

<u>Type</u>	<u>Manufacture</u>	<u>Model Number</u>	<u>Next CAL Date</u>
EMI Test Receiver	Rohde & Schwarz	ESI40	2008.11.06
EMI Test Receiver	Rohde & Schwarz	ESCI	2009.06.01
LISN	EMCO	703125	2009.05.04
LISN	Rohde & Schwarz	ESH2-Z5	2009.04.18
LISN	Rohde & Schwarz	ESH3-Z5	2009.06.13
LISN	EMCO	3816/2SH	2009.02.01
Attenuator	Rohde & Schwarz	ESH3-Z2	2009.10.30
TRILOG Antenna	Schwarzbeck	VULB9168	2009.01.18
Communication Antenna	TDK	LPDA-0802	N/A
Antenna Position Tower	HD	240/520/00	N/A
Base Station	Rohde & Schwarz	CMU 200	2009.02.28
Horn Antenna	Schwarzbeck	BBHA 9120D	2009.03.18
RF-Amplifier	MITEQ	AMF-6D-00101800-35.20P.PS	2009.04.25
Bluetooth Base Station	TESCOM	TC-3000A	2009.01.11

7. Conclusion

The data collected shows that the **LG Electronics, Inc. PCS GSM/EDGE Phone with Bluetooth**
FCC ID: BEJKP270 Complies with §15.107 and §15.109 of the FCC Rules.