

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : OT-212-RWD-024

Reception No. : 2101000175

Applicant : LG Electronics USA

Address : 111 Sylvan Avenue, North Building, Englewood Cliffs, New Jersey, 07632, United States

Manufacturer : LG Electronics Inc

Address : 10, Magokjungang 10-ro, Gangseo-gu, Seoul, Republic of Korea

Type of Equipment : NAVIGATION RADIO

FCC ID. : BEJLANR22

Model Name : LANR22

Multiple Model Name : N/A

EUT Part Number : ASRNCNAG1A1

Serial Part Number : Refer to the clause 2.2

Total page of Report : 11 pages (including this page)

Date of Incoming : January 28, 2021

Date of issue : February 08, 2021

SUMMARY

The equipment complies with the regulation; *FCC PART 15 SUBPART C Section 15.247 and FCC PART 15 SUBPART E Section 15.407*

This test report only contains the result of a single test of the sample supplied for the examination.


It is not a generally valid assessment of the features of the respective products of the mass-production.



Tested by
Hyung-Kwon, Oh / Manager
ONETECH Corp.



Reviewed by
Tae-Ho, Kim / Senior Manager
ONETECH Corp.



Approved by
Ki-Hong, Nam / General Manager
ONETECH Corp.

CONTENTS**PAGE**

1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	7
3. EUT MODIFICATIONS.....	7
4. MAXIMUM PERMISSIBLE EXPOSURE	8
4.1 RF EXPOSURE CALCULATION	8
4.2 EUT DESCRIPTION.....	8
4.3 CALCULATED MPE SAFE DISTANCE FOR WLAN	9
4.4 CALCULATED MPE SAFE DISTANCE FOR BLUETOOTH LE	10
4.5 CALCULATED MPE SAFE DISTANCE FOR BLUETOOTH	10
4.6 DATA FOR INTERMODULATION TRANSMIT	11

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-212-RWD-024	February 08, 2021	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : LG Electronics USA
 Address : 111 Sylvan Avenue, North Building, Englewood Cliffs, New Jersey, 07632, United States
 Contact Person : Dae Woong Kim / Director, Regulatory and Environmental Affairs
 Telephone No. : 201-266-2215
 FCC ID : BEJLANR22
 Model Name : LANR22
 Brand Name : Alliance-RNM
 Serial Number : N/A
 Date : February 08, 2021

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM Unlicensed National Information infrastructure(UNII)
E.U.T. DESCRIPTION	NAVIGATION RADIO
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02 FCC PART 15 SUBPART E Section 15.407 789033 D02 General UNII Test Procedures New Rules v02r01
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The LG Electronics USA, Model LANR22 (referred to as the EUT in this report) is a NAVIGATION RADIO. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	NAVIGATION RADIO	
Temperature Range	-40 °C ~ 80 °C	
OPERATING FREQUENCY	Bluetooth LE	2 402 MHz ~ 2 480 MHz
	Bluetooth	2 402 MHz ~ 2 480 MHz
	WLAN 2.4 GHz	2 412 MHz ~ 2 462 MHz (802.11b/g/n(HT20))
	5 150 MHz ~ 5 250 MHz Band	5 180 MHz ~ 5 240 MHz (802.11a/n(HT20)/ac(VHT20))
		5 190 MHz ~ 5 230 MHz (802.11n(HT40)/ac(VHT40))
		5 210 MHz (802.11ac(VHT80))
	5 725 MHz ~ 5 850 MHz Band	5 745 MHz ~ 5 805 MHz (802.11a/n(HT20)/ac(VHT20))
		5 755 MHz ~ 5 795 MHz (802.11n(HT40)/ac(VHT40))
5 775 MHz (802.11ac(VHT80))		
MODULATION TYPE	Bluetooth LE	GFSK for 1 Mbps / 2 Mbps
	Bluetooth	GFSK for 1 Mbps, $\pi/4$ -DQPSK for 2 Mbps, 8-DPSK for 3 Mbps
	WLAN 2.4 GHz	802.11b: DSSS Modulation(DBPSK/DQPSK/CCK)
		802.11g/n(HT20): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)
WLAN 5 GHz	802.11a/n(HT20)/n(HT40)/ac(VHT80): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)	

RF OUTPUT POWER	Bluetooth LE	1 Mbps	-2.62 dBm
		2 Mbps	-2.89 dBm
	Bluetooth	1 Mbps	-3.01 dBm
		2 Mbps	-4.21 dBm
		3 Mbps	-3.73 dBm
	WLAN 2.4 GHz	16.35 dBm(802.11b) 16.52 dBm(802.11g) 15.47 dBm(802.11n_HT20)	
	5 150 MHz ~ 5 250 MHz Band	13.44 dBm(802.11a)	
		9.37 dBm(802.11n_HT20)	
		8.70 dBm(802.11n_HT40) 6.72 dBm(802.11ac_VHT80)	
	5 725 MHz ~ 5 850 MHz Band	11.70 dBm(802.11a)	
11.60 dBm(802.11n_HT20)			
12.44 dBm(802.11n_HT40) 9.47 dBm(802.11ac_VHT80)			
ANTENNA TYPE	Bluetooth LE	Chip Antenna	
	Bluetooth	Chip Antenna	
	WLAN 2.4 GHz	PCB Antenna	
	WLAN 5 GHz	Chip Antenna	
ANTENNA GAIN	Bluetooth LE	2.49 dBi	
	Bluetooth	2.49 dBi	
	WLAN 2.4 GHz	-2.91 dBi	
	5 150 MHz ~ 5 250 MHz Band	2.89 dBi	
		2.53 dBi	
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)		32.768 kHz, 20 MHz, 25 MHz, 28.636 36 MHz, 38.4 MHz, 55.466 67 MHz	

2.2 Alternative type(s)/model(s); also covered by this test report.

-. The following lists consist of the added model and their differences.

Model Name : LANR22

Tested sample P/N : ASRNCNAG1A1

Variant P/N :

A	S	#	#	C	N	A	G	1	#	#
A1	A2	B1	B2	C1	C2	C3	C4	D1	E1	F1

The # in P/N can be 0 to 9 or A to Z according to below Character or Number table.

A1/A2 (Platform)	
AS	AV Silver Box

B1/B2 (Customer Code)	
RN	Renault
NS	Nissan
RS	Infinity

C1/C2/C3/C4 (Product spec.)	
CNAG	Ext. Display/Radio/RVC/Bluetooth/Wi-fi

D1 (Generation)	
1	Generation 1

E1 (Production Year)	
A	2021
B	2022
C	2023
D	2024
E	2025
F	2026

F1 (Country Information)	
1	EU/Canada
2	Mexico
3	USA
4	EU
5	Else
6	Japan
7	Korea

3. EUT MODIFICATIONS

-. None

4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are $f/1500$ mW/cm² for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm² for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm² exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm², Z = Impedance of free space, 377 Ω

E = Electric field strength in V/m, G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm, using P (mW) = P (W) / 1 000, d (cm) = 0.01 * d (m)

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm, P = Power in mW, G = Numeric antenna gain, and S = Power density in mW/cm²

4.2 EUT Description

Kind of EUT	NAVIGATION RADIO
Device Category	<input type="checkbox"/> Portable (< 20 cm separation) <input type="checkbox"/> Mobile (> 20 cm separation) <input checked="" type="checkbox"/> Others
Exposure Evaluation Applied	<input checked="" type="checkbox"/> MPE <input type="checkbox"/> SAR <input type="checkbox"/> N/A

4.3 Calculated MPE Safe Distance for WLAN

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)	Log	Linear			
2 400 ~ 2 483.5	802.11b	16.5 ± 1.0	17.50	56.23	-2.91	0.51	1.51	0.005 7	1.00
	802.11g	16.5 ± 1.0	17.50	56.23			1.51	0.005 7	1.00
	802.11n_HT20	15.5 ± 1.0	16.50	44.67			1.35	0.004 5	1.00
5 150 ~ 5 250	802.11a	13.5 ± 1.0	14.50	28.18	2.89	1.95	2.09	0.010 9	1.00
	802.11n_HT20	9.5 ± 1.0	10.50	11.22			1.32	0.004 3	1.00
	802.11n_HT40	8.5 ± 1.0	9.50	8.91			1.17	0.003 5	1.00
	802.11ac80	6.5 ± 1.0	7.50	5.62			0.93	0.002 2	1.00
5 725 ~ 5 850	802.11a	11.5 ± 1.0	12.50	17.78	2.53	1.79	1.59	0.006 3	1.00
	802.11n_HT20	11.5 ± 1.0	12.50	17.78			1.59	0.006 3	1.00
	802.11n_HT40	12.5 ± 1.0	13.50	22.39			1.79	0.008 0	1.00
	802.11ac80	9.5 ± 1.0	10.50	11.22			1.26	0.004 0	1.00

According to above table, for 5 150 ~ 5 250 MHz Band(802.11 a), safe distance,

$$D = 0.282 * \sqrt{(28.18 * 1.95)/1.00} = 2.09 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 28.18 * 1.95 / (4 * \pi * 20^2) = 0.010 9$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

4.4 Calculated MPE Safe Distance for Bluetooth LE

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)	Log	Linear			
2 402 ~ 2 480	1 Mbps	-3.0 ± 1.0	-2.00	0.63	2.49	1.77	0.30	0.000 2	1.00
	2 Mbps	-3.0 ± 1.0	-2.00	0.63			0.30	0.000 2	1.00

According to above table, for 2 402 ~ 2480 MHz Band(1 Mbps), safe distance,

$$D = 0.282 * \sqrt{(0.63 * 1.77)/1.00} = 0.30 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 0.63 * 1.77 / (4 * \pi * 20^2) = 0.000 2$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

4.5 Calculated MPE Safe Distance for Bluetooth

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)	Log	Linear			
2 402 ~ 2 480	1 Mbps	-3.5 ± 1.0	-3.50	0.45	2.49	1.77	0.25	0.000 2	1.00
	2 Mbps	-4.5 ± 1.0	-3.50	0.45			0.25	0.000 2	1.00
	3 Mbps	-4.0 ± 1.0	-3.00	0.50			0.27	0.000 2	1.00

According to above table, for 2 402 ~ 2480 MHz Band(3 Mbps), safe distance,

$$D = 0.282 * \sqrt{(0.50 * 1.77)/1.00} = 0.27 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 0.50 * 1.77 / (4 * \pi * 20^2) = 0.000 2$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

4.6 DATA for Intermodulation Transmit

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Power Density (mW/cm ²) @ 20 cm Separation	Sum Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)			
Bluetooth + WLAN 2 G	Bluetooth (1 Mbps)	-3.0 ± 1.0	-2.00	0.63	0.0002	0.005 9	1.00
	WLAN 2 G (802.11 b)	16.5 ± 1.0	17.50	56.23	0.0057		
Bluetooth + WLAN 5 G	Bluetooth (1 Mbps)	-3.0 ± 1.0	-2.00	0.63	0.0002	0.011 1	1.00
	WLAN 5 G (UNII 1_ 802.11 a)	13.5 ± 1.0	14.50	28.18	0.0109		
Bluetooth LE + WLAN 2 G	Bluetooth LE (3 Mbps)	-4.0 ± 1.0	-3.00	0.50	0.000 2	0.005 9	1.00
	WLAN 2 G (802.11 b)	16.5 ± 1.0	17.50	56.23	0.0057		
Bluetooth LE + WLAN 5 G	Bluetooth LE (3 Mbps)	-4.0 ± 1.0	-3.00	0.50	0.0002	0.011 1	1.00
	WLAN 5 G (UNII 1_ 802.11 a)	13.5 ± 1.0	14.50	28.18	0.0109		