

FCC LTE REPORT

FCC Certification

Applicant Name:
LG Electronics Inc.

Date of Issue:

May 28, 2015

Test Site/Location:

HCT CO., LTD., 74, Seoicheon-ro 578beon-gil,
Majang-myeon, Icheon-si, Gyeonggi-do, Korea

Report No.: HCT-R-1505-F009

HCT FRN: 0005866421

FCC ID: BEJLGAJ10

APPLICANT: LG Electronics Inc.

FCC Model(s): TM01LA-N

EUT Type: GSM/WCDMA /LTE Telematics NAD module

FCC Classification: PCS Licensed Transmitter (PCB)

FCC Rule Part(s): §2 , §27

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band7 (5)	2502.5 – 2567.5	4M51G7D	QPSK	0.141	21.48
		4M52W7D	16QAM	0.108	20.35
LTE – Band7 (10)	2505.0 – 2565.0	9M01G7D	QPSK	0.143	21.54
		8M96W7D	16QAM	0.110	20.40
LTE – Band7 (15)	2507.5 – 2562.5	13M5G7D	QPSK	0.145	21.62
		13M5W7D	16QAM	0.112	20.49
LTE – Band7 (20)	2510.0 – 2560.0	17M9G7D	QPSK	0.152	21.82
		17M9W7D	16QAM	0.115	20.61

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)



Report prepared by
: Kyoung Houn Seo
Test engineer of RF Team



Approved by
: Sang Jun Lee
Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1505-F009	May 28, 2015	- First Approval Report

Table of Contents

1. GENERAL INFORMATION	4
2. INTRODUCTION	5
2.1. EUT DESCRIPTION.....	5
2.2. MEASURING INSTRUMENT CALIBRATION.....	5
2.3. TEST FACILITY	5
3. DESCRIPTION OF TESTS	6
3.1 CONDUCTED OUTPUT POWER	6
3.2 EIRP RADIATED POWER AND RADIATED SPURIOUS EMISSIONS	7
3.3 PEAK-AVERAGE RATIO	8
3.4 OCCUPIED BANDWIDTH	9
3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	10
3.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	11
4. LIST OF TEST EQUIPMENT	12
5. SUMMARY OF TEST RESULTS	13
6. SAMPLE CALCULATION	14
7. TEST DATA	15
7.1 CONDUCTED OUTPUT POWER	15
7.2 EQUIVALENT ISOTROPIC RADIATED POWER OUTPUT (Band 7).....	20
7.3 RADIATED SPURIOUS EMISSIONS.....	23
7.3.1 RADIATED SPURIOUS EMISSIONS (5 MHz Band 7 LTE)	23
7.3.2 RADIATED SPURIOUS EMISSIONS (10 MHz Band 7 LTE)	24
7.3.3 RADIATED SPURIOUS EMISSIONS (15 MHz Band 7 LTE)	25
7.3.4 RADIATED SPURIOUS EMISSIONS (20 MHz Band 7 LTE)	26
7.4 PEAK-TO-AVERAGE RATIO	27
7.5 OCCUPIED BANDWIDTH	27
7.6 CONDUCTED SPURIOUS EMISSIONS	28
7.6.1 BAND EDGE.....	28
7.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	29
7.7.1 FREQUENCY STABILITY (5 MHz Band 7 LTE)	29
7.7.2 FREQUENCY STABILITY (10 MHz Band 7 LTE)	30
7.7.3 FREQUENCY STABILITY (15 MHz Band 7 LTE)	31
7.7.4 FREQUENCY STABILITY (20 MHz Band 7 LTE)	32
8. TEST PLOTS.....	33

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name: LG Electronics Inc.

Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do 451-713, Korea

FCC ID: BEJLGAJ10

Application Type: Certification

FCC Classification: PCS Licensed Transmitter (PCB)

FCC Rule Part(s): §2 , §27

EUT Type: GSM/WCDMA /LTE Telematics NAD module

FCC Model(s): TM01LA-N

Tx Frequency: 2502.5 MHz – 2567.5 MHz (LTE – Band 7): 5 MHz
2505.0 MHz – 2565.0 MHz (LTE – Band 7): 10 MHz
2507.5 MHz – 2562.5 MHz (LTE – Band 7): 15 MHz
2510.0 MHz – 2560.0 MHz (LTE – Band 7): 20 MHz

Max. RF Output Power:

Band 7 (5 MHz) :	0.141 W (QPSK) (21.48 dBm) 0.108 W (16-QAM) (20.35 dBm)
Band 7 (10 MHz) :	0.143 W (QPSK) (21.54 dBm) 0.110 W (16-QAM) (20.40 dBm)
Band 7 (15 MHz) :	0.145 W (QPSK) (21.62 dBm) 0.112 W (16-QAM) (20.49 dBm)
Band 7 (20 MHz) :	0.152 W (QPSK) (21.82 dBm) 0.115 W (16-QAM) (20.61 dBm)

Emission Designator(s):

Band 7 (5 MHz) :	4M51G7D (QPSK) / 4M52W7D (16-QAM)
Band 7 (10 MHz) :	9M01G7D (QPSK) / 8M96W7D (16-QAM)
Band 7 (15 MHz) :	13M5G7D (QPSK) / 13M5W7D (16-QAM)
Band 7 (20 MHz) :	17M9G7D (QPSK) / 17M9W7D (16-QAM)

Date(s) of Tests: April 22, 2015 ~ May 28, 2015

Antenna Specification Manufacturer: Laird Technologies
Antenna type: MIMO capable vehicle dome antenna
Peak Gain: Band 7 : -0.22 dBi

2. INTRODUCTION

2.1. EUT DESCRIPTION

The LG Electronics Inc. TM01LA-N GSM/WCDMA /LTE Telematics NAD module consists of LTE 7.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea.**

3. DESCRIPTION OF TESTS

3.1 CONDUCTED OUTPUT POWER

Test Procedure

Conducted Output Power is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 5.2.

5.2.1 Procedure for use with a spectrum/signal analyzer when EUT can be configured to transmit continuously or when sweep triggering/signal gating can be properly implemented

The EUT is considered to transmit continuously if it can be configured to transmit at a burst duty cycle of greater than or equal to 98% throughout the duration of the measurement. If this condition can be achieved, then the following procedure can be used to measure the average output power of the EUT.

This procedure can also be used when the EUT cannot be configured to transmit continuously, provided that the measurement instrument can be configured to trigger a sweep at the beginning of each full-power transmission burst, and the sweep time is less than or equal to the minimum transmission time during each burst (*i.e.*, no burst off-time is to be included in the measurement).

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Set number of points in sweep $\geq 2 \times$ span / RBW.
- e) Sweep time = auto-couple.
- f) Detector = RMS (power averaging).
- g) If the EUT can be configured to transmit continuously (*i.e.*, burst duty cycle $\geq 98\%$), then set the trigger to free run.
- h) If the EUT cannot be configured to transmit continuously (*i.e.*, burst duty cycle $< 98\%$), then use a sweep trigger with the level set to enable triggering only on full power bursts and configure the EUT to transmit at full power for the entire duration of each sweep. Ensure that the sweep time is less than or equal to the transmission burst duration.
- i) Trace average at least 100 traces in power averaging (*i.e.*, RMS) mode.
- j) Compute the power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with the band limits set equal to the OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

3.2 EIRP RADIATED POWER AND RADIATED SPURIOUS EMISSIONS

Note: EIRP(Equivalent Isotropic Radiated Power)

Test Procedure

Radiated emission measurements are performed in the Fully-anechoic chamber. The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-D-2010 Clause 2.2.17. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission. The level and position of the maximized emission is recorded with the spectrum analyzer using RMS detector.

A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_{d(dBm)} = P_{g(dBm)} - \text{cable loss}_{(dB)} + \text{antenna gain}_{(dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

The maximum EIRP is calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

Radiated spurious emissions

1. Frequency Range : 30 MHz ~ 10th Harmonics of highest channel fundamental frequency.
2. Measured distance : 30 MHz ~ 11 GHz at 3 m
11 GHz ~ 26 GHz at 1m
3. The EUT was setup to maximum output power. The 100 kHz RBW was used to scan from 30 MHz to 1 GHz. Also, the 1 MHz RBW was used to scan from 1 GHz to 26.5 GHz. And limit is -25 dBm. The high, low and a middle channel were tested for out of band measurements.

3.3 PEAK-AVERAGE RATIO.

Test Procedure


Peak to Average Power Ratio is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 5.7.

- Section 5.7.1 CCDF Procedure

- a) Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
- b) Set the number of counts to a value that stabilizes the measured CCDF curve;
- c) Set the measurement interval as follows:
 - 1) for continuous transmissions, set to 1 ms,
 - 2) for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
- d) Record the maximum PAPR level associated with a probability of 0.1%.

3.4 OCCUPIED BANDWIDTH.

Test set-up



(Configuration of conducted Emission measurement)

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

Test Procedure

OBW is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 4.2..

The EUT makes a call to the communication simulator. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels(low, middle and high operational range.)

The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.

Test Procedure

Spurious and harmonic emissions at antenna terminal is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 6.0.

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer.

The EUT was setup to maximum output power. The 1 MHz RBW was used to scan from 30 MHz to 26.5 GHz. And limit is -25 dBm. The high, low and a middle channel were tested for out of band measurements.


- Channel Edge Requirement : In the 1 MHz bands immediately outside and adjacent to the channel, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.

NOTES: The analyzer plot offsets were determined by below conditions.

- For LTE Band 7, total offset 27.7 dBm = 20 dBm attenuator + 6 dBm Divider + 1.7 dBm RF cables.

3.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

Test Set-up



* Nominal Operating Voltage

Test Procedure

Frequency stability is tested in accordance with ANSI/TIA-603-D-2010 section 2.2.2.

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from - 30 °C to + 50 °C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from battery end point to 100 % of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification — the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block(LTE Band7).

Time Period and Procedure:

The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).

1. The equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
2. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

NOTE: The EUT is tested down to the battery endpoint.

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Interval	Calibration Due
Agilent	N1921A/ Power Sensor	MY45241059	Annual	07/09/2015
Agilent	N1911A/ Power Meter	MY45100523	Annual	01/15/2016
MITEQ	AMF-6D-001180-35-20P/AMP	1081666	Annual	09/04/2015
Wainwright	WHK1.2/15G-10EF/H.P.F	4	Annual	06/17/2015
Wainwright	WRCJV2400/2483.5-2370/2520-60/12SS / B.R.F.	1	Annual	06/17/2015
Wainwright	WHK3.3/18G-10EF/H.P.F	2	Annual	06/17/2015
Hewlett Packard	11667B / Power Splitter	10545	Annual	02/22/2016
Hewlett Packard	11667B / Power Splitter	11275	Annual	04/29/2016
Digital	EP-3010/ Power Supply	3110117	Annual	10/29/2015
Schwarzbeck	UHAP/ Dipole Antenna	557	Biennial	03/23/2017
Schwarzbeck	UHAP/ Dipole Antenna	558	Biennial	03/23/2017
Korea Engineering	KR-1005L / Chamber	KRAC05063-3CH	Annual	10/29/2015
Schwarzbeck	BBHA 9120D/ Horn Antenna	147	Biennial	09/01/2016
Schwarzbeck	BBHA 9120D/ Horn Antenna	1151	Biennial	10/05/2015
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170541	Biennial	07/05/2015
WEINSCHL	ATTENUATOR	BR0592	Annual	10/22/2015
REOHDE&SCHWARZ	FSV40/Spectrum Analyzer	1307.9002K40-100931-NK	Annual	06/09/2015
Agilent	8960 (E5515C)/ Base Station	MY48360222	Annual	08/26/2015
Agilent	N9020A/ Signal Analyzer	MY51240695	Annual	02/12/2016
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6200863156	Annual	03/24/2016

5. SUMMARY OF TEST RESULTS

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS
2.1051, 27.53(m)(4)	Band Edge / Conducted Spurious Emissions.	< 40 + 10log10 (P[Watts]) at Channel edges < 43 + 10log10 (P[Watts]) between 5 and X MHz from Channel edges < 55 + 10log10 (P[Watts]) beyond X MHz beyond from Channel edges		PASS
27.50(d)(5)	Peak-Average Ratio	< 13 dB		PASS
2.1046	Conducted Output Power	N/A		PASS
2.1055, 27.54	Frequency stability	Emission must remain in band		PASS
27.50(h)(2)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP	RADIATED	PASS
2.1053, 27.53(m)(4)	Undesirable Emissions	< 40 + 10log10 (P[Watts]) at Channel edges < 43 + 10log10 (P[Watts]) between 5 and X MHz from Channel edges < 55 + 10log10 (P[Watts]) beyond X MHz beyond from Channel edges		PASS

6. SAMPLE CALCULATION

A. EIRP Sample Calculation

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
	channel	Freq.(MHz)						W	dBm
LTE Band7	21100	2,535.00	-15.36	19.46	10.72	1.78	V	0.69	28.40

EIRP = SubstituteLEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a wooden tripod is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter’s level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter’s level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of Equivalent Isotropic Radiated Power (**EIRP**).

B. Emission Designator

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

16QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = main carrier modulated in a combination of two

or more of the following modes;

amplitude, angle, pulse

7 = Quantized/Digital Info


D = Data transmission; telemetry; telecommand

7. TEST DATA

7.1 CONDUCTED OUTPUT POWER

Conducted Output Power was tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 5.2.

A base station simulator was used to establish communication with the EUT, and Spectrum analyzer was used for test results. This device was tested under all configurations and the highest power is reported. Conducted Output Powers of EUT are reported below.



Test Result

Band	Band Width (MHz)	Frequency (MHz)	Channel	Resource Block Size	Resource Block Offset	Average Power [dBm]	
						QPSK	16-QAM
Band 7	5	2502.5	20775	1	0	24.22	23.02
				1	12	24.10	22.92
				1	24	24.07	22.93
				12	0	22.99	22.12
				12	6	23.10	22.04
				12	11	23.05	21.93
				25	0	23.05	22.00
		2535.0	21100	1	0	24.16	23.06
				1	12	24.11	23.03
				1	24	24.13	23.07
				12	0	23.07	22.14
				12	6	23.00	22.12
				12	11	23.08	22.16
				25	0	23.04	22.09
		2567.5	21425	1	0	24.10	22.96
				1	12	23.76	22.72
				1	24	23.66	22.46
				12	0	22.87	21.94
				12	6	22.76	21.81
				12	11	22.70	21.77
				25	0	22.77	21.73

LTE Conducted Average Output Powers (5 MHz Band 7 LTE)

Band	Band Width (MHz)	Frequency (MHz)	Channel	Resource Block Size	Resource Block Offset	Average Power [dBm]	
						QPSK	16-QAM
Band 7	10	2505.0	20800	1	0	24.21	23.10
				1	24	24.05	22.94
				1	49	24.04	22.90
				25	0	23.05	22.01
				25	12	22.96	21.85
				25	24	23.01	21.93
				50	0	22.88	21.77
		2535.0	21100	1	0	24.16	23.03
				1	24	24.12	23.02
				1	49	24.17	23.07
				25	0	23.09	22.08
				25	12	23.10	22.08
				25	24	23.02	22.00
				50	0	23.05	21.98
		2565.0	21400	1	0	24.24	23.11
				1	24	24.17	23.05
				1	49	23.72	22.60
				25	0	23.15	22.06
				25	12	23.02	22.01
				25	24	22.83	21.84
				50	0	22.91	21.80

LTE Conducted Average Output Powers (10 MHz Band 7 LTE)

Band	Band Width (MHz)	Frequency (MHz)	Channel	Resource Block Size	Resource Block Offset	Average Power [dBm]	
						QPSK	16-QAM
Band 7	15	2507.5	20825	1	0	24.13	22.99
				1	36	24.09	22.93
				1	74	24.21	23.10
				36	0	22.90	21.94
				36	18	23.03	22.00
				36	38	23.06	22.01
				75	0	22.90	21.90
		2535.0	21100	1	0	24.24	23.10
				1	36	24.18	23.15
				1	74	24.26	23.22
				36	0	23.20	22.18
				36	18	23.15	22.13
				36	38	23.14	22.09
				75	0	23.07	22.03
		2562.5	21375	1	0	24.37	23.35
				1	36	24.05	23.03
				1	74	23.68	22.59
				36	0	23.19	22.17
				36	18	23.08	22.08
				36	38	22.90	21.95
				75	0	22.93	21.97

LTE Conducted Average Output Powers (15 MHz Band 7 LTE)

Band	Band Width (MHz)	Frequency (MHz)	Channel	Resource Block Size	Resource Block Offset	Average Power [dBm]	
						QPSK	16-QAM
Band 7	20	2510.0	20850	1	0	24.13	22.98
				1	49	24.05	22.95
				1	99	24.11	23.01
				50	0	22.85	21.83
				50	25	22.92	21.86
				50	49	22.84	21.83
				100	0	22.99	21.91
		2535.0	21100	1	0	24.07	23.00
				1	49	24.12	23.03
				1	99	24.26	23.11
				50	0	23.03	22.03
				50	25	22.95	21.98
				50	49	23.02	22.07
				100	0	23.02	22.08
		2560.0	21350	1	0	24.32	23.30
				1	49	24.18	23.12
				1	99	23.69	22.59
				50	0	23.20	22.22
				50	25	23.16	22.09
				50	49	22.90	21.91
				100	0	23.09	22.06

LTE Conducted Average Output Powers (20 MHz Band 7 LTE)

Note : Detecting mode is average.

7.2 EQUIVALENT ISOTROPIC RADIATED POWER OUTPUT (Band 7)

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	
								W	dBm
2502.5	5 MHz	QPSK	-23.66	11.69	10.63	1.60	H	0.118	20.72
		16-QAM	-24.93	10.42	10.63	1.60	H	0.088	19.45
2535.0		QPSK	-23.19	12.41	10.70	1.63	H	0.141	21.48
		16-QAM	-24.32	11.28	10.70	1.63	H	0.108	20.35
2567.5		QPSK	-23.53	12.23	10.73	1.64	H	0.135	21.32
		16-QAM	-24.71	11.05	10.73	1.64	H	0.103	20.14

Equivalent Isotropic Radiated Power Data (5 MHz Band 7 LTE)

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

This device uses 1 m cables interchangeably. After testing under all configurations, worst case has been determined for the 1m cable.

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	
								W	dBm
2505.0	10 MHz	QPSK	-23.74	11.61	10.64	1.61	H	0.116	20.64
		16-QAM	-24.89	10.46	10.64	1.61	H	0.089	19.49
2535.0		QPSK	-23.13	12.47	10.70	1.63	H	0.143	21.54
		16-QAM	-24.27	11.33	10.70	1.63	H	0.110	20.40
2565.0		QPSK	-23.66	12.06	10.73	1.63	H	0.131	21.16
		16-QAM	-24.84	10.88	10.73	1.63	H	0.100	19.98

Equivalent Isotropic Radiated Power Data (10 MHz Band 7 LTE)

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

This device uses 1 m cables interchangeably. After testing under all configurations, worst case has been determined for the 1m cable.

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	
								W	dBm
2507.5	15 MHz	QPSK	-23.84	11.51	10.64	1.61	H	0.113	20.54
		16-QAM	-24.97	10.38	10.64	1.61	H	0.087	19.41
2535.0		QPSK	-23.15	12.45	10.70	1.63	H	0.142	21.52
		16-QAM	-24.27	11.33	10.70	1.63	H	0.110	20.40
2562.5		QPSK	-23.18	12.51	10.73	1.62	H	0.145	21.62
		16-QAM	-24.31	11.38	10.73	1.62	H	0.112	20.49

Equivalent Isotropic Radiated Power Data (15 MHz Band 7 LTE)

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

This device uses 1 m cables interchangeably. After testing under all configurations, worst case has been determined for the 1m cable.

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	
								W	dBm
2510.0	20 MHz	QPSK	-23.84	11.50	10.65	1.61	H	0.113	20.54
		16-QAM	-25.00	10.34	10.65	1.61	H	0.087	19.38
2535.0		QPSK	-23.37	12.23	10.70	1.63	H	0.135	21.30
		16-QAM	-24.45	11.15	10.70	1.63	H	0.105	20.22
2560.0		QPSK	-22.96	12.71	10.73	1.62	H	0.152	21.82
		16-QAM	-24.17	11.50	10.73	1.62	H	0.115	20.61

Equivalent Isotropic Radiated Power Data (20 MHz Band 7 LTE)

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

This device uses 1 m cables interchangeably. After testing under all configurations, worst case has been determined for the 1m cable.

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method

according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:

The EUT was placed on a non-conductive styrofoam resin table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For 5 MHz, 10MHz BW signals, a peak detector is used, with RBW ≥ OBW, VBW ≥ 3 x RBW. A Horn antenna was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain

the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

Also, we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna. The worst case of the EUT is x plane in LTE mode. Also worst case of detecting Antenna is horizontal polarization in LTE mode.

7.3 RADIATED SPURIOUS EMISSIONS

7.3.1 RADIATED SPURIOUS EMISSIONS (5 MHz Band 7 LTE)

- ▣ OPERATING FREQUENCY : 2535.00 MHz
- ▣ MEASURED OUTPUT POWER: 21.48 dBm = 0.141 W
- ▣ MODULATION SIGNAL: 5 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT: $55 + 10 \log_{10}(W) =$ 46.48 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
20775 (2502.5)	5,005.00	-42.41	12.40	-41.34	2.40	V	-31.34	52.82
	7,507.50	-54.20	11.06	-45.13	2.97	V	-37.04	58.52
	10,010.00	-56.63	11.68	-41.82	3.70	V	-33.84	55.32
21100 (2535.0)	5,070.00	-42.31	12.30	-40.83	2.39	V	-30.92	52.40
	7,605.00	-49.51	11.30	-40.32	3.07	V	-32.09	53.57
	10,140.00	-57.38	11.59	-43.26	3.66	V	-35.33	56.81
21425 (2567.5)	5,135.00	-42.95	12.35	-40.94	2.38	V	-30.97	52.45
	7,702.50	-54.69	11.45	-45.07	3.10	H	-36.72	58.20
	10,270.00	-53.50	11.40	-39.54	3.61	V	-31.75	53.23

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. This device uses 1 m cables interchangeably. After testing under all configurations, worst case has been determines for the 1 m cable.

7.3.2 RADIATED SPURIOUS EMISSIONS (10 MHz Band 7 LTE)

- ▣ OPERATING FREQUENCY : 2535.00 MHz
- ▣ MEASURED OUTPUT POWER: 21.54 dBm = 0.143 W
- ▣ MODULATION SIGNAL: 10 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT: $55 + 10 \log_{10}(W) =$ 46.54 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
20800 (2505.0)	5,010.00	-42.58	12.39	-41.34	2.38	V	-31.33	52.87
	7,515.00	-53.18	11.08	-44.24	3.00	V	-36.16	57.70
	10,020.00	-55.54	11.69	-40.73	3.83	V	-32.87	54.41
21100 (2535.0)	5,070.00	-42.67	12.30	-41.19	2.39	V	-31.28	52.82
	7,605.00	-50.59	11.30	-41.40	3.07	V	-33.17	54.71
	10,140.00	-54.94	11.59	-40.82	3.66	V	-32.89	54.43
21400 (2565.0)	5,130.00	-42.07	12.34	-40.22	2.37	V	-30.25	51.79
	7,695.00	-52.59	11.45	-43.05	3.10	V	-34.70	56.24
	10,260.00	-58.36	11.41	-43.78	3.69	V	-36.06	57.60

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. This device uses 1 m cables interchangeably. After testing under all configurations, worst case has been determines for the 1 m cable.

7.3.3 RADIATED SPURIOUS EMISSIONS (15 MHz Band 7 LTE)

- ▣ OPERATING FREQUENCY : 2562.50 MHz
- ▣ MEASURED OUTPUT POWER: 21.62 dBm = 0.145 W
- ▣ MODULATION SIGNAL: 15 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT: $55 + 10 \log_{10}(W) =$ 46.62 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
20825 (2507.5)	5,015.00	-41.38	12.39	-40.20	2.39	V	-30.20	51.82
	7,522.50	-53.27	11.10	-44.37	3.03	H	-36.30	57.92
	10,030.00	-54.64	11.69	-39.65	3.79	H	-31.75	53.37
21100 (2535.0)	5,070.00	-42.06	12.30	-40.58	2.39	V	-30.67	52.29
	7,605.00	-54.25	11.30	-45.06	3.07	V	-36.83	58.45
	10,140.00	-58.25	11.59	-44.13	3.66	H	-36.20	57.82
21375 (2562.5)	5,125.00	-40.38	12.33	-38.56	2.41	V	-28.64	50.26
	7,687.50	-59.43	11.44	-49.88	3.12	H	-41.56	63.18
	10,250.00	-58.24	11.42	-44.08	3.70	H	-36.36	57.98

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. This device uses 1 m cables interchangeably. After testing under all configurations, worst case has been determines for the 1 m cable.

7.3.4 RADIATED SPURIOUS EMISSIONS (20 MHz Band 7 LTE)

- ▣ OPERATING FREQUENCY : 2560.00 MHz
- ▣ MEASURED OUTPUT POWER: 21.82 dBm = 0.152 W
- ▣ MODULATION SIGNAL: 20 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT: $55 + 10 \log_{10}(W) =$ 46.82 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
20850 (2510.0)	5,020.00	-40.61	12.38	-39.50	2.39	V	-29.51	51.33
	7,530.00	-57.11	11.12	-48.02	3.03	H	-39.93	61.75
	10,040.00	-55.78	11.70	-40.54	3.84	H	-32.68	54.50
21100 (2535.0)	5,070.00	-42.08	12.30	-40.60	2.39	V	-30.69	52.51
	7,605.00	-57.01	11.30	-47.82	3.07	H	-39.59	61.41
	10,140.00	-56.33	11.59	-42.21	3.66	H	-34.28	56.10
21350 (2560.0)	5,120.00	-40.36	12.31	-38.56	2.45	V	-28.70	50.52
	7,680.00	-55.65	11.43	-45.95	3.12	V	-37.64	59.46
	10,240.00	-55.15	11.44	-41.09	3.67	H	-33.32	55.14

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 30 MHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. This device uses 1 m cables interchangeably. After testing under all configurations, worst case has been determines for the 1 m cable.

7.4 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
Band 7	5 MHz	2535.0	QPSK	25	0	4.83
			16-QAM	25	0	5.66
	10 MHz		QPSK	50	0	4.92
			16-QAM	50	0	5.72
	15 MHz		QPSK	75	0	4.69
			16-QAM	75	0	5.54
	20 MHz		QPSK	100	0	4.83
			16-QAM	100	0	5.70

- Plots of the EUT's Peak- to- Average Ratio are shown Page 38 ~ 41

7.5 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
Band 7	5 MHz	2535.0	QPSK	25	0	4.5119
			16-QAM	25	0	4.5172
	10 MHz		QPSK	50	0	9.0055
			16-QAM	50	0	8.9611
	15 MHz		QPSK	75	0	13.4740
			16-QAM	75	0	13.4650
	20 MHz		QPSK	100	0	17.9390
			16-QAM	100	0	17.9430

- Plots of the EUT's Occupied Bandwidth are shown Page 34 ~ 37

7.6 CONDUCTED SPURIOUS EMISSIONS

- Plots of the EUT's Conducted Spurious Emissions are shown Page 48 ~ 59.

7.6.1 BAND EDGE

Band	Band Width (MHz)	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Channel Edge Data [dBm]					
						Channel Edge (Limit: -10dBm)		5 MHz ~ X MHz from the Channel Edge (Limit: -13dBm)		X MHz ~ from the Channel Edge (Limit: -25dBm)	
						Lower	Upper	Lower	Upper	Lower	Upper
Band 7	5	2,502.5	QPSK	25	0	-11.83	-12.22	-26.95	-26.69	-30.52	-29.65
		2,535.0		25	0	-11.36	-12.63	-25.66	-27.01	-30.02	-31.54
		2,567.5		25	0	-10.08	-11.50	-24.54	-26.15	-28.69	-30.27
	10	2,505.0		50	0	-14.50	-16.30	-18.93	-19.49	-29.83	-27.93
		2,535.0		50	0	-14.56	-16.23	-19.36	-21.20	-27.77	-29.28
		2,565.0		50	0	-14.91	-15.39	-18.99	-19.36	-27.04	-30.32
	15	2,507.5		75	0	-15.65	-18.86	-19.17	-21.47	-34.94	-29.87
		2,535.0		75	0	-16.21	-18.50	-20.66	-22.27	-30.39	-30.63
		2,562.5		75	0	-17.67	-17.99	-21.09	-20.84	-28.10	-34.22
	20	2,510.0		100	0	-16.63	-19.85	-19.23	-21.83	-43.05	-31.45
		2,535.0		100	0	-17.47	-19.80	-21.28	-22.52	-31.35	-31.70
		2,560.0		100	0	-18.27	-20.20	-20.66	-22.53	-28.44	-42.33


- Plots of the EUT's Band Edge are shown Page 42 ~ 47

7.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

7.7.1 FREQUENCY STABILITY (5 MHz Band 7 LTE)

- ▣ OPERATING FREQUENCY: 2535.000,000 Hz
- ▣ CHANNEL: 21100 (5 MHz)
- ▣ REFERENCE VOLTAGE: 12.0 VDC
- ▣ DEVIATION LIMIT: -


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	12.0	+20(Ref)	2534 999 978	0	0.000 000	0.000
100%		-30	2534 999 956	-21.7	-0.000 001	-0.009
100%		-20	2534 999 998	19.7	0.000 001	0.008
100%		-10	2534 999 965	-12.6	0.000 000	-0.005
100%		0	2535 000 000	22.6	0.000 001	0.009
100%		+10	2534 999 965	-12.8	-0.000 001	-0.005
100%		+30	2534 999 966	-11.8	0.000 000	-0.005
100%		+40	2535 000 000	22.1	0.000 001	0.009
100%		+50	2534 999 963	-14.9	-0.000 001	-0.006
Batt. Endpoint	10.2	+20	2534 999 998	20.0	0.000 001	0.008



7.7.2 FREQUENCY STABILITY (10 MHz Band 7 LTE)

- ▣ OPERATING FREQUENCY: 2535.000,000 Hz
- ▣ CHANNEL: 21100 (10 MHz)
- ▣ REFERENCE VOLTAGE: 12.0 VDC
- ▣ DEVIATION LIMIT: -


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	12.0	+20(Ref)	2535 000 017	0	0.000 000	0.000
100%		-30	2535 000 037	19.8	0.000 001	0.008
100%		-20	2535 000 034	17.3	0.000 001	0.007
100%		-10	2535 000 033	16.7	0.000 001	0.007
100%		0	2535 000 035	17.8	0.000 001	0.007
100%		+10	2535 000 041	24.5	0.000 001	0.010
100%		+30	2535 000 037	20.1	0.000 001	0.008
100%		+40	2535 000 030	13.6	0.000 001	0.005
100%		+50	2535 000 039	22.3	0.000 001	0.009
Batt. Endpoint	10.2	+20	2535 000 030	13.3	0.000 001	0.005



7.7.3 FREQUENCY STABILITY (15 MHz Band 7 LTE)

- ▣ OPERATING FREQUENCY: 2535.000,000 Hz
- ▣ CHANNEL: 21100 (15 MHz)
- ▣ REFERENCE VOLTAGE: 12.0 VDC
- ▣ DEVIATION LIMIT: -


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	12.0	+20(Ref)	2535 000 012	0	0.000 000	0.000
100%		-30	2535 000 022	10.6	0.000 000	0.004
100%		-20	2534 999 990	-21.5	-0.000 001	-0.008
100%		-10	2535 000 029	17.7	0.000 001	0.007
100%		0	2535 000 020	8.4	0.000 000	0.003
100%		+10	2535 000 000	-11.7	0.000 000	-0.005
100%		+30	2535 000 000	-11.5	0.000 000	-0.005
100%		+40	2535 000 029	17.2	0.000 001	0.007
100%		+50	2535 000 030	18.8	0.000 001	0.007
Batt. Endpoint	10.2	+20	2535 000 026	14.7	0.000 001	0.006



7.7.4 FREQUENCY STABILITY (20 MHz Band 7 LTE)


- ▣ OPERATING FREQUENCY: 2535.000,000 Hz
- ▣ CHANNEL: 21100 (20 MHz)
- ▣ REFERENCE VOLTAGE: 12.0 VDC
- ▣ DEVIATION LIMIT: -

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	12.0	+20(Ref)	2534 999 986	0	0.000 000	0.000
100%		-30	2535 000 015	28.2	0.000 001	0.011
100%		-20	2534 999 967	-19.8	-0.000 001	-0.008
100%		-10	2534 999 972	-14.0	-0.000 001	-0.006
100%		0	2534 999 968	-17.9	-0.000 001	-0.007
100%		+10	2534 999 994	7.9	0.000 000	0.003
100%		+30	2534 999 963	-23.7	-0.000 001	-0.009
100%		+40	2535 000 007	20.6	0.000 001	0.008
100%		+50	2534 999 967	-19.2	-0.000 001	-0.008
Batt. Endpoint	10.2	+20	2534 999 995	8.9	0.000 000	0.004




8. TEST PLOTS


BAND7. Occupied Bandwidth Plot (5MHz Ch.21100 QPSK RB 25)




BAND7. Occupied Bandwidth Plot (5MHz Ch.21100 16-QAM RB 25)




BAND7. Occupied Bandwidth Plot (10MHz Ch.21100 QPSK RB 50)




BAND7. Occupied Bandwidth Plot (10MHz Ch.21100 16-QAM RB 50)




BAND7. Occupied Bandwidth Plot (15MHz Ch.21100 QPSK RB 75)




BAND7. Occupied Bandwidth Plot (15MHz Ch.21100 16-QAM RB 75)




BAND7. Occupied Bandwidth Plot (20MHz Ch.21100 QPSK RB 100)




BAND7. Occupied Bandwidth Plot (20MHz Ch.21100 16-QAM RB 100)




BAND7. Peak to Average Ratio Plot (5MHz Ch.21100 QPSK RB 25)




BAND7. Peak to Average Ratio Plot (5MHz Ch.21100 16-QAM RB 25)




BAND7. Peak to Average Ratio Plot (10MHz Ch.21100 QPSK RB 50)




BAND7. Peak to Average Ratio Plot (10MHz Ch.21100 16-QAM RB 50)




BAND7. Peak to Average Ratio Plot (15MHz Ch.21100 QPSK RB 75)




BAND7. Peak to Average Ratio Plot (15MHz Ch.21100 16-QAM RB 75)




BAND7. Peak to Average Ratio Plot (20MHz Ch.21100 QPSK RB 100)




BAND7. Peak to Average Ratio Plot (20MHz Ch.21100 16-QAM RB 100)




BAND7. Low Channel Edge Plot (5MHz Ch.20775 QPSK RB 25)




BAND7. Mid Channel Edge Plot (5MHz Ch.21100 QPSK RB 25)




BAND7. High Channel Edge Plot (5MHz Ch.21425 QPSK RB 25)




BAND7. Low Channel Edge Plot (10MHz Ch.20800 QPSK RB 50)




BAND7. Mid Channel Edge Plot (10MHz Ch.21100 QPSK RB 50)




BAND7. High Channel Edge Plot (10MHz Ch.21400 QPSK RB 50)




BAND7. Low Channel Edge Plot (15MHz Ch.20825 QPSK RB 75)




BAND7. Mid Channel Edge Plot (15MHz Ch.21100 QPSK RB 75)




BAND7. High Channel Edge Plot (15MHz Ch.21375 QPSK RB 75)




BAND7. Low Channel Edge Plot (20MHz Ch.20850 QPSK RB 100)




BAND7. Mid Channel Edge Plot (20MHz Ch.21100 QPSK RB 100)




BAND7. High Channel Edge Plot (20MHz Ch.21350 QPSK RB 100)




BAND7. Conducted Spurious Plot 1 (5MHz Ch.20775 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (5MHz Ch.20775 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (5MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (5MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (5MHz Ch.21425 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (5MHz Ch.21425 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (10MHz Ch.20800 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (10MHz Ch.20800 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (10MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (10MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (10MHz Ch.21400 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (10MHz Ch.21400 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (15MHz Ch.20825 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (15MHz Ch.20825 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (15MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (15MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (15MHz Ch.21375 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (15MHz Ch.21375 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (20MHz Ch.21100 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (20MHz Ch.21100 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 1 (20MHz Ch.21350 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (20MHz Ch.21350 QPSK RB 1, Offset 0)

