

WA-F-LB-02-271 Specification

1. Explanation of part number :

WA - F - LB - 02 - 271
(1) (2) (3) (4) (5)

(1) Product Type : Wireless Antenna

(2) Material: FPC

(3) Frequency : 2400~2500/5150~5850 MHZ

(4) Coaxial Cable Type : 02

(5) Suffix : 271

2. Storage Condition:

Temperature -40 to +70°C
Humidity 20 to 65 %RH

3. Operating Condition:

Temperature -40 to +70°C
Humidity 10 to 85 %RH

4. Electrical Specification :

Those specifications were specially defined for LG DXD WIFI model, and all characteristics were measured under the model's handset testing jig .

4-1. Frequency Band:

Frequency Band	MHz
WIFI\BT	2400~2500 & 5100~5800 & 5925~7125

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±

ANGLES=± HOLEDIA=±

SCALE : UNIT : mm

DRAWN BY: 张涛 CHECKED BY: 张涛

DESIGNED BY: 胡志清 APPROVED BY: 徐克文



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : WA-F-LB-02-271 Specification

DOCUMENT NO.

ENS000147470

PAGE REV.
A0

4-2. Impedance

50 ohm nominal

4-3. Matching circuit

None

4-4. VSWR

4-4.1 Measuring Method


1.A 50Ω coaxial cable is connected to the antenna. Then this cable is connected to a network analyzer to measure the VSWR

2.Keeping this jig away from metal at least 20cm

4-4.2 Measurement frequency points and VSWR value

VSWR	Frequency (Unit MHz)	Spec	1	2	3	4	5
Main Antenna	2400	≦3.5	2.2	2.2	1.5	1.9	1.7
	2500	≦3.0	1.7	1.5	1.5	1.6	1.9
	5000	≦3.0	1.6	1.7	2	1.8	1.7
	6000	≦3.0	1.8	1.8	1.9	1.8	1.8
	Judgement			ok	ok	ok	ok
Aux Antenna	2400	≦3.5	2.2	2	2.3	2.2	2.3
	2500	≦3.0	1.3	1.5	1.8	1.3	1.7
	5000	≦3.0	1.9	1.9	1.9	1.8	1.9
	6000	≦3.0	1.4	1.3	1.3	1.4	1.4
	Judgement			ok	ok	ok	ok


Main Antenna-1




Main Antenna-2



Main Antenna-3



Main Antenna-4



Main Antenna-5



UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±

ANGLES=± HOLEDIA=±

SCALE : UNIT : mm

DRAWN BY: 张涛 CHECKED BY: 张涛

DESIGNED BY: 胡志清 APPROVED BY: 徐克文



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : WA-F-LB-02-271 Specification

DOCUMENT
NO.


ENS000147470

PAGE REV.
A0


AUX Antenna-1




AUX Antenna-2




AUX Antenna-3



AUX Antenna-4



AUX Antenna-5




4-5. Efficiency and Gain

4-5.1 Measure method

1. Using a low loss coaxial cable to link a standard handset jig
2. Fixed this handset jig on chamber's rotator plane
3. Linking jig into network analyzer port and using a probing horn antenna to collect data.
4. Using another standard gain horn antenna to calibrated those data

4-5.2 Chamber definition

UNLESS OTHER SPECIFIED TOLERANCES ON :		 佳邦科技股份有限公司 INPAQ TECHNOLOGY CO., LTD.	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION
X=±	X.X=± X.XX=±		
ANGLES=±	HOLEDIA=±		
SCALE :	UNIT : mm		
DRAWN BY: 张涛	CHECKED BY: 张涛		
DESIGNED BY : 胡志清	APPROVED BY : 徐克文		
TITLE : WA-F-LB-02-271 Specification		DOCUMENT NO.	ENS000147470 PAGE REV. A0



1. An anechoic chamber (8mx4mx3.5m) which satisfied far-field condition was applied to avoid multi-path effect
2. The quiet room region is 40cmx40cmx40cm at the center of rotator
3. The distance between DUT and standard antenna is 4.38 m
4. Probing antenna (9120D horn antenna) and standard gain horn antenna (BBHA9120 LPF 700MHz ~6GHz)

4-5.3 Efficiency and Gain

Antenna gain is marked (dBi) and is based on STANDARD HORN antenna. The data shows Peak Gain and Average Gain.

4-5-3-1 Electrical specification

Frequency (MHz)	Average Efficiency (%)	Average Gain(dBi)
2400~2500	>30	>-5
5100~5825	>30	>-5

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±

ANGLES=± HOLEDIA=±

SCALE : UNIT : mm

DRAWN BY: 张涛 CHECKED BY: 张涛

DESIGNED BY: 胡志清 APPROVED BY: 徐克文



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : WA-F-LB-02-271 Specification

DOCUMENT
NO.

ENS000147470

PAGE REV.
A0

4-5.3-2 Efficiency and Gain Test Data


Frequency	Main Antenna-1			Main Antenna-2			Main Antenna-3		
	Efficiency	Average Gain	Peak Gain	Efficiency	Average Gain	Peak Gain	Efficiency	Average Gain	Peak Gain
2400MHz	44.4 %	-3.5 dBi	3.9 dBi	41.7 %	-3.8 dBi	1.5 dBi	45.4 %	-3.4 dBi	2.5 dBi
2425MHz	57.8 %	-2.4 dBi	5.3 dBi	43.3 %	-3.6 dBi	2.4 dBi	59.9 %	-2.2 dBi	3.2 dBi
2450MHz	52.4 %	-2.8 dBi	5.1 dBi	41.3 %	-3.8 dBi	2.3 dBi	53.6 %	-2.7 dBi	3.5 dBi
2475MHz	57.6 %	-2.4 dBi	6.0 dBi	44.4 %	-3.5 dBi	2.2 dBi	58.5 %	-2.3 dBi	4.7 dBi
2500MHz	61.3 %	-2.1 dBi	6.3 dBi	43.2 %	-3.6 dBi	1.4 dBi	62.3 %	-2.1 dBi	5.2 dBi
5150MHz	41.9 %	-3.8 dBi	2.9 dBi	31.3 %	-5.0 dBi	2.9 dBi	44.5 %	-3.5 dBi	2.7 dBi
5250MHz	42.5 %	-3.7 dBi	3.8 dBi	33.0 %	-4.8 dBi	2.5 dBi	43.8 %	-3.6 dBi	3.7 dBi
5350MHz	38.9 %	-4.1 dBi	0.5 dBi	32.3 %	-4.9 dBi	0.7 dBi	40.3 %	-3.9 dBi	3.1 dBi
5725MHz	44.4 %	-3.5 dBi	2.4 dBi	42.8 %	-3.7 dBi	1.9 dBi	44.3 %	-3.5 dBi	3.1 dBi
5825MHz	47.4 %	-3.2 dBi	2.7 dBi	44.6 %	-3.5 dBi	3.0 dBi	48.8 %	-3.1 dBi	3.0 dBi

Frequency	Main Antenna-4			Main Antenna-5		
	Efficiency	Average Gain	Peak Gain	Efficiency	Average Gain	Peak Gain
2400MHz	46.1 %	-3.4 dBi	3.9 dBi	47.0 %	-3.3 dBi	2.7 dBi
2425MHz	59.3 %	-2.3 dBi	4.2 dBi	61.6 %	-2.1 dBi	3.7 dBi
2450MHz	51.0 %	-2.9 dBi	3.9 dBi	55.0 %	-2.6 dBi	3.7 dBi
2475MHz	55.2 %	-2.6 dBi	4.4 dBi	59.8 %	-2.2 dBi	4.6 dBi
2500MHz	58.0 %	-2.4 dBi	4.6 dBi	62.7 %	-2.0 dBi	5.0 dBi
5150MHz	43.3 %	-3.6 dBi	3.7 dBi	44.1 %	-3.6 dBi	-0.6 dBi
5250MHz	42.3 %	-3.7 dBi	3.8 dBi	43.1 %	-3.7 dBi	0.1 dBi
5350MHz	38.2 %	-4.2 dBi	3.4 dBi	39.0 %	-4.1 dBi	-0.5 dBi
5725MHz	43.3 %	-3.6 dBi	4.0 dBi	44.3 %	-3.5 dBi	1.2 dBi
5825MHz	46.3 %	-3.3 dBi	4.7 dBi	48.3 %	-3.2 dBi	0.9 dBi

Frequency	AUX Antenna-1			AUX Antenna-2			AUX Antenna-3		
	Efficiency	Average Gain	Peak Gain	Efficiency	Average Gain	Peak Gain	Efficiency	Average Gain	Peak Gain
2400MHz	39.2 %	-4.1 dBi	3.0 dBi	34.2 %	-4.7 dBi	3.2 dBi	36.4 %	-4.4 dBi	3.1 dBi
2425MHz	40.6 %	-3.9 dBi	3.4 dBi	38.0 %	-4.2 dBi	3.5 dBi	40.2 %	-4.0 dBi	3.3 dBi
2450MHz	28.3 %	-5.5 dBi	2.0 dBi	34.8 %	-4.6 dBi	2.8 dBi	36.5 %	-4.4 dBi	2.9 dBi
2475MHz	28.8 %	-5.4 dBi	1.8 dBi	46.5 %	-3.3 dBi	3.6 dBi	47.2 %	-3.3 dBi	4.5 dBi
2500MHz	30.6 %	-5.1 dBi	1.8 dBi	51.3 %	-2.9 dBi	3.9 dBi	50.9 %	-2.9 dBi	5.0 dBi
5150MHz	32.7 %	-4.9 dBi	2.9 dBi	33.0 %	-4.8 dBi	2.9 dBi	32.8 %	-4.8 dBi	2.7 dBi
5250MHz	33.3 %	-4.8 dBi	3.8 dBi	33.3 %	-4.8 dBi	2.5 dBi	34.1 %	-4.7 dBi	3.7 dBi
5350MHz	32.3 %	-4.9 dBi	0.5 dBi	32.7 %	-4.9 dBi	0.7 dBi	33.7 %	-4.7 dBi	3.1 dBi
5725MHz	34.2 %	-4.7 dBi	2.4 dBi	39.4 %	-4.0 dBi	1.9 dBi	39.4 %	-4.1 dBi	3.1 dBi
5825MHz	36.8 %	-4.3 dBi	2.7 dBi	41.0 %	-3.9 dBi	3.0 dBi	41.0 %	-3.9 dBi	3.0 dBi

Frequency	AUX Antenna-4			AUX Antenna-5		
	Efficiency	Average Gain	Peak Gain	Efficiency	Average Gain	Peak Gain
2400MHz	36.2 %	-4.4 dBi	2.8 dBi	36.9 %	-4.3 dBi	3.3 dBi
2425MHz	39.9 %	-4.0 dBi	3.2 dBi	40.6 %	-3.9 dBi	3.9 dBi
2450MHz	36.1 %	-4.4 dBi	2.8 dBi	36.5 %	-4.4 dBi	3.4 dBi
2475MHz	47.1 %	-3.3 dBi	4.0 dBi	47.5 %	-3.2 dBi	4.4 dBi
2500MHz	51.2 %	-2.9 dBi	4.4 dBi	51.7 %	-2.9 dBi	4.5 dBi
5150MHz	32.9 %	-4.8 dBi	3.7 dBi	33.0 %	-4.8 dBi	-0.6 dBi
5250MHz	33.3 %	-4.8 dBi	3.8 dBi	33.9 %	-4.7 dBi	0.1 dBi
5350MHz	33.2 %	-4.8 dBi	3.4 dBi	32.4 %	-4.9 dBi	-0.5 dBi
5725MHz	39.2 %	-4.1 dBi	4.0 dBi	38.9 %	-4.1 dBi	1.2 dBi
5825MHz	40.7 %	-3.9 dBi	4.7 dBi	41.1 %	-3.9 dBi	0.9 dBi

4-5.3-3 Antenna 3D Radiation Pattern



UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
 ANGLES=± HOLEDIA=±

SCALE : UNIT : mm

DRAWN BY: 张涛 CHECKED BY: 张涛

DESIGNED BY: 胡志清 APPROVED BY: 徐克文



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.


THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : WA-F-LB-02-271 Specification

DOCUMENT NO.

ENS000147470


PAGE REV.
A0



AUX Antenna-1


AUX Antenna-2

AUX Antenna-3



AUX Antenna-4


AUX Antenna-5



5. Mechanical Specification:

Connector: I-PEX: 20278; Cable: RF Cable 1.13 (Black)

Cable length: 150 ± 2 mm(Include connector)





UNLESS OTHER SPECIFIED TOLERANCES ON :		 佳邦科技股份有限公司 INPAQ TECHNOLOGY CO., LTD.
X=±	X.X=±	
ANGLES=±	HOLEDIA=±	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION
SCALE :	UNIT : mm	
DRAWN BY: 张涛	CHECKED BY: 张涛	
DESIGNED BY : 胡志清	APPROVED BY : 徐克文	DOCUMENT NO. ENS000147470
TITLE : WA-F-LB-02-271 Specification		PAGE REV. A0

Mechanical Configuration: (* dimension is important dimension)



实物照片:



UNLESS OTHER SPECIFIED TOLERANCES ON :		 佳邦科技股份有限公司 INPAQ TECHNOLOGY CO., LTD.	
X=±	X.X=± X.XX=±		
ANGLES=±		THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
HOLEDIA=±			
SCALE :	UNIT : mm	DOCUMENT NO. ENS000147470	
DRAWN BY: 张涛	CHECKED BY: 张涛		PAGE REV. A0
DESIGNED BY: 胡志清	APPROVED BY: 徐克文		
TITLE : WA-F-LB-02-271 Specification		DOCUMENT NO. ENS000147470	