

WA-F-LB-03-162 Specification

1. Explanation of part number :

WA - F - LB - 03 - 162
(1) (2) (3) (4) (5)

(1) Product Type : Wireless Antenna

(2) Material: FPC

(3) Frequency : 2400~2500/5150~5850 MHz

(4) Coaxial Cable Type : 03

(5) Suffix : 162

2. Storage Condition:

Temperature -40 to +70°C
Humidity 20 to 65 %RH

3. Operating Condition:

Temperature -40 to +70°C
Humidity 10 to 85 %RH

4. Electrical Specification :

Those specifications were specially defined for LG DXD WIFI model, and all characteristics were measured under the model's handset testing jig .

4-1. Frequency Band:

Frequency Band	MHz
WIFI\BT	2400~2500 & 5150~5850

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±

ANGLES=± HOLEDIA=±

SCALE : UNIT : mm

DRAWN BY: 张涛 CHECKED BY: 张涛

DESIGNED BY: 胡志清 APPROVED BY: 徐克文



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : WA-F-LB-03-162 Specification

DOCUMENT NO.

ENS000164520

PAGE REV.
A0

4-2. Impedance

50 ohm nominal

4-3. Matching circuit

None

4-4. VSWR

4-4.1 Measuring Method

1.A 50Ω coaxial cable is connected to the antenna. Then this cable is connected to a network analyzer to measure the VSWR

2.Keeping this jig away from metal at least 20cm


4-4.2 Measurement frequency points and VSWR value

VSWR	Frequency (Unit MHz)	Spec	1	2	3	4	5
	2400	≦ 3.5	2.2	2	2.3	2.2	2.3
	2500	≦ 3.0	1.3	1.5	1.8	1.3	1.7
	5000	≦ 3.0	1.9	1.9	1.9	1.8	1.9
	6000	≦ 3.0	1.4	1.3	1.3	1.4	1.4
Judgement			ok	ok	ok	ok	ok

Antenna-1


Antenna-2

Antenna-3



Antenna-4

Antenna-5



4-5. Efficiency and Gain

4-5.1 Measure method

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±

ANGLES=± HOLEDIA=±

SCALE : UNIT : mm

DRAWN BY: 张涛 CHECKED BY: 张涛

DESIGNED BY: 胡志清 APPROVED BY: 徐克文



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : WA-F-LB-03-162 Specification


DOCUMENT
NO.

ENS000164520

PAGE REV.
A0

1. Using a low loss coaxial cable to link a standard handset jig
2. Fixed this handset jig on chamber's rotator plane
3. Linking jig into network analyzer port and using a probing horn antenna to collect data.
4. Using another standard gain horn antenna to calibrated those data

4-5.2 Chamber definition



1. An anechoic chamber (8mx4mx3.5m) which satisfied far-field condition was applied to avoid multi-path effect
2. The quiet room region is 40cmx40cmx40cm at the center of rotator
3. The distance between DUT and standard antenna is 4.38 m
4. Probing antenna (9120D horn antenna) and standard gain horn antenna (BBHA9120 LPF 700MHz ~6GHz)

4-5.3 Efficiency and Gain

Antenna gain is marked (dBi) and is based on STANDARD HORN antenna. The data shows Peak Gain and Average Gain.

4-5-3-1 Electrical specification

Frequency (MHz)	Antenna Average SPEC	
	Efficiency (%)	Average Gain(dBi)
2400~2500	>30	>-5
5100~5825	>30	>-5

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±

ANGLES=± HOLEDIA=±

SCALE : UNIT : mm

DRAWN BY: 张涛 CHECKED BY: 张涛

DESIGNED BY: 胡志清 APPROVED BY: 徐克文



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : WA-F-LB-03-162 Specification

DOCUMENT NO.

ENS000164520


PAGE REV.
A0

4-5.3-2 Efficiency and Gain Test Data

Frequency	Antenna-1			Antenna-2			Antenna-3		
	Efficiency	Average Gain	Peak Gain	Efficiency	Average Gain	Peak Gain	Efficiency	Average Gain	Peak Gain
2400MHz	43.1 %	-3.7 dBi	3.0 dBi	44.2 %	-3.5 dBi	3.2 dBi	46.4 %	-3.3 dBi	3.1 dBi
2425MHz	44.3 %	-3.5 dBi	3.4 dBi	44.0 %	-3.6 dBi	3.5 dBi	43.2 %	-3.6 dBi	3.3 dBi
2450MHz	43.3 %	-3.6 dBi	2.7 dBi	42.8 %	-3.7 dBi	2.8 dBi	42.5 %	-3.7 dBi	2.9 dBi
2475MHz	49.6 %	-3.0 dBi	2.8 dBi	46.5 %	-3.3 dBi	2.6 dBi	47.2 %	-3.3 dBi	2.5 dBi
2500MHz	45.5 %	-3.4 dBi	2.8 dBi	47.3 %	-3.3 dBi	2.9 dBi	50.9 %	-2.9 dBi	3.0 dBi
5150MHz	32.7 %	-4.9 dBi	2.9 dBi	33.0 %	-4.8 dBi	2.9 dBi	32.8 %	-4.8 dBi	2.7 dBi
5250MHz	33.3 %	-4.8 dBi	2.8 dBi	33.3 %	-4.8 dBi	2.5 dBi	34.1 %	-4.7 dBi	2.7 dBi
5350MHz	32.3 %	-4.9 dBi	3.0 dBi	32.7 %	-4.9 dBi	2.7 dBi	33.7 %	-4.7 dBi	3.1 dBi
5725MHz	37.2 %	-4.3 dBi	2.8 dBi	39.4 %	-4.0 dBi	2.9 dBi	39.4 %	-4.1 dBi	3.1 dBi
5825MHz	39.8 %	-4.0 dBi	2.7 dBi	41.0 %	-3.9 dBi	3.0 dBi	41.0 %	-3.9 dBi	3.0 dBi


Frequency	Antenna-4			Antenna-5		
	Efficiency	Average Gain	Peak Gain	Efficiency	Average Gain	Peak Gain
2400MHz	46.2 %	-3.4 dBi	2.8 dBi	44.9 %	-3.5 dBi	3.3 dBi
2425MHz	42.9 %	-3.7 dBi	3.2 dBi	40.6 %	-3.9 dBi	3.5 dBi
2450MHz	43.1 %	-3.7 dBi	2.8 dBi	46.5 %	-3.3 dBi	3.0 dBi
2475MHz	47.1 %	-3.3 dBi	3.0 dBi	47.5 %	-3.2 dBi	2.8 dBi
2500MHz	49.2 %	-3.1 dBi	2.9 dBi	48.7 %	-3.1 dBi	2.9 dBi
5150MHz	32.9 %	-4.8 dBi	2.7 dBi	33.0 %	-4.8 dBi	2.6 dBi
5250MHz	33.3 %	-4.8 dBi	2.8 dBi	33.9 %	-4.7 dBi	3.1 dBi
5350MHz	33.2 %	-4.8 dBi	3.1 dBi	32.4 %	-4.9 dBi	3.2 dBi
5725MHz	39.2 %	-4.1 dBi	3.0 dBi	38.9 %	-4.1 dBi	3.2 dBi
5825MHz	40.7 %	-3.9 dBi	2.7 dBi	41.1 %	-3.9 dBi	2.9 dBi

4-5.3-3 Antenna 3D Radiation Pattern




5. Mechanical Specification:


Connector: I-PEX: 20278; Cable: RF Cable 1.13 (Gray)

UNLESS OTHER SPECIFIED TOLERANCES ON :		 佳邦科技股份有限公司 INPAQ TECHNOLOGY CO., LTD.
X=±	X.X=±	
ANGLES=±	HOLEDIA=±	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION
SCALE :	UNIT : mm	
DRAWN BY: 张涛	CHECKED BY: 张涛	
DESIGNED BY: 胡志清	APPROVED BY: 徐克文	DOCUMENT NO. ENS000164520
TITLE : WA-F-LB-03-162 Specification		PAGE REV. A0

Cable length: 340 ± 2mm(Include connector)



Mechanical Configuration: (* dimension is important dimension)



实物照片:



UNLESS OTHER SPECIFIED TOLERANCES ON :		 佳邦科技股份有限公司 INPAQ TECHNOLOGY CO., LTD.	
X=±	X.X=± X.XX=±		
ANGLES=±		THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
HOLE DIA=±			
SCALE :	UNIT : mm	DOCUMENT NO. ENS000164520	
DRAWN BY: 张涛	CHECKED BY: 张涛		PAGE REV. A0
DESIGNED BY: 胡志清	APPROVED BY: 徐克文		
TITLE : WA-F-LB-03-162 Specification		DOCUMENT NO. ENS000164520	



UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±

ANGLES=± HOLEDIA=±

SCALE : UNIT : mm

DRAWN BY: 张涛 CHECKED BY: 张涛

DESIGNED BY : 胡志清 APPROVED BY : 徐克文



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : WA-F-LB-03-162 Specification

DOCUMENT NO.

ENS000164520

PAGE REV.
A0