



# TEST REPORT

FCC/ISED MPE Test for LGSBWAC97

**APPLICANT**

LG Electronics Inc.

**REPORT NO.**

HCT-RF-2207-FI010

**DATE OF ISSUE**

July 20, 2022

**Tested by**  
Jin Gwan Lee

**Technical Manager**  
Se Wook Park

Accredited by KOLAS, Republic of KOREA

**HCT CO., LTD.**

*BongJai Huh*

BongJai Huh / CEO

**HCT CO., LTD.**

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si,  
Gyeonggi-do, 17383 KOREA  
Tel. +82 31 634 6300 Fax. +82 31 645 6401

HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA  
Tel. +82 31 634 6300 Fax. +82 31 645 6401



# TEST REPORT

FCC MPE Test for  
LGSBWAC97

REPORT NO.

HCT-RF-2207-FI010

DATE OF ISSUE

July 20, 2022

Additional Model

-

Applicant

**LG Electronics Inc.**

222, LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 451-713, Republic of Korea

Eut Type  
Model Name

RF Module  
LGSBWAC97

FCC ID

BEJLGSBWAC97

Frequency range

2 402 MHz ~ 2 480 MHz (Bluetooth)  
2 412 MHz ~ 2 472 MHz (WLAN)  
5 180 MHz ~ 5 825 MHz (UNII)

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test results were applied only to the test methods required by the standard.

## REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	July 20, 2022	Initial Release

### Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance

### KOLAS Statement:

The above Test Report is the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (KOLAS Accreditation No. KT197)

If this report is required to confirmation of authenticity, please contact to [www.hct.co.kr](http://www.hct.co.kr)

## RF Exposure Statement

### 1. Limit

According to § 1.1310, § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f <sup>2</sup> )	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	.....	.....	f/1500	30
1500 - 100.000.....	.....	.....	1.0	30

F = frequency in MHz

\* = Plane-wave equivalent power density

### 2. Maximum Permissible Exposure Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = Power input to antenna

G = Power gain to the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

### 3. RESULTS

#### 3-1. Bluetooth

Max Average output Power at antenna input terminal	10.00	dBm
Max Average output Power at antenna input terminal	10.00	mW
Prediction distance	20.00	cm
Prediction frequency	2402 – 2480	MHz
Antenna Gain(typical)	1.12	dBi
Antenna Gain(numeric)	1.294	-
Power density at prediction frequency( S)	0.0026	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm <sup>2</sup>

#### 2.1091

EIRP	11.12	(dBm)
ERP	8.97	(dBm)
ERP	0.008	(W)
ERP Limit	3.00	(W)
MARGIN	25.80	(dB)

**3-1. BT LE**

Max Average output Power at antenna input terminal	10.00	dBm
Max Average output Power at antenna input terminal	10.00	mW
Prediction distance	20.00	cm
Prediction frequency	2402 – 2480	MHz
Antenna Gain(typical)	1.12	dBi
Antenna Gain(numeric)	1.294	-
Power density at prediction frequency( S)	0.0026	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm <sup>2</sup>

**2.1091**

EIRP	11.12	(dBm)
ERP	8.97	(dBm)
ERP	0.008	(W)
ERP Limit	3.00	(W)
MARGIN	25.80	(dB)

### 3-1. DTS\_MIMO

Max Average output Power at antenna input terminal	23.00	dBm
Max Average output Power at antenna input terminal	199.53	mW
Prediction distance	20.00	cm
Prediction frequency	2412 – 2472	MHz
Directional Gain(typical)	1.71	dBi
Directional Gain(numeric)	1.483	-
Power density at prediction frequency( S)	0.0588	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm <sup>2</sup>

### 2.1091

EIRP	24.71	(dBm)
ERP	22.56	(dBm)
ERP	0.180	(W)
ERP Limit	3.00	(W)
MARGIN	12.21	(dB)

**3-1. UNII\_MIMO**

Max Average output Power at antenna input terminal	23.00	dBm
Max Average output Power at antenna input terminal	199.53	mW
Prediction distance	20.00	cm
Prediction frequency	5180 – 5825	MHz
Directional Gain(typical)	4.51	dBi
Directional Gain(numeric)	2.825	-
Power density at prediction frequency( S)	0.1121	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm <sup>2</sup>

**2.1091**

EIRP	27.51	(dBm)
ERP	25.36	(dBm)
ERP	0.344	(W)
ERP Limit	3.00	(W)
MARGIN	9.41	(dB)

**Worst Case: Simultaneous MPE 20cm is**

5G MIMO WLAN (0.1121) + BT (0.0026) = 0.1147 < 1