

TEST REPORT

FCC MPE Test for TC10AN3NUN8
Class II Permissive Change

APPLICANT
LG Electronics Inc.

REPORT NO.
HCT-RF-2107-FC007-R1

DATE OF ISSUE
July 20, 2021

Tested by
Jae Mun Do

Technical Manager
Jong Seok Lee

HCT CO., LTD.
Bongjai Huh
BongJai Huh / CEO

HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401

TEST REPORT

FCC MPE Test for
TC10AN3NUN8

REPORT NO.

HCT-RF-2107-FC007-R1

DATE OF ISSUE

July 20, 2021

Additional Model

TC10AN3NUN5, TC10AN3NUN6, TC10AN3NUN7

Applicant

LG Electronics Inc.

222, LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 451-713, Korea

**Eut Type
Model Name**

GSM/WCDMA/LTE Telematics
TC10AN3NUN8

FCC ID

BEJLTC10N

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test results were applied only to the test methods required by the standard.

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	July 09, 2021	Initial Release
1	July 20, 2021	Revised the EUT Type

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

If this report is required to confirmation of authenticity, please contact to www.hct.co.kr



RF Exposure Statement

1. Limit

According to § 1.1310, § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	f/1500	30
1500 - 100.000.....	1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

2. Maximum Permissible Exposure Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = Power input to antenna

G = Power gain to the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

3. RESULTS

- GSM850(Voice & GPRS 1TX)-

Max Peak output Power at antenna input terminal	34.50	dBm
Max Peak output Power at antenna input terminal	2818.38	mW
Prediction distance	20.00	cm
Prediction frequency	824.2 - 848.8	MHz
Antenna Gain including Cable (typical)	2.905	dBi
Antenna Gain including Cable (numeric)	1.952	-
Duty Factor	9.175	dB
Power density at prediction frequency(S)	0.1324	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.5495	mW/cm ²

- GSM850(GPRS 2TX)-

Max Peak output Power at antenna input terminal	33.50	dBm
Max Peak output Power at antenna input terminal	2238.72	mW
Prediction distance	20.00	cm
Prediction frequency	824.2 - 848.8	MHz
Antenna Gain including Cable (typical)	2.905	dBi
Antenna Gain including Cable (numeric)	1.952	-
Duty Factor	6.083	dB
Power density at prediction frequency(S)	0.2143	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.5495	mW/cm ²

- GSM850(EDGE 1TX)-

Max Peak output Power at antenna input terminal	28.50	dBm
Max Peak output Power at antenna input terminal	707.95	mW
Prediction distance	20.00	cm
Prediction frequency	824.2 - 848.8	MHz
Antenna Gain including Cable (typical)	2.905	dBi
Antenna Gain including Cable (numeric)	1.952	-
Duty Factor	9.175	dB
Power density at prediction frequency(S)	0.0332	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.5495	mW/cm ²

- GSM850(EDGE 2TX)-

Max Peak output Power at antenna input terminal	27.50	dBm
Max Peak output Power at antenna input terminal	562.34	mW
Prediction distance	20.00	cm
Prediction frequency	824.2 - 848.8	MHz
Antenna Gain including Cable (typical)	2.905	dBi
Antenna Gain including Cable (numeric)	1.952	-
Duty Factor	6.083	dB
Power density at prediction frequency(S)	0.0538	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.5495	mW/cm ²

- GSM1900(Voice & GPRS 1TX)--

Max Peak output Power at antenna input terminal	31.00	dBm
Max Peak output Power at antenna input terminal	1258.93	mW
Prediction distance	20.00	cm
Prediction frequency	1 850.2 - 1 909.8	MHz
Antenna Gain including Cable (typical)	1.857	dBi
Antenna Gain including Cable (numeric)	1.534	-
Duty Factor	9.175	dB
Power density at prediction frequency(S)	0.0464	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- GSM1900(GPRS 2TX)-

Max Peak output Power at antenna input terminal	31.00	dBm
Max Peak output Power at antenna input terminal	1258.93	mW
Prediction distance	20.00	cm
Prediction frequency	1 850.2 - 1 909.8	MHz
Antenna Gain including Cable (typical)	1.857	dBi
Antenna Gain including Cable (numeric)	1.534	-
Duty Factor	6.083	dB
Power density at prediction frequency(S)	0.0947	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- GSM1900(EDGE 1TX)-

Max Peak output Power at antenna input terminal	27.50	dBm
Max Peak output Power at antenna input terminal	562.34	mW
Prediction distance	20.00	cm
Prediction frequency	1 850.2 - 1 909.8	MHz
Antenna Gain including Cable (typical)	1.857	dBi
Antenna Gain including Cable (numeric)	1.534	-
Duty Factor	9.175	dB
Power density at prediction frequency(S)	0.0207	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- GSM1900(GPRS 2TX)-

Max Peak output Power at antenna input terminal	27.00	dBm
Max Peak output Power at antenna input terminal	501.19	mW
Prediction distance	20.00	cm
Prediction frequency	1 850.2 - 1 909.8	MHz
Antenna Gain including Cable (typical)	1.857	dBi
Antenna Gain including Cable (numeric)	1.534	-
Duty Factor	6.083	dB
Power density at prediction frequency(S)	0.0377	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- WCDMA850-

Max Peak output Power at antenna input terminal	24.50	dBm
Max Peak output Power at antenna input terminal	281.84	mW
Prediction distance	20.00	cm
Prediction frequency	826.4 - 846.6	MHz
Antenna Gain including Cable (typical)	2.905	dBi
Antenna Gain including Cable (numeric)	1.952	-
Power density at prediction frequency(S)	0.1095	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.5509	mW/cm ²

- WCDMA1900-

Max Peak output Power at antenna input terminal	24.50	dBm
Max Peak output Power at antenna input terminal	281.84	mW
Prediction distance	20.00	cm
Prediction frequency	1 852.4 – 1 907.6	MHz
Antenna Gain including Cable (typical)	1.857	dBi
Antenna Gain including Cable (numeric)	1.534	-
Power density at prediction frequency(S)	0.0860	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- WCDMA1700-

Max Peak output Power at antenna input terminal	24.50	dBm
Max Peak output Power at antenna input terminal	281.84	mW
Prediction distance	20.00	cm
Prediction frequency	1 712.4 – 1 752.6	MHz
Antenna Gain including Cable (typical)	1.575	dBi
Antenna Gain including Cable (numeric)	1.437	-
Power density at prediction frequency(S)	0.0806	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- LTE Band 2-

Max Peak output Power at antenna input terminal	24.00	dBm
Max Peak output Power at antenna input terminal	251.19	mW
Prediction distance	20.00	cm
Prediction frequency	1 857.5 – 1 902.5	MHz
Antenna Gain including Cable (typical)	1.857	dBi
Antenna Gain including Cable (numeric)	1.534	-
Power density at prediction frequency(S)	0.0766	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- LTE Band 4-

Max Peak output Power at antenna input terminal	24.00	dBm
Max Peak output Power at antenna input terminal	251.19	mW
Prediction distance	20.00	cm
Prediction frequency	1 712.5 – 1 752.5	MHz
Antenna Gain including Cable (typical)	1.575	dBi
Antenna Gain including Cable (numeric)	1.437	-
Power density at prediction frequency(S)	0.0718	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- LTE Band 5-

Max Peak output Power at antenna input terminal	24.00	dBm
Max Peak output Power at antenna input terminal	251.19	mW
Prediction distance	20.00	cm
Prediction frequency	826.5 – 846.5	MHz
Antenna Gain including Cable (typical)	2.905	dBi
Antenna Gain including Cable (numeric)	1.952	-
Power density at prediction frequency(S)	0.0976	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.5510	mW/cm ²

- LTE Band 13-

Max Peak output Power at antenna input terminal	24.00	dBm
Max Peak output Power at antenna input terminal	251.19	mW
Prediction distance	20.00	cm
Prediction frequency	779.5 – 784.5	MHz
Antenna Gain including Cable (typical)	2.600	dBi
Antenna Gain including Cable (numeric)	1.820	-
Power density at prediction frequency(S)	0.0909	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.5197	mW/cm ²

- LTE Band 17-

Max Peak output Power at antenna input terminal	24.00	dBm
Max Peak output Power at antenna input terminal	251.19	mW
Prediction distance	20.00	cm
Prediction frequency	706.5 – 713.5	MHz
Antenna Gain including Cable (typical)	2.600	dBi
Antenna Gain including Cable (numeric)	1.820	-
Power density at prediction frequency(S)	0.0909	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.4710	mW/cm ²