



TEST REPORT

FCC/ISED BT LE Test for MR24GN
Certification

APPLICANT
LG Electronics Inc.

REPORT NO.
HCT-RF-2306-FI007

DATE OF ISSUE
June 28, 2023

Tested by
Woong Jin Kim

Technical Manager
Jong Seok Lee

Accredited by KOLAS, Republic of KOREA

HCT CO., LTD.
Bongjai Huh
BongJai Huh / CEO

HCT CO., LTD.
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si,
Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401



| | |
|--|--|
| <h1 style="margin: 0;">TEST REPORT</h1> <p style="margin: 0;">FCC/ISED BT LE Test for MR24GN</p> | <p>REPORT NO. HCT-RF-2306-FI007</p> |
| | <p>DATE OF ISSUE June 28, 2023</p> |
| | <p>Additional Model -</p> |

Applicant **LG Electronics Inc.**
222, LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do 17709, Republic of Korea

| | |
|-----------------------------|--|
| Eut Type | Magic Remote |
| Model Name | MR24GN |
| FCC ID | BEJMR24GN |
| IC | 2703H-MR24GN |
| Max. RF Output Power | 3.288 dBm (2.13 mW) |
| Modulation type | GFSK |
| FCC Classification | Digital Transmission System(DTS) |
| FCC Rule Part(s) | Part 15.247 |
| ISED Rule Part(s) | RSS-247 Issue 2 (February 2017) RSS-Gen Issue 5_Amendment 2 (February 2021) |

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.
This test results were applied only to the test methods required by the standard.

REVISION HISTORY

The revision history for this test report is shown in table.

| Revision No. | Date of Issue | Description |
|--------------|---------------|-----------------|
| 0 | June 28, 2023 | Initial Release |

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC / ISED Rules under normal use and maintenance.

KOLAS Statement:

The above Test Report is the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (KOLAS Accreditation No. KT197)

If this report is required to confirmation of authenticity, please contact to www.hct.co.kr

CONTENTS

| | |
|---|----|
| 1. EUT DESCRIPTION | 5 |
| 2. TEST METHODOLOGY | 6 |
| EUT CONFIGURATION | 6 |
| EUT EXERCISE | 6 |
| GENERAL TEST PROCEDURES | 6 |
| DESCRIPTION OF TEST MODES | 7 |
| 3. INSTRUMENT CALIBRATION | 7 |
| 4. FACILITIES AND ACCREDITATIONS | 7 |
| FACILITIES | 7 |
| EQUIPMENT | 7 |
| 5. ANTENNA REQUIREMENTS | 8 |
| 6. MEASUREMENT UNCERTAINTY | 9 |
| 7. DESCRIPTION OF TESTS | 10 |
| 8. SUMMARY TEST OF RESULTS | 28 |
| 9. TEST RESULT | 30 |
| 9.1 DUTY CYCLE | 30 |
| 9.2 6 dB BANDWIDTH & 99 % BANDWIDTH | 32 |
| 9.3 OUTPUT POWER | 36 |
| 9.4 POWER SPECTRAL DENSITY | 37 |
| 9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS | 40 |
| 9.6 RADIATED SPURIOUS EMISSIONS | 49 |
| 9.7 RADIATED RESTRICTED BAND EDGES | 53 |
| 9.8 RECEIVER SPURIOUS EMISSIONS | 55 |
| 10. LIST OF TEST EQUIPMENT | 56 |
| 11. ANNEX A_ TEST SETUP PHOTO | 58 |

1. EUT DESCRIPTION

| | | |
|---|---|--------------------------------|
| Model | MR24GN | |
| Additional Model | - | |
| EUT Type | Magic Remote | |
| Power Supply | DC 3.00 V | |
| Frequency Range | 2 402 MHz – 2 480 MHz | |
| Max. RF Output Power | Peak | 1 MBit/s : 3.288 dBm (2.13 mW) |
| | Average | 1 MBit/s : 3.11 dBm (2.05 mW) |
| Modulation Type | GFSK | |
| Bluetooth Version | 4.2 | |
| Number of Channels | 40 Channels | |
| Antenna Specification | Antenna type: PCB Antenna Peak Gain : 2.87 dBi | |
| Date(s) of Tests | June 12, 2023 ~ June 28, 2023 | |
| EUT Serial Number | Conduction : 23060900095F Radiation : 23060900094F | |
| PMN (Product Marketing Number) | Magic Remote | |
| HVIN (Hardware Version Identification Number) | MR24GN | |
| FVIN (Firmware Version Identification Number) | 1.0.192.2 | |
| HMN (Host Marketing Name) | N/A | |
| Manufacturer | LG Electronics Inc. 222, LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do 17709, Republic of Korea | |
| Factory | Hansung Electronics CO.,LTD. -. 49-29, Cheomdangieop 4-ro, Sandong-myeon, Gumi-si, Gyeongsangbuk-do, Korea -. Jl. Rotan 1 Blok F27 No.37A Lippo, Cikarang Delta Silicon 3, Kelurahan Cicau, Kecamatan Cikarang Pusat, Kabupaten Bekasi, Indonesia 17530 | |
| | OHSUNG Electronics CO.,LTD. -. 335-4, Sanho-daero, Gumi-si, Gyeongsangbuk-do, KOREA -. No.188 Tunpu South Road, Qiushe Economic Development Zone, Tongli Town, Wujiang City, Jiangsu Province, China -. Jl. Selayar Blok D7 Kawasan Industri MM 2100, Mekarwangi, Cikarang Barat 17845 Jawa Barat, Indonesia -. CERRADA CENTINELA 1719, PARQUE INDUSTRIAL CACHANILLA, MEXICALI, BAJA CALIFORNIA, MEXICO 21394 | |

2. TEST METHODOLOGY

FCC KDB 558074 D01 15.247 Meas Guidance v05r02 dated April 02, 2019 entitled “guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices and the measurement procedure described in ANSI C63.10(Version : 2013) ‘the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices’.

EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C. / RSS-Gen issue 5, RSS-247 issue 2.

GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1 GHz. Above 1 GHz with 1.5 m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.6.5 of ANSI C63.10. (Version: 2013)

DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment's, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

4. FACILITIES AND ACCREDITATIONS

FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil,

Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.

The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated April 02, 2018 (Registration Number: KR0032).

For ISED, test facility was accepted dated February 14, 2019 (CAB identifier: KR0032).

EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5. ANTENNA REQUIREMENTS

According to FCC 47 CFR § 15.203:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- (1) The antennas of this E.U.T are permanently attached.
- (2) The E.U.T Complies with the requirement of § 15.203

According to RSS-GEN(Issue 5) Section 6.8:

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence.


The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Parameter | Expanded Uncertainty (dB) |
|--|---|
| Conducted Disturbance (150 kHz ~ 30 MHz) | 1.90 (Confidence level about 95 %, $k=2$) |
| Radiated Disturbance (9 kHz ~ 30 MHz) | 4.14 (Confidence level about 95 %, $k=2$) |
| Radiated Disturbance (30 MHz ~ 1 GHz) | 5.82 (Confidence level about 95 %, $k=2$) |
| Radiated Disturbance (1 GHz ~ 18 GHz) | 5.74 (Confidence level about 95 %, $k=2$) |
| Radiated Disturbance (18 GHz ~ 40 GHz) | 5.76 (Confidence level about 95 %, $k=2$) |
| Radiated Disturbance (Above 40 GHz) | 5.52 (Confidence level about 95 %, $k=2$) |

7. DESCRIPTION OF TESTS

7.1. Duty Cycle

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to the zero-span measurement method, 6.0)b) in KDB 558074 v05r02.

The largest available value of RBW is 8 MHz and VBW is 50 MHz.

The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. (50/6.25 = 8)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.


1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz (\geq RBW)
3. SPAN = 0 Hz
4. Detector = Peak
5. Number of points in sweep > 100
6. Trace mode = Clear write
7. Measure T_{total} and T_{on}
8. Calculate Duty Cycle = T_{on}/T_{total} and Duty Cycle Factor = $10\log(1/Duty\ Cycle)$

7.2. 6 dB Bandwidth & 99 % Bandwidth(ISED)

Limit

The minimum permissible 6 dB bandwidth is 500 kHz.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Procedure 8.2 in KDB 558074 v05r02, Procedure 11.8.1 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW \geq 3 x RBW
- 3) Detector = Peak
- 4) Trace mode = Max hold
- 5) Sweep = auto couple
- 6) Allow the trace to stabilize
- 7) We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.

Test Procedure (99 % Bandwidth for ISED)

The transmitter output is connected to the spectrum analyzer.

RBW = 1 % ~ 5 % of the occupied bandwidth

VBW \approx 3 x RBW

Detector = Peak

Trace mode = max hold

Sweep = auto couple

Allow the trace to stabilize


Note : We tested OBW using the automatic bandwidth measurement capability of a spectrum analyzer.

7.3. Output Power

Limit

The maximum permissible conducted output power is 1 Watt.

Test Configuration



Test Procedure

The transmitter output is connected to the Power Meter.

- Peak Power (Procedure 11.9.1.3 in ANSI 63.10-2013)
: Measure the peak power of the transmitter.

- Average Power (Procedure 8.3.2.3 in KDB 558074 v05r02, Procedure 11.9.2.3 in ANSI 63.10-2013)
 - 1) Measure the duty cycle.
 - 2) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
 - 3) Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

Sample Calculation


- Conducted Output Power(Peak) = Measured Level + ATT loss + Cable loss
- Conducted Output Power(Average) = Measured Level + ATT loss + Cable loss + Duty Cycle Factor

7.4. Power Spectral Density

Limit

The transmitter power density average over 1-second interval shall not be greater than 8 dBm in any 3 kHz BW.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to Procedure 8.4 in KDB 558074 v05r02, Procedure 11.10 in ANSI 63.10-2013.

The spectrum analyzer is set to :

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Set span to at least 1.5 times the OBW.
- 3) $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$.
- 4) $VBW \geq 3 \times RBW$.
- 5) Sweep = auto couple
- 6) Detector = Peak
- 7) Trace mode = Max hold
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum amplitude level.
- 10) Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Sample Calculation

- Power Spectral Density = Measured Level + ATT loss + Cable loss


7.5. Conducted Band Edge(Out of Band Emissions) & Conducted Spurious Emissions

Limit

The maximum conducted (Peak) output power was used to demonstrate compliance, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

[Conducted > 20 dBc]

Test Configuration



Test Procedure

The transmitter output is connected to the spectrum analyzer.

(Procedure 8.5 in KDB 558074 v05r02, Procedure 11.11 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW \geq 3 x RBW
- 3) Set span to encompass the spectrum to be examined
- 4) Detector = Peak
- 5) Trace Mode = Max hold
- 6) Sweep time = auto couple
- 7) Ensure that the number of measurement points \geq 2 x Span/VBW
- 8) Allow trace to fully stabilize.
- 9) Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

Factors for frequency

| Freq(MHz) | Factor(dB) |
|-----------|------------|
| 30 | 20.07 |
| 100 | 20.14 |
| 200 | 20.15 |
| 300 | 20.20 |
| 400 | 20.23 |
| 500 | 20.25 |
| 600 | 20.25 |
| 700 | 20.27 |
| 800 | 20.28 |
| 900 | 20.29 |
| 1000 | 20.33 |
| 2000 | 20.47 |
| 2400 | 20.55 |
| 2480 | 20.53 |
| 2500 | 20.49 |
| 3000 | 20.58 |
| 4000 | 20.67 |
| 5000 | 20.76 |
| 5150 | 20.75 |
| 5850 | 20.84 |
| 6000 | 20.82 |
| 7000 | 20.90 |
| 8000 | 20.94 |
| 9000 | 21.02 |
| 10000 | 21.07 |
| 11000 | 21.12 |
| 12000 | 21.14 |
| 13000 | 21.20 |
| 14000 | 21.24 |
| 15000 | 21.27 |
| 16000 | 21.31 |
| 17000 | 21.38 |
| 18000 | 21.50 |
| 19000 | 21.50 |
| 20000 | 21.56 |
| 21000 | 21.77 |
| 22000 | 21.74 |
| 23000 | 21.94 |
| 24000 | 21.77 |
| 25000 | 21.80 |
| 26000 | 21.80 |

Note : 1. 2400 ~ 2500 MHz is fundamental frequency range.

2. Factor = Attenuator loss + Cable loss

3. Spectrum offset Loss = Attenuator loss + Cable loss + EUT Cable loss(0.5 dB) = 21.05 dB

7.6. Radiated Test

Limit

FCC

| Frequency (MHz) | Field Strength ($\mu\text{V}/\text{m}$) | Measurement Distance (m) |
|-----------------|---|--------------------------|
| 0.009 – 0.490 | 2400/F(kHz) | 300 |
| 0.490 – 1.705 | 24000/F(kHz) | 30 |
| 1.705 – 30 | 30 | 30 |

ISED


| Frequency (MHz) | Field Strength ($\mu\text{A}/\text{m}$) | Measurement Distance (m) |
|-----------------|---|--------------------------|
| 0.009 – 0.490 | 6.37/F(kHz) | 300 |
| 0.490 – 1.705 | 63.7/F(kHz) | 30 |
| 1.705 – 30 | 0.08 | 30 |

FCC&ISED


| Frequency (MHz) | Field Strength ($\mu\text{V}/\text{m}$) | Measurement Distance (m) |
|-----------------|---|--------------------------|
| 30-88 | 100 | 3 |
| 88-216 | 150 | 3 |
| 216-960 | 200 | 3 |
| Above 960 | 500 | 3 |

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



Test Procedure of Radiated spurious emissions(Below 30 MHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3 m from the EUT
3. The EUT is placed on a turntable, which is 0.8 m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization and Parallel to the ground plane in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor(0.009 MHz – 0.490 MHz) = $40\log(3 \text{ m}/300 \text{ m}) = - 80 \text{ dB}$
Measurement Distance : 3 m
7. Distance Correction Factor(0.490 MHz – 30 MHz) = $40\log(3 \text{ m}/30 \text{ m}) = - 40 \text{ dB}$
Measurement Distance : 3 m
8. Spectrum Setting
 - Frequency Range = 9 kHz ~ 30 MHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 9 kHz
 - VBW $\geq 3 \times$ RBW
9. Total = Measured Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)
10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

KDB 414788 OFS and Chamber Correlation Justification

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

Test Procedure of Radiated spurious emissions(Below 1 GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8 m above ground plane.
3. The Hybrid antenna was placed at a location 3 m from the EUT, which is varied from 1 m to 4 m to find out the highest emissions.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Spectrum Setting
 - (1) Measurement Type(Peak):
 - Measured Frequency Range : 30 MHz – 1 GHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 100 kHz
 - VBW \geq 3 x RBW
 - (2) Measurement Type(Quasi-peak):
 - Measured Frequency Range : 30 MHz – 1 GHz
 - Detector = Quasi-Peak
 - RBW = 120 kHz

※In general, (1) is used mainly
7. Total = Measured Value + Antenna Factor(A.F) + Cable Loss(C.L)
8. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

Test Procedure of Radiated spurious emissions (Above 1 GHz)

1. Radiated test is performed with hopping off.
 2. The EUT is placed on a turntable, which is 1.5 m above ground plane.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
 5. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
 6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
 7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
 8. Spectrum Setting
 - (1) Measurement Type(Peak):
 - Measured Frequency Range 1 GHz – 10th Harmonics
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 1 MHz
 - VBW \geq 3 x RBW
 - (2) Measurement Type(Average):
 - Duty cycle < 98%, duty cycle variations are less than $\pm 2\%$
 - Measured Frequency Range : 1 GHz – 25 GHz
 - Detector = RMS
 - Averaging type = power (*i.e.*, RMS)
 - RBW = 1 MHz
 - VBW \geq 3 x RBW
 - Sweep time = auto.
 9. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 10. Distance extrapolation factor = $20\log(\text{test distance} / \text{specific distance})$ (dB)
 11. Total (Measurement Type : Peak)
 - = Peak Measured Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)
 - Total (Measurement Type : Average)
 - = Average Measured Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)
- The duty cycle factor was the maximum supported by the protocol , then we measured average with no correction.

Test Procedure of Radiated Restricted Band Edge

1. Radiated test is performed with hopping off.
2. The EUT is placed on a turntable, which is 1.5 m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
5. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. Spectrum Setting
 - (1) Measurement Type(Peak):
 - Measured Frequency Range : 1 GHz – 10th Harmonics
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 1 MHz
 - VBW \geq 3 x RBW
 - (2) Measurement Type(Average):
 - Duty cycle < 98%, duty cycle variations are less than $\pm 2\%$
 - Measured Frequency Range : 1 GHz – 10th Harmonics
 - Detector = RMS
 - Averaging type = power (*i.e.*, RMS)
 - RBW = 1 MHz
 - VBW \geq 3 x RBW
 - Sweep time = auto.
 - Trace mode = average (at least 100 traces).
8. Distance extrapolation factor = $20\log(\text{test distance} / \text{specific distance})$ (dB)
9. Total(Measurement Type : Peak)
 - = Peak Measured Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)
 Total(Measurement Type : Average)
 - = Average Measured Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)
 - The duty cycle factor was the maximum supported by the protocol , then we measured average with no correction.
10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

7.7. AC Power line Conducted Emissions

Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

| Frequency Range (MHz) | Limits (dB μ V) | |
|-----------------------|-------------------------|-------------------------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 ^(a) | 56 to 46 ^(a) |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

^(a)Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.

Sample Calculation

Quasi-peak(Final Result) = Measured Level + Correction Factor

7.8. Receiver Spurious Emissions

Limit


| Frequency (MHz) | Field Strength ($\mu\text{V}/\text{m}$) | Measurement Distance (m) |
|-----------------|---|--------------------------|
| 30-88 | 100 | 3 |
| 88-216 | 150 | 3 |
| 216-960 | 200 | 3 |
| Above 960 | 500 | 3 |

Note:

Measurements for compliance with the limits in table may be performed at distances other than 3 metres.

Test Configuration


30 MHz - 1 GHz



Test Procedure of Receiver Spurious Emissions (Below 1GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8 m above ground plane.
3. The Hybrid antenna was placed at a location 3 m from the EUT, which is varied from 1 m to 4 m to find out the highest emissions.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Spectrum Setting
 - (1) Measurement Type(Peak):
 - Measured Frequency Range : 30 MHz – 1 GHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 100 kHz
 - VBW \geq 3 x RBW
 - (2) Measurement Type(Quasi-peak):
 - Measured Frequency Range : 30 MHz – 1 GHz
 - Detector = Quasi-Peak
 - RBW = 120 kHz
7. Total = Measured Value + Antenna Factor(A.F) + Cable Loss(C.L)

Above 1 GHz



Test Procedure of Radiated spurious emissions (Above 1 GHz)

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. Spectrum Setting
 - (1) Measurement Type(Peak):
 - Measured Frequency Range : 1 GHz – 25 GHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 1 MHz
 - VBW \geq 3 x RBW
 - (2) Measurement Type(Average):
 - Duty cycle < 98%, duty cycle variations are less than $\pm 2\%$
 - Measured Frequency Range : 1 GHz – 25 GHz

- Detector = RMS
 - Averaging type = power (*i.e.*, RMS)
 - RBW = 1 MHz
 - VBW \geq 3 x RBW
 - Sweep time = auto.
8. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
9. Distance extrapolation factor = $20\log$ (test distance / specific distance) (dB)
10. Total = Measured Level + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(A.G) + Distance Factor(D.F)

7.9. Worst case configuration and mode

Radiated Test

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone
 - Worstcase : Stand alone
2. EUT Axis:
 - Radiated Spurious Emissions : Z
 - Radiated Restricted Band Edge : X
3. All packet length of operation were investigated and the test results are worst case in lowest packet length.
(Worst case : 37 Byte)
4. All position of loop antenna were investigated and the test result is a no critical peak found at all positions.
 - Position : Horizontal, Vertical, Parallel to the ground plane

AC Power line Conducted Emissions

1. We don't perform powerline conducted emission test. Because this EUT is used DC.

Conducted test

1. The EUT was configured with packet length of highest power.

8. SUMMARY TEST OF RESULTS

FCC Part

| Test Description | FCC Part Section(s) | Test Limit | Test Condition | Test Result |
|-----------------------------------|-----------------------------------|----------------------|----------------|--------------|
| 6 dB Bandwidth | § 15.247(a)(2) | > 500 kHz | Conducted | PASS |
| Conducted Maximum Output Power | § 15.247(b)(3) | < 1 Watt | | PASS |
| Power Spectral Density | § 15.247(e) | < 8 dBm / 3 kHz Band | | PASS |
| Band Edge (Out of Band Emissions) | § 15.247(d) | Conducted > 20 dBc | | PASS |
| AC Power line Conducted Emissions | § 15.207 | cf. Section 7.7 | | N/A (#Note1) |
| Radiated Spurious Emissions | § 15.247(d), 15.205, 15.209 | cf. Section 7.6 | Radiated | PASS |
| Radiated Restricted Band Edge | § 15.247(d), 15.205, 15.209 | cf. Section 7.6 | | PASS |

#Note1 : Not Tested

ISED Part

| Test Description | ISED Part Section(s) | Test Limit | Test Condition | Test Result |
|--|----------------------------|--------------------------------|----------------|-------------|
| 6 dB Bandwidth | RSS-247, 5.2 | > 500 kHz | Conducted | PASS |
| 99% Bandwidth | RSS-GEN, 6.7 | N/A | | PASS |
| Conducted Maximum Peak Output Power And e.i.r.p. | RSS-247, 5.4.b | < 1 Watt <4 Watt(e.i.r.p.) | | PASS |
| Power Spectral Density | RSS-247, 5.2 | < 8 dBm / 3 kHz Band | | PASS |
| Band Edge(Out of Band Emissions) | RSS-247, 5.5 | Conducted > 20 dBc | | PASS |
| AC Power line Conducted Emissions | RSS-GEN, 8.8 | RSS-GEN section 8.8 table 4 | | N/A(#Note1) |
| Radiated Spurious Emissions | RSS-GEN, 8.9 | RSS-GEN section 8.9 table 5, 6 | Radiated | PASS |
| Receiver Spurious Emissions | RSS-GEN, 5 RSS-GEN, 7.3 | RSS-GEN section 7.3 table 3 | | PASS |
| Radiated Restricted Band Edge | RSS-GEN, 8.10 | RSS-GEN section 8.10 table 7 | | PASS |

#Note1 : Not Tested




9. TEST RESULT

9.1 DUTY CYCLE

| Data rate (Bit/s) | Packet length (Byte) | T _{on} (ms) | T _{total} (ms) | Duty Cycle | Duty Cycle Factor (dB) |
|----------------------|-------------------------|-------------------------|----------------------------|------------|---------------------------|
| 1M | 37 | 0.415 | 0.624 | 0.665 | 1.77 |

▣ 1M Bit/s (37 Byte) Test Plots

Duty Cycle (Low-CH 0)




9.2 6 dB BANDWIDTH & 99 % BANDWIDTH

FCC

| Mode (Bit/s) | Channel | 6 dB Bandwidth (kHz) | Limit (kHz) |
|-----------------|---------|-------------------------|----------------|
| 1M 37 Byte | 0 | 677.6 | > 500 |
| | 19 | 706.9 | |
| | 39 | 719.0 | |

▣ 1M Bit/s(37 Byte) Test Plots


6 dB Bandwidth plot (Low-CH 0)



6 dB Bandwidth plot (Mid-CH 19)



6 dB Bandwidth plot (High-CH 39)




99 % Bandwidth(ISED)


| Mode (Bit/s) | Packet length (Byte) | Channel | 99 % Bandwidth (MHz) |
|--------------|----------------------|---------|----------------------|
| 1M | 37 | 0 | 1.0436 |
| | | 19 | 1.0478 |
| | | 39 | 1.0491 |

1M Bit/s (37 Byte) Test Plots

99 % Bandwidth plot (Low-CH 0)



99 % Bandwidth plot (Mid-CH 19)



99 % Bandwidth plot (High-CH 39)



9.3 OUTPUT POWER

Peak Power

| Data rate (Bit/s) | Packet length (Byte) | LE Mode | | Measured Power(dBm) | Limit (dBm) |
|----------------------|-------------------------|-----------------|---------|---------------------|-------------|
| | | Frequency [MHz] | Channel | | |
| 1M | 37 | 2402 | 0 | 3.288 | 30 |
| | | 2440 | 19 | 2.975 | |
| | | 2480 | 39 | 2.681 | |

Average Power

| Data rate (Bit/s) | Packet length (Byte) | LE Mode | | Measured Power (dBm) | Duty Cycle Factor (dB) | Result (dBm) | Limit (dBm) |
|----------------------|-------------------------|-----------------|---------|----------------------|---------------------------|-----------------|-------------|
| | | Frequency [MHz] | Channel | | | | |
| 1M | 37 | 2402 | 0 | 1.34 | 1.77 | 3.11 | 30 |
| | | 2440 | 19 | 0.97 | 1.77 | 2.74 | |
| | | 2480 | 39 | 0.74 | 1.77 | 2.51 | |

9.4 POWER SPECTRAL DENSITY

| Frequency (MHz) | Channel No. | Mode (Bit/s) | Test Result | |
|-----------------|-------------|---------------------|---------------------|-------------------|
| | | | Measured Power(dBm) | Limit (dBm/3 kHz) |
| 2402 | 0 | 1M Bit/s 37 Byte | 3.060 | 8 |
| 2440 | 19 | | 2.742 | |
| 2480 | 39 | | 2.477 | |

Note :

1. The PSD measured results in plot is already including the actual values of loss for the attenuator and cable combination.

▣ 1M Bit/s (37 Byte) Test Plots

Power Spectral Density (Low-CH 0)



Power Spectral Density (Mid-CH 19)





Power Spectral Density (High-CH 39)





9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS

Test Result : please refer to the plot below.

In order to simplify the report, attached plots were only the worst case channel and data rate.

[BAND EDGE]

| Frequency (MHz) | Mode | Channel No. | Position | Test Result | |
|--------------------|------------------|-------------|----------|------------------------|----------------|
| | | | | Measured Level (dB) | Limit (dBc) |
| 2402 | 1M Bit/s 37 Byte | 0 | Lower | 60.209 | 20 |
| 2480 | | 39 | Upper | 61.693 | 20 |

1M Bit/s (37 Byte) Test Plots -BandEdge

Low-CH 0



High-CH 39




[CONDUCTED SPURIOUS EMISSIONS]


1M Bit/s 37 Byte

☐ Test Plots


30 MHz ~ 1 GHz




1 GHz ~ 3 GHz




3 GHz ~ 5 GHz




5 GHz ~ 7 GHz




7 GHz ~ 9 GHz




9 GHz ~ 11 GHz




11 GHz ~ 13 GHz




13 GHz ~ 15 GHz




15 GHz ~ 17 GHz




17 GHz ~ 19 GHz



19 GHz ~ 21 GHz



21 GHz ~ 23 GHz



23 GHz ~ 25 GHz



Note :

Limit : -18.49 dBm

9.6 RADIATED SPURIOUS EMISSIONS

Frequency Range : 9 kHz – 30MHz

| Frequency | Measured Value | A.F+C.L-A.G+D.F | Ant. POL | Total | Limit | Margin |
|-------------------------|----------------|-----------------|----------|--------------|--------------|--------|
| MHz | dB μ V/m | dB/m | (H/V) | dB μ V/m | dB μ V/m | dB |
| No Critical peaks found | | | | | | |

Note:

1. The Measured Level of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor = 40log (specific distance / test distance) (dB)
3. Limit line = specific Limits (dB μ V) + Distance extrapolation factor

Frequency Range : Below 1 GHz

| Frequency | Measured Value | A.F+C.L | Ant. POL | Total | Limit | Margin |
|-------------------------|----------------|---------|----------|--------------|--------------|--------|
| MHz | dB μ V/m | dB/m | (H/V) | dB μ V/m | dB μ V/m | dB |
| No Critical peaks found | | | | | | |

Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

Frequency Range : Above 1 GHz

Mode : 1M Bit/s (37 Byte)

Operation Mode: CH Low

| Frequency | Measured Value | A.F+C.L-A.G+D.F | Ant. Pol. | Total | Limit | Margin | Measurement Type |
|-----------|----------------|-----------------|-----------|----------------|----------------|--------|------------------|
| [MHz] | [dB μ V] | [dB/m] | [H/V] | [dB μ V/m] | [dB μ V/m] | [dB] | |
| 4804 | 46.66 | 3.74 | V | 50.40 | 73.98 | 23.58 | PK |
| 4804 | 39.71 | 3.74 | V | 43.45 | 53.98 | 10.53 | AV |
| 7206 | 38.02 | 11.83 | V | 49.85 | 73.98 | 24.13 | PK |
| 7206 | 26.12 | 11.83 | V | 37.95 | 53.98 | 16.03 | AV |
| 4804 | 46.32 | 3.74 | H | 50.06 | 73.98 | 23.92 | PK |
| 4804 | 39.41 | 3.74 | H | 43.15 | 53.98 | 10.83 | AV |
| 7206 | 38.12 | 11.83 | H | 49.95 | 73.98 | 24.03 | PK |
| 7206 | 26.23 | 11.83 | H | 38.06 | 53.98 | 15.92 | AV |

Operation Mode: CH Mid

| Frequency | Measured Value | A.F+C.L-A.G+D.F | Ant. Pol. | Total | Limit | Margin | Measurement Type |
|-----------|----------------|-----------------|-----------|----------------|----------------|--------|------------------|
| [MHz] | [dB μ V] | [dB/m] | [H/V] | [dB μ V/m] | [dB μ V/m] | [dB] | |
| 4880 | 46.30 | 3.87 | V | 50.17 | 73.98 | 23.81 | PK |
| 4880 | 39.80 | 3.87 | V | 43.67 | 53.98 | 10.31 | AV |
| 7320 | 37.64 | 12.16 | V | 49.80 | 73.98 | 24.18 | PK |
| 7320 | 25.32 | 12.16 | V | 37.48 | 53.98 | 16.50 | AV |
| 4880 | 46.02 | 3.87 | H | 49.89 | 73.98 | 24.09 | PK |
| 4880 | 38.85 | 3.87 | H | 42.72 | 53.98 | 11.26 | AV |
| 7320 | 37.73 | 12.16 | H | 49.89 | 73.98 | 24.09 | PK |
| 7320 | 25.41 | 12.16 | H | 37.57 | 53.98 | 16.41 | AV |




Operation Mode: CH High


| Frequency | Measured Value | A.F+C.L-A.G+D.F | Ant. Pol. | Total | Limit | Margin | Measurement Type |
|-----------|----------------|-----------------|-----------|----------------|----------------|--------|------------------|
| [MHz] | [dB μ V] | [dB/m] | [H/V] | [dB μ V/m] | [dB μ V/m] | [dB] | |
| 4960 | 46.91 | 4.28 | V | 51.19 | 73.98 | 22.79 | PK |
| 4960 | 39.74 | 4.28 | V | 44.02 | 53.98 | 9.96 | AV |
| 7440 | 38.15 | 12.27 | V | 50.42 | 73.98 | 23.56 | PK |
| 7440 | 26.21 | 12.27 | V | 38.48 | 53.98 | 15.50 | AV |
| 4960 | 46.71 | 4.28 | H | 50.99 | 73.98 | 22.99 | PK |
| 4960 | 39.51 | 4.28 | H | 43.79 | 53.98 | 10.19 | AV |
| 7440 | 38.30 | 12.27 | H | 50.57 | 73.98 | 23.41 | PK |
| 7440 | 26.27 | 12.27 | H | 38.54 | 53.98 | 15.44 | AV |

1M Bit/s 37 Byte Test Plots

Radiated Spurious Emissions plot – Average Result (Ch.39 2nd Harmonic, Z-V)



Radiated Spurious Emissions plot – Peak Result (Ch.39 2nd Harmonic, Z-V)



Note:

Plot of worst case are only reported.

9.7 RADIATED RESTRICTED BAND EDGES


Mode : 1 MBit/s (37 Byte)

| | |
|---------------------|---------------------|
| Operating Frequency | 2402 MHz & 2480 MHz |
| Channel No. | 0 & 39 |


| Frequency | Measured Level | Duty Cycle Factor | AF+CL+DF | Ant. Pol. | Total | Limit | Margin | Measurement Type |
|-----------|----------------|-------------------|----------|-----------|----------------|----------------|--------|------------------|
| [MHz] | [dB μ V] | [dB] | [dB/m] | [H/V] | [dB μ V/m] | [dB μ V/m] | [dB] | |
| 2390.0 | 46.90 | 0.00 | 2.76 | H | 49.66 | 73.98 | 24.32 | PK |
| 2390.0 | 34.62 | 1.77 | 2.76 | H | 39.15 | 53.98 | 14.83 | AV |
| 2390.0 | 46.75 | 0.00 | 2.76 | V | 49.51 | 73.98 | 24.47 | PK |
| 2390.0 | 34.57 | 1.77 | 2.76 | V | 39.10 | 53.98 | 14.88 | AV |
| 2483.5 | 50.27 | 0.00 | 2.86 | H | 53.13 | 73.98 | 20.85 | PK |
| 2483.5 | 36.36 | 1.77 | 2.86 | H | 40.99 | 53.98 | 12.99 | AV |
| 2483.5 | 48.24 | 0.00 | 2.86 | V | 51.10 | 73.98 | 22.88 | PK |
| 2483.5 | 35.81 | 1.77 | 2.86 | V | 40.44 | 53.98 | 13.54 | AV |

1M Bit/s (37 Byte) Test Plots

Radiated Restricted Band Edges plot – Average Result (Ch.39, X-H)



Radiated Restricted Band Edges plot – Peak Result (Ch.39, X-H)



Note:

Plot of worst case are only reported.

9.8 RECEIVER SPURIOUS EMISSIONS

Frequency Range : Below 1 GHz

| Frequency | Measured Value | A.F+C.L-A.G+D.F | Ant. POL | Total | Limit | Margin |
|-------------------------|----------------|-----------------|----------|--------------|--------------|--------|
| MHz | dB μ V/m | dB/m | (H/V) | dB μ V/m | dB μ V/m | dB |
| No Critical peaks found | | | | | | |

Note:

- Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

Frequency Range : Above 1 GHz

| Frequency | Measured Value | A.F+C.L | Ant. POL | Total | Limit | Margin |
|-------------------------|----------------|---------|----------|--------------|--------------|--------|
| MHz | dB μ V/m | dB/m | (H/V) | dB μ V/m | dB μ V/m | dB |
| No Critical peaks found | | | | | | |

10. LIST OF TEST EQUIPMENT

Conducted Test

| Equipment | Model | Manufacturer | Serial No. | Due to Calibration | Calibration Interval |
|--|----------|-----------------|------------|--------------------|----------------------|
| LISN | ENV216 | Rohde & Schwarz | 102245 | 08/22/2023 | Annual |
| EMI Test Receiver | ESR | Rohde & Schwarz | 101910 | 05/26/2024 | Annual |
| Temperature Chamber | SU-642 | ESPEC | 0093008124 | 02/22/2024 | Annual |
| Signal Analyzer | N9030A | Agilent | MY49432108 | 03/02/2024 | Annual |
| Power Measurement Set | OSP 120 | Rohde & Schwarz | 101231 | 06/09/2024 | Annual |
| Power Meter | N1911A | Agilent | MY45100523 | 03/06/2024 | Annual |
| Power Sensor | N1921A | Agilent | MY57820067 | 03/06/2024 | Annual |
| Directional Coupler | 87300B | Agilent | 3116A03621 | 11/02/2023 | Annual |
| Power Splitter | 11667B | Hewlett Packard | 10545 | 02/06/2024 | Annual |
| DC Power Supply | E3632A | HP | KR75303243 | 04/24/2024 | Annual |
| Attenuator(10 dB) (DC-26.5 GHz) | 8493C | HP | 08285 | 06/02/2024 | Annual |
| Attenuator(20 dB) | 18N-20dB | Rohde & Schwarz | 8 | 03/08/2024 | Annual |
| Software | EMC32 | Rohde & Schwarz | N/A | N/A | N/A |
| FCC WLAN&BT&BLE Conducted Test Software v3.0 | N/A | HCT CO., LTD. | N/A | N/A | N/A |
| Bluetooth Tester | CBT | Rohde & Schwarz | 100808 | 02/16/2024 | Annual |

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

Radiated Test

| Equipment | Model | Manufacturer | Serial No. | Due to Calibration | Calibration Interval |
|-------------------------------------|------------------------------------|------------------------|-------------|--------------------|----------------------|
| Controller(Antenna mast) | CO3000 | Innco system | CO3000-4p | N/A | N/A |
| Antenna Position Tower | MA4640/800-XP-EP | Innco system | N/A | N/A | N/A |
| EM1000 / Controller | EM1000 | Audix | 060520 | N/A | N/A |
| Turn Table | N/A | Audix | N/A | N/A | N/A |
| Amp & Filter Bank Switch Controller | FBSM-01B | TNM system | TM19050002 | N/A | N/A |
| Loop Antenna | FMZB 1513 | Rohde & Schwarz | 1513-333 | 03/17/2024 | Biennial |
| Hybrid Antenna | VULB 9168 | Schwarzbeck | 9168-0895 | 08/16/2024 | Biennial |
| Horn Antenna | BBHA 9120D | Schwarzbeck | 9120D-1300 | 01/18/2024 | Biennial |
| Horn Antenna | BBHA 9120D | Schwarzbeck | 9120D-2296 | 05/18/2024 | Biennial |
| Horn Antenna(15 GHz ~ 40 GHz) | BBHA9170 | Schwarzbeck | BBHA9170342 | 09/29/2024 | Biennial |
| Spectrum Analyzer | FSV(10 Hz ~ 40 GHz) | Rohde & Schwarz | 101055 | 05/12/2024 | Annual |
| Band Reject Filter | WRCJV2400/2483.5-2370/2520-60/12SS | Wainwright Instruments | 2 | 01/05/2024 | Annual |
| Band Reject Filter | WRCJV12-4900-5100-5900-6100-50SS | Wainwright Instruments | 5 | 06/12/2024 | Annual |
| Band Reject Filter | WRCJV12-4900-5100-5900-6100-50SS | Wainwright Instruments | 6 | 06/12/2024 | Annual |
| High Pass Filter(7 GHz ~ 18 GHz) | WHKX10-7150-8000-18000-50SS | Wainwright Instruments | 1 | 03/02/2024 | Annual |
| Power Amplifier | CBL18265035 | CERNEK | 22966 | 12/01/2023 | Annual |
| Power Amplifier | CBL26405040 | CERNEK | 25956 | 03/02/2024 | Annual |
| Bluetooth Tester | TC-3000C | TESCOM | 3000C000175 | 03/28/2024 | Annual |
| HPF(3~18GHz)+LNA1(1~18GHz) | FMSR-05B | TNM system | F6 | 01/17/2024 | Annual |
| ATT(10dB) + LNA1(1~18GHz) | FMSR -05B | TNM system | None | 01/17/2024 | Annual |
| ATT(3dB) + LNA1(1~18GHz) | FMSR -05B | TNM system | None | 01/17/2024 | Annual |
| LNA1(1~18GHz) | FMSR -05B | TNM system | 25540 | 01/17/2024 | Annual |
| HPF(7~18GHz)+LNA2(6~18GHz) | FMSR -05B | TNM system | 28550 | 01/17/2024 | Annual |
| Thru(30MHz ~ 18GHz) | FMSR -05B | TNM system | None | 01/17/2024 | Annual |

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
3. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5(Version : 2017).



11. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

| No. | Description |
|-----|---------------------|
| 1 | HCT-RF-2306-FI007-P |