



TEST REPORT

FCC MPE Test for MTVWBE01GLX
Certification

APPLICANT
LG Electronics Inc.

REPORT NO.
HCT-RF-2103-FI009-R1

DATE OF ISSUE
July 26, 2021

Tested by
Jin Gwan Lee

Technical Manager
Jong Seok Lee

Accredited by KOLAS, Republic of KOREA

HCT CO., LTD.
BongJai Huh
BongJai Huh / CEO

HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401



TEST REPORT

FCC MPE Test for
MTVWBE01GLX

REPORT NO.

HCT-RF-2103-FI009-R1

DATE OF ISSUE

July 26, 2021

Additional Model

-

Applicant

LG Electronics Inc.

222, LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 451-713, Korea

**Eut Type
Model Name**

RF Module
MTVWBE01GLX

FCC ID

BEJMTVWBE01GLX

Date of Receipt

March 15, 2021

Frequency range

2 402 MHz ~ 2 480 MHz (Bluetooth)
2 412 MHz ~ 2 462 MHz (WLAN)
5 180 MHz ~ 5 825 MHz (UNII)

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test results were applied only to the test methods required by the standard.

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	March 15, 2021	Initial Release
1	July 26, 2021	Page 5, 6, 7, 8 Typo.

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance

This laboratory is not accredited for the test results marked *.

The above Test Report is the accredited test result by (KS Q) ISO/IEC 17025 AND KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA.(HCT Accreditation No.: KT197)

* The report shall not be reproduced except in full(only partly) without approval of the laboratory.

RF Exposure Statement

1. Limit

According to § 1.1310, § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	f/1500	30
1500 - 100.000.....	1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

2. Maximum Permissible Exposure Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = Power input to antenna

G = Power gain to the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

3. RESULTS

3-1. Bluetooth

Average output Power at antenna input terminal	8.50	dBm
Average output Power at antenna input terminal	7.08	mW
Prediction distance	20.00	cm
Prediction frequency	2402 – 2480	MHz
Antenna Gain(typical)	1.510	dBi
Antenna Gain(numeric)	1.416	-
Power density at prediction frequency(S)	0.0020	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

2.1091

EIRP	10.01	(dBm)
ERP	7.86	(dBm)
ERP	0.006	(W)
ERP Limit	3.00	(W)
MARGIN	26.91	(dB)

3-1. BT LE

Average output Power at antenna input terminal	8.50	dBm
Average output Power at antenna input terminal	7.08	mW
Prediction distance	20.00	cm
Prediction frequency	2402 – 2480	MHz
Antenna Gain(typical)	1.510	dBi
Antenna Gain(numeric)	1.416	-
Power density at prediction frequency(S)	0.0020	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

2.1091

EIRP	10.01	(dBm)
ERP	7.86	(dBm)
ERP	0.006	(W)
ERP Limit	3.00	(W)
MARGIN	26.91	(dB)

3-1. DTS

Average output Power at antenna input terminal	18.50	dBm
Average output Power at antenna input terminal	70.79	mW
Prediction distance	20.00	cm
Prediction frequency	2412 – 2472	MHz
Antenna Gain(typical)	2.630	dBi
Antenna Gain(numeric)	1.832	-
Power density at prediction frequency(S)	0.0258	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

2.1091

EIRP	21.13	(dBm)
ERP	18.98	(dBm)
ERP	0.079	(W)
ERP Limit	3.00	(W)
MARGIN	15.79	(dB)

3-1. UNII

Average output Power at antenna input terminal	22.00	dBm
Average output Power at antenna input terminal	158.49	mW
Prediction distance	20.00	cm
Prediction frequency	5180 – 5825	MHz
Antenna Gain(typical)	4.590	dBi
Antenna Gain(numeric)	2.877	-
Power density at prediction frequency(S)	0.0907	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

2.1091

EIRP	26.59	(dBm)
ERP	24.44	(dBm)
ERP	0.278	(W)
ERP Limit	3.00	(W)
MARGIN	10.33	(dB)

Worst Case: Simultaneous MPE 20cm is

$$5G\ WLAN\ (0.0907) + BT\ (0.0020) = 0.0927 < 1$$