

## FCC 2.1093 SAR Test Report

for

**LG Electronics Inc.**

**222, LG-roJinwi-myeon, Pyeongtaek-Si, Gyeonggi-Do,  
451-713, Korea**

**Product Name : Notebook Computer**  
**Model Name : (1)13U70P (2)13UD70P**  
**(3)13UB70P (4)13UG70P**  
**Brand : LG**  
**FCC ID : BEJNT-13U70P**

**Prepared by: : AUDIX Technology Corporation,  
EMC Department**



The test report is based on a single evaluation of one sample of the above-mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab logo.  
The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

## TABLE OF CONTENTS

Description	Page
TEST REPORT.....	3
<b>1. REVISION RECORD OF TEST REPORT .....</b>	<b>4</b>
<b>2. SUMMARY OF TEST RESULTS .....</b>	<b>5</b>
<b>3. GENERAL INFORMATION .....</b>	<b>7</b>
3.1. Description of Application .....	7
3.2. Description of EUT .....	8
3.3. Reference Test Guidance.....	9
3.4. Antenna Information .....	9
3.5. EUT Specifications Assessed in Current Report.....	10
3.6. Description of Key Components .....	12
3.7. Test Environment .....	14
3.8. Description of Test Facility .....	14
3.9. Measurement Uncertainty .....	15
<b>4. MEASUREMENT EQUIPMENTLIST.....</b>	<b>17</b>
<b>5. SAR MEASUREMENT SYSTEM .....</b>	<b>17</b>
5.1. Definition of Specific Absorption Rate (SAR).....	18
5.2. SPEAG DASY System.....	18
5.3. SAR System Verification .....	26
5.4. SAR Measurement Procedure .....	32
<b>6. SAR MEASUREMENT EVALUATION .....</b>	<b>35</b>
6.1. EUT Configuration and Setting.....	35
6.2. EUT Testing Position .....	36
6.3. Tissue Calibration Result .....	37
6.4. SAR Exposure Limits.....	38
6.5. Conducted Power Measurement.....	39
6.6. SAR Test Result .....	45

APPENDIX A TEST DATA AND PLOTS

APPENDIX B TESTPHOTOGRAPHS

## TEST REPORT

Applicant : LG Electronics Inc.  
Manufacturer : LG Electronics Inc.  
Factory : DIGITEK (CHONGQING) LIMITED  
EUT Description  
(1) Product : Notebook Computer  
(2) Model : (1)13U70P (2)13UD70P (3)13UB70P (4)13UG70P  
(3) Brand : LG  
(4) Power Supply: DC 19V, 3.42A

Applicable Standards:

Title 47 FCC CFR, Part 2(§2.1093)  
IEEE 1528-2013

**Audix Technology Corp.** tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.

**Audix Technology Corp.** does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens and samples.

Date of Report: 2020. 10. 12

Reviewed by:



(Sabrina Wang/Administrator)

Approved by:



(Johnny Hsueh/Section Manager)

## 1. REVISION RECORD OF TEST REPORT

Edition No	Issued Date	Revision Summary	Report Number
0	2020. 10. 12	Original Report	EM-SR200013

## 2. SUMMARY OF TEST RESULTS

### Test SKU: SKU #1 with AWAN Antenna

Highest Simultaneous Transmission SAR	Reported Body SAR <sub>1g</sub>
WLAN 2.4G ANT Main+ WLAN 2.4G ANT AUX	0.365 (W/kg)
WLAN 2.4G ANT AUX+ BT ANT AUX	0.169 (W/kg)
WLAN 5G ANT AUX+ BT ANT AUX	1.316 (W/kg)
WLAN 5G ANT Main+ WLAN 5 ANT AUX	2.030 (W/kg) <sup>NOTE 3</sup>
WLAN 5G ANT Main+ WLAN 5 ANT AUX + BT ANT AUX	2.046 (W/kg) <sup>NOTE 3</sup>
Note: 1. The SAR limit (SAR <sub>1g</sub> 1.6 W/kg) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093). 2. It is calculated from scale SAR. 3. It is larger than the limit 1.6(W/kg), SAR test exclusion is determined by the SAR to peak location separation ratio.	

Simultaneous Transmission SAR	Frequency	Measured Body SAR <sub>1g</sub> (SAR <sub>1</sub> +SAR <sub>2</sub> ) <sup>Note2</sup>	Ri (mm) Note2	SPLSR <sup>Note2</sup>
WLAN 5G ANT Main+ WLAN 5G ANT AUX	5580MHz	1.90 (W/kg) <sup>Note 2</sup>	112.03	0.02
	5745MHz	1.84 (W/kg) <sup>Note 2</sup>	113.20	0.02
	5785MHz	1.63 (W/kg) <sup>Note 2</sup>	83.20	0.03
	5825MHz	1.60 (W/kg) <sup>Note 2</sup>	82.41	0.02

Note: 1. The SAR limit (SAR<sub>1g</sub> 1.6 W/kg) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093).  
 2.  $SPLSR = (SAR_1 + SAR_2)^{1.5} / Ri$  must  $\leq 0.04$

<p>Find distance of maxima</p> <ul style="list-style-type: none"> <li>Maxima and position w.r.t. Grid Reference Point   associated 1g averages</li> <li>Zoom Scan (D:\SAR Test Data\2020 09\CIM2009193-1 AWAN\dasy\P3 802.11a CH116 5580MHz ant1.da53... Max. 1 at (114.60, -26.60, -0.13) mm   0.79 W/kg</li> <li>Zoom Scan (D:\SAR Test Data\2020 09\CIM2009193-1 AWAN\dasy\P4 802.11a CH116 5580MHz ant2.da53... Max. 2 at (112.20, 85.40, 0.04) mm   1.11 W/kg</li> <li>Distances and Separation Ratios</li> <li>Max. 1 - Max. 2   Distance [mm]: 112.03 / Separation ratio [W/kg/mm]: 0.02</li> </ul>	<p>Find distance of maxima</p> <ul style="list-style-type: none"> <li>Maxima and position w.r.t. Grid Reference Point   associated 1g averages</li> <li>Zoom Scan (D:\SAR Test Data\2020 09\CIM2009193-1 AWAN\dasy\P5 802.11a CH149 5745MHz ant1.da53... Max. 1 at (114.20, -27.00, -0.17) mm   0.66 W/kg</li> <li>Zoom Scan (D:\SAR Test Data\2020 09\CIM2009193-1 AWAN\dasy\P6 802.11a CH149 5745MHz ant2.da53... Max. 2 at (113.40, 86.20, -0.01) mm   1.18 W/kg</li> <li>Distances and Separation Ratios</li> <li>Max. 1 - Max. 2   Distance [mm]: 113.20 / Separation ratio [W/kg/mm]: 0.02</li> </ul>
<p>Find distance of maxima</p> <ul style="list-style-type: none"> <li>Maxima and position w.r.t. Grid Reference Point   associated 1g averages</li> <li>Zoom Scan (D:\SAR Test Data\2020 09\CIM2009193-1 AWAN\dasy\P7 802.11a CH157 5785MHz ant1.da53... Max. 1 at (113.80, 2.20, -0.27) mm   0.58 W/kg</li> <li>Zoom Scan (D:\SAR Test Data\2020 09\CIM2009193-1 AWAN\dasy\P8 802.11a CH157 5785MHz ant2.da53... Max. 2 at (113.40, 85.40, -0.02) mm   1.05 W/kg</li> <li>Distances and Separation Ratios</li> <li>Max. 1 - Max. 2   Distance [mm]: 83.20 / Separation ratio [W/kg/mm]: 0.03</li> </ul>	<p>Find distance of maxima</p> <ul style="list-style-type: none"> <li>Maxima and position w.r.t. Grid Reference Point   associated 1g averages</li> <li>Zoom Scan (D:\SAR Test Data\2020 09\CIM2009193-1 AWAN\dasy\P9 802.11a CH165 5825MHz ant2.da53... Max. 1 at (112.60, 85.40, -0.05) mm   0.98 W/kg</li> <li>Zoom Scan (D:\SAR Test Data\2020 09\CIM2009193-1 AWAN\dasy\P19 802.11a CH165 5825MHz ant1.da53... Max. 2 at (113.00, 3.00, -0.29) mm   0.62 W/kg</li> <li>Distances and Separation Ratios</li> <li>Max. 1 - Max. 2   Distance [mm]: 82.41 / Separation ratio [W/kg/mm]: 0.02</li> </ul>

**Test SKU: SKU #2 with Speed Antenna**

Highest Simultaneous Transmission SAR	Reported Body SAR <sub>1g</sub>
WLAN 2.4G ANT Main+ WLAN 2.4G ANT AUX	0.651 (W/kg)
WLAN 2.4G ANT AUX+ BT ANT AUX	0.363 (W/kg)
WLAN 5G ANT AUX+ BT ANT AUX	1.430 (W/kg)
WLAN 5G ANT Main+ WLAN 5 ANT AUX	2.460 (W/kg) <sup>NOTE 3</sup>
WLAN 5G ANT Main+ WLAN 5 ANT AUX + BT ANT AUX	2.480 (W/kg) <sup>NOTE 3</sup>

Note: 1. The SAR limit (SAR<sub>1g</sub> 1.6 W/kg) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093).  
 2. It is calculated from scale SAR.  
 3. It is larger than the limit 1.6(W/kg), SAR test exclusion is determined by the SAR to peak location separation ratio.

Simultaneous Transmission SAR	Frequency	Measured Body SAR <sub>1g</sub> (SAR <sub>1</sub> +SAR <sub>2</sub> ) <sup>Note2</sup>	Ri (mm) <sup>Note2</sup>	SPLSR <sup>Note2</sup>
WLAN 5G ANT Main+ WLAN 5G ANT AUX	5580MHz	2.05 (W/kg) <sup>Note 2</sup>	100.41	0.03
	5745MHz	2.23 (W/kg) <sup>Note 2</sup>	109.40	0.03
	5785MHz	1.70 (W/kg) <sup>Note 2</sup>	110.62	0.02

Note: 1. The SAR limit (SAR<sub>1g</sub> 1.6 W/kg) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093).  
 2. SPLSR=(SAR<sub>1</sub>+SAR<sub>2</sub>)<sup>1.5</sup>/Ri must ≤0.04

The screenshots show the following data for each frequency:

- 5580MHz:** Max. 1 at (119.00, -13.00, -0.02) mm: 0.85 W/kg; Max. 2 at (117.40, 87.40, -0.01) mm: 1.20 W/kg; Distance: 100.41 mm; Separation ratio: 0.03.
- 5745MHz:** Max. 1 at (118.00, -23.00, -0.02) mm: 0.96 W/kg; Max. 2 at (117.40, 86.40, -0.01) mm: 1.28 W/kg; Distance: 109.40 mm; Separation ratio: 0.03.
- 5785MHz:** Max. 1 at (114.00, -30.00, -0.02) mm: 0.48 W/kg; Max. 2 at (116.00, 79.80, 0.02) mm: 1.22 W/kg; Distance: 110.62 mm; Separation ratio: 0.02.

### 3. GENERAL INFORMATION

#### 3.1. Description of Application

Applicant	LG Electronics Inc. 222, LG-roJinwi-myeon, Pyeongtaek-Si, Gyeonggi-Do, 451-713, Korea
Manufacturer	LG Electronics Inc. 222, LG-roJinwi-myeon, Pyeongtaek-Si, Gyeonggi-Do, 451-713, Korea
Factory	DIGITEK (CHONGQING) LIMITED B01, Section C, Airport Function Zone, LiangluCuntan Free Trade Port Area, Yubei District, Chongqing City, China.
Product	Notebook Computer
Model	(1)13U70P (2)13UD70P (3)13UB70P (4)13UG70P The difference between all models is different in the sales customers. <b>Note: The 4 models [(1)13U70P (2)13UD70P (3)13UB70P (4)13UG70P] are for FCC ID application, and only 1 model (13U70P) is for ISED application.</b>
Brand	LG

### 3.2. Description of EUT

Test Model	13U70P		
Serial Number	N/A		
Power Rating	DC 19V, 3.42A		
Hardware Version	2.1		
Software Version	XY (X, Y can be 0 to 9 for different SW version not influence RF parameter)		
RF Features	WLAN: 802.11 a/b/g/n/ac/ax Bluetooth: BT and BLE (BT 5.0)		
Transmit Type	<b>2.4 GHz</b>		
	802.11b		1T1R
	802.11g		1T1R
	802.11n-HT20		2T2R
	802.11n-HT40		2T2R
	802.11ax-HE20		2T2R
	802.11ax-HE40		2T2R
	BT/BLE		1T1R
	<b>UNII Bands</b>		
	802.11a		1T1R
	802.11n-HT20/802.11ac-VHT20/802.11ax-HE20		2T2R
	802.11n-HT40/802.11ac-VHT40/802.11ax-HE40		2T2R
	802.11ac-VHT80/802.11ax-HE80		2T2R
	802.11ac-VHT160/802.11ax-HE160		2T2R
Test Sample	<b>Sample No.</b>	<b>Test Item</b>	<b>Firmware</b>
	-01	SAR	N/A
	-02	SAR	N/A
Sample Status	Mass production		
Date of Receipt	2020. 09. 16		
Date of Test	2020. 09. 23 ~ 25		
Interface Ports of EUT	<ul style="list-style-type: none"> <li>• One Micro SD Card Slot</li> <li>• One Earphone Port</li> <li>• Two USB 3.0 Ports</li> <li>• One USB Type C Port</li> <li>• One HDMI Port</li> <li>• One DC Input Port</li> </ul>		
Accessories Supplied	<ul style="list-style-type: none"> <li>• AC Adapter</li> <li>• LAN Gender</li> </ul>		



### 3.3. Reference Test Guidance

KDB 447498 D01 General RF Exposure Guidance v06  
 KDB 865664 D01 SAR Measurement 100MHz to 6GHz v01r04  
 KDB 616217 D04 SAR for laptop and tablets v01r02

### 3.4. Antenna Information

No.	Antenna Part Number	Manufacture	Antenna Type	Frequency (MHz)	Max Gain (dBi)
1.	1415-07YW000 (Main)	AWAN	PIFA Type	2400~2500	-0.66
				5150-5350	-1.31
				5470-5725	1.59
				5725-5850	1.59
	1415-07YW000 (AUX)	AWAN	PIFA Type	2400~2500	-0.15
				5150-5350	-0.21
				5470-5725	0.24
				5725-5850	-1.01
2.	F.0G.LS-6017-001-00 (Main)	Speed	PIFA Type	2400~2500	1.60
				5150-5350	-1.26
				5470-5725	2.54
				5725-5850	2.54
	F.0G.LS-6017-0041-00 (AUX)	Speed	PIFA Type	2400~2500	1.51
				5150-5350	0.78
				5470-5725	0.24
				5725-5850	-2.36

### 3.5. EUT Specifications Assessed in Current Report

2.4GHz		
Mode	Fundamental Range (MHz)	Channel Number
802.11b	2412-2472	13
802.11g		13
802.11n-HT20		13
802.11n-HT40	2422-2462	9
Bluetooth	2402-2480	79
BLE	2402-2480	40

5GHz			
Mode	Band	Fundamental Range (MHz)	Channel Number
802.11a	NII-I	5180-5240	4
	NII-2A	5260-5320	4
	NII-2C	5500-5700	11
	NII-III	5745-5825	5
802.11n-HT20/ 802.11ac-VHT20 802.11ax-HE20	NII-I	5180-5240	4
	NII-2A	5260-5320	4
	NII-2C	5500-5720	12
	NII-III	5745-5825	5
802.11n-HT40/ 802.11ac-VHT40 802.11ax-HE40	NII-I	5190-5230	2
	NII-2A	5270-5310	2
	NII-2C	5510-5710	6
	NII-III	5755-5795	2
802.11ac-VHT80 802.11ax-HE80	NII-I	5210	1
	NII-2A	5290	1
	NII-2C	5530-5690	3
	NII-III	5775	1
802.11ac-VHT160 /802.11ax-HE160	NII-I	5250	1
	NII-2A		
	NII-2C	5570	1

Remark: Band NII-2A and NII-2C (DFS Function, Slave/no In service monitor, no Ad-Hoc mode)

Mode	Modulation	Data Rate (Mbps)
802.11b	DSSS (DBPSK/DQPSK/CCK)	Up to 11
802.11g	OFDM (BPSK/QPSK/16QAM/64QAM)	Up to 54
802.11a	OFDM (BPSK/QPSK/16QAM/64QAM)	Up to 54
802.11n-HT20	OFDM (BPSK/QPSK/16QAM/64QAM)	Up to 144.4
802.11n-HT40		Up to 300
802.11ac-VHT20	OFDM (BPSK/QPSK/16QAM/64QAM/256QAM)	Up to 173.3
802.11ac-VHT40		Up to 400
802.11ac-VHT80		Up to 866.7
802.11ac-VHT160		Up to 1733.3
802.11ax-HE20	OFDMA (BPSK/ QPSK/ 16QAM/ 64QAM/ 256QAM/1024QAM)	Up to 287
802.11ax-HE40		Up to 574
802.11ax-HE80		Up to 1201
802.11ax-HE160		Up to 2402
Bluetooth	FHSS (GFSK, $\pi/4$ DQPSK, 8-DPSK)	1/2/3
BLE	GFSK (1M, 2M, PHY Coded S8, PHY Coded S2)	2

### 3.6. Description of Key Components

#### 3.6.1. For the All Component Lists

Item	Supplier	Model / Type	Character
System	Microsoft	Win10 Home	---
		Win10 Pro	---
Main Board	LG	GT13R MB	Manufacturer: #1 HannstarBoardTech(Jiang Yin)Corp.,Ltd. #2 Changshu Gold Circuit Technoligy Co. Ltd.
WLAN SUB Board	LG	GT13R IO BD	Manufacturer: #1 HannstarBoardTech(Jiang Yin)Corp.,Ltd. #2 Changshu Gold Circuit Technoligy Co. Ltd.
CPU (Socket: BGA (FP6))	AMD	RYZEN 7 4700U	2.0GHz,
		RYZEN 5 4500U	2.3GHz
		RYZEN 3 4300U	2.7GHz
13" LCD Panel	LG Display	LP133WF7-SPA1	Resolution: 1920 x 1080, 60Hz FHD IPS
Memory (RAM)	SK Hynix	---	16Gb x16 DDR4-3200 (on Board)
		---	8Gb x16 DDR4-3200 (on Board)
	Samsung	---	16Gb x16 DDR4-3200 (on Board)
		---	8Gb x16 DDR4-3200 (on Board)
Storage (SSD)	SK hynix	---	512GB-NVMe
		---	256GB-NVMe
	Samsung	---	512GB-NVMe
		---	256GB-NVMe
		---	128GB-SATA
Battery Pack	LG	LBU5228E	DC 11.25V, 51Wh, Typ 4540mAh
Web Camera	Chicony	CKFIH3421005110LH	With two microphones
WLAN Combo Card	Intel	AX200NGW	WLAN and BT, 2x2 FCC ID: PD9AX200NG IC: 1000M-AX200NG NCC ID: CCAH19LP0850T0
WLAN Combo Antenna	AWAN	AYP6Y-200017	PIFA Type, Main: Black
			PIFA Type, Aux: Gray
	Speed	F.0G.LS-6017-001-00	PIFA Type, Main: Black
	F.0G.LS-6017-0041-00	PIFA Type, Aux: Gray	
LAN Gender (Type C to LAN)	MEC	80-5946-111	(White) 10/100Megabit Ethernet
		80-5946-101	(Black) 10/100 Megabit Ethernet
	MEC	80-5946-200	(White) 10/100/1000 Megabit Ethernet
		80-5946-210	(Black) 10/100/1000 Megabit Ethernet
	Type C to LAN: Shielded, Undetached, 0.12m		
AC Adapter	Chicony	A18-065N3A	I/P: AC 100-240V, 50-60Hz, 1.7A, O/P: DC 19V,3.42A, 65W
	DC Power Cord: Non-Shielded, Undetached, 1.8m, bonded a ferrite core AC Power Cord: Non-Shielded, Detached, 1m (3C)		

Remark: For more detailed features description, please refer to the manufacturer's specifications or the user manual.

3.6.2. The EUT collocates with following worst components, which are used to establish a basic configuration of system during test:

SKU		1	2
System	Microsoft, Win10 Home	V	V
Main Board	LG, GT13R MB	V	V
WLAN SUB Board	LG, GT13R IO BD	V	V
CPU	AMD, RYZEN 7 4700U	V	
	AMD, RYZEN 3 4300U		V
13" LCD Panel	LG Display, LP133WF7-SPA1	V	V
Memory (RAM)	16GB	V	
	8GB		V
Storage (SSD)	512GB	V	
	256GB		V
Battery Pack	LG, LBU5228E	V	V
Web Camera	Chicony, CKFIH3421005110LH	V	V
WLAN Combo Card	Intel, AX200NGW	V	V
WLAN Combo Antenna	AWAN, PIFA Type, Main/Aux	V	
	Speed, PIFA Type, Main/Aux		V
AC Adapter	Chicony, A18-065N3A	V	V
Type C	Type C to LAN Gender	V	V
	MEC, 80-5946-111	V	
	MEC, 80-5946-200		V

### 3.7. Test Environment

Ambient conditions in the laboratory:

Item	Require	Actual
Temperature (°C)	18-25	22 ±2
Humidity (%RH)	30-70	48 ± 2

### 3.8. Description of Test Facility

Name of Test Firm	Audix Technology Corporation / EMC Department No. 53-11, Dingfu, Linkou Dist., New Taipei City 244, Taiwan Tel: +886-2-26092133 Fax: +886-2-26099303 Website : www.audixtech.com Contact e-mail: attemc_report@audixtech.com
Accreditations	The laboratory is accredited by following organizations under ISO/IEC 17025:2017 (1) NVLAP(USA) NVLAP Lab Code 200077-0 (2) TAF(Taiwan) No. 1724
Test Facilities	FCC OET Designation Number under APEC MRA by NCC is : TW1724 (1) SAR Room

### 3.9. Measurement Uncertainty

<b>DASY5 Uncertainty</b>								
According to IEEE 1528-2013 and IEC 62209-1/2016 (0.3 - 6 GHz range)								
Error Description	Uncert. value	Prob. Dist.	Div.	(ci) 1g	(ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(vi) $v_{eff}$
<b>Measurement System</b>								
Probe Calibration	±6.0%	N	1	1	1	±6.0%	±6.0%	∞
Axial Isotropy	±4.7%	R	$\sqrt{3}$	0.7	0.7	±1.9%	±1.9%	∞
Hemispherical Isotropy	±9.6%	R	$\sqrt{3}$	0.7	0.7	±3.9%	±3.9%	∞
Boundary Effects	±1.0%	R	$\sqrt{3}$	1	1	±0.6%	±0.6%	∞
Linearity	±4.7%	R	$\sqrt{3}$	1	1	±2.7%	±2.7%	∞
System Detection Limits	±1.0%	R	$\sqrt{3}$	1	1	±0.6%	±0.6%	∞
Readout Electronics	±0.3%	N	1	1	1	±0.3%	±0.3%	∞
Response Time	±0.8%	R	$\sqrt{3}$	1	1	±0.5%	±0.5%	∞
Integration Time	±2.6%	R	$\sqrt{3}$	1	1	±1.5%	±1.5%	∞
RF Ambient Noise	±3.0%	R	$\sqrt{3}$	1	1	±1.7%	±1.7%	∞
RF Ambient Reflections	±3.0%	R	$\sqrt{3}$	1	1	±1.7%	±1.7%	∞
Probe Positioner	±0.4%	R	$\sqrt{3}$	1	1	±0.2%	±0.2%	∞
Probe Positioning	±2.9%	R	$\sqrt{3}$	1	1	±1.7%	±1.7%	∞
Max. SAR Eval.	±1.0%	R	$\sqrt{3}$	1	1	±0.6%	±0.6%	∞
<b>Test Sample Related</b>								
Device Positioning	±2.9%	N	1	1	1	±2.9%	±2.9%	145
Device Holder	±3.6%	N	1	1	1	±3.6%	±3.6%	5
Power Drift	±5.0%	R	$\sqrt{3}$	1	1	±2.9%	±2.9%	∞
<b>Phantom and Setup</b>								
Phantom Uncertainty	±4.0%	R	$\sqrt{3}$	1	1	±2.3%	±2.3%	∞
Liquid Conductivity (target)	±5.0%	R	$\sqrt{3}$	0.64	0.43	±1.8%	±1.2%	∞
Liquid Conductivity (meas.)	±2.5%	N	1	0.64	0.43	±1.6%	±1.1%	∞
Liquid Permittivity (target)	±5.0%	R	$\sqrt{3}$	0.6	0.49	±1.7%	±1.4%	∞
Liquid Permittivity (meas.)	±2.5%	N	1	0.6	0.49	±1.5%	±1.2%	∞
<b>Combined Std. Uncertainty</b>						±11%	±10.8%	387
<b>Expanded STD Uncertainty</b>						±22%	±21.5%	

<b>DASY5 Uncertainty</b> According to IEC 62209-2/2010 (30 MHz - 6 GHz range)								
Error Description	Uncert. value	Prob. Dist.	Div.	(ci) 1g	(ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(vi) v <sub>eff</sub>
<b>Measurement System</b>								
Probe Calibration	±6.0%	N	1	1	1	±6.0%	±6.0%	∞
Axial Isotropy	±4.7%	R	√3	0.7	0.7	±1.9%	±1.9%	∞
Hemispherical Isotropy	±9.6%	R	√3	0.7	0.7	±3.9%	±3.9%	∞
Boundary Effects	±1.0%	R	√3	1	1	±0.6%	±0.6%	∞
Linearity	±4.7%	R	√3	1	1	±2.7%	±2.7%	∞
System Detection Limits	±1.0%	R	√3	1	1	±0.6%	±0.6%	∞
Readout Electronic	±0.3%	N	1	1	1	±0.3%	±0.3%	∞
Response Time	±0.8%	R	√3	1	1	±0.5%	±0.5%	∞
Integration Time	±2.6%	R	√3	1	1	±1.5%	±1.5%	∞
RF Ambient Noise	±3.0%	R	√3	1	1	±1.7%	±1.7%	∞
RF Ambient Reflections	±3.0%	R	√3	1	1	±1.7%	±1.7%	∞
Probe Positioner	±0.4%	R	√3	1	1	±0.2%	±0.2%	∞
Probe Positioning	±2.9%	R	√3	1	1	±1.7%	±1.7%	∞
Modulation Response	±2.5%	R	√3	1	1	±1.45 %	±1.45 %	∞
Post-processing	±3.8%	R	√3	1	1	±2.2%	±2.2%	∞
<b>Test Sample Related</b>								
Test Sample Positioning	±2.9%	N	1	1	1	±2.9%	±2.9%	145
Device Holder	±3.6%	N	1	1	1	±3.6%	±3.6%	5
Power Drift	±5.0%	R	√3	1	1	±2.9%	±2.9%	∞
Power Scaling	±0.0%	R	√3	1	1	±0.0%	±0.0%	∞
<b>Phantom and Setup</b>								
Phantom Uncertainty	±4.5%	R	√3	1	1	±2.4%	±2.4%	∞
SAR correction	±1.9%	R	√3	1	0.84	±1.9%	±1.9%	∞
Liquid Conductivity (target)	±5.0%	R	√3	0.64	0.43	±1.8%	±1.2%	∞
Liquid Conductivity (mea.)DAK	±2.5%	R	√3	0.64	0.43	±0.9%	±0.6%	∞
Liquid Permittivity (target)	±5.0%	R	√3	0.6	0.49	±1.7%	±1.4%	∞
Liquid Permittivity(me.)DAK	±2.5%	R	√3	0.6	0.49	±0.9%	±0.7%	∞
<b>Combined Std. Uncertainty</b>						±11.0%	±10.9%	387
<b>Expanded STD Uncertainty</b>						±22.1%	±21.8%	



#### 4. MEASUREMENT EQUIPMENT LIST

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Stäubli Robot TX90 XL	Stäubli	TX90	F12/5K9SA1/A101	N/A	N/A
2.	Controller	SPEAG	CS8c	N/A	N/A	N/A
3.	SAM Twin Phantom	SPEAG	N/A	1706	N/A	N/A
4.	ELI5 Phantom	SPEAG	N/A	1170	N/A	N/A
5.	Device Holder	SPEAG	N/A	N/A	N/A	N/A
6.	SAR Software	SPEAG	DASY52	V.52.8.8.1222	N/A	N/A
7.	Data Acquisition Electronic	SPEAG	DAE4	679	2020.05.06	1 Year
8.	E-Field Probe	SPEAG	EX3DV4	7375	2019.12.18	1 Year
9.	ENA Network Analyzer	Agilent	E5071C-285	MY46215502	2020.04.09	1 Year
10.	Signal Generator	Aglient	N5181A	MY50143917	2020.09.15	1 Year
11.	Power Meter	Aglient	ML2487A	MY52180007	2020.09.17	1 Year
12.	Power Sensor	Aglient	N8481H	MY52080006	2020.09.17	1 Year
13.	Dipole Antenna	SPEAG	D2450V2	888	2018.09.27	3 Years
14.	Dipole Antenna	SPEAG	D5GHzV2	1124	2018.09.27	3 Years

## 5. SAR MEASUREMENT SYSTEM

### 5.1. Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)


SAR measurement can be related to the electrical field in the tissue by

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

### 5.2. SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.



**Fig-3.1 DASY6 System Setup**


### 5.2.1. Robot

The DASY6 system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:


- High precision (repeatability  $\pm 0.035$  mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)




### 5.2.2. Probes


Model	Ex3DV4	
Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz to 6 GHz Linearity: $\pm 0.2$ dB	
Directivity	$\pm 0.3$ dB in HSL (rotation around probe axis) $\pm 0.5$ dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 $\mu$ W/g to 100 mW/g Linearity: $\pm 0.2$ dB (noise: typically $< 1$ $\mu$ W/g)	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

### 5.2.3. Data Acquisition Electronics (DAE)


Model	DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY4/5 embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	$< 5\mu$ V (with auto zero)	
Input Bias Current	$< 50$ fA	
Dimensions	60 x 60 x 68 mm	


### 5.2.4. Phantom

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Vinyl ester, glass fiber reinforced (VE-GF)	
Shell Thickness	$2 \pm 0.2$ mm ( $6 \pm 0.2$ mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	


Model	ELI	
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Material	Vinyl ester, glass fiber reinforced (VE-GF)	
Shell Thickness	$2.0 \pm 0.2$ mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	

### 5.2.5. Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	


Model	Laptop Extensions Kit	
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
Material	POM, Acrylic glass, Foam	

### 5.2.6. Reference Dipole

Model	System Validation Dipoles	
Construction	Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	750 MHz to 5800 MHz	
Return Loss	> 20 dB	
Power Capability	> 100 W (f < 1GHz), > 40 W (f > 1GHz)	

### 5.2.7. Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-5.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528 and FCC OET 65 Supplement C Appendix C. For the body tissue simulating liquids, the dielectric properties are defined in FCC OET 65 Supplement C Appendix C. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using an Agilent 85070D Dielectric Probe Kit and an Agilent Network Analyzer.

**Table-5.1 Targets of Tissue Simulating Liquid**

Target Frequency [MHz]	Target Permittivity ( $\epsilon_r$ )	Range of $\pm 5\%$	Target Conductivity $\sigma$ [s/m]	Range of $\pm 5\%$
For Head				
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53
For Body				
750	55.5	52.7 ~ 58.3	0.96	0.91 ~ 1.01
835	55.2	52.4 ~ 58.0	0.97	0.92 ~ 1.02
900	55.0	52.3 ~ 57.8	1.05	1.00 ~ 1.10
1450	54.0	51.3 ~ 56.7	1.30	1.24 ~ 1.37
1640	53.8	51.1 ~ 56.5	1.40	1.33 ~ 1.47
1750	53.4	50.7 ~ 56.1	1.49	1.42 ~ 1.56
1800	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
1900	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2000	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2300	52.9	50.3 ~ 55.5	1.81	1.72 ~ 1.90
2450	52.7	50.1 ~ 55.3	1.95	1.85 ~ 2.05
2600	52.5	49.9 ~ 55.1	2.16	2.05 ~ 2.27
3500	51.3	48.7 ~ 53.9	3.31	3.14 ~ 3.48
5200	49.0	46.6 ~ 51.5	5.30	5.04 ~ 5.57
5300	48.9	46.5 ~ 51.3	5.42	5.15 ~ 5.69
5500	48.6	46.2 ~ 51.0	5.65	5.37 ~ 5.93
5600	48.5	46.1 ~ 50.9	5.77	5.48 ~ 6.06
5800	48.2	45.8 ~ 50.6	6.00	5.70 ~ 6.30




**Table-5.2 Recipes of Tissue Simulating Liquid**

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
For Head								
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.5	17.3
For Body								
B750	0.2	-	0.2	0.8	48.8	-	50.0	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B900	0.2	-	0.2	0.9	48.2	-	50.5	-
B1450	-	34.0	-	0.3	-	-	65.7	-
B1640	-	32.5	-	0.3	-	-	67.2	-
B1750	-	31.0	-	0.2	-	-	68.8	-
B1800	-	29.5	-	0.4	-	-	70.1	-
B1900	-	29.5	-	0.3	-	-	70.2	-
B2000	-	30.0	-	0.2	-	-	69.8	-
B2300	-	31.0	-	0.1	-	-	68.9	-
B2450	-	31.4	-	0.1	-	-	68.5	-
B2600	-	31.8	-	0.1	-	-	68.1	-
B3500	-	28.8	-	0.1	-	-	71.1	-
B5G	-	-	-	-	-	10.7	78.6	10.7

### 5.3. SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The power meter PM1 measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter PM2 is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter PM2.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

5.3.1. SAR System Verification Result

System Performance Check at WLAN				
Dipole Kit: D2450V2(Body)				
Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Liquid Temp. [°C]
2450MHz	Reference result	51.5	24.2	N/A
	± 10% window	46.350 to 56.650	21.780 to 26.620	
	2020. 09. 25	51.2	23.2	22.6
Note: All SAR values are normalized to 1W forward power.				

System Performance Check at WLAN				
Dipole Kit: D5GHzV2 (Body)				
Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Liquid Temp. [°C]
5300MHz	Reference result	80.6	23.3	N/A
	± 10% window	72.540 to 88.660	20.970 to 25.630	
	2020. 09. 23	81.2	23.2	22.4
Note: All SAR values are normalized to 1W forward power.				

System Performance Check at WLAN				
Dipole Kit: D5GHzV2 (Body)				
Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Liquid Temp. [°C]
5600MHz	Reference result	85.3	24.4	N/A
	± 10% window	76.770 to 93.830	21.960 to 26.840	
	2020. 09. 24	80.8	23.7	22.4
Note: All SAR values are normalized to 1W forward power.				

System Performance Check at WLAN				
Dipole Kit: D5GHzV2 (Body)				
Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Liquid Temp. [°C]
5800MHz	Reference result	79.6	22.8	N/A
	± 10% window	71.640 to 87.560	20.520 to 25.080	
	2020. 09. 24	75.3	23.3	22.4
Note: All SAR values are normalized to 1W forward power.				

### 5.3.2. SAR System Check Data

Page 1 of 1

Date: 9/25/2020

Test Laboratory: Audix\_SAR Lab

#### System Check\_H2450

DUT: D2450V2 - SN888


Communication System: UID 0, CW (0); Frequency: 2450 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.787$  S/m;  $\epsilon_r = 39.614$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN7375; ConvF(7.69, 7.69, 7.69) @ 2450 MHz; Calibrated: 12/18/2019
- Sensor-Surface: 2mm (Mechanical Surface Detection), Sensor-Surface: 4mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 5/6/2020
- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1170
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

**P=250mW/Area Scan (8x8x1):** Measurement grid:  $dx=10$ mm,  $dy=10$ mm  
Maximum value of SAR (measured) = 19.5 W/kg

**P=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm  
Reference Value = 73.39 V/m; Power Drift = 0.20 dB  
Peak SAR (extrapolated) = 32.2 W/kg  
**SAR(1 g) = 12.8 W/kg; SAR(10 g) = 5.81 W/kg**  
Smallest distance from peaks to all points 3 dB below = 8 mm  
Ratio of SAR at M2 to SAR at M1 = 43.5%  
Maximum value of SAR (measured) = 14.2 W/kg



Date: 9/23/2020

Test Laboratory: Audix\_SAR Lab

**System Check\_H5300**

DUT: D5GHzV2 - SN1124


Communication System: UID 0, CW (0); Frequency: 5300 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5300$  MHz;  $\sigma = 4.93$  S/m;  $\epsilon_r = 35.93$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN7375; ConvF(5.25, 5.25, 5.25) @ 5300 MHz; Calibrated: 12/18/2019
- Sensor-Surface: 2mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 5/6/2020
- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1170
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

**P=100mW/Area Scan (7x7x1):** Measurement grid:  $dx=10$ mm,  $dy=10$ mm  
Maximum value of SAR (measured) = 15.0 W/kg

**P=100mW/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:  $dx=4$ mm,  $dy=4$ mm,  $dz=2.5$ mm  
Reference Value = 28.44 V/m; Power Drift = 0.29 dB  
Peak SAR (extrapolated) = 55.2 W/kg  
**SAR(1 g) = 8.12 W/kg; SAR(10 g) = 2.32 W/kg**  
Smallest distance from peaks to all points 3 dB below = 7.1 mm  
Ratio of SAR at M2 to SAR at M1 = 44.7%  
Maximum value of SAR (measured) = 17.9 W/kg



Date: 9/24/2020

Test Laboratory: Audix\_SAR Lab

**System Check\_B5600**

DUT: D5GHzV2 - SN1124


Communication System: UID 0, CW (0); Frequency: 5600 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5600$  MHz;  $\sigma = 5.29$  S/m;  $\epsilon_r = 35.399$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN7375; ConvF(4.63, 4.63, 4.63) @ 5600 MHz; Calibrated: 12/18/2019
- Sensor-Surface: 2mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 5/6/2020
- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1170
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

**P=100mW/Area Scan (7x7x1):** Measurement grid:  $dx=10$ mm,  $dy=10$ mm  
Maximum value of SAR (measured) = 11.3 W/kg

**P=100mW/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:  $dx=4$ mm,  $dy=4$ mm,  $dz=2.5$ mm  
Reference Value = 28.48 V/m; Power Drift = 0.13 dB  
Peak SAR (extrapolated) = 92.4 W/kg  
**SAR(1 g) = 8.08 W/kg; SAR(10 g) = 2.37 W/kg**  
Smallest distance from peaks to all points 3 dB below = 7.7 mm  
Ratio of SAR at M2 to SAR at M1 = 46.4%  
Maximum value of SAR (measured) = 16.9 W/kg



Date: 9/24/2020

Test Laboratory: Audix\_SAR Lab

**System Check\_B5800**

DUT: D5GHzV2 - SN1124


Communication System: UID 0, CW (0); Frequency: 5800 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5800$  MHz;  $\sigma = 5.475$  S/m;  $\epsilon_r = 35.053$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN7375; ConvF(4.79, 4.79, 4.79) @ 5800 MHz; Calibrated: 12/18/2019
- Sensor-Surface: 2mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 5/6/2020
- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1170
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

**Area Scan (7x7x1):** Measurement grid:  $dx=10$ mm,  $dy=10$ mm  
Maximum value of SAR (measured) = 10.8 W/kg

**Zoom Scan (7x7x9)/Cube 0:** Measurement grid:  $dx=4$ mm,  $dy=4$ mm,  $dz=2.5$ mm  
Reference Value = 25.91 V/m; Power Drift = 0.82 dB  
Peak SAR (extrapolated) = 82.9 W/kg  
**SAR(1 g) = 7.53 W/kg; SAR(10 g) = 2.33 W/kg**  
Smallest distance from peaks to all points 3 dB below = 5.7 mm  
Ratio of SAR at M2 to SAR at M1 = 47.2%  
Maximum value of SAR (measured) = 15.8 W/kg



## 5.4. SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- (a) Make EUT to transmit maximum output power
- (b) Measure conducted output power through RF cable
- (c) Place the EUT in the specific position of phantom
- (d) Perform SAR testing steps on the DASY system
- (e) Record the SAR value

### 5.4.1. Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664D01v01r03, the resolution for Area and Zoom scan is specified in the table below.

Items	<= 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan ( $\Delta x, \Delta y$ )	<= 15mm	<= 12mm	<= 12mm	<= 10mm	<= 10mm
Zoom Scan ( $\Delta x, \Delta y$ )	<= 8mm	<= 5mm	<= 5mm	<= 4mm	<= 4mm
Zoom Scan ( $\Delta z$ )	<= 5mm	<= 5mm	<= 4mm	<= 3mm	<= 2mm
Zoom Scan Volume	>= 30mm	>= 30mm	>= 28mm	>= 25mm	>= 22mm

Note:

When zoom scan is required and report SAR is <= 1.4 W/kg, the zoom scan resolution of  $\Delta x / \Delta y$  (2-3GHz: <= 8 mm, 3-4GHz: <= 7 mm, 4-6GHz: <= 5 mm) may be applied.



#### 5.4.2. Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

#### 5.4.3. Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

#### 5.4.4. Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values form the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

#### 5.4.5. SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

## 6. SAR MEASUREMENT EVALUATION

### 6.1. EUT Configuration and Setting

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 D01 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is  $> 1.2$  W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required.

A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance  $\leq 5$  mm to support compliance.

## 6.2. EUT Testing Position

The SAR testing required mode is listed as below.

Antenna	Front Face	Rear Face	Top Side	Bottom Side	Left Side	Right Side
WLAN		√				

Note: Per KDB 447498 D01

- a) For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:  

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR, where
  - $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- b) For 100 MHz to 6 GHz and test separation distances  $> 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following (also illustrated in Appendix B):<sup>32</sup>
  - 1)  $\{[\text{Power allowed at numeric threshold for 50 mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]\}$  mW, for 100 MHz to 1500 MHz
  - 2)  $\{[\text{Power allowed at numeric threshold for 50 mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot 10]\}$  mW, for  $> 1500$  MHz and  $\leq 6$  GHz

SAR test exclusion table distance is  $> 50$ mm @ Left Side (AUX to edge)

Frequency (GHz)	In Step 1 threshold Power (mW)	Distance between antenna and user (mm)	SAR Exclusion Threshold Power @ $> 50$ mm (mW)	EUT tune-up maximum power (mW)	SAR test
2.442	95.9883	124	835.9883	112.202	No
5.260	65.4031	124	805.4031	100.000	No
5.580	63.5001	124	803.5001	100.000	No
5.745	62.5815	124	802.5815	100.000	No
5.785	62.3648	124	802.3648	100.000	No
5.825	62.1503	124	802.1503	100.000	No

SAR test exclusion table distance is  $> 50$ mm @ Right Side (Main to edge)

Frequency (GHz)	In Step 1 threshold Power (mW)	Distance between antenna and user (mm)	SAR Exclusion Threshold Power @ $> 50$ mm (mW)	EUT tune-up maximum power (mW)	SAR test
2.442	95.9883	65	245.9883	112.202	No
5.260	65.4031	65	215.4031	100.000	No
5.580	63.5001	65	213.5001	100.000	No
5.745	62.5815	65	212.5815	102.329	No
5.785	62.3648	65	212.3648	102.329	No
5.825	62.1503	65	212.1503	100.000	No

### 6.3. Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using Agilent Dielectric Probe Kit and Agilent E5071C Vector Network Analyzer.

Body Tissue Simulate Measurement					
Frequency [MHz]	Description	Dielectric Parameters			Liquid Temp. [°C]
		$\epsilon_r$		$\sigma$ [s/m]	
2450MHz	Reference result	39.2		1.8	N/A
	$\pm 5\%$ window	37.240	to 41.160	1.710 to 1.890	
	2020. 09. 25	40.205		1.777	22.6

Body Tissue Simulate Measurement					
Frequency [MHz]	Description	Dielectric Parameters			Liquid Temp. [°C]
		$\epsilon_r$		$\sigma$ [s/m]	
5300MHz	Reference result	35.99		4.66	N/A
	$\pm 5\%$ window	34.191	to 37.790	4.427 to 4.893	
	2020. 09. 23	37.007		4.687	22.4

Body Tissue Simulate Measurement					
Frequency [MHz]	Description	Dielectric Parameters			Liquid Temp. [°C]
		$\epsilon_r$		$\sigma$ [s/m]	
5600MHz	Reference result	35.53		5.07	N/A
	$\pm 5\%$ window	33.754	to 37.307	4.817 to 5.324	
	2020. 09. 24	36.135		5.188	22.4

Body Tissue Simulate Measurement					
Frequency [MHz]	Description	Dielectric Parameters			Liquid Temp. [°C]
		$\epsilon_r$		$\sigma$ [s/m]	
5800MHz	Reference result	35.30		5.27	N/A
	$\pm 5\%$ window	33.535	to 37.065	5.007 to 5.534	
	2020. 09. 24	35.687		5.422	22.4

## 6.4. SAR Exposure Limits

SAR assessments have been made in line with the requirements of IEEE-1528, FCC Supplement C, and comply with ANSI/IEEE C95.1-1992 “Uncontrolled Environments” limits. These limits apply to a location which is deemed as “Uncontrolled Environment” which can be described as a situation where the general public may be exposed to an RF source with no prior knowledge or control over their exposure.

Limits for General Population/Uncontrolled Exposure (W/kg)

Type Exposure	Uncontrolled Environment Limit
Spatial Peak SAR (1g cube tissue for brain or body)	1.60 W/kg
Spatial Average SAR (whole body)	0.08 W/kg
Spatial Peak SAR (10g for hands, feet, ankles and wrist)	4.00 W/kg

## 6.5. Conducted Power Measurement

### Note:

1. Per KDB 447498 D01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.  
Scale Factor = tune-up limit power (mW)/EUT Conducted power (mW), where tune-up limit is the maximum rated power among all production units.  
Scale SAR(W/kg)= Measured SAR(W/kg)\* Scaling Factor
2. Per KDB 447498 D01, for each exposure position, if the highest output channel reported SAR  $\leq 0.8$ W/kg, other channels SAR testing is not necessary.
3. Per KDB 248227 D01, for OFDM transmission configuration in the 2.4G and 5G bands. An initial test configuration is determined by the highest maximum output power including tune-up tolerance. When multiple transmission modes(802.11 a/g/n/ac/ax) have same maximum power, largest channel bandwidth, lowest order modulation and lowest data rate, lowest order 802.11 mode is selected.( i.e. a, g, n, ac then ax)
4. Per KDB 248227 D01, when the highest reported SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for that subsequent test configuration.
5. Per KDB 248227 D01, U-NII-1 and U-NII-2A bands have the same specified maximum output and tolerance; SAR is measured for U-NII-2A band first. Adjusted SAR of U-NII-2A band is  $\leq 1.2$  W/kg, SAR is not required for U-NII-1 band.
6. Per KDB 248227 D01, When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested.
7. Per KDB 248227 D01, when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.

6.5.1. For WLAN Function

Type of Network	Channel	Frequency (MHz)	Output Power (dBm)						SAR Test
			Chain A (AUX)			Chain B (Main)			
			Average Power	Tune-Up Limit	Scale Factor	Average Power	Tune-Up Limit	Scale Factor	
802.11b	CH 1	2412	19.87	20.0	---	19.40	19.5	---	No <sup>NOTE2</sup>
	CH 7	2442	21.12	21.5	1.09	21.25	21.5	1.06	Yes
	CH 11	2462	19.22	20.0	---	19.37	19.5	---	No <sup>NOTE2</sup>
	CH 12	2467	17.97	18.0	---	17.14	17.5	---	
	CH 13	2472	15.19	15.5	---	14.74	15.0	---	
802.11g	CH 1	2412	17.09	17.5	---	17.09	17.5	---	No <sup>NOTE6</sup>
	CH 7	2442	20.61	21.0	---	20.52	21.0	---	
	CH 11	2462	15.27	15.5	---	15.04	15.5	---	
	CH 12	2467	13.65	14.0	---	13.58	14.0	---	
	CH 13	2472	11.81	12.0	---	11.74	12.0	---	
802.11n-HT20	CH 1	2412	15.72	16.0	---	15.71	16.0	---	No <sup>NOTE4-3</sup>
	CH 7	2442	18.89	19.0	---	19.11	19.5	---	
	CH 11	2462	14.37	14.5	---	14.41	14.5	---	
	CH 12	2467	12.15	12.5	---	12.24	12.5	---	
	CH 13	2472	8.56	9.0	---	7.44	7.5	---	
802.11n-HT40	CH 3	2422	15.12	15.5	---	13.76	14.0	---	No <sup>NOTE4-3</sup>
	CH 7	2442	15.17	15.5	---	14.58	15.0	---	
	CH 9	2452	14.62	15.0	---	15.03	15.5	---	
	CH 10	2457	7.92	8.0	---	7.96	8.0	---	
	CH 11	2462	10.26	10.5	---	10.28	10.5	---	
802.11ax-HE20	CH 1	2412	15.84	16.0	---	15.89	16.0	---	No <sup>NOTE4-3</sup>
	CH 7	2442	16.37	16.5	---	16.82	17.0	---	
	CH 11	2462	14.15	14.5	---	14.41	14.5	---	
	CH 12	2467	11.86	12.0	---	10.50	11.0	---	
	CH 13	2472	7.97	8.0	---	8.45	8.5	---	
802.11ax-HE40	CH 3	2422	15.94	16.0	---	13.97	14.0	---	No <sup>NOTE4-3</sup>
	CH 7	2442	15.19	15.5	---	14.95	15.0	---	
	CH 9	2452	14.56	15.0	---	14.71	15.0	---	
	CH 10	2457	7.32	7.5	---	7.50	8.0	---	
	CH 11	2462	10.08	10.5	---	12.91	13.0	---	

Type of Network	RU Configuration	Frequency (MHz)	Output Power (dBm)						SAR Test
			Chain A (AUX)			Chain B (Main)			
			Average Power	Tune-Up Limit	Scale Factor	Average Power	Tune-Up Limit	Scale Factor	
802.11ax-HE20	26/0	2412	17.36	17.5	---	17.21	17.5	---	No <sup>NOTE4-3</sup>
	52/37		16.58	17.0	---	16.62	17.0	---	
	106/53		16.06	16.5	---	15.92	16.0	---	
	26/8	2472	0.24	0.50	---	0.47	0.50	---	
	52/40		3.11	3.5	---	3.07	3.5	---	
	106/54		6.12	6.5	---	6.23	6.5	---	
802.11ax-HE40	242/61	2422	15.96	16.0	---	14.63	15.0	---	
	242/62	2467	8.56	9.0	---	7.57	8.0	---	



Type of Network	Channel	Frequency (MHz)	Output Power (dBm)						SAR Test	
			Chain 0 (AUX)			Chain1 (Main)				
			Average Power	Tune-Up Limit	Scale Factor	Average Power	Tune-Up Limit	Scale Factor		
802.11a	NII-I	CH 36	5180	19.01	19.5	---	19.95	20.0	---	No <sup>NOTE5·3</sup>
		CH 40	5200	21.04	21.5	---	21.01	21.5	---	
		CH 48	5240	21.11	21.5	1.09	21.00	21.5	1.12	
	NII-2A	CH 52	5260	21.01	21.5	---	21.06	21.5	---	No <sup>NOTE2</sup>
		CH 60	5300	20.98	21.0	---	21.00	21.5	---	
		CH 64	5320	18.39	18.5	---	18.41	18.5	---	
	NII-2C	CH 100	5500	19.03	19.5	1.11	19.06	19.5	1.11	Yes
		CH 116	5580	21.09	21.5	1.10	21.05	21.5	1.11	
		CH 140	5700	18.82	19.0	1.04	19.39	19.5	1.03	
	NII-III	CH 149	5745	21.08	21.5	1.10	21.10	21.5	1.10	
CH 157		5785	21.02	21.5	1.12	21.03	21.5	1.11		
CH 165		5825	21.01	21.5	1.12	20.95	21.0	1.01		
802.11n-HT20	NII-I	CH 36	5180	18.21	18.5	---	18.15	18.5	---	No <sup>NOTE4·3</sup>
		CH 40	5200	19.50	20.0	---	19.51	20.0	---	
		CH 48	5240	19.69	20.0	---	19.43	19.5	---	
	NII-2A	CH 52	5260	19.67	20.0	---	19.48	19.5	---	
		CH 60	5300	19.64	20.0	---	19.62	20.0	---	
		CH 64	5320	16.79	17.0	---	16.74	17.0	---	
	NII-2C	CH 100	5500	18.12	18.5	---	18.15	18.5	---	
		CH 116	5580	19.33	20.0	---	19.44	20.5	---	
		CH 140	5700	16.39	17.5	---	17.85	18.5	---	
	NII-III	CH 144	5720	18.89	19.0	---	18.79	19.0	---	
CH 149		5745	20.08	20.5	---	19.89	20.0	---		
CH 157		5785	20.19	20.5	---	20.07	20.5	---		
CH 165	5825	20.19	20.5	---	20.04	20.5	---			
802.11n-HT40	NII-I	CH 38	5190	17.41	17.5	---	17.43	17.5	---	No <sup>NOTE4·3</sup>
		CH 46	5230	19.23	19.5	---	19.18	20.0	---	
	NII-2A	CH 54	5270	18.87	19.0	---	18.89	19.0	---	
		CH 62	5310	14.40	14.5	---	14.81	15.0	---	
	NII-2C	CH 102	5510	17.41	18.0	---	17.35	18.0	---	
		CH 110	5550	20.35	20.5	---	20.23	20.5	---	
		CH 134	5670	18.68	19.0	---	19.25	19.5	---	
	NII-III	CH 142	5710	19.67	20.0	---	19.61	20.0	---	
CH 151		5755	20.14	20.5	---	19.50	20.0	---		
CH 159	5795	20.25	20.5	---	19.89	20.0	---			
802.11ac-VHT80	NII-I	CH 52	5210	17.37	17.5	---	17.31	17.5	---	No <sup>NOTE4·3</sup>
	NII-2A	CH 58	5290	15.94	16.0	---	15.81	16.0	---	
		CH 106	5530	17.67	18.0	---	17.82	18.0	---	
	NII-2C	CH 122	5610	18.86	19.0	---	18.96	19.0	---	
		CH 138	5690	19.85	20.0	---	19.92	20.0	---	
NII-III	CH 155	5775	18.53	18.5	---	18.70	19.5	---		
802.11ac-VHT160	NII-I/ NII-2A	CH 50	5250	13.28	13.5	---	13.48	13.5	---	No <sup>NOTE4·3</sup>
	NII-2C	CH 114	5570	13.33	13.5	---	14.97	14.5	---	

Type of Network	Channel	Frequency (MHz)	Output Power (dBm)						SAR Test	
			Chain 0 (AUX)			Chain1 (Main)				
			Average Power	Tune-Up Limit	Scale Factor	Average Power	Tune-Up Limit	Scale Factor		
802.11ax-HE20	NII-I	CH 36	5180	18.23	18.5	---	18.31	18.5	---	No <sup>NOTE4.3</sup>
		CH 40	5200	19.77	20.0	---	19.69	20.0	---	
		CH 48	5240	19.79	20.0	---	19.60	20.0	---	
	NII-2A	CH 52	5260	19.57	20.0	---	19.67	20.0	---	
		CH 60	5300	19.44	19.5	---	19.57	20.0	---	
		CH 64	5320	16.98	17.0	---	17.03	17.5	---	
	NII-2C	CH 100	5500	18.04	18.5	---	18.04	18.5	---	
		CH 116	5580	19.99	20.0	---	20.09	20.5	---	
		CH 140	5700	16.56	17.0	---	18.63	19.0	---	
	NII-III	CH 144	5720	18.80	19.0	---	18.82	19.0	---	
		CH 149	5745	20.08	20.5	---	20.00	20.0	---	
		CH 157	5785	20.19	20.5	---	20.06	20.5	---	
		CH 165	5825	19.98	20.0	---	20.04	20.5	---	
802.11ax-HE40	NII-I	CH 38	5190	17.33	17.5	---	17.35	17.5	---	No <sup>NOTE4.3</sup>
		CH 46	5230	19.13	19.5	---	18.95	19.0	---	
	NII-2A	CH 54	5270	18.77	19.0	---	18.71	19.0	---	
		CH 62	5310	15.07	15.5	---	15.15	15.5	---	
	NII-2C	CH 102	5510	17.38	18.0	---	17.93	18.0	---	
		CH 110	5550	20.10	20.5	---	20.13	20.5	---	
		CH 134	5670	18.02	18.5	---	18.44	18.5	---	
	NII-III	CH 142	5710	19.51	20.0	---	19.26	19.5	---	
CH 151		5755	19.45	19.5	---	19.25	19.5	---		
		CH 159	5795	19.88	20.0	---	19.78	20.0	---	
802.11ax-HE80	NII-I	CH 52	5210	17.20	17.5	---	17.14	17.5	---	No <sup>NOTE4.3</sup>
	NII-2A	CH 58	5290	14.95	15.0	---	14.88	15.0	---	
		CH 106	5530	17.60	18.0	---	17.72	18.0	---	
	NII-2C	CH 133	5610	18.09	18.5	---	18.45	18.5	---	
		CH 138	5690	19.88	20.0	---	20.02	20.5	---	
NII-III	CH 155	5775	17.74	18.0	---	17.73	18.0	---		
802.11ax-HE160	NII-I/ NII-2A	CH 50	5250	13.24	13.5	---	13.27	13.5	---	No <sup>NOTE4.3</sup>
	NII-2C	CH 114	5570	13.47	13.5	---	14.52	15.0	---	

Type of Network	Channel	Frequency (MHz)	RU Configuration	Output Power (dBm)						SAR Test	
				Chain 0			Chain 1				
				Average Power	Tune-Up Limit	Scale Factor	Average Power	Tune-Up Limit	Scale Factor		
802.11ax-HE20	NII-I	CH 36	5180	26/0	10.63	11.0	---	10.62	11.0	---	No <sup>NOTE4-3</sup>
				52/37	13.50	13.5	---	13.43	13.5	---	
				106/53	16.62	17.0	---	16.68	17.0	---	
	NII-2A	CH 64	5320	26/8	10.72	11.0	---	10.65	11.0	---	
				52/40	13.55	14.0	---	13.61	14.0	---	
				106/54	16.56	17.0	---	16.62	17.0	---	
	NII-2C	CH 100	5500	26/0	10.66	11.0	---	10.55	11.0	---	
				52/37	13.46	13.5	---	13.50	13.5	---	
				106/53	16.55	17.0	---	16.59	17.0	---	
		CH 140	5700	26/8	10.47	10.5	---	10.54	11.0	---	
				52/40	13.64	14.0	---	13.61	14.0	---	
				106/54	16.78	17.0	---	16.74	17.0	---	
	NII-III	CH 149	5745	26/0	14.23	14.5	---	13.83	14.0	---	
				52/37	16.81	17.0	---	16.61	17.0	---	
				106/53	19.86	20.0	---	19.61	20.0	---	
CH 165		5825	26/8	14.77	15.0	---	15.00	15.0	---		
			52/40	17.36	17.5	---	17.22	17.5	---		
			106/54	19.82	20.0	---	19.75	20.0	---		
802.11ax-HE40	NII-I	CH 38	5190	242/61	18.05	18.5	---	18.11	18.5	---	No <sup>NOTE4-3</sup>
	NII-2A	CH 62	5310	242/62	17.21	17.5	---	16.98	17.0	---	
	NII-2C	CH 102	5510	242/61	18.51	19.0	---	18.84	19.0	---	
		CH 142	5710	242/62	18.69	19.0	---	19.27	20.0	---	
	NII-III	CH 151	5755	242/61	19.85	20.0	---	19.70	20.0	---	
		CH 159	5795	242/62	19.77	20.0	---	19.74	20.0	---	
802.11ax-HE80	NII-I	CH 52	5210	484/65	16.95	17.0	---	16.61	17.0	---	No <sup>NOTE4-3</sup>
	NII-2A	CH 58	5290	484/66	16.51	17.0	---	16.55	17.0	---	
	NII-2C	CH 106	5530	484/65	17.16	17.5	---	17.55	18.0	---	
		CH 133	5610	484/66	18.63	19.0	---	19.05	19.5	---	
	NII-III	CH 155	5775	484/65	19.05	19.5	---	19.13	19.5	---	
				484/66	19.02	19.5	---	19.33	19.5	---	
802.11ax-HE160	NII-2A	CH 50	5250	996/67	16.88	17.0	---	16.68	17.0	---	No <sup>NOTE4-3</sup>
				996/S67	15.71	16.0	---	15.27	15.5	---	
	NII-2C	CH 114	5570	996/67	16.27	17.5	---	16.68	17.0	---	
				996/S67	18.43	18.5	---	18.98	19.0	---	

### 6.5.2. For BT Function

Type of Network	Channel	Frequency (MHz)	Max Output Power (dBm)	Tune-Up Limit	Scale Factor	SAR Test
Bluetooth-GFSK	CH 0	2402	9.48	10.0	---	No
	CH 39	2441	9.76	10.0	1.06	Yes
	CH 78	2480	9.96	10.0	---	No
Bluetooth-8-DPSK	CH 0	2402	8.88	10.0	---	No
	CH 39	2441	9.11	10.0	---	No
	CH 78	2480	9.39	10.0	---	No
BLE (1M)	CH 37	2402	7.76	8.0	---	No
	CH 17	2440	7.85	8.0	---	No
	CH 39	2480	7.93	8.0	---	No
BLE (2M)	CH 37	2402	7.75	8.0	---	No
	CH 17	2440	7.87	8.0	---	No
	CH 39	2480	7.94	8.0	---	No
BLE (PHY Coded S2)	CH 37	2402	7.74	8.0	---	No
	CH 17	2440	7.84	8.0	---	No
	CH 39	2480	7.92	8.0	---	No
BLE (PHY Coded S8)	CH 37	2402	7.73	8.0	---	No
	CH 17	2440	7.83	8.0	---	No
	CH 39	2480	7.91	8.0	---	No

### 6.6. SAR Test Result

Test Date	2020. 09. 25	Temp./Hum.	23°C/48%
Test Voltage	AC 120V, 60Hz (with AC Adapter)	Tested by	Sean Wang
Test SKU	SKU #1 with AWAN Antenna		

Liquid Temperature : 22.6°C							Depth of Liquid: > 15cm			
<b>Test Mode: 2.4GHz</b>										
Plot No.	Test Position: Body	Antenna Position	Separation Distance (cm)	Frequency	Conducted Power (dBm)	Maximum Tune-up (dBm)	SAR 1g (W/kg)	Scale Factor	Scale SAR	Limit (W/kg)
802.11b										
Antenna:Chain A (AUX)										
13	Rear	Fixed	0	2442	21.12	21.5	0.14	1.09	0.153	1.60
Antenna:Chain B (Main)										
12	Rear	Fixed	0	2442	21.25	21.5	0.200	1.06	0.212	1.60

Liquid Temperature : 22.6°C							Depth of Liquid: > 15cm			
<b>Test Mode: BT-GFSK</b>										
Plot No.	Test Position: Body	Antenna Position	Separation Distance (cm)	Frequency	Conducted Power (dBm)	Maximum Tune-up (dBm)	SAR 1g (W/kg)	Scale Factor	Scale SAR	Limit (W/kg)
Antenna:Chain A (AUX)										
14	Rear	Fixed	0	2441	9.76	10.0	0.015	1.06	0.016	1.60

Test Date	2020. 09. 23 ~ 24	Temp./Hum.	23°C/48%
Test Voltage	AC 120V, 60Hz (with AC Adapter)	Tested by	Sean Wang
Test SKU	SKU #1 with AWAN Antenna		

Liquid Temperature : 23.0°C							Depth of Liquid: > 15cm				
<b>Test Mode: 5GHz</b>											
Plot No.	Test Position: Body	Antenna Position	Separation Distance (cm)	Frequency	Conducted Power (dBm)	Maximum Tune-up (dBm)	SAR 1g (W/kg)	Scale Factor	Scale SAR	Limit (W/kg)	
802.11a (UNII Band II-2A)											
Antenna:Chain A (AUX)											
2	Rear	Fixed	0	5240	21.11	21.5	0.597	1.09	0.65	1.60	
Antenna:Chain B (Main)											
1	Rear	Fixed	0	5240	21.00	21.5	0.475	1.12	0.53	1.60	
802.11a (UNII Band II-2C)											
Antenna:Chain A (AUX)											
11	Rear	Fixed	0	5500	19.03	19.5	0.710	1.11	0.79	1.60	
4	Rear	Fixed	0	5580	21.09	21.5	<b>1.110</b>	1.10	1.22	1.60	
Antenna:Chain B (Main)											
10	Rear	Fixed	0	5500	19.06	19.5	0.414	1.11	0.46	1.60	
3	Rear	Fixed	0	5580	21.05	21.5	0.793	1.11	0.88	1.60	
802.11a (UNII Band III)											
Antenna:Chain A (AUX)											
6	Rear	Fixed	0	5745	21.08	21.5	<b>1.180</b>	1.10	<b>1.30</b>	1.60	
8	Rear	Fixed	0	5785	21.02	21.5	<b>1.050</b>	1.12	1.17	1.60	
9	Rear	Fixed	0	5825	21.01	21.5	<b>0.983</b>	1.12	1.10	1.60	
Antenna:Chain B (Main)											
5	Rear	Fixed	0	5745	21.10	21.5	0.663	1.10	0.73	1.60	
7	Rear	Fixed	0	5785	21.03	21.5	0.581	1.11	0.65	1.60	
19	Rear	Fixed	0	5825	20.95	21.0	0.622	1.01	0.63	1.60	

Test Date	2020. 09. 25	Temp./Hum.	23°C/48%
Test Voltage	AC 120V, 60Hz (with AC Adapter)	Tested by	Sean Wang
Test SKU	SKU #2 with Speed Antenna		

Liquid Temperature : 22.6°C							Depth of Liquid: > 15cm			
<b>Test Mode: 2.4GHz</b>										
Plot No.	Test Position: Body	Antenna Position	Separation Distance (cm)	Frequency	Conducted Power (dBm)	Maximum Tune-up (dBm)	SAR 1g (W/kg)	Scale Factor	Scale SAR	Limit (W/kg)
802.11b										
Antenna:Chain A (AUX)										
13	Rear	Fixed	0	2442	21.12	21.5	0.314	1.09	0.343	1.60
Antenna:Chain B (Main)										
12	Rear	Fixed	0	2442	21.25	21.5	0.291	1.06	0.308	1.60

Liquid Temperature : 22.6°C							Depth of Liquid: > 15cm			
<b>Test Mode: BT-GFSK</b>										
Plot No.	Test Position: Body	Antenna Position	Separation Distance (cm)	Frequency	Conducted Power (dBm)	Maximum Tune-up (dBm)	SAR 1g (W/kg)	Scale Factor	Scale SAR	Limit (W/kg)
Antenna:Chain A (AUX)										
14	Rear	Fixed	0	2441	9.76	10.0	0.019	1.06	0.020	1.60

Test Date	2020. 09. 23 ~ 24	Temp./Hum.	23°C/48%
Test Voltage	AC 120V, 60Hz (with AC Adapter)	Tested by	Sean Wang
Test SKU	SKU #2 with Speed Antenna		

Liquid Temperature : 23.0°C							Depth of Liquid: > 15cm				
<b>Test Mode: 5GHz</b>											
Plot No.	Test Position: Body	Antenna Position	Separation Distance (cm)	Frequency	Conducted Power (dBm)	Maximum Tune-up (dBm)	SAR 1g (W/kg)	Scale Factor	Scale SAR	Limit (W/kg)	
802.11a (UNII Band II-2A)											
Antenna:Chain A (AUX)											
2	Rear	Fixed	0	5240	21.11	21.5	0.646	1.09	0.71	1.60	
Antenna:Chain B (Main)											
1	Rear	Fixed	0	5240	21.00	21.5	0.701	1.12	0.79	1.60	
802.11a (UNII Band II-2C)											
Antenna:Chain A (AUX)											
4	Rear	Fixed	0	5580	21.09	21.5	<b>1.200</b>	1.10	1.32	1.60	
Antenna:Chain B (Main)											
3	Rear	Fixed	0	5580	21.05	21.5	<b>0.847</b>	1.11	0.94	1.60	
802.11a (UNII Band III)											
Antenna:Chain A (AUX)											
11	Rear	Fixed	0	5700	18.82	19.0	0.536	1.04	0.56	1.60	
6	Rear	Fixed	0	5745	21.08	21.5	<b>1.280</b>	1.10	1.41	1.60	
8	Rear	Fixed	0	5785	21.02	21.5	<b>1.220</b>	1.12	1.36	1.60	
9	Rear	Fixed	0	5825	21.01	21.5	<b>0.867</b>	1.12	0.97	1.60	
Antenna:Chain B (Main)											
10	Rear	Fixed	0	5700	19.39	19.5	0.496	1.03	0.51	1.60	
5	Rear	Fixed	0	5745	21.10	21.5	<b>0.956</b>	1.10	1.05	1.60	
7	Rear	Fixed	0	5785	21.03	21.5	0.479	1.11	0.53	1.60	
19	Rear	Fixed	0	5825	20.95	21.0	0.687	1.01	0.69	1.60	



**Repeated SAR measurement**

Test Date	2020. 09. 23 ~ 24	Temp./Hum.	23°C/48%
Test Voltage	AC 120V, 60Hz (with AC Adapter)	Tested by	Sean Wang
Test SKU	SKU #1 with AWAN Antenna		

802.11a					
Plot No		Frequency (MHz)	SAR 1g (W/kg)	Variation	Additional repeat SAR
4	original	5580	1.110	--	Yes <sup>Note 1</sup>
*21	first repeat	5580	1.040	0.94	No <sup>Note 2</sup>
6	original	5745	1.180	--	Yes <sup>Note 1</sup>
*22	first repeat	5745	1.110	0.94	No <sup>Note 2</sup>
8	original	5785	1.050	--	Yes <sup>Note 1</sup>
*23	first repeat	5785	1.070	1.02	No <sup>Note 2</sup>
9	original	5825	0.983	--	Yes <sup>Note 1</sup>
*24	first repeat	5825	0.962	0.98	No <sup>Note 2</sup>

**Remark: \*: It means repeated SAR measurement.**

Note: 1. Pursuant section 2.8.1(2) KDB 865664 D01, when the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.

2. Pursuant section 2.8.1(3) KDB 865664 D01, perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg (~ 10% from the 1-g SAR limit)

Test Date	2020. 09. 23 ~ 24	Temp./Hum.	23°C/48%
Test Voltage	AC 120V, 60Hz (with AC Adapter)	Tested by	Sean Wang
Test SKU	SKU #2 with Speed Antenna		

802.11a					
Plot No	Frequency (MHz)	SAR 1g (W/kg)	Variation	Additional repeat SAR	
4	original	5580	1.200	--	Yes <sup>Note 1</sup>
*22	first repeat	5580	1.070	0.89	No <sup>Note 2</sup>
3	original	5580	0.847	--	Yes <sup>Note 1</sup>
*21	first repeat	5580	0.817	0.96	No <sup>Note 2</sup>
6	original	5745	1.280	--	Yes <sup>Note 1</sup>
*25	first repeat	5745	1.280	1.00	No <sup>Note 2</sup>
8	original	5785	1.220	--	Yes <sup>Note 1</sup>
*27	first repeat	5785	1.040	0.85	No <sup>Note 2</sup>
9	original	5825	0.867	--	Yes <sup>Note 1</sup>
*29	first repeat	5825	0.868	1.00	No <sup>Note 2</sup>
5	original	5745	0.956	--	Yes <sup>Note 1</sup>
*24	first repeat	5745	0.967	1.01	No <sup>Note 2</sup>

**Remark: \*: It means repeated SAR measurement.**

Note: 1. Pursuant section 2.8.1(2) KDB 865664 D01, when the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.

2. Pursuant section 2.8.1(3) KDB 865664 D01, perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg (~ 10% from the 1-g SAR limit)



*Audix Technology Corp.  
No. 53-11, Dingfu, Linkou, Dist.,  
New Taipei City 244, Taiwan*

*APPENDIX A*

*Tel: +886 2 26099301  
Fax: +886 2 26099303*

---

# APPENDIX A

## GRAPH RESULT

(Model: 13U70P)



*Audix Technology Corp.*  
*No. 53-11, Dingfu, Linkou, Dist.,*  
*New Taipei City 244, Taiwan*

*APPENDIX B*

*Tel: +886 2 26099301*  
*Fax: +886 2 26099303*

---

# APPENDIX B

## TEST PHOTOGRAPHS

(Model: 13U70P)



# APPENDIX C

## Test Equipment Calibration Data