




**Audix Technology Corp.**  
 No. 491, Zhongfu Rd., Linkou Dist.,  
 New Taipei City 244, Taiwan


**Tel: +886 2 26099301**  
**Fax: +886 2 26099303**
















































## A.5 FREQUENCY STABILITY

Test Date	2022/10/31	Temp./Hum.	22°C/66%
Cable Loss	---	Tested By	Brian Hsieh
Test Voltage	AC 120V 60Hz (Via AC Adapter)		

### A.5.1 Frequency stability Result

Temperature (°C)	Voltage (Vac)	Centre Frequency (MHz)	Measurement Value (MHz)	Frequency Stability (ppm)
25	120	5180	5179.976	-4.633
-30	102		5179.984	-3.089
	138		5179.985	-2.896
-20	102		5179.995	-0.965
	138		5179.997	-0.579
-10	102		5180.027	5.212
	138		5180.019	3.668
0	102		5180.023	4.440
	138		5180.024	4.633
10	102		5180.018	3.475
	138		5180.029	5.598
20	102		5179.976	-4.633
	138		5179.97	-5.792
30	102		5179.994	-1.158
	138		5179.973	-5.212
40	102		5179.999	-0.193
	138		5180.017	3.282
50	102		5180.005	0.965
	138		5180.022	4.247