

FCC 15.407 NII 5GHz Test Report

for

LG Electronics Inc.

**222, LG-ro, Jinwi-myeon Pyeongtaek-Si, Gyeonggi-Do,
17709 Republic of Korea**

Product Name : Notebook Computer
Model Name : (1)17G90Q (2)17GB90Q
(3)17GD90Q (4)17GG90Q
Brand : LG
FCC ID : BEJNT-17G90Q

**Prepared by: : AUDIX Technology Corporation,
EMC Department**



The test report is based on a single evaluation of one sample of the above-mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab logo.

TABLE OF CONTENTS

Description	Page
TEST REPORT.....	4
1. REVISION RECORD OF TEST REPORT	5
2. SUMMARY OF TEST RESULTS	6
3. GENERAL INFORMATION	7
3.1. Description of Application	7
3.2. Description of EUT	8
3.3. Reference Test Guidance.....	9
3.4. Antenna Information	9
3.5. EUT Specifications Assessed in Current Report	10
3.6. Description of Key Components	12
3.7. Test Configuration.....	14
3.8. Output Power Setting	21
3.9. Tested Supporting System List.....	23
3.10. Setup Configuration.....	23
3.11. Operating Condition of EUT	24
3.12. Description of Test Facility	24
3.13. Measurement Uncertainty	25
4. MEASUREMENT EQUIPMENT LIST.....	26
4.1. Conducted Emission Measurement	26
4.2. Radiated Emission Measurement	26
4.3. RF Conducted Measurement	27
5. CONDUCTED EMISSION.....	28
5.1. Block Diagram of Test Setup	28
5.2. Conducted Emission Limit	28
5.3. Test Procedure	28
5.4. Test Results	28
6. RADIATED EMISSION	29
6.1. Block Diagram of Test Setup	29
6.2. Radiated Emission Limits.....	30
6.3. Test Procedure	32
6.4. Measurement Result Explanation.....	33
6.5. Test Results	33
7. EMISSION/OCCUPIED BANDWIDTH.....	34
7.1. Block Diagram of Test Setup	34
7.2. Specification Limits.....	34
7.3. Test Procedure	34
7.4. Test Results	34
8. MAXIMUM OUTPUT POWER	35
8.1. Block Diagram of Test Setup	35
8.2. Specification Limits.....	35
8.3. Test Procedure	36
8.4. Test Results	36
9. POWER SPECTRAL DENSITY	37
9.1. Block Diagram of Test Setup	37

9.2. Specification Limits.....	37
9.3. Test Procedure	37
9.4. Test Results	37
10. FREQUENCY STABILITY	38
10.1. Block Diagram of Test Setup	38
10.2. Specification Limits.....	38
10.3. Test Procedure	38
10.4. Test Results	38
11. DEVIATION TO TEST SPECIFICATIONS	39

APPENDIX A TEST DATA AND PLOTS
APPENDIX B TESTPHOTOGRAPHS

TEST REPORT

Applicant : LG Electronics Inc.
Manufacturer : LG Electronics Inc.
Factory : LG Electronics Nanjing New Technology Co., Ltd.
EUT Description
(1) Product : Notebook Computer
(2) Model : (1)17G90Q (2)17GB90Q (3)17GD90Q (4)17GG90Q
(3) Brand : LG
(4) Power Supply : DC 19.5V, 10.8A

Applicable Standards:

Title 47 FCC CFR Part 15 Subpart E
ANSI C63.10:2013

Audix Technology Corp. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.

Audix Technology Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens and samples.


Date of Report: 2022. 02. 21

Reviewed by:



(Sabrina Wang/Administrator)

Approved by:



(Johnny Hsueh/Section Manager)

1. REVISION RECORD OF TEST REPORT

Edition No	Issued Date	Revision Summary	Report Number
0	2022. 02. 21	Original Report	EM-F220012

2. SUMMARY OF TEST RESULTS

Rule	Description	Results
15.207	Conducted Emission	PASS
15.205/15.209	Radiated Band Edge and Radiated Spurious Emission	PASS
15.407(a)(5)/15.407(e)	Emission/Occupied Bandwidth	PASS
15.407(a)	Maximum Output Power	PASS
15.407(b)	Conducted Band Edges	N/A
15.407(a)	Power Spectral Density	PASS
15.407	Frequency Stability	PASS
15.203	Antenna Requirement	Compliance
Note: The uncertainties value is not used in determining the result.		

3. GENERAL INFORMATION

3.1. Description of Application

Applicant	LG Electronics Inc. 222, LG-ro, Jinwi-myeon Pyeongtaek-Si, Gyeonggi-Do, 17709 Republic of Korea
Manufacturer	LG Electronics Inc. 222, LG-ro, Jinwi-myeon Pyeongtaek-Si, Gyeonggi-Do, 17709 Republic of Korea
Factory	LG Electronics Nanjing New Technology Co., Ltd. No.346, Yaoxin Road, Economic & Technical Development Zone, Nanjing, China.
Product	Notebook Computer
Model	(1)17G90Q (2)17GB90Q (3)17GD90Q (4)17GG90Q The difference between all models is different in the sales customers.
Brand	LG

3.2. Description of EUT

Test Model	17G90Q		
Serial Number	N/A		
Power Rating	DC 19.5V, 10.8A		
Software Version	XY (X, Y can be 0 to 9 for different SW version not influence RF parameter)		
RF Features	WLAN:802.11 a/b/g/n/ac/ax Bluetooth: BT and BLE (BT 5.1)		
Transmit Type	2.4 GHz		
	802.11b		1T1R
	802.11g		1T1R
	802.11n-HT20		2T2R
	802.11n-HT40		2T2R
	802.11ax-HE20		2T2R
	802.11ax-HE40		2T2R
	BT/BLE		1T1R
	U-NII Bands		
	802.11a		1T1R
	802.11n-HT20/802.11ac-VHT20/802.11ax-HE20		2T2R
	802.11n-HT40/802.11ac-VHT40/802.11ax-HE40		2T2R
	802.11ac-VHT80/802.11ax-HE80		2T2R
	802.11ac-VHT160/802.11ax-HE160		2T2R
	The MIMO is uncorrelated and supported SDM mode only.		
	Device Category	<input type="checkbox"/> Outdoor Access Point <input type="checkbox"/> Fixed point-to-point Access Point <input type="checkbox"/> Indoor Access Point <input checked="" type="checkbox"/> Mobile and Portable client device	
Test Sample	Sample No.	Test Item	Firmware
	01	AC Conduction, Radiated, RF Conducted	N/A
Sample Status	Trial sample		
Date of Receipt	2021. 12. 13		
Date of Test	2021. 12. 22 ~ 2022. 02. 21		
Interface Ports of EUT	<ul style="list-style-type: none"> • One Micro SD Card Slot • One Earphone Port • Two USB 3.0 Ports • Two USB Type C Ports • One HDMI Port • One LAN Port • One DC In Port 		
Accessories Supplied	<ul style="list-style-type: none"> • AC Adapter 		

3.3. Reference Test Guidance

KDB 789033 D02 General UNII Test Procedures New Rules v02r01

3.4. Antenna Information

No.	Antenna Part Number	Manufacturer	Antenna Type	Frequency (MHz)	Max Gain(dBi)	
					Main	AUX
1.	WA-P-LELE-04-005	INPAQ	Mono-Pole	2400	2.4	0.7
				2450	2.9	2.0
				2500	3.6	1.6
				5150	1.0	0.6
				5470	3.0	-0.1
				5850	2.8	-0.2
				5925	1.3	-2.7
				6525	1.1	-3.0
				7125	3.4	0.1
Note 1. 2.4G: Directional gain = $10 \log[(10^{3.6/10} + 10^{2.0/10})/2] = 2.87\text{dBi}$ Note 2. UNII Band (1/2A/2C/3): Directional gain = $10 \log[(10^{3.0/10} + 10^{0.6/10})/2] = 1.96\text{dBi}$ Note 3. UNII Band (5/6/7/8): Directional gain = $10 \log[(10^{3.4/10} + 10^{0.1/10})/2] = 2.06\text{dBi}$						

3.5. EUT Specifications Assessed in Current Report

Mode	U-NII Band	Fundamental Range (MHz)	Channel Number
802.11a	1	5180-5240	4
	2A	5260-5320	4
	2C	5500-5720	12
	3	5745-5825	5
802.11n-HT20/ 802.11ac-VHT20 802.11ax-HE20	1	5180-5240	4
	2A	5260-5320	4
	2C	5500-5720	12
	3	5745-5825	5
802.11n-HT40/ 802.11ac-VHT40 802.11ax-HE40	1	5190-5230	2
	2A	5270-5310	2
	2C	5510-5710	6
	3	5755-5795	2
802.11ac-VHT80 802.11ax-HE80	1	5210	1
	2A	5290	1
	2C	5530-5690	3
	3	5775	1
802.11ac-VHT160 802.11ax-HE160	1	5250	1
	2A		
	2C	5570	1

Remark: U-NII Band 2A and 2C (DFS Function, Slave/no In service monitor, no Ad-Hoc mode)

Mode	Modulation	Data Rate (Mbps)
802.11a	OFDM (BPSK/QPSK/16QAM/64QAM)	Up to 54
802.11n-HT20	OFDM (BPSK/QPSK/16QAM/64QAM)	Up to 144.4
802.11n-HT40		Up to 300
802.11ac-VHT20	OFDM (BPSK/QPSK/16QAM/64QAM/256QAM)	Up to 173.3
802.11ac-VHT40		Up to 400
802.11ac-VHT80		Up to 866.7
802.11ac-VHT160		Up to 1733.3
802.11ax-HE20	OFDMA (BPSK/ QPSK/ 16QAM/ 64QAM/ 256QAM/1024QAM)	Up to 287
802.11ax-HE40		Up to 574
802.11ax-HE80		Up to 1201
802.11ax-HE160		Up to 2402

Channel List											
802.11a/802.11n-HT20/802.11ac-VHT20/802.11ax-HE20											
U-NII Band	Channel Number	Frequency (MHz)	U-NII Band	Channel Number	Frequency (MHz)	U-NII Band	Channel Number	Frequency (MHz)	U-NII Band	Channel Number	Frequency (MHz)
1	36	5180	2A	52	5260	2C	100	5500	3	149	5745
	40	5200		56	5280		104	5520		153	5765
	44	5220		60	5300		108	5540		157	5785
	48	5240		64	5320		112	5560		161	5805
					116		5580	165		5825	
					120		5600				
					124		5620				
					128		5640				
					132		5660				
					136		5680				
					140		5700				
					144		5720				

Channel List											
802.11n-HT40/802.11ac-VHT40/802.11ax-HE40											
U-NII Band	Channel Number	Frequency (MHz)	U-NII Band	Channel Number	Frequency (MHz)	U-NII Band	Channel Number	Frequency (MHz)	U-NII Band	Channel Number	Frequency (MHz)
1	38	5190	2A	54	5270	2C	102	5510	3	151	5755
	46	5230		62	5310		110	5550		159	5795
					118		5590				
					126		5630				
					134		5670				
					142		5710				

Channel List											
802.11ac-VHT80/802.11ax-HE80											
U-NII Band	Channel Number	Frequency (MHz)	U-NII Band	Channel Number	Frequency (MHz)	U-NII Band	Channel Number	Frequency (MHz)	U-NII Band	Channel Number	Frequency (MHz)
1	42	5210	2A	58	5290	2C	106	5530	3	155	5775
							122	5610			
							138	5690			

Channel List					
802.11ac-VHT160/802.11ax-HE160					
U-NII Band	Channel Number	Frequency (MHz)	U-NII Band	Channel Number	Frequency (MHz)
1/2A	50	5250	2C	114	5570

Note: Test modes are presented at section 3.7.

3.6. Description of Key Components

3.6.1. For the All Component Lists

Item	Supplier	Model / Type	Character
System	Microsoft	Windows 11	---
Main Board	LG	17G90Q MAIN B/D	Manufacturer: #1 Hannstar Board Tech(Jiang Yin) Corp.,Ltd. #2 Elec & Eltek Company (MCO) Limited.
SUB Board	LG	17G90Q SUB B/D	Manufacturer: #1 Hannstar Board Tech(Jiang Yin) Corp.,Ltd. #2 Elec & Eltek Company (MCO) Limited.
CPU (Socket: BGA1787)	Intel	I7-11800H	2.3GHz
GPU	NVIDIA	RTX3080 (GN20-E7)	---
	NVIDIA	RTX3060 (GN20-E3)	---
17.3" LCD Panel	LG Display	LP173WFG(SP)(V4)	17.3" FHD(1920*1080) 300Hz
Storage (SSD)	Samsung	---	NVMe 256GB / 512GB /1TB Gen4
	Samsung	---	NVMe 256GB / 512GB /1TB Gen3
	SK hynix	---	NVMe 256GB / 512GB /1TB Gen3
Memory (RAM)	SK Hynix	---	16GB+16GB (On Card)
	Samsung	---	16GB+16GB (On Card)
	Samsung	---	8GB+8GB (On Card)
Battery Pack	LG	LBW222AM	DC 11.4V, 93Wh Typ 8184mAh
Touch Pad	LITE ON	SP8001	
	Elan	SD081A-36H0	
Keyboard	LITE ON	SN8102	
Web Camera	Chicony	CKFLF26	---
	Chicony	CKFLF12	
WLAN Combo Card	Intel	AX210D2W	FCC ID: PD9AX210D2 IC: 1000M-AX210D2
WLAN Combo Antenna	LG (INPAQ)	WA-P-LELE-04-005	PCB, Mono-pole Type Main: Black, Aux: Gray
AC Adapter	LG	ACC-LATP1	I/P: AC 100-240V, 50-60Hz, 3.0A O/P: DC 19.5V, 10.8A
	LG	ACC-LATP2	I/P: AC 100-240V, 50-60Hz, 2.5A O/P: DC 19.5V, 10.8A
	DC Power Cord: Non-Shielded, Undetached, 1.5m, Bonded a ferrite core AC Power Cord: Non-Shielded, Detached, 1.55m(3C)		

Remark: For more detailed features description, please refer to the manufacturer's specifications or the user manual.

3.6.2. The EUT collocates with following worst components, which are used to establish a basic configuration of system during test:

SKU (Mode) 1	
Main Board	LG, 17G90Q MAIN B/D
SUB Board	LG, 17G90Q SUB B/D
CPU	Intel, I7-11800H, 2.3GHz
GPU	NVIDIA, RTX3080 (GN20-E7)
17.3" LCD Panel	LG Display, LP173WFG(SP)(V4)
Storage (SSD) #1	Samsung, 1TB
Storage (SSD) #2	SK Hynix, 256GB
Memory (RAM) (On Card)	SK Hynix, 16GB+16GB
Battery Pack	LG, LBW222AM, 93Wh
Touch Pad	LITE ON, SP8001
Keyboard	LITE ON, SN8102
Web Camera	Chicony, CKFLF26
WLAN Combo Card	Intel, AX210D2W
WLAN Combo Antenna	LG (INPAQ), WA-P-LELE-04-005
AC Adapter	LG, ACC-LATP1

3.7. Test Configuration

Mode	TX _{on} (ms)	1/ TX _{on} (kHz)	Duty Cycle (x)	Duty Cycle Factor [10log(1/x)] (dB)
802.11a	2.090	0.478	0.981	N/A
802.11n-HT20	3.980	0.251	0.993	N/A
802.11n-HT40	3.980	0.251	0.990	N/A
802.11ac-VHT80	3.970	0.252	0.993	N/A
802.11ac-VHT160	2.790	0.358	0.989	N/A
802.11ax-HE20	3.960	0.253	0.992	N/A
802.11ax-HE40	3.960	0.253	0.990	N/A
802.11ax-HE80	3.970	0.252	0.990	N/A
802.11ax-HE160	2.280	0.439	0.983	N/A
802.11ax-HE20 (RU Configuration)	3.380	0.296	0.991	N/A
802.11ax-HE40 (RU Configuration)	3.380	0.296	0.988	N/A
802.11ax-HE80 (RU Configuration)	3.370	0.297	0.988	N/A
802.11ax-HE160 (RU Configuration)	3.380	0.296	0.988	N/A

Note: When duty cycle is less than 98% (0.98) that duty cycle factor $10\log(1/x)$ is needed to add in conducted test items measured in average detector.

Mode	TX _{on} (ms)	T _{on} +T _{off} (ms)
802.11a	<p>ΔMkr1 2.090 ms 12.99 dB</p>	<p>ΔMkr1 2.130 ms -42.92 dB</p>
802.11n- HT20	<p>ΔMkr1 3.980 ms -2.33 dB</p>	<p>ΔMkr1 4.010 ms -54.81 dB</p>
802.11n- HT40	<p>ΔMkr1 3.980 ms 8.06 dB</p>	<p>ΔMkr1 4.020 ms -42.39 dB</p>
802.11ac- VHT80	<p>ΔMkr1 3.970 ms 6.40 dB</p>	<p>ΔMkr1 4.000 ms -43.31 dB</p>
802.11ac- VHT160	<p>ΔMkr1 2.790 ms -5.02 dB</p>	<p>ΔMkr1 2.820 ms -38.02 dB</p>

Mode	TX _{on} (ms)	T _{on} +T _{off} (ms)
802.11ax-HE20	<p>Center: 5.19000000 GHz Res BW: 1.0 MHz Video BW: 3.0 MHz Sweep: 10.0 ms (1001 pts)</p>	<p>Center: 5.19000000 GHz Res BW: 1.0 MHz Video BW: 3.0 MHz Sweep: 10.0 ms (1001 pts)</p>
802.11ax-HE40	<p>Center: 5.19000000 GHz Res BW: 1.0 MHz Video BW: 3.0 MHz Sweep: 10.0 ms (1001 pts)</p>	<p>Center: 5.19000000 GHz Res BW: 1.0 MHz Video BW: 3.0 MHz Sweep: 10.0 ms (1001 pts)</p>
802.11ax-HE80	<p>Center: 5.21000000 GHz Res BW: 1.0 MHz Video BW: 3.0 MHz Sweep: 10.0 ms (1001 pts)</p>	<p>Center: 5.21000000 GHz Res BW: 1.0 MHz Video BW: 3.0 MHz Sweep: 10.0 ms (1001 pts)</p>
802.11ax-HE160	<p>Center: 5.25000000 GHz Res BW: 1.0 MHz Video BW: 3.0 MHz Sweep: 10.0 ms (1001 pts)</p>	<p>Center: 5.25000000 GHz Res BW: 1.0 MHz Video BW: 3.0 MHz Sweep: 10.0 ms (1001 pts)</p>

Mode	TX _{on} (ms)	T _{on} +T _{off} (ms)
802.11ax-HE20 (RU Configuration)	<p>KEYSIGHT Spectrum Analyzer 1 Input RF, Input Z: 50 Ω, Atten: 40 dB, PNO: Fast, Gate: Off, IF: Clean Low, Sig Track: Off, Avg Type: Log Power, Trig: Free Run Scale/Div: 10 dB, Ref Lvl Offset: 2.00 dB, Ref Level: 25.00 dBm, ΔMkr1: 3.380 ms, 16.66 dB</p>	<p>KEYSIGHT Spectrum Analyzer 1 Input RF, Input Z: 50 Ω, Atten: 40 dB, PNO: Fast, Gate: Off, IF: Clean Low, Sig Track: Off, Avg Type: Log Power, Trig: Free Run Scale/Div: 10 dB, Ref Lvl Offset: 2.00 dB, Ref Level: 25.00 dBm, ΔMkr1: 3.410 ms, -40.30 dB</p>
802.11ax-HE40 (RU Configuration)	<p>KEYSIGHT Spectrum Analyzer 1 Input RF, Input Z: 50 Ω, Atten: 40 dB, PNO: Fast, Gate: Off, IF: Clean Low, Sig Track: Off, Avg Type: Log Power, Trig: Free Run Scale/Div: 10 dB, Ref Lvl Offset: 2.00 dB, Ref Level: 25.00 dBm, ΔMkr1: 3.380 ms, 8.76 dB</p>	<p>KEYSIGHT Spectrum Analyzer 1 Input RF, Input Z: 50 Ω, Atten: 40 dB, PNO: Fast, Gate: Off, IF: Clean Low, Sig Track: Off, Avg Type: Log Power, Trig: Free Run Scale/Div: 10 dB, Ref Lvl Offset: 2.00 dB, Ref Level: 25.00 dBm, ΔMkr1: 3.420 ms, -30.01 dB</p>
802.11ax-HE80 (RU Configuration)	<p>KEYSIGHT Spectrum Analyzer 1 Input RF, Input Z: 50 Ω, Atten: 40 dB, PNO: Fast, Gate: Off, IF: Clean Low, Sig Track: Off, Avg Type: Log Power, Trig: Free Run Scale/Div: 10 dB, Ref Lvl Offset: 2.00 dB, Ref Level: 25.00 dBm, ΔMkr1: 3.370 ms, -4.18 dB</p>	<p>KEYSIGHT Spectrum Analyzer 1 Input RF, Input Z: 50 Ω, Atten: 40 dB, PNO: Fast, Gate: Off, IF: Clean Low, Sig Track: Off, Avg Type: Log Power, Trig: Free Run Scale/Div: 10 dB, Ref Lvl Offset: 2.00 dB, Ref Level: 25.00 dBm, ΔMkr1: 3.410 ms, -24.56 dB</p>
802.11ax-HE160 (RU Configuration)	<p>KEYSIGHT Spectrum Analyzer 1 Input RF, Input Z: 50 Ω, Atten: 40 dB, PNO: Fast, Gate: Off, IF: Clean Low, Sig Track: Off, Avg Type: Log Power, Trig: Free Run Scale/Div: 10 dB, Ref Lvl Offset: 2.00 dB, Ref Level: 25.00 dBm, ΔMkr1: 3.380 ms, -2.90 dB</p>	<p>KEYSIGHT Spectrum Analyzer 1 Input RF, Input Z: 50 Ω, Atten: 40 dB, PNO: Fast, Gate: Off, IF: Clean Low, Sig Track: Off, Avg Type: Log Power, Trig: Free Run Scale/Div: 10 dB, Ref Lvl Offset: 2.00 dB, Ref Level: 25.00 dBm, ΔMkr1: 3.420 ms, -26.44 dB</p>

AC Conduction
Normal operation

Item	Mode	Data Rate	Test Channel
Radiated Test Case	Radiated Band Edge <small>Note1</small>	802.11a	6 Mbps 36/64/100/140/144/149/165
		802.11n-HT20	MCS8 36/64/100/140/144/149/165
		802.11n-HT40	MCS8 38/62/102/134/142/151/159
		802.11ac-VHT80	MCS0 42/58/106/122/138/155
		802.11ac-VHT160	MCS0 50/114
		802.11ax-HE20	HE0 36/64/100/140/144/149/165
		802.11ax-HE40	HE0 38/62/102/134/142/151/159
		802.11ax-HE80	HE0 42/58/106/122/138/155
		802.11ax-HE160	HE0 50/114
	Radiated Spurious Emission <small>Note1 & 2</small>	802.11a	6 Mbps 48/60/100/144/149
		802.11n-HT20	MCS8 36/60/100/144/165
		802.11n-HT40	MCS8 46/54/134/142/159
		802.11ac-VHT80	MCS0 42/58/122/138/155
		802.11ac-VHT160	MCS0 50/114
		802.11ax-HE20	HE0 36/60/100/144/157
		802.11ax-HE40	HE0 46/54/134/142/159
		802.11ax-HE80	HE0 42/58/122/138/155
		802.11ax-HE160	HE0 50/114

Item	Mode	Data Rate	RU Configuration	Test Channel	
Radiated Test Case	Radiated Band Edge <small>Note1</small>	802.11ax-HE20	HE0	26/0	36/100/149
			HE0	52/37	
			HE0	106/53	
		802.11ax-HE40	HE0	26/8	64/140/165
			HE0	52/40	
			HE0	106/54	
	802.11ax-HE80	HE0	242/61	38/102/151	
		HE0	242/62	62/134/159	
		HE0	484/65	42/106/155	
		HE0	484/66	58/122/155	
		802.11ax-HE160	HE0	996/67	50/114
			HE0	996/S67	50/114
HE0	996/S67		50/114		

Item		Mode	Data Rate	Test Channel
Conducted Test Case	Emission/ Occupied Bandwidth	802.11a	6 Mbps	36/40/48/52/60/64/100/116/140/144/149/157/165
		802.11n-HT20	MCS8	36/40/48/52/60/64/100/116/140/144/149/157/165
		802.11n-HT40	MCS8	38/46/54/62/102/110/134/142/151/159
		802.11ac-VHT80	MCS0	42/58/106/122/138/155
		802.11ac-VHT160	MCS0	50/114
		802.11ax-HE20	HE0	36/40/48/52/60/64/100/116/140/144/149/157/165
		802.11ax-HE40	HE0	38/46/54/62/102/110/134/142/151/159
		802.11ax-HE80	HE0	42/58/106/122/138/155
	802.11ax-HE160	HE0	50/114	
	Maximum output power	802.11a	6 Mbps	36/40/48/52/60/64/100/116/140/144/149/157/165
		802.11n-HT20	MCS8	36/40/48/52/60/64/100/116/140/144/149/157/165
		802.11n-HT40	MCS8	38/46/54/62/102/110/134/142/151/159
		802.11ac-VHT80	MCS0	42/58/106/122/138/155
		802.11ac-VHT160	MCS0	50/114
		802.11ax-HE20	HE0	36/40/48/52/60/64/100/116/140/144/149/157/165
		802.11ax-HE40	HE0	38/46/54/62/102/110/134/142/151/159
		802.11ax-HE80	HE0	42/58/106/122/138/155
	802.11ax-HE160	HE0	50/114	
	Power spectral density	802.11a	6 Mbps	36/40/48/52/60/64/100/116/140/144/149/157/165
		802.11n-HT20	MCS8	36/40/48/52/60/64/100/116/140/144/149/157/165
		802.11n-HT40	MCS8	38/46/54/62/102/110/134/142/151/159
		802.11ac-VHT80	MCS0	42/58/106/122/138/155
		802.11ac-VHT160	MCS0	50/114
		802.11ax-HE20	HE0	36/40/48/52/60/64/100/116/140/144/149/157/165
		802.11ax-HE40	HE0	38/46/54/62/102/110/134/142/151/159
		802.11ax-HE80	HE0	42/58/106/122/138/155
	802.11ax-HE160	HE0	50/114	

Item		Mode	Data Rate	RU Configuration	Test Channel
Conducted Test Case	Emission/ Occupied Bandwidth	802.11ax-HE20	HE0	26/0	36/100/149
				52/37	
				106/53	
			HE0	26/8	64/140/165
				52/40	
				106/54	
		802.11ax-HE40	HE0	242/61	38/102/151
			HE0	242/62	62/134/159
		802.11ax-HE80	HE0	484/65	42/106/155
			HE0	484/66	58/122/155
		802.11ax-HE160	HE0	996/67	50/114
			HE0	996/S67	50/114
Conducted Test Case	Maximum output power	802.11ax-HE20	HE0	26/0	36/100/149
				52/37	
				106/53	
			HE0	26/8	64/140/165
				52/40	
				106/5	
		802.11ax-HE40	HE0	242/61	38/102/151
			HE0	242/62	62/134/159
		802.11ax-HE80	HE0	484/65	42/106/155
			HE0	484/66	58/122/155
		802.11ax-HE160	HE0	996/67	50/114
			HE0	996/S67	50/114
Conducted Test Case	Power spectral density	802.11ax-HE20	HE0	26/0	36/100/149
				52/37	
				106/53	
			HE0	26/8	64/140/165
				52/40	
				106/54	
		802.11ax-HE40	HE0	242/61	38/102/151
			HE0	242/62	62/134/159
		802.11ax-HE80	HE0	484/65	42/106/155
			HE0	484/66	58/122/155
		802.11ax-HE160	HE0	996/67	50/114
			HE0	996/S67	50/114

Note 1: Mobile Device

Portable Device, and 3 axis were assessed. The worst scenario for Radiated Spurious Emission as follow: Lie Side Stand

Note 2: Low, mid, and high channels were measured, only the worst channel of each modulation was presented in this report.

Note 3: The modulation and bandwidth are similar for 802.11n mode for HT20/HT40 and 802.11ac mode for VHT20/VHT40, therefore investigated worst case to representative mode in the test report.

Note 4: The data rates were selected based on preliminary testing that identified rate as the worst case for output power.

3.8. Output Power Setting

Mode	U-NII Band	Centre Frequency (MHz)	Power Setting	
			Chain 0 (AUX)	Chain 1 (Main)
802.11a	I	5180	18.000	18.000
		5200	20.000	20.000
		5240	20.000	20.000
	2A	5260	20.000	20.000
		5300	20.000	20.000
		5320	18.000	18.250
	2C	5500	18.500	18.500
		5580	20.000	20.000
		5700	18.500	18.500
		5720	20.000	20.000
	III	5745	20.000	20.000
		5785	20.000	20.000
5825		20.000	20.000	

Mode	U-NII Band	Centre Frequency (MHz)	Power Setting	Mode	U-NII Band	Centre Frequency (MHz)	Power Setting
802.11n-HT20	I	5180	16.500	802.11ax-HE20	I	5180	16.500
		5200	18.000			5200	18.000
		5240	18.000			5240	18.000
	2A	5260	18.000		2A	5260	18.000
		5300	18.000			5300	18.000
		5320	16.750			5320	16.750
	2C	5500	18.000		2C	5500	18.000
		5580	18.000			5580	18.000
		5700	18.000			5700	16.250
		5720	18.000			5720	18.000
	III	5745	20.000		III	5745	20.000
		5785	20.000			5785	20.000
5825		20.000	5825	20.000			

Mode	U-NII Band	Centre Frequency (MHz)	Power Setting	Mode	U-NII Band	Centre Frequency (MHz)	Power Setting
802.11n-HT40	I	5190	14.250	802.11ax-HE40	I	5190	14.250
		5230	19.000			5230	19.000
	2A	5270	17.500		2A	5270	17.500
		5310	13.750			5310	13.750
	2C	5510	14.000		2C	5510	14.125
		5550	20.000			5550	20.000
		5670	17.625			5670	18.000
		5710	20.000			5710	20.000
	III	5755	19.750		III	5755	19.750
		5795	20.000			5795	20.000

Mode	U-NII Band	Centre Frequency (MHz)	Power Setting	Mode	U-NII Band	Centre Frequency (MHz)	Power Setting
802.11ac- VT80	I	5210	13.750	802.11ax- HE80	I	5210	13.750
	2A	5290	14.250		2A	5290	14.250
	2C	5530	15.000		2C	5530	15.000
		5610	18.750			5610	18.750
		5690	20.000			5690	20.000
	III	5775	17.500		III	5775	17.500

Mode	U-NII Band	Centre Frequency (MHz)	Power Setting	Mode	U-NII Band	Centre Frequency (MHz)	Power Setting
802.11ac- VT160	I/2A	5250	12.250	802.11ax- HE160	I/2A	5250	12.250
	2C	5570	13.000		2C	5570	13.000

Mode	U-NII Band	Centre Frequency (MHz)	RU Configuration	Power Setting
802.11ax- HE20	I	5180	26/0	10.000
			52/37	13.000
			106/53	16.000
	2A	5320	26/8	10.000
			52/40	13.000
			106/54	14.750
	2C	5500	26/0	10.000
			52/37	13.000
			106/53	15.750
		5700	26/8	10.000
			52/40	13.000
			106/54	16.000
	III	5745	26/0	15.000
			52/37	13.000
			106/53	17.000
5825		26/8	17.000	
		52/40	13.000	
		106/54	17.000	
802.11ax- HE40	I	5190	242/61	16.250
	2A	5310	242/62	16.250
	2C	5510	242/61	17.500
		5670	242/62	18.000
	III	5755	242/61	19.500
		5795	242/62	20.000
802.11ax- HE80	I	5210	484/65	14.250
	2A	5290	484/66	12.000
	2C	5530	484/65	14.375
		5610	484/66	18.500
	III	5775	484/65	18.250
		5775	484/66	20.000
802.11ax- HE160	I/2A	5250	996/67	13.750
			996/S67	13.750
	2C	5570	996/67	13.750
			996/S67	17.750

3.9. Tested Supporting System List

3.9.1. Support Peripheral Unit


No.	Product	Brand	Model No.	Serial No.	Approval
1.	TV	LG	22LK330-DB	N/A	N/A
2.	USB Mouse	DENGEKI	P012 (MS-P12)	N/A	N/A
3.	Earphone	APPLE	N/A	N/A	N/A
4.	SD Card	ADATA	MicroSDHC Card	N/A	N/A
5.	Mobile phone	ASUS	ASUS_Z01FD	N/A	N/A
Partner System					
6.	WiFi 6E Router	NETGEAR	RAXE500	N/A	FCC ID: PY320300508

3.9.2. Cable Lists

No.	Cable Description Of The Above Support Units
1.	HDMI Cable: Shielded, Detachable, 1.2m AC Power Cord: Unshielded, Detachable, 1.8m
2.	USB Cable: Unshielded, Undetachable, 1.5m
3.	Earphone Cable: Unshielded, Undetachable, 1.2m
4.	N/A
5.	USB Cable: Unshielded, Undetachable, 1.5m
6.	AC adapter: M/N:2ABS060K, DC Cable: Unshielded, Detachable, 1.8m AC Cord: Wall-mounted: 2C LAN cable: Unshielded, Detachable, 3.0m

3.10. Setup Configuration

3.10.1. EUT Configuration for Power Line & Radiated Emission



3.10.2. EUT Configuration for RF Conducted Test Items



3.11. Operating Condition of EUT

Test program “DRTU” is used for enabling EUT WLAN function under continues transmitting and choosing data rate/ channel.

[Chain 0 is aux port (A Button in DRTU) Chain 1 is main port (B Button in DRTU)].

3.12. Description of Test Facility

Name of Test Firm	Audix Technology Corporation / EMC Department No. 491, Zhongfu Rd., Linkou Dist., New Taipei City 244, Taiwan Tel: +886-2-26092133 Fax: +886-2-26099303 Website : www.audixtech.com Contact e-mail: attemc_report@audixtech.com
Accreditations	The laboratory is accredited by following organizations under ISO/IEC 17025:2017 (1) NVLAP(USA) NVLAP Lab Code 200077-0 (2) TAF(Taiwan) No. 1724
Test Facilities	FCC OET Designation Number under APEC MRA by NCC is : TW1724 ISED CAB Identifier Number under APEC TEL MRA by NCC is TW1724 (1) No.8 Shielded Room (2) No.1 3m Semi Anechoic Chamber

3.13.Measurement Uncertainty

Test Items/Facilities		Frequency Range	Uncertainty	
Conduction Test		9kHz-150kHz	±3.7dB	
		150kHz-30MHz	±3.4dB	
Radiation Test	<input checked="" type="checkbox"/>	No.1 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±3.8dB
			200MHz-1000MHz, 3m, Horizontal	±4.1dB
			30MHz-200MHz, 3m, Vertical	±4.5dB
			200MHz-1000MHz, 3m, Vertical	±4.5dB
			1GHz-6GHz, 3m	±4.7dB
			6GHz-18GHz, 3m	±4.1dB
			18GHz~40GHz	±3.52dB
	<input type="checkbox"/>	No.3 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±3.9dB
			200MHz-1000MHz, 3m, Horizontal	±4.2dB
			30MHz-200MHz, 3m, Vertical	±4.3dB
			200MHz-1000MHz, 3m, Vertical	±4.5dB
			30MHz-200MHz, 3m, Horizontal	±4.1dB
			200MHz-1000MHz, 3m, Horizontal	±4.5dB
	<input type="checkbox"/>	No.4 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Vertical	±4.4dB
			200MHz-1000MHz, 3m, Vertical	±4.8dB
			1GHz-6GHz, 3m	±5.0dB
			6GHz-18GHz, 3m	±4.7dB
			30MHz-200MHz, 3m, Horizontal	±4.2dB
			200MHz-1000MHz, 3m, Horizontal	±4.3dB
	<input type="checkbox"/>	No.5 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Vertical	±4.3dB
			200MHz-1000MHz, 3m, Vertical	±4.7dB
			1GHz-6GHz, 3m	±4.8dB
			6GHz-18GHz, 3m	±4.5dB
			30MHz-200MHz, 3m, Horizontal	±4.2dB
200MHz-1000MHz, 3m, Horizontal			±4.3dB	

Remark : Uncertainty = $ku_c(y)$

Test Items	Uncertainty
Emission Bandwidth	± 0.2kHz
Maximum output power	± 0.33dB
Power spectral density	± 0.13dB

4. MEASUREMENT EQUIPMENT LIST

4.1. Conducted Emission Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Test Receiver	R&S	ESR3	101774	2021.02.02	1 Year
2.	A.M.N.	R&S	ENV432	101567	2021.04.21	1 Year
3.	L.I.S.N.	Kyoritsu	KNW-407	8-855-9	2021.12.19	1 Year
4.	Pulse Limiter	R&S	ESH3-Z2	100354	2021.01.04	1 Year
5.	Digital Thermo-Hygro Meter	iMax	HTC-1	No.8 S/R	2021.04.15	1 Year
6.	Coaxial Cable	Yeida	RG/58AU	CE-08	2021.09.13	1 Year
7.	Test Software	Audix	e3	V6.120619c	N.C.R.	N.C.R.

4.2. Radiated Emission Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A-526	MY53400071	2021.09.09	1 Year
2.	Spectrum Analyzer	Agilent	N9030A-526	MY53310269	2021.01.14	1 Year
3.	Spectrum Analyzer	Keysight	N9010B-544	MY55460198	2021.04.14	1 Year
4.	Test Receiver	R&S	ESCS30	100039	2021.06.02	1 Year
5.	Amplifier	Sonoma	310N	187161	2021.05.21	1 Year
6.	Microwave Amplifier	Keysight	83051A	MY53010042	2021.07.30	1 Year
7.	Microwave Amplifier	Keysight	83017A	MY53270365	2021.05.27	1 Year
8.	Loop Antenna	ETS	6512	00035867	2021.09.29	1 Year
9.	Bilog Antenna	TESEQ	CBL6112D	33821	2021.07.16	1 Year
10.	Double-Ridged Waveguide Horn	ETS-Lindgren	3115	00114104	2021.04.02	1 Year
11.	Horn Antenna	COM-POWER	AH-840	101092	2021.01.05	1 Year
12.	5G Notch Filter	Microwave Circuits	N0452502	459775	2021.05.05	1 Year
13.	5G Notch Filter	Microwave Circuits	N0555983	504921	2021.08.04	1 Year
14.	5G Notch Filter	Microwave Circuits	N0257881	459776	2021.08.16	1 Year
15.	Coaxial Cable	MIYAZAKI	5D2W	RE-11	2021.01.29	1 Year
16.	Coaxial Cable	HUBER+SUHNER	SUCOFLEX 106	RE-14	2021.01.29	1 Year
17.	Coaxial Cable	HUBER+SUHNER	SUCOFLEX 102	RE-30	2021.05.25	1 Year
18.	Digital Thermo-Hygro Meter	iMax	HTC-1	No.1 3m A/C	2021.04.15	1 Year
20.	Test Software	Audix	e3	V6.120619c	N.C.R.	N.C.R.

4.3. RF Conducted Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Keysight	N9020B-544	MY57120357	2021.01.06	1 Year
2.	Power Meter	Anritsu	ML2495A	1145008	2021.06.30	1 Year
3.	Power Sensor	Anritsu	MA2411B	1126096	2021.06.30	1 Year
4.	Digital Thermo-Hygro Meter	iMax	HTC-1	RF-03	2021.04.15	1 Year


5. CONDUCTED EMISSION

5.1. Block Diagram of Test Setup

5.1.1. Block Diagram of EUT

Indicated as section 3.9

5.1.2. Shielded Room Setup Diagram



5.2. Conducted Emission Limit

Frequency	Conducted Limit	
	Quasi-Peak Level	Average Level
150kHz ~ 500kHz	66 ~ 56 dB μ V	56 ~ 46 dB μ V
500kHz ~ 5MHz	56 dB μ V	46 dB μ V
5MHz ~ 30MHz	60 dB μ V	50 dB μ V

Remark1.: If the average limit is met when using a Quasi-Peak detector, the measurement using the average detector is not required.

2.: The lower limit applies to the band edges.

5.3. Test Procedure

- 5.3.1. To set up the EUT as indicated in ANSI C63.10. The EUT was placed on the table which has 80 cm height to the ground and 40 cm distance to the conducting wall.
- 5.3.2. Power supplier of the EUT was connected to the AC mains through an Artificial Mains Network (A.M.N.).
- 5.3.3. The AC power supplies to all peripheral devices must be provided through line impedance stabilization network (L.I.S.N.)
- 5.3.4. Checking frequency range from 150kHz to 30 MHz and record the emission which does not have 20 dB below limit.

5.4. Test Results

Please refer to Appendix A.


6. RADIATED EMISSION

6.1. Block Diagram of Test Setup


6.1.1. Block Diagram of EUT

Indicated as section 3.9


6.1.2. Setup Diagram for 9kHz-30MHz



6.1.3. Setup Diagram for 30-1000MHz



6.1.4. Setup Diagram for above 1GHz



6.2. Radiated Emission Limits

Radiated emissions fall in restricted bands, as defined in Section 15.205 must be in compliance with the radiated emission limits specified in 15.209 as below.

6.2.1. General Limit

Frequency (MHz)	Distance(m)	Limits	
		dB μ V/m	μ V/m
0.009 - 0.490	300	67.6-20 log f(kHz)	2400/f kHz
0.490 - 1.705	30	87.6-20 log f(kHz)	24000/f kHz
1.705 - 30	30	29.5	30
30 - 88	3	40.0	100
88- 216	3	43.5	150
216- 960	3	46.0	200
Above 960	3	54.0	500
Above 1000	3	74.0 dB μ V/m (Peak) 54.0 dB μ V/m (Average)	

Remark : (1) dB μ V/m = 20 log (μ V/m)


- (2) The tighter limit applies to the edge between two frequency bands.
- (3) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- (4) Fundamental and emission fall within operation band are exempted from this section.
- (5) Pursuant to ANSI C63.10: 6.6.4.3, if the maximized peak measured value complies with the average limit, then it is unnecessary to perform an average measurement.

6.2.2. Limit for non-restricted frequency above 1 GHz

Frequency Band (MHz)	E.I.R.P. Limit	Field Strength Limit at 3 m
5150 to 5250	-27 dBm	68.2
5250 to 5350		68.2
5470 to 5725		68.2

Note: Field Strength at 3 m= E.I.R.P. + 95.2 dB

Frequency Band (MHz)	Field Strength Limit at 3 m
5725 to 5850	<input checked="" type="checkbox"/> 15.407(b)(4)(i) All emissions shall be limited to a level of 68.2 dB μ V/m at 75 MHz or more above or below the band edge increasing linearly to 105.2dB μ V/m at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 110.8 dB μ V/m at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 68.2 dB μ V/m at the band edge.
	<input type="checkbox"/> 15.407(b)(4)(ii) ,compliance with the emission limits in § 15.247(d) Shall be at least 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power,. Attenuation below the general limits specified in §15.209(a) is not required. In addition,radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))



6.3. Test Procedure

Frequency Range 9kHz~30MHz:

The EUT setup on the turntable which has 0.8 m height to the ground. The turn table rotated 360 degrees and antenna fixed to 1 m to find the maximum emission level. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013 regulation.

- (1) RBW = 9kHz with peak and average detector.
- (2) Detector: average and peak (9kHz-490kHz)
Q.P. (490kHz-30MHz)

Frequency Range 30MHz ~ 40GHz:

The EUT setup on the turn table which has 80cm (for 30-1000MHz) and 1.5m (for above 1GHz) height to the ground. The turn table rotated 360 degrees and antenna varied from 1 m to 4 m to find the maximum emission level. Both horizontal and vertical polarization are required. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013 regulation.

Frequency below 1GHz:

Spectrum Analyzer is used for pre-testing with following setting:

- (1)RBW = 120kHz
- (2)VBW $\geq 3 \times$ RBW.
- (3)Detector = Peak.
- (4)Sweep time = auto.
- (5)Trace mode = max hold.
- (6)Allow sweeps to continue until the trace stabilizes.

Note 1: When peak-detected value is lower than limit that the measurement using the Q.P. detector is not required, otherwise using Q.P. for final measurement.

Note 2: When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.

Frequency above 1GHz to 10th harmonic(up to 40 GHz):

Peak Detector:

- (1)RBW = 1MHz
- (2)VBW $\geq 3 \times$ RBW.
- (3)Detector = Peak.
- (4)Sweep time = auto.
- (5)Trace mode = max hold.
- (6)Allow sweeps to continue until the trace stabilizes.

Note: When peak-detected value is lower than limit that the measurement using the average detector is not required, otherwise using average detector for final measurement.

Average Detector:

■ Option 1:

(1) RBW = 1MHz

(2) VBW \geq 1/ T.

Modulation Type	T (ms)	1/ T (kHz)	VBW Setting(kHz)
802.11a	2.090	0.478	10Hz
802.11n-HT20	3.980	0.251	10Hz
802.11n-HT40	3.980	0.251	10Hz
802.11ac-VHT80	3.970	0.252	10Hz
802.11ac-VHT160	2.790	0.358	10Hz
802.11ax-HE20	3.960	0.253	10Hz
802.11ax-HE40	3.960	0.253	10Hz
802.11ax-HE80	3.970	0.252	10Hz
802.11ax-HE160	2.280	0.439	10Hz
802.11ax-HE20 (RU Configuration)	3.380	0.296	10Hz
802.11ax-HE40 (RU Configuration)	3.380	0.296	10Hz
802.11ax-HE80 (RU Configuration)	3.370	0.297	10Hz
802.11ax-HE160 (RU Configuration)	3.380	0.296	10Hz

N/A: 1/ T is not implemented when duty cycle presented in section 3.6 is \geq 98%.

(1) Detector = Peak.

(2) Sweep time = auto.

(3) Trace mode = max hold.

(4) Allow sweeps to continue until the trace stabilizes.

 Option 2:


Average Emission Level= Peak Emission Level+ D.C.C.F.

6.4.Measurement Result Explanation**■** Peak Emission Level=Antenna Factor + Cable Loss + Meter Reading (including Preamp factor if test used)**■** Average Emission Level l=Antenna Factor + Cable Loss + Meter Reading (including Preamp factor if test used) Average Emission Level= Peak Emission Level+ DCCFDuty Cycle Correction Factor (DCCF)= $20\log(TX_{on}/TX_{on+off})$ presented in section 3.6. ERP= Peak Emission Level-95.2dB-2.14dB**6.5.Test Results**

Please refer to Appendix A.

7. EMISSION/OCCUPIED BANDWIDTH

7.1. Block Diagram of Test Setup



7.2. Specification Limits

Frequency Band (MHz)	Limit
5150 to 5250	Reference only
5250 to 5350	
5470 to 5725	
5725 to 5850	$\geq 500\text{kHz}$

7.3. Test Procedure

Following measurement procedure is reference to KDB 789033 D02 General UNII Test Procedures New Rules v02r01:

■ Applicable to all bands except to 5725 MHz- 5850 MHz

- (1) Set RBW= 1% of the emission bandwidth
- (2) Set VBW > RBW
- (3) Detector = Peak
- (4) Trace mode = max hold
- (5) Setting channel bandwidth function x dB to -26 dB to record the final bandwidth.

■ 5725 MHz- 5850 MHz


- (1) Set RBW = 100 kHz.
- (2) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Trace mode = max hold.
- (5) Sweep = auto couple.
- (6) Allow the trace to stabilize.
- (7) Setting channel bandwidth function x dB to -6 dB to record the final bandwidth.

7.4. Test Results


Please refer to Appendix A

8. MAXIMUM OUTPUT POWER

8.1. Block Diagram of Test Setup



- For 802.11ac-VHT80/160, 802.11ax-HE160 modes only



8.2. Specification Limits

Frequency Band (MHz)	Category	Limit
5150 to 5250	Outdoor Access Point	1 W(30 dBm)/ Max e.i.r.p. ≤125 mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon
	Fixed point-to-point Access Point	1 W(30 dBm)
	Indoor Access Point	1 W(30 dBm)
	Mobile and Portable client device	250 mW(24 dBm)
5250 to 5350	N/A	250 mW or 11 dBm + 10 log B ^{Note1}
5470 to 5725		250 mW or 11 dBm + 10 log B ^{Note1}
5725 to 5850		1 W(30 dBm)

Note 1: B is the 26 dB emission bandwidth, which presented in section 7 and appendix A.1.

8.3. Test Procedure

Following measurement procedure is reference to KDB 789033 D02 General UNII Test Procedures New Rules v02r01:

■ **Method AVGPM (Measurement using an RF average power meter):**

EUT is connected to power sensor and record the maximum average output power and duty cycle factor is added when duty cycle presented in section 3.7 is < 98%.

■ **Method AVGSA-2 (Spectrum channel power) for 802.11ac-VHT80/160, 802.11ax-HE80/160 modes only**


- (1) Set span to at least 1.5 times the OBW
- (2) Set RBW = 1 MHz
- (3) Set the video bandwidth (VBW) \geq 3 MHz.
- (4) Detector = RMS.
- (5) Trace mode = trace average at least 100 traces
- (6) Sweep = auto couple.
- (7) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges.
- (8) Duty cycle factor is added when duty cycle presented in section 3.6 is < 98%.

8.4. Test Results

Please refer to Appendix A

9. POWER SPECTRAL DENSITY

9.1. Block Diagram of Test Setup



9.2. Specification Limits

Frequency Band (MHz)	Category	Limit
5150 to 5250	Outdoor Access Point	17dBm/MHz
	Fixed point-to-point Access Point	
	Indoor Access Point	
	Mobile and Portable client device	11 dBm/MHz
5250 to 5350	N/A	11 dBm/MHz
5470 to 5725		11 dBm/MHz
5725 to 5850		30dBm/500 kHz

9.3. Test Procedure

Following measurement procedure is reference to KDB 789033 D02 General UNII Test Procedures New Rules v02r01:

■ Method AVGSA-2 (Spectrum channel power)


- (1) Set span to at least 1.5 times the OBW
- (2) Set RBW = 1 MHz
- (3) Set the video bandwidth (VBW) \geq 3 MHz.
- (4) Detector = RMS.
- (5) Trace mode = trace average at least 100 traces
- (6) Sweep = auto couple.
- (7) Use peak search function to find out the maximum power density.
- (8) Duty cycle factor is added when duty cycle presented in section 3.6 is $<$ 98%.

9.4. Test Results

Please refer to Appendix A

10. FREQUENCY STABILITY

10.1. Block Diagram of Test Setup



10.2. Specification Limits

NONE

10.3. Test Procedure

- (1) Frequency: Test frequency.
- (2) Span: enough to cover the complete power envelope
- (3) RBW: 1MHz(modulation ON) ; 10KHz(CW)
- (4) VBW: 1MHz(modulation ON) ; 10KHz(CW)
- (5) Detector Mode: Positive Peak
- (6) Indication mode: Max hold
- (7) Find the peak frequency and take calculate by the formula:
(Measurement Value-declaration frequency)/ declaration frequency)

10.4. Test Results

Please refer to Appendix A

11. DEVIATION TO TEST SPECIFICATIONS

【NONE】



Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City 244, Taiwan

APPENDIX A

Tel: +886 2 26099301
Fax: +886 2 26099303

APPDNDIX A

TEST DATA AND PLOTS

(Model: 17G90Q)