

On your side

HCT

TEST REPORT

FCC /ISED SAR Exclusion Report for certification of PM20GA

APPLICANT

LG Electronics Inc

REPORT NO.

HCT-SR-1910-FI001

DATE OF ISSUE

October 18, 2019

HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA

Tel. +82 31 634 6300 F ax. +82 31 645 6401



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401

TEST REPORT

(If needed)
FCC SAR Test for
certification

REPORT NO.
HCT-SR-1910-FI001

DATE OF ISSUE
October 18, 2019

FCC ID
BEJPM20GA
ISED ID
2703H-PM20GA

Applicant **LG Electronics inc**
222, LG-ro, Jinwi-myeon,, Pyeongtae-si,, Gyeonggi-do, 451-713, Rep. of Korea

Product Name Premium Magic Remote
Model Name PM20GA
FCC ID BEJMR20GA
ISED ID 2703H-PM20GA

Date of Test October 17, 2019

FCC Test Standard Used **47CFR §2.1093**
ISED Test Standard Used **RSS-102 Issue 5; Health Canada Safety Code 6**

Test Results PASS
This device has been excluded from SAR based on FCC and ISED Standard

Manufacturer LG Electronics inc
Bluetooth 4.0 LE. 2 402 – 2 480 MHz

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

Technical Manager
Yun Jeang Heo

HCT CO., LTD.

SooChon Lee / CEO

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	Oct.18, 2019	Initial Release

CONTENTS

REVISION HISTORY	3
CONTENTS.....	4
1. Test Regulations.....	5
2. Test Location	5
2.1 Test Laboratory	5
3. Information of the EUT.....	5
3.1 General Information of the EUT.....	5
4. FCC	6
5. ISED	7

1. Test Regulations

The results in this report apply only to sample tested.

The tests were performed according to the following regulations:

Test Standard	FCC: 47CFR §2.1093 ISED : RSS102 Issue 5
Phenomena	Calculation
Application Port	SAR
Test Method	FCC KDB 447498 D01 v06 Per RSS102 Issue 5

2. Test Location

2.1 Test Laboratory

Company Name	HCT Co., Ltd.
Address	74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Telephone	031-645-6300
Fax	031-645-6401

3. Information of the EUT

3.1 General Information of the EUT

Model Name	LG Electronics inc
Product Name	Premium Magic Remote
Manufacturer	LG Electronics inc
Manufacturer's Address	222, LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 451-713, Korea

4. FCC

4.1 Lim SAR and Face SAR Test Exclusions Applied _Bluetooth 4.0 LE

Since this product is a remote control product, it is used by most users in the hand, so Limb SAR standard is applied. In addition, since this product is capable of voice recognition by the user, an exception evaluation is applied at a distance of 10 mm from the face SAR (head SAR).

According to the FCC KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

a) For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

$$\frac{\text{Max Power of Channel(mW)}}{\text{Test Separation Distance (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0 \text{ For 1g SAR, 7.5 for 10g SAR}$$

where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Calculation Result::

Tx frequency range: 2 402 MHz ~ 2 480 MHz

Limb SAR Consideration Min. test separation distance: 5 mm

Face SAR Consideration Min. test separation distance: 10 mm

Maximum Output Power: 6 mW

The Highest RF channel frequency: 2 480 MHz

For Face SAR Exclusion

Mode	Frequency	Maximum Allowed Power	Separation Distance	≤ 3.0 for 1g SAR
	[MHz]	[mW]	[mm]	
Bluetooth 4.0 LE	2 480	6	10	0.9

For Limb SAR exclusion

Mode	Frequency	Maximum Allowed Power	Separation Distance	≤ 7.5 for 10g SAR
	[MHz]	[mW]	[mm]	
Bluetooth 4.0 LE	2 480	6	5	1.9

Based on the maximum output power of Bluetooth 4.0 LE and antenna to use separation distance, Bluetooth 4.0 LE Limb SAR and Face SAR were not required.

5. ISED

5.1 SAR Test Exclusions Applied _Bluetooth 4.0 LE

Per RSS102 Issue 5, 2.5.1 Exemption Limits for Routine Evaluation

Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance^{4,5}

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of ≤5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
≤300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of ≥50 mm
≤300	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

For Lim-worn SAR Exclusion: $4\text{mW} * 2.5 = 10\text{ mW}$

For Face SAR Exclusion: $= 7\text{ mW}$

Calculation Result::

Tx frequency range: 2 402 MHz ~ 2 480 MHz

Limb SAR Consideration Min. test separation distance: 5 mm

Face SAR Consideration Min. test separation distance: 10 mm

Maximum Output Power: 6 mW

The Highest RF channel frequency: 2 480 MHz

The SAR exemption from RSS102: Issue 5 was also exempted by the above exclusion conditions.