

# LG Electronics USA, Inc.

# EMC TEST REPORT

**Report Type:**

FCC Part 18 EMC report

**Model:**

MS0995###

**REPORT NUMBER:**

230300754SHA-001

**ISSUE DATE:**

May 12, 2023

**DOCUMENT CONTROL NUMBER:**

TTRF18\_V1 © 2018 Intertek



**Applicant:** LG Electronics USA, Inc.  
111 Sylvan Avenue North Building, Englewood Cliffs, New Jersey, United States

**Manufacturing Site:** LG Electronics Tianjin Appliances Co., Ltd.  
No.9 Jinwei Road, Bei Chen Dist., Tianjin 300402, People's Republic of China

**Product Name:** Microwave oven

**Type/Model:** MS0995###  
("#" on model/type reference represents A to Z or blank, according to exterior design, color, cooking utensil or market)

**FCC ID:** BEJS099TZ


### SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

**47CFR Part 18 (2018):** Industrial, Scientific, and Medical Equipment

**FCC/OET MP-5 (1986):** FCC methods of Measurements of Radio Noise Emissions From Industrial, Scientific, and Medical Equipment

### PREPARED BY:



Project Engineer  
Dylan Tang

### REVIEWED BY:



Reviewer  
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**TEST REPORT**

**Content**

**REVISION HISTORY..... 4**

**MEASUREMENT RESULT SUMMARY ..... 5**

**1 GENERAL INFORMATION ..... 6**

1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) ..... 6

1.2 DESCRIPTION OF TEST FACILITY ..... 6

**2 TEST SPECIFICATIONS..... 7**

2.1 STANDARDS OR SPECIFICATION ..... 7

2.2 MODE OF OPERATION DURING THE TEST ..... 7

2.3 TEST SOFTWARE LIST ..... 7

2.4 TEST PERIPHERALS LIST ..... 7

2.5 TEST LOAD DESCRIPTION ..... 7

2.6 TEST ENVIRONMENT CONDITION:..... 8

2.7 INSTRUMENT LIST ..... 9

2.8 MEASUREMENT UNCERTAINTY ..... 10

**3 OPERATING FREQUENCY..... 11**

3.1 LIMIT ..... 11

3.2 MEASUREMENT PROCEDURE ..... 11

3.3 TEST RESULTS ..... 11

**4 RF OUTPUT POWER MEASUREMENT ..... 12**

4.1 LIMIT ..... 12

4.2 MEASUREMENT PROCEDURE ..... 12

4.3 TEST RESULTS ..... 12

**5 RADIATION HAZARD MEASUREMENT ..... 13**

5.1 LIMIT ..... 13

5.2 MEASUREMENT PROCEDURE ..... 13

5.3 TEST RESULTS ..... 13

**6 RADIATED EMISSIONS ..... 14**

6.1 LIMIT ..... 14

6.2 MEASUREMENT PROCEDURE ..... 14

6.3 TEST CONFIGURATION ..... 16

6.4 TEST RESULTS OF RADIATED EMISSIONS ..... 18

**7 CONDUCTED EMISSION ..... 23**

7.1 LIMIT ..... 23

7.2 TEST CONFIGURATION ..... 23

7.3 MEASUREMENT PROCEDURE ..... 24

7.4 TEST RESULTS OF POWER LINE CONDUCTED EMISSION..... 25

**APPENDIX I: PHOTOGRAPH OF TEST SETUP ..... 27**

**APPENDIX II: PHOTOGRAPH OF EQUIPMENT UNDER TEST ..... 27**

## Revision History

Report No.	Version	Description	Issued Date
230300754SHA-001	Rev. 01	Initial issue of report	May 12, 2023

## Measurement result summary

TEST ITEM	FCC REFERANCE	RESULT
Conducted Emission (150 kHz to 30 MHz)	18.307(b)	Pass
Radiated Emission (9 kHz to 30 MHz)	18.305(b)	Pass
Radiated Emission (30 MHz to1 GHz)	18.305(b)	Pass
Radiated Emission (1 GHz to 25 GHz)	18.305(b)	Pass
Operating Frequency	Clause 4.5	Pass
RF Output Power Measurement	Clause 4.3	Pass

Notes: 1: NA =Not Applicable

2. Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

3: Additions, Deviations and Exclusions from Standards: None.

**TEST REPORT**

**1 GENERAL INFORMATION**

**1.1 Description of Equipment Under Test (EUT)**

Product name:	Microwave oven
Type/Model:	MS0995### ("#" on model/type reference represents A to Z or blank, according to exterior design, color, cooking utensil or market)
Brand Name:	LG
Description of EUT:	The EUT is a Microwave oven which have series models, and they are electric identical. The model LMC0975ST were chosen to testing.
Rating:	AC 120V 60Hz Output: 1040W
Frequency:	2450MHz
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	April 20, 2023
Date of test:	April 20, 2023 ~ May 10, 2023

**1.2 Description of Test Facility**

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

## 2 TEST SPECIFICATIONS

### 2.1 Standards or specification

47CFR Part 18 (2018)  
FCC/OET MP-5 (1986)

### 2.2 Mode of operation during the test

Within this test report, EUT was tested under all available operation modes and tested under its rating voltage and frequency. Other voltage and frequency are specified if used.

Worst test mode: Working mode with full power.

### 2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

### 2.4 Test peripherals list

Item No.	Name	Band and Model	Description
1	Beaker	NA	1000/700/300mL

### 2.5 Test Load Description

Load for power output measurement, frequency measurement, radiation hazard test: 1000 milliliters of water in the beaker located in the center of the oven;

Load for measurement of radiation on second and third harmonic: Two loads, one of 700 and the other of 300 milliliters, of water are used. Each load is tested both with the beaker located in the center of the oven and with it in the right front corner.

Load for all other measurements: 700 milliliters of water, with the beaker located in the center of the oven.

**2.6 Test environment condition:**

Test items	Temperature	Humidity
Radiated Emissions	22°C	55% RH
Conducted Emission	21°C	52% RH



**TEST REPORT**

**2.7 Instrument list**

Conducted Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESCS 30	EC 2107	2023-07-18
<input checked="" type="checkbox"/>	A.M.N.	R&S	ESH2-Z5	EC 3119	2023-11-09
<input type="checkbox"/>	A.M.N.	R&S	ENV4200	EC 3558	2023-06-04
<input checked="" type="checkbox"/>	Attenuator	Weinschel	68-6-44	EC 3043-9	2024-02-08
<input checked="" type="checkbox"/>	Shielded room	Zhongyu	-	EC 2838	2024-01-11
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESIB 26	EC 3045	2023-07-18
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESR	EC6501	2023-09-05
<input checked="" type="checkbox"/>	Bilog Antenna	TESEQ	CBL 6112B	EC 6411	2023-08-23
<input checked="" type="checkbox"/>	Active loop antenna	Schwarzbeck	FMZB1519	EC 5345	2023-06-15
<input checked="" type="checkbox"/>	Horn antenna	Tonscend	bha9120d	EC 6432-2	2024-02-15
<input checked="" type="checkbox"/>	Pre-amplifier	Tonscend	tap01018050	EC 6432-1	2023-12-07
<input checked="" type="checkbox"/>	Horn antenna	ETS	3117	EC 4792-1	2023-08-28
<input checked="" type="checkbox"/>	Horn antenna	ETS	3116C	EC 5955	2023-06-17
<input checked="" type="checkbox"/>	Semi-anechoic chamber	Albatross project	-	EC 3048	2023-07-08
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3783	2024-03-24
<input checked="" type="checkbox"/>	Pressure meter	YM3	Shanghai Mengde	EC 4620	2023-09-13

## 2.8 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Measurement uncertainty
Radiated Emissions in restricted frequency bands below 1GHz	± 4.90dB
Radiated Emissions in restricted frequency bands above 1GHz	± 5.02dB
Power line conducted emission	± 3.19dB

### 3 Operating Frequency

Test result: Pass

#### 3.1 Limit

ISM equipment may be operated on any frequency above 9 kHz. And the frequency band 2400-2500MHz is allocated for use by ISM equipment. (§18.301)

ISM frequency	Tolerance
6.78 MHz .....	±15.0 kHz
13.56 MHz .....	±7.0 kHz
27.12 MHz .....	±163.0 kHz
40.68 MHz .....	±20.0 kHz
915 MHz .....	±13.0 MHz
2,450 MHz .....	±50.0 MHz
5,800 MHz .....	±75.0 MHz
24,125 MHz .....	±125.0 MHz
61.25 GHz .....	±250.0 MHz
122.50 GHz .....	±500.0 MHz
245.00 GHz .....	±1.0 GHz

#### 3.2 Measurement Procedure

a) Frequency for Normal Voltage

The operating frequency was measured using a spectrum analyzer. Starting with the EUT at room temperature, a 1000mL water load was placed in the center of the oven and the oven was operated at maximum output power. The fundamental operating frequency was monitored until the water load was reduced to 20 percent of the original load.

b) Frequency for Line Voltage

The EUT was operated / warmed by at least 10 minutes of use with a 1000 mL water load at room temperature at the beginning of the test. Then the operating frequency was monitored as the input voltage was varied between 80 and 125 percent of the nominal rating.

#### 3.3 Test Results

Item	START Frequency (MHz)	STOP Frequency (MHz)
Frequency for Normal Voltage	2401.70	2464.73
Frequency for Line Voltage	2400.95	2469.35

## 4 RF Output Power Measurement

Test result: Pass

### 4.1 Limit

NA

### 4.2 Measurement Procedure

The EUT in microwave mode with full power.

Formula:

$$P = \frac{4,187 \cdot m_w (T_2 - T_1) + 0,55 \cdot m_c (T_2 - T_0)}{t}$$

NOTE:

*P* is the microwave power output (W)

*m<sub>w</sub>* is the mass of the water (ml)

*m<sub>c</sub>* is the mass of the container (g)

*T<sub>0</sub>* is the ambient temperature (°C)

*T<sub>1</sub>* is the initial temperature of the water (°C)

*T<sub>2</sub>* is the final temperature of the water (°C)

*t* is the heating time (s), excluding the magnetron filament heating-up time (s).

### 4.3 Test Results

Quantity of Water [ml]	Mass of the container [g]	Ambient temperature [°C]	Initial temperature [°C]	Final temperature [°C]	Heating time [s]	Power output [W]
1 000	450	24.4	23.8	45.8	120	<b>811.75</b>

## 5 Radiation Hazard Measurement

Test result: Pass

### 5.1 Limit

A maximum of 1.0mW/cm<sup>2</sup> is allowed in accordance with the applicable FCC standards. Hence, microwave leakage in the as-received condition with the oven door closed was below the maximum allowed.

### 5.2 Measurement Procedure

The EUT was set-up according to the FCC MP-5 and FCC Part 18 for Radiation Hazard Measurement. The measurement was using a microwave leakage meter to measure the Radiation leakage in the as-received condition with the oven door closed. A 1000ml water load in a beaker was located in the center of the oven and the Microwave Oven was set to maximum power. While the oven operating, the microwave meter will check the leakage and then record the maximum leakage.

### 5.3 Test Results

There was no microwave leakage exceeding a power level of 0.15mW/cm<sup>2</sup> observed at any point 5cm or more from the external surface of the oven.

## 6 Radiated Emissions

Test result: Pass

### 6.1 Limit

- (a) ISM equipment operation on a frequency specified in §18.301 is permitted unlimited radiated energy in the band specified for that frequency.
- (b) The field strength levels of emissions which lie outside the bands specified in §18.301, unless otherwise indicated, shall not exceed the following:

Equipment	Operating frequency	RF Power generated by equipment (watts)	Field strength limit (uV/m)	Distance (meters)
Any type unless otherwise specified (miscellaneous)	Any ISM frequency	Below 500	25	300
		500 or more	$25 \times \text{SQRT}(\text{power}/500)$	300

RF Power = 811.75W according to clause 4.3

**Below 30MHz Limit:**

Limit =  $20\lg(25 \times \text{SQRT}(\text{power}/500)) + 40\lg(300/3) = 30.06 + 80 = 110.06\text{dBuV/m @ 3m distance.}$

**Above 30MHz Limit:**

Limit =  $20\lg(25 \times \text{SQRT}(\text{power}/500)) + 20\lg(300/3) = 30.06 + 40 = 70.06\text{dBuV/m @ 3m distance.}$

### 6.2 Measurement Procedure

**For Radiated emission below 30MHz:**

- a) The EUT was placed on the top of a rotating table 1 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) Both X and Y axes of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

**TEST REPORT****For Radiated emission above 30MHz:**


- a) The EUT was placed on the top of a rotating table 1.0 meters above the ground at 3-meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle  $< 98\%$ ) or  $3 \times \text{RBW}$  (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported

### 6.3 Test Configuration

For Radiated emission below 30MHz:




For Radiated emission 30MHz to 1GHz:







**For Radiated emission above 1GHz:**



### 6.4 Test Results of Radiated Emissions

Test plots of 9KHz ~ 30MHz:



**TEST REPORT**


**Test data of 9KHz ~ 30MHz:**

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
X	0.0259	86.3	110.06	23.76	AV
X	0.0440	86.6	110.06	23.46	AV
X	0.0485	96.6	110.06	13.46	AV
X	0.0978	82.0	110.06	28.06	AV
X	0.1905	74.0	110.06	36.06	AV
X	0.2625	66.5	110.06	43.56	AV
Y	0.0261	88.2	110.06	21.86	AV
Y	0.0494	97.8	110.06	12.26	AV
Y	0.0993	84.0	110.06	26.06	AV
Y	0.1725	81.7	110.06	28.36	AV
Y	0.1905	82.4	110.06	27.66	AV
Y	0.2895	74.4	110.06	35.66	AV


TEST REPORT

Test plots of 30MHz ~ 1GHz:

Horizontal



Vertical



**TEST REPORT**

**Test data of 30MHz ~ 1GHz:**

Polarization	Frequency (MHz)	Corrected Reading (dBuV/m)	Limits (dBuV/m)	Margin (dBuV/m)	Detector
Horizontal	33.783	32.9	70.06	37.16	AV
	106.533	37.9	70.06	32.16	AV
	148.340	53.0	70.06	17.06	AV
	170.359	39.5	70.06	30.56	AV
	334.677	36.0	70.06	34.06	AV
	736.451	43.1	70.06	26.96	AV
Vertical	33.686	48.6	70.06	21.46	AV
	38.245	45.8	70.06	24.26	AV
	51.146	42.6	70.06	27.46	AV
	146.109	50.4	70.06	19.66	AV
	236.610	36.7	70.06	33.36	AV
	713.365	42.7	70.06	27.36	AV

**TEST REPORT**

**Test data of 1GHz ~ 25GHz:**

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	2279	68.2	70.06	1.86	AV
H	2331	67.0	70.06	3.06	AV
H	2511	67.3	70.06	2.76	AV
H	8188	65.2	70.06	4.86	AV
H	9756	67.5	70.06	2.56	AV
H	14798	68.9	70.06	1.16	AV
H	17251	65.3	70.06	4.76	AV
V	2275	65.8	70.06	4.26	AV
V	2327	63.8	70.06	6.26	AV
V	2500	61.6	70.06	8.46	AV
V	8188	65.2	70.06	4.86	AV
V	9824	67.5	70.06	2.56	AV
V	14798	68.9	70.06	1.16	AV
V	17216	68.3	70.06	1.76	AV
H	19903	62.9	70.06	7.16	AV
H	20189	63.5	70.06	6.56	AV
H	22556	65.8	70.06	4.26	AV
V	19621	63.5	70.06	6.56	AV
V	20109	65.3	70.06	4.76	AV
V	22672	67.2	70.06	2.86	AV

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.

2. Corrected Reading = Original Receiver Reading + Correct Factor

3. Margin = Limit - Corrected Reading

4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,  
 Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,  
 Limit = 40.00dBuV/m.  
 Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;  
 Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m;  
 Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.

## 7 Conducted Emission


Test result: Pass

### 7.1 Limit

Frequency range (MHz)	Limits dB(μV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 ~ 56 *	56 ~ 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

Note: 1. \* Means the limit decreasing linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz  
 2. If the limit for the measurement with the average detector is met when using a receiver with a quasi-peak detector, the equipment under test shall be deemed to meet both limits and the measurement using the receiver with an average detector need not be carried out.

### 7.2 Test Configuration



**TEST REPORT****7.3 Measurement Procedure**

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50  $\Omega$  LISN port (to which the EUT is connected), where permitted, terminated into a 50  $\Omega$  measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50  $\Omega$  measuring port is terminated by a measuring instrument having 50  $\Omega$  input impedance. All other ports are terminated in 50  $\Omega$  loads.



Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.



### 7.4 Test Results of Power line conducted emission

Test Curve:



**TEST REPORT**

**Test Data:**

No.	Frequency	Limit dBuV	Level dBuV	Margin dB	Reading dBuV	Factor dB	Detector	Phase
1	150.000kHz	66.0	57.7	8.3	51.5	6.2	QP	L1
2	213.000kHz	63.1	45.0	18.1	38.8	6.2	QP	L1
3	924.000kHz	56.0	39.5	16.5	33.3	6.2	QP	L1
4	1.361MHz	56.0	39.1	16.9	32.9	6.2	QP	L1
5	19.415MHz	60.0	41.8	18.2	35.4	6.4	QP	L1
6	26.246MHz	60.0	47.4	12.6	40.9	6.5	QP	L1
7	150.000kHz	66.0	50.4	15.6	44.2	6.2	QP	N
8	199.500kHz	63.6	42.7	20.9	36.4	6.3	QP	N
9	271.500kHz	61.1	46.8	14.2	40.6	6.2	QP	N
10	960.000kHz	56.0	43.8	12.2	37.5	6.3	QP	N
11	19.482MHz	60.0	43.4	16.6	36.9	6.5	QP	N
12	25.562MHz	60.0	44.6	15.4	38.0	6.6	QP	N
13	168.000kHz	55.1	42.8	12.3	36.7	6.1	AV	L1
14	199.500kHz	53.6	31.9	21.7	25.7	6.2	AV	L1
15	253.500kHz	51.6	32.8	18.9	26.6	6.2	AV	L1
16	375.000kHz	48.4	25.5	22.9	19.3	6.2	AV	L1
17	492.000kHz	46.1	31.0	15.1	24.8	6.2	AV	L1
18	25.908MHz	50.0	37.9	12.1	31.4	6.5	AV	L1
19	154.500kHz	55.8	33.8	22.0	27.5	6.3	AV	N
20	190.500kHz	54.0	26.2	27.9	20.0	6.2	AV	N
21	546.000kHz	46.0	30.1	15.9	23.8	6.3	AV	N
22	636.000kHz	46.0	30.6	15.4	24.3	6.3	AV	N
23	19.559MHz	50.0	34.6	15.4	28.1	6.5	AV	N
24	25.692MHz	50.0	34.3	15.7	27.7	6.6	AV	N

- Remark: 1. Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.*
- 2. Corrected Reading = Original Receiver Reading + Correct Factor*
- 3. Margin = Limit - Corrected Reading*
- 4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.*
- 5. The emissions of number 6, 13, 19 and 26 are the product's RF signal.*

**Appendix I: Photograph of test setup**

Refer to Test set up photos.

**Appendix II: Photograph of equipment under test**

Refer to EUT External photos and Internal photos.

\*\*\*\*\* END \*\*\*\*\*